



#### **Emily**

#### **Research interests:**

star clusters, machine learning, variable stars, Gaia, LSST

#### Career:

Postdoc in Heidelberg, ►
Career path: 

→

#### Friedrich

#### **Research interests:**

galactic archeology, data science, stellar populations

#### Career:

# Topics we'll cover over the next two days

- Supervised machine learning classification; regression; neural networks; decision trees
- Unsupervised machine learning clustering algorithms, dimensionality reduction techniques
- The future of machine learning interpreting models; uncertainty; symbolic regression; the future


#### Question:

Who has used machine learning (ML) before?

#### Question:

Who feels especially comfortable using ML?

#### When ML is not the best answer



Please do not re-derive Kepler's laws with ML!

Machine learning is the **flashy** solution, but **often not the best one** 

If you can write down a model for your problem, then solve it that way

'Traditional' statistics has stuck around for **centuries** for a reason


#### When a model is too hard to write down

But machine learning is **amazing** when you **cannot write down a model** 

Image recognition is one such case

Imagine modelling a 128×128 pixel 3-color image with classical techniques!

(that's ~50 000 'input parameters')




Credit: CTIO/NOIRLab/DOE/NSF/AURA/J. Moustakas

### Many things are very hard to model!

ML is common in astronomy to...

- Classify galaxy images
- Extract stellar parameters from spectra
- Blindly search for clusters in data
  - + MANY more things!



## What is machine learning?

## What is machine learning?

Machine learning is about using **flexible models** to make predictions from data.


## What is machine learning?

Machine learning is about using **flexible models** to make predictions from data.

A few **popular techniques** like neural networks or decision trees can solve many different problems.

# Terminology 1: the type of problem

Machine learning can be divided into classification or regression problems.



## Terminiology 2: the type of method

ML methods are usually either supervised or unsupervised.

#### **Supervised ML:**

fit your method on data with **known labels**, a.k.a. **'training data'**. Then, use it to predict labels of **new data**.

#### **Unsupervised ML:**

fit your method on data with **unknown labels**, using a set of parameters to try and find patterns.

### How flexible is machine learning?

Universal approximation theorem:

A **sufficiently large** neural network can approximate **any** function.

### How flexible is machine learning?

Universal approximation theorem:

A sufficiently large neural network can approximate any function.

In plainer English:

if you make your neural network big enough, it can do anything!


(This applies to many other architectures too, but neural networks are most proven)

## The craziest example of this

Let's go back to thinking about galaxy classification again.

Isn't it pretty **crazy** that we have access to models **so flexible** that image classification is possible?

The universal approximation theorem seems impossible, right?



Credit: CTIO/NOIRLab/DOE/NSF/AURA/J. Moustakas

#### Question time!


How the hell does the maths for something like galaxy classification even work?

Do you think it must be really complicated?

#### **Neural networks**

- They're modelled after "human brains"
- They're usually drawn with these obtuse diagrams like on the right

Must be hard, right?




I'm allowed to insult this diagram because it's from my master's thesis!

#### **Neural networks**

- They're modelled after "human brains"
- They're usually drawn with these obtuse diagrams like on the right

Must be hard, right?

Let's dive into the maths of how they work as an exercise in why **you** can do machine learning.




I'm allowed to insult this diagram because it's from my master's thesis!

#### The simplest model in science

Let's build them up from scratch!

You've all seen y = mx + c.

**Linear regression** is as simple as it comes.



#### The simplest model in science


Let's build them up from scratch!

You've all seen y = mx + c.

**Linear regression** is as simple as it comes.

Let's use slightly different letters:


$$y = wx + b$$



## Making it multi-dimensional

# n-dimensional linear regression isn't much harder:

$$y = w_1 x_1 + ... + w_n x_n + b$$




## Making it multi-dimensional

# n-dimensional linear regression isn't much harder:

$$y = w_1 x_1 + ... + w_n x_n + b$$

Or, written as vectors:

$$y = \vec{w} \cdot \vec{x} + b$$




### Making it non-linear

We can do non-linear regression if we apply a function f:

$$y = f(\vec{w} \cdot \vec{x} + b)$$

This allows us to fit any function f that we want to.



#### Recap

We've taken the simplest model in science, linear regression:

$$y = wx + b$$

We've made it multi-dimensional:

$$y = \vec{w} \cdot \vec{x} + b$$

And we made it **non-linear** with a function f that we can choose:

$$y = f(\vec{w} \cdot \vec{x} + b)$$


### This model is special!

What if I told you that:

$$y = f\left(\vec{w}\cdot\vec{x} + b\right)$$

is a **building block** we can use to approximate **anything**.

How can we extend it further?



# Idea 1: connect them together in 'layers'

What happens if we **connect** the blocks together?

Let's define a new **intermediate vector**  $\vec{h_j}$  of length n, with elements:

$$ec{h_j} = egin{pmatrix} f\left(ec{w_{1j}} \cdot ec{x} + b_{1j}
ight) \ \cdots \ f\left(ec{w_{nj}} \cdot ec{x} + b_{nj}
ight) \end{pmatrix}$$


We can connect them together as many times as we want to.

#### A universal approximator?

Let's try two  $\vec{h}$  vectors of size 20, giving us three 'layers' of computation:

$$ec{h_1} = egin{pmatrix} f\left( ec{w_{1,1}} \cdot ec{x} + b_{1,1} 
ight) \ dots \ f\left( ec{w_{20,1}} \cdot ec{x} + b_{20,1} 
ight) \end{pmatrix} \ ec{h_2} = egin{pmatrix} f\left( ec{w_{1,2}} \cdot ec{h_1} + b_{1,2} 
ight) \ dots \ f\left( ec{w_{20,2}} \cdot ec{h_1} + b_{20,2} 
ight) \end{pmatrix} \ y = f\left( ec{w_{1,3}} \cdot ec{h_2} + b_{1,3} 
ight) \end{pmatrix}$$

We now have 41 'layered' nonlinear regressions.




### A universal approximator?

Let's try two  $\vec{h}$  vectors of size 20, giving us three 'layers' of computation:

$$ec{h_1} = egin{pmatrix} f\left( ec{w_{1,1}} \cdot ec{x} + b_{1,1} 
ight) \ dots \ f\left( ec{w_{20,1}} \cdot ec{x} + b_{20,1} 
ight) \end{pmatrix} \ ec{h_2} = egin{pmatrix} f\left( ec{w_{1,2}} \cdot ec{h_1} + b_{1,2} 
ight) \ dots \ f\left( ec{w_{20,2}} \cdot ec{h_1} + b_{20,2} 
ight) \end{pmatrix} \ y = f\left( ec{w_{1,3}} \cdot ec{h_2} + b_{1,3} 
ight) \end{pmatrix}$$

We now have 41 'layered' nonlinear regressions.




#### A universal approximator?

Let's try two  $\vec{h}$  vectors of size 20, giving us three 'layers' of computation:

$$ec{h_1} = egin{pmatrix} f\left( ec{w_{1,1}} \cdot ec{x} + b_{1,1} 
ight) \ dots \ f\left( ec{w_{20,1}} \cdot ec{x} + b_{20,1} 
ight) \end{pmatrix} \ ec{h_2} = egin{pmatrix} f\left( ec{w_{1,2}} \cdot ec{h_1} + b_{1,2} 
ight) \ dots \ f\left( ec{w_{20,2}} \cdot ec{h_1} + b_{20,2} 
ight) \end{pmatrix} \ y = f\left( ec{w_{1,3}} \cdot ec{h_2} + b_{1,3} 
ight) \end{pmatrix}$$

We now have 41 'layered' nonlinear regressions.




# Idea 2: choosing the right f


We can choose a function f that has nice properties as a building block


#### **Activation Functions**

#### **Sigmoid**

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$








#### ReLU

tanh(x)


tanh

 $\max(0,x)$ 



#### Leaky ReLU


 $\max(0.1x, x)$ 



#### **Maxout**

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$


$$\begin{cases} x & x \ge 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



# Let's try tanh

Our model of 20 + 20 + 1 nonlinear fitting blocks now fits the curve!

The type of model we made has a special name. Any guesses?



1. Machine learning is, at its core, maths that you can already understand.

- 1. Machine learning is, at its core, maths that you can already understand.
- 2. It works because the models are generally **large**, and are set up to work well as **large** models.

- 1. Machine learning is, at its core, maths that you can already understand.
- 2. It works because the models are generally **large**, and are set up to work well as **large** models.
- 3. We can make clever choices of things like the activation function f to make them **flexible**.

1. How did I choose the 481 parameters of that model?

1. How did I choose the 481 parameters of that model?



ML only works because of sophisticated ways to train models.

1. How did I choose the 481 parameters of that model?



ML only works because of sophisticated ways to train models.

2. How is it computationally possible to do that?

1. How did I choose the 481 parameters of that model?



ML only works because of sophisticated ways to train models.

2. How is it computationally possible to do that?



Advances in computers over the last 20 years.

1. How did I choose the 481 parameters of that model?



ML only works because of sophisticated ways to train models.

2. How is it computationally possible to do that?



Advances in computers over the last 20 years.

3. Did I have to write the code for that myself?

1. How did I choose the 481 parameters of that model?



ML only works because of sophisticated ways to train models.

2. How is it computationally possible to do that?



Advances in computers over the last 20 years.

3. Did I have to write the code for that myself?



No! There is a **huge** ecosystem of open source software for ML

#### Recap

#### We discussed...

- What machine learning is and why to use it
- Classification vs. regression
- Supervised vs. unsupervised learning
- The universal approximation theorem
- ... & that the maths of ML doesn't have to be scary =)