

What Is an ARIMAX Model?

GeeksforGeeks · Artificial Intelligence

Introduction

An ARIMAX model, which stands for **AutoRegressive Integrated Moving Average with eXogenous inputs**, is an advanced version of the ARIMA (AutoRegressive Integrated Moving Average) model. The ARIMAX model extends the ARIMA framework by integrating exogenous variables — external factors that can influence the time series being studied. This integration allows the model to leverage additional information that can significantly enhance forecasting accuracy.

ARIMA Model Core

The ARIMA component of the ARIMAX model consists of three main parts:

AR (AutoRegressive): This part of the model uses the dependency between an observation and a number of lagged observations. It helps in understanding the influence of past values on the current value.

I (Integrated): This involves differencing the time series to achieve stationarity, which means ensuring that the mean and variance are constant over time.

MA (Moving Average): This component accounts for the effect of past forecast errors (residuals) on the current prediction, using the average of past errors to improve forecast accuracy.

The model is defined by three key parameters: **p** (number of autoregressive terms), **d** (degree of differencing), and **q** (number of moving average terms), written as ARIMA(p, d, q).

Exogenous Variables in ARIMAX

The key distinction of ARIMAX over plain ARIMA is the inclusion of exogenous (external) variables. These are independent inputs — such as economic indicators, weather data, or promotional spending — that are believed to influence the target time series but are not themselves modelled as part of the autoregressive process.

By incorporating these external factors, the ARIMAX model can capture relationships that a pure ARIMA model would miss, often yielding significantly better forecasts in real-world

settings.

How the ARIMAX Model Works

Step 1 — Data Preparation & Stationarity

Before fitting an ARIMAX model, the time series must be stationary (constant mean and variance). This is achieved through differencing (the 'I' component). The Augmented Dickey-Fuller (ADF) test is commonly used to check stationarity.

Step 2 — Parameter Selection (p, d, q)

The order of the model is identified using tools such as the Autocorrelation Function (ACF) and Partial Autocorrelation Function (PACF) plots, or by automated selection methods.

Step 3 — Model Fitting

The model is fitted to historical data alongside the exogenous variables. In Python, the statsmodels library's SARIMAX class is used for this purpose — there is no separate ARIMAX class, as SARIMAX generalises ARIMAX.

Step 4 — Model Validation

Evaluating the model's performance through diagnostic checks is vital. Analysts inspect residuals, perform out-of-sample testing, and use information criteria such as AIC (Akaike Information Criterion) or BIC (Bayesian Information Criterion) to validate effectiveness.

Python Implementation Example

The example below generates synthetic time series data and fits an ARIMAX model using the statsmodels library. Note that SARIMAX is used instead of a dedicated ARIMAX class.

```
import numpy as np
import pandas as pd
from statsmodels.tsa.statespace.sarimax import SARIMAX

def generate_data(n=100, seed=42):
    """Generate synthetic time series data with exogenous variables."""
    np.random.seed(seed)
    exog = np.random.randn(n)          # exogenous variable
    noise = np.random.randn(n) * 0.5
    y = 0.8 * np.arange(n) + 1.5 * exog + noise
    return y, exog

y, exog = generate_data()
```

```
# Fit ARIMAX (via SARIMAX) with order (1, 1, 1)
model = SARIMAX(y, exog=exog, order=(1, 1, 1))
result = model.fit(dispatch=False)
print(result.summary())
```

Note: The statsmodels library does not provide a distinct ARIMAX class separate from SARIMAX, because SARIMAX handles a broad family of state-space models including ARIMAX. When using statsmodels, SARIMAX is the appropriate choice even when the model is conceptually ARIMAX.

Applications of ARIMAX

ARIMAX models are used across many domains where external factors are known to affect a target variable:

Finance: Forecasting stock prices or exchange rates using economic indicators as exogenous inputs.

Energy: Predicting electricity demand incorporating temperature or calendar variables.

Retail: Sales forecasting with promotional spend or holiday flags as external regressors.

Economics: Modelling GDP growth with policy variables or commodity prices.

Advantages and Limitations

Advantages

- Incorporates external information that improves forecast accuracy over plain ARIMA.
- Interpretable coefficients for both time-series dynamics and exogenous effects.
- Flexible — the exogenous variables can be continuous or categorical (with encoding).

Limitations

- Requires future values of exogenous variables at forecast time, which may not always be available.
- Assumes a linear relationship between exogenous variables and the target series.
- Model selection (p, d, q plus exogenous variables) adds complexity compared to ARIMA.

ARIMAX vs Related Models

ARIMA — No exogenous variables; univariate time series only.

ARIMAX — ARIMA plus exogenous (external) variables.

SARIMA — ARIMA with a seasonal component; no exogenous variables.

SARIMAX — The most general form: seasonal ARIMA with exogenous variables. This is the class used in statsmodels to fit ARIMAX models.

Conclusion

The ARIMAX model is a powerful extension of ARIMA that allows practitioners to fold in domain knowledge through exogenous variables. When external factors are known to drive a time series, ARIMAX typically outperforms pure ARIMA. In Python, the SARIMAX class from statsmodels is the standard implementation. Proper stationarity testing, careful parameter selection, and thorough validation are key to building a reliable ARIMAX model.

Source: [geeksforgeeks.org/artificial-intelligence/what-is-an-arimax-model/](https://www.geeksforgeeks.org/artificial-intelligence/what-is-an-arimax-model/) · Tags: ARIMAX, ARIMA, Time Series, AI, Machine Learning