



Cybersecurity

Module 5 Challenge Submission File

Archiving and Logging Data

Step 1: Create, Extract, Compress, and Manage tar Backup Archives

1. Command to **extract** the `TarDocs.tar` archive to the current directory:

```
[cd into project (/home/sysadmin/projects/)  
tar -xvzf TarDocs.tar]
```

2. Command to **create** the `Javaless_Doc.tar` archive from the `TarDocs/` directory, while excluding the `TarDocs/Documents/Java` directory:

```
[tar cvf Javaless_Docs.tar --exclude='Java' TarDocs]
```

3. Command to ensure `Java/` is not in the new `Javaless_Docs.tar` archive:

```
[tar -tvf Javaless_Docs.tar | grep Java (no output)]
```

Bonus

4. Command to create an incremental archive called `logs_backup.tar.gz` with only changed files to `snapshot.file` for the `/var/log` directory:

```
[sudo tar -cvzf --listed-incremental=snapshot.file] logs_backup.tar.gz  
/var/log
```

Critical Analysis Question

5. Why wouldn't you use the options `-x` and `-c` at the same time with `tar`?

`-c` creates the file, and `-x` executes the tar, they are conflicting commands

Step 2: Create, Manage, and Automate Cron Jobs

1. Cron job for backing up the `/var/log/auth.log` file:

```
[0 6 * * 3 tar zcvf auth_backup.tgz /var/log/auth.log]
```

Step 3: Write Basic Bash Scripts

1. Brace expansion command to create the four subdirectories:

```
[mkdir ~/backups/{freemem,diskuse,openlist,freedisk}]
```

2. Paste your `system.sh` script edits:

```
#!/bin/bash
[#print free mem
free -h > ~/backups/freemem/free_mem.txt
#disk usage
du -h > ~/backups/diskuse/disk_usage.txt
#open files
lsof > ~/backups/openlist/open_list.txt
#file sys disk space
df -h > ~/backups/freedisk/free_disk.txt]
```

3. Command to make the `system.sh` script executable:

```
[chmod +x system.sh]
```

Optional

4. Commands to test the script and confirm its execution:

```
[cat ~/backups/freemem/free_mem.txt]
```

Bonus

5. Command to copy `system` to system-wide cron directory:

```
[sudo cp system.sh /etc/crontab]
```

Step 4. Manage Log File Sizes

1. Run `sudo nano /etc/logrotate.conf` to edit the `logrotate` configuration file.

Configure a log rotation scheme that backs up authentication messages to the `/var/log/auth.log`.

- a. Add your config file edits:

```
[# system-specific logs may be configured here
/var/log/auth.log {
    missingok
    weekly
    delaycompress
    rotate 7
    notifempty
}]
```

Bonus: Check for Policy and File Violations

1. Command to verify ``auditd`` is active:

```
[sudo systemctl status auditd]
```

2. Command to set number of retained logs and maximum log file size:

```
[sudo nano /etc/audit/auditd.conf]
```

Add the edits made to the configuration file:

```
[max_log_file = 35  
num_logs = 7]
```

3. Command using `auditd` to set rules for `/etc/shadow`, `/etc/passwd`, and `/var/log/auth.log`:

```
[sudo nano /etc/shadow  
Sudo nano /etc/passwd  
Sudo nano /var/log/auth.log]
```

Add the edits made to the `rules` file below:

```
[-w /etc/shadow -p wra -k hashpass_audit  
-w /etc/passwd -p wra -k userpass_audit  
-w /var/log/auth.log -p wra -k authlog_audit]
```

4. Command to restart `auditd`:

```
[ sudo systemctl restart auditd]
```

5. Command to list all `auditd` rules:

```
[sudo auditctl -l]
```

6. Command to produce an audit report:

```
[sudo aureport -au]
```

7. Create a user with `sudo useradd attacker` and produce an audit report that lists account modifications:

```
[sudo useradd attacker  
Sudo aureport -m]
```

8. Command to use auditd to watch `/var/log/cron`:

```
[sudo auditctl -w /var/log/cron]
```

9. Command to verify auditd rules:

```
[sudo auditctl -l]
```

Bonus (Research Activity): Perform Various Log Filtering Techniques

1. Command to return `journalctl` messages with priorities from emergency to error:

```
[sudo journalctl -b -1 -p "emergency".."error"]
```

2. Command to check the disk usage of the system journal unit since the most recent boot:

```
[sudo journalctl --disk-usage]
```

3. Command to remove all archived journal files except the most recent two:

```
[Sudo journalctl --vacuum-fils=2]
```

4. Command to filter all log messages with priority levels between zero and two, and save output to `/home/sysadmin/Priority_High.txt`:

```
[sudo journalctl -p 0..2 >> /home/sysadmin/Priority_High.txt]
```

5. Command to automate the last command in a daily cron job. Add the edits made to the crontab file below:

```
[0 8 * * * sudo journalctl -p 0..2 >> /home/sysadmin/Priority_High.txt]
```

© 2022 Trilogy Education Services, a 2U, Inc. brand. All Rights Reserved.