



Cybersecurity

Module 11 Challenge Submission File

Network Security Homework

Part 1: Review Questions

Security Control Types

The concept of defense in depth can be broken down into three security control types. Identify the security control type of each set of defense tactics.

1. Walls, bollards, fences, guard dogs, cameras, and lighting are what type of security control?

[Physical Controls]

2. Security awareness programs, BYOD policies, and ethical hiring practices are what type of security control?

[Management Controls]

3. Encryption, biometric fingerprint readers, firewalls, endpoint security, and intrusion detection systems are what type of security control?

[Data Protections]

Intrusion Detection and Attack Indicators

1. What's the difference between an IDS and an IPS?

[Intrusion Detection System analyzes traffic for anything suspicious or malicious, Intrusion Prevention System can respond to the attacks as well as analyze them, preventing them rather than just detecting them.]

2. What's the difference between an indicator of attack (IOA) and an indicator of compromise (IOC)?

[IOCs show that a system has just been breached, with a threat of being attacked, IOAs show that a system is actually under attack.]

The Cyber Kill Chain

Name the seven stages of the cyber kill chain, and provide a brief example of each.

1. Stage 1:

[Reconnaissance: Attackers research their victim, looking for backdoor entry and exploitable vulnerabilities (DNS Registration, social media accounts, etc)]

2. Stage 2:

[Weaponization: The attacker may create malware to use against the victim, after they have gathered sufficient information]

3. Stage 3:

[Delivery: Essentially deploying the malicious programs, gaining access to the system and delivering the payload]

4. Stage 4:

[Exploitation: Now that the attacker has access to the system, they will hunt for further vulnerabilities to spread their programs and inflict further damage]

5. Stage 5:

[Installation: The attacker will escalate their privileges, and deploy other malicious programs to higher level accounts and users. They may change permissions, and delete or manipulate information]

6. Stage 6:

[Command and Control: Used to control the victim's computer, often will include obfuscation, where the attacker tries to make it appear that there is no attack happening. They can track and maintain their malware remotely]

7. Stage 7:

[Actions and Objectives: The culmination of all of the above efforts, the attacker may now act on whatever their objective is; data exfiltration, DoS, etc.]

Snort Rule Analysis

Use the provided Snort rules to answer the following questions:

Snort Rule #1

```
alert tcp $EXTERNAL_NET any -> $HOME_NET 5800:5820 (msg:"ET SCAN Potential VNC Scan 5800-5820"; flags:S,12; threshold: type both, track by_src, count 5, seconds 60; reference:url,doc.emergingthreats.net/2002910; classtype:attempted-recon; sid:2002910; rev:5; metadata:created_at 2010_07_30, updated_at 2010_07_30;)
```

1. Break down the Snort rule header and explain what this rule does.

[TCP/IP protocol, tried to port map \$HOME_NET, ports 5800-5820]

2. What stage of the cyber kill chain does the alerted activity violate?

[Recon]

3. What kind of attack is indicated?

[Port Mapping]

Snort Rule #2

```
alert tcp $EXTERNAL_NET $HTTP_PORTS -> $HOME_NET any (msg:"ET POLICY PE EXE
or DLL Windows file download HTTP"; flow:established,to_client;
flowbits:isnotset,ET.http.binary; flowbits:isnotset,ET.INFO.WindowsUpdate;
file_data; content:"MZ"; within:2; byte_jump:4,58,relative,little;
content:"PE|00 00|"; distance:-64; within:4; flowbits:set,ET.http.binary;
metadata: former_category POLICY;
reference:url,doc.emergingthreats.net/bin/view/Main/2018959;
classtype:policy-violation; sid:2018959; rev:4; metadata:created_at
2014_08_19, updated_at 2017_02_01;)
```

1. Break down the Snort rule header and explain what this rule does.

[tried to deliver payload to any port via http port]

2. What layer of the defense in depth model does the alerted activity violate?

[Delivery]

3. What kind of attack is indicated?

[Cross site scripting]

Snort Rule #3

Your turn! Write a Snort rule that alerts when traffic is detected inbound on port 4444 to the local network on any port. Be sure to include the `msg` in the rule option.

```
[alert tcp $EXTERNAL_NET any -> $HOME_NET 4444 (msg:"Inbound traffic on 444")]
```

Part 2: “Drop Zone” Lab

Set up.

Log into the Azure `firewalld` machine using the following credentials:

- Username: `sysadmin`
- Password: `cybersecurity`

Uninstall UFW.

Before getting started, you should verify that you do not have any instances of UFW running. This will avoid conflicts with your `firewalld` service. This also ensures that `firewalld` will be your default firewall.

- Run the command that removes any running instance of UFW.

```
$ sudo ufw disable
```

Enable and start `firewalld`.

By default, the `firewalld` service should be running. If not, then run the commands that enable and start `firewalld` upon boots and reboots.

```
$ sudo systemctl enable firewalld
$ sudo systemctl start firewalld
```

Note: This will ensure that firewalld remains active after each reboot.

Confirm that the service is running.

Run the command that checks whether the `firewalld` service is up and running.

```
$ sudo systemctl status firewalld
```

List all firewall rules currently configured.

Next, list all currently configured firewall rules. This will give you a good idea of what's currently configured and save you time in the long run by ensuring that you don't duplicate work that's already done.

- Run the command that lists all currently configured firewall rules:

```
$ sudo firewall-cmd --list-all
```

- Take note of what zones and settings are configured. You may need to remove unneeded services and settings.

List all supported service types that can be enabled.

- Run the command that lists all currently supported services to find out whether the service you need is available.

```
$ Sudo firewall-cmd --get-services
```

- Notice that the `home` and `drop` zones are created by default.

Zone views.

- Run the command that lists all currently configured zones.

```
$ Sudo firewall-cmd --list-all-zones
```

- Notice that the `public` and `drop` zones are created by default. Therefore, you will need to create zones for `web`, `sales`, and `mail`.

Create zones for `web`, `sales`, and `mail`.

- Run the commands that create `web`, `sales`, and `mail` zones.

```
$ sudo firewall-cmd --permanent --new-zone=web
$ sudo firewall-cmd --permanent --new-zone=sales
$ sudo firewall-cmd --permanent --new-zone=mail
```

Set the zones to their designated interfaces.

- Run the commands that set your `eth` interfaces to your zones.

```
$ Sudo firewall-cmd --zone=public --change-interface=eth0
$ Sudo firewall-cmd --zone=web --change-interface=eth1
$ Sudo firewall-cmd --zone=sales --change-interface=eth2
$ Sudo firewall-cmd --zone=mail --change-interface=eth3
```

Add services to the active zones.

- Run the commands that add services to the `public` zone, the `web` zone, the `sales` zone, and the `mail` zone.

- `public:`

```
$ sudo firewall-cmd --add-service=http --zone=public --permanent
```

```
$ sudo firewall-cmd --add-service=https --zone=public --permanent
$ sudo firewall-cmd --add-service=pop3 --zone=public --permanent
$ sudo firewall-cmd --add-service=smtp --zone=public --permanent
$ sudo firewall-cmd --reload (to apply change)
```

- web:

```
$ sudo firewall-cmd --add-service=http --zone=web --permanent
$ sudo firewall-cmd --reload
```

- sales:

```
$ sudo firewall-cmd --add-service=https --zone=sales --permanent
$ sudo firewall-cmd --reload
```

- mail:

```
$ sudo firewall-cmd --add-service=smtp --zone=mail --permanent
$ sudo firewall-cmd --add-service=pop3 --zone=mail --permanent
$ sudo firewall-cmd --reload
```

- What is the status of http, https, smtp and pop3?

```
[All active]
```

Add your adversaries to the drop zone.

- Run the command that will add all current and any future blacklisted IPs to the drop zone.

```
$ sudo firewall-cmd --zone=drop --add-source=10.208.56.23
$ sudo firewall-cmd --zone=drop --add-source=135.95.103.76
$ sudo firewall-cmd --zone=drop --add-source=76.34.169.118
```


Make rules permanent, then reload them.

It's good practice to ensure that your firewalld installation remains nailed up and retains its services across reboots. This helps ensure that the network remains secure after unplanned outages such as power failures.

- Run the command that reloads the firewalld configurations and writes it to memory:

```
$ sudo firewall-cmd -reload
```

View active zones.

Now, provide truncated listings of all currently **active** zones. This is a good time to verify your zone settings.

- Run the command that displays all zone services.

```
$ sudo firewall-cmd -list-all-zones
```

Block an IP address.

- Use a rich-rule that blocks the IP address 138.138.0.3 on your public zone.

```
$ sudo firewall-cmd -permanent -add-rich-rule="rule family='ipv4' source address='138.138.0.3' reject"
```

Block ping/ICMP requests.

Harden your network against ping scans by blocking icmp echo replies.

- Run the command that blocks pings and icmp requests in your public zone.

```
$ sudo firewall-cmd -zone=public -add-icmp-block=echo-reply
```

Rule check.

Now that you've set up your brand new firewalld installation, it's time to verify that all of the settings have taken effect.

- Run the command that lists all of the rule settings. Do one command at a time for each zone.

```
$ <sudo firewall-cmd zone=public -list-all>
$ <sudo firewall-cmd zone=web -list-all>
$ <sudo firewall-cmd zone=sales -list-all>
$ <sudo firewall-cmd zone=mail -list-all>
$ <sudo firewall-cmd zone=drop -list-all>
```

- Are all of the rules in place? If not, then go back and make the necessary modifications before checking again.

Congratulations! You have successfully configured and deployed a fully comprehensive firewalld installation.

Part 3: IDS, IPS, DiD and Firewalls

Now, you'll work on another lab. Before you start, complete the following review questions.

IDS vs. IPS Systems

1. Name and define two ways an IDS connects to a network.

```
[TAP: Monitors in and out traffic]
```

```
[SPAN: Logs everything, and flags suspicious things to be reviewed]
```

2. Describe how an IPS connects to a network.

[Placed between source and destination in the flow of traffic]

3. What type of IDS compares patterns of traffic to predefined signatures and is unable to detect zero-day attacks?

[Signature based intrusion detection]

4. What type of IDS is beneficial for detecting all suspicious traffic that deviates from the well-known baseline and is excellent at detecting when an attacker probes or sweeps a network?

[Anomaly based intrusion detection]

Defense in Depth

1. For each of the following scenarios, provide the layer of defense in depth that applies:
 - a. A criminal hacker tailgates an employee through an exterior door into a secured facility, explaining that they forgot their badge at home.

[Perimeter]

- b. A zero-day goes undetected by antivirus software.

[Network]

- c. A criminal successfully gains access to HR's database.

[Data]

- d. A criminal hacker exploits a vulnerability within an operating system.

[Application]

- e. A hacktivist organization successfully performs a DDoS attack, taking down a government website.

[Network]

- f. Data is classified at the wrong classification level.

[Host]

- g. A state-sponsored hacker group successfully firewalked an organization to produce a list of active services on an email server.

[Data]

- 2. Name one method of protecting data-at-rest from being readable on hard drive.

[Encryption]

- 3. Name one method of protecting data-in-transit.

[Public Key]

- 4. What technology could provide law enforcement with the ability to track and recover a stolen laptop?

[GPS Tracking/tracing]

- 5. How could you prevent an attacker from booting a stolen laptop using an external hard drive?

[2 Factor Authentication, disk encryption]

Firewall Architectures and Methodologies

1. Which type of firewall verifies the three-way TCP handshake? TCP handshake checks are designed to ensure that session packets are from legitimate sources.

[Circuit level gateways]

2. Which type of firewall considers the connection as a whole? Meaning, instead of considering only individual packets, these firewalls consider whole streams of packets at one time.

[Stateful Firewall]

3. Which type of firewall intercepts all traffic prior to forwarding it to its final destination? In a sense, these firewalls act on behalf of the recipient by ensuring the traffic is safe prior to forwarding it.

[Application Firewall]

4. Which type of firewall examines data within a packet as it progresses through a network interface by examining source and destination IP address, port number, and packet type—all without opening the packet to inspect its contents?

[Stateless Firewalls/Packet Filtering Firewalls]

5. Which type of firewall filters solely based on source and destination MAC address?

[MAC Layer Firewalls]

Optional Additional Challenge Lab: “Green Eggs & SPAM”

In this activity, you will target spam, uncover its whereabouts, and attempt to discover the intent of the attacker.

- You will assume the role of a junior security administrator working for the Department of Technology for the State of California.

- As a junior administrator, your primary role is to perform the initial triage of alert data: the initial investigation and analysis followed by an escalation of high-priority alerts to senior incident handlers for further review.
- You will work as part of a Computer and Incident Response Team (CIRT), responsible for compiling **threat intelligence** as part of your incident report.

Threat Intelligence Card

Note: Log in to the Security Onion VM, and use the following **indicator of attack** to complete this portion of the assignment.

Locate the indicator of attack in Sguil based off of the following:

- **Source IP/port:** 188.124.9.56:80
- **Destination address/port:** 192.168.3.35:1035
- **Event message:** ET TROJAN JS/Nemucod.M.gen downloading EXE payload

Answer the following questions:

1. What was the indicator of an attack? (*Hint: What do the details reveal?*)

[A trojan EXE malware file is being downloaded]

2. What was the adversarial motivation (purpose of the attack)?

[Steal info]

3. What are your recommended mitigation strategies?

[IDS and IPS to detect and prevent future downloads]