Banquet Concierge

An OpenTable-style booking app for banquet halls anywhere in the United States, run by a team of cooperating Claude agents, with guardrails enforced in code and a harness that traces every call and accounts for every token.

How it works · generated October 23, 2026 by `.\run.ps1 guide`

50 + DC states with venues	**214** fictional venues	**3** Claude agents
7 guardrails in code	**6/6** scenarios passed (simulated)	**67,755** tokens across the suite, incl. cache reads (simulated)

What it does


A customer describes an event in plain language, for example "*a wedding for about 180 guests in Austin, Texas next October, budget around $45,000*". The **Concierge** agent works out what's needed and delegates: the **Venue Scout** searches venues in that state and checks dates, and the **Pricing Analyst** builds itemized quotes with that state's sales tax. The customer sees venue cards and exact quotes, can ask for a free 72-hour hold, and confirms the booking themselves. No agent can commit the customer to a purchase.

In this guide


1. A session, screen by screen
2. Functionality map
3. Agentic workflow
4. Guardrails
5. The harness
6. Tokens per tool and per agent
7. Running it

1. A session, screen by screen


These screenshots are the real web app, driven by Playwright, with the scripted `SimulatedClient` in place of Claude (so the agents' wording is scripted, but every tool result, card, hold and guardrail is real).




The start screen: describe the event or pick a suggestion. Venues are available in every state.



The Venue Scout found Austin venues and the Pricing Analyst quoted them. 'Agent activity' lists each step and the turn's token count.




The customer asked for a hold and gave an email. The Concierge placed a free 72-hour hold; it appears in the Holds panel.



Only the customer can confirm: the button calls the API directly. No agent has a confirm tool (guardrail G7).

2. Functionality map

Everything the program does, grouped into six areas.




Interfaces at a glance

Interface	What it offers
Web chat `.\run.ps1 serve`	Chat, venue cards, holds panel with Confirm / Release, agent activity with tokens
Terminal `.\run.ps1 cli --verbose`	Chat, `/holds`, `/confirm <id>` after y/N, per-call token printout
REST API	`POST /api/chat`, `GET /api/venues?state=TX`, `GET /api/venues/{id}`, `GET /api/sessions/{id}/holds`, `POST /api/bookings/{id}/confirm` and `/cancel`
Harness `.\run.ps1 scenarios`	Six scripted conversations, eight scorers, a token ledger, simulated or live

3. Agentic workflow

One customer turn: the Concierge delegates to the specialists (in parallel when it needs both), each specialist works in a fresh context and returns only a summary, and every reply passes the price-grounding check before the customer sees it. Guardrails are shown where they apply.



Agent	Effort	Tools (least privilege)	Job
Concierge	medium	ask_venue_scout, ask_pricing_analyst, check_availability, show_venues, place_hold	Talks to the customer, delegates, shows cards, places holds
Venue Scout	low	search_venues, get_venue_details, check_availability	Finds and shortlists venues in the right state (read-only)
Pricing Analyst	low	get_venue_details, build_quote	Prices options and compares them to the budget (read-only)

A turn, step by step


1. **G1** checks the message. Injection attempts are answered without any model call.
2. The **Concierge** calls `ask_venue_scout` with a self-contained brief (state, city, guests, date, budget).
3. The **Venue Scout** runs `search_venues` (with the `state` filter) and `check_availability`, and returns a shortlist with ids.
4. The Concierge calls `show_venues` (cards) and `ask_pricing_analyst` together; the **Pricing Analyst** runs `build_quote` for each option.
5. The Concierge writes the reply; **G4** checks every dollar amount against the tool results. On request it places a hold (**G3** checks); confirming is the customer's action only (**G7**).

4. Guardrails

Prompts describe the rules so the agents usually comply first time, but every guardrail is enforced in code and tested in both directions (the bad case is blocked, and the harmless look-alike, such as "please ignore the previous date", still works).

#	Guardrail	What it does	Where
G1	Customer input	Strips control characters, limits length, and politely refuses prompt-injection phrasing before any model call (zero cost).	`ConciergeSession.send`
G2	Tool arguments	Every tool call is checked against the tool's JSON schema (types, ranges, required fields, no extra fields) before it runs; problems go back to the agent as fixable errors.	`Agent._execute`
G3	Holds	At most 3 active holds per conversation, and the email must be one the customer actually typed, so an agent can't invent or reuse one.	`_place_hold`
G4	Price grounding	Every dollar amount in the Concierge's reply must match a dollar amount from a tool result (a money field such as a quote total, or a $-figure in a specialist's reply) or the customer's own words, at the precision written. Guest counts, ids and percentages never count. Otherwise the reply is sent back once; if it's still wrong, a warning is added.	`ConciergeSession.send`
G5	Privacy	Emails are replaced with <email> in traces and run reports. (Customers still see their own email on their own screen.)	`harness.trace`
G6	Token budgets	400,000 tokens per customer turn and 2,000,000 per conversation, checked before every model call.	`Agent.run`
G7	Human-only commitments	No agent has a confirm or cancel tool. Only the customer can confirm (API, web button or CLI after y/N).	`team.py`, `api.py`

Host safety (CLAUDE.md): no `os` module, paths and temporary files kept in the project folder, no file deletions, the server bound to 127.0.0.1, and security headers on every response. Source scans in the test suite enforce these.



An off-topic request is politely declined, and an injection attempt is stopped by G1 before any agent runs; the activity panel shows the guardrail.

5. The harness

The harness wraps the agent team without changing it. The runtime emits an event for every model call and tool call; the harness records, measures and scores them.

Part	What it does
Runtime events	`model_call` (agent, usage, latency, stop reason, tools requested and their argument sizes), `tool_call`, `tool_result` (ok/error, latency, result size) and `guardrail` events. A specialist's events carry the id of the delegation call that started it.
Trace	`runs/<id>/<scenario>/trace.jsonl`: every event, emails redacted (G5).
Token ledger	Exact usage per agent; attributed usage per tool (see below); cost at the configured claude-opus-5-5 prices.
Scenarios	Six scripted conversations: Texas wedding with a hold, Ohio corporate dinner, NYC gala on a booked date, a Denver price guess (G4), a hold without an email (G3), an off-topic request and an injection (G1).
Scorers	completed · venues_in_state · prices_grounded · expected_guardrails · holds · read_only_specialists · no_tools_when_declining · within_budget
Modes	**Simulated**: free, offline, scripted agents, estimated tokens. **Live**: real Claude agents, real usage, a cost cap (default $5) checked between scenarios. In live mode, G3 and G4 may fire but aren't required, since real agents rarely misbehave on cue.

How tokens are attributed to tools

The API reports usage per model call, not per tool, so the ledger attributes it:


- **Decision**: the output tokens of the call that requested the tool (reasoning plus writing the call), split by argument size when several tools are requested at once.
- **Result**: how much the agent's prompt grew on its next call, minus the previous output, split by result size: the cost of reading the tool's output.
- **Specialist**: for `ask_venue_scout` and `ask_pricing_analyst`, everything the delegated agent used.

Per-agent totals are exact sums of reported usage; per-tool numbers are an attribution. If an API version leaves earlier reasoning out of later prompts, result tokens are understated (the subtraction assumes the previous output stays in the history).

6. Tokens per tool and per agent

Simulated numbers. These token counts come from the scripted `SimulatedClient`, which estimates tokens as text characters ÷ 4 and adds a fixed reasoning allowance. They show how the harness measures and attributes tokens, not what live Claude calls cost. Run `.\run.ps1 scenarios --live --max-cost 5` for real numbers.


Tokens attributed to each tool (whole suite)



Tool	Calls	Decision	Result	Specialist	Total	Est. cost
`ask_venue_scout`	5	944	571	19,521	**21,036**	$0.0850
`ask_pricing_analyst`	5	850	412	8,506	**9,768**	$0.0592
`build_quote`	8	567	1,223	0	**1,790**	$0.0162
`search_venues`	5	452	1,269	0	**1,721**	$0.0141
`check_availability`	8	506	496	0	**1,002**	$0.0121
`place_hold`	2	389	401	0	**790**	$0.0094
`show_venues`	5	173	141	0	**314**	$0.0040

The delegation tools are the largest because they include the specialists' whole runs. Among the data tools, the ones with the biggest results (for example `search_venues` and `build_quote`) cost the most to read.

Tokens per agent (simulated; exact sums of the usage each call reported)



Agent	Model calls	Input	Cache read	Output	Total	Est. cost
Concierge	21	12,025	23,510	4,193	**39,728**	$0.1367
Venue Scout	15	7,200	10,675	1,646	**19,521**	$0.0639
Pricing Analyst	10	4,610	2,820	1,076	**8,506**	$0.0405

Suite total: 46 model calls, 38 tool calls, 67,755 tokens (including cache reads), $0.2411 at the configured prices (input $4, output $20, cache write $5, cache read $0.20 per million tokens; check current pricing).

Tokens and scores per scenario (simulated)

Scenario	Turns	Model calls	Tokens	Est. cost	Guardrails fired	Scorers
texas-wedding Wedding in Austin, Texas, then a hold	2	10	16,323	$0.0544	none	8/8
ohio-corporate Corporate dinner in Columbus, Ohio	1	8	11,304	$0.0443	none	8/8
nyc-gala-date-taken Gala in Manhattan on a booked date	1	8	10,371	$0.0385	none	8/8
denver-price-guess Unquoted price caught by the grounding guardrail	1	9	13,420	$0.0478	G4 grounding	8/8
hold-without-email Hold refused until the customer gives an email	2	10	14,939	$0.0476	G3 holds	8/8
off-topic-injection Off-topic request and a prompt-injection attempt	2	1	1,398	$0.0084	G1 input	8/8

7. Running it

Command	What it does
`.\run.ps1 serve`	Web app on http://127.0.0.1:8000 with live agents (needs ANTHROPIC_API_KEY)
`.\run.ps1 serve --simulated`	Web app with the scripted stand-in: no key, no cost
`.\run.ps1 cli --verbose`	Terminal chat with agent activity and tokens
`.\run.ps1 test`	Offline test suite: booking rules, states, guardrails, agents, harness, API, CLAUDE.md scans
`.\run.ps1 scenarios`	Scenario suite, simulated; writes runs/<id>/
`.\run.ps1 scenarios --live --max-cost 5`	Scenario suite with real Claude agents; cost cap checked between scenarios
`.\run.ps1 install-browser` then `.\run.ps1 guide`	Re-take the screenshots and rebuild this PDF

Limits

- Venues are fictional. Sales tax is the state base rate (approximate; local and meals taxes are not modeled), except the original New York and New Jersey venues, which use combined local rates.
- The injection check catches known phrasings; the agents' instructions are the second line of defense.
- Token budgets are checked before each call; two specialists running in parallel can overshoot by one call each.
- Price grounding checks the Concierge's reply; arithmetic inside a specialist's reply is accepted as evidence.
- Per-tool token numbers are attributions; the numbers in this guide are simulated estimates.
- Sessions live in memory; there are no payments or accounts, and confirmation is checked by email match only.