

Estimating the Visual Complexity of Images from Textual Descriptions

Speech Lab Talks | September 30, 2022
Eleanor Lin

Outline

1. Goal & motivations
2. Developing a visual complexity metric
3. Predicting visual complexity from text

Goals

- Develop automated metric for visual complexity
- Identify visually complex images from text descriptions





Intuition: Biases exist in how humans describe images of different complexities

“a **very cluttered** chinese street showing **many** business signs”

Motivation

- CV models struggle on complex images
- Examples
 - visual search
 - caption generation
 - object detection/segmentation



What is visual complexity?

- SAVOIAS dataset: **cluttered background, number/diversity of objects, people, textures, patterns, shapes** (Saraee et al., 2018)
- Other definitions/dimensions:
 - Difficulty to describe image
 - Amount of information contained (image compression ratio)
 - Colorfulness

(. . . and more)

SAVOIAS Dataset (Saraee et al., 2018, p. 5)




Table 2: Sample images of the SAVOIAS dataset with increased visual complexity from left to right in each row.

Choosing a Visual Complexity Metric

Problems:

- SAVOIAS dataset lacks image captions
- SAVOIAS is small (200 images per most categories)

Approach:

1. Find automated visual complexity metric correlated with SAVOIAS human visual complexity scores
2. Use metric to score complexity of images from **COCO dataset**
3. Train model to identify complex images from captions

COCO Dataset (Lin et al., 2014)

123,287 images (train/val sets), 80 object categories, 11 supercategories



“a store with bunches of bananas hanging from a wire.”

“a man putting something on is desk while food is sitting in the front in boxes.”


“a kitchen with a bunch of food in boxes and bananas hanging from hooks”

“a man working in an outdoor market with various vegetables and fruits.”

“the storefront of a small open produce market.”

Visual complexity metric: Distinct # of regions

Type	Metric	Scenes	Objects	Interior Design	All
Low-level	Compression ratio (Saraee et al., 2020)	0.30	0.16	0.72	—
Low-level	Feature congestion (Saraee et al., 2020)	0.42	0.30	0.63	—
Low-level	Number of regions (Saraee et al., 2020)	0.57	0.29	0.69	—
High-level	VGG16 Scene Recognition, UAE (Saraee et al., 2020)	0.76	0.67	0.82	—
High-level	VGG16 Object Classification, UAE (Saraee et al., 2020)	0.77	0.64	0.83	—
High-level	VGG16 Object Classification, SAE from Depth Features (Saraee et al., 2020)	0.85	0.80	0.86	—
Low-level	Number of regions [Ours] (Comaniciu and Meer, 2002; Jean, 2020)	0.63	0.36	0.71	0.50
Low-level	Number of distinct regions [Ours]	0.73	0.55	0.81	0.62



Unfiltered regions: 382


Number of distinct regions: 83



Mean-shift
segmentation



Filter for distinct
regions
(compare color
and size)



Training the Models: Classify Complex v. Noncomplex

- Images with top/bottom 10% most/fewest distinct regions
 - label “complex”/”noncomplex”

Task	Split	Image source	# images	# captions
Binary classification	train	MS COCO 2017 train set	22656	113342
Binary classification	val	MS COCO 2017 train set	1000	5001
Binary classification	test	MS COCO 2017 val set	1000	5004
Regression	train	MS COCO 2017 train set	113287	566747
Regression	val	MS COCO 2017 train set	5000	25006
Regression	test	MS COCO 2017 val set	5000	25014

Probability that image is
complex: 0.923



Label:
complex

“people watching an
elephant near some water
and a fence”

BERT
BASE

Training the Models: Classify Complex v. Noncomplex (+ regression)

Classification

- **Inputs:** tokenized COCO captions, size = 128
- **Labels:** "complex" or "noncomplex"
- **Output:** probability that input caption describes a complex image
- **Loss:** Binary cross-entropy loss
- $\lambda = 2 * 10^{-5}$
- Fine-tune for 4 epochs > choose model with highest accuracy on validation set

$$P(\text{complex}) = p = \sigma(x) = \frac{1}{1 + e^{-x}}$$

$$l = y * \log(p) + (1 - y) * \log(1 - p)$$

Regression

- **Inputs, learning rate, # of epochs:** same as above
- **Labels:** complexity score in (0, 1)
 - **Normalization:** $c = \tanh(r/80)$
- **Output:** Normalized complexity score
- **Loss:** MSE loss

$$l = (x - y)^2$$

Results: What's going on?

Complex



"several different types of stuffed animals arranged on shelves."
 $p(\text{complex}) = 0.994$,
label = 1



"a colorful farmers market has vegetables and fruit on display."
 $p(\text{complex}) = 0.995$,
label = 1



"a crowd gathered for a small-town parade looks on as the next float comes down the street."
 $p(\text{complex}) = 0.994$,
label = 1



"a plate with sliced pizza and a bottle of beer."
 $p(\text{complex}) = 0.991$,
label = 1

noncomplex



"a couple of surfers in wetsuits catching a gentle wave"
 $p(\text{complex}) = 0.002$,
label=0



"a skier jumps into the air in front of a huge audience."
 $p(\text{complex}) = 0.004$,
label=1



"the airplane is flying in the clear blue sky."
 $p(\text{complex}) = 0.002$,
label=0




"a woman on a sandy beach flying a kite."
 $p(\text{complex}) = 0.001$,
label=0

Classifier:
83.9% accuracy
BCE Loss = 0.411
(val set)

Regression model:
MSE = 0.03
 $r = 0.659$
($p < 0.001$)
(val set)

Problem: Class Imbalance between Complex/Noncomplex



Solutions to Class Imbalance

1. Cross-domain evaluation
2. Transformed captions

What if we fine-tune only on images containing ____ ?

Goal: reduce ability of model to exploit biases in COCO dataset wrt complexity of specific object type images

COCO (super)category	classification set # complex	classification set # noncomplex	regression set # total
person	35,895	30,674	307,365
vehicle	16,808	11,748	131,297
outdoor	8,075	3,673	61,860
animal	8,860	12,163	114,834
accessory	13,200	6,817	84,781
sports	6,466	17,956	111,282
kitchen	15,976	3,137	99,430
food	16,792	1,521	77,820
furniture	18,321	8,785	141,086
electronic	5,282	2,897	62,151
appliance	2,111	3,527	37,632
indoor	7,773	4,821	75,917

all n labels in our training set

$$t_1, t_2, \dots, t_n \quad (7)$$

the Weighted Random Sampler samples from the set according to probabilities (or weights)

$$p_1, p_2, \dots, p_n \quad (8)$$

We compute the weights as follows. If $t_i = 1$ (complex) for $1 \leq i \leq n$, then

$$p_i = \frac{1}{n_{\text{complex}}} \quad (9)$$

i.e., the weight for a complex sample is the reciprocal of the number of complex training samples. Similarly, if $t_i = 0$ (noncomplex), then

$$p_i = \frac{1}{n_{\text{noncomplex}}} \quad (10)$$

Results

COCO (super)category of dataset	Best classifier trained on	Validation set accuracy [Baseline accuracy]	Average validation set loss (Cross-entropy)	Average precision
none (full set)	full set	0.839 [0.500]	0.411	0.913
person	full set	0.830 [0.539]	0.432	0.908
vehicle	vehicle	0.821 [0.589]	0.444	0.919
outdoor	person	0.758 [0.687]	0.613	0.864
animal	full set	0.802 [0.579]	0.501	0.818
accessory	accessory	0.818 [0.659]	0.531	0.902
sports	full set	0.851 [0.735]	0.370	0.762
kitchen	electronic	0.909 [0.646]	0.342	0.965
food	full set	0.923 [0.917]	0.273	0.974
furniture	indoor	0.892 [0.617]	0.308	0.939
electronic	electronic	0.811 [0.646]	0.547	0.900
appliance	indoor	0.836 [0.626]	0.421	0.865
indoor	indoor	0.827 [0.617]	0.427	0.924
COCO (super)category of dataset	Best regression model trained on	Pearson's r	Average validation set loss (Mean squared error)	Average precision
none (full set)	full set	0.659 ($p < 0.001$)	0.030	0.951
person	full set	0.594 ($p < 0.001$)	0.031	0.946
vehicle	full set	0.016 ($p = 0.238$)	0.031	0.954
outdoor	full set	0.483 ($p < 0.001$)	0.032	0.939
animal	full set	0.517 ($p < 0.001$)	0.032	0.861
accessory	full set	0.506 ($p < 0.001$)	0.035	0.968
sports	full set	0.603 ($p < 0.001$)	0.030	0.866
kitchen	kitchen	0.520 ($p < 0.001$)	0.027	0.977
food	food	0.500 ($p < 0.001$)	0.029	0.991
furniture	furniture	0.595 ($p < 0.001$)	0.028	0.988
electronic	electronic	0.479 ($p < 0.001$)	0.025	0.978
appliance	full set	0.571 ($p < 0.001$)	0.023	0.896
indoor	full set	0.497 ($p < 0.001$)	0.029	0.961

Transformed captions

Thus the caption

(1) Shelves of stuffed animals of various color and shapes.

becomes

(2) objects of plain objects of plain object and objects.

Word tagged with

Substitute with

NN, NNP

object

NNS, NNPS

objects

VB, VBP

act

VBD, VBN

acted

VBG

acting

VBZ

acts

JJ

plain

JJR, RBR



plainer

JJS, RBS

plainest

RB

plainly



Conclusions

- Visual complexity ~ Description of image
- BERT learns complexity biases in COCO
- Other possible directions:
 - Using different groundtruth visual complexity metric
 - Training on other captioned image datasets
 - Are images predicted complex by text-based model actually more difficult for CV models (caption generators, object detectors, etc.)?
 - Are images with high complexity score (distinct # of regions) actually more difficult for CV models?

Acknowledgements

Thank you to Vicente Ordonez and Ziyang Yang for their mentorship throughout this project.

This work was supported by the Computing Research Association's Distributed Research Experiences for Undergraduates program, which receives funding from the National Science Foundation.

This work was also supported by the National Science Foundation under Grant No. 2221943. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.