Multiplayer Blackjack

Software Requirements Specification

Revision History

Date	Revision	Description	Author
02/15/2026	1.0	Initial Version	Michael, Curtis, Emma
02/25/2026	2.0	Started requirement list (2.3), added modules, filled out first three sections of SRS	Curtis, Michael, Emma
02/26/2026	2.5	Filled functional requirements (3.1)	Emma
02/27/2026	2.6	Added to functional requirements (3.1)	Emma
02/28/2026	2.7	Modified dependencies (2.5), modified and added to functional requirements (3.1), created non-functional requirements (4), resolved a contradiction from high-level features and player module requirements (2.3)	Curtis

Table of Contents

1. Purpose **4**
1.1. Scope 4
1.2. Definitions, Acronyms, Abbreviations 4
1.3. References 4
1.4. Overview 4
2. Overall Description **5**
2.1. Product Perspective 5
2.2. Product Architecture 5
2.3. Product Functionality/Features 5
2.4. Constraints 6
2.5. Assumptions and Dependencies 6
3. Specific Requirements **7**
3.1. Functional Requirements 7
3.1.1. Common Requirements: 7
3.1.2. Server Module Requirements: 7
3.1.3. Client Module Requirements: 7
3.1.4. Dealer Module Requirements: 7
3.1.5. Player Module Requirements 8
3.1.6. Game Module Requirements: 8
3.1.7. Table Module Requirements: 9
3.2. External Interface Requirements 9
3.3. Internal Interface Requirements 10
4. Non-Functional Requirements **11**
4.1. Security and Privacy Requirements 11
4.2. Environmental Requirements 11
4.3. Performance Requirements 11

1. Purpose

This document outlines the requirements for the Multiplayer Blackjack program.

1.1. Scope

This document will catalog the user, system, and hardware requirements for the Multiplayer Blackjack program. It will not, however, document how these requirements will be implemented.

1.2. Definitions, Acronyms, Abbreviations

Balance - How much currency a player user can use to bet with.

Bust - When a card total surpasses 21.

Boot/Shoe - A set of cards composed of multiple decks shuffled together.

Hand - The cards a player possesses in a round.

Hit - To get another card to add to hand during a turn.

Hole card - The first card drawn by the dealer; it is dealt face down.

Rank - The value of a card.

Stand - To keep current hand during a turn.

1.3. References

UML Use Case Diagrams – Pages X-X

UML Class Diagrams – Pages X-X

UML Sequence Diagrams – Pages X-X

1.4. Overview

The Multiplayer Blackjack program simulates the experience of walking into a casino and playing blackjack. Players join a table with a dealer and bet from their balance. Players can hit or stand to get their score as close to 21 as possible without going over. If a player's score is better than the dealer's, they win their bets, but if the dealer has a better score, the player loses their bets.

2. Overall Description

2.1. Product Perspective

The Multiplayer Blackjack program is perfect for casinos who wish to provide their users with a mobile experience for this classic card game.

2.2. Product Architecture

The system will be organized into 6 major modules: The Server Module, The Client Module, The Dealer Module, The Player Module, The Game Module, and The Table Module.

2.3. Product Functionality/Features

The high-level features of the system are as follows (see section 3 of this document for more detailed requirements that address these features):

2.3.1. Users are split into two roles: dealers and players
2.3.2. Client connects to server
2.3.3. User logs into client application with username and password
2.3.4. There is a main menu
2.3.5. From main menu, the user can quit, join a table, or check balance
2.3.6. Players can deposit or withdraw from their balance
2.3.7. Each table can take 6 players and 1 dealer
2.3.8. Blackjack game starts when a table has at least 1 player and 1 host
2.3.9. Players choose what they bet each game under a time limit
2.3.10. Bets are validated
2.3.11. All users draw two cards, starting with the dealer going clockwise one at a time
2.3.12. The turn order goes counterclockwise, starting with the player closest to the dealer
2.3.13. Users can see every users' cards,excluding the dealer's hole card
2.3.14. Users can hit or stand during their turn
2.3.15. Players who stand cannot take another turn
2.3.16. Users have a time limit on their turns
2.3.17. Users draw from the boot, which consists of six decks of standard playing cards
2.3.18. Users whose ranks add to over 21 bust, with players losing bets and the dealer causing the whole table to win theirs
2.3.19. Dealers must stand at at least 17
2.3.20. After all players stand or bust, the dealer hits until the must stand or they bust
2.3.21. Users whose ranks are below the dealer's loses their bets
2.3.22. Users whose ranks are above the dealer's win their bets
2.3.23. Users whose ranks match the dealer's keep their bets
2.3.24. Blackjacks are an instant win for users, prioritizing dealers
2.3.25. Aces count as either 11 or, if 11 would cause a bust, 1 in terms of rank
2.3.26. Face cards all count as 10 in terms of rank
2.3.27. Users can leave tables at any time
2.3.28. Users who disconnect may be timed out from joining another table to prevent players not losing their bets
2.3.29. Users who join mid game can only start playing when the next game starts
2.3.30. Games start every 10 seconds at a table if none are in progress
2.3.31. Servers should keep record of players' balances, usernames, passwords and roles
2.3.32. Player/Dealer have a time limit to make choices

2.4. Constraints

2.4.1. The program must be programmed in Java
2.4.2. The program must use TCP/IP for communication
2.4.3. No databases should be used for saving information

2.5. Assumptions and Dependencies

2.5.1. The program is assumed to run on hardware that supports a mouse and keyboard for user input.

2.5.2. The program is assumed to run on hardware that tracks time.

3. Specific Requirements

3.1. Functional Requirements

3.1.1. Common Requirements:

3.1.1.1. The system stores account data (username, password, balance).
3.1.1.2. Passwords are encrypted in storage.

3.1.2. Server Module Requirements:

3.1.2.1. The server allows multiple client connections simultaneously.

3.1.2.2. The server stores account data when users register.

3.1.2.3. The server validates users when they sign in.

3.1.2.4. The server stores users' balances.

3.1.2.5. The server automatically picks an applicable table for a player to join.

3.1.2.6. The server hosts tables and their blackjack games.

3.1.2.7. The server validates bets.

3.1.2.8. The server keeps track of the boot and the cards players hold and draw.

3.1.2.9. The server issues time outs to players who disconnect from the server or table mid-game to prevent players from keeping lost bets.

3.1.2.10. The server informs the client of any validation errors or time outs.

3.1.3. Client Module Requirements:

3.1.3.1. The client connects to the server on start up.

3.1.3.2. Users navigate the client application using a GUI.

3.1.3.3. The client can receive player balance from the server.

3.1.3.4. The client can send back a modified player balance to the server to be stored.

3.1.3.5. The client can request the server to find a table for the client to join.

3.1.3.6. During a blackjack round, the client receives information from the server on what cards a user is holding and what the dealer's non-hole card is.

3.1.3.7. The client tells the server when a user has stood or hit.

3.1.3.8. When the client is informed of a validation error or time out, that information is displayed to the user.

3.1.4. Dealer Module Requirements:

3.1.4.1. New dealer accounts can be created.
3.1.4.2. Dealers sign into their account using username and password.

3.1.4.3. Failed dealer login alerts user and prompts again.

3.1.4.4. A dealer account can only be signed in on one device at a time.

3.1.4.5. At the beginning of a round, the dealer first deals two cards to each player (all face up), then two to themself (one face up and one face down).

3.1.4.6. After all players have played, the dealer plays following fixed rules.

3.1.4.7. The dealer must hit on a hand of 16 or less and stand on a hand of 17 or more.

3.1.4.8. The dealer must continue to hit until their card total adds to 17 or more.

3.1.4.9. Once the dealer finishes their turn the round is completed.

3.1.4.10. The dealer reveals their hand at the end of the round.

3.1.5. Player Module Requirements

3.1.5.1. New player accounts can be created.

3.1.5.2. Players sign into their account using username and password.

3.1.5.3. Failed player login alerts user and prompts again.

3.1.5.4. A player account can only be signed in on one device at a time.

3.1.5.5. Players have a balance attached to their account.

3.1.5.6. Players can deposit to and withdraw from their balance. This is entered manually by the player.

3.1.5.7. The player must place a bet at the beginning of each round.

3.1.5.8. A player places a bet by selecting chips.

3.1.5.9. When a player places a bet, the bet amount is removed from the player's balance.

3.1.5.10. A player cannot bet more than what is available in their balance. Bets are validated.

3.1.5.11. During a round of blackjack, a player has a hand made up of cards.

3.1.5.12. A player starts every round with two cards that are visible to everyone.

3.1.5.13. A player’s turn times out after 3 minutes. A turn timeout is an automatic stand.

3.1.5.14. During a player's turn, they can either hit (get another card to add to their hand) or stand (stay with their current hand).

3.1.5.15. During a player’s turn, they can continue to hit until their card total surpasses 21, at which point they have busted.

3.1.5.16. Cards received with hits are visible to everyone.

3.1.5.17. A player's turn ends once they either stand or bust.

3.1.5.18. A bust is an automatic loss.

3.1.5.19. At the end of a round a player loses or gains from their bet depending on how their hand compares to the dealer's hand.

3.1.5.20. If the player wins, the winnings are added to the player’s balance.

3.1.6. Game Module Requirements:

3.1.6.1. A card deck contains 52 cards.

3.1.6.2. A card deck is made up of 4 suits and 13 ranks.

3.1.6.3. A card deck can be shuffled.

3.1.6.4. A shoe consists of 6 mixed card decks.

3.1.6.5. The goal of the game blackjack is to get the card total of your hand as close to 21 as possible without going over.

3.1.6.6. Each player plays individually against the dealer.

3.1.6.7. Number cards 2-10 count as their respective numbers.

3.1.6.8. Face cards (king, queen, jack) each count as 10.

3.1.6.9. Ace cards count as either a 1 or an 11 depending on what is best for the hand.

3.1.6.10. A Blackjack is when the first two cards in a hand are an ace and a 10-value card.

3.1.6.11. A hand busts when its total surpasses 21.

3.1.6.12. The blackjack round cycle is betting, initial dealing, player turns, dealer turn, then bet resolution.

3.1.6.13.

3.1.6.14. Bets are placed with chips.

3.1.6.15. Chips are tokens that equate to either $1, $5, $25, $50, $100, or $500.

3.1.6.16. Players play first.

3.1.6.17. The dealer plays last.

3.1.6.18. At the end of a round, hands are compared and bets are settled.

3.1.6.19. When the player's hand is larger than the dealer's hand, the player wins 2x their bet (1:1 winning).

3.1.6.20. When the dealer busts, the player wins 2x their bet (1:1 winning).

3.1.6.21. When the player busts, the player loses their bet.

3.1.6.22. When the dealer's hand is larger than the player's hand, the player loses their bet.

3.1.6.23. When the player's hand and the dealer's hand are the same, the player gets their bet back.

3.1.6.24. When the player has a Blackjack and does not tie with the dealer, the player wins 2.5x their bet (3:2 winning).

3.1.7. Table Module Requirements:

3.1.7.1. A table consists of exactly 1 dealer.

3.1.7.2. A table can host 0-6 players.

3.1.7.3. A round of blackjack at an empty table begins once a player joins the table.

3.1.7.4. A table hosts consecutive rounds while the table is not empty.

3.1.7.5. A player cannot join a full table (6 players).

3.1.7.6. A new table automatically opens when all current tables are full.

3.1.7.7. Joining a table, a player must wait until the next round to play.

3.1.7.8. Multiple tables can be active at once.

3.1.7.9. Blackjack rounds start every 10 seconds at a table if none are in progress.

3.2. External Interface Requirements

3.2.1. There will be a graphical user interface.

3.2.2. There will be a sign in menu. From this menu a user can sign into an existing account, register as a player, or register as a dealer.

3.2.3. If the user chooses to sign in they are taken to a menu that asks for a username and password for an existing account.

3.2.4. If the user chooses to register they are taken to a menu that asks for a username and password to register a new account.

3.2.5. After players sign in, there will be a main player menu. From this menu players can view their account balance, add funds to their account, cash out their account, join a blackjack table, or log out.

3.2.6. Players will be able to see their current updated balance while playing a game.

3.2.7. At the beginning of a round, a player places a bet by selecting from chips displayed.

3.2.8. During a player's turn, the player will have a button to hit and a button to stand.

3.2.9. At the end of a round, a player's outcome is displayed (win, loss, tie).

3.2.10. After dealers sign in, there will be a main dealer menu. From this menu dealers can host a table or log out.
3.2.11. The system must run on hardware with networking abilities, keyboard, mouse, and display.
3.2.12. Depositing or withdrawing from the players' balance is handled by a banking service.

3.3. Internal Interface Requirements

3.3.1. Server and clients will communicate over TCP/IP.
3.3.2. User actions passed from client to server.
3.3.3. Clients cannot modify game data.
3.3.4. Balance modifications are concurrent.
3.3.5. No component shall directly modify another component's internal data.

4. Non-Functional Requirements

4.1. Security and Privacy Requirements

4.1.1. Passwords are encrypted in storage
4.1.2. User balance modifications and betting is validated

4.2. Environmental Requirements

4.2.1. No databases should be used for saving information

4.3. Performance Requirements

4.3.1. Users should be able to use their allotted decision making time within a minute

UML Use Case Diagrams

UML Class Diagram

UML Sequence Diagrams