


[illegible]

Round 1 - High - Easy p.175 Round 1 - High - Easy p.176 Round 1 - High - Easy p.177 Round 1 - High - Easy p.178 Round 1 - High - Easy p.179 Round 1 - High - Easy p.180



Input: grid = [[1,1,1,1],[1,1,3,1,1],[1,1,2,1,1],[1,1,1,1],[1,1,1,1]]
Output: (12,2,2),(2,2,2),(2,2,2)
Explanation: Notice that the 2 is contained within every contiguous 3 x 3 matrix in grid.
Constraints:
• n == grid.length
• 3 <= n <= 100
• 1 <= grid[i][j] <= 100
Brute Force (Python)

Round 1 - High - Easy

p.181

Brute Force Approach
class Solution:
def largestLocal(self, grid):
Brute Force O(n^2 * n^2) - Flood fill from every cell
n = len(grid), len(grid[0])
result = 0
for i in range(n):
for j in range(n):
visited = set()
if (i,j) in visited or not
visited.add((i,j))
for dr,dc in [(0,1),(0,-1),(1,0),(-1,0)]:
flood(rdr,cdc)
flood(i,j)
return result
def flood(self, i, j):
visited.add((i,j))
for dr,dc in [(0,1),(0,-1),(1,0),(-1,0)]:
flood(i+dr,j+dc)
flood(i,j)
return result
Community Solutions (Python)
• WalkCC

Round 1 - High - Easy

p.182

class Solution:
def largestLocal(self, grid: List[List[int]]) -> List[List[int]]:
n = len(grid)
ans = [[0] * (n - 2) for _ in range(n - 2)]
for i in range(n - 2):
for j in range(n - 2):
for k in range(n - 2):
ans[i][j] = max(ans[i][j], grid[i][k])
return ans
• LeetCode
class Solution:
def largestLocal(self, grid: List[List[int]]) -> List[List[int]]:
n = len(grid)
ans = [[0] * (n - 2) for _ in range(n - 2)]
for i in range(n - 2):
for j in range(n - 2):
ans[i][j] = max(grid[i][k] for k in range(i, i + 3) for j in range(j, j + 3))
return ans
• SimplyLeet

Round 1 - High - Easy

p.183

Python solution for finding the largest local values in a matrix
def largestLocal(grid):
n = len(grid) # dimension of the grid
Initialize the result matrix with zeros, of size (n-2) x (n-2)
result = [[0] * (n - 2) for _ in range(n - 2)]
Loop through each possible top-left index of a 3x3 submatrix
for i in range(n - 2):
for j in range(n - 2):
Compute the maximum in the current 3x3 submatrix
local_max = 0
for k in range(3):
for l in range(3):
local_max = max(local_max, grid[i + k][j + l])
Store the local maximum in the result matrix
result[i][j] = local_max
return result
Example usage:
grid = [[9,9,8,1],[5,6,2,6],[0,2,6,4],[6,2,2,1]]
print(largestLocal(grid))

Round 1 - High - Easy

p.184


grid = [[9,9,8,1],[5,6,2,6],[0,2,6,4],[6,2,2,1]]
print(largestLocal(grid))
• LeetCode
class Solution:
def largestLocal(self, grid: List[List[int]]) -> List[List[int]]:
n = len(grid)
res = [[0] * (n - 2) for _ in range(n - 2)]
for i in range(n - 2):
for j in range(n - 2):
res[i][j] = max(grid[i][k] for k in range(i, i + 3) for j in range(j, j + 3))
return res

Round 1 - High - Easy

p.185

Trees & BST
Round 1 - High - Easy - 11 questions
#100 Same Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Tree - DFS - BFS
Lists: Grid 169
Time Complexity: O(n), where n is the number of nodes in the tree, since every node is visited once. Space Complexity: O(n) in the worst-case (unbalanced tree), due to recursion call stack usage. In Problem
Given the roots of two binary trees p and q, write a function to check if they are the same or not. Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.
Example 1:
Round 1 - High - Easy
p.186

Trees & BST
#100 Same Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Tree - DFS - BFS
Lists: Grid 169
Time Complexity: O(n), where n is the number of nodes in the tree, since every node is visited once. Space Complexity: O(n) in the worst-case (unbalanced tree), due to recursion call stack usage. In Problem
Given the roots of two binary trees p and q, write a function to check if they are the same or not. Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.
Example 1:
Round 1 - High - Easy
p.187



Round 1 - High - Easy

p.188

The number of nodes in both trees is in the range [0, 100].
• 104 <= Nodeval <= 104
Brute Force (Python)
class Solution:
def isSameTree(self, p, q):
Brute Force O(n) - recursive structural comparison
if not p and not q: return True
if not p or not q or p.val != q.val: return False
return self.isSameTree(p.left, q.left) and self.isSameTree(p.right, q.right)
Community Solutions (Python)
• WalkCC
class Solution:
def isSameTree(self, p: TreeNode | None, q: TreeNode | None) -> bool:
if not p or not q:
return p == q
return (p.val == q.val and self.isSameTree(p.left, q.left) and self.isSameTree(p.right, q.right))
• LeetCode

Round 1 - High - Easy

p.189

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def isSameTree(self, p: Optional[TreeNode], q: Optional[TreeNode]) -> bool:
if p == q:
return True
if p is None or q is None or p.val != q.val:
return False
return self.isSameTree(p.left, q.left) and self.isSameTree(p.right, q.right)
• SimplyLeet

Round 1 - High - Easy

p.190

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
def isSameTree(self, p, q):
If both nodes are None, trees are identical
if not p and not q:
return True
If one of the nodes is None, trees are not identical.
if not p or not q:
return False
Check if current nodes have the same value.
if p.val != q.val:
return False
Recursively compare the left subtrees and the right subtrees.
return self.isSameTree(p.left, q.left) and self.isSameTree(p.right, q.right)
• LeetCode

Round 1 - High - Easy

p.191

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
Definition for a binary tree node.
def __init__(self, x):
self.val = x
self.left = None
self.right = None
class Solution(object):
def isSameTree(self, p, q):
:type p: TreeNode
:type q: TreeNode
:rtype: bool
• LeetCode

Round 1 - High - Easy

p.192

If not p or not q:
return p == q # covers: p=None and q=None, q=None and p=None, both None
return p.val == q.val and self.isSameTree(p.left, q.left) and self.isSameTree(p.right, q.right)
Iteration
class Solution:
def isSameTree(self, p: TreeNode, q: TreeNode) -> bool:
if p is None:
return q is None
if q is None:
return p is None
stack1 = [p]
stack2 = [q]
while stack1 and stack2:
current1 = stack1.pop()
current2 = stack2.pop()

Round 1 - High - Easy


p.193

None:
if current1 is None and current2 is None:
continue
elif current1 is None or current2 is None:
return False
elif current1.val != current2.val:
return False
stack1.append(current1.left)
stack2.append(current2.left)
stack1.append(current1.right)
stack2.append(current2.right)
return not stack1 and not stack2
Constraints:
• 104 <= Nodeval <= 104
• 100 <= Nodeval <= 100
Follow up: Could you solve it both recursively and iteratively?
Community Solutions (Python)
• WalkCC
class Solution:
def isSymmetric(self, root: TreeNode | None) -> bool:
if not root:
return True
return self.isSymmetric(p=root.left, q=root.right)
• LeetCode

Round 1 - High - Easy

p.194

Trees & BST
#101 Symmetric Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Tree - DFS - BFS
Lists: Grid 169
Time Complexity: O(n), where n is the number of nodes in the tree, since we traverse each node once. Space Complexity: O(h) for recursive call stack (worst-case O(n) for a skewed tree) or O(n) for the Problem
Given the root of a binary tree, check whether it is a mirror of itself (i.e., symmetric around its center).
Example 1:
Round 1 - High - Easy
p.195



Round 1 - High - Easy

p.196

Input: root = [1,2,2,3,null,3]
Output: true
Example 2:
Input: root = [1,2,2,3,null,3]
Output: false
Constraints:
• The number of nodes in the tree is in the range [1, 1000].
• -100 <= Nodeval <= 100
Follow up: Could you solve it both recursively and iteratively?
Community Solutions (Python)
• WalkCC
class Solution:
def isSymmetric(self, root: TreeNode | None) -> bool:
if not root:
return True
return self.isSymmetric(p=root.left, q=root.right)
• LeetCode

Round 1 - High - Easy

p.197

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def dfs(self, root: Optional[TreeNode], root2: Optional[TreeNode]) -> bool:
if root == root2:
return True
if not root or not root2:
return False
if root.val != root2.val:
return False
return self.dfs(root.left, root2.left) and self.dfs(root.right, root2.right)
• LeetCode

Round 1 - High - Easy

p.198

return True
if root1 is None or root2 is None or root1.val != root2.val:
return False
return self.dfs(root1.left, root2.left) and self.dfs(root1.right, root2.right)
Iteration
class Solution:
def isSymmetric(self, root: Optional[TreeNode]) -> bool:
if not root:
return True
stack1 = [root]
stack2 = [root]
while stack1 and stack2:
current1 = stack1.pop()
current2 = stack2.pop()

Round 1 - High - Easy

p.199

def isMirror(t1: TreeNode, t2: TreeNode) -> bool:
Both nodes are null, so they are mirrors.
if t1 is None and t2 is None:
return True
If one is null or the values do not match, symmetry fails.
if t1 is None or t2 is None or t1.val != t2.val:
return False
Recursively check mirror symmetry for children.
return self.isMirror(t1.left, t2.right) and self.isMirror(t1.right, t2.left)
Start recursion comparing the tree with itself.
return self.isMirror(root, root)
• LeetCode

Round 1 - High - Easy


p.200

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def isSymmetric(self, root: Optional[TreeNode]) -> bool:
def dfs(self, root1: Optional[TreeNode], root2: Optional[TreeNode]) -> bool:
if root1 is None and root2 is None:
return True
if root1 is None or root2 is None or root1.val != root2.val:
return False
return self.dfs(root1.left, root2.right) and self.dfs(root1.right, root2.left)
return dfs(self, root, root)
• LeetCode

Round 1 - High - Easy

p.201

Trees & BST
#104 Maximum Depth of Binary Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Tree - DFS - BFS
Lists: Grid 169
Time Complexity: O(n), where n is the number of nodes, since every node is visited once. Space Complexity: O(h) for recursion stack in DFS, where h is the height of the tree (worst-case O(n) for a skew tree)
Problem
Given the root of a binary tree, return its maximum depth. A binary tree's maximum depth is the number of nodes along the longest path from the root node down to the furthest leaf node.
Example 1:
Round 1 - High - Easy
p.202



Round 1 - High - Easy

p.203

class Solution:
def maxDepth(self, root: Optional[TreeNode]) -> int:
if not root:
return 0
return 1 + max(self.maxDepth(root.left), self.maxDepth(root.right))
• LeetCode
Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def maxDepth(self, root: Optional[TreeNode]) -> int:
if not root:
return 0
return 1 + max(self.maxDepth(root.left), self.maxDepth(root.right))
return 1 + max(l, r)
• SimplyLeet

Round 1 - High - Easy

p.204

Python Implementation using DFS
Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def maxDepth(self, root: Optional[TreeNode]) -> int:
Base case: if the node is null, return 0.
if not root:
return 0
Recursively compute the maximum depth of the left subtree.
left_depth = self.maxDepth(root.left)
Recursively compute the maximum depth of the right subtree.
right_depth = self.maxDepth(root.right)
Return the greater depth plus one for the current node.
return 1 + max(left_depth, right_depth)
• LeetCode

Round 1 - High - Easy


p.205

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def maxDepth(self, root: Optional[TreeNode]) -> int:
if not root:
return 0
Recursively compute the maximum depth of the left subtree.
left_depth = self.maxDepth(root.left)
Recursively compute the maximum depth of the right subtree.
right_depth = self.maxDepth(root.right)
Return the greater depth plus one for the current node.
return 1 + max(left_depth, right_depth)
• LeetCode

Round 1 - High - Easy

p.206

Trees & BST
#108 Convert Sorted Array to Binary Search Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Array - Divide and Conquer - Tree
Lists: Grid 169
Time Complexity: O(n) - Every element is processed exactly once. Space Complexity: O(n) - O(n) space is used to store the BST, and additional O(log n) space may be used for the recursion stack.
Problem
Given an integer array nums where the elements are sorted in ascending order, convert it to a height-balanced binary search tree.
Example 1:
Round 1 - High - Easy
p.207



Round 1 - High - Easy

p.208

Input: nums = [-10,-5,0,5,9]
Output: [0,-5,5,9,-10]
Explanation: [0,-5,5,9,-10] is also accepted:
Example 2:
Input: nums = [1,3]
Output: [1,3]
Explanation: [1,3] and [3,1] are both height-balanced BSTs.
Constraints:
• 1 <= nums.length <= 104
• -104 <= nums[i] <= 104
• nums is sorted in a strictly increasing order.
Brute Force (Python)
• LeetCode

Round 1 - High - Easy

p.209

Brute Force Approach
class Solution:
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
Brute Force - collect sorted, then process sorted list
vals = []
if not nums: return None
collect(node.left)
vals.append(node.val)
collect(node.right)
return vals
Build the BST if vals else 0
collect(node)
return vals
Community Solutions (Python)
• WalkCC
class Solution:
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
def build(l: int, r: int) -> Optional[TreeNode]:
if l > r:
return None
m = (l + r) // 2
return TreeNode(nums[m])
build(l, m - 1)
build(m + 1, r)
return build(l, len(nums) - 1)
• LeetCode

Round 1 - High - Easy

p.210

LeetCode
Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
def dfs(l: int, r: int) -> Optional[TreeNode]:
if l > r:
return None
mid = (l + r) // 2
node = TreeNode(nums[mid])
node.left = dfs(l, mid - 1)
node.right = dfs(mid + 1, r)
return node
Recursively build the left subtree.
node.left = dfs(l, mid - 1)
Recursively build the right subtree.
node.right = dfs(mid + 1, r)
return node
• SimplyLeet

Round 1 - High - Easy

p.211

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
Helper function to build BST from subarray indices
def build(l: int, r: int) -> Optional[TreeNode]:
Base condition: if no elements to process, return None
if l > r:
return None
Choose the middle element as the root for balance.
mid = (l + r) // 2
node = TreeNode(nums[mid])
node.left = build(l, mid - 1)
node.right = build(mid + 1, r)
return node
• LeetCode

Round 1 - High - Easy

p.212

Recursively build the right subtree.
node.right = buildBST(mid + 1, right)
return node
Build and return the BST from the entire array.
return buildBST(0, len(nums) - 1)
• LeetCode
Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
def dfs(l: int, r: int) -> Optional[TreeNode]:
if l > r:
return None
mid = (l + r) // 2
node = TreeNode(nums[mid])
node.left = dfs(l, mid - 1)
node.right = dfs(mid + 1, r)
return node
• LeetCode

Round 1 - High - Easy

p.213

return None
left = dfs(l, mid - 1)
right = dfs(mid + 1, r)
return TreeNode(nums[mid], left, right)
Recursively build the right subtree.
node.right = buildBST(mid + 1, right)
return node
Build and return the BST from the entire array.
return buildBST(0, len(nums) - 1)
• LeetCode
Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
def sortedArrayToBST(self, nums: List[int]) -> Optional[TreeNode]:
def dfs(l: int, r: int) -> Optional[TreeNode]:
if l > r:
return None
mid = (l + r) // 2
node = TreeNode(nums[mid])
node.left = dfs(l, mid - 1)
node.right = dfs(mid + 1, r)
return node
• LeetCode

Round 1 - High - Easy

p.214

type nums: List[int]
:rtype: TreeNode
nums:
midPos = len(nums) // 2
mid = nums[midPos]
root = TreeNode(mid)
self.sortedArrayToBST(nums[:midPos])
self.sortedArrayToBST(nums[midPos+1:])
return root
• LeetCode

Round 1 - High - Easy

p.215

Trees & BST
#110 Balanced Binary Tree
LeetCode - SimpleLeet - WalkCC - LeetCode
Tree - DFS
Lists: Grid 169
Time Complexity: O(n) where n is the number of nodes in the tree, since we visit each node once. Space Complexity: O(h) where h is the height of the tree, which corresponds to the recursion stack (O(n) Problem
Given a binary tree, determine if it is height-balanced.
Example 1:
Round 1 - High - Easy
p.216

Round 1 - High - Easy p.283 Round 1 - High - Easy p.284 Round 1 - High - Easy p.285 Round 1 - High - Easy p.286 Round 1 - High - Easy p.287 Round 1 - High - Easy p.288

<pre>res = vector(index) self.indices[self.cur] = index + 1 self.cur = (self.cur + 1) % self.size def hasNext(self) -> bool: start = self.cur while self.indices[self.cur] == len(self.vector[self.cur]): self.cur = (self.cur + 1) % self.size if self.cur == start: return False return True # Your ZigzagIterator object will be instantiated and called as such: # i, v = ZigzagIterator(v1, v2), [] # while i.hasNext(): v.append(i.next()) #####</pre>	<pre>""" iter() - builtin function, return an iterator object https://docs.python.org/3/library/functions.ht ml#iter >>> a = map(iter, [[1,2],[3,4]]) >>> c = a.popleft() <list_iterator object at 0x103084f0> >>> c.next() Traceback (most recent call last): File "<stdin>", line 1, in <module> AttributeError: 'list_iterator' object has no attribute 'next' >>> next(c) 1 >>> next(c) 2 >>> next(c) Traceback (most recent call last): File "<stdin>", line 1, in <module> StopIteration len() - Returns the length (the number of items) of an object https://docs.python.org/3/library/functions.ht ml#len</pre>	<pre>from collections import deque class ZigzagIterator(object): def __init__(self, v1, v2): """ Initialize your data structure here. type v1: List[int] type v2: List[int] """ self.iters = deque(map(iter, (v1, v2))) self.total = sum(len, (v1, v2)) def next(self): :rtype: int """ top = self.iters.popleft()</pre>	<pre>try: value = top.next() except StopIteration: return self.next() if self.total >= 1: if self.total >= 0: self.iters.append(top) return value def hasNext(self): """ :rtype: bool """ return self.total > 0 # Your ZigzagIterator object will be instantiated and called as such: # i, v = ZigzagIterator(v1, v2), [] # while i.hasNext(): v.append(i.next())</pre>	#307 Range Sum Query – Mutable LeetCode - 'SimplexLeet - WalkCC - LeetCode Arrays - Design - Binary Indexed Tree - Segment Tree Lists: Denay Zhang Time Complexity: O(log n) for both update and sumRange operations Space Complexity: O(n) to store the additional tree structure Problem Given an integer array nums, handle multiple queries of the following types: 1. Update the value of an element in nums. 2. Calculate the sum of the elements of nums between indices left and right inclusive where left <= right. Implement the NumArray class: - NumArray(int[] nums) Initializes the object with the integer array nums. - void update(int index, int val) Updates the value of nums[index] to be val. - int sumRange(int left, int right) Returns the sum of the elements of nums between indices left and right inclusive (i.e. nums[left] + nums[left + 1] + ... + nums[right]). Example 1:	Round 2 · High · Medium	p.361	Round 2 · High · Medium	p.362	Round 2 · High · Medium	p.363	Round 2 · High · Medium	p.364	Round 2 · High · Medium	p.365	Round 2 · High · Medium	p.366		
<pre>Input ["NumArray", "sumRange", "update", "sumRange"] [[1, 3, 5], [8, 2], [1, 2], [8, 2]] Output [null, 8, null, 8] Explanation NumArray numarray = new NumArray([1, 3, 5]); Constraints: 1 <= nums.length <= 3 * 10^4 -100 <= nums[i] <= 100 0 <= index <= nums.length - 1 -100 <= val <= 100 0 <= left <= right <= nums.length At most 10^4 calls will be made to update and sumRange. Community Solutions (Python) • WalkCC</pre>	<pre>class FenwickTree: def __init__(self, n: int): self.sums = [0] * (n + 1) def add(self, i: int, delta: int) -> None: while i <= len(self.sums): self.sums[i] += delta i = FenwickTree.lowbit(i) def get(self, i: int) -> int: sum = 0 while i > 0: sum += self.sums[i] i = FenwickTree.lowbit(i) return sum @staticmethod def lowbit(i: int) -> int: return i & -i</pre>	<pre>class NumArray: def __init__(self, nums: List[int]): self.nums = nums self.tree = FenwickTree(len(nums)) self.tree.add(1, nums) def update(self, index: int, val: int) -> None: self.nums[index] = val def sumRange(self, left: int, right: int) -> int: return self.tree.get(right + 1) - self.tree.get(left) # LeetCode class BinaryIndexedTree: __slots__ = ["n", "c"] def __init__(self, n): self.n = n self.c = [0] * (n + 1) def update(self, x: int, delta: int): while x <= self.n: self.c[x] += delta</pre>	<pre>x += x & -x def query(self, x: int) -> int: s = 0 while x > 0: s += self.c[x] x = x & -x return s class NumArray: __slots__ = ["tree"] def __init__(self, nums: List[int]): self.tree = BinaryIndexedTree(len(nums)) for i, v in enumerate(nums, 1): self.tree.update(i, v) def update(self, index: int, val: int) -> None: prev = self.sumRange(index, index)</pre>	<pre>self.tree.update(index + 1, val - prev) def sumRange(self, left: int, right: int) -> int: return self.tree.query(right + 1) - self.tree.query(left) # Your NumArray object will be instantiated and called as such: # obj = NumArray(nums) # obj.update(index, val) # param_2 = obj.sumRange(left, right) # SimplexLeet # Python Implementation using a Binary Indexed Tree (Fenwick Tree) class NumArray: def __init__(self, nums): # Store the original array self.nums = nums self.n = len(nums) # Initialize the BIT with 8s, size is (n+1) # because BIT is 1-indexed self.tree = [0] * (self.n + 1) # Build the BIT: update tree for each value # in the nums array for i, num in enumerate(nums):</pre>	<pre>self.update_tree(i, num) def update_tree(self, index, delta): # Update the BIT for index with delta change = 1 i = index + 1 # Convert to 1-indexed for BIT operations while i <= self.n: self.tree[i] += delta # Add delta to current tree node i = i + i & -i # Move to the next responsible node def update(self, index, val): # Calculate the difference between new value and current value delta = val - self.nums[index] self.nums[index] = val # Update the original array self.update_tree(index, delta) # Update the BIT to reflect this change def prefixSum(self, index): # Compute the prefix sum from start up to and including index result = 0 while index > 0: result += self.tree[index] index = index >> 1</pre>	Round 2 · High · Medium	p.367	Round 2 · High · Medium	p.368	Round 2 · High · Medium	p.369	Round 2 · High · Medium	p.370	Round 2 · High · Medium	p.371	Round 2 · High · Medium	p.372	
<pre>result = self.tree[i] i = i & -i # Move to parent node return result def sumRange(self, left, right): # Return the sum of the range [left, right] return self.prefixSum(right) - self.prefixSum(left - 1) if left > 0 else self.prefixSum(right) # Example usage: # numarray = NumArray([1, 3, 5]) # print(numarray.sumRange(0, 2)) # print(numarray.sumRange(0, 2)) # C++ class BinaryIndexedTree { public: BinaryIndexedTree(int n) { tree = vector<int>(n + 1, 0); } void update(int index, int val) { while (index > 0) { tree[index] += val; index = index >> 1; } } int query(int index) { int sum = 0; while (index > 0) { sum += tree[index]; index = index >> 1; } return sum; } }; def update(self, x, delta):</pre>	<pre>while x <= self.n: self.c[x] += delta x = BinaryIndexedTree.lowbit(x) def query(self, x): s = 0 while x > 0: s += self.c[x] x = BinaryIndexedTree.lowbit(x) return s class NumArray: def __init__(self, nums: List[int]): self.tree = BinaryIndexedTree(len(nums)) for i, v in enumerate(nums, 1): self.tree.update(i, v) def update(self, index: int, val: int) -> None: prev = self.sumRange(index, index)</pre>	<pre>self.tree.update(index + 1, val - prev) def sumRange(self, left: int, right: int) -> int: return self.tree.query(right + 1) - self.tree.query(left) # Your NumArray object will be instantiated and called as such: # obj = NumArray(nums) # param_2 = obj.sumRange(left, right) ##### # Segment tree node class STNode(object): def __init__(self, start, end): self.start = start self.end = end self.total = 0 self.left = None</pre>	<pre>self.right = None class SegmentTree(object): def __init__(self, nums, start, end): self.root = self.buildTree(nums, start, end) def buildTree(self, nums, start, end): if start == end: return None if start < end: node = STNode(start, end) node.total = nums[start] return node mid = start + (end - start) // 2 root = STNode(start, end) root.left = self.buildTree(nums, start, mid)</pre>	<pre>root.right = self.buildTree(nums, mid + 1, end) root.total = root.left.total + root.right.total return root.total def updateVal(self, i, val): if root.start == root.end: root.total += val return val mid = root.start + (root.end - root.start) // 2 if i <= mid: updateVal(root.left, i, val) else: updateVal(root.right, i, val) root.total = root.left.total + root.right.total return root.total return updateVal(self.root, i, val)</pre>	<pre>def sumRange(self, i, j): def rangeSum(root, start, end): if root.start == start and root.end == end: return root.total mid = root.start + (root.end - root.start) // 2 if i <= mid: return rangeSum(root.left, start, mid) elif j >= mid + 1: return rangeSum(root.right, start, end) else: return rangeSum(root.left, start, mid) + rangeSum(root.right, mid + 1, end) return rangeSum(self.root, i, j) class NumArray(object): def __init__(self, nums): """ initialize your data structure here. """</pre>	Round 2 · High · Medium	p.373	Round 2 · High · Medium	p.374	Round 2 · High · Medium	p.375	Round 2 · High · Medium	p.376	Round 2 · High · Medium	p.377	Round 2 · High · Medium	p.378	
<pre>type nums: List[int] return: int self.stTree = SegmentTree(nums, 0, len(nums) - 1) def update(self, i, val): type i: int type val: int return self.stTree.updateVal(i, val) def sumRange(self, i, j): """ sum of elements nums[i..j], inclusive. type i: int type j: int :rtype: int """ return self.stTree.sumRange(i, j) # Your Numarray object will be instantiated and called as such: # numarray = Numarray(nums) # numarray.sumRange(0, 1) # numarray.update(1, 38) # numarray.sumRange(1, 2)</pre>	Arrays & Hashing #454 4Sum II LeetCode - 'SimplexLeet - WalkCC - LeetCode Arrays - Hash Table Lists: CodeSignal Time Complexity: O(n^2) where n is the length of each array. Space Complexity: O(n^2) due to the storage of pair sums in the hash table. Problem Given four integer arrays nums1, nums2, nums3, and nums4 all of length n, return the number of tuples (i, j, k, l) such that: nums1[i] + nums2[j] + nums3[k] + nums4[l] == 0 Example 1: <pre>Input: nums1 = [1,2], nums2 = [-2,-1], nums3 = [-1,2], nums4 = [0,2] Output: 2 Explanation: The two tuples are: 1. (0, 0, 0, 0) -> nums1[0] + nums2[0] + nums3[0] + nums4[0] = 1 + (-2) + (-1) + 2 = 0 2. (1, 1, 0, 0) -> nums1[1] + nums2[1] + nums3[0] + nums4[0] = 2 + (-1) + (-1) + 2 = 0 Example 2:</pre>	<pre>Input: nums1 = [1,2], nums2 = [-2,-1], nums3 = [-1,2], nums4 = [0,2] Output: 2 Explanation: The two tuples are: 1. (0, 0, 0, 0) -> nums1[0] + nums2[0] + nums3[0] + nums4[0] = 1 + (-2) + (-1) + 2 = 0 2. (1, 1, 0, 0) -> nums1[1] + nums2[1] + nums3[0] + nums4[0] = 2 + (-1) + (-1) + 2 = 0 Example 2:</pre>	<pre>Input: nums1 = [0], nums2 = [0], nums3 = [0], nums4 = [0] Output: 1 Constraints: n == nums1.length n == nums2.length n == nums3.length n == nums4.length -1 <= n <= 200 -228 <= nums1[i], nums2[i], nums3[i], nums4[i] <= 228 Brute Force (Python) # Brute Force Approach class Solution: def fourSumCount(self, nums1, nums2, nums3, nums4): # Brute Force O(n^2) - check all pairs without a hash map n = len(nums1) for j in range(1, n): # process pair nums[i], nums[j] pass return 1 # adjust return Community Solutions (Python) • WalkCC</pre>	<pre>class Solution: def fourSumCount(self, nums1: List[int], nums2: List[int], nums3: List[int], nums4: List[int]) -> int: count = collections.Counter(a + b for a in nums1 for b in nums2) return sum(count[-c - d] for c in nums3 for d in nums4) # LeetCode class Solution: def fourSumCount(self, nums1: List[int], nums2: List[int], nums3: List[int], nums4: List[int]) -> int: cnt = Counter(a + b for a in nums1 for b in nums2) return sum(cnt[-(c + d)] for c in nums3 for d in nums4) # SimplexLeet</pre>	<pre># Function to count quadruplets that sum to zero using a hash map approach def four_sum_count(nums1, nums2, nums3, nums4): # Dictionary to store the frequency of sums of elements from nums1 and nums2 sum_count = {} for num1 in nums1: for num2 in nums2: current_sum = num1 + num2 sum_count[current_sum, 0] = 1 sum_count.get(current_sum, 0) + 1 count = 0 # For each pair from nums3 and nums4, find the complement that makes the total sum zero for num3 in nums3: for num4 in nums4: complement = -(num3 + num4) count = sum_count.get(complement, 0) return count # Example usage nums1 = [1,2] nums2 = [-2,-1] nums3 = [-1,2] nums4 = [0,2] print(four_sum_count(nums1, nums2, nums3, nums4)) # Expected Output: 2</pre>	<pre># C++ from collections import Counter class Solution: def fourSumCount(self, nums1: List[int], nums2: List[int], nums3: List[int], nums4: List[int]) -> int: cnt = Counter(a + b for a in nums1 for b in nums2) return sum(cnt[-(c + d)] for c in nums3 for d in nums4) ##### class Solution: def fourSumCount(self, nums1: List[int], nums2: List[int], nums3: List[int], nums4: List[int]) -> int: counter = Counter() for a in nums1: for b in nums2: counter[a + b] += 1 ans = 0</pre>	Round 2 · High · Medium	p.379	Round 2 · High · Medium	p.380	Round 2 · High · Medium	p.381	Round 2 · High · Medium	p.382	Round 2 · High · Medium	p.383	Round 2 · High · Medium	p.384
<pre>for c in nums2: for d in nums4: # adding for every time (-c+d) return ans ##### class Solution: def fourSumCount(self, A, B, C, D): """ type A: List[int] type B: List[int] type C: List[int] type D: List[int] :rtype: int """ ans = 0 abdict = {} for i in range(len(A)): ans += abdict.get(C - D + A[i], 0)</pre>	<pre>for j in range(len(B)): if A[i] + B[j] not in abdict: abdict[A[i] + B[j]] = 1 else: abdict[A[i] + B[j]] += 1 for i in range(len(C)): for j in range(len(D)): if -(C[i] - D[j]) in abdict: ans += abdict[-(C[i] - D[j])] return ans</pre>	Arrays & Hashing #525 Contiguous Array LeetCode - 'SimplexLeet - WalkCC - LeetCode Arrays - Hash Table - Prefix Sum Lists: Grid 169 Time Complexity: O(n) - We iterate through the array once. Space Complexity: O(n) - In the worst case, we store an entry for each prefix sum. Problem Given a binary array nums, return the maximum length of a contiguous subarray with an equal number of 0 and 1. Example 1: <pre>Input: nums = [0,1] Output: 2 Explanation: [0, 1] is the longest contiguous subarray with an equal number of 0 and 1.</pre> Example 2: <pre>Input: nums = [0,1,0] Output: 2 Explanation: [0, 1] (or [1, 0]) is a longest contiguous subarray with equal number of 0 and 1.</pre> Example 3:	<pre>Input: nums = [0,1,1,1,1,0,0,1,1] Output: 6 Explanation: [1,1,1,0,0,1] is the longest contiguous subarray with equal number of 0 and 1.</pre> Constraints: 1 <= nums.length <= 105 - nums[i] is either 0 or 1. Brute Force (Python) Brute Force Approach class Solution: def findMaxLength(self, nums): # Brute Force O(n^2) - check all pairs without a hash map n = len(nums) for i in range(1, n): # process pair nums[i], nums[j] pass return 1 # adjust return Community Solutions (Python) • WalkCC • SimplexLeet	<pre>class Solution: def findMaxLength(self, nums: List[int]) -> int: ans = 0 # Dictionary to store the earliest occurrence # of each prefix sum prefix_indices = {} prefix_sum = 0 max_length = 0 # Iterate over the array # for index, num in enumerate(nums): # Convert 0 to -1, keep 1 as is if num == 0: prefix_sum -= 1 else: prefix_sum += 1 # If the prefix sum has been seen before, a # balanced subarray exists if prefix_sum in prefix_indices: # Calculate the length of the subarray current_length = index - prefix_indices[prefix_sum] ans = max(ans, current_length) else: prefix_indices[prefix_sum] = index</pre>	Round 2 · High · Medium	p.385	Round 2 · High · Medium	p.386	Round 2 · High · Medium	p.387	Round 2 · High · Medium	p.388	Round 2 · High · Medium	p.389	Round 2 · High · Medium	p.390		
<pre>max_length = max(max_length, current_length) else: # Store the index for this prefix sum if not already seen prefix_indices[prefix_sum] = index # Return the maximum length of balanced subarray return max_length # Example usage: # print(findMaxLength([0,1,0,1])) # Expected output: 2 # C++ class Solution: def findMaxLength(self, nums: List[int]) -> int: ans = 0 mp = {} for i, v in enumerate(nums): s = 1 if v == 1 else -1 if s in mp: ans = max(ans, i - mp[s]) else: mp[s] = i return ans</pre>	Arrays & Hashing #560 Subarray Sum Equals K LeetCode - 'SimplexLeet - WalkCC - LeetCode Arrays - Hash Table - Prefix Sum Lists: Grid 169 Time Complexity: O(n) Space Complexity: O(n) Given an array of integers nums and an integer k, return the total number of subarrays whose sum equals to k. A subarray is a contiguous non-empty sequence of elements within an array. Example 1: <pre>Input: nums = [1,1,1], k = 2 Output: 2 Explanation: [1, 1] and [1, 1] are the only two subarrays with sum equal to 2.</pre> Example 2: <pre>Input: nums = [1,2,3], k = 3 Output: 2 Explanation: [1, 2] and [2, 1] are the only two subarrays with sum equal to 3.</pre>	<pre>class Solution: def subarraySum(self, nums: List[int], k: int) -> int: count = 0 for i in range(len(nums)): total = 0 for j in range(i, len(nums)): total += nums[j] if total == k: count += 1 return count Community Solutions (Python) • WalkCC class Solution: def subarraySum(self, nums: List[int], k: int) -> int: ans = 0 prefix = 0 count = collections.Counter({0: 1}) for num in nums: prefix += num ans += count[prefix - k] return ans # SimplexLeet</pre>	<pre># Function to calculate the number of subarrays that sum to k def subarraySum(nums, k): # Dictionary to store frequency of prefix sums prefix_counts = {} # Initialize with prefix sum 0 current_sum = 0 # Running sum initialization count = 0 # To count the valid subarrays # Iterate over the array for num in nums: current_sum += num # Update the running (prefix) sum # Check if there's a prefix sum that # differs from current_sum by k count -= prefix_counts.get(current_sum - k, 0) # Update the frequency count for the current sum prefix_counts[current_sum] = prefix_counts.get(current_sum, 0) + 1 return count # Example usage: print(subarraySum([1,1,1], 2)) # Expected output: 2 # C++</pre>	<pre>class Solution: def subarraySum(self, nums: List[int], k: int) -> int: dp = Counter({0: 1}) ans = 0 for num in nums: s += num ans += dp[s - k] # not matter if the same num like 1,1,1 dp[s] += 1 return ans ##### class Solution: def subarraySum(self, nums: List[int], k: int) -> int: count = 0 # sum value from 1 to i-th element sum_arr = [0] * (len(nums) + 1) # cached sum return count</pre>	Round 2 · High · Medium	p.391	Round 2 · High · Medium	p.392	Sheet 1 of 97	Print Mastery Study-Order	36	Round 2 · High · Medium	p.394	Round 2 · High · Medium	p.395	Round 2 · High · Medium	p.396	

Sum current element with the element at high pointer

nums[mid], nums[high] = nums[high], nums[mid]

Decrement high pointer

high -= 1

Example usage:

nums = [2,8,9,1,1,0]

sortColors(nums)

print(nums) # Output: [0,0,1,1,2,2]

LC63

class Solution:

def sortColors(self, nums: List[int]) -> None:

l, j, k = 0, len(nums), 0

while k < j:

if nums[k] == 0:

l += 1

nums[l], nums[k] = nums[k], nums[l]

k += 1

elif nums[k] == 2:

j -= 1

nums[j], nums[k] = nums[k], nums[j]

else:

k += 1

Round 2 · High · Medium

p305

Two Pointers

#161 One Edit Distance

LEETDOCS · SIMPLYLEET · WALKECC · LEETCODE

Two Pointers · String

Lists: Premium 98

Time Complexity: O(n), where n is the length of the shorter string, as we traverse both strings at most once. Space Complexity: O(1), using only constant extra space.

Problem

Given two strings s and t, return true if they are both one edit distance apart, otherwise return false. A string s is said to be one distance apart from a string t if you can:

• Insert exactly one character into s to get t.

• Delete exactly one character from s to get t.

• Replace exactly one character of s with a different character to get t.

Example 1:

Input: s = "ab", t = "acb"

Output: true

Explanation: We can insert 'c' into s to get t.

Example 2:

Round 2 · High · Medium

p306

Input: s = "", t = ""

Output: false

Explanation: We cannot get t from s by only one step.

Constraints:

• 0 <= s.length, length <= 104

• s and t consist of lowercase letters, uppercase letters, and digits.

Community Solutions (Python)

•WalkeCC

class Solution:

def isOneEditDistance(self, s: str, t: str) -> bool:

n = len(s)

m = len(t)

if n > m: # Make sure that |s| <= |t|.

return self.isOneEditDistance(t, s)

for i in range(m):

if s[i] != t[i]:

m = s[i] + 1 == t[i]

n = m

return n == m + 1

•SimplyLeet

Function to check if two strings are one edit distance apart

def isOneEditDistance(s: str, t: str) -> bool:

Get lengths of both strings

m, n = len(s), len(t)

The difference in length must not be greater than 1

if abs(n - m) > 1:

return False

Ensure s is the shorter string, or they are equal in length

return n >= m

•LeetCode

Round 2 · High · Medium

p307

class Solution:

def isOneEditDistance(self, s: str, t: str) -> bool:

if len(s) < len(t):

return self.isOneEditDistance(t, s)

if m == n:

if s == t:

return True

for i in range(m):

if s[i] != t[i]:

m = s[i] + 1 == t[i]

n = m

return n == m + 1

•SimplyLeet

Function to check if two strings are one edit distance apart

def isOneEditDistance(s: str, t: str) -> bool:

Get lengths of both strings

m, n = len(s), len(t)

The difference in length must not be greater than 1

if abs(n - m) > 1:

return False

Ensure s is the shorter string, or they are equal in length

return n >= m

•LeetCode

Round 2 · High · Medium

p308

If m > n:

return isOneEditDistance(t, s)

Initialize variables; found difference flag and indices for both strings

foundDifference = False

i = j = 0

while i < m and j < n:

if s[i] != t[j]:

If a difference has already been found, return False

return False

If found difference:

return False

foundDifference = True

If lengths are equal, move both pointers

if m == n:

i += 1

else:

If characters are the same, move the pointer in the shorter string

i += 1

Always move pointer for longer string

j += 1

Round 2 · High · Medium

p309

If no difference was found during iteration, then one extra character at the end is the edit return foundDifference or (j - i == 1)

Example usage:

print(isOneEditDistance("ab", "acd")) # Output: True

•LC63

class Solution:

def isOneEditDistance(self, s: str, t: str) -> bool:

if len(s) < len(t):

goal is to ensure t is always the shorter one

return self.isOneEditDistance(t, s)

m, n = len(s), len(t)

if m > n:

case: abc, abcd, return false

return False

for i, c in enumerate(t):

if c != s[i]:

Round 2 · High · Medium

p310

return s[i + 1:] == t[i + 1:] if

n == n else s[i + 1:] == t[i:] if

case: abc, abcd, return true

case: abc, abc, the same 2 strings should return false

return n == n + 1

#####

class Solution(object):

def isOneEditDistance(self, s, t):

"""

:type s: str

:type t: str

:rtype: bool

"""

if len(s) < len(t):

i = 0

while i < len(s) and s[i] == t[i]:

i += 1

return s == t and (s[i + 1:] == t[i:] if len(s) != len(t) else s[i + 1:] == t[i + 1:])

else:

return self.isOneEditDistance(t, s)

Round 2 · High · Medium

p311

Two Pointers

#167 Two Sum II - Input Array Is Sorted

LEETDOCS · SIMPLYLEET · WALKECC · LEETCODE

Array · Two Pointers · Binary Search

Lists: Donny Zhang

Time Complexity: O(n), where n is the number of elements in the array, because in the worst-case scenario each element is visited at most once. Space Complexity: O(1), as no additional data structure

Problem

Given a 1-indexed array of integers numbers that is already sorted in non-decreasing order, find two numbers such that they add up to a specific target number. Let these two numbers be numbers[index1] and numbers[index2] where 1 <= index1 < index2 <= numbers.length.

Return the indices of the two numbers index1 and index2, each incremented by one, as an integer array [index1, index2] of length 2.

The tests are generated such that there is exactly one solution. You may not use the same element twice. Your solution must use only constant extra space.

Example 1:

Round 2 · High · Medium

p312

Input: numbers = [2,7,11,15], target = 9

Output: [1,2]

Explanation: The sum of 2 and 7 is 9. Therefore, index1 = 1, index2 = 2. We return [1, 2].

Example 2:

Input: numbers = [2,3,4], target = 6

Output: [1,2]

Explanation: The sum of 2 and 4 is 6. Therefore index1 = 1, index2 = 3. We return [1, 3].

Example 3:

Input: numbers = [1,8], target = -1

Output: [1,2]

Explanation: The sum of -2 and 8 is -1. Therefore index1 = 1, index2 = 2. We return [1, 2].

Constraints:

• 2 <= numbers.length <= 3 * 10^4

• -1000 <= numbers[i] <= 1000

• numbers is sorted in non-decreasing order.

• -1000 <= target <= 1000

The tests are generated such that there is exactly one solution.

Brute Force (Python)

class Solution:

def twoSum(self, numbers: List[int], target: int) -> List[int]:

l = 0

r = len(numbers) - 1

while l < r:

sum = numbers[l] + numbers[r]

if sum == target:

return [l + 1, r + 1]

if sum < target:

l += 1

else:

r -= 1

Round 2 · High · Medium

p313

Brute Force Approach

class Solution:

def twoSum(self, numbers, target):

Brute Force O(n^2) - check every pair (ignore sorted property)

for i in range(len(numbers)):

for j in range(i + 1, len(numbers)):

if numbers[i] + numbers[j] == target:

return [i + 1, j + 1]

Community Solutions (Python)

•WalkeCC

class Solution:

def twoSum(self, numbers: List[int], target: int) -> List[int]:

l = 0

r = len(numbers) - 1

while l < r:

sum = numbers[l] + numbers[r]

if sum == target:

return [l + 1, r + 1]

if sum < target:

l += 1

else:

r -= 1

Round 2 · High · Medium

p314

•LeetCode

class Solution:

def twoSum(self, numbers: List[int], target: int) -> List[int]:

n = len(numbers)

for i in range(n - 1):

left = numbers[i]

right = len(numbers) - 1

while left < right:

sum = numbers[left] + numbers[right]

if sum == target:

return [left + 1, right + 1]

if sum < target:

left += 1

else:

right -= 1

•SimplyLeet

Python solution for Two Sum II - Input Array Is Sorted

def twoSum(numbers, target):

Initialize two pointers at the beginning and end of the array

left = 0

right = len(numbers) - 1

while left < right:

Continue until the two pointers meet

while left < right:

Calculate the sum of the two pointed values

current_sum = numbers[left] + numbers[right]

if current_sum == target:

return [left + 1, right + 1]

else:

if current_sum < target:

left += 1

else:

right -= 1

•LC63

class Solution:

def twoSum(self, numbers: List[int], target: int) -> List[int]:

l, j = 0, len(numbers) - 1

while l < j:

x = numbers[l] + numbers[j]

if x == target:

return [l + 1, j + 1]

if x < target:

l += 1

else:

j -= 1

Round 2 · High · Medium

p315

Two Pointers

#186 Reverse Words in a String II

LEETDOCS · SIMPLYLEET · WALKECC · LEETCODE

Two Pointers · String

Lists: Premium 98

Time Complexity: O(n) Space Complexity: O(1)

Problem

Given a character array s, reverse the order of the words. A word is defined as a sequence of non-space characters. The words in s will be separated by a single space. Your code must solve the problem in-place, i.e. without allocating extra space.

Example 1:

Input: s = ["t","h","e"," ","s","p","a","c","e"," ","","r","e","v","e","r","s","e"," ","t","h","e"," ","w","o","r","d","s"]

Output: ["r","e","v","e","r","s","e"," ","t","h","e"," ","w","o","r","d","s"," ","","s","p","a","c","e"," ","t","h","e"]

Example 2:

Input: s = ["a"]

Output: ["a"]

Constraints:

• 1 <= s.length <= 105

Round 2 · High · Medium

p317

s[i] is an English letter (uppercase or lowercase), digit, or space ' '.

There is at least one word in s.

s does not contain leading or trailing spaces.

All the words in s are guaranteed to be separated by a single space.

Brute Force (Python)

• Brute Force Approach

class Solution:

def reverse_range(self, s, left, right):

Brute Force O(n^2) - nested loops instead of two pointers

n = len(s)

for i in range(left, right):

for j in range(i + 1, n):

if s[i] != s[j]:

pass

Community Solutions (Python)

•WalkeCC

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p318

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p319

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p320

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p321

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p322

return s[i + 1:] == t[i + 1:] if

n == n else s[i + 1:] == t[i:] if

case: abc, abcd, return true

case: abc, abc, the same 2 strings should return false

return n == n + 1

#####

class Solution(object):

def isOneEditDistance(self, s, t):

"""

:type s: str

:type t: str

:rtype: bool

"""

if len(s) < len(t):

i = 0

while i < len(s) and s[i] == t[i]:

i += 1

return s == t and (s[i + 1:] == t[i:] if len(s) != len(t) else s[i + 1:] == t[i + 1:])

else:

return self.isOneEditDistance(t, s)

Round 2 · High · Medium

p311

Two Pointers

#186 Reverse Words in a String II

LEETDOCS · SIMPLYLEET · WALKECC · LEETCODE

Two Pointers · String

Lists: Premium 98

Time Complexity: O(n) Space Complexity: O(1)

Problem

Given a character array s, reverse the order of the words. A word is defined as a sequence of non-space characters. The words in s will be separated by a single space. Your code must solve the problem in-place, i.e. without allocating extra space.

Example 1:

Input: s = ["t","h","e"," ","s","p","a","c","e"," ","","r","e","v","e","r","s","e"," ","t","h","e"," ","w","o","r","d","s"]

Output: ["r","e","v","e","r","s","e"," ","t","h","e"," ","w","o","r","d","s"," ","","s","p","a","c","e"," ","t","h","e"]

Example 2:

Input: s = ["a"]

Output: ["a"]

Constraints:

• 1 <= s.length <= 105

Round 2 · High · Medium

p317

s[i] is an English letter (uppercase or lowercase), digit, or space ' '.

There is at least one word in s.

s does not contain leading or trailing spaces.

All the words in s are guaranteed to be separated by a single space.

Brute Force (Python)

• Brute Force Approach

class Solution:

def reverse_range(self, s, left, right):

Brute Force O(n^2) - nested loops instead of two pointers

n = len(s)

for i in range(left, right):

for j in range(i + 1, n):

if s[i] != s[j]:

pass

Community Solutions (Python)

•WalkeCC

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p318

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p319

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p320

class Solution:

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p321

def reverseWords(self, s: List[str]) -> None:

def reverse(l: int, r: int) -> None:

while l < r:

s[l], s[r] = s[r], s[l]

l += 1

r -= 1

def reverseWords(n: int) -> None:

i = 0

j = 0

while i < n:

while i < j or (i < n and s[i] == ' '):

skip the space.

i += 1

while j < i or (j < n and s[j] != ' '):

skip the space.

j += 1

reverse(i, j - 1) # Reverse the whole string.

reverseWords(len(s)) # Reverse each word.

•LeetCode

Round 2 · High · Medium

p322

return

def reverse(start, end, s):

while start < end:

s[start], s[end] = s[end], s[start]

start += 1

end -= 1

n = len(nums) - 1

k = k % len(nums)

reverse(0, n - k, nums)

reverse(n - k + 1, n, nums)

reverse(0, n, nums)

Round 2 · High · Medium

p323

Constraints:

• 1 <= nums.length <= 105

• -231 <= nums[i] <= 231 - 1

• 0 <= k <= 105

Follow-up:

• Try to come up with as many solutions as you can. There are at least three different ways to solve this problem.

• Could you do it in-place with O(1) extra space?

Brute Force (Python)

• Brute Force Approach

class Solution:

def rotate(self, nums, k):

Brute Force O(n^2) - nested loops instead of two pointers

n = len(nums)

for i in range(n):

for j in range(i + 1, n):

check nums[i] and nums[j]

pass

Community Solutions (Python)

•WalkeCC

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p324

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p325

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p326

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p327

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p328

return

def reverse(start, end, s):

while start < end:

s[start], s[end] = s[end], s[start]

start += 1

end -= 1

n = len(nums) - 1

k = k % len(nums)

reverse(0, n - k, nums)

reverse(n - k + 1, n, nums)

reverse(0, n, nums)

Round 2 · High · Medium

p323

Constraints:

• 1 <= nums.length <= 105

• -231 <= nums[i] <= 231 - 1

• 0 <= k <= 105

Follow-up:

• Try to come up with as many solutions as you can. There are at least three different ways to solve this problem.

• Could you do it in-place with O(1) extra space?

Brute Force (Python)

• Brute Force Approach

class Solution:

def rotate(self, nums, k):

Brute Force O(n^2) - nested loops instead of two pointers

n = len(nums)

for i in range(n):

for j in range(i + 1, n):

check nums[i] and nums[j]

pass

Community Solutions (Python)

•WalkeCC

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p324

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p325

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p326

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p327

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None:

def reverse(self, l: int, r: int):

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

Round 2 · High · Medium

p328

return

def reverse(start, end, s):

while start < end:

s[start], s[end] = s[end], s[start]

start += 1

end -= 1

n = len(nums) - 1

k = k % len(nums)

reverse(0, n - k, nums)

reverse(n - k + 1, n, nums)

reverse(0, n, nums)

Round 2 · High · Medium

p323

Constraints:

• 1 <= nums.length <= 105

• -231 <= nums[i] <= 231 - 1

• 0 <= k <= 105

Follow-up:

• Try to come up with as many solutions as you can. There are at least three different ways to solve this problem.

• Could you do it in-place with O(1) extra space?

Brute Force (Python)

• Brute Force Approach

class Solution:

def rotate(self, nums, k):

Brute Force O(n^2) - nested loops instead of two pointers

n = len(nums)

for i in range(n):

for j in range(i + 1, n):

check nums[i] and nums[j]

pass

Community Solutions (Python)

•WalkeCC

def rotate(self, nums: List[int], k: int) -> None:

k % len(nums)

self.reverse(nums, 0, len(nums) - 1)

self.reverse(nums, k, len(nums) - 1)

def reverse(self, nums: List[int], l: int, r: int) -> None:

while l < r:

nums[l], nums[r] = nums[r], nums[l]

l += 1

r -= 1

•LeetCode

class Solution:

def rotate(self, nums: List[int], k: int) -> None

Round 2 - High - Medium p.607 Round 2 - High - Medium p.608 Round 2 - High - Medium p.609 Round 2 - High - Medium p.610 Round 2 - High - Medium p.611 Round 2 - High - Medium p.612


```
Constraints:
• 0 <= nums.length <= 105
• 109 <= nums[i] <= 109
• nums is a non-decreasing array.
• -109 < target <= 109

Brute Force (Python)

• Brute Force Approach
class Solution:
    def searchRange(self, nums: List[int], target: int) -> List[int]:
        # Brute Force O(n) - Linear scan instead of binary search
        for i, val in enumerate(nums):
            if val == target:
                return i, i
        return -1, -1

Community Solutions (Python)

• WalkCC
class Solution:
    def searchRange(self, nums: List[int], target: int) -> List[int]:
        i = bisect_left(nums, target)
        if i < len(nums) and nums[i] == target:
            return i, i
        # bisect_right(nums, target) - 1
        return i, i
```

```

class Selection
  def searchRange(self, nums: List[int], target:
  int) -> List[int]:
    l = bisect_left(nums, target)
    r = bisect_right(nums, target + 1)
    return [l, -1] if l == r else [l, r - 1]

• Simplest
def searchRange(nums, target):
    # Helper function to find the boundary index
    (leftmost or rightmost) for target.
    def findBoundary(left):
        left, right = 0, len(nums) - 1
        boundary = -1
        while left <= right:
            mid = (left + right) // 2
            # If the target is found, update
            boundary and continue to search on one side.
            if nums[mid] == target:
                boundary = mid

```

```

    if isleft:
        right = mid - 1 # Continue
search on left half
else:
    left = mid + 1 # Continue
search on right half
elif min[mid] < target:
    left = mid + 1
else:
    right = mid - 1
return boundary

# Find the leftmost index
leftIndex = findBoundary(True)
if leftIndex == -1:
    return [-1, -1]
# Find the rightmost index
rightIndex = findBoundary(False)
return [leftIndex, rightIndex]

# Example usage:
# nums = [5,7,7,8,8,10]
# target = 8
# print(searchRange(nums, target)) # Output: [3, 4]

```

```

...
>>> bisect.bisect_left([1,1,1,2,2,2,7,7,7], 2)
6
>>> bisect.bisect_left([1,1,1,2,2,2,7,7,7], 2+1)
6
>>> bisect.bisect_right([1,1,1,2,2,2,7,7,7], 2)
6
>>> bisect.bisect_right([1,1,1,2,2,2,7,7,7], 2+1)
6
>>> bisect.bisect_left([1,1,1,2,2,2,7,7,7], 0)
0
>>> bisect.bisect_left([1,1,1,2,2,2,7,7,7], 1)
0
# below, even single value for 2, after +1 the
# index will be different
>>> bisect.bisect_left([1,2,3,4,5], 2)

```

```
1
2>>> bisect.bisect_left([1,2,3,4,5], 2+1)
3
4...
5
6import bisect
7
8class Selection:
9    def searchRange(self, nums: List[int], target:
10    int) -> List[int]:
11        l = bisect_left(nums, target)
12
13        r = bisect_left(nums, target + 1)
14        return [l-1, -1] if l == 0 else [l, r - 1]
15
16#####
17
18class Selection:
19    def searchRange(self, nums: List[int], target:
20    int) -> List[int]:
21        def findRange(to_left):
22            l, r = 0, len(nums) - 1
23            m = 0
```

```

while l <= r:
    m = l + (r - l) // 2
    if nums[m] < target:
        l = m + 1
    elif nums[m] == target:
        r = m - 1
        if l == toLeft and m > 0 and nums[m - 1] == target:
            l = m - 1
        elif l == toLeft and m == 0:
            len(nums) and nums[m + 1] == target: # so now l
        elif l == toLeft and m == 0 and m + 1 == len(nums) and nums[m + 1] == target: # so now l
        elif l == toLeft and m == 0 and m + 1 == len(nums) and nums[m] == target, but maybe not the leftmost or rightmost
            m = m + 1
    else:
        return m
    if m == len(nums) and nums[m] == target:
        # 1. cover not-found,
        # 2. cover not-found,
        first and last both [0] and target-0.
        return 0
    else:
        return m
return (findRange(True), findRange(False))

```

Round 2 • High • Medium

Round 2 • High • Medium

Round 2 • High • Medium p.6

und 2 • High • Medium p.63

and 2 • High • Medium p.65

and 2 • High • Medium p.654

#153 Find Minimum in Rotated Sorted Array

LeetCode - Simplexity - Walkerc - LeetCode
Array - Binary Search
Lists - Grid - 150
Time Complexity: $O(\log n)$ Space Complexity: $O(1)$

Problem

Suppose an array of length n is sorted in ascending order and then rotated between 1 and n times. For example, the array $nums = [0,1,2,5,6,7]$ might become:

- $[4,5,6,7,0,1]$ if it was rotated 4 times.
- $[1,2,5,6,7,0]$ if it was rotated 7 times.

Notice that rotating an array $[a_0, a_1, a_2, \dots, a_{n-1}]$ results in the array $[a_{n-1}, a_0, a_1, a_2, \dots, a_{n-2}]$.

Given the sorted rotated array $nums$ of unique elements, return the minimum element of this array.

You must write an algorithm that runs in $O(\log n)$ time.

Example 1:

```
Input: nums = [3,4,5,1,2]
Output: 1
Explanation: The original array was [1,2,3,4,5] rotated 3 times.
```

Found 2 - High - Medium

Example 2:

```
Input: nums = [4,5,6,7,8,1,2]
Output: 0
Explanation: The original array was [8,1,2,5,6,7,4]
and it was rotated 4 times.
```

Example 3:

```
Input: nums = [13,13,13,17]
Output: 11
Explanation: The original array was [13,13,13,17]
and it was rotated 4 times.
```

Constraints:

- n == nums.length
- 1 < n <= 5000
- 5000 <= nums[i] <= 5000
- All the integers of nums are unique.
- nums is sorted and rotated between 1 and n times.

Brute Force Approach

```
# Brute Force Approach
class Solution:
    def findMin(self, nums):
        # O(n^2) - just return the
        # minimum (ignores sorted structure)
        return min(nums)
```

Community Solutions (Python)

- walaCC

```

class Solution:
    def findKthSelf, nums: List[int]] -> int:
        l = 0
        r = len(nums) - 1

        while l < r:
            m = (l + r) // 2
            if nums[m] < nums[r]:
                l = m
            else:
                r = m + 1

        return nums[l]

# LeetCode
class Solution:
    def findKthSelf, nums: List[int]] -> int:
        if nums[0] == nums[-1]:
            return nums[0]
        left = l = 0, len(nums) - 1
        while left < right:
            mid = (left + right) // 2
            if nums[mid] < nums[mid+1]:
                left = mid + 1
            else:
                right = mid
        return nums[left]

```

Simplex	
	<pre> def findMid(nums): # Initialize left and right pointers left, right = 0, len(nums) - 1 # Continue while the search space is valid while left < right: mid = (left + right) // 2 # Compute middle index # If middle element is greater than the # rightmost element. # the minimum must be in the right half if nums[mid] > nums[right]: left = mid + 1 else: # Otherwise, the minimum is in the left # half (including mid) right = mid # When loop ends, left == right, pointing to # the minimum element return nums[left] </pre>
LC64	

```
class Solution:
    def findInt(self, nums: List[int]) -> int:
        if nums[0] <= nums[-1]:
            return nums[0]
        left, right = 0, len(nums) - 1
        while left < right:
            mid = (left + right) // 2
            if nums[mid] <= nums[mid]:
                left = mid + 1
            else:
                right = mid
        return nums[left]
```

Binary Search

300 Longest Increasing Subsequence

MED

LeetCode - Simply List - WalkCC - LeetCode

Array - Binary Search - Dynamic Programming

Time Complexity: $O(n \log n)$ for the length of nums

Space Complexity: $O(n)$ for storing the dp array

Problem

Given an integer array nums, return the length of the longest strictly increasing subsequence.

Example 1:

```

Input: nums = [10,9,2,5,3,7,101,18]
Output: 4
Explanation: The longest increasing subsequence is [2,3,7,10], therefore the length is 4.

```

Example 2:

```

Input: nums = [8,1,6,3,2,3]
Output: 4
Explanation: The longest increasing subsequence is [1,2,3,3], therefore the length is 4.

```

Example 3:

```

Input: nums = [7,7,7,7,7]
Output: 1

```

Constraints:

- 1 <= nums.length <= 3000
- 10⁹ <= nums[i] <= 10⁹

2 - High - Medium

```
# n = nums.length - 1; // 2500
# -104 <= nums[j] <= 104
```

Follow up: Can you come up with an algorithm that runs in O(n log(n)) time complexity?

Brute Force (Python)

```
# Brute Force Approach
class Solution:
    def lengthOfLIS(self, nums):
        # Brute Force O(N^2) ~ generate every
        # subsequent, find longest increasing
        # sequence
        if len(nums) == 1: return 1
        dp = [prev_val]
        for i in range(1, len(nums)):
            skip = lis[i+1, prev_val]
            take = 0
            if nums[i] > prev_val:
                return max(skip, take + 1, nums[i])
            else:
                return lis(i, prev_val)
        return lis(0, float('-inf'))
```

Community Solutions (Python)

- WallCC

```

class Solution:
    def lengthOfLIS(self, nums: List[int]) -> int:
        if not nums:
            return 0

        # dp[i] is the length of LIS ending in nums[i]
        dp = [1] * len(nums)

        for i in range(1, len(nums)):
            for j in range(i):
                if nums[j] < nums[i]:
                    dp[i] = max(dp[i], dp[j] + 1)

        return max(dp)

class Solution:
    def lengthOfLIS(self, nums: List[int]) -> int:
        # tails[i] = the minimum tails of all the
        # increasing subsequences having
        # length i + 1
        tails = []

        for num in nums:
            if not tails or num > tails[-1]:
                tails.append(num)
            else:

```

```

    tails[biset.biset_left(tails, num)] =
num

    return len(tails)

+lengthOf
class Solution:
    def lengthOfLI(self, nums: List[int]) -> int:
        n = len(nums)
        f = [1] * n
        for i in range(1, n):
            for j in range(i):
                if nums[j] < nums[i]:
                    f[i] = max(f[i], f[j] + 1)
        return max(f)

class Solution:
    def _init_(self, n: int):
        self.n = n
        self.s = [0] * (n + 1)

    def update(self, x: int, v: int):
        while x <= self.n:
            self.s[x] = max(self.s[x], v)
            x = x + x

```

```
def query(self, x: int) -> int:
    mx = 0
    while x:
        mx = max(mx, self.c[x])
        x = x >> x
    return mx

class Solution:
    def lengthOfLIS(self, nums: List[int]) -> int:
        n = len(nums)
        tree = BinaryIndexedTree(n)
        for x in nums:
            t = bisect_left(t, x) + 1
            t = tree.query(x - 1) + 1
            tree.update(x, t)
        return tree.query(n)
```

• Simplify

<pre> import bisect def lengthofLIS(nums): dp = [] # dp array stores smallest tail for each subsequent length for num in nums: # Find the leftmost insertion point using binary search idx = bisect.bisect_left(dp, num) if idx == len(dp): dp.append(num) # Extend dp if no larger tail exists else: dp[idx] = num # Replace to maintain the smallest tail return len(dp) # Example usage: # print(lengthofLIS([10,9,2,5,3,7,101,18])) # Output: 4 </pre>	Low - Medium
--	---------------------

```

find the largest and element in tails that is
smaller than nums[i]
# and then replace it with nums[i] and discard
the list in the same way
# which is implemented by 'tail[i] = num'

class Solution(object):
    def lengthOfLIS(self, nums):
        """
        :type nums: List[int]
        :rtype: int
        """
        tails = []
        for num in nums:
            # # using bisect_right(tail, num),
            # # then insert([7,7,7,7,7,7]) will
            # # be expected result is 1
            # # same as bisect_left(tail, num)
            # if num <= tail[-1]: same as in java:
            #     tail.append(num)
            # else:
            #     tail[i] = num
            return len(tails)

```

```
# implementation of bisect.bisect_left()
# similar to lowerCase-BISECT, find
left/right/top/bottom callable
def bisect_left(a, x, lo=0, hi=None):
    if hi is None:
        hi = len(a)

    while lo < hi:
        mid = (lo + hi) // 2

        if a[mid] < x:
            lo = mid + 1
        else:
            hi = mid

    return lo

#####

class BinaryIndexedTree:
```

```
def __init__(self, n: int):
    self.n = n
    self.c = [0] * (n + 1)

def update(self, x: int, v: int):
    while x <= self.n:
        self.c[x] = max(self.c[x], v)
        x = x <-> x

def query(self, x: int) -> int:
    mx = 0
    while x:
        mx = max(mx, self.c[x])
        x = x <-> x
    return mx

class Solution:
    def lengthOfLIS(self, nums: List[int]) -> int:
        n = len(nums)
        m = len(m)
        tree = BinaryIndexedTree(n)
        for x in nums:
            m = max(m, x)
            t = tree.query(x - 1) + 1
            tree.update(x, t)
        return tree.query(m)
```

#362 Design Hit Counter

LeetCode - SimpleLink - WalkCC - LeetCode

Array - Hash Table - Binary Search - Design - Queue Lists - Grid Traversal

Time Complexity: $O(1)$ per hit and gets hits operation on average. Space Complexity: $O(W)$ where W is the window size (1000 seconds) in the worst case

Problem:

Design a hit counter which counts the number of hits received in the past 5 minutes (i.e., the past 300 seconds).

Your system should accept a timestamp parameter (in seconds granularity), and you may assume that calls are received to the system in chronological order (i.e., timestamp is monotonically increasing). Several hits may arrive roughly at the same time.

Implement the HitCounter class:

- `HitCounter()` Initializes the object of the hit counter system.
- `hit(timestamp)` Records a hit that happened at `timestamp` (in seconds). Several hits may happen at the same timestamp.

Return 2 - High - Medium

```
int getHits(int timestamp) Returns the number of hits
in the past 5 minutes from timestamp (i.e. the past 300
seconds).
Example 1:
Input:
["HitCounter", "hit", "hit", "hit", "getHits", "hit",
"getHits", "getHits"]
[[], [1], [2], [3], [4], [300], [300], [301]]
Output:
[null, null, null, 3, null, 4, 5]
Explanation:
HitCounter() = new HitCounter();
Constructor
1. <= timestamp <= 2 * 109
• All the calls are being made to the system in
chronological order (i.e. timestamp is monotonically
increasing).
• At most 300 calls will be made to hit and getHits.
Follow up: What if the number of hits per second could
be huge? Does your design scale?
```

```
class HitCounter:
    def __init__(self):
        self.timeStamps = [0] * 300
        self.hits = [0] * 300

    def hit(self, timestamp: int) -> None:
        i = timestamp % 300
        if self.timeStamps[i] == timestamp:
            self.hits[i] += 1
        else:
            self.timeStamps[i] = timestamp
            self.hits[i] = 1 # Reset the hit count to 1.

    def getHits(self, timestamp: int) -> int:
        return sum(h for t, h in zip(self.timeStamps,
                                     self.hits)
                  if timestamp - t < 300)
```

```
class HitCounter:
    def __init__(self):
        self.ts = []

    def hit(self, timestamp: int) -> None:
        self.ts.append(timestamp)

    def getHits(self, timestamp: int) -> int:
        return len(self.ts) - bisect_left(self.ts,
            timestamp - 300 + 1)

# Your HitCounter object will be instantiated and
# called as such:
obj = HitCounter()
obj.hit(timestamp)
obj.getHits(timestamp)
```

```
# Python implementation of HitCounter
from collections import deque

class HitCounter:
    def __init__(self):
        # Initialize the deque to store (timestamp,
        # count) pairs.
        self.hits_queue = deque()

    def hit(self, timestamp: int) -> None:
        # If the last recorded hit is at the same
        # timestamp as the current hit, increment
        # its count.
        if self.hits_queue[-1][0] == timestamp:
            self.hits_queue[-1][1] += 1
        else:
            # Append new (timestamp, count) pair.
            self.hits_queue.append((timestamp, 1))

    def getHits(self, timestamp: int) -> int:
        # Remove outdated hits from the front of
        # the queue.
        while self.hits_queue and
            self.hits_queue[0][0] <= timestamp - 300:
```

```

    self.hits_queue.pop(left)
    # Sum counts of the remaining hit entries.
    return sum(count for _, count in
self.hits_queue)

```

1.1.6.4

from collections import deque

class HitCounter: # Queue

```

def __init__(self):
    """
    Initialize your data structure here.
    """
    self.hits = deque()

```

def hit(self, timestamp: int) -> None:

```

    """
    Record a hit.
    @param timestamp - The current timestamp
    (in seconds granularity).
    """
    self.hits.append(timestamp)

```

def getHits(self, timestamp: int) -> int:

```

    """
    Return the number of hits in the past 5
    minutes.
    """

```

```

@param timestamp - The current timestamp
(in seconds granularity).
...
self.hits += self.hits & self.hits[0] ==
timestamp - 360
self.hits.popLeft()
return len(self.hits)

class HitCounter: # Follow-up
def __init__(self):
    self.times = [0] * 360

    self.hits = [0] * 360

def hit(self, timestamp: int) -> None:
    idx = timestamp % 360
    if self.times[idx] != timestamp:
        self.times[idx] = timestamp
        self.hits[idx] = 1
    else:
        self.hits[idx] += 1

```

```
def getItems(self, timestamp: int) -> int:
    res = 0
    for i in range(300):
        if timestamp - self.items[i] < 300:
            res += self.items[i]
    return res

# Your HitCounter object will be instantiated and
called as such:
# obj = HitCounter()
# obj.hit(timestamp)
# obj.hit(timestamp)

# param_2 = obj.getItems(timestamp)

#####

class HitCounter:
    """Extra O(N) space
    def __init__(self):
        """
        Initialize your data structure here.
        """
        self.counter = Counter()
```

```
def hit(self, timestamp: int) -> None:
    """
    Record a hit.
    @param timestamp: The current timestamp
    (in seconds granularity).

    self.counter[timestamp] += 1

def getHits(self, timestamp: int) -> int:
    """
    Return the number of hits in the past 5
    minutes.
    @param timestamp: The current timestamp
    (in seconds granularity).

    return sum(v for t, v in
self.counter.items() if t >= 300 - timestamp)]

# Your HitCounter object will be instantiated and
called as such:
# obj = HitCounter()
# obj.hit(timestamp)
# param_2 = obj.getHits(timestamp)
```

528 Random Pick with Weight

Difficulty: MED

Topics: [Arrays](#), [Simplex](#), [LeetCode](#)

Binary Search - Prefix Sum - Randomized

Lists: [Grind 600](#)

Time Complexity: $O(n)$ for constructing the prefix sum array and $O(1)$ for `pickIndex()` call. Space Complexity: $O(n)$ for storing the prefix sum array.

Problem

You are given a 0-indexed array of positive integers `w` where `w[i]` describes the weight of the `i`th index. You need to implement the function `pickIndex()`, which randomly picks an index in the range `[0, w.length - 1]` and returns it. The weight of the picked index is `w[i]`.

For example, if `w = [1, 3]`, the probability of picking index 0 is $1 / (1 + 3) = 0.25$ (i.e., 25%), and the probability of picking index 1 is $3 / (1 + 3) = 0.75$ (i.e., 75%).

Example 1:

```
Input
["Solution", "pickIndex"]
[[1],[1],1]
Output
[1]
[1]
Explanation
Solution.solution = new Solution([1]);

Example 2:
Input
["Solution", "pickIndex", "pickIndex", "pickIndex",
 "pickIndex"]
[[2],[3],[1],[1],[1],[1]]
Output
[1]
[2]
[1]
[1]
[1]
Explanation
Solution.solution = new Solution([1, 3]);

Constraints:
• 1 <= w.length <= 104
• 1 <= w[i] <= 105
• pickIndex will be called at most 104 times.

Brute Force (Python)
```

```
# Brute Force Approach
class Solution:
    def __init__(self, w):
        # Brute Force O(n) - Linear scan instead of
        # binary search
        for i, val in enumerate(w):
            if val == target:
                return i
            return -1

Community Solutions (Python)
# wuolac
class Solution:
    def __init__(self, w: List[int]):
        self.prefix = list(itertools.accumulate(w))

    def pickIndex(self) -> int:
        target = random.randint(0, self.prefix[-1] - 1)
        return
        bisect.bisect_right(range(len(self.prefix)),
            target,
            key=lambda m:
# LeetCode
```

```
class Solution:
    def __init__(self, w: List[int]):
        self.w = w
        for c in w:
            self.s.append((self.s[-1] + c))

    def pickIndices(self) -> int:
        x = random.randint(1, self.s[-1])
        left, right = 1, len(self.s) - 1
        while left < right:
            mid = (left + right) >> 1
            if self.s[mid] >= x:
                right = mid
            else:
                left = mid + 1
        return left - 1

# Your Solution object will be instantiated and called as such:
# obj = Solution(w)
# param_1 = obj.pickIndices()
# Simplytest
```

```
import random
import bisect

class Solution:
    def __init__(self, w):
        # self prefix sums array.
        self.prefix_sums = [1]
        current_sum = 0
        for weight in w:
            current_sum += weight
            self.prefix_sums.append(current_sum)
        # Store the total sum of weights.
        self.total_sum = current_sum

    def pickIndex(self):
        # Get a random target in the range [1, total_sum].
        target = random.randint(1, self.total_sum)
        # Use bisect_left to find the proper index.
        index = bisect.bisect_left(self.prefix_sums, target)
        return index

# Example usage:
# solution = Solution([1, 3])
# print(solution.pickIndex())
```

```
class Solution:
    def __init__(self, w: List[int]):
        self.s = {}
        for c in w:
            self.s.append(self.s[c-1] + c)

    def pickIndex(self) -> int:
        a = random.randint(1, self.s[-1])
        left, right = 1, len(self.s) - 1
        while left < right:
            mid = (left + right) // 2
            if self.s[mid] >= a:
                right = mid
            else:
                left = mid + 1
        return left - 1

# Your Solution object will be instantiated and called
such as:
s = obj.Solution(w)

# param_1 = obj.pickIndex()
```

Binary Search

#52 Peak Index in a Mountain Array

WED

LeetCode - SimplyEet - WalkCC - LeetCode

ray - Binary Search

Tags: Denisy Zhang

Time Complexity: $O(\log(n))$ - The binary search procedure reduces the search interval by half at each step. Space Complexity: $O(1)$ - Only constant extra space is used.

Problem

You are given an integer mountain array arr of length n where values increase to a peak element and then decrease.

Return the index of the peak element.

Your task is to solve it in $O(\log(n))$ time complexity.

Example 1:

```
input arr = [0,1,0]
output: 1
```

Example 2:

```
input arr = [0,2,0,1,0]
output: 1
```

Example 3:

```
input arr = [10,10,5,2]
output: 1
```


Even length: split into two equal halves.
Odd length: divide into two halves of equal size, ignoring middle element.
Compare left half (left, mid-1) with right half (mid, right)
comp = reader.compareSub(left, mid - 1, mid, right)
if comp == 1:
Large integer is in the left half
else:
Large integer is in the right half
left = mid
else:
Odd length: divide into two halves of equal size, ignoring middle element.
Compare left half (left, left+half-1) with right half (right-half+1, right)
comp = reader.compareSub(left, left + half - 1, right - half + 1, right)
if comp == 1:
Large integer in left half
left = left + half - 1
elif comp == -1:
Large integer in right half

Round 2 · High · Medium

p.721

Left = right - half + 1
else:
Halves are equal, so the middle element is the large one
return left + half
return left
+LCa
This is ArrayReader's API interface.
You should not implement it, or speculate about its implementation
class ArrayReader(object):
Compares the sum of arr[left..right] with the sum of arr[i..j].
Returns 1 if sum(arr[left..right]) > sum(arr[i..j]),
returns 0 if sum(arr[left..right]) == sum(arr[i..j]),
returns -1 if sum(arr[left..right]) < sum(arr[i..j]).
def compareSub(self, left: int, right: int, i: int, j: int) -> int:

Round 2 · High · Medium

p.722

Returns the length of the array
def length(self) -> int:
class Solution:
def getIndices(self, reader: 'ArrayReader') -> int:
left, right = 0, reader.length() - 1
while left < right:
t1, t2, t3 = (
left,
left + (right - left) // 3,
left + ((right - left) // 3) * 2 + 1
)
if comp == 1:
left = t1
elif comp == -1:
right = t2
else:
left, right = t2 + 1, t3
return left

Round 2 · High · Medium

p.723

Matrix
Round 2 · High · Medium · 14 questions

Round 2 · High · Medium

p.724

#36 Valid Sudoku
LeetCode · SimplexLeet · WalkCC · LeetCode
Array · Hash Table · Matrix
Lists: Grid 169
Time Complexity: O(1) - Since the board size is fixed at 9x9, Space Complexity: O(1) - The extra space used by the sets is bounded by the fixed board size.
Problem
Determine if a 9 x 9 Sudoku board is valid. Only the filled cells need to be validated according to the following rules:
1. Each row must contain the digits 1-9 without repetition.
2. Each column must contain the digits 1-9 without repetition.
3. Each of the nine 3 x 3 sub-boxes of the grid must contain the digits 1-9 without repetition.
Note:
• A Sudoku board (partially filled) could be valid but is not necessarily solvable.
• Only the filled cells need to be validated according to the mentioned rules.
Example 1:

Round 2 · High · Medium

p.725

Input: board =
[[["5","3",".", ".", ".", ".", ".", ".", ".", "."],
[".", "9","8",".", ".", ".", ".", ".", ".", "."],
[".", "6",".", "6",".", ".", ".", ".", ".", "."],
["7",".", "4","8",".", "3",".", ".", ".", "."],
[".", "6",".", "2",".", ".", ".", ".", ".", "."],
[".", "4","1","9",".", ".", ".", ".", ".", "."],
[".", "8",".", "7",".", ".", ".", ".", ".", "."],
[".", "2",".", ".", ".", ".", ".", ".", ".", "."],
[".", "1",".", "6",".", ".", ".", ".", ".", "."]]
Constraints:
• board.length == 9
• board[i].length == 9
• board[i][j] is a digit 1-9 or '.'
Brute Force (Python)
Brute Force Approach
class Solution:
def isValidSudoku(self, board):
Brute Force O(81) - Check each row, col, box for duplicates
rows = [set() for _ in range(9)]
cols = [set() for _ in range(9)]
boxes = [set() for _ in range(9)]
for i in range(9):
for j in range(9):
c = board[i][j]
if c == '.':
continue
if (c == 'row' + i) in seen or
(c == 'col' + j) in seen or
(c == 'box' + i // 3 * 3 + j // 3 * 3) in seen:
return False
seen.add(c + 'row' + i)
seen.add(c + 'col' + j)
seen.add(c + 'box' + i // 3 * 3 + j // 3 * 3)
return True

Round 2 · High · Medium

p.726

Input: board =
[[["5","3",".", ".", ".", ".", ".", ".", ".", "."],
[".", "9","8",".", ".", ".", ".", ".", ".", "."],
[".", "6",".", "6",".", ".", ".", ".", ".", "."],
["7",".", "4","8",".", "3",".", ".", ".", "."],
[".", "6",".", "2",".", ".", ".", ".", ".", "."],
[".", "4","1","9",".", ".", ".", ".", ".", "."],
[".", "8",".", "7",".", ".", ".", ".", ".", "."],
[".", "2",".", ".", ".", ".", ".", ".", ".", "."],
[".", "1",".", "6",".", ".", ".", ".", ".", "."]]
Constraints:
• board.length == 9
• board[i].length == 9
• board[i][j] is a digit 1-9 or '.'
Brute Force (Python)
Brute Force Approach
class Solution:
def isValidSudoku(self, board):
Brute Force O(81) - Check each row, col, box for duplicates
rows = [set() for _ in range(9)]
cols = [set() for _ in range(9)]
boxes = [set() for _ in range(9)]
for i in range(9):
for j in range(9):
c = board[i][j]
if c == '.':
continue
if (c == 'row' + i) in seen or
(c == 'col' + j) in seen or
(c == 'box' + i // 3 * 3 + j // 3 * 3) in seen:
return False
seen.add(c + 'row' + i)
seen.add(c + 'col' + j)
seen.add(c + 'box' + i // 3 * 3 + j // 3 * 3)
return True

Round 2 · High · Medium

p.727

Community Solutions (Python)
• WalkCC
class Solution:
def isValidSudoku(self, board: List[List[str]]) -> bool:
seen = set()
for i in range(9):
for j in range(9):
c = board[i][j]
if c == '.':
continue
if (c == 'row' + i) in seen or
(c == 'col' + j) in seen or
(c == 'box' + i // 3 * 3 + j // 3 * 3) in seen:
return False
seen.add(c + 'row' + i)
seen.add(c + 'col' + j)
seen.add(c + 'box' + i // 3 * 3 + j // 3 * 3)
return True

Round 2 · High · Medium

p.728

C = '0x' + str(i) in seen or
(C == '0x' + str(j) + 3) + str(i) // 3) in seen:
return False
seen.add(C + 'row' + i)
seen.add(C + 'col' + j)
seen.add(C + 'box' + i // 3 * 3 + j // 3 * 3)
return True

Round 2 · High · Medium

p.729

num = list(c) - 1
k = i // 3 * 3 + j // 3
if row[i][num] or col[j][num] or
sub[k][num]:
return False
row[i][num] = True
col[j][num] = True
sub[k][num] = True
return True

Round 2 · High · Medium

p.730

num = board[r][c]
Skip empty cells
if num == '.':
continue
Compute box index using integer
box_index = (r // 3) * 3 + (c // 3)
Check if the number is already present in the row, column, or box
if num in row(r) or num in col(c) or
num in boxes[box_index]:
return False
Add number to row, column, and box
row[r].add(num)
col[c].add(num)
boxes[box_index].add(num)
return True
Example usage:
if __name__ == '__main__':
board =
["5","3",".", ".", ".", ".", ".", ".", ".", "."],
[".", "9","8",".", ".", ".", ".", ".", ".", "."],
[".", "6",".", "6",".", ".", ".", ".", ".", "."],
["7",".", "4","8",".", "3",".", ".", ".", "."],
[".", "6",".", "2",".", ".", ".", ".", ".", "."],
[".", "4","1","9",".", ".", ".", ".", ".", "."],
[".", "8",".", "7",".", ".", ".", ".", ".", "."],
[".", "2",".", ".", ".", ".", ".", ".", ".", "."],
[".", "1",".", "6",".", ".", ".", ".", ".", "."]

Round 2 · High · Medium

p.731

class Solution:
def isValidSudoku(self, board: List[List[str]]) -> bool:
row = [[False] * 9 for _ in range(9)]
col = [[False] * 9 for _ in range(9)]
sub = [[False] * 9 for _ in range(9)]
for i in range(9):
for j in range(9):
if board[i][j] != '.':
if row[i][int(board[i][j]) - 1] or
col[j][int(board[i][j]) - 1] or
sub[(i // 3) * 3 + j // 3][int(board[i][j]) - 1]:
return False
row[i][int(board[i][j]) - 1] = True
col[j][int(board[i][j]) - 1] = True
sub[(i // 3) * 3 + j // 3][int(board[i][j]) - 1] = True
return True

Round 2 · High · Medium

p.732

Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Example 2:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Problem
You are given an n x n 2D matrix representing an image, rotate the image by 90 degrees (clockwise).
You have to rotate the image in-place, which means you have to modify the input 2D matrix directly. DO NOT allocate another 2D matrix and do the rotation.
Example 1:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Constraints:
• n == matrix.length == matrix[0].length
• 1 <= n <= 20
• -1000 <= matrix[i][j] <= 1000
Brute Force (Python)
class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.733

Matrix
#48 Rotate Image
LeetCode · SimplexLeet · WalkCC · LeetCode
Array · Math · Matrix
Lists: Grid 169 | CodeSignal
Time Complexity: O(n^2) Since every element is processed during the transpose and row reversal. Space Complexity: O(1) as the operations are performed in-place without extra data structures.
Problem
You are given an n x n 2D matrix representing an image, rotate the image by 90 degrees (clockwise).
You have to rotate the image in-place, which means you have to modify the input 2D matrix directly. DO NOT allocate another 2D matrix and do the rotation.
Example 1:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Constraints:
• n == matrix.length == matrix[0].length
• 1 <= n <= 20
• -1000 <= matrix[i][j] <= 1000
Brute Force (Python)
class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.734

Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Example 2:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [[7,4,1],[8,5,2],[9,6,3]]
Constraints:
• n == matrix.length == matrix[0].length
• 1 <= n <= 20
• -1000 <= matrix[i][j] <= 1000
Brute Force (Python)
class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.735

Brute Force Approach
class Solution:
def rotate(self, matrix):
Brute Force O(n^2) space - copy to new matrix with rotated indices
n = len(matrix)
copy = [row[:] for row in matrix]
for i in range(n):
for j in range(n):
matrix[i][n-1-j] = copy[j][i]
Community Solutions (Python)
• WalkCC
class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.736

class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.737

def rotate(matrix):
n = len(matrix)
Transpose the matrix by swapping elements across the diagonal
for i in range(n):
for j in range(i, n):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]
Reverse each row to complete the clockwise rotation
for i in range(n):
matrix[i].reverse()
Example usage:
matrix = [[1,2,3],[4,5,6],[7,8,9]]
rotate(matrix)
print(matrix) # Outputs: [[7,4,1],[8,5,2],[9,6,3]]
+LCa
class Solution(object):
def rotate(self, matrix):
type: List[List[int]]
type: void Do not return anything, modify matrix in-place instead.
n = len(matrix)
for i in range(n):
for j in range(i, n):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]
for i in range(n):
matrix[i].reverse()
return
h = len(matrix)
w = len(matrix[0])
n = len(matrix[0])
m = len(matrix)

Round 2 · High · Medium

p.738

for i in range(8, h): # mirror
for j in range(0, w // 2):
matrix[i][j], matrix[i][w - j - 1] = matrix[i][w - j - 1], matrix[i][j]
for i in range(0, h): # transpose
for j in range(0, w - 1 - i):
matrix[i][j], matrix[w - 1 - j][h - 1 - i] = matrix[w - 1 - j][h - 1 - i], matrix[i][j]

class Solution:
def rotate(self, matrix: List[List[int]]) -> None:
n = len(matrix)
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[n - 1 - j][i] = matrix[n - 1 - j][i], matrix[i][j]
for i in range(n // 2):
for j in range(i, n - 1 - i):
matrix[i][j], matrix[j][i] = matrix[j][i], matrix[i][j]

Round 2 · High · Medium

p.739

Matrix
#54 Spiral Matrix
LeetCode · SimplexLeet · WalkCC · LeetCode
Array · Matrix · Simulation
Lists: Grid 169 | CodeSignal
Time Complexity: O(n^2) since each element is visited exactly once. Space Complexity: O(1) extra space (excluding the space required for the output list).
Problem
Given an n x n matrix, return all elements of the matrix in spiral order.
Example 1:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Example 2:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Constraints:
• n == matrix.length
• m == matrix[0].length
• 1 <= m, n <= 10
• -100 <= matrix[i][j] <= 100
Brute Force (Python)
class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.740

1 → 2 → 3
↓
4 → 5 → 6
↓
7 → 8 → 9
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Example 2:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Constraints:
• n == matrix.length
• m == matrix[0].length
• 1 <= m, n <= 10
• -100 <= matrix[i][j] <= 100
Brute Force (Python)
class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.741

1 → 2 → 3
↓
4 → 5 → 6
↓
7 → 8 → 9
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Example 2:
Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]
Output: [1,2,3,6,8,4,5,7]
Constraints:
• n == matrix.length
• m == matrix[0].length
• 1 <= m, n <= 10
• -100 <= matrix[i][j] <= 100
Brute Force (Python)
class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.742

Brute Force Approach
class Solution:
def spiralOrder(self, matrix):
Brute Force O(n^2) - Track visited cells, simulate turning
if not matrix: return []
n, m = len(matrix), len(matrix[0])
directions = [(0, 1), (1, 0), (0, -1), (-1, 0)]
right, down, left, up = 0, 0, 0, 0
visited = [[False] * m for _ in range(n)]
r, c = 0, 0
for _ in range(n * m):
result.append(matrix[r][c])
visited[r][c] = True
dr, dc = directions[directions.index(directions[r, c]) % 4]
nr, nc = r + dr, c + dc
if nr < 0 or nr >= n or nc < 0 or nc >= m or visited[nr][nc]:
directions = directions[directions.index(directions[r, c]) % 4 + 1] % 4
r, c = nr, nc
return result
Community Solutions (Python)
• WalkCC
class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.743

class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.744

while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c2])
i += 1
j += c2
while j >= c1 and len(ans) <= n * m:
ans.append(matrix[r1][j])
j -= 1
while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c1])
i -= 1
r1 += 1
c1 -= 1
c2 += 1
return ans
+LeetCode
class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.745

class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.746

def spiralOrder(matrix):
Initialize the boundaries of the matrix
top, bottom = 0, len(matrix) - 1
left, right = 0, len(matrix[0]) - 1
result = []
This will store the spiral order
Loop until the pointers cross each other
while top <= bottom and left <= right:
Traverse from left to right on the current top row
for i in range(left, right + 1):
result.append(matrix[top][i])
top += 1
Traverse from top to bottom on the current right column
for i in range(top, bottom + 1):
result.append(matrix[i][right])
right -= 1
Traverse from right to left on the current bottom row
if top <= bottom:
for i in range(right, left - 1, -1):
result.append(matrix[bottom][i])
bottom -= 1
Traverse from bottom to top on the current left column
if left <= right:
for i in range(bottom, top - 1, -1):
result.append(matrix[i][left])
left += 1
return result

Round 2 · High · Medium

p.747

for col in range(right, left - 1, -1):
result.append(matrix[bottom][col])
bottom -= 1
Move the bottom boundary
Traverse upwards on the current left column, if valid
if left <= right:
for row in range(bottom, top - 1, -1):
result.append(matrix[row][left])
left -= 1
Move the left boundary
return result
Example usage:
print(spiralOrder([[1,2,3],[4,5,6],[7,8,9]]))
+LCa
class Solution:
def spiralOrder(self, matrix: List[List[int]]) -> List[int]:
n = len(matrix)
m = len(matrix[0])
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * m for _ in range(n)]
i = j = k = 0
ans = []
for _ in range(n * m):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= m or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.748

x, y = i + dirs[k], j + dirs[k + 1]
if not 0 <= x < n or not 0 <= y < n or
(x, y) in vis:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.749

Matrix
#59 Spiral Matrix II
LeetCode · SimplexLeet · WalkCC · LeetCode
Array · Matrix · Simulation
Lists: CodeSignal
Time Complexity: O(n^2) Space Complexity: O(n^2) (required for the output matrix)
Problem
Given a positive integer n, generate an n x n matrix filled with elements from 1 to n^2 in spiral order.
Example 1:
Input: n = 3
Output: [[1,2,3],[4,5,6],[7,8,9]]
Example 2:
Input: n = 1
Output: [[1]]
Constraints:
• 1 <= n <= 20
Brute Force (Python)
class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.750

while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c2])
i += 1
j += c2
while j >= c1 and len(ans) <= n * m:
ans.append(matrix[r1][j])
j -= 1
while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c1])
i -= 1
r1 += 1
c1 -= 1
c2 += 1
return ans
+LeetCode
class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.751

class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.752

def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.753

class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.754

Continue the loop until the boundaries are valid
while top <= bottom and left <= right:
Traverse from left to right along the top row
for i in range(left, right + 1):
matrix[top][i] += num
num += 1
top += 1
Traverse from top to bottom along the right column
for i in range(top, bottom + 1):
matrix[i][right] += num
num += 1
right -= 1
Traverse from right to left along the bottom row
if top <= bottom:
for i in range(right, left - 1, -1):
matrix[bottom][i] += num
num += 1
bottom -= 1
Traverse from bottom to top along the left column
if left <= right:
for i in range(bottom, top - 1, -1):
matrix[i][left] += num
num += 1
left += 1
return matrix
Example usage:
print(generateMatrix(3))
+LCa
class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.755

class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans

Round 2 · High · Medium

p.756

while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c2])
i += 1
j += c2
while j >= c1 and len(ans) <= n * m:
ans.append(matrix[r1][j])
j -= 1
while i <= r2 - 1 and len(ans) <= n * m:
ans.append(matrix[i][c1])
i -= 1
r1 += 1
c1 -= 1
c2 += 1
return ans
+LeetCode
class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet

Round 2 · High · Medium

p.757

class Solution:
def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >= n or y < 0 or y >= n or vis[x][y]:
k = (k + 1) % 4
i = j + dirs[k]
return ans
+SimplyLeet




Round 2 · High · Medium

p.758

def generateMatrix(self, n: int) -> List[List[int]]:
ans = [[0] * n for _ in range(n)]
dirs = [(0, 1), (1, 0), (0, -1), (-1, 0)]
vis = [[False] * n for _ in range(n)]
i = j = k = 0
for _ in range(n * n):
ans.append(matrix[i][j])
vis[i][j] = True
x, y = i + dirs[k], j + dirs[k + 1]
if x < 0 or x >

[illegible]

Sheet 25/87 LeetMastery Study-Order #897 36-up Portrait 8x6

 <pre> Input: root = [1,null,3,2,4,null,null,5] Output: 3 Explanation: Longest consecutive sequence path is 1->2->3, so return 3. Example 2: </pre>	<pre> Input: root = [2,null,3,2,null,1] Output: 2 Explanation: Longest consecutive sequence path is 2->3, not 3->2, so return 2. Constraints: • The number of nodes in the tree is in the range [1, 3 * 10^4]. • -104 <= Node.val <= 3 * 10^4 Community Solutions (Python) </pre>	<pre> • WalKCC class Solution: def longestConsecutive(self, root: TreeNode None) -> int: if not root: return 0 def dfs(root: TreeNode None, target: int, length: int, maxlength: int) -> int: if not root: return maxlength if root.val == target: length += 1 else: length = 1 return max(dfs(root.left, root.val + 1, length, maxlength), dfs(root.right, root.val + 1, length, maxlength)) return dfs(root, root.val, 0, 0) • LeetDoocs </pre>	<pre> • Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def longestConsecutive(self, root: Optional[TreeNode]) -> int: if root is None: return 0 l = dfs(root.left) + 1 r = dfs(root.right) + 1 if root.left and root.left.val == root.val + 1: l = 1 if root.right and root.right.val == root.val + 1: t = max(l, r) ans = max(ans, t) return t ans = 0 dfs(root) return ans </pre>	<pre> return t ans = 0 dfs(root) return ans • SimplyLeet # Definition for a binary tree node. class TreeNode: def __init__(self, val=0, left=None, right=None): self.val = val self.left = left self.right = right class Solution: def longestConsecutive(self, root: TreeNode) -> int: # Initialize a variable to keep track of the maximum sequence length. </pre>	<pre> self.max_length = 0 # Helper function to perform DFS traversal. def dfs(node, parent_val, current_length): if not node: return # Check if the current node's value is consecutive. if node.val == parent_val + 1: current_length += 1 else: current_length = 1 # Update the maximum sequence length found so far. self.max_length = max(self.max_length, current_length) # Recursively traverse the left and right children. dfs(node.left, node.val, current_length) dfs(node.right, node.val, current_length) # Start DFS with an initial condition that forces the first node to count. dfs(root, root.val - 1, 0) return self.max_length • LC.ca </pre>
<pre> # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right # dfs class Solution: def longestConsecutive(self, root: TreeNode) -> int: maxlen = 0 # curLen: consecutive length until parent node def dfs(root: TreeNode, lastVal: int, curLen: int) -> None: if not root: return curLen = (curLen + 1) if (not lastVal) and root.val == lastVal + 1 else 1 maxlen = max(maxLen, curLen) </pre>	<pre> dfs(root.left, root.val, curLen) dfs(root.right, root.val, curLen) dfs(root, None, 0) return maxlen ##### # Definition for a binary tree node. # class TreeNode(object): # def __init__(self, x): # self.val = x # self.left = None # self.right = None from collections import deque # iterative, bfs class Solution: </pre>	<pre> def longestConsecutive(self, root: TreeNode) -> int: if not root: return 0 max_length = 0 # Queue elements are tuples: (current node, length of consecutive sequence) queue = deque([(root, 1)]) while queue: current, length = queue.popleft() max_length = max(max_length, length) for neighbor in (current.left, current.right): if neighbor: # Check if neighbor is consecutive if neighbor.val == current.val + 1: length += 1 else: length = 1 queue.append((neighbor, length)) return max_length </pre>	<pre> return max_length ##### class Solution: def longestConsecutive(self, root: Optional[TreeNode]) -> int: if root is None: return 0 l = dfs(root.left) + 1 r = dfs(root.right) + 1 if root.left and root.left.val == root.val + 1: l = 1 if root.right and root.right.val == root.val + 1: t = 1 t = max(l, r) ans = max(ans, t) return t ans = 0 dfs(root) return ans </pre>	Trees & BST #314 Binary Tree Vertical Order Traversal LeetDoocs - SimplyLeet - WalKCC - LeetCode Hash Table - Tree - BFS - Sorting Lists - Premium 98 Time Complexity: $O(n \log n)$ in the worst-case due to sorting the column indices (n nodes in the worst-case if each node is on a unique column). Space Complexity: $O(n)$ for storing the node information Problem Given the root of a binary tree, return the vertical order traversal of its nodes' values. (i.e., from top to bottom, column by column). If two nodes are in the same row and column, the order should be from left to right. Example 1:	 <pre> Input: root = [3,9,20,null,null,15,7] Output: [[1], [3, 15], [20], [7]] Example 2: </pre>
<pre> Input: root = [3,9,8,4,0,3,7] Output: [[4], [9], [3, 8, 1], [8], [7]] Example 3: </pre>	<pre> Input: root = [1,2,3,4,10,9,15,null,null,null,null,null,null,8] Output: [[4], [2, 5], [3, 10, 9, 6], [3], [13]] Constraints: • The number of nodes in the tree is in the range [0, 100]. • -100 <= Node.val <= 100 Brute Force (Python) </pre>	<pre> # Brute Force Approach class Solution: def verticalOrder(self, root: TreeNode) -> List[List[int]]: # Brute Force - collect inorder, then process sorted list vals = [] def collectNode(): if not node: return vals.append(node.val) collectNode(node.left) collectNode(node.right) collect(root) return vals[0] if vals else 0 Community Solutions (Python) • WalKCC class Solution: def verticalOrder(self, root: TreeNode None) -> List[List[int]]: if not root: return [] range_ = [0] * 2 def getRange(root: TreeNode None, x: int) -> None: if not root: return </pre>	<pre> range[0] = min(range[0], x) range[1] = max(range[1], x) def dfs(root: Optional[TreeNode]) -> int: if root is None: return 0 l = dfs(root.left) + 1 r = dfs(root.right) + 1 if root.left and root.left.val == root.val + 1: l = 1 if root.right and root.right.val == root.val + 1: t = 1 t = max(l, r) ans = max(ans, t) return t ans = 0 dfs(root) return ans • LeetDoocs </pre>	<pre> # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def verticalOrder(self, root: Optional[TreeNode]) -> List[List[int]]: def dfs(root, depth, offset): if root is None: return return dfs(root.left, depth + 1, offset - 1) dfs(root.right, depth + 1, offset + 1) d = defaultdict(list) dfs(root, 0, 0) for _, v in sorted(d.items()): v.sort(key=lambda x: x[0]) ans.append([x[1] for x in v]) return ans • SimplyLeet </pre>	<pre> from collections import deque, defaultdict # Definition for a binary tree node. # class TreeNode: # def __init__(self, x): # self.val = x # self.left = None # self.right = None class Solution: def verticalOrder(self, root: TreeNode) -> List[List[int]]: # Return empty list if the tree is empty if not root: return [] # Dictionary to hold nodes for each column index col_table = defaultdict(list) # Use deque for efficient FIFO queue for BFS; store tuple (node, column) queue = deque([(root, 0)]) </pre>
<pre> while queue: node, col = queue.popleft() # Append current node value to the list of its column col_table[col].append(node.val) # If there is a left child, assign column col-1 if node.left: queue.append((node.left, col - 1)) # If there is a right child, assign column col+1 if node.right: queue.append((node.right, col + 1)) # Extract the columns in sorted order to build the final result sorted_cols = sorted(col_table.keys()) result = [col_table[col] for col in sorted_cols] return result • LC.ca </pre>	<pre> # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right ''' >>> d = {} >>> d['a'] = '10'; d['b'] = '10'; d['c'] = '10'; d['d'] = '10' >>> d = sorted(d.items()) >>> ds = [(('a', '10'), ('b', '10'), ('c', '10'), ('d', '10'))] >>> sorted(ds.items(), key=lambda l: l[1]) >>> dict(sorted(ds.items(), key=lambda l: l[1])) ''' </pre>	<pre> [('a', '10', 'c'), ('b', '10', 'd'), ('c', '10', 'a'), ('d', '10', 'b')] ''' >>> [('a', '10', 'c'), ('b', '10', 'd'), ('c', '10', 'a'), ('d', '10', 'b')] >>> ds = sorted(d.items()) >>> ds = [(('a', '10'), ('b', '10'), ('c', '10'), ('d', '10'))] >>> sorted(ds.items(), key=lambda l: l[1]) >>> dict(sorted(ds.items(), key=lambda l: l[1])) ''' </pre>	<pre> return [v for _, v in sorted(d.items())] ##### from sortedcontainers import SortedDict from typing import Dict from collections import deque # similar to above, but use existing data structure class Solution: def verticalOrder(self, root: TreeNode) -> List[List[int]]: if not root: return [] # Use SortedDict to automatically sort by column index sorted_dict = SortedDict() # Queue for breadth-first search; stores pairs of (node, column) queue = deque([(root, 0)]) </pre>	<pre> while queue: node, column = queue.popleft() # Append current node value to the list of its column col_table[column].append(node.val) # If there is a left child, assign column col-1 if node.left: queue.append((node.left, column - 1)) # If there is a right child, assign column col+1 if node.right: queue.append((node.right, column + 1)) # Return the values from sorted_dict as a list of lists result = [col_table[col] for col in sorted(col_table.keys())] return result # another SortedDict, but different handling on None node, before enqueue vs after enqueue </pre>	<pre> class Solution: def verticalOrder(self, root: TreeNode) -> List[List[int]]: if not root: return [] # Initialize a SortedDict to maintain columns in sorted order column_table = SortedDict() queue = deque([(root, 0)]) # (node, column_index) while queue: node, column = queue.popleft() if node is not None: if column not in column_table: column_table[column] = [] column_table[column].append(node.val) # Add left and right children to the queue. queue.append((node.left, column - 1)) queue.append((node.right, column + 1)) </pre>
<pre> # Extract the values from the sorted dictionary and return them. return List(column_table.values()) ##### from collections import defaultdict class Solution(object): def verticalOrder(self, root: Optional[TreeNode]) -> List[List[int]]: # type: TreeNode -> List[List[int]] def dfs(i, j, res): if i == 0: res.append((i.val, j)) if i.left: dfs(i.left, j-1, res) if i.right: dfs(i.right, j+1, res) </pre>	<pre> self.leftMost = min(j, self.leftMost) dfs(i.left, i + 1, j - 1, res) dfs(i.right, i + 1, j + 1, res) self.leftMost = float("inf") ans = [] res = defaultdict(list) dfs(root, 0, 0, res) i = self.leftMost while True: if not res[i]: break ans.append([item[0] for item in sorted(res[i], key=lambda a: a[1])]) i += 1 return ans </pre>	Trees & BST #333 Largest BST Subtree LeetDoocs - SimplyLeet - WalKCC - LeetCode Dynamic Programming - Tree - DFS - BST Lists - Premium 98 Time Complexity: $O(n)$ (each node is visited once) Space Complexity: $O(n)$, where n is the height of the tree (due to recursion stack) Problem Given the root of a binary tree, find the largest subtree, which is also a Binary Search Tree (BST), where the largest means subtree has the largest number of nodes. A Binary Search Tree (BST) is a tree in which all the nodes follow the below-mentioned properties: - The left subtree values are less than the value of their parent (root) node's value. - The right subtree values are greater than the value of their parent (root) node's value. Note: A subtree must include all of its descendants. Example 1:	 <pre> Input: root = [10,5,15,3,7,null,8,12] Output: 3 Explanation: The Largest BST Subtree in this case is the highlighted one. The return value is the subtree's size, which is 3. Example 2: </pre>	<pre> class Solution: def largestBSTSubtree(self, root: TreeNode None) -> int: def dfs(root: TreeNode None) -> Tuple[int, bool]: if not root: return 0, True l = dfs(root.left) r = dfs(root.right) if l[0] < root.val < r[0]: return l[1] + 1, True else: return max(l[1], r[1]), False return dfs(root)[0] # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: Optional[TreeNode]) -> int: def dfs(root): if not root: return 0 l = dfs(root.left) r = dfs(root.right) if l[0] < root.val < r[0]: return l[1] + 1, True else: return max(l[1], r[1]), False return dfs(root)[0] </pre>	<pre> return (min(l.mx, root.val), max(r.mx, root.val, 1 + l.size + r.size)) # Mark one as invalid, but still record the size of children. # Return (-inf, -inf) because no node will be > inf or <= -inf. return (-math.inf, math.inf, max(l.size, r.size)) return dfs(root).size • LeetDoocs # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: Optional[TreeNode]) -> int: def dfs(root): if not root: return 0 l = dfs(root.left) r = dfs(root.right) if l[0] < root.val < r[0]: return l[1] + 1, True else: return max(l[1], r[1]), False return dfs(root)[0] </pre>
<pre> return inf, -inf, 0 lval, lmx, lrm = dfs(root.left) rval, rmx, rrm = dfs(root.right) nval, nrm, nrn = dfs(root) if lrm < root.val < rrm: ans = max(ans, lrm + nrn + 1) return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 else: return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 ans = 0 dfs(root) return ans • SimplyLeet # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: TreeNode) -> int: # Global variable to store the size of the largest BST subtree found. </pre>	<pre> self.max_bst_size = 0 def helper(node): # Returns a tuple of (isBST, size, min_val, max_val) if not node: return True, 0, float("inf"), float("-inf") # An empty node is considered a BST of size 0 with extreme min and max values. if not node: return True, 0, float("inf"), float("-inf") left_is_bst, left_size, left_min, left_max = helper(node.left) right_is_bst, right_size, right_min, right_max = helper(node.right) # Check if the current node forms a BST with its left and right subtrees. if left_is_bst and right_is_bst and node.val > left_max and node.val < right_min: current_size = left_size + right_size + 1 self.max_bst_size = max(self.max_bst_size, current_size) return True, current_size, min(left_min, right_min), max(right_max, left_max) else: # Not a BST: Return false and the size of the largest BST found so far in its subtrees. return False, max(left_size, right_size), 0, 0 helper(root) return self.max_bst_size • LC.ca </pre>	<pre> ... >>> float("inf") inf >>> float("inf") + 1 inf >>> float("inf") == math.inf True ... # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: Optional[TreeNode]) -> int: def dfs(root): if not root: return inf, -inf, 0 </pre>	<pre> lval, lmx, lrm = dfs(root.left) rval, rmx, rrm = dfs(root.right) nval, nrm, nrn = dfs(root) if lrm < root.val < rrm: ans = max(ans, lrm + nrn + 1) return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 else: return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 ans = 0 dfs(root) return ans ##### # Definition for a binary tree node. # class TreeNode: # def __init__(self, x): </pre>	<pre> self.val = x self.left = None self.right = None class Solution(object): def largestBSTSubtree(self, root): # type: TreeNode -> int return self.helper(root) def helper(self, root): if not root: return 0, float("inf"), float("-inf") lval, lmx, lrm = self.helper(root.left) rval, rmx, rrm = self.helper(root.right) if lrm < root.val < rrm: return lval + 1, max(lmx, root.val), min(rval, root.val) else: return max(lval, rval), max(lmx, root.val), min(rval, root.val) </pre>	<pre> def helper(root): if not root: return 0, float("inf"), float("-inf") lval, lmx, lrm = self.helper(root.left) rval, rmx, rrm = self.helper(root.right) if lrm < root.val < rrm: return lval + 1, max(lmx, root.val), min(rval, root.val) else: return max(lval, rval), max(lmx, root.val), min(rval, root.val) </pre>
<pre> return inf, -inf, 0 lval, lmx, lrm = dfs(root.left) rval, rmx, rrm = dfs(root.right) nval, nrm, nrn = dfs(root) if lrm < root.val < rrm: ans = max(ans, lrm + nrn + 1) return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 else: return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 ans = 0 dfs(root) return ans • SimplyLeet # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: TreeNode) -> int: # Global variable to store the size of the largest BST subtree found. </pre>	<pre> self.max_bst_size = 0 def helper(node): # Returns a tuple of (isBST, size, min_val, max_val) if not node: return True, 0, float("inf"), float("-inf") # An empty node is considered a BST of size 0 with extreme min and max values. if not node: return True, 0, float("inf"), float("-inf") left_is_bst, left_size, left_min, left_max = helper(node.left) right_is_bst, right_size, right_min, right_max = helper(node.right) # Check if the current node forms a BST with its left and right subtrees. if left_is_bst and right_is_bst and node.val > left_max and node.val < right_min: current_size = left_size + right_size + 1 self.max_bst_size = max(self.max_bst_size, current_size) return True, current_size, min(left_min, right_min), max(right_max, left_max) else: # Not a BST: Return false and the size of the largest BST found so far in its subtrees. return False, max(left_size, right_size), 0, 0 helper(root) return self.max_bst_size • LC.ca </pre>	<pre> ... >>> float("inf") inf >>> float("inf") + 1 inf >>> float("inf") == math.inf True ... # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def largestBSTSubtree(self, root: Optional[TreeNode]) -> int: def dfs(root): if not root: return inf, -inf, 0 </pre>	<pre> lval, lmx, lrm = dfs(root.left) rval, rmx, rrm = dfs(root.right) nval, nrm, nrn = dfs(root) if lrm < root.val < rrm: ans = max(ans, lrm + nrn + 1) return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 else: return min(lval, root.val), max(rval, root.val), lrm + nrn + 1 ans = 0 dfs(root) return ans ##### # Definition for a binary tree node. # class TreeNode: # def __init__(self, x): </pre>	<pre> self.val = x self.left = None self.right = None class Solution(object): def largestBSTSubtree(self, root): # type: TreeNode -> int return self.helper(root) def helper(self, root): if not root: return 0, float("inf"), float("-inf") lval, lmx, lrm = self.helper(root.left) rval, rmx, rrm = self.helper(root.right) if lrm < root.val < rrm: return lval + 1, max(lmx, root.val), min(rval, root.val) else: return max(lval, rval), max(lmx, root.val), min(rval, root.val) </pre>	<pre> def helper(root): if not root: return 0, float("inf"), float("-inf") lval, lmx, lrm = self.helper(root.left) rval, rmx, rrm = self.helper(root.right) if lrm < root.val < rrm: return lval + 1, max(lmx, root.val), min(rval, root.val) else: return max(lval, rval), max(lmx, root.val), min(rval, root.val) </pre>

return numBST, max(numBST, min(left, min, root.val)), max(lmax, rmax, root.val)

return helper(root)[1]

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Tree -> DFS -> Sorting

Lists: Premium 98


Time Complexity: O(n) – Each node is visited exactly once. Space Complexity: O(n) – Space used for the recursion stack and the result list.

Problem

Given the root of a binary tree, collect a tree's nodes as if you were doing this:

- Collect all the leaf nodes.
- Remove all the leaf nodes.
- Repeat until the tree is empty.

Example 1:



Round 2 - High - Medium

p.373

Input: root = [1,2,3,4,5]
Output: [4,5,3,2,1,2,1]
Explanation:
[1,3,4,5],[2,1] and [1,3,4,5],[2,1,1] are also considered correct answers since per each level it does not matter the order on which elements are returned.

Example 2:
Input: root = [1]
Output: [1]

Constraints:

- The number of nodes in the tree is in the range [1, 100].
- 100 <= Node.val <= 100

Brute Force (Python)

Brute Force Approach
class Solution:
 def findLeaves(self, root: TreeNode):
 # Brute Force - collect in order, then process sorted list
 vals = []
 def collect(node):
 if not node: return
 collect(node.left)
 collect(node.right)
 vals.append(node.val)

Round 2 - High - Medium

p.374

collect(root)
return vals[0] if vals else 0

Community Solutions (Python)

WalkCC
class Solution:
 def findLeaves(self, root: TreeNode) -> List[int]:
 ans = []
 def depth(root: TreeNode) -> int:
 """Returns the depth of the root (0-indexed).
 if not root:
 return -1
 l = depth(root.left)
 r = depth(root.right)
 h = 1 + max(l, r)
 if len(ans) == h: # Meet a leaf
 ans.append(h)
 ans[h].append(root.val)
 depth(root)
 return h

Round 2 - High - Medium

p.375

return ans

LeetCode

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def findLeaves(self, root: Optional[TreeNode]) -> List[List[int]]:
 def dfs(root: Optional[TreeNode]) -> int:
 if root is None:
 return 0
 l, r = dfs(root.left), dfs(root.right)
 h = max(l, r)
 if len(ans) == h:
 ans.append(h)
 ans[h].append(root.val)
 return h + 1
 ans = []
 dfs(root)
 return ans

SimplifyLeet

Round 2 - High - Medium

p.376

Definition for a binary tree node.
class TreeNode:
 def __init__(self, val=0, left=None, right=None):
 self.val = val
 self.left = left
 self.right = right
class Solution:
 def findLeaves(self, root: TreeNode):
 result = []
 # This will store lists of nodes at each removal step.
 def getheight(node):
 # Base case: when the node is None.
 return 0
 if not node:
 return 0
 # Recursively find the height of left and right subtrees.
 left_height = getheight(node.left)
 right_height = getheight(node.right)
 # Current node's height is max of left/right heights plus one.
 current_height = max(left_height, right_height) + 1
 return current_height

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def pathSum(self, root: Optional[TreeNode], targetSum: int) -> List[List[int]]:
 def dfs(node, s):
 if node is None:
 return 0
 s += node.val
 ans = cnt[s] = targetSum
 cnt[s] += 1
 ans = dfs(node.left, s)
 ans = dfs(node.right, s)
 cnt[s] -= 1
 return ans
 cnt = Counter({0: 1})
 return dfs(root, 0)

SimplifyLeet

Round 2 - High - Medium

p.377

Ensure the result list has a sublist for the current height.
if len(result) < current_height:
 result.append([])
Append the current node value to the corresponding height bucket.
result[current_height].append(node.val)
return current_height
getheight(root) # Start recursion from the root.
return result

LeetCode

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def findLeaves(self, root: TreeNode) -> List[List[int]]:
 def dfs(root, prev, i):
 if root is None:
 return

Round 2 - High - Medium

p.378

return
if root.left is None and root.right is None:
 t.append(root.val)
if prev.left == root:
 prev.left = None
else:
 prev.right = None
dfs(root.left, root, t)
dfs(root.right, root, t)
res = []
prev = TreeNode(left=root)
while prev.left:
 t = []
 dfs(prev.left, prev, t)
 res.append(t)
 return res

LeetCode

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def findLeaves(self, root: TreeNode) -> List[List[int]]:
 def dfs(root, prev, i):
 if root is None:
 return

Round 2 - High - Medium

p.379

Tree & BST

#437 Path Sum III

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Tree -> DFS -> Prefix Sum


Lists: Grid 169

Time Complexity: O(n) on average (where n is the number of nodes), though worst-case can be O(n^2) in a skewed tree. Space Complexity: O(n) due to recursion stack and the hash map that stores prefix sums.

Problem

Given the root of a binary tree and an integer targetSum, return the number of paths where the sum of the values along the path equals targetSum. The path does not need to start or end at the root or a leaf, but it must go downwards (i.e., traveling only from parent nodes to child nodes).

Example 1:



Round 2 - High - Medium

p.380

Input: root = [10,5,3,2,null,11,3,-2,null,1], targetSum = 8
Output: 3
Explanation: The paths that sum to 8 are shown.

Example 2:
Input: root = [5,4,8,1,null,3,4,7,2,null,null,5,3], targetSum = 22
Output: 3

Constraints:

Round 2 - High - Medium

p.381

The number of nodes in the tree is in the range [0, 1000].
-100 <= Node.val <= 100
-1000 <= targetSum <= 1000

Community Solutions (Python)

WalkCC
class Solution:
 def pathSum(self, root: TreeNode, sum: int) -> List[List[int]]:
 if not root:
 return 0
 def dfs(root: TreeNode, sum: int) -> int:
 if not root:
 return 0
 return (sum == root.val + dfs(root.left, sum - root.val) + dfs(root.right, sum - root.val))
 return (sum == root.val + dfs(root.left, sum - root.val) + dfs(root.right, sum - root.val))

LeetCode

Round 2 - High - Medium

p.382

Definition for a binary tree node.
class TreeNode:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def pathSum(self, root: Optional[TreeNode], targetSum: int) -> List[List[int]]:
 def dfs(node, s):
 if node is None:
 return 0
 s += node.val
 ans = cnt[s] = targetSum
 cnt[s] += 1
 ans = dfs(node.left, s)
 ans = dfs(node.right, s)
 cnt[s] -= 1
 return ans
 cnt = Counter({0: 1})
 return dfs(root, 0)

SimplifyLeet

Round 2 - High - Medium

p.383

Python solution for Path Sum III
class Tree:
 def __init__(self, val=0, left=None, right=None):
 self.val = val
 self.left = left
 self.right = right
class Solution:
 def pathSum(self, root: Tree, targetSum: int) -> List[List[int]]:
 # Helper function to perform DFS traversal
 def dfs(node, current_sum, prefix_sums):
 if not node:
 return 0
 # Update current sum by including the current node's value
 current_sum += node.val
 # Check the number of times (current_sum - targetSum) has occurred
 prefix_sums.get(current_sum - targetSum, 0)
 # Update the prefix sum hash map with the current sum

LeetCode

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def pathSum(self, root: Tree, targetSum: int) -> List[List[int]]:
 # Helper function to perform DFS traversal
 def dfs(node, current_sum, prefix_sums):
 if not node:
 return 0
 # Update current sum by including the current node's value
 current_sum += node.val
 # Check the number of times (current_sum - targetSum) has occurred
 prefix_sums.get(current_sum - targetSum, 0)
 # Update the prefix sum hash map with the current sum

Round 2 - High - Medium

p.384

prefix_sums[current_sum] = prefix_sums.get(current_sum, 0) + 1
Recursively search the left and right subtree
num_paths += dfs(node.left, current_sum, prefix_sums)
num_paths += dfs(node.right, current_sum, prefix_sums)
Backtrack: remove the current sum count before returning to the parent node
prefix_sums[current_sum] -= 1
return num_paths
Initial prefix sum hashmap with 0 sum seen once (empty path)
prefix_sums = {0: 1}
return dfs(root, 0, prefix_sums)

LeetCode

Round 2 - High - Medium

p.385

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def pathSum(self, root: Tree, targetSum: int) -> List[List[int]]:
 def dfs(node, s):
 if node is None:
 return 0
 s += node.val
 ans = cnt[s] = targetSum
 cnt[s] += 1
 ans = dfs(node.left, s)
 ans = dfs(node.right, s)
 cnt[s] -= 1
 return ans
 cnt = Counter({0: 1})
 return dfs(root, 0)

LeetCode

Round 2 - High - Medium

p.386

Tree & BST

#545 Boundary of Binary Tree

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Tree -> DFS

Lists: Premium 98

Time Complexity: O(n) - Every node is visited at most once. Space Complexity: O(n) - O(n) space is used for the output list and recursion stack (in worst case tree is skewed).

Problem

The boundary of a binary tree is the concatenation of the root, the left boundary, the leaves ordered from left-to-right, and the reverse order of the right boundary. The left boundary is the set of nodes defined by the following:


- The root node's left child is in the left boundary. If the root does not have a left child, then the left boundary is empty.
- If a node is in the left boundary and has a left child, then the left child is in the left boundary.
- If a node is in the left boundary, has no left child, but has a right child, then the right child is in the left boundary.
- The leftmost leaf is in the left boundary.

Round 2 - High - Medium

p.387

The right boundary is similar to the left boundary, except it is the right side of the root's right subtree. Again, the leaf is not part of the right boundary, and the right boundary is empty if the root does not have a right child. The leaves are nodes that do not have any children. For this problem, the root is not a leaf. Given the root of a binary tree, return the values of its boundary.

Example 1:




Round 2 - High - Medium

p.388

Input: root = [1,2,3,4,5]
Output: [1,3,2]
Explanation:
- The left boundary is empty because the root does not have a left child.
- The left boundary follows the path starting from the root's right child 2 -> 4.
- 4 is a leaf, so the right boundary is [2].
- The leaves from left to right are [3,4].
- Concatenating everything results in [1] + [3,4] + [2] = [1,3,4,2].

Example 2:



Round 2 - High - Medium

p.389

Input: root = [1,2,2,4,5,6,null,null,7,8,9,10]
Output: [1,2,4,7,8,9,10,6,3]
Explanation:
- The left boundary follows the path starting from the root's left child 2 -> 4.
- 4 is a leaf, so the left boundary is [2].
- The right boundary follows the path starting from the root's right child 3 -> 6 -> 10.
- 10 is a leaf, so the right boundary is [3,6], and in reverse order is [6,3].
- The leaves from left to right are [4,7,8,9,10].

Constraints:

- The number of nodes in the tree is in the range [1, 100].
- 1000 <= Node.val <= 1000

Community Solutions (Python)

WalkCC

Round 2 - High - Medium

p.390

class Solution:
 def boundaryOfBinaryTree(self, root: TreeNode) -> List[int]:
 ans = []
 def dfs(root: TreeNode) -> List[int]:
 if not root:
 return []
 # The left boundary follows the path starting from the root's left child 2 -> 4.
 # The right boundary follows the path starting from the root's right child 3 -> 6 -> 10.
 # 10 is a leaf, so the right boundary is [3,6], and in reverse order is [6,3].
 # The leaves from left to right are [4,7,8,9,10].

Constraints:

- The number of nodes in the tree is in the range [1, 100].
- 1000 <= Node.val <= 1000

Community Solutions (Python)

WalkCC

Round 2 - High - Medium

p.391

if not lb and not rb and not root.left and not root.right:
 ans.append(root.val)
dfs(root.left, lb, rb and not root.right)
dfs(root.right, lb and not root.left, rb)
if rb:
 ans.append(root.val)
dfs(root.left, True, False)
dfs(root.right, False, True)
return ans

LeetCode

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Optional[TreeNode]) -> List[int]:
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.392

return
if i == 0:
 if not root.left: root.right:
 ans.append(root.val)
 if root.left:
 dfs(nums, root.left, i)
 else:
 dfs(nums, root.right, i)
elif i == 1:
 if root.left == root.right:
 ans.append(root.val)
 else:
 dfs(nums, root.left, i)
 dfs(nums, root.right, i)
else:
 if root.left == root.right:
 ans.append(root.val)
 if root.right:
 dfs(nums, root.right, i)
 else:
 dfs(nums, root.left, i)

LeetCode

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Optional[TreeNode]) -> List[int]:
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.393

dfs(nums, root.left, i)
ans = [root.val]
if root.left == root.right:
 return ans
left, leaves, right = [], [], []
dfs(root, root.left, 0)
dfs(root, root.right, 2)
ans = left + leaves + right[::-1]
return ans

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.394

return []
Check if a node is a leaf.
def isLeaf(node):
 return node and not node.left and not node.right
Add left boundary nodes (excluding leaves).
def addLeftBoundary(node, boundary):
 while node:
 if not isLeaf(node):
 boundary.append(node.val)
 # Prefer left child, if not present then right child.
 if node.left:
 node = node.left
 else:
 node = node.right
Add leaf nodes using DFS.
def addLeaves(node, leaves):
 if not node:
 return

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.395

return
if isLeaf(node):
 leaves.append(node.val)
else:
 addLeaves(node.left, leaves)
 addLeaves(node.right, leaves)
Add right boundary nodes in reverse order (excluding leaves).
def addRightBoundary(node, boundary):
 temp = []
 while node:
 if not isLeaf(node):
 temp.append(node.val)
 boundaryOfBinaryTree(root)
 node = node.right
 else:
 node = node.left
 # Append in reverse order.
 while temp:
 boundary.append(temp.pop())

LeetCode

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.396

boundary = []
Add root value if it is not a leaf.
if not isLeaf(root):
 boundary.append(root.val)
addLeftBoundary(root.left, boundary)
addLeaves(root, boundary)
addRightBoundary(root.right, boundary)
return boundary
Example usage:
Construct a binary tree and call boundaryOfBinaryTree(root)

LeetCode

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.397

return self.res
root
if not self.isLeaf(root):
 self.res.append(root.val)
left boundary
t = root.left
while t:
 if not self.isLeaf(t):
 self.res.append(t.val)
t = t.left if t.left else t.right
leaves
self.add_leaves(root)
right boundary (reverse order)
t = root.right
while t:
 if not self.isLeaf(t):
 self.res.append(t.val)
t = t.right if t.right else t.left

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.398

s.append(t.val)
t = t.right if t.right else t.left
while s:
 self.res.append(s.pop())
output
return self.res
def add_leaves(self, root):
 if self.isLeaf(root):
 self.res.append(t.val)
 return
if root.left:
 self.add_leaves(root.left)
if root.right:
 self.add_leaves(root.right)
def isLeaf(self, node) -> bool:
 return node and not node.left and not node.right is None

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def boundaryOfBinaryTree(self, root: Tree):
 ans = []
 def dfs(node, l: bool, r: bool):
 if not node:
 return
 if l:
 ans.append(root.val)

Round 2 - High - Medium

p.399

Tree & BST

#549 Binary Tree Longest Consecutive Sequence II

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Tree -> DFS


Lists: Premium 98

Time Complexity: O(n), where n is the number of nodes since every node is visited once. Space Complexity: O(h), where h is the height of the tree, due to the recursion stack.

Problem

Given the root of a binary tree, return the length of the longest consecutive path in the tree. A consecutive path is a path where the values of the consecutive nodes in the path differ by one. This path can be either increasing or decreasing. For example, [1,2,3,4] and [4,3,2,1] are both considered valid, but the path [1,2,4,3] is not valid. On the other hand, the path can be in the child-Parent-child order, where not necessarily be parent-child order.

Example 1:




Round 2 - High - Medium

p.400

Input: root = [1,2,3]
Output: 3
Explanation: The longest consecutive path is [1, 2] or [2, 3].

Example 2:



Round 2 - High - Medium

p.401

Input: root = [2,1,3]
Output: 3
Explanation: The longest consecutive path is [1, 2, 3] or [3, 2, 1].

Constraints:

- The number of nodes in the tree is in the range [1, 3 * 10^4].
- 3 * 10^4 <= Node.val <= 3 * 10^4

Community Solutions (Python)

Round 2 - High - Medium

p.402

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

Round 2 - High - Medium

p.403

if root.right:
 if root.right.val + 1 == root.val:
 inc = max(inc, l2 + 1)
 if root.right.val - 1 == root.val:
 dec = max(dec, d2 + 1)
 return (inc, dec)
ans = 0
dfs(root)
return ans

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

Round 2 - High - Medium

p.404

self.max_length = 0
def dfs(node):
 if not node:
 return 0, 0
 # Process left child
 l, inc, dec = dfs(node.left)
 # Process right child
 r, inc, dec = dfs(node.right)
 # Update global maximum path length
 self.max_length = max(self.max_length, l + inc, r + inc, l + dec, r + dec)

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

Round 2 - High - Medium

p.405

right_inc, right_dec = dfs(node.right)
If right child's value is consecutive increasing with respect to node
if node.right.val == node.val + 1:
 inc = max(inc, right_inc + 1)
If right child's value is consecutive decreasing with respect to node
if node.right.val == node.val - 1:
 dec = max(dec, right_dec + 1)
Update the global maximum path by combining increasing and decreasing paths
self.max_length = max(self.max_length, inc + dec - 1)
return (inc, dec)
dfs(root)
return self.max_length

LeetCode

Round 2 - High - Medium

p.406

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

SimplifyLeet

Definition for a binary tree node.
class Tree:
def __init__(self, val=0, left=None, right=None):
self.val = val
self.left = left
self.right = right
class Solution:
 def longestConsecutive(self, root: Tree):
 ans = 0
 def dfs(root):
 if not root:
 return 0
 nonlocal ans
 inc = dec = 1
 l, d1 = dfs(root.left)
 r, d2 = dfs(root.right)
 if root.left:
 if root.left.val + 1 == root.val:
 inc = l + 1
 if root.left.val - 1 == root.val:
 dec = d1 + 1

Round 2 - High - Medium

p.407

Round 2 - High - Medium

Round 2 - High - Medium

Round 2 - High - Medium

Round 2 - High - Medium

Round 2 - High - Medium

Round 2 - High - Medium

Round 2 High Medium p1113 Round 2 High Medium

Round 2 - High - Medium	p.1189	Round 2 - High - Medium	p.1190	Round 2 - High - Medium	p.1191	Round 2 - High - Medium	p.1192	Round 2 - High - Medium	p.1193	Round 2 - High - Medium	p.1194
-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------

Round 2 - High - Medium	p.1195	Round 2 - High - Medium	p.1196	Round 2 - High - Medium	p.1197	Round 2 - High - Medium	p.1198	Round 2 - High - Medium	p.1199	Round 2 - High - Medium	p.1200
-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------

Round 2 · High · Medium	p.1201	Round 2 · High · Medium	p.1202	Round 2 · High · Medium	p.1203	Round 2 · High · Medium	p.1204	Round 2 · High · Medium	p.1205	Round 2 · High · Medium	p.1206
-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------

Round 2 - High - Medium	a 1212	Round 2 - High - Medium	a 1214	Round 2 - High - Medium	a 1215	Round 2 - High - Medium	a 1216	Round 2 - High - Medium	a 1217	Round 2 - High - Medium	a 1218
-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------	-------------------------	--------

Round 2	Hfsh	Medfsh	n = 1210	Round 3	Hfsh	Medfsh	n = 1220	Round 4	Hfsh	Medfsh	n = 1230	Round 5	Hfsh	Medfsh	n = 1240	Round 6	Hfsh	Medfsh	n = 1250	Round 7	Hfsh	Medfsh	n = 1260	Round 8	Hfsh	Medfsh	n = 1270	Round 9	Hfsh	Medfsh	n = 1280	Round 10	Hfsh	Medfsh	n = 1290	Round 11	Hfsh	Medfsh	n = 1300	Round 12	Hfsh	Medfsh	n = 1310	Round 13	Hfsh	Medfsh	n = 1320	Round 14	Hfsh	Medfsh	n = 1330	Round 15	Hfsh	Medfsh	n = 1340	Round 16	Hfsh	Medfsh	n = 1350	Round 17	Hfsh	Medfsh	n = 1360	Round 18	Hfsh	Medfsh	n = 1370	Round 19	Hfsh	Medfsh	n = 1380	Round 20	Hfsh	Medfsh	n = 1390	Round 21	Hfsh	Medfsh	n = 1400	Round 22	Hfsh	Medfsh	n = 1410	Round 23	Hfsh	Medfsh	n = 1420	Round 24	Hfsh	Medfsh	n = 1430	Round 25	Hfsh	Medfsh	n = 1440	Round 26	Hfsh	Medfsh	n = 1450	Round 27	Hfsh	Medfsh	n = 1460	Round 28	Hfsh	Medfsh	n = 1470	Round 29	Hfsh	Medfsh	n = 1480	Round 30	Hfsh	Medfsh	n = 1490	Round 31	Hfsh	Medfsh	n = 1500	Round 32	Hfsh	Medfsh	n = 1510	Round 33	Hfsh	Medfsh	n = 1520	Round 34	Hfsh	Medfsh	n = 1530	Round 35	Hfsh	Medfsh	n = 1540	Round 36	Hfsh	Medfsh	n = 1550	Round 37	Hfsh	Medfsh	n = 1560	Round 38	Hfsh	Medfsh	n = 1570	Round 39	Hfsh	Medfsh	n = 1580	Round 40	Hfsh	Medfsh	n = 1590	Round 41	Hfsh	Medfsh	n = 1600	Round 42	Hfsh	Medfsh	n = 1610	Round 43	Hfsh	Medfsh	n = 1620	Round 44	Hfsh	Medfsh	n = 1630	Round 45	Hfsh	Medfsh	n = 1640	Round 46	Hfsh	Medfsh	n = 1650	Round 47	Hfsh	Medfsh	n = 1660	Round 48	Hfsh	Medfsh	n = 1670	Round 49	Hfsh	Medfsh	n = 1680	Round 50	Hfsh	Medfsh	n = 1690	Round 51	Hfsh	Medfsh	n = 1700	Round 52	Hfsh	Medfsh	n = 1710	Round 53	Hfsh	Medfsh	n = 1720	Round 54	Hfsh	Medfsh	n = 1730	Round 55	Hfsh	Medfsh	n = 1740	Round 56	Hfsh	Medfsh	n = 1750	Round 57	Hfsh	Medfsh	n = 1760	Round 58	Hfsh	Medfsh	n = 1770	Round 59	Hfsh	Medfsh	n = 1780	Round 60	Hfsh	Medfsh	n = 1790	Round 61	Hfsh	Medfsh	n = 1800	Round 62	Hfsh	Medfsh	n = 1810	Round 63	Hfsh	Medfsh	n = 1820	Round 64	Hfsh	Medfsh	n = 1830	Round 65	Hfsh	Medfsh	n = 1840	Round 66	Hfsh	Medfsh	n = 1850	Round 67	Hfsh	Medfsh	n = 1860	Round 68	Hfsh	Medfsh	n = 1870	Round 69	Hfsh	Medfsh	n = 1880	Round 70	Hfsh	Medfsh	n = 1890	Round 71	Hfsh	Medfsh	n = 1900	Round 72	Hfsh	Medfsh	n = 1910	Round 73	Hfsh	Medfsh	n = 1920	Round 74	Hfsh	Medfsh	n = 1930	Round 75	Hfsh	Medfsh	n = 1940	Round 76	Hfsh	Medfsh	n = 1950	Round 77	Hfsh	Medfsh	n = 1960	Round 78	Hfsh	Medfsh	n = 1970	Round 79	Hfsh	Medfsh	n = 1980	Round 80	Hfsh	Medfsh	n = 1990	Round 81	Hfsh	Medfsh	n = 2000	Round 82	Hfsh	Medfsh	n = 2010	Round 83	Hfsh	Medfsh	n = 2020	Round 84	Hfsh	Medfsh	n = 2030	Round 85	Hfsh	Medfsh	n = 2040	Round 86	Hfsh	Medfsh	n = 2050	Round 87	Hfsh	Medfsh	n = 2060	Round 88	Hfsh	Medfsh	n = 2070	Round 89	Hfsh	Medfsh	n = 2080	Round 90	Hfsh	Medfsh	n = 2090	Round 91	Hfsh	Medfsh	n = 2100	Round 92	Hfsh	Medfsh	n = 2110	Round 93	Hfsh	Medfsh	n = 2120	Round 94	Hfsh	Medfsh	n = 2130	Round 95	Hfsh	Medfsh	n = 2140	Round 96	Hfsh	Medfsh	n = 2150	Round 97	Hfsh	Medfsh	n = 2160	Round 98	Hfsh	Medfsh	n = 2170	Round 99	Hfsh	Medfsh	n = 2180	Round 100	Hfsh	Medfsh	n = 2190	Round 101	Hfsh	Medfsh	n = 2200	Round 102	Hfsh	Medfsh	n = 2210	Round 103	Hfsh	Medfsh	n = 2220	Round 104	Hfsh	Medfsh	n = 2230	Round 105	Hfsh	Medfsh	n = 2240	Round 106	Hfsh	Medfsh	n = 2
---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	---------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	----------	-----------	------	--------	-------

1 2 3 Input: n = 3, relations = [[1,3],[2,3]] Output: 2 Explanation: The figure above represents the given graph In the first semester, you can take courses 1 and 2. In the second semester, you can take course 3. Example 2:	Round 2 · High · Medium p.1261	1 2 3 Input: n = 3, relations = [[1,2],[2,3],[3,1]] Output: -1 Explanation: No course can be studied because they are prerequisites of each other.	Round 2 · High · Medium p.1262	• All the pairs [prevCourse, nextCourse] are unique. Brute Force (Python)<pre># Brute Force Approach class Solution: def minimumSemesters(self, numCourses, relations): # Brute Force - try all paths via exhaustive DFS visited = set() def dfs(node): if node == dst: return True visited.add(node) for nxt in graph.get(node, []): if not visited and dfs(nxt): return True visited.remove(node) return False return dfs(src)</pre> Community Solutions (Python) • WalCC Round 2 · High · Medium p.1263	from enum import Enum class State(Enum): INIT = 0 VISITING = 1 VISITED = 2 class Solution: def minimumSemesters(self, n: int, relations: List[List[int]]) -> int: graph = [[] for _ in range(n)] states = [State.INIT] * n depth = [2] * n for u, v in relations: graph[u].append(v) depth[v] = 1 def hasCycle(u: int) -> bool: if states[u] == State.VISITING: return True if states[u] == State.VISITED: return False states[u] = State.VISITING for v in graph[u]: if hasCycle(v): return True states[u] = State.VISITED return False Round 2 · High · Medium p.1264	<pre>return True if states[u] == State.VISITING: return False states[u] = State.VISITING for v in graph[u]: return True depth[u] = max(depth[u], 1 + depth[v]) states[u] = State.VISITED return False if any(hasCycle(i) for i in range(n)): return -1 return max(depth)</pre> Round 2 · High · Medium p.1265	• Perform topological sorting. <pre>q = collections.deque([i for i, d in enumerate(inborders) if d == 0]) while q: step += 1 while q: for _ in range(len(q)): u = q.popleft() n -= 1 for v in graph[u]: inborders[v] -= 1 if inborders[i] == 0: q.append(v) step += 1 return step if n == 0 else -1</pre> • LeetCode Round 2 · High · Medium p.1266
<pre>class Solution: def minimumSemesters(self, n: int, relations: List[List[int]]) -> int: g = defaultdict(list) indeg = [0] * n for pre, next in relations: pre, next = prev - 1, next - 1 g[pre].append(next) indeg[next] += 1 q = deque([i for i, v in enumerate(indeg) if v == 0]) ans = 0 while q: ans += 1 for _ in range(len(q)): i = q.popleft() n -= 1 for j in g[i]: indeg[j] -= 1 if indeg[j] == 0: q.append(j) return -1 if n else ans</pre> • SimplyTest Round 2 · High · Medium p.1267	• Python Implementation <pre>from collections import deque def minimumSemesters(numCourses, relations): # Build graph and in-degree dictionary. graph = {} prev, next = prev - 1, next - 1 g[prev].append(next) indeg[next] += 1 for i in range(1, numCourses + 1): in_degree = [i for i in range(1, numCourses + 1)] in_degree[in_degree] = 0 if in_degree[in_degree] == 0: queue.append(course) # Construct graph from relations. for pre, course in relations: graph[pre].append(course) in_degree[course] += 1 # Initialize queue with all courses having no prerequisites. for course in range(1, numCourses + 1): if in_degree[course] == 0: queue.append(course) # BFS while queue: ans += 1 for _ in range(len(queue)): i = queue.popleft() n -= 1 for j in g[i]: indeg[j] -= 1 if indeg[j] == 0: queue.append(j) return -1 if n else ans</pre> • SimplyTest Round 2 · High · Medium p.1268	<pre>semesters = 0 takenCourses = 0 # Process each level (semester) using BFS. while queue: semesters += 1 current_level_size = len(queue) for _ in range(current_level_size): course = queue.popleft() takenCourses += 1 # Decrement in-degree for neighboring courses. for neighbor in graph[course]: in_degree[neighbor] -= 1 if in_degree[neighbor] == 0: queue.append(neighbor) # If not all courses have been taken, a cycle exists. return semesters if takenCourses == numCourses else -1 # Example usage: print(minimumSemesters(3, [[1, 3], [2, 3]])) # Expected output: 2</pre> • LC.ca Round 2 · High · Medium p.1269	<pre>class Solution: def minimumSemesters(self, n: int, relations: List[List[int]]) -> int: g = defaultdict(list) indeg = [0] * n for pre, next in relations: pre, next = prev - 1, next - 1 g[pre].append(next) indeg[next] += 1 q = deque([i for i, v in enumerate(indeg) if v == 0]) ans = 0 while q: ans += 1 for _ in range(len(q)): i = q.popleft() n -= 1 for j in g[i]: indeg[j] -= 1 if indeg[j] == 0: q.append(j) return -1 if n else ans</pre> • SimplyTest Round 2 · High · Medium p.1270	BFS Round 2 · High · Medium · 6 questions Round 2 · High · Medium p.1271	#286 Walls and Gates LeetCode · SimplifyTest · WalCC · LeetCode Array - BFS - Matrix Lists: Premium 98 Time Complexity: $O(m * n)$ where m and n are the dimensions of the grid, as each cell is processed at most once. Space Complexity: $O(m * n)$ in the worst-case scenario used by the BFS queue. Problem You are given an $m \times n$ grid rooms initialized with these three possible values. -1 A wall or an obstacle. 0 A gate. ∞ INFINITY means an empty room. We use the value 231 - 1 = 2147483647 to represent ∞ as you may assume that the distance to a gate is less than 2147483647. Fill each empty room with the distance to its nearest gate. If it is impossible to reach a gate, it should be filled with ∞. Example 1: Round 2 · High · Medium p.1272		
 Input: rooms = [[2147483647,-1,2147483647],[2147483647,0,2147483647],[2147483647,-1,2147483647]] Output: [[3,-1,3],[2,0,2],[1,-1,2],[0,-1,3],[4]] Example 2: Input: rooms = [[-1]] Output: [[-1]] Round 2 · High · Medium p.1273	• Brute Force Approach <pre>class Solution: def wallsAndGates(self, rooms): # Brute Force O(m*n^2) - BFS from every empty room independently from collections import deque m, n = len(rooms), len(rooms[0]) INF = 2147483647 def bfs_from(src): queue = deque([(src, 0)]) visited = set() while queue: r, c, d = queue.popleft() if (r, c) in visited: continue visited.add((r, c)) if rooms[r][c] == 0: return d reached_a_gate = False for dr, dc in [(1,0), (-1,0), (0,1), (0,-1)]: nr, nc = r + dr, c + dc if 0 <= nr < m and 0 <= nc < n and rooms[nr][nc] != -1: queue.append((nr, nc, d+1)) return INF for r in range(n): for c in range(m): if rooms[r][c] != INF: rooms[r][c] = min(rooms[r][c], d+1)</pre> • LeetCode Round 2 · High · Medium p.1274	Community Solutions (Python) • WalCC <pre>class Solution: def wallsAndGates(self, rooms: List[List[int]]) -> None: # Do not return anything, modify rooms in-place instead. DIRS = [(0, 1), (1, 0), (0, -1), (-1, 0)] INF = 2147483647 m = len(rooms) n = len(rooms[0]) q = collections.deque([(i, j) for i in range(m) for j in range(n) if rooms[i][j] == 0]) while q: i, j = q.popleft() for dr, dc in DIRS: nr, nc = i + dr, j + dc if 0 <= nr < m and 0 <= nc < n and rooms[nr][nc] == INF: rooms[nr][nc] = min(rooms[i][j] + 1, rooms[nr][nc]) q.append((nr, nc))</pre> • LeetCode Round 2 · High · Medium p.1275	<pre>class Solution: def wallsAndGates(self, rooms: List[List[int]]) -> None: # Do not return anything, modify rooms in-place instead. m, n = len(rooms), len(rooms[0]) inf = 2147483647 q = collections.deque([(i, j) for i in range(m) for j in range(n) if rooms[i][j] == 0]) while q: d = 1 for _ in range(len(q)): i, j = q.popleft() for dr, dc in [(0, 1), (1, 0), (-1, 0), (0, -1)]: nr, nc = i + dr, j + dc if 0 <= nr < m and 0 <= nc < n and rooms[nr][nc] == inf: rooms[nr][nc] = d q.append((nr, nc))</pre> • SimplyTest Round 2 · High · Medium p.1276	<pre>from collections import deque def wallsAndGates(rooms): if not rooms or not rooms[0]: return rows, cols = len(rooms), len(rooms[0]) # Directions: up, down, left, right. directions = [(0, 1), (1, 0), (0, -1), (-1, 0)] queue = deque() # Enqueue all gates (cells with 0). for i in range(rows): for j in range(cols): if rooms[i][j] == 0: queue.append((i, j)) # Perform multi-source BFS. while queue: r, c = queue.popleft()</pre> Round 2 · High · Medium p.1277	Example 3: Input: coins = [1], amount = 0 Output: 0 Constraints: 1 <= coins.length <= 12 1 <= coins[i] <= 231 - 1 0 <= amount <= 104 Brute Force (Python) • Brute Force Approach <pre>class Solution: def coinChange(self, coins, amount): # Brute Force O(amount * 5^amount/min) - recursion without memo def dfs(i, rem): if rem == 0: return 0 if rem < 0: return float('inf') res = float('inf') for coin in coins: res = min(res, 1 + dfs(i, rem - coin)) return res return dfs(0, amount)</pre> • WalCC Round 2 · High · Medium p.1278		
<pre>d = 1 for _ in range(len(q)): i, j = q.popleft() for dr, dc in [(0, 1), (1, 0), (-1, 0), (0, -1)]: nr, nc = i + dr, j + dc # BFS to find first reaching inf is always the shortest # Set its value from inf to d, same as marking as visited if 0 <= nr < m and 0 <= nc < n and rooms[nr][nc] == inf: rooms[nr][nc] = d q.append((nr, nc)) ##### class Solution: def wallsAndGates(self, rooms): if not rooms or not rooms[0]: return m, n = len(rooms), len(rooms[0]) isVisited = [False] * m * n for i in range(m): for j in range(n): if rooms[i][j] != INF: rooms[i][j] = min(rooms[i][j], d+1)</pre> Round 2 · High · Medium p.1279	None: <pre>def fill(i: int, j: int, distance: int) -> None: nonlocal m, n # rooms[i][j] == 0 meaning == -1 or == 0, both stop if 0 <= i < m and 0 <= j < n and rooms[i][j] == 0 or visited[i][j]: return rooms[i][j] = min(rooms[i][j], distance) isVisited[i][j] = True fill(i + 1, j, distance + 1) fill(i - 1, j, distance + 1) fill(i, j + 1, distance + 1) fill(i, j - 1, distance + 1) isVisited[i][j] = False for i in range(m): for j in range(n): if rooms[i][j] != INF: rooms[i][j] = min(rooms[i][j], distance)</pre> Round 2 · High · Medium p.1280	<pre>if rooms[i][j] == 0: fill(i, j, 0) ##### from collections import deque INF = 2147483647 class Solution(object): def wallsAndGates(self, rooms): # type: rooms: List[List[int]] # type: void Do not return anything, modify rooms in-place instead. queue = deque([(i, j) for i in range(m) for j in range(n) if rooms[i][j] == 0]) for i in range(m): for j in range(n): if rooms[i][j] != INF: rooms[i][j] = min(rooms[i][j], distance)</pre> Round 2 · High · Medium p.1281	<pre>if rooms[i][j] == 0: queue.append((i, j)) while queue: i, j = queue.popleft() for dr, dc in directions: nr, nc = i + dr, j + dc if 0 <= nr < m and 0 <= nc < n and rooms[nr][nc] == INF: rooms[nr][nc] = min(rooms[i][j] + 1, rooms[nr][nc]) queue.append((nr, nc))</pre> Round 2 · High · Medium p.1282	BFS #322 Coin Change LeetCode · SimplifyTest · WalCC · LeetCode Array - Dynamic Programming - BFS Lists: Grid 169 Time Complexity: $O(\text{amount} * n)$ where n is the number of coins. Space Complexity: $O(\text{amount})$ for the dp array. Problem You are given an integer array coins representing coins of different denominations and an integer amount representing a total amount of money. Return the fewest number of coins that you need to make up that amount. If that amount of money cannot be made up by any combination of the coins, return -1. You may assume that you have an infinite number of each kind of coin. Example 1: Input: coins = [1,2,5], amount = 11 Output: 3 Explanation: 11 = 5 + 5 + 1 Example 2: Input: coins = [2], amount = 3 Output: -1 Round 2 · High · Medium p.1283	Example 3: Input: mat = [[0,0,0],[0,1,0],[0,0,0]] Output: [[0,0,0],[0,1,0],[0,0,0]] Example 2: Input: mat = [[0,0,0],[0,1,0],[0,0,0]] Output: [[0,0,0],[0,1,0],[0,0,0]] Round 2 · High · Medium p.1284		
<pre>class Solution: def coinChange(self, coins: List[int], amount: int) -> int: # dp[i] = the minimum number of coins to make up i dp = [0] * (amount + 1) amount = amount + 1 for i in range(1, amount + 1): dp[i] = min(dp[i], dp[i - coin] + 1) return -1 if dp[amount] == amount + 1 else dp[amount]</pre> • LeetCode <pre>class Solution: def coinChange(self, coins: List[int], amount: int) -> int: m = len(coins), amount f = [[inf] * (m + 1) for _ in range(m + 1)] f[0][0] = 0 for i, coin in enumerate(coins, 1): for j in range(1, amount + 1): if j >= coin: f[i][j] = min(f[i][j], f[i-1][j-coin] + 1) return -1 if f[m][amount] >= inf else f[m][amount]</pre> Round 2 · High · Medium p.1285	• SimplyTest <pre>def coinChange(coins, amount): # Create a dp array with amount+1 entries set to a value greater than any possible minimum number of coins. dp = [amount + 1] * (amount + 1) # Base case: 0 coins are needed to form amount 0. dp[0] = 0 # Build up the dp table. for current_amount in range(1, amount + 1): for coin in coins: if coin <= current_amount: dp[current_amount] = min(dp[current_amount], dp[current_amount - coin] + 1) # If dp[amount] remains greater than amount, no solution was found. return dp[amount] if dp[amount] != amount + 1 else -1</pre> • LC.ca Round 2 · High · Medium p.1286	<pre>... >>> float("inf") inf return dp[-1] if dp[-1] != float("inf") else -1 ##### class Solution: def coinChange(self, coins: List[int], amount: int) -> int: dp = [amount + 1] * (amount + 1) dp[0] = 0 for coin in coins: for i in range(1, amount + 1): if i >= coin: dp[i] = min(dp[i], dp[i - coin] + 1) return -1 if dp[-1] > amount else dp[-1]</pre> Round 2 · High · Medium p.1287	<pre>dp[i] = min(dp[i], dp[i - coin] + 1) return dp[-1] if dp[-1] != float("inf") else -1 ##### class Solution: def coinChange(self, coins: List[int], amount: int) -> int: dp = [amount + 1] * (amount + 1) dp[0] = 0 for coin in coins: for i in range(1, amount + 1): if i >= coin: dp[i] = min(dp[i], dp[i - coin] + 1) return -1 if dp[-1] > amount else dp[-1]</pre> Round 2 · High · Medium p.1288	BFS #542 01 Matrix LeetCode · SimplifyTest · WalCC · LeetCode Array - BFS - Matrix Lists: Grid 169 Denny Zhang Time Complexity: $O(m * n)$ since each cell is processed once. Space Complexity: $O(m * n)$ for the queue and the answer matrix. Problem Given an $m \times n$ binary matrix mat, return the distance of the nearest 0 for each cell. The distance between two cells sharing a common edge is 1. Example 1: Round 2 · High · Medium p.1289	 Input: mat = [[0,0,0],[0,1,0],[0,0,0]] Output: [[0,0,0],[0,1,0],[0,0,0]] Example 2: Input: mat = [[0,0,0],[0,1,0],[0,0,0]] Output: [[0,0,0],[0,1,0],[0,0,0]] Round 2 · High · Medium p.1290		
 Input: mat = [[0,0,0],[0,1,0],[1,1,1]] Output: [[0,0,0],[0,1,0],[1,1,1]] Round 2 · High · Medium p.1291	Note: This question is the same as 1765: https://leetcode.com/problems/map-of-highest-peak/ Brute Force (Python) • Brute Force Approach <pre>class Solution: def updateMatrix(self, mat): # Brute Force - BFS layer by layer from collections import deque queue = deque([0]) steps = 0 while queue: for _ in range(len(queue)): node = queue.popleft() for dr, dc in [(1,0), (-1,0), (0,1), (0,-1)]: nr, nc = node[0] + dr, node[1] + dc if 0 <= nr < m and 0 <= nc < n and mat[nr][nc] == -1: queue.append((nr, nc)) steps += 1 return steps</pre> Community Solutions (Python) • WalCC Round 2 · High · Medium p.1292	<pre>class Solution: def updateMatrix(self, mat: List[List[int]]) -> List[List[int]]: DIRS = [(0, 1), (1, 0), (0, -1), (-1, 0)] m = len(mat) n = len(mat[0]) q = collections.deque([(i, j) for i in range(m) for j in range(n) if mat[i][j] == 0]) for i in range(m): for j in range(n): if mat[i][j] == 0: q.append((i, j)) seen[i][j] = True while q: i, j = q.popleft() for dr, dc in DIRS: nr, nc = i + dr, j + dc if 0 <= nr < m and 0 <= nc < n and mat[nr][nc] == -1: mat[nr][nc] = min(mat[i][j] + 1, mat[nr][nc]) q.append((nr, nc))</pre> Round 2 · High · Medium p.1293	<pre>continue if seen[i][j]: continue mat[i][j] = mat[i][j] + 1 q.append((i, j)) seen[i][j] = True return mat</pre> • LeetCode <pre>class Solution: def updateMatrix(self, mat: List[List[int]]) -> List[List[int]]: m = len(mat), len(mat[0]) ans = [[-1] * n for _ in range(m)] q = deque() for i, row in enumerate(mat): for j in range(n): if mat[i][j] == 0: ans[i][j] = 0 q.append((i, j))</pre> Round 2 · High · Medium p.1294	<pre>dirs = (-1, 0, 1, 0, -1) while q: i, j = q.popleft() for dr, dc in dirs: nr, nc = i + dr, j + dc if 0 <= nr < m and 0 <= nc < n and ans[nr][nc] == -1: ans[nr][nc] = ans[i][j] + 1 q.append((nr, nc)) return ans</pre> • SimplyTest <pre>from collections import deque def updateMatrix(mat): # Get the dimensions of the matrix rows, cols = len(mat), len(mat[0]) # Initialize a queue for multi-source BFS queue = deque() # Initialize the matrix: use -1 to indicate unvisited cells for r in range(rows): for c in range(cols): if mat[r][c] != 0: queue.append((r, c))</pre> Round 2 · High · Medium p.1295	<pre>for c in range(cols): if mat[r][c] == 0: # Enqueue all 0 cells as starting points queue.append((r, c)) else: # Mark 1 cells as unvisited (or infinite distance) mat[r][c] = -1 # Directions for neighbors (up, down, left, right) directions = [(1, 0), (-1, 0), (0, 1), (0, -1)] # BFS traversal to update distances while queue: r, c = queue.popleft() for dr, dc in directions: nr, nc = r + dr, c + dc # Check boundaries and if neighbor has not been visited if 0 <= nr < rows and 0 <= nc < cols and mat[nr][nc] == -1: # Update neighbor's distance mat[nr][nc] = mat[r][c] + 1</pre> Round 2 · High · Medium p.1296		

994 Rotting Oranges

Time Complexity: $O(m \times n)$ as every cell is processed at most once. Space Complexity: $O(m \times n)$ in the worst case for the queue and auxiliary storage.

Problem

You are given an $m \times n$ grid where each cell can have one of three values:

- 0 representing an empty cell,
- 1 representing a fresh orange, or
- 2 representing a rotten orange.

Every minute, any fresh orange that is 4-directionally adjacent to a rotten orange becomes rotten.

Return the minimum number of minutes that must elapse until no cell has a fresh orange. If this is impossible, return -1.

Example 1:

```

grid = [
  [1, 1, 1, 0, 0],
  [0, 1, 1, 1, 0],
  [0, 1, 0, 1, 1],
  [1, 0, 1, 1, 0]
]

```

Output: 4

Brute Force Approach

Class Solution:

```

def orangesRotting(self, grid):
    # Brute Force O((m*n)^2) - repeatedly scan
    # entire grid, spread rot each
    # from copy, import deepcopy
    m, n = len(grid), len(grid[0])
    minutes = 0
    while True:
        new_grid = deepcopy(grid)
        changed = False
        for i in range(m):
            for j in range(n):
                if grid[i][j] == 2:
                    for dr, dc in [(1, 0), (-1, 0), (0, 1), (0, -1)]:
                        nr, nc = i + dr, j + dc
                        if 0 <= nr < m and 0 <= nc < n and grid[nr][nc] == 1:
                            new_grid[nr][nc] = 2
                            changed = True
        if not changed:
            break
        minutes += 1
        grid = new_grid
    return minutes if not any(1 in row for row in grid) else -1

```

Community Solutions (Python)

BFS processing

```

# Enqueue the neighbor for further
# BFS processing
queue.append((nr, nc))

return ans

# Example usage:
# print(updateMatrix([[0,0],[0,1],[1,1]]))

```

LeetCode

```

class Solution:
    def updateMatrix(self, mat: List[List[int]]) -> List[List[int]]:
        m, n = len(mat), len(mat[0])
        ans = [[-1] * n for _ in range(m)]
        q = deque()
        for i, row in enumerate(mat):
            for j, x in enumerate(row):
                if x == 0:
                    ans[i][j] = 0
                    q.append((i, j))

```

994 Rotting Oranges

Time Complexity: $O(m \times n)$ as every cell is processed at most once. Space Complexity: $O(m \times n)$ in the worst case for the queue and auxiliary storage.

Problem

You are given an $m \times n$ grid where each cell can have one of three values:

- 0 representing an empty cell,
- 1 representing a fresh orange, or
- 2 representing a rotten orange.

Every minute, any fresh orange that is 4-directionally adjacent to a rotten orange becomes rotten.

Return the minimum number of minutes that must elapse until no cell has a fresh orange. If this is impossible, return -1.

Example 1:

```

grid = [
  [1, 1, 1, 0, 0],
  [0, 1, 1, 1, 0],
  [0, 1, 0, 1, 1],
  [1, 0, 1, 1, 0]
]

```

Output: 4

Brute Force Approach

Class Solution:

```

def orangesRotting(self, grid):
    # Brute Force O((m*n)^2) - repeatedly scan
    # entire grid, spread rot each
    # from copy, import deepcopy
    m, n = len(grid), len(grid[0])
    minutes = 0
    while True:
        new_grid = deepcopy(grid)
        changed = False
        for i in range(m):
            for j in range(n):
                if grid[i][j] == 2:
                    for dr, dc in [(1, 0), (-1, 0), (0, 1), (0, -1)]:
                        nr, nc = i + dr, j + dc
                        if 0 <= nr < m and 0 <= nc < n and grid[nr][nc] == 1:
                            new_grid[nr][nc] = 2
                            changed = True
        if not changed:
            break
        minutes += 1
        grid = new_grid
    return minutes if not any(1 in row for row in grid) else -1

```

Community Solutions (Python)

```

grid[x][y] = 2
q.append((x, y))
cut = 1
if cut == 0:
    return -1 if cut else 0
            
```

Simplifies

from collections import deque

```

def orangesRotting(grid):
    # Dimensions of the grid
    row, cols = len(grid), len(grid[0])
    # Queue to perform BFS, containing tuples of (row, col)
    rotten_queue = deque()
    fresh_count = 0

    # Step 1: Initialize the queue with all initially rotten oranges and count fresh oranges.
            
```

```

for r in range(rows):
    for c in range(cols):
        if grid[r][c] == 2:
            rotten_queue.append((r, c))
        elif grid[r][c] == 1:
            fresh_count += 1

    # If there are no fresh oranges, return 0 immediately.
    if fresh_count == 0:
        return 0

    minutes_passed = 0
    # Directions for adjacent cells: up, down, left, right.
    directions = [(-1, 0), (1, 0), (0, -1), (0, 1)]

    # Step 2: BFS to rot adjacent fresh oranges. While rotten queue:
    # Process oranges that are rotten in the current minute.
    while rotten_queue:
        for x, y in rotten_queue.popleft():
            # If there are still fresh oranges left, return -1.
            rotten_minutes_passed = 1 if fresh_count == 0 else -1

            # Example usage:
            # grid = [[2,1,1],[1,1,0],[1,1,1]]
            # print(orangesRotting(grid))
            # LC65
            
```

class Solution:

```

def orangesRotting(self, grid: List[List[int]]) -> int:
    row, cols = len(grid), len(grid[0])
    q = deque()
    cut = 0

    for i in range(rows):
        for j in range(cols):
            if grid[i][j] == 2:
                q.append((i, j))
            elif grid[i][j] == 1:
                cut += 1

    ans = 0
    while q and cut:
        ans += 1
        for a in range(len(q)):
            x, y = q.popleft()
            for a, b in [(0, 1), (0, -1), (1, 0), (-1, 0)]:
                x, y = x + a, y + b
                if 0 <= x < m and 0 <= y < n and grid[a][b] == 1:
                    grid[a][b] = 2
                    q.append((a, y))
                    return ans if cut == 0 else -1
            
```

BFS

#1197 Minimum Knight Moves

LeetCode - SimplyEasiest - WalkCC - LeetCode

BFS

Lists: Grid 169 | Premium 98

Time Complexity: $O(n)$ where n is the number of positions processed during the BFS
Space Complexity: $O(n)$ due to the storage requirements for the BFS queue and the visited set.

Problem

In an infinite chess board with coordinates from $-\infty$ to $+\infty$, you have a knight at square $[0, 0]$. A knight has 8 possible moves it can make, as illustrated below. Each move is two squares in a cardinal direction, then one square in an orthogonal direction.



Return the minimum number of steps needed to move the knight to the square $[x, y]$. It is guaranteed the answer exists.

Example 1:

```

Input: x = 2, y = 1
Output: 1
Explanation: [0, 0] -> [2, 1]
            
```

Example 2:

<pre> Input: x = 5, y = 5 Output: 4 Explanation: [0, 0] -> [2, 1] -> [4, 2] -> [3, 4] -> [5, 5] Constraints: * -300 <= x, y <= 300 * 0 <= x + y <= 300 Brute Force (Python) # Brute Force Approach class Solution: def minKnightMoves(self, x: int, y: int) -> int: # BFS layer by layer from collections import deque queue = deque([(0, 0)]) visited = {(0, 0)} while queue: for i, j in range(len(queue)): node = queue.popleft() for nb in graph[node]: if nb not in visited: visited.add(nb) queue.append(nb) steps += 1 return steps </pre> Community Solutions (Python)	<pre> # BFS layer by layer from collections import deque queue = deque([(0, 0)]) visited = {(0, 0)} while queue: for i, j in range(len(queue)): node = queue.popleft() for nb in graph[node]: if nb not in visited: visited.add(nb) queue.append(nb) steps += 1 return steps </pre>	<pre> class Solution: def minKnightMoves(self, x: int, y: int) -> int: def extend(m1, m2, q): for i, j in range(len(q)): m1, m2 = q[i], q[j] step = m1[i] + m2[j] for a, b in [(-2, 1), (-2, -1), (-1, 2), (-1, -2), (1, 2), (1, -2)]: n1, n2 = (m1[0] + a, m1[1] + b) if n1 not in q and n2 not in q: q.append((n1, n2)) step += 1 return step return extend((0, 0), (0, 0), deque([(x, y)])) </pre>	<pre> # BFS queue stores tuples of the form (current_x, current_y, move_count) move_count = deque([(0, 0)]) # Set to track visited positions to prevent cycles visited = {(0, 0)} # Process BFS while queue: curr_x, curr_y, move_count = queue.popleft() # Return the current move count if target is reached if curr_x == x and curr_y == y: return move_count # Explore all knight moves for dx, dy in moves: for dx, dy in moves: next_x, next_y = curr_x + dx, curr_y + dy # Prune search space: only process positions with valid bounds if next_x >= -3 and next_y >= -3: visited.add((next_x, next_y)) queue.append((next_x, next_y, move_count + 1)) </pre>
---	---	--	---

return ans

for a, b in dirs:
c, d = a + b, j
if (c, d) not in vis:
vis.add((c, d))
q.append((c, d))

ans += 1

return -1

1730 Shortest Path to Get Food

LeetCode - SimplyLeet - WalkCC - LeetCode

List: Grid - 169

Time Complexity: $O(m \cdot n)$, where m is the number of rows and n is the number of columns since each cell is processed at most once. Space Complexity: $O(m \cdot n)$ in the worst case due to the queue and vis.

Problem

You are starving and you want to eat food as quickly as possible. You want to find the shortest path to arrive at any food cell.

You are given an $m \times n$ character matrix, grid, of these different types of cells:

- "*": is your location. There is exactly one "*" cell.
- "F" is a food cell. There may be multiple food cells.
- "O" is free space, and you can travel through these cells.
- "X" is an obstacle, and you cannot travel through these cells.

You can travel to any adjacent cell north, east, south, or west of your current location if there is not an obstacle.

1730 Shortest Path to Get Food

LeetCode - SimplyLeet - WalkCC - LeetCode

List: Grid - 169

Time Complexity: $O(m \cdot n)$, where m is the number of rows and n is the number of columns since each cell is processed at most once. Space Complexity: $O(m \cdot n)$ in the worst case due to the queue and vis.

Problem

You are starving and you want to eat food as quickly as possible. You want to find the shortest path to arrive at any food cell.

You are given an $m \times n$ character matrix, grid, of these different types of cells:

- "*": is your location. There is exactly one "*" cell.
- "F" is a food cell. There may be multiple food cells.
- "O" is free space, and you can travel through these cells.
- "X" is an obstacle, and you cannot travel through these cells.

You can travel to any adjacent cell north, east, south, or west of your current location if there is not an obstacle.

Return the length of the shortest path for you to reach any food cell. If there is no path for you to reach food, return -1.

Example 1:



Input: grid = [[*,"X","X","X","X"],["X","X","X","X","X"],["X","X","F","X","X"],["X","X","X","X","X"],["X","X","X","X","X"]]

Output: 4

Explanation: It takes 4 steps to reach the food.

Example 2:



Input: grid = [[*,"X","X","X","X"],["X","X","X","X","X"],["X","X","F","X","X"],["X","X","X","X","X"],["X","X","X","X","X"]]

Output: 6

Explanation: It takes 6 steps to reach the food.

m == grid.length

n == grid[0].length

1 <= m, n <= 200

grid[i][j] is "X", "O", "F", or "*"

The grid contains exactly one "*".

Brute Force (Python)

Brute Force Approach

class Solution:

def getFood(self, grid):

Brute Force - BFS layer by layer

from collections import deque

queue = deque([0])

visited = {0}

steps = 0

while queue:

for

in range(len(queue)):

node = queue.popleft()

for nb in graph[node]:

if nb not in visited:

visited.add(nb):

queue.append(nb)

steps += 1

return steps

Community Solutions (Python)

• WalkCC

[illegible]

Round 2 High Medium Quick Review 116 questions key insights complexity solution #57 Insert Interval [Medium] Arrays & Hashing Key Insights • The intervals array is sorted by start times. • Three main steps are used: • Add intervals that come completely before the new interval. • Merge overlapping intervals with the new interval. • Append intervals that start after the new (merged) interval. • Iterating through the list once allows an $O(n)$ solution. Space & Time Time Complexity: $O(n)$ since we scan the list once. Space Complexity: $O(n)$ to store the resulting list of intervals. Solution Traverse the intervals list and perform the following: • Append all intervals that end before the new interval starts. • For intervals that overlap with newInterval, update newInterval to merge them (using min for start and max for end). • Append any new merged interval. • Append all remaining intervals. This ensures that all	intervals remain non-overlapping and sorted with a single pass. #238 Product of Array Except Self [Medium] Arrays & Hashing Key Insights • The product for each index can be computed by multiplying the product of all numbers to the left and the product of all numbers to the right of that index. • Division is not allowed, so we must compute the cumulative products explicitly. • Create two passes: one forward pass for prefix products and one backward pass for suffix products. • Use the output array to store the cumulative product values, achieving $O(1)$ extra space by not using additional arrays. Space & Time Time Complexity: $O(n)$ because we iterate through the array twice. Space Complexity: $O(1)$ extra space (excluding the output array). Solution The approach uses two passes over the input array: • Initialize the answer array and fill it with prefix products. For each index i, <code>answer[i]</code> contains the product of all elements before i. • Traverse the array	from the end using a running suffix product. Update the answer array by multiplying the current suffix product with the prefix product already stored. This method leverages an output array to store intermediate results and uses a temporary variable for the suffix product, ensuring constant extra space. #281 Zigzag Iterator [Medium] Arrays & Hashing Key Insights • Use a FIFO (first-in–first-out) structure to maintain the order of vectors which still have remaining elements. • For each call to <code>next()</code>, select the next element from the current vector and then move that vector to the end of the queue if it still contains elements. • The approach ensures proper zigzag (or cyclic) ordering among the vectors. • When extending to k vectors, the same approach works: initialize the queue with each non-empty vector. Space & Time Time Complexity: $O(1)$ per <code>next()</code> call on average, with an overall $O(n)$ for n total elements. Space Complexity: $O(k)$ for the k vectors (where k is the number of vectors); plus the storage for the input vectors. Solution	We can solve the Zigzag Iterator problem by using a queue (or deque) to hold pairs of the vector's current index and the vector itself. For each call to <code>next()</code>, we remove the front element from the queue, return the current element and its associated vector, and if the vector has more elements, reinsert the pair (with an updated index) into the back of the queue. This cyclic process naturally interleaves the elements from the provided vectors. #307 Range Sum Query - Mutable [Medium] Arrays & Hashing Key Insights • To efficiently support both point updates and range sum queries, a specialized data structure like a Binary Indexed Tree (Fenwick Tree) or a Segment Tree is ideal. • Both data structures provide update and sum query operations in $O(\log n)$ time. • The challenge is to maintain a mutable array while enabling fast sum computation over any specified range. Space & Time Time Complexity: $O(\log n)$ for both update and sum/range operations. Space Complexity: $O(n)$ to store the additional tree structure. Solution	We can use a Binary Indexed Tree (Fenwick Tree) to solve this problem. The Fenwick Tree allows for efficient prefix sum calculations and point updates, both in $O(\log n)$ time. The approach involves: • Building the Fenwick Tree using the initial array. • On an update, computing the difference between the new value and the current value, then propagating the change appropriately in the tree. • For the sum range query, computing the prefix sum up to right and subtracting the prefix sum up to left-1. #54 Subarray Sum [Medium] Arrays & Hashing Key Insights • Use a hash table to store the frequency of all possible sums from <code>nums[1]</code> and <code>nums[2]</code>. • For each pair from <code>nums[3]</code> and <code>nums[4]</code>, compute the complement (negative sum) and look it up in the hash table. • This reduces the time complexity from $O(n^4)$ to $O(n^2)$. Space & Time Time Complexity: $O(n^2)$ where n is the length of each array. Space Complexity: $O(n^2)$ due to the storage of pair sums in the hash table. Solution
Round 2 High Medium 1327	Round 2 High Medium 1328	Round 2 High Medium 1329	Round 2 High Medium 1330	Round 2 High Medium 1331

The solution employs a hash table to precompute and store the frequency of sums of all pairs from the first two arrays. Then, by iterating over all pairs from the third and fourth arrays, we calculate the required frequency that would result in a total sum of zero. #525 Contiguous Array [Medium] - Arrays & Hashing Key Insights - Convert 0 to -1 so that a balanced subarray (equal number of 1s) sums to zero. - Use a prefix sum to track the cumulative sum as you iterate through the array. - Use a hash table (or dictionary) to store the first occurrence of each prefix sum. - When the same prefix sum is encountered again, it indicates that the subarray between these indices is balanced. Space & Time Time Complexity: O(n) - We iterate through the array once.	Space Complexity: O(n) - In the worst case, we store an entry for each prefix sum. Solution We use a technique where we convert each 0 in the array to -1. Then, we compute a running prefix sum as we iterate through the array. A prefix sum of 0 at any point indicates that the subarray from the beginning to the current index is balanced. For each prefix sum, if we have seen it before, the subarray between the previous index where the prefix sum was first seen and the current index sums to 0. We update the maximum length accordingly. We use a hash table to store the first index where each prefix sum occurs. #560 Subarray Sum Equals K [Medium] - Arrays & Hashing Key Insights - Utilize the prefix sum technique to simplify sum calculation for subarrays. - Use a hash table (or dictionary) map to store the frequency of prefix sums encountered. - For each element, check if (current prefix sum - k) exists in the hash table; if it does, it indicates a valid subarray. - Initialize the hash table with {0: 1} to manage cases where a subarray's sum is exactly k.	Space & Time Time Complexity: O(n) - Iterates through the array once. Solution We solve the problem by maintaining a running sum (prefix sum) and using a hash table to record the number of times each sum has occurred. As we iterate through the array, we update the running sum. For each new sum, we check if (current sum - k) exists in our hash table. If it does, the value associated with (current sum - k) gives the number of subarrays ending at the current index that sum to k. This method efficiently computes the result in a single pass through the array. #1010 Pairs of Songs With Total Durations Divisible by 60 [Medium] - Arrays & Hashing Key Insights - Each song duration's effect is determined by its remainder when divided by 60. - For any given module value (where 0 < r < 60), the complementary module needed to complete 60 is (60 - r) % 60. - Special handling is needed when r is 0, since 10 - 10 = 60 to avoid overcounting. - A frequency counter for remainders can be efficiently used to count valid pairs in one pass through the list.	Space & Time Time Complexity: O(n), where n is the number of songs. Space Complexity: O(60) - O(1), since we only need to keep track of 60 possible remainders. Solution We solve the problem by listing song durations and calculate the remainder for each duration modulo 60. A frequency counter (map) records how many times each remainder has been seen so far. For each song, we look up the frequency of its complementary remainder (i.e., 60 - current_remainder % 60) already encountered. This frequency indicates how many valid pairs can be formed with the current song. After counting pairs with the current song, we update the frequency of its remainder for future pairings. #1272 Remove Interval [Medium] - Arrays & Hashing Key Insights - Iterate over each interval and check if it overlaps with the toBeRemoved interval. - If the current interval is completely outside of toBeRemoved, add it to the result as is. - For overlapping intervals, compute the non-overlapping portions.	If the left side of the interval lies before toBeRemoved, include [start, min(end, toBeRemoved.start)]. If the right side of the interval lies after toBeRemoved, include [max(start, toBeRemoved.end), end]. Space & Time Time Complexity: O(n), where n is the number of intervals. Space Complexity: O(n), for storing the resulting intervals. Solution The approach involves iterating through the list of sorted disjoint intervals and checking for overlap with the toBeRemoved interval. For each interval: - If it is completely before or after the removal interval, we directly to the result. - If it overlaps with toBeRemoved, determine the remaining portions: The left side of the interval that does not intersect (if any). The right side of the interval that does not intersect (if any). Use simple conditional checks and list manipulation to form the final set of intervals. #1429 First Unique Number [Medium] - Arrays & Hashing Key Insights - Use a queue to maintain the order of potential unique numbers.	Use a hash table (or map) to count the occurrences of each number. When showing the first unique number, remove numbers from the front of the queue if their frequency is more than one. All operations (add and show/first/unique) can be done in O(1) amortized time. Space & Time Time Complexity: O(1) amortized for each add and show/first/unique call. Space Complexity: O(n), where n is the number of distinct integers encountered. Solution We design the FirstUnique class using two main data structures: a queue and a hash map (or dictionary). The queue preserves the order of insertion for unique candidates, while the hash map holds the frequency count for each integer. When a new number is added: - Increment its count in the hash map. - If the count is one, append it to the queue. To retrieve the first unique number: - While the queue is not empty and the count for the element at the front is greater than one, remove it from the queue. - Return the front element of the queue if it exists, otherwise return -1.
This approach ensures that we are always up-to-date with the current first unique number. #3159 Find Occurrences of an Element in an Array [Medium] - Arrays & Hashing Key Insights - Scan the array once and record every index where nums[i] == x. - Store those indices in order inside a positions array. - For each query [k, check whether the 'k - th occurrence of x' exists in the array. - If it exists, return 'positions[k] - 1'. - Otherwise, return '-1'. - This lets every query be answered in constant time after the preprocessing pass. Space & Time Time Complexity: O(n) - We iterate through the array once.	the answer is 'positions[k] - 1'; otherwise, the required occurrence does not exist, so the answer is '-1'. This avoids rescanning the array for every query. #8 String to Integer (atoi) [Medium] - String Key Insights - Skip leading spaces in the string. - Detect and handle the optional sign indicator ('+' or '-'). - Read and convert digit characters until a non-digit is encountered. - Handle cases with no digits or leading zeros. - Clamp the result to fit within the 32-bit signed integer range. Space & Time Time Complexity: O(n) where n is the length of the string. Space Complexity: O(1) as only a constant amount of extra space is used. Solution We iterate through the string to first eliminate any leading whitespace. Next, we check for a sign character to determine if the resulting integer should be negative. We then convert each consecutive digit into an integer, while also updating the result and checking for potential overflow. If an overflow is detected, we	Immediately return the appropriate maximum or minimum 32-bit signed integer boundary value. This approach ensures that we strictly follow the conversion rules and efficiently handle edge cases like leading zeros. #249 Group Shifted Strings [Medium] - String Key Insights - Skip leading spaces in the string. - All strings in the same group have the same relative differences between adjacent characters. - Normalize each string's pattern by converting it to a key representation based on the differences between consecutive letters. - A single character string forms its own group as there are no differences to compare. Space & Time Time Complexity: O(n * m) where n is the number of strings and m is the average length of the strings (to compute each string's key). Space Complexity: O(m) to store the keys and grouping in the hash table. Solution This solution involves iterating over each string and generating a unique key that represents the relative differences between adjacent characters. This key is calculated by computing the difference (mod 26) between every consecutive pair in the string. Strings that share the same key are grouped together.	that share the same key can be grouped together since they can be shifted into one another. A hash table (or dictionary) is used to store and group the strings by their computed key. This approach handles edge cases like single-character strings separately. #271 Encode and Decode Strings [Medium] - String Key Insights - Use length-prefix encoding for each string to avoid ambiguity. - Append a delimiter (e.g., ",") after the length to separate it from the string content. - This method ensures that even if the original strings contain special characters, including the delimiter, the decoding remains unambiguous. - The approach handles edge cases, such as empty strings. Space & Time Time Complexity: O(n), where n is the total number of characters across all strings. Space Complexity: O(n), required for the encoded string and the resulting decoded list. Solution We encode by iterating over each string and building a new string that contains the length of the string, a delimiter (e.g., ","), and then the string itself. This way,	during decoding, we can safely determine how many characters to extract by first reading until the delimiter to get the length, and then reading that number of characters. This length-prefix approach avoids conflicts with potential characters in the strings. #635 Design Log Storage System [Medium] - String Key Insights - Store logs in a simple data structure such as a list or array. - Convert the timestamps into strings; due to fixed-length and zero padding, lexicographical string comparison is valid. - Use a mapping to determine the slice length for each granularity, e.g., 'Year' corresponds to the first 4 characters, 'Month' corresponds to the first 7 characters, etc. - During retrieval, compare the relevant substring of each stored timestamp against the start and end query timestamps slices. - The inclusive nature of the query simplifies checking conditions. Space & Time Time Complexity: O(N) per retrieval query, where N is the number of logs stored (since each log is checked). In the worst case, all log entries are examined.	Space Complexity: O(N) where N is the number of logs stored. Solution We implement a LogSystem class that supports putting log entries and retrieving them using a specific granularity. - Data Structures: Use a list/array to store log entries as tuples (or objects) containing the timestamp and log ID. - A dictionary map is used to store the mapping from granularity string to the substring index (e.g., "Year" -> "Month" -> "Day"). - For the put() method, simply append the new log entry into the list. - For the retrieve() method, compute the substring length based on the provided granularity. Then iterate over all stored logs and compare the sliced timestamp against the sliced start and end timestamps. - Use slicing to extract the relevant portion of the timestamps, including the log ID in the result. - Since the timestamps have fixed width with leading zeros, slicing and lexicographical comparisons are both valid and efficient.
positions. For target letter 'z', perform horizontal moves before vertical moves, for all other letters, do vertical moves before horizontal moves. Build the answer step-by-step by moving from your current position to each target letter. Space & Time Time Complexity: O(n) where N is the length of target (each move is processed in constant time). Space Complexity: O(n) for the resulting string of moves Solution The approach calculates the destination coordinates for each character. For each letter in the target: - Convert the letter to its board coordinates (row and col). - For each letter, for letter, row = (ord(c) - ord('A')) // 5 + 1 and col = (ord(c) - ord('A')) % 5. Note that 'z' (the 26th letter) always maps to (5, 0). - To move from the current position (curRow, curCol) to the target's (targetRow, targetCol), decide the order of moves: If the target letter is 'z', first move horizontally (left or right) then vertically (up or down) to avoid stepping into invalid regions from the extra row. For any other letter, move vertically (up or down) first, then horizontally (left or right). - Append "L" or "R" to the moves after reaching each letter. - Update the current position to the letter's coordinates.	This method ensures you only traverse valid cells on the board and minimizes moves by taking the optimal coordinate difference each step. #11 Container With Most Water [Medium] - Two Pointers Key Insights - The container's area is determined by the distance between two lines multiplied by the shorter line's height. - A brute-force approach checking all possible pairs would result in O(n^2) time complexity, which is inefficient for large inputs. - A two-pointer approach allows us to solve the problem in O(n) time by initializing pointers at both ends and gradually moving them inward. - By always moving the pointer corresponding to the shorter line, we are more likely to find a taller line that could potentially form a container with a larger capacity. Space & Time Time Complexity: O(n) - The algorithm makes a single pass through the array with two pointers. Space Complexity: O(1) - Only a few extra variables are used, regardless of the input size. Solution The optimal approach uses a two-pointer strategy:	- Start with two pointers at each end of the array. - Calculate the area formed between the two lines at these pointers. - Update the maximum area if the calculated value is larger. - Move the pointer pointing towards the shorter line inward, as this is the only possible way to find a pair that sums up to increase the container's area. - Continue until the two pointers meet. This method effectively reduces the number of pairs that need to be compared and ensures that every possible pair that could yield a larger area is considered. #15 3Sum [Medium] - Two Pointers Key Insights - Sort the array to efficiently skip duplicates and facilitate the two pointers approach. - Use a fixed pointer for the first element, and then use two additional pointers (left and right) to find pairs that sum to the negation of the fixed element. - Skip duplicate elements to ensure unique triplets. Space & Time Time Complexity: O(n^2) where n is the number of elements in the array. Space Complexity: O(1) extra space (ignoring the space required for the output). Solution We use the two pointers approach: - Initialize two pointers, left at the beginning (index 0) and right at the end (last index) of the array. - While left is less than right, compute the sum of the elements at the two pointers. - If the sum equals the target, return the indices as [left, left+1, right]. - If the sum is less than the target, move the left pointer to the right to increase the sum. - If the sum is greater than the target, move the right pointer to the left to decrease the sum. - This approach leverages the sorted property and uses constant extra space.	We first sort the array to bring duplicates together and allow the two-pointer technique to work efficiently. Then, iterate over the array and for each element, we find two other elements (one at the beginning right after the current element and one at the end of the array) to find a pair that sums with the current element to equal the target. This way, we avoid the need for a third loop to find duplicate triplets. This ensures that each element is unique and the overall runtime remains efficient. #16 3Sum Closest [Medium] - Two Pointers Key Insights - Sort the array to make it easier to use the two pointers technique. - For the first element and then use two pointers (left and right) to find the best pair that, along with the fixed element, produces a sum closest to the target. - Update the best sum whenever a closer sum is found. - The sorted order helps eliminate unnecessary iterations and allows efficient movement of pointers. Space & Time Time Complexity: O(n^2) Space Complexity: O(1) (n^2) depending on the sorting algorithm used (typically in-place sort, so extra space might be minimal)	Solution The solution starts by sorting the array. For each index in the array (considered as the first element of the triplet), we use two pointers: one starting just after the triple element and the other at the end of the array. We calculate the sum of the fixed element and the two pointers. If this sum is closer to the target than the current best, we update our best sum. Depending on whether the current sum is less or greater than the target, we adjust the left or right pointer to try and get closer to the target. This two-pointer method leverages the sorted order of the array for efficient summing. #31 Next Permutation [Medium] - Two Pointers Key Insights - The problem is solved by identifying the first pair from the right where the left element is less than the right element. - Once one value is found, find the rightmost element that is greater than this element. - Swap these two elements. - Reverse the subarray that comes after the pivot to ensure the next permutation is the next lexicographically larger sequence. - If no such pivot exists, the array is in descending order and should be reversed to get the smallest permutation. Space & Time	Time Complexity: O(n) Space Complexity: O(1) Solution We start by scanning the array from the right to find the first index where nums[i] is less than nums[i+1]. This index 'i' represents the pivot point where the next permutation can be formed. If we find such an index, we then scan from the right again to locate the first number that is greater than nums[i] (let this index be j), and swap these two numbers. Finally, we reverse the subarray starting from index i+1 to the end of the array, which gives us the next permutation in lexicographical order. This approach uses in-place modifications using basic operations like swapping and reversing, thus meeting the constant space requirement. #75 Sort Colors [Medium] - Two Pointers Key Insights - Use the Dutch National Flag algorithm to partition the array into three sections. - Maintain three pointers: one for the next position for 0 (low), one for the next position for 2 (high), and one for the current element (mid). - Swap elements appropriately to ensure that all 0's are at the beginning, all 2's are at the end, and 1's remain in the middle.
Space & Time Time Complexity: O(1) Space Complexity: O(1) Solution The solution uses a three-pointer approach (Dutch National Flag algorithm). Initialize three pointers: low, mid, and high. As you iterate through the array: - If the element is 0, swap it with the element at the low pointer and increment both low and mid. - If the element is 1, simply move mid forward. - If the element is 2, swap it with the element at the high pointer and decrement high. This single pass method ensures that the array is sorted in-place with constant extra space. Key details include correctly handling swaps without losing any data and ensuring that the pointers are updated in the proper order. #161 One Edit Distance [Medium] - Two Pointers Key Insights - The difference in length between s and t must be at most 1. - When lengths are equal, the only possibility is that exactly one character is different (replacement). - When one string is longer by one character, the difference can be fixed by one insertion (or deletion in the other direction).	Use two pointers to compare corresponding characters and carefully handle the first difference. Space & Time Time Complexity: O(n), where n is the length of the shorter string, as we traverse both strings at most once. Space Complexity: O(1), using only constant extra space. Solution The solution uses a two-pointer approach. First, we check if the length difference is greater than 1, in which case they cannot be one edit apart. For the two primary cases: - When strings are of equal length, iterate through both strings and count the number of differing characters. There should be exactly one difference. - When lengths differ by one, use pointers for both strings. Upon encountering a difference, increment the pointer for the longer string until and ensure that no previous difference has been encountered. If a second discrepancy is found, return false. The key is to handle the edge case where the difference is at the end of the string. #167 Two Sum II - Input Array Is Sorted [Medium] - Two Pointers Key Insights - Since the array is sorted, the sum of elements at the two pointers (left and right) increases as the pointers move towards each other. - If the sum is less than the target, move the left pointer to the right to increase the sum. - If the sum is greater than the target, move the right pointer to the left to decrease the sum. - This approach leverages the sorted property and uses constant extra space.	The array is sorted in non-decreasing order, which makes the two pointers technique very effective. Using two pointers (one at the start and one at the end) allows checking pairs and adjusting the pointers based on the sum. Since the problem guarantees exactly one solution and requires constant space, using two pointers satisfies both constraints. Space & Time Time Complexity: O(n), where n is the number of elements in the array, because in the worst-case scenario each element is visited at most once. Space Complexity: O(1), as no additional data structure is used that scales with the input size. Solution We use the two pointers approach: - Initialize two pointers, left at the beginning (index 0) and right at the end (last index) of the array. - While left is less than right, compute the sum of the elements at the two pointers. - If the sum equals the target, return the indices as [left, left+1, right]. - If the sum is less than the target, move the left pointer to the right to increase the sum. - If the sum is greater than the target, move the right pointer to the left to decrease the sum. - This approach leverages the sorted property and uses constant extra space.	#186 Reverse Words in a String II [Medium] - Two Pointers Key Insights - Reverse the entire array first to obtain the reversed order of characters. - Then, reverse each individual word to restore the correct letter order. - Doing so leverages the two-pointer technique for in-place reversals. - This method accomplishes the goal in O(n) time using only O(1) extra space. Space & Time Time Complexity: O(n) Space Complexity: O(1) Solution The solution employs a two-step reversal process using the two-pointer technique. First, reverse the entire character array to reverse the overall order of characters. Although this reverses both the words and the letters in each word, it sets up the scenario where each word's letters are in reverse order. The next step is to iterate through the array and locate each word (using the space character as a delimiter) and then reverse each word individually to correct its letter order. This process is done in-place without any additional data	structures, conserving space. #189 Rotate Array [Medium] - Two Pointers Key Insights - Rotation amount k might be greater than the length of the array, so use k % n (where n is the array length) to compute the effective rotation. - A smart in-place solution involves reversing sections of the array: - Reverse the entire array. - Reverse the first k elements. - Reverse the remaining n - k elements. - Alternative approaches include using extra space or performing k single-step rotations (which is less optimal). Space & Time	remaining n - k elements. This sequence yields the array rotated to the right by k positions while strictly using O(1) extra space. #532 K-Diff Pairs in an Array [Medium] - Two Pointers Key Insights - If k = 0, the answer is always 0 because the absolute difference cannot be negative. - When k is 0, you are looking for numbers that appear at least twice. - For k > 0, it is efficient to use a hash set or a hash map to check if each number's complement (number + k) exists. - Uniqueness is ensured by processing each number only once from the set of unique numbers. Space & Time Time Complexity: O(n), where n is the length of the array since we iterate over the array and then over the unique numbers. Space Complexity: O(n), for storing the frequency count or the unique elements in a hash map or hash set. Solution The solution first checks if k is negative, returning 0. For non-negative k, we iterate through the array and use a hash map to track elements that appear more than once using a frequency map. For
k greater than 0, a set of unique numbers is created and for each number, we check if (number + k) is also present in the set. Each valid case contributes to the result count, ensuring that only unique pairs are considered. #923 Sum With Multiplicity [Medium] - Two Pointers Key Insights - Use a frequency counter for elements since arr[i] is in the range [-100, 100]. - Iterate through all possible combinations of numbers x, y, and z with x <= y <= z. - For each valid triplet (x, y, z) that sums to target, count the number of ways using combinatorial formulas: All distinct counts (x != y != z) / count(z). - Two numbers the same (x == y != z) for the repeated element. - All three the same: use nC3. - Use modular arithmetic MOD = 10^9 + 7 at every step to avoid overflow. Space & Time Time Complexity: O(N^2), where N = 101 (the range of possible numbers), which is efficient given the constraints. Space Complexity: O(M) for the frequency array.	Solution The solution first counts the frequency of each number in the array. Then it iterates through all valid triplets (x, y, z) where x <= y <= z and checks if they sum up to the target. Depending on whether x, y, and z are distinct or have duplicates, the combination count is computed accordingly. - If x, y, and z are all the same, compute the combination as nC3. - If only two are the same, compute as nC2 multiplied by the count of the third number. - If all are distinct, use the direct product of the counts. - When lengths differ by one, use pointers for both strings. Upon encountering a difference, increment the pointer for the longer string until and ensure that no previous difference has been encountered. If a second discrepancy is found, return false. The key is to handle the edge case where the difference is at the end of the string. #966 Interval List Intersections [Medium] - Two Pointers Key Insights - Use two pointers to traverse both lists simultaneously. - Determine the overlapping interval by taking the maximum of the start points and the minimum of the end points. - If the overlapping condition (start <= end) is met, add the intersection to the result. - Move the pointer that has the smaller end value to explore further potential intersections efficiently. - Achieve an overall time complexity of O(n + m), where n and m are the lengths of the two interval lists.	Space & Time Time Complexity: O(n + m) where n and m are the lengths of firstList and secondList respectively. Space Complexity: O(1) extra space (excluding the space used for the output). Solution The solution uses two pointers approach. Initialize two pointers, one for each list, and iterate through both lists. For each pair of intervals, the potential intersection is computed by: - Calculating the maximum of the two start values. - Calculating the minimum of the two end values. - If the maximum start is less than or equal to the minimum end, there is an intersection, and it is added to the result list. - The pointer corresponding to the interval with the smaller end value is then incremented since that interval cannot intersect with any further intervals from the other list. This process repeats until one of the lists is fully traversed. #1055 Shortest Way to Form String [Medium] - Two Pointers Key Insights - Check if every character in target exists in source; if not, the answer is -1.	Use a greedy two-pointer strategy: iterate over target while scanning source for matching characters. During each pass over source, match as many characters as possible from target. Count the number of passes (subsequences) required until the target is completely matched. An optimized approach may precompute indices for binary search; however, the basic greedy simulation is efficient for the given constraints. Space & Time Time Complexity: O(n * m) in the worst-case, where n = length of source and m = length of target. Space Complexity: O(1) for the greedy simulation (O(n) for additional data structures for binary search are used). Solution The solution uses a greedy two-pointer approach. We simulate the process of reading the target by repeatedly scanning through the source. Each time we find a character in target that is present in the source, we treat it as a subsequence concatenated to form the target. A pointer in the target moves forward whenever a matching character is found in source. If a complete pass through source does not advance the target pointer, then it is impossible to form the target and we return -1. The algorithm counts the number of passes required until the target is fully matched.	#2563 Count the Number of Fair Pairs [Medium] - Two Pointers Key Insights - Sorting the array simplifies searching for pairs with specific value limits. - For each element, binary search is used to locate: The first index where the element makes the sum >= upper. - The last index where the element makes the sum <= upper. - This avoids the need for a nested loop through the entire array, yielding a more efficient solution. Space & Time Time Complexity: O(n log n), primarily due to sorting and (for each element) binary search operations. Space Complexity: O(1) (n log n) since we sort a copy of the array. Solution The solution starts by sorting the input array. For each element at index i in the sorted array, we search for indices (j) where j > i such that the sum of nums[i] and nums[j] falls between lower and upper. Two binary search operations are performed: - To find the smallest index j where nums[i] + nums[j] >= lower. - To find the largest index j where nums[i] + nums[j] <= upper. - Subtracting the two positions (and	summing the counts for each j) gives the total number of fair pairs. Edge cases (like no valid pair) are automatically handled by the binary search approach. #3 Longest Substring Without Repeating Characters [Medium] - Sliding Window Key Insights - Use the sliding window technique to maintain a window of unique characters. - Use a hash table (or dictionary) to quickly check for duplicate characters and update window boundaries. - The window is expanded by moving a pointer (right) and contracted by moving another pointer (left) when duplicates are encountered. - Time complexity can be maintained at O(n) by ensuring each character is processed a limited number of times. Space & Time Time Complexity: O(n), where n is the length of the input string. Space Complexity: O(min(n, m)), where m is the size of the character set (constant for fixed character sets). Solution The solution uses a sliding window technique with two pointers: left and right. The window expands as the right pointer moves, keeping track of the current substring without repeating characters. A hash table
(dictionary or map) is used to store the most recent index of each character encountered. As the right pointer moves forward, if a duplicate character is found within the current window, the left pointer is advanced to the position right after where the duplicate was last seen. This ensures that the window always contains unique characters. The maximum length is updated throughout the process. #159 Longest Substring with At Most Two Distinct Characters [Medium] - Sliding Window Key Insights - Use a sliding window to maintain a contiguous substring. - Keep track of character frequencies within the current window using a hash map or dictionary. - When the window contains more than two distinct characters, shrink the window from the left until only two remain. - Update the maximum length each time the window satisfies the condition. Space & Time Time Complexity: O(n) where n is the length of the string, since each character is processed at most twice. Space Complexity: O(n) because the hash map holds at most 2 entries (usually up to 2 distinct characters).	Solution We use the sliding window technique with two pointers (left and right) to represent the current window. A hash table (or dictionary) records the count of each character inside the window. As we extend the right pointer, we update the count. If the hash table contains more than two distinct characters, we start moving the left pointer to reduce the number of distinct characters until we have at most two distinct keys. The length of the current valid window is then used to update our maximum length answer. #340 Longest Substring with At Most K Distinct Characters [Medium] - Sliding Window Key Insights - Use the sliding window technique to efficiently scan through the string. - Maintain a hash table (or dictionary) that keeps track of the frequency of characters in the current window. - When the number of distinct characters exceeds k, increment the left pointer to shrink the window until the condition is met. - Update the maximum length of valid substrings throughout the process. Space & Time	Time Complexity: O(n) where n is the length of the string, as each character is processed at most twice (once when expanding the window and once when contracting it). Space Complexity: O(min(n, k)), where k is the size of the character (or number of unique characters in s), since at most k + 1 keys are stored. Solution This problem is solved using the sliding window technique. The algorithm keeps track of a window defined by two indices (left and right pointers). A hash map is used to count the frequency of each character within the current window. As the right pointer extends the window, the count of the character is incremented. When the count of distinct keys in the map exceeds k, the left pointer is moved forward while decrementing the count of the leftmost character, until the condition is restored. The maximum window length encountered is recorded and returned as the result. #424 Longest Repeating Character Replacement [Medium] - Sliding Window Key Insights - Use a Sliding Window algorithm to keep track of a contiguous substring. - Maintain a frequency count of letters in the current window.	Keep track of the count of the most frequent character in the window. If the current window size minus the maximum frequency is greater than k, shrink the window. The maximum window size seen during the process is the answer. Space & Time Time Complexity: O(n) where n is the length of the string, since the window traverses the string in linear time. Space Complexity: O(1) because the frequency count for letters (A-Z) has a constant size. Solution The problem is solved using the sliding window technique. We initialize two pointers representing the left and right bounds of the current window. As we expand the window by moving the right pointer, we keep the frequency of each character in a hash map. The pointer and track the letter that appears most frequently. The key observation is that the number of characters that need to be replaced in the current window is the window's size minus the count of the most frequently occurring letter. If this number exceeds k, we increment the left pointer to shrink the window until the condition is satisfied again. The maximum size of the window during the process gives the answer.	#438 Find All Anagrams in a String [Medium] - Sliding Window Key Insights - Use a sliding window of length equal to p over s. - Maintain a frequency count of characters in p and within the current window in s. - Compare frequency counts to determine if the current window is an anagram. - Update the window efficiently by adding one character and removing the character that goes out of the window. Space & Time Time Complexity: O(n) where n is the length of s. Space Complexity: O(1) since we use fixed-size frequency arrays or hash maps. Solution We use the sliding window technique to iterate over s with a window size equal to the length of p. First, count the frequencies of characters in p. Then, iterate over s and update a frequency count for the current window. When the window size equals the length of p, compare the two frequency counts. If they match, record the start index of the window. If the window exceeds k, increment the count for the incoming character and decrement the count for the outgoing character. This way, we achieve an O(1) solution that is optimal for the problem constraints.	#487 Max Consecutive Ones II [Medium] - Sliding Window Key Insights - Utilize a sliding window to maintain the current sequence of 1s. - The window can contain at most one 0. - Expand the window with the right pointer and contract with the left pointer when the constraint is violated. - The maximum window size observed during this process is the desired result. Space & Time Time Complexity: O(n) where n is the number of elements in the array. Space Complexity: O(1). Solution We use a sliding window approach to efficiently find the longest contiguous subarray that contains at most one 0. Two pointers (left and right) define the window. As we iterate with the right pointer, counting zeros in the window, we adjust the left pointer when the count of zeros exceeds one. The length of the valid window gives us the maximum number of consecutive 1's (converting one 0 to 1), and we update the maximum length accordingly.
Dictionary or map) is used to store the most recent index of each character encountered. As the right pointer moves forward, if a duplicate character is found within the current window, the left pointer is advanced to the position right after where the duplicate was last seen. This ensures that the window always contains unique characters. The maximum length is updated throughout the process. #159 Longest Substring with At Most Two Distinct Characters [Medium] - Sliding Window Key Insights - Use a sliding window to maintain a contiguous substring. - Keep track of character frequencies within the current window using a hash map or dictionary. - When the window contains more than two distinct characters, shrink the window from the left until only two remain. - Update the maximum length each time the window satisfies the condition. Space & Time Time Complexity: O(n) where n is the length of the string, since each character is processed at most twice. Space Complexity: O(n) because the hash map holds at most 2 entries (usually up to 2 distinct characters).	Solution We use the sliding window technique with two pointers (left and right) to represent the current window. A hash table (or dictionary) records the count of each character inside the window. As we extend the right pointer, we update the count. If the hash table contains more than two distinct characters, we start moving the left pointer to reduce the number of distinct characters until we have at most two distinct keys. The length of the current valid window is then used to update our maximum length answer. #340 Longest Substring with At Most K Distinct Characters [Medium] - Sliding Window Key Insights - Use the sliding window technique to efficiently scan through the string. - Maintain a hash table (or dictionary) that keeps track of the frequency of characters in the current window. - When the number of distinct characters exceeds k, increment the left pointer to shrink the window until the condition is met. - Update the maximum length of valid substrings throughout the process. Space & Time	Time Complexity: O(n) where n is the length of the string, as each character is processed at most twice (once when expanding the window and once when contracting it). Space Complexity: O(min(n, k)), where k is the size of the character (or number of unique characters in s), since at most k + 1 keys are stored. Solution This problem is solved using the sliding window technique. The algorithm keeps track of a window defined by two indices (left and right pointers). A hash map is used to count the frequency of each character within the current window. As the right pointer extends the window, the count of the character is incremented. When the count of distinct keys in the map exceeds k, the left pointer is moved forward while decrementing the count of the leftmost character, until the condition is restored. The maximum window length encountered is recorded and returned as the result. #424 Longest Repeating Character Replacement [Medium] - Sliding Window Key Insights - Use a Sliding Window algorithm to keep track of a contiguous substring. - Maintain a frequency count of letters in the current window.	Keep track of the count of the most frequent character in the window. If the current window size minus the maximum frequency is greater than k, shrink the window. The maximum window size seen during the process is the answer. Space & Time Time Complexity: O(n) where n is the length of the string, since the window traverses the string in linear time. Space Complexity: O(1) because the frequency count for letters (A-Z) has a constant size. Solution The problem is solved using the sliding window technique. We initialize two pointers representing the left and right bounds of the current window. As we expand the window by moving the right pointer, we keep the frequency of each character in a hash map. The pointer and track the letter that appears most frequently. The key observation is that the number of characters that need to be replaced in the current window is the window's size minus the count of the most frequently occurring letter. If this number exceeds k, we increment the left pointer to shrink the window until the condition is satisfied again. The maximum size of the window during the process gives the answer.	#438 Find All Anagrams in a String [Medium] - Sliding Window Key Insights - Use a sliding window of length equal to p over s. - Maintain a frequency count of characters in p and within the current window in s. - Compare frequency counts to determine if the current window is an anagram. - Update the window efficiently by adding one character and removing the character that goes out of the window. Space & Time Time Complexity: O(n) where n is the length of s. Space Complexity: O(1) since we use fixed-size frequency arrays or hash maps. Solution We use the sliding window technique to iterate over s with a window size equal to the length of p. First, count the frequencies of characters in p. Then, iterate over s and update a frequency count for the current window. When the window size equals the length of p, compare the two frequency counts. If they match, record the start index of the window. If the window exceeds k, increment the count for the incoming character and decrement the count for the outgoing character. This way, we achieve an O(1) solution that is optimal for the problem constraints.	#487 Max Consecutive Ones II [Medium] - Sliding Window Key Insights - Utilize a sliding window to maintain the current sequence of 1s. - The window can contain at most one 0. - Expand the window with the right pointer and contract with the left pointer when the constraint is violated. - The maximum window size observed during this process is the desired result. Space & Time Time Complexity: O(n) where n is the number of elements in the array. Space Complexity: O(1). Solution We use a sliding window approach to efficiently find the longest contiguous subarray that contains at most one 0. Two pointers (left and right) define the window. As we iterate with the right pointer, counting zeros in the window, we adjust the left pointer when the count of zeros exceeds one. The length of the valid window gives us the maximum number of consecutive 1's (converting one 0 to 1), and we update the maximum length accordingly.

#100 Find K-Length Substrings with No Repeated Characters [Medium] - Sliding Window Key Insights - Use a sliding window of fixed size k. - Track character counts within the current window using a hash table (or frequency array). - When a duplicate is found in the window, slide the window from left to remove duplicates. - Count a valid window when its size equals k and all characters are unique. - Optimize by adjusting the window immediately after counting a valid substring. Space & Time Time Complexity: O(n) where n is the length of s, as each character is visited at most twice. Space Complexity: O(1) since the frequency tracking is over a fixed set (26 lowercase letters). Solution We use a sliding window approach with two pointers: left and right. A hash table (or frequency array) tracks the occurrences of characters in the window. As we move the right pointer, we update the frequency and check for duplicates. If a duplicate is encountered, we increment the left pointer until the duplicate is removed. Once the window size exactly equals k, we have a valid substring, so we increment our count and then slide the window forward. This ensures that every possible k-length substring is examined once. Round 2 - High - Medium p.1369	#1248 Count Number of Nice Subarrays [Medium] - Sliding Window Key Insights - Convert the problem to counting subarrays with a specific 'prefix sum' value where the sum represents the count of odd numbers. - Use a hash table (or dictionary) to store the frequency of prefix sums encountered. - The number of nice subarrays ending at the current index equals the frequency of current prefix sum - k seen so far. - This approach allows you to find the answer in one pass over the array. Space & Time Time Complexity: O(n), where n is the number of elements in nums, because we traverse the array once. Space Complexity: O(n), in the worst case where each entire sum is unique and stored in the hash table. Solution We solve the problem using a prefix sum approach. First, we iterate through the array and convert it into a prefix sum representing the number of odd numbers encountered. As we compute the prefix sums, we use a Round 2 - High - Medium p.1370	#49 Group Anagrams [Medium] - Sorting Key Insights - Anagrams have the same characters when sorted alphabetically. - Sorting each string provides a unique key for grouping. - Use a hash table (dictionary) to map each sorted key to a list of its original strings. - Finally, gather all the lists from the dictionary to form the result. Space & Time Time Complexity: O(n * k log k), where n is the number of strings and k is the maximum length of a string (due to sorting each string). Solution We hash table to record how many times each prefix sum appears. For every current prefix sum value, we check how many times we have seen a prefix sum equal to current prefix sum - k. The idea is that if prefix[i] - prefix[j] equals k, then between indices i and j, there are exactly k odd numbers. This gives us a count of valid subarrays ending at the current index. Round 2 - High - Medium p.1371	#56 Merge Intervals [Medium] - Sorting Key Insights - Sort the intervals based on their start values. - Use a pointer or iteration to compare the current interval with the last merged interval. - If the current interval overlaps with the previous one, merge them by updating the end time. - Otherwise, add the current interval to the results as a new merged interval. Space & Time Time Complexity: O(n log n) due to sorting the intervals. Space Complexity: O(n) to store the merged intervals. Solution Space Complexity: O(n) for storing the grouped strings in the hash table. Solution The primary idea is to iterate through each string, sort it to obtain a key that represents its character composition, and then group the original string under this key. In a hash table, the key is formed by sorting the values of the hash table will be the groups of anagrams. This approach efficiently groups anagrams by leveraging sorting and a dictionary for constant-time lookups. Round 2 - High - Medium p.1372	#1152 Analyze User Website Visit Pattern [Medium] - Sorting Key Insights - Combine the inputs into a single list of events and sort them by timestamp. - Group the visits by each user, preserving the sorted order of events. - Generate all unique combinations of 3-sequences for each user (order matters and non-contiguous visits are allowed). - Use a dictionary (or hash map) to map each 3-sequence pattern to the set of users who visited that pattern. - The problem constraints are simple, so generating combinations per user (even using triple nested loops) is acceptable. Space & Time Time Complexity: O(n * L * L * L) where L is the number of users and L is the maximum length of visits per user (since we generate combinations of 3 visits per user). Solution We sort all events across O(n log n) for N total events. Space Complexity: O(n) where P is the number of unique 3-sequence patterns stored in the dictionary, plus O(n) for grouping the events. Round 2 - High - Medium p.1373	#3 Search in Rotated Sorted Array [Medium] - Binary Search Key Insights The array is originally sorted and then rotated at an unknown pivot. Space & Time Time Complexity: O(log n) for constructing the prefix sum array, and O(log n) per pickindex() call. Solution We use a sliding window of 300 seconds to count hits. Space & Time Time Complexity: O(n) per hit and getHits operation on average, since each hit is enqueued and later dequeued only once. Solution The solution uses a queue (or deque) data structure where each element stores a timestamp, count pair. A hit is recorded if the element's timestamp is less than or equal to the current timestamp. The queue shares the same timestamp, thus its count is incremented; otherwise, a new element is added. When getHits() is called, the algorithm removes elements from the front of the queue whose timestamp is out of the 300-second window relative to the current timestamp, and then sums the counts of the remaining elements to return the result. This ensures that only relevant hits within the past 300 minutes are counted. The design scales well when hit frequency is high because Round 2 - High - Medium p.1374										
#34 Find First and Last Position of Element in Sorted Array [Medium] - Binary Search Key Insights - The array is sorted, allowing the use of binary search. - The array is sorted, allowing the use of binary search. - The array is sorted, allowing the use of binary search. Space & Time Time Complexity: O(log n) Solution We perform a binary search while accounting for the possibility of a rotated array. At each iteration, we check if the left-to-mid portion is sorted. If it is, and the target falls within that range, we search the left half; otherwise, we search the right half. If the left half is not sorted, then the right half must be sorted and, similarly, we check if the target is in that sorted half. This approach ensures logarithmic time complexity while handling the rotation correctly. Round 2 - High - Medium p.1375	#153 Find Minimum in Rotated Sorted Array [Medium] - Binary Search Key Insights Handling edge cases where the target is not present by checking bounds. Space & Time Time Complexity: O(log n) Solution The approach is to use binary search twice: - The first binary search finds the leftmost occurrence of the target by continuing to search in the left half even after finding the target. - The second binary search finds the rightmost occurrence by searching in the right half. The algorithm maintains pointers for the current search bounds and narrows the search space using comparisons. If a duplicate is encountered, we increment the left pointer until the duplicate is removed. Once the window size exactly equals k, we have a valid substring, so we increment our count and then slide the window forward. This ensures that every possible k-length substring is examined once. Round 2 - High - Medium p.1376	#300 Longest Increasing Subsequence [Medium] - Binary Search Key Insights By comparing the middle element to the rightmost element, we can decide which half of the array contains the minimum. Space & Time Time Complexity: O(log n) Solution We use a binary search approach. Initialize two pointers, left and right, at the start and end of the array. While left is less than right, calculate the middle index. If the middle element is greater than the right element, then the target is in the right half; move the left pointer to mid + 1; otherwise, the minimum must be in the left half including mid, so adjust the right pointer to mid. When the loop terminates, left equals right and points to the minimum element. This approach leverages the properties of the rotated sorted array to achieve logarithmic time complexity. Round 2 - High - Medium p.1377	#62 Design Hit Counter [Medium] - Binary Search Key Insights - Using binary search and a dp array, we can achieve O(n log n) time. - The dp array maintains the smallest possible last increasing subsequence of various lengths. - For each number, perform binary search to decide if it can extend or replace a value in dp. Space & Time Time Complexity: O(n log n) where n is the length of nums Solution We use a dynamic programming approach combined with binary search. The idea is to maintain a dp array where dp[i] holds the smallest last value for any increasing subsequence with length i + 1. For each number in the array, we perform a binary search on dp to find its correct insertion position: - If the number is larger than all elements, we append it, effectively extending the current longest subsequence. - Otherwise, we replace the first element in dp that is greater than or equal to the current number. This keeps the tail as small as possible. This process ensures that dp remains sorted and its length grows the length of the longest increasing subsequence. Round 2 - High - Medium p.1378	#1060 Missing Element in Sorted Array [Medium] - Binary Search Key Insights - The array is sorted and every element is unique. - Any index i with the number of missing numbers up to i that can be computed as num[i] - num[0] - 1. - When missing[i] is less than k, the kth missing element is further to the right. - Use binary search to find the smallest index where the count of missing numbers is greater than or equal to k. - If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Space & Time Time Complexity: O(n) Solution We simulate the matrix iteration through the matrix and swap each element (i, j) with the element (j, i) for j > i - 1. Reverse each row after the transpose. Check the key is to realize that the transpose followed by a reversal of each row achieves the rotation without needing extra space. Round 2 - High - Medium p.1379	#1062 Repeating Substring [Medium] - Binary Search Key Insights Boundaries indicate the current submatrix to traverse. You iterate as follows: - Traverse from left to right along the top boundary. - Traverse downward along the right boundary. - If the top boundary has not passed the bottom, traverse from left to right along the bottom boundary. - If the left boundary has not passed the right, traverse upward along the left boundary. After each traversal, the boundaries are adjusted accordingly. This continues until all elements have been visited. Space & Time Time Complexity: O(n^2) Solution We use a binary search to find the smallest index where the count of missing numbers is greater than or equal to k. If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Round 2 - High - Medium p.1380	#531 Linear Pixel I [Medium] - Matrix Key Insights - Count the number of 'W' pixels in each row. - Count the number of 'B' pixels in each column. - A pixel is considered lonely if the count in its corresponding row and column is exactly 1. - To efficiently solve the problem, one can use row and column checking conditions. Space & Time Time Complexity: O(m * n) Solution The solution works by first scanning the entire matrix to compute the number of black pixels in each row and each column using two arrays. Once these counts are available, a second pass scans through the matrix Round 2 - High - Medium p.1381	#981 Time Based Key-Value Store [Medium] - Binary Search Key Insights ensures an O(nlog(n)) solution. Space & Time Time Complexity: O(n log n) Solution We use a hash table to store keys mapping to a list of their timestamps and corresponding values. Since the timestamps are inserted in strictly increasing order, the list remains sorted. For the get operation, a binary search is applied to quickly locate the appropriate value. Round 2 - High - Medium p.1382	#1011 Capacity to Ship Packages Within D Days [Medium] - Binary Search Key Insights - The minimal possible capacity is the maximum value in weights; no ship can carry a package heavier than its capacity. - The maximum possible capacity is the sum of all weights; this allows shipping all packages in one go. - The problem is monotonic: if a capacity C works, any capacity greater than C will also work. - Use binary search on the capacity range and a greedy approach to simulate shipping for each candidate capacity. Space & Time Time Complexity: O(n * log(sum(weights))) where n is the number of packages. Solution The solution employs binary search to find the minimum ship capacity. Start by setting the search bounds: the lower bound is the maximum weight (since each package must be shipped individually if needed) and the upper bound is the sum of all weights (shipping everything in one go). For each midpoint capacity in the binary search, use a greedy method to simulate the shipping process: accumulating weights until adding another package would exceed the candidate ship capacity, at which point you increment the day counter. If the number of days required exceeds D, the capacity is insufficient and the lower bound is increased; otherwise, the upper bound is decreased. Continue until the bounds converge. Round 2 - High - Medium p.1383	#1060 Missing Element in Sorted Array [Medium] - Binary Search Key Insights - The array is sorted and every element is unique. - Any index i with the number of missing numbers up to i that can be computed as num[i] - num[0] - 1. - When missing[i] is less than k, the kth missing element is further to the right. - Use binary search to find the smallest index where the count of missing numbers is greater than or equal to k. - If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Space & Time Time Complexity: O(n) Solution We simulate the matrix iteration through the matrix and swap each element (i, j) with the element (j, i) for j > i - 1. Reverse each row after the transpose. Check the key is to realize that the transpose followed by a reversal of each row achieves the rotation without needing extra space. Round 2 - High - Medium p.1384	#54 Spiral Matrix [Medium] - Matrix Key Insights - Four boundaries: top, bottom, left, and right to track the current layer. - Traverse right across the top row, then down the right column, then left on the bottom row, and finally up the left column. - After each direction, adjust the corresponding boundary to move inward. - Continue the traversal until the boundaries cross. Space & Time Time Complexity: O(n^2) Solution We use a binary search to find the smallest index where the count of missing numbers is greater than or equal to k. If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Round 2 - High - Medium p.1385	#59 Spiral Matrix II [Medium] - Matrix Key Insights - Use four pointers: top, bottom, left, right to keep track of the matrix boundaries. - Traverse the matrix in a spiral: move right along the top row, then down the right column, left along the bottom row, and finally up the left column. - Update the boundary pointers after each complete traversal of a side. - Continue until all numbers from 1 to n^2 are filled into the matrix. Space & Time Time Complexity: O(n^2) Solution We use a binary search to find the smallest index where the count of missing numbers is greater than or equal to k. If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Round 2 - High - Medium p.1386	#46 Minimum Path Sum [Medium] - Dynamic Programming Key Insights - The problem can be solved using Dynamic Programming. - The optimal solution for each cell depends on the minimum path sum of the cell above and to the left and the cell to the right. - Since you can only move right or down, only two adjacent cells affect the current cell's result. - Edge cases include the first row and first column, which have only one direction of movement. Space & Time Time Complexity: O(m * n) Solution We use a recursive approach to validate the BST property. We maintain two values, low and high, representing the valid range for the current node's value. For the left child, the valid range becomes (low - 1 and high) for the right child, it becomes (low and high). By checking if each node's value falls within its Round 2 - High - Medium p.1387	#981 Time Based Key-Value Store [Medium] - Binary Search Key Insights Alternative approaches include dynamic programming and suffix arrays, but the binary search with rolling hash is efficient and conceptually clean. Space & Time Time Complexity: O(n log n) on average, where n is the length of the string. (Each binary search step takes O(n) time for computing rolling hashes and O(1) for the search. Space Complexity: O(n) for storing hash values in the hash set. Solution The solution uses binary search to decide on the candidate length L of the repeating substring. For each candidate length L, we use a rolling hash to compute hash values for all substrings of length L and store them in a hash set. If any hash is repeated, it confirms the presence of a repeating substring of length L, and we try a longer length. Otherwise, we decrease the candidate length. The rolling hash is computed using a base (26) for lowercase letters and a modulus (2^32 to limit integer overflow) which allows efficient hash recomputation for sliding windows. This approach efficiently narrows down the maximum repeating substring length. Round 2 - High - Medium p.1388	#531 Find the Index of the Large Integer [Medium] - Binary Search Key Insights - We simulate the spiral movement by initializing four pointers: top, bottom, left, and right, which denote the current boundaries of the matrix that have not yet been traversed. - Traverse from left to right along the top boundary. - Traversal from top to bottom along the right boundary. - Traversal from right to left along the bottom boundary. - Traversal from bottom to top along the left boundary. After each traversal, the boundaries are adjusted accordingly. This continues until all elements have been visited. Space & Time Time Complexity: O(n^2) Solution We use a binary search to find the smallest index where the count of missing numbers is greater than or equal to k. If all missing numbers before the last array element are counted and the kth missing still hasn't been reached, calculate the result by continuing past the last element. Round 2 - High - Medium p.1389	#46 Minimum Path Sum [Medium] - Dynamic Programming Key Insights - The problem can be solved using Dynamic Programming. - The optimal solution for each cell depends on the minimum path sum of the cell above and to the left and the cell to the right. - Since you can only move right or down, only two adjacent cells affect the current cell's result. - Edge cases include the first row and first column, which have only one direction of movement. Space & Time Time Complexity: O(m * n) Solution We use a recursive approach to validate the BST property. We maintain two values, low and high, representing the valid range for the current node's value. For the left child, the valid range becomes (low - 1 and high) for the right child, it becomes (low and high). By checking if each node's value falls within its Round 2 - High - Medium p.1390
Time Complexity: O(m * n), where m and n are the number of rows and columns. Space Complexity: O(1) for the DP table (this can be optimized to O(1) with in-place computations). Solution We use a Dynamic Programming (DP) approach where we create a DP table (or use the grid itself) that stores the minimum path sum to each cell. For each cell (i, j): - If i = 0 (first row), the only possible path is from the left. - If j = 0 (first column), the only possible path is from above. - For other cells, the minimum path sum is the cell value plus the minimum of the two possible previous cells (above and left). This ensures that by the time we reach the bottom-right cell, we have accumulated the minimum sum required to reach that cell. Round 2 - High - Medium p.1391	#73 Set Matrix Zeroes [Medium] - Matrix Key Insights - The challenge is to mark rows and columns that need to be zeroed without using extra space. - A common trick is to use the first row and first column as markers. - A special case is needed for the first row and first column, as they are also used as markers. Space & Time Time Complexity: O(m * n) Solution We use a two-dimensional dynamic programming approach. We define a dp array where dp[i][j] represents the side length of the largest square submatrix of 1s ending at (i, j). The recurrence relation is: dp[i][j] = min(dp[i-1][j], dp[i][j-1]) + 1 if both dp[i-1][j] and dp[i][j-1] are non-zero, otherwise it's 1. The maximum count recorded in the dp array is the largest overlap achievable by any translation. This approach avoids simulating every possible shift over the matrix and focuses only on relative alignments of 1's. Round 2 - High - Medium p.1392	#74 Search a 2D Matrix [Medium] - Matrix Key Insights - The matrix is essentially a flattened sorted array due to its properties. - Use binary search to efficiently determine if the target exists. - Map the 1D binary search index to the corresponding 2D matrix coordinates using division and modulus operations. - Achieve O(log(m*n)) time complexity by navigating the matrix as if it were a single sorted list. Space & Time Time Complexity: O(log(m * n)) Solution We can treat the matrix as a flattened sorted list without actually flattening it. We use the row and column indices of elements - m * n, perform binary search on indices ranging from 0 to (m * n) - 1. We calculate the corresponding row and column as row = mid / n, col = mid % n. Compare the element at matrix[row][col] with the target. If it equals target, return true; if it's less than target, search the right half; otherwise, search the left half. Round 2 - High - Medium p.1393	#221 Maximal Square [Medium] - Matrix Key Insights - Use dynamic programming to build a solution where each cell in the DP table represents the side length of the largest square submatrix of 1s ending at (i, j). - If the current cell is '1', its DP value is the minimum of the top, left, and top-left neighbors plus 1. - The square's area is the square of its maximum side length. Space & Time Time Complexity: O(m * n) Solution We use a two-dimensional dynamic programming approach. We define a dp array where dp[i][j] represents the side length of the largest square submatrix of 1s ending at (i, j). The recurrence relation is: dp[i][j] = min(dp[i-1][j], dp[i][j-1]) + 1 if both dp[i-1][j] and dp[i][j-1] are non-zero, otherwise it's 1. The maximum count recorded in the dp array is the largest overlap achievable by any translation. This approach avoids simulating every possible shift over the matrix and focuses only on relative alignments of 1's. Round 2 - High - Medium p.1394	#311 Sparse Matrix Multiplication [Medium] - Matrix Key Insights - Exploit sparsity by iterating only over non-zero elements. - For each non-zero element in mat[i], multiply it with the corresponding non-zero elements in mat[j]. - Accumulate the product into the result matrix. - This approach reduces unnecessary multiplication operations when many elements are zero. Space & Time Time Complexity: O(m * n) Solution We loop through each row of mat and for every non-zero element, we traverse the corresponding row in mat, multiplying only non-zero elements in mat[j]. This approach reduces unnecessary multiplication operations when many elements are zero. Round 2 - High - Medium p.1395	#498 Diagonal Traverse [Medium] - Matrix Key Insights - Traverse the matrix diagonally with alternating directions: upward (top-right) and downward (bottom-left). - When the traversal reaches a boundary (top, bottom, left, or right), adjust the position and change the direction. - Use simulation to process each element exactly once while managing the indices based on the current direction. Space & Time Time Complexity: O(m * n) Solution We use a recursive approach to validate the BST property. We maintain two values, low and high, representing the valid range for the current node's value. For the left child, the valid range becomes (low - 1 and high) for the right child, it becomes (low and high). By checking if each node's value falls within its Round 2 - High - Medium p.1396	#981 Time Based Key-Value Store [Medium] - Binary Search Key Insights Alternative approaches include dynamic programming and suffix arrays, but the binary search with rolling hash is efficient and conceptually clean. Space & Time Time Complexity: O(n log n) on average, where n is the length of the string. (Each binary search step takes O(n) time for computing rolling hashes and O(1) for the search. Space Complexity: O(n) for storing hash values in the hash set. Solution The solution uses binary search to decide on the candidate length L of the repeating substring. For each candidate length L, we use a rolling hash to compute hash values for all substrings of length L and store them in a hash set. If any hash is repeated, it confirms the presence of a repeating substring of length L, and we try a longer length. Otherwise, we decrease the candidate length. The rolling hash is computed using a base (26) for lowercase letters and a modulus (2^32 to limit integer overflow) which allows efficient hash recomputation for sliding windows. This approach efficiently narrows down the maximum repeating substring length. Round 2 - High - Medium p.1397	#981 Time Based Key-Value Store [Medium] - Binary Search Key Insights Alternative approaches include dynamic programming and suffix arrays, but the binary search with rolling hash is efficient and conceptually clean. Space & Time Time Complexity: O(n log n) on average, where n is the length of the string. (Each binary search step takes O(n) time for computing rolling hashes and O(1) for the search. Space Complexity: O(n) for storing hash values in the hash set. Solution The solution uses binary search to decide on the candidate length L of the repeating substring. For each candidate length L, we use a rolling hash to compute hash values for all substrings of length L and store them in a hash set. If any hash is repeated, it confirms the presence of a repeating substring of length L, and we try a longer length. Otherwise, we decrease the candidate length. The rolling hash is computed using a base (26) for lowercase letters and a modulus (2^32 to limit integer overflow) which allows efficient hash recomputation for sliding windows. This approach efficiently narrows down the maximum repeating substring length. Round 2 - High - Medium p.1398	#981 Time Based Key-Value Store [Medium] - Binary Search Key Insights Alternative approaches include dynamic programming and suffix arrays, but the binary search with rolling hash is efficient and conceptually clean. Space & Time Time Complexity: O(n log n) on average, where n is the length of the string. (Each binary search step takes O(n) time for computing rolling hashes and O(1) for the search. Space Complexity: O(n) for storing hash values in the hash set. Solution The solution uses binary search to decide on the candidate length L of the repeating substring. For each candidate length L, we use a rolling hash to compute hash values for all substrings of length L and store them in a hash set. If any hash is repeated, it confirms the presence of a repeating substring of length L, and we try a longer length. Otherwise, we decrease the candidate length. The rolling hash is computed using a base (26) for lowercase letters and a modulus (2^32 to limit integer overflow) which allows efficient hash recomputation for sliding windows. This approach efficiently narrows down the maximum repeating substring length. Round 2 - High - Medium p.1399							
row, increment the column and switch direction. When moving down/up: If at the last row, increment the column and switch direction. If at the first column, increment the row and switch direction. This process continues until all elements are added to the result array. Key Insights - Count the number of 'W' pixels in each row. - Count the number of 'B' pixels in each column. - A pixel is considered lonely if the count in its corresponding row and column is exactly 1. - To efficiently solve the problem, one can use row and column checking conditions. Space & Time Time Complexity: O(m * n) Solution The solution works by first scanning the entire matrix to compute the number of black pixels in each row and each column using two arrays. Once these counts are available, a second pass scans through the matrix Round 2 - High - Medium p.1399	determines for each black pixel if it is lonely by checking if its corresponding row and column count equals 1. The approach uses simple array data structures for tallying counts and ensures that each element is processed only a constant number of times. Key Insights - Use a simulation approach: repeatedly delete crushable candies and simulate their removal. - Count the number of candies remaining. - A pixel is considered lonely if the count in its corresponding row and column is exactly 1. - Two passes through the matrix can efficiently solve the problem: one for counting and one for checking conditions. Space & Time Time Complexity: O(m * n) Solution The solution works by first scanning the entire matrix to compute the number of black pixels in each row and each column using two arrays. Once these counts are available, a second pass scans through the matrix Round 2 - High - Medium p.1400	#723 Candy Crush [Medium] - Matrix Key Insights - Use a simulation approach: repeatedly delete crushable candies and simulate their removal. - Count the number of candies remaining. - A pixel is considered lonely if the count in its corresponding row and column is exactly 1. - Two passes through the matrix can efficiently solve the problem: one for counting and one for checking conditions. Space & Time Time Complexity: O(m * n) Solution The solution works by first scanning the entire matrix to compute the number of black pixels in each row and each column using two arrays. Once these counts are available, a second pass scans through the matrix Round 2 - High - Medium p.1401	#353 Lonely Pixel I [Medium] - Matrix Key Insights - Count the number of 'W' pixels in each row. - Count the number of 'B' pixels in each column. - A pixel is considered lonely if the count in its corresponding row and column is exactly 1. - To efficiently solve the problem, one can use row and column checking conditions. Space & Time Time Complexity: O(m * n) Solution The solution works by first scanning the entire matrix to compute the number of black pixels in each row and each column using two arrays. Once these counts are available, a second pass scans through the matrix Round 2 - High - Medium p.1402	#1198 Find Smallest Common Element in All Rows [Medium] - Matrix Key Insights Using a hash map (or dictionary) to count how many times each translation vector appears thus you compute Space & Time Time Complexity: O(n * L) Solution The solution involves iteratively scanning the board to identify candy groups that should be crushed using two passes. - Horizontal Check: For each row, check segments of 3 consecutive candies. - Vertical Check: For each column, check segments of 3 consecutive candies. If any candy qualifies, mark its position for crushing. After marking, update the board by turning all marked positions into 0. - Finally, zero out the first row or first column if needed. This approach avoids extra space usage apart from the two boolean flags while ensuring that the matrix is Round 2 - High - Medium p.1403	#221 Maximal Square [Medium] - Matrix Key Insights - Use dynamic programming to build a solution where each cell in the DP table represents the side length of the largest square submatrix of 1s ending at (i, j). - If the current cell is '1', its DP value is the minimum of the top, left, and top-left neighbors plus 1. - The square's area is the square of its maximum side length. Space & Time Time Complexity: O(m * n) Solution We use a two-dimensional dynamic programming approach. We define a dp array where dp[i][j] represents the side length of the largest square submatrix of 1s ending at (i, j). The recurrence relation is: dp[i][j] = min(dp[i-1][j], dp[i][j-1]) + 1 if both dp[i-1][j] and dp[i][j-1] are non-zero, otherwise it's 1. The maximum count recorded in the dp array is the largest overlap achievable by any translation. This approach avoids simulating every possible shift over the matrix and focuses only on relative alignments of 1's. Round 2 - High - Medium p.1404	#311 Sparse Matrix Multiplication [Medium] - Matrix Key Insights - Exploit sparsity by iterating only over non-zero elements. - For each non-zero element in mat[i], multiply it with the corresponding non-zero elements in mat[j]. - Accumulate the product into the result matrix. - This approach reduces unnecessary multiplication operations when many elements are zero. Space & Time Time Complexity: O(m * n) Solution We loop through each row of mat and for every non-zero element, we traverse the corresponding row in mat, multiplying only non-zero elements in mat[j]. This approach reduces unnecessary multiplication operations when many elements are zero. Round 2 - High - Medium p.1405	#498 Diagonal Traverse [Medium] - Matrix Key Insights - Traverse the matrix diagonally with alternating directions: upward (top-right) and downward (bottom-left). - When the traversal reaches a boundary (top, bottom, left, or right), adjust the position and change the direction.								

[illegible]

Round 3 - High - Hard	p.1513	Round 3 - High - Hard	p.1514	Round 3 - High - Hard	p.1515	Round 3 - High - Hard	p.1516	Round 3 - High - Hard	p.1517	Round 3 - High - Hard	p.1518
-----------------------	--------	-----------------------	--------	-----------------------	--------	-----------------------	--------	-----------------------	--------	-----------------------	--------

Round 2 - Minib - Used	n1510	Round 2 - Minib - Used	n1520	Round 2 - Minib - Used	n1521	Round 2 - Minib - Used	n1522	Round 2 - Minib - Used	n1523	Round 2 - Minib - Used	n1524
------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------




[illegible]

Country	Year	Value
Algeria	2010	0.00
Algeria	2011	0.00
Algeria	2012	0.00
Algeria	2013	0.00
Algeria	2014	0.00
Algeria	2015	0.00
Algeria	2016	0.00
Algeria	2017	0.00
Algeria	2018	0.00
Algeria	2019	0.00
Algeria	2020	0.00
Algeria	2021	0.00
Algeria	2022	0.00
Algeria	2023	0.00
Algeria	2024	0.00
Algeria	2025	0.00
Algeria	2026	0.00
Algeria	2027	0.00
Algeria	2028	0.00
Algeria	2029	0.00
Algeria	2030	0.00
Algeria	2031	0.00
Algeria	2032	0.00
Algeria	2033	0.00
Algeria	2034	0.00
Algeria	2035	0.00
Algeria	2036	0.00
Algeria	2037	0.00
Algeria	2038	0.00
Algeria	2039	0.00
Algeria	2040	0.00
Algeria	2041	0.00
Algeria	2042	0.00
Algeria	2043	0.00
Algeria	2044	0.00
Algeria	2045	0.00
Algeria	2046	0.00
Algeria	2047	0.00
Algeria	2048	0.00
Algeria	2049	0.00
Algeria	2050	0.00
Algeria	2051	0.00
Algeria	2052	0.00
Algeria	2053	0.00
Algeria	2054	0.00
Algeria	2055	0.00
Algeria	2056	0.00
Algeria	2057	0.00
Algeria	2058	0.00
Algeria	2059	0.00
Algeria	2060	0.00
Algeria	2061	0.00
Algeria	2062	0.00
Algeria	2063	0.00
Algeria	2064	0.00
Algeria	2065	0.00
Algeria	2066	0.00
Algeria	2067	0.00
Algeria	2068	0.00
Algeria	2069	0.00
Algeria	2070	0.00
Algeria	2071	0.00
Algeria	2072	0.00
Algeria	2073	0.00
Algeria	2074	0.00
Algeria	2075	0.00
Algeria	2076	0.00
Algeria	2077	0.00
Algeria	2078	0.00
Algeria	2079	0.00
Algeria	2080	0.00
Algeria	2081	0.00
Algeria	2082	0.00
Algeria	2083	0.00
Algeria	2084	0.00
Algeria	2085	0.00
Algeria	2086	0.00
Algeria	2087	0.00
Algeria	2088	0.00
Algeria	2089	0.00
Algeria	2090	0.00
Algeria	2091	0.00
Algeria	2092	0.00
Algeria	2093	0.00
Algeria	2094	0.00
Algeria	2095	0.00
Algeria	2096	0.00
Algeria	2097	0.00
Algeria	2098	0.00
Algeria	2099	0.00
Algeria	2100	0.00
Algeria	2101	0.00
Algeria	2102	0.00
Algeria	2103	0.00
Algeria	2104	0.00
Algeria	2105	0.00
Algeria	2106	0.00
Algeria	2107	0.00
Algeria	2108	0.00
Algeria	2109	0.00
Algeria	2110	0.00
Algeria	2111	0.00
Algeria	2112	0.00
Algeria	2113	0.00
Algeria	2114	0.00
Algeria	2115	0.00
Algeria	2116	0.00
Algeria	2117	0.00
Algeria	2118	0.00
Algeria	2119	0.00
Algeria	2120	0.00
Algeria	2121	0.00
Algeria	2122	0.00

Country	Year	Population (millions)	Urban population (millions)	Urban population (%)	Population density (per sq km)	Population density (per sq mile)
Algeria	2000	24.0	11.0	45.8	10.0	26.0
Algeria	2005	26.0	12.0	46.2	10.0	26.0
Algeria	2010	28.0	13.0	46.4	10.0	26.0
Algeria	2015	30.0	14.0	46.7	10.0	26.0
Algeria	2020	32.0	15.0	46.9	10.0	26.0
Algeria	2025	34.0	16.0	47.1	10.0	26.0
Algeria	2030	36.0	17.0	47.2	10.0	26.0
Algeria	2035	38.0	18.0	47.4	10.0	26.0
Algeria	2040	40.0	19.0	47.5	10.0	26.0
Algeria	2045	42.0	20.0	47.6	10.0	26.0
Algeria	2050	44.0	21.0	47.7	10.0	26.0
Algeria	2055	46.0	22.0	47.8	10.0	26.0
Algeria	2060	48.0	23.0	47.9	10.0	26.0
Algeria	2065	50.0	24.0	48.0	10.0	26.0
Algeria	2070	52.0	25.0	48.1	10.0	26.0
Algeria	2075	54.0	26.0	48.1	10.0	26.0
Algeria	2080	56.0	27.0	48.2	10.0	26.0
Algeria	2085	58.0	28.0	48.3	10.0	26.0
Algeria	2090	60.0	29.0	48.3	10.0	26.0
Algeria	2095	62.0	30.0	48.4	10.0	26.0
Algeria	2100	64.0	31.0	48.4	10.0	26.0
Algeria	2105	66.0	32.0	48.5	10.0	26.0
Algeria	2110	68.0	33.0	48.5	10.0	26.0
Algeria	2115	70.0	34.0	48.6	10.0	26.0
Algeria	2120	72.0	35.0	48.6	10.0	26.0
Algeria	2125	74.0	36.0	48.7	10.0	26.0
Algeria	2130	76.0	37.0	48.7	10.0	26.0
Algeria	2135	78.0	38.0	48.8	10.0	26.0
Algeria	2140	80.0	39.0	48.8	10.0	26.0
Algeria	2145	82.0	40.0	48.9	10.0	26.0
Algeria	2150	84.0	41.0	48.9	10.0	26.0
Algeria	2155	86.0	42.0	49.0	10.0	26.0
Algeria	2160	88.0	43.0	49.0	10.0	26.0
Algeria	2165	90.0	44.0	49.1	10.0	26.0
Algeria	2170	92.0	45.0	49.1	10.0	26.0
Algeria	2175	94.0	46.0	49.2	10.0	26.0
Algeria	2180	96.0	47.0	49.2	10.0	26.0
Algeria	2185	98.0	48.0	49.3	10.0	26.0
Algeria	2190	100.0	49.0	49.3	10.0	26.0
Algeria	2195	102.0	50.0	49.4	10.0	26.0
Algeria	2200	104.0	51.0	49.4	10.0	26.0
Algeria	2205	106.0	52.0	49.5	10.0	26.0
Algeria	2210	108.0	53.0	49.5	10.0	26.0
Algeria	2215	110.0	54.0	49.6	10.0	26.0
Algeria	2220	112.0	55.0	49.6	10.0	26.0
Algeria	2225	114.0	56.0	49.7	10.0	26.0
Algeria	2230	116.0	57.0	49.7	10.0	26.0
Algeria	2235	118.0	58.0	49.8	10.0	26.0
Algeria	2240	120.0	59.0	49.8	10.0	26.0
Algeria	2245	122.0	60.0	49.9	10.0	26.0
Algeria	2250	124.0	61.0	49.9	10.0	26.0
Algeria	2255	126.0	62.0	50.0	10.0	26.0
Algeria	2260	128.0	63.0	50.0	10.0	26.0

Country	Year	Value
Algeria	2000	0.00
Algeria	2001	0.00
Algeria	2002	0.00
Algeria	2003	0.00
Algeria	2004	0.00
Algeria	2005	0.00
Algeria	2006	0.00
Algeria	2007	0.00
Algeria	2008	0.00
Algeria	2009	0.00
Algeria	2010	0.00
Algeria	2011	0.00
Algeria	2012	0.00
Algeria	2013	0.00
Algeria	2014	0.00
Algeria	2015	0.00
Algeria	2016	0.00
Algeria	2017	0.00
Algeria	2018	0.00
Algeria	2019	0.00
Algeria	2020	0.00
Algeria	2021	0.00
Algeria	2022	0.00
Algeria	2023	0.00
Algeria	2024	0.00
Algeria	2025	0.00
Algeria	2026	0.00
Algeria	2027	0.00
Algeria	2028	0.00
Algeria	2029	0.00
Algeria	2030	0.00
Algeria	2031	0.00
Algeria	2032	0.00
Algeria	2033	0.00
Algeria	2034	0.00
Algeria	2035	0.00
Algeria	2036	0.00
Algeria	2037	0.00
Algeria	2038	0.00
Algeria	2039	0.00
Algeria	2040	0.00
Algeria	2041	0.00
Algeria	2042	0.00
Algeria	2043	0.00
Algeria	2044	0.00
Algeria	2045	0.00
Algeria	2046	0.00
Algeria	2047	0.00
Algeria	2048	0.00
Algeria	2049	0.00
Algeria	2050	0.00
Algeria	2051	0.00
Algeria	2052	0.00
Algeria	2053	0.00
Algeria	2054	0.00
Algeria	2055	0.00
Algeria	2056	0.00
Algeria	2057	0.00
Algeria	2058	0.00
Algeria	2059	0.00
Algeria	2060	0.00
Algeria	2061	0.00
Algeria	2062	0.00
Algeria	2063	0.00
Algeria	2064	0.00
Algeria	2065	0.00
Algeria	2066	0.00
Algeria	2067	0.00
Algeria	2068	0.00
Algeria	2069	0.00
Algeria	2070	0.00
Algeria	2071	0.00
Algeria	2072	0.00
Algeria	2073	0.00
Algeria	2074	0.00
Algeria	2075	0.00
Algeria	2076	0.00
Algeria	2077	0.00
Algeria	2078	0.00
Algeria	2079	0.00
Algeria	2080	0.00
Algeria	2081	0.00
Algeria	2082	0.00
Algeria	2083	0.00
Algeria	2084	0.00
Algeria	2085	0.00
Algeria	2086	0.00
Algeria	2087	0.00
Algeria	2088	0.00
Algeria	2089	0.00
Algeria	2090	0.00
Algeria	2091	0.00
Algeria	2092	0.00
Algeria	2093	0.00
Algeria	2094	0.00
Algeria	2095	0.00
Algeria	2096	0.00
Algeria	2097	0.00
Algeria	2098	0.00
Algeria	2099	0.00
Algeria	2100	0.00
Algeria	2101	0.00
Algeria	2102	0.00
Algeria	2103	0.00
Algeria	2104	0.00
Algeria	2105	0.00
Algeria	2106	0.00
Algeria	2107	0.00
Algeria	2108	0.00
Algeria	2109	0.00
Algeria	2110	0.00
Algeria	2111	0.00
Algeria	2112	0.00

Sheet 3 of 7 Round 3 - High - Hard

#329 Longest Increasing Path in a Matrix LeetCode - SimplifyLet - WalkCC - LeetCode Array - DFS - BFS - Graph - Topological Sort - Memoization - Matrix Lists: Grid 169 Time Complexity: O(m * n) - each cell is computed once due to memoization. Space Complexity: O(m * n) - space is used for the memoization cache and recursion stack. Problem Given an m x n integers matrix, return the length of the longest increasing path in matrix. From each cell, you can either move in four directions: left, right, up, or down. You may not move diagonally or move outside the boundary (i.e., wrap-around is not allowed). Example 1:  Input: matrix = [[9,9,4],[6,6,8],[2,1,1]] Output: 4 Explanation: The longest increasing path is [1, 2, 6, 9]. Example 2:  Input: matrix = [[3,4,5],[3,2,6],[2,2,1]] Output: 4 Explanation: The longest increasing path is [3, 4, 5, 6]. Moving diagonally is not allowed. Example 3: Input: matrix = [[1]] Output: 1 Constraints: m == matrix.length n == matrix[i].length Round 3 High - Hard p.1385	Python Implementation for Longest Increasing Path in a Matrix class Solution: def longestIncreasingPath(self, matrix: List[List[int]]) -> int: @cache def dfs(i: int, j: int) -> int: ans = 0 for a, b in pairwise(-1, 0, 1, 0, -1, 0): x, y = i + a, j + b if 0 <= x < m and 0 <= y < n and matrix[x][y] > matrix[i][j]: ans = max(ans, dfs(x, y)) return ans + 1 m, n = len(matrix), len(matrix[0]) return max(dfs(i, j) for i in range(m) for j in range(n)) = SimplifyLet Python Implementation for Longest Increasing Path in a Matrix class Solution: def longestIncreasingPath(self, matrix: List[List[int]]) -> int: # Return 0 if matrix is empty if not matrix or not matrix[0]: return 0 # Dimensions of the matrix m, n = len(matrix), len(matrix[0]) # Create a memoization table (same dimensions as the matrix) initialized to 0 memo = [[0] * n for _ in range(m)] # Define the DFS function to explore the matrix def dfs(i, j): # If result is already computed, return it if memo[i][j]: return memo[i][j] # Start with a path length of 1 (the cell itself) Round 3 High - Hard p.1389	the given 2D-array. Example 1:  Input: edges = [[1,2],[1,3],[2,3]] Output: [2,3] Example 2: Input: edges = [[1,2],[1,3],[2,3]] Output: [2,3] Round 3 High - Hard p.1388	DFS #685 Redundant Connection II LeetCode - SimplifyLet - WalkCC - LeetCode DFS - BFS - Union-Find - Graph Lists: Deny Zhang Time Complexity: O(n) Space Complexity: O(n) Problem In this problem, a rooted tree is a directed graph such that there is exactly one node (the root) for which all other nodes are descendants of this node, plus every node has exactly one parent, except for the root node which has no parents. The given input is a directed graph that started as a rooted tree with n nodes (with distinct values from 1 to n), with one additional directed edge added. The added edge has two different vertices chosen from 1 to n, and is not an edge that already existed. The resulting graph is given as a 2D-array of edges. Each element of edges is a pair [u, v] that represents a directed edge connecting nodes u and v, where u is a parent of child v. Return an edge that can be removed so that the resulting graph is a rooted tree of n nodes. If there are multiple answers, return the answer that occurs last in the input. Round 3 High - Hard p.1386	Brute Force Approach class Solution: def findRedundantDirectedConnection(self, edges): # Brute Force - DFS from every unvisited node def dfs(node): count = 0 def dfs(node): if node not in visited: dfs(node); count += 1 return count for node in range(1, n): if node not in visited: dfs(node); count += 1 return count = WalkCC Brute Force Approach class Solution: def findRedundantDirectedConnection(self, edges): # Brute Force - DFS from every unvisited node def dfs(node): count = 0 def dfs(node): if node not in visited: dfs(node); count += 1 return count for node in range(1, n): if node not in visited: dfs(node); count += 1 return count = WalkCC Round 3 High - Hard p.1389	Community Solutions (Python) #1392 Critical Connections in a Network LeetCode - SimplifyLet - WalkCC - LeetCode DFS - Graph - Bi-connected Component Lists: Deny Zhang Time Complexity: O(n * m) where n is the number of nodes and m is the number of connections. Space Complexity: O(m) for the graph representation and DFS recursion stack. Problem There are n servers numbered from 0 to n - 1 connected by undirected server-to-server connections forming a network where connections[i] = [a, b] represents a connection between servers a and b. Any server can reach other servers directly or indirectly through the network. A critical connection is a connection that, if removed, will make some servers unable to reach some other server. Return all critical connections in the network in any order. Example 1: Round 3 High - Hard p.1618	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1405	Brute Force (Python) class Solution: def isEscapePossible(self, blocked: List[List[int]], source: List[int], target: List[int]) -> bool: # Brute Force - DFS from every unvisited node visited = set() count = 0 def dfs(node): visited.add(node) for nb in graph.get(node, []): if nb not in visited: dfs(nb) for node in range(1, n): if node not in visited: dfs(node); count += 1 return count = SimplifyLet Brute Force (Python) class Solution: def isEscapePossible(self, blocked: List[List[int]], source: List[int], target: List[int]) -> bool: # Brute Force - DFS from every unvisited node visited = set() count = 0 def dfs(node): visited.add(node) for nb in graph.get(node, []): if nb not in visited: dfs(nb) for node in range(1, n): if node not in visited: dfs(node); count += 1 return count = SimplifyLet Round 3 High - Hard p.1407	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1406	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1407	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1408
Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1409	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1410	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1411	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1412	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1413	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1414	Community Solutions (Python) #1036 Escape a Large Maze LeetCode - SimplifyLet - WalkCC - LeetCode Array - Hash Table - DFS - BFS Lists: Deny Zhang Time Complexity: O(B * 2) in the worst case, where B is the number of blocked cells (with B <= 200). Space Complexity: O(B * 2) due to the storage of visited cells in the worst-case scenario. Problem There is a 1 million by 1 million grid on an XY-plane, and the coordinates of each blocked square are (x, y). We start at the source = [sx, sy] square and want to reach the target = [tx, ty] square. There is also an array of blocked squares, where each blocked[i] = [xi, yi] represents a blocked square with coordinates (xi, yi). Each move, we can walk one square north, east, south, or west if the square is not in the array of blocked squares. We are also not allowed to walk outside of the grid. Return true if and only if it is possible to reach the target square from the source square through a sequence of valid moves. Example 1: Round 3 High - Hard p.1415				

Graphs

#305 Number of Islands II

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Array - Hash Table - Union Find - Matrix

Lists: Premium

Time Complexity: $O(K \cdot \log n)$ where K is the number of operations and n is the inverse Ackermann function (almost constant time per union/find). Space Complexity: $O(m \cdot n)$ for storing the union-find set.

Problem

You are given an empty $2D$ binary grid grid of size $m \times n$. The grid represents a map where 0 's represent water and 1 's represent land. Initially, all the cells of grid are water cells (i.e., all the cells are 0 's).

We may perform an add land operation which turns the water at position (i, j) into a land. You are given an array positions where $positions[i] = (r_i, c_i)$ is the position (r_i, c_i) at which we should operate the i th operation.

Return an array of integers answer where $answer[i]$ is the number of islands after turning the cell (r_i, c_i) into a land.

An island is surrounded by water and is formed by connecting adjacent lands horizontally or vertically. You may assume all four edges of the grid are all surrounded by water.

Example 1:

3 → 4 → 5

3 2 6

2 2 1

Input: m = 2, n = 3, positions = [[0,0],[0,1],[1,1],[2,1]]

Output: [1,1,1,2]

Explanation:

Initially, the 2d grid is filled with water.

- Operation #0: addLand(0, 0) turns the water at grid[0][0] into a land. We have 1 island.

- Operation #1: addLand(0, 1) turns the water at grid[0][1] into a land. We still have 1 island.

- Operation #2: addLand(1, 1) turns the water at grid[1][1] into a land. We have 2 islands.

- Operation #3: addLand(2, 1) turns the water at grid[2][1] into a land. We have 3 islands.

Example 2:

Input: m = 1, n = 1, positions = [[0,0]]

Output: [1]

Constraints:

- $1 \leq m, n \leq positions.length \leq 104$
- $1 \leq m \times n \leq 104$
- $positions.length == 2$
- $0 \leq r_i < m$
- $0 \leq c_i < n$

Follow up: Could you solve it in time complexity $O(k \log(mn))$, where $k == positions.length$?

Brute Force (Python)

If Brute Force Approach

class Solution:

def numIslands(self, m, n, positions):

Brute Force - try all paths via exhaustive BFS

visited = set()

def dfs(node):

if node == dest: return True

visited.add(node)

for next in graph.get(node, []):

if next not in visited and dfs(next):

return True

return False

return dfs(src)

Community Solutions (Python)

WalshCC

class UnionFind:

def __init__(self, n, int):

self.id = [-1] * n

self.rank = [0] * n

def unionByRank(self, u, int, v, int) -> None:

u = self.find(u)

v = self.find(v)

if u == v:

return

for x, y in zip(range(n), range(n)):

if check1(x, y, j + y) and find1(x + n, j) != find1((i + x) + n + j + y):

find1(x + n, j + y) = find1((i + x) + n + j + y)

cur += 1

1 0 1

0 1 0

For above, if setting

list-row 2nd-col 0-to-1

cur will -1 for 3 times

but cur == 1 after grid[i][j] is 1 so cur final result is 1.

res.append(cur)

Round 3 - High - Hard

p.1621

Round 3 - High - Hard

p.1622

Round 3 - High - Hard

p.1623

Round 3 - High - Hard

p.1624

Round 3 - High - Hard

p.1625

Round 3 - High - Hard

p.1626

Round 3 - High - Hard

p.1627

Round 3 - High - Hard

p.1628

Round 3 - High - Hard

p.1629

Round 3 - High - Hard

p.1630

Round 3 - High - Hard

p.1631

Round 3 - High - Hard

p.1632

Round 3 - High - Hard

p.1633

Round 3 - High - Hard

p.1634

Round 3 - High - Hard

p.1635

Round 3 - High - Hard

p.1636

Round 3 - High - Hard

p.1637

Round 3 - High - Hard

p.1638

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

Graphs

#1153 String Transforms Into Another String

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Hash Table - String - Union Find

Lists: Devan Zhang

Time Complexity: $O(n)$, where n is the length of the strings, because we traverse the strings to build and check the mapping. Space Complexity: $O(1)$ or $O(26)$, which is constant space, to store the mapp

Problem

Given two strings $str1$ and $str2$ of the same length, determine whether you can transform $str1$ into $str2$ by doing zero or more conversions.

In one conversion you can convert all occurrences of one character in $str1$ to any other lowercase English character.

Return true if and only if you can transform $str1$ into $str2$.

Example 1:

Input: str1 = "abacc", str2 = "cdede"

Output: true

Explanation: Convert 'c' to 'a' then 'b' to 'd' then 'a' to 'c'. Note that the order of conversions matter.

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

Graphs

#1153 String Transforms Into Another String

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Hash Table - String - Union Find

Lists: Devan Zhang

Time Complexity: $O(n)$, where n is the length of the strings, because we traverse the strings to build and check the mapping. Space Complexity: $O(1)$ or $O(26)$, which is constant space, to store the mapp

Problem

Given two strings $str1$ and $str2$ of the same length, determine whether you can transform $str1$ into $str2$ by doing zero or more conversions.

In one conversion you can convert all occurrences of one character in $str1$ to any other lowercase English character.

Return true if and only if you can transform $str1$ into $str2$.

Example 1:

Input: str1 = "abacc", str2 = "cdede"

Output: true

Explanation: Convert 'c' to 'a' then 'b' to 'd' then 'a' to 'c'. Note that the order of conversions matter.

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

Graphs

#127 Word Ladder

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Hash Table - String - BFS

Lists: Grid 169

Time Complexity: $O(N \cdot M^2)$ where N is the number of words and M is the length of each word. Space Complexity: $O(N \cdot M)$ for the storage of intermediate mappings and the BFS queue.

Problem

A transformation sequence from word $beginWord$ to word $endWord$ using a dictionary $wordList$ is a sequence of words $beginWord \rightarrow s_1 \rightarrow s_2 \rightarrow \dots \rightarrow s_k$ such that:

- Every adjacent pair of words differs by a single letter.
- Every s_i for $1 \leq i \leq k$ is in $wordList$. Note that $beginWord$ does not need to be in $wordList$.

Return the number of words in the transformation sequence from $beginWord$ to $endWord$, or 0 if no such sequence exists.

Example 1:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot","dot","dog","lat","log","cog"]

Output: 5

Explanation: One shortest transformation sequence is "hit" -> "hot" -> "dot" -> "dog" -> "cog", which is 5 words long.

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

Graphs

#127 Word Ladder

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Hash Table - String - BFS

Lists: Grid 169

Time Complexity: $O(N \cdot M^2)$ where N is the number of words and M is the length of each word. Space Complexity: $O(N \cdot M)$ for the storage of intermediate mappings and the BFS queue.

Problem

A transformation sequence from word $beginWord$ to word $endWord$ using a dictionary $wordList$ is a sequence of words $beginWord \rightarrow s_1 \rightarrow s_2 \rightarrow \dots \rightarrow s_k$ such that:

- Every adjacent pair of words differs by a single letter.
- Every s_i for $1 \leq i \leq k$ is in $wordList$. Note that $beginWord$ does not need to be in $wordList$.

Return the number of words in the transformation sequence from $beginWord$ to $endWord$, or 0 if no such sequence exists.

Example 1:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot","dot","dog","lat","log","cog"]

Output: 5

Explanation: One shortest transformation sequence is "hit" -> "hot" -> "dot" -> "dog" -> "cog", which is 5 words long.

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

Graphs

#127 Word Ladder

LeetCode -> SimplifyLeet -> WalkCC -> LeetCode

Hash Table - String - BFS

Lists: Grid 169

Time Complexity: $O(N \cdot M^2)$ where N is the number of words and M is the length of each word. Space Complexity: $O(N \cdot M)$ for the storage of intermediate mappings and the BFS queue.

Problem

A transformation sequence from word $beginWord$ to word $endWord$ using a dictionary $wordList$ is a sequence of words $beginWord \rightarrow s_1 \rightarrow s_2 \rightarrow \dots \rightarrow s_k$ such that:

- Every adjacent pair of words differs by a single letter.
- Every s_i for $1 \leq i \leq k$ is in $wordList$. Note that $beginWord$ does not need to be in $wordList$.

Return the number of words in the transformation sequence from $beginWord$ to $endWord$, or 0 if no such sequence exists.

Example 1:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot","dot","dog","lat","log","cog"]

Output: 5

Explanation: One shortest transformation sequence is "hit" -> "hot" -> "dot" -> "dog" -> "cog", which is 5 words long.

Round 3 - High - Hard

p.1639

Round 3 - High - Hard

p.1640

Round 3 - High - Hard

p.1641

Round 3 - High - Hard

p.1642

Round 3 - High - Hard

p.1643

Round 3 - High - Hard

p.1644

Round 3 - High - Hard

p.1645

Round 3 - High - Hard

p.1646

Round 3 - High - Hard

p.1647

Round 3 - High - Hard

p.1648

Round 3 - High - Hard

p.1649

Round 3 - High - Hard

p.1650

Round 3 - High - Hard

p.1651

Round 3 - High - Hard

p.1652

Round 3 - High - Hard

p.1653

Round 3 - High - Hard

p.1654

Round 3 - High - Hard

p.1655

Round 3 - High - Hard

p.1656

#####

while at and q2:
if len(q1) <= len(q2):
Prioritize the queue with fewer elements for expansion == <2(p)
extend(n1, n2, q1)
else:
extend(n2, n1, q2)

def extend(n1, n2, q):
New round of expansion
for _ in range(len(q1)):
p = q.popleft()
for t in next(p):
if t in n1:
Already visited before
continue
The other direction has been found
return step + 1 + n2(t)
q.append(t)
n1(t) = step + 1

#137 Shortest Distance from All Buildings

LeetCode - SimpleLeet - WA:RC - LeetCode
Array - BFS - Matrix
Lists - Premium 98
Time Complexity: O(k * m * n) where k is the number of buildings and m,n are the grid dimensions. Space Complexity: O(m * n) due to the auxiliary matrices and visited state tracking used in BFS.
Problem
You are given an m x n grid grid of values 0, 1, or 2, where:
• each 0 marks an empty land that you can pass by freely,
• each 1 marks a building that you cannot pass through, and
• each 2 marks an obstacle that you cannot pass through.
You want to build a house on an empty land that reaches all buildings in the shortest travel distance. You can only move up, down, left, and right.
Return the shortest travel distance for such a house. If it is not possible to build such a house according to the above rules, return -1.

Round 3

High

Hard

p.1657

The total travel distance is the sum of the distances between the houses of the friends and the meeting point.
Example 1:

1	0	2	0	1
0	0	0	0	0
0	0	1	0	0

Input: grid = [[1,0,2,0,1]]
Output: 1
Example 2:

Input: grid = [[1]]
Output: -1
Constraints:
• m == grid.length
• n == grid[0].length
• 1 <= m, n <= 50
• grid[i][j] is either 0, 1, or 2.
• There will be at least one building in the grid.

Brute Force (Python)

• Brute Force Approach
class Solution:
def shortestDistance(self, grid):
Brute Force - BFS layer by layer
from collections import deque
queue = deque([0])
dist = [0] * n * m
steps = 0
while queue:
for _ in range(len(queue)):
Return 7
Explanation: gives three buildings at (0,0), (0,4), (2,2), and an obstacle at (0,2).
The point (1,2) is an ideal empty land to build a house, as the total travel distance of 3+0+2=7 is minimal.
So return 7.
So return 7.

Round 3

High

Hard

p.1658

node = queue.popleft()
for nb in graph[node]:
if nb not in visited:
visited.add(nb)
queue.append(nb)
steps += 1
return steps

Community Solutions (Python)
• WA:RC
class Solution:
def shortestDistance(self, grid):
List(list(int)) -> int:
DIRS = [(0, 1), (1, 0), (0, -1), (-1, 0)]
n = len(grid)
m = len(grid[0])
nbldings = sum(n1 == 1 for row in grid for a in row)
ans = math.inf
dist[i][j] is the total distance of grid[i][j] to reach all the buildings (1)
dist = [[0] * n for _ in range(m)]
for a, b in [(0, 1), (-1, 0)]:
x, y = r + a, c + b
if 0 <= x < n and 0 <= y < m and grid[x][y] == 0 and (x, y) not in visited:
cnt[x][y] = 1
dist[x][y] = 1
q.append((x, y))
vis.add((x, y))
ans = inf
for j in range(m):
for i in range(n):
if grid[i][j] == 0 and cnt[i][j] == 0:
ans = min(ans, dist[i][j])
return -1 if ans == inf else ans

Round 3

High

Hard

p.1660

If not grid[x][y]:
dist[x][y] += step
reachCount[x][y] += 1
q.append((x, y))
elif grid[x][y] == 1:
seenBuildings += 1
step += 1
True if all the buildings (1) are connected
return seenBuildings == nbldings

for i in range(n):
for j in range(m):
if grid[i][j] == 1: # BFS from this building.
if not bfs(i, j):
return -1
for i in range(n):
for j in range(m):
if reachCount[i][j] == nbldings:
ans = min(ans, dist[i][j])
return -1 if ans == math.inf else ans

#733 Sliding Puzzle

LeetCode - SimpleLeet - WA:RC - LeetCode
Array - BFS - Matrix
Lists - Premium 98
Time Complexity: O(1) in practice, since there are at most 720 states (6! permutations). Space Complexity: O(1) for the same reason, as the state space is fixed and limited.
Problem
On a 2 x 3 board, there are five tiles labeled from 1 to 5, and an empty square represented by 0. A move consists of choosing 0 and a 4-directionally adjacent number and swapping it.
The state of the board is solved if and only if the board is [[1,2,3],[4,5,0]].
Given the puzzle board board, return the least number of moves required so that the state of the board is solved. If it is impossible for the state of the board to be solved, return -1.
Example 1:

Round 3

High

Hard

p.1662

visited[x][y] = True
total_distance[x][y] += dist + 1
reachable_count[x][y] += 1
q.append((x, y, dist+1))

for i in range(n):
for j in range(m):
if grid[i][j] == 1:
total_buildings += 1
bfs(i, j)

min_distance = float('inf')
for i in range(n):
for j in range(m):
if grid[i][j] == 0 and reachable_count[i][j] == total_buildings:
min_distance = min(min_distance, total_distance[i][j])
return min_distance if min_distance != float('inf') else -1

Example test:
print(shortestDistance([[1,2,0,1],[0,0,0,0],[0,0,1,0]]))
LC:6

Brute Force (Python)

• Brute Force Approach
class Solution:
def shortestDistance(self, grid):
List(list(int)) -> int:
n = len(grid)
m = len(grid[0])
q = deque()
total = 0
cnt: how many buildings can reach (x,y)
If there is a column all blockers, then (x,y) cannot reach every building
cnt = [[0] * n for _ in range(m)]
for i in range(n):
for j in range(m):
if grid[i][j] == 1:
total += 1
q.append((i, j))
d = 0
vis = set() # reset for every free-land
while q:
d += 1
for i in range(len(q)):
r, c = q.popleft()
if nb not in visited:
visited.add(nb)
queue.append(nb)
steps += 1
return steps

Community Solutions (Python)

• SimplyLeet

Round 3

High

Hard

p.1665

for a, b in [(0, 1), (-1, 0)]:
x, y = r + a, c + b
if 0 <= x < n and 0 <= y < m and grid[x][y] == 0 and (x, y) not in visited:
cnt[x][y] = 1
dist[x][y] = 1
q.append((x, y))
vis.add((x, y))
ans = inf
for j in range(m):
for i in range(n):
if grid[i][j] == 0 and cnt[i][j] == 0:
ans = min(ans, dist[i][j])
return -1 if ans == inf else ans

Round 3

High

Hard

p.1666

1	2	3
4		5

Input: board = [[1,2,3],[4,5,0]]
Output: -1
Explanation: Swap the 0 and the 5 in one move.
Example 2:

1	2	3
5	4	

Input: board = [[1,2,3],[5,4,0]]
Output: 1
Explanation: No number of moves will make the board solved.
Example 3:

1	2	3
5		4

Input: board = [[1,2,3],[5,4,0]]
Output: 1
Explanation: No number of moves will make the board solved.
Example 3:

Round 3

High

Hard

p.1669

4	1	2
5		3

Input: board = [[4,1,2],[5,3,0]]
Output: 1
Explanation: 5 is the smallest number of moves that solves the board.
An example path:
After move 0: [[4,1,2],[5,3,0]]
After move 1: [[4,1,2],[0,3,5]]
After move 2: [[0,1,2],[4,5,3]]
After move 3: [[1,0,2],[4,5,3]]
After move 4: [[1,0,2],[4,5,3]]
After move 5: [[1,0,2],[4,5,3]]
After move 6: [[1,0,2],[4,5,3]]
After move 7: [[1,0,2],[4,5,3]]
After move 8: [[1,0,2],[4,5,3]]
After move 9: [[1,0,2],[4,5,3]]
After move 10: [[1,0,2],[4,5,3]]
After move 11: [[1,0,2],[4,5,3]]
After move 12: [[1,0,2],[4,5,3]]
After move 13: [[1,0,2],[4,5,3]]
After move 14: [[1,0,2],[4,5,3]]
After move 15: [[1,0,2],[4,5,3]]
After move 16: [[1,0,2],[4,5,3]]
After move 17: [[1,0,2],[4,5,3]]
After move 18: [[1,0,2],[4,5,3]]
After move 19: [[1,0,2],[4,5,3]]
After move 20: [[1,0,2],[4,5,3]]
After move 21: [[1,0,2],[4,5,3]]
After move 22: [[1,0,2],[4,5,3]]
After move 23: [[1,0,2],[4,5,3]]
After move 24: [[1,0,2],[4,5,3]]
After move 25: [[1,0,2],[4,5,3]]
After move 26: [[1,0,2],[4,5,3]]
After move 27: [[1,0,2],[4,5,3]]
After move 28: [[1,0,2],[4,5,3]]
After move 29: [[1,0,2],[4,5,3]]
After move 30: [[1,0,2],[4,5,3]]
After move 31: [[1,0,2],[4,5,3]]
After move 32: [[1,0,2],[4,5,3]]
After move 33: [[1,0,2],[4,5,3]]
After move 34: [[1,0,2],[4,5,3]]
After move 35: [[1,0,2],[4,5,3]]
After move 36: [[1,0,2],[4,5,3]]
After move 37: [[1,0,2],[4,5,3]]
After move 38: [[1,0,2],[4,5,3]]
After move 39: [[1,0,2],[4,5,3]]
After move 40: [[1,0,2],[4,5,3]]
After move 41: [[1,0,2],[4,5,3]]
After move 42: [[1,0,2],[4,5,3]]
After move 43: [[1,0,2],[4,5,3]]
After move 44: [[1,0,2],[4,5,3]]
After move 45: [[1,0,2],[4,5,3]]
After move 46: [[1,0,2],[4,5,3]]
After move 47: [[1,0,2],[4,5,3]]
After move 48: [[1,0,2],[4,5,3]]
After move 49: [[1,0,2],[4,5,3]]
After move 50: [[1,0,2],[4,5,3]]
After move 51: [[1,0,2],[4,5,3]]
After move 52: [[1,0,2],[4,5,3]]
After move 53: [[1,0,2],[4,5,3]]
After move 54: [[1,0,2],[4,5,3]]
After move 55: [[1,0,2],[4,5,3]]
After move 56: [[1,0,2],[4,5,3]]
After move 57: [[1,0,2],[4,5,3]]
After move 58: [[1,0,2],[4,5,3]]
After move 59: [[1,0,2],[4,5,3]]
After move 60: [[1,0,2],[4,5,3]]
After move 61: [[1,0,2],[4,5,3]]
After move 62: [[1,0,2],[4,5,3]]
After move 63: [[1,0,2],[4,5,3]]
After move 64: [[1,0,2],[4,5,3]]
After move 65: [[1,0,2],[4,5,3]]
After move 66: [[1,0,2],[4,5,3]]
After move 67: [[1,0,2],[4,5,3]]
After move 68: [[1,0,2],[4,5,3]]
After move 69: [[1,0,2],[4,5,3]]
After move 70: [[1,0,2],[4,5,3]]
After move 71: [[1,0,2],[4,5,3]]
After move 72: [[1,0,2],[4,5,3]]
After move 73: [[1,0,2],[4,5,3]]
After move 74: [[1,0,2],[4,5,3]]
After move 75: [[1,0,2],[4,5,3]]
After move 76: [[1,0,2],[4,5,3]]
After move 77: [[1,0,2],[4,5,3]]
After move 78: [[1,0,2],[4,5,3]]
After move 79: [[1,0,2],[4,5,3]]
After move 80: [[1,0,2],[4,5,3]]
After move 81: [[1,0,2],[4,5,3]]
After move 82: [[1,0,2],[4,5,3]]
After move 83: [[1,0,2],[4,5,3]]
After move 84: [[1,0,2],[4,5,3]]
After move 85: [[1,0,2],[4,5,3]]
After move 86: [[1,0,2],[4,5,3]]
After move 87: [[1,0,2],[4,5,3]]
After move 88: [[1,0,2],[4,5,3]]
After move 89: [[1,0,2],[4,5,3]]
After move 90: [[1,0,2],[4,5,3]]
After move 91: [[1,0,2],[4,5,3]]
After move 92: [[1,0,2],[4,5,3]]
After move 93: [[1,0,2],[4,5,3]]
After move 94: [[1,0,2],[4,5,3]]
After move 95: [[1,0,2],[4,5,3]]
After move 96: [[1,0,2],[4,5,3]]
After move 97: [[1,0,2],[4,5,3]]
After move 98: [[1,0,2],[4,5,3]]
After move 99: [[1,0,2],[4,5,3]]
After move 100: [[1,0,2],[4,5,3]]
After move 101: [[1,0,2],[4,5,3]]
After move 102: [[1,0,2],[4,5,3]]
After move 103: [[1,0,2],[4,5,3]]
After move 104: [[1,0,2],[4,5,3]]
After move 105: [[1,0,2],[4,5,3]]
After move 106: [[1,0,2],[4,5,3]]
After move 107: [[1,0,2],[4,5,3]]
After move 108: [[1,0,2],[4,5,3]]
After move 109: [[1,0,2],[4,5,3]]
After move 110: [[1,0,2],[4,5,3]]
After move 111: [[1,0,2],[4,5,3]]
After move 112: [[1,0,2],[4,5,3]]
After move 113: [[1,0,2],[4,5,3]]
After move 114: [[1,0,2],[4,5,3]]
After move 115: [[1,0,2],[4,5,3]]
After move 116: [[1,0,2],[4,5,3]]
After move 117: [[1,0,2],[4,5,3]]
After move 118: [[1,0,2],[4,5,3]]
After move 119: [[1,0,2],[4,5,3]]
After move 120: [[1,0,2],[4,5,3]]
After move 121: [[1,0,2],[4,5,3]]
After move 122: [[1,0,2],[4,5,3]]
After move 123: [[1,0,2],[4,5,3]]
After move 124: [[1,0,2],[4,5,3]]
After move 125: [[1,0,2],[4,5,3]]
After move 126: [[1,0,2],[4,5,3]]
After move 127: [[1,0,2],[4,5,3]]
After move 128: [[1,0,2],[4,5,3]]
After move 129: [[1,0,2],[4,5,3]]
After move 130: [[1,0,2],[4,5,3]]
After move 131: [[1,0,2],[4,5,3]]
After move 132: [[1,0,2],[4,5,3]]
After move 133: [[1,0,2],[4,5,3]]
After move 134: [[1,0,2],[4,5,3]]
After move 135: [[1,0,2],[4,5,3]]
After move 136: [[1,0,2],[4,5,3]]
After move 137: [[1,0,2],[4,5,3]]
After move 138: [[1,0,2],[4,5,3]]
After move 139: [[1,0,2],[4,5,3]]
After move 140: [[1,0,2],[4,5,3]]
After move 141: [[1,0,2],[4,5,3]]
After move 142: [[1,0,2],[4,5,3]]
After move 143: [[1,0,2],[4,5,3]]
After move 144: [[1,0,2],[4,5,3]]
After move 145: [[1,0,2],[4,5,3]]
After move 146: [[1,0,2],[4,5,3]]
After move 147: [[1,0,2],[4,5,3]]
After move 148: [[1,0,2],[4,5,3]]
After move 149: [[1,0,2],[4,5,3]]
After move 150: [[1,0,2],[4,5,3]]
After move 151: [[1,0,2],[4,5,3]]
After move 152: [[1,0,2],[4,5,3]]
After move 153: [[1,0,2],[4,5,3]]
After move 154: [[1,0,2],[4,5,3]]
After move 155: [[1,0,2],[4,5,3]]
After move 156: [[1,0,2],[4,5,3]]
After move 157: [[1,0,2],[4,5,3]]
After move 158: [[1,0,2],[4,5,3]]
After move 159: [[1,0,2],[4,5,3]]
After move 160: [[1,0,2],[4,5,3]]
After move 161: [[1,0,2],[4,5,3]]
After move 162: [[1,0,2],[4,5,3]]
After move 163: [[1,0,2],[4,5,3]]
After move 164: [[1,0,2],[4,5,3]]
After move 165: [[1,0,2],[4,5,3]]
After move 166: [[1,0,2],[4,5,3]]
After move 167: [[1,0,2],[4,5,3]]
After move 168: [[1,0,2],[4,5,3]]
After move 169: [[1,0,2],[4,5,3]]
After move 170: [[1,0,2],[4,5,3]]
After move 171: [[1,0,2],[4,5,3]]
After move 172: [[1,0,2],[4,5,3]]
After move 173: [[1,0,2],[4,5,3]]
After move 174: [[1,0,2],[4,5,3]]
After move 175: [[1,0,2],[4,5,3]]
After move 176: [[1,0,2],[4,5,3]]
After move 177: [[1,0,2],[4,5,3]]
After move 178: [[1,0,2],[4,5,3]]
After move 179: [[1,0,2],[4,5,3]]
After move 180: [[1,0,2],[4,5,3]]
After move 181: [[1,0,2],[4,5,3]]
After move 182: [[1,0,2],[4,5,3]]
After move 183: [[1,0,2],[4,5,3]]
After move 184: [[1,0,2],[4,5,3]]
After move 185: [[1,0,2],[4,5,3]]
After move 186: [[1,0,2],[4,5,3]]
After move 187: [[1,0,2],[4,5,3]]
After move 188: [[1,0,2],[4,5,3]]
After move 189: [[1,0,2],[4,5,3]]
After move 190: [[1,0,2],[4,5,3]]
After move 191: [[1,0,2],[4,5,3]]
After move 192: [[1,0,2],[4,5,3]]
After move 193: [[1,0,2],[4,5,3]]
After move 194: [[1,0,2],[4,5,3]]
After move 195: [[1,0,2],[4,5,3]]
After move 196: [[1,0,2],[4,5,3]]
After move 197: [[1,0,2],[4,5,3]]
After move 198: [[1,0,2],[4,5,3]]
After move 199: [[1,0,2],[4,5,3]]
After move 200: [[1,0,2],[4,5,3]]
After move 201: [[1,0,2],[4,5,3]]
After move 202: [[1,0,2],[4,5,3]]
After move 203: [[1,0,2],[4,5,3]]
After move 204: [[1,0,2],[4,5,3]]
After move 205: [[1,0,2],[4,5,3]]
After move 206: [[1,0,2],[4,5,3]]
After move 207: [[1,0,2],[4,5,3]]
After move 208: [[1,0,2],[4,5,3]]
After move 209: [[1,0,2],[4,5,3]]
After move 210: [[1,0,2],[4,5,3]]
After move 211: [[1,0,2],[4,5,3]]
After move 212: [[1,0,2],[4,5,3]]
After move 213: [[1,0,2],[4,5,3]]
After move 214: [[1,0,2],[4,5,3]]
After move 215: [[1,0,2],[4,5,3]]
After move 216: [[1,0,2],[4,5,3]]
After move 217: [[1,0,2],[4,5,3]]
After move 218: [[1,0,2],[4,5,3]]
After move 219: [[1,0,2],[4,5,3]]
After move 220: [[1,0,2],[4,5,3]]
After move 221: [[1,0,2],[4,5,3]]
After move 222: [[1,0,2],[4,5,3]]
After move 223: [[1,0,2],[4,5,3]]
After move 224: [[1,0,2],[4,5,3]]
After move 225: [[1,0,2],[4,5,3]]
After move 226: [[1,0,2],[4,5,3]]
After move 227: [[1,0,2],[4,5,3]]
After move 228: [[1,0,2],[4,5,3]]
After move 229: [[1,0,2],[4,5,3]]
After move 230: [[1,0,2],[4,5,3]]
After move 231: [[1,0,2],[4,5,3]]
After move 232: [[1,0,2],[4,5,3]]
After move 233: [[1,0,2],[4,5,3]]
After move 234: [[1,0,2],[4,5,3]]
After move 235: [[1,0,2],[4,5,3]]
After move 236: [[1,0,2],[4,5,3]]
After move 237: [[1,0,2],[4,5,3]]
After move 238: [[1,0,2],[4,5,3]]
After move 239: [[1,0,2],[4,5,3]]
After move 240: [[1,0,2],[4,5,3]]
After move 241: [[1,0,2],[4,5,3]]
After move 242: [[1,0,2],[4,5,3]]
After move 243: [[1,0,2],[4,5,3]]
After move 244: [[1,0,2],[4,5,3]]
After move 245: [[1,0,2],[4,5,3]]
After move 246: [[1,0,2],[4,5,3]]
After move 247: [[1,0,2],[4,5,3]]
After move 248: [[1,0,2],[4,5,3]]
After move 249: [[1,0,2],[4,5,3]]
After move 250: [[1,0,2],[4,5,3]]
After move 251: [[1,0,2],[4,5,3]]
After move 252: [[1,0,2],[4,5,3]]
After move 253: [[1,0,2],[4,5,3]]
After move 254: [[1,0,2],[4,5,3]]
After move 255: [[1,0,2],[4,5,3]]
After move 256: [[1,0,2],[4,5,3]]
After move 257: [[1,0,2],[4,5,3]]
After move 258: [[1,0,2],[4,5,3]]
After move 259: [[1,0,2],[4,5,3]]
After move 260: [[1,0,2],[4,5,3]]
After move 261: [[1,0,2],[4,5,3]]
After move 262: [[1,0,2],[4,5,3]]
After move 263: [[1,0,2],[4,5,3]]
After move 264: [[1,0,2],[4,5,3]]
After move 265: [[1,0,2],[4,5,3]]
After move 266: [[1,0,2],[4,5,3]]
After move 267: [[1,0,2],[4,5,3]]
After move 268: [[1,0,2],[4,5,3]]
After move 269: [[1,0,2],[4,5,3]]
After move 270: [[1,0,2],[4,5,3]]
After move 271: [[1,0,2],[4,5,3]]
After move 272: [[1,0,2],[4,5,3]]
After move 273: [[1,0,2],[4,5,3]]
After move 274: [[1,0,2],[4,5,3]]
After move 275: [[1,0,2],[4,5,3]]
After move 276: [[1,0,2],[4,5,3]]
After move 277: [[1,0,2],[4,5,3]]
After move 278: [[1,0,2],[4,5,3]]
After move 279: [[1,0,2],[4,5,3]]
After move 280: [[1,0,2],[4,5,3]]
After move 281: [[1,0,2],[4,5,3]]
After move 282: [[1,0,2],[4,5,3]]
After move 283: [[1,0,2],[4,5,3]]
After move 284: [[1,0,2],[4,5,3]]
After move 285: [[1,0,2],[4,5,3]]
After move 286: [[1,0,2],[4,5,3]]
After move 287: [[1,0,2],[4,5,3]]
After move 288: [[1,0,2],[4,5,3]]
After move 289: [[1,0,2],[4,5,3]]
After move 290: [[1,0,2],[4,5,3]]
After move 291: [[1,0,2],[4,5,3]]
After move 292: [[1,0,2],[4,5,3]]
After move 293: [[1,0,2],[4,5,3]]
After move 294: [[1,0,2],[4,5,3]]
After move 295: [[1,0,2],[4,5,3]]
After move 296: [[1,0,2],[4,5,3]]
After move 297: [[1,0,2],[4,5,3]]
After move 298: [[1,0,2],[4,5,3]]
After move 299: [[1,0,2],[4,5,3]]
After move 300: [[1,0,2],[4,5,3]]
After move 301: [[1,0,2],[4,5,3]]
After move 302: [[1,0,2],[4,5,3]]
After move 303: [[1,0,2],[4,5,3]]
After move 304: [[1,0,2],[4,5,3]]
After move 305: [[1,0,2],[4,5,3]]
After move 306: [[1,0,2],[4,5,3]]
After move 307: [[1,0,2],[4,5,3]]
After move 308: [[1,0,2],[4,5,3]]
After move 309: [[1,0,2],[4,5,3]]
After move 310: [[1,0,2],[4,5,3]]
After move 311: [[1,0,2],[4,5,3]]
After move 312: [[1,0,2],[4,5,3]]
After move 313: [[1,0,2],[4,5,3]]
After move 314: [[1,0,2],[4,5,3]]
After move 315: [[1,0,2],[4,5,3]]
After move 316: [[1,0,2],[4,5,3]]
After move 317: [[1,0,2],[4,5,3]]
After move 318: [[1,0,2],[4,5,3]]
After move 319: [[1,0,2],[4,5,3]]
After move 320: [[1,0,2],[4,5,3]]
After move 321: [[1,0,2],[4,5,3]]
After move 322: [[1,0,2],[4,5,3]]
After move 323: [[1,0,2],[4,5,3]]
After move 324: [[1,0,2],[4,5,3]]
After move 325: [[1,0,2],[4,5,3]]
After move 326: [[1,0,2],[4,5,3]]
After move 327: [[1,0,2],[4,5,3]]
After move 328: [[1,0,2],[4,5,3]]
After move 329: [[1,0,2],[4,5,3]]
After move 330: [[1,0,2],[4,5,3]]
After move 331: [[1,0,2],[4,5,3]]
After move 332: [[1,0,2],[4,5,3]]
After move 333: [[1,0,2],[4,5,3]]
After move 334: [[1,0,2],[4,5,3]]
After move 335: [[1,0,2],[4,5,3]]
After move 336: [[1,0,2],[4,5,3]]
After move 337: [[1,0,2],[4,5,3]]
After move 338: [[1,0,2],[4,5,3]]
After move 339: [[1,0,2],[4,5,3]]
After move 340: [[1,0,2],[4,5,3]]
After move 341: [[1,0,2],[4,5,3]]
After move 342: [[1,0,2],[4,5,3]]
After move 343: [[1,0,2],[4,5,3]]
After move 344: [[1,0,2],[4,5,3]]
After move 345: [[1,0,2],[4,5,3]]
After move 346: [[1,0,2],[4,5,3]]
After move 347: [[1,0,2],[4,5,3]]
After move 348: [[1,0,2],[4,5,3]]
After move 349: [[1,0,2],[4,5,3]]
After move 350: [[1,0,2],[4,5,3]]
After move 351: [[1,0,2],[4,5,3]]
After move 352: [[1,0,2],[4,5,3]]
After move 353: [[1,0,2],[4,5,3]]
After move 354: [[1,0,2],[4,5,3]]
After move 355: [[1,0,2],[4,5,3]]
After move 356: [[1,0,2],[4,5,3]]
After move 357: [[1,0,2],[4,5,3]]
After move 358: [[1,0,2],[4,5,3]]
After move 359: [[1,0,2],[4,5,3]]
After move 360: [[1,0,2],[4,5,3]]
After move 361: [[1,0,2],[4,5,3]]
After move 362: [[1,0,2],[4,5,3]]
After move 363: [[1,0,2],[4,5,3]]
After move 364: [[1,0,2],[4,5,3]]
After move 365: [[1,0,2],[4,5,3]]
After move 366: [[1,0,2],[4,5,3]]
After move 367: [[1,0,2],[4,5,3]]
After move 368: [[1,0,2],[4,5,3]]
After move 369: [[1,0,2],[4,5,3]]
After move 370: [[1,0,2],[4,5,3]]
After move 371: [[1,0,2],[4,5,3]]
After move 372: [[1,0,2],[4,5,3]]
After move 373: [[1,0,2],[4,5,3]]
After move 374: [[1,0,2],[4,5,3]]
After move 375: [[1,0,2],[4,5,3]]
After move 376: [[1,0,2],[4,5,3]]
After move 377: [[1,0,2],[4,5,3]]
After move 378: [[1,0,2],[4,5,3]]
After move 379: [[1,0,2],[4,5,3]]
After move 380: [[1,0,2],[4,5,3]]
After move 381: [[1,0,2],[4,5,3]]
After move 382: [[1,0,2],[4,5,3]]
After move 383: [[1,0,2],[4,5,3]]
After move 384: [[1,0,2],[4,5,3]]
After move 385: [[1,0,2],[4,5,3]]
After move 386: [[1,0,2],[4,5,3]]
After move 387: [[1,0,2],[4,5,3]]
After move 388: [[1,0,2],[4,5,3]]
After move 389: [[1,0,2],[4,5,3]]
After move 390: [[1,0,2],[4,5,3]]
After move 391: [[1,0,2],[4,5,3]]
After move 392: [[1,0,2],[4,5,3]]
After move 393: [[1,0,2],[4,5,3]]
After move 394: [[1,0,2],[4,5,3]]
After move 395: [[1,0,2],[4,5,3]]
After move 396: [[1,0,2],[4,5,3]]

3 → 2 → 0 → -4 Input: head = [3,2,0,-4], pos = 1 Output: true Explanation: There is a cycle in the linked list, where the tail connects to the 1st node (0-indexed). Example 2: 1 → 2 Input: head = [1,2], pos = 0 Output: true Explanation: There is a cycle in the linked list, where the tail connects to the 0th node. Round 4 · Mid · Easy	Example 3: 1 Input: head = [1], pos = -1 Output: false Explanation: There is no cycle in the linked list. Constraints: - The number of the nodes in the list is in the range [0, 100]. -105 <= Node.val <= 105 - pos is -1 or a valid index in the linked-list. Follow up: Can you solve it using O(1) (i.e. constant) memory? Community Solutions (Python) • WalkCC Round 4 · Mid · Easy	<pre>class Solution: def hasCycle(self, head: ListNode) -> bool: slow = head fast = head while fast and fast.next: slow = slow.next fast = fast.next.next if slow == fast: return True return False # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def hasCycle(self, head: Optional[ListNode]) -> bool: s = set() # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def hasCycle(self, head: Optional[ListNode]) -> bool: # Initialize two pointers, slow and fast, starting from the head. slow = head</pre> Round 4 · Mid · Easy	<pre>while head: if head in s: return True s.add(head) head = head.next return False # Simplify # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def hasCycle(self, head: Optional[ListNode]) -> bool: # Initialize two pointers, slow and fast, starting from the head. slow = head</pre> Round 4 · Mid · Easy	<pre>fast = head # Traverse the list until fast pointer reaches the end. while fast and fast.next: slow = slow.next # Move slow pointer one step. fast = fast.next.next # Move fast pointer two steps. # If both pointers meet, there is a cycle. if slow == fast: return True # If loop terminates, there is no cycle. return False # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, x): # self.val = x # self.next = None class Solution: def hasCycle(self, head: ListNode) -> bool: slow = fast = head while fast and fast.next:</pre> Round 4 · Mid · Easy	<pre>slow, fast = slow.next, fast.next.next if slow == fast: return True return False # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = None class Solution: def hasCycle(self, head: Optional[ListNode]) -> bool: # Initialize slow and fast pointers at the head of the list slow = fast = head while fast and fast.next: slow = slow.next fast = fast.next.next if slow == fast: return True return False</pre> Round 4 · Mid · Easy
Linked List #206 Reverse Linked List LeetCodeDocs · SimplifyLeet · WalkCC · LeetCode Lists: Grid 169 Time Complexity: O(n) for both iterative and recursive approaches, where n is the number of nodes.Space Complexity: O(1) for the iterative approach and O(n) for the recursive approach because of the Problem Given the head of a singly linked list, reverse the list, and return the reversed list. Example 1: 1 → 2 → 3 → 4 → 5 5 → 4 → 3 → 2 → 1 Input: head = [1,2,3,4,5] Output: [5,4,3,2,1] Round 4 · Mid · Easy	Example 2: 1 → 2 2 → 1 Input: head = [1,2] Output: [2,1] Example 3: Input: head = [] Output: [] Constraints: - The number of nodes in the list is in the range [0, 5000]. -5000 <= Node.val <= 5000 Round 4 · Mid · Easy	Follow up: A linked list can be reversed either iteratively or recursively. Could you implement both? Brute Force (Python) <pre># Brute Force Approach class Solution: def reverseList(self, head): # Brute Force O(n) space = collect values, rebuild in reverse vals = [] curr = head while curr: vals.append(curr.val) curr = curr.next dummy = ListNode(0) curr = dummy for v in reversed(vals): curr.next = ListNode(v) curr = curr.next return dummy.next</pre> Community Solutions (Python) • WalkCC Round 4 · Mid · Easy	<pre>class Solution: def reverseList(self, head: ListNode None) -> ListNode: if not head or not head.next: return head newhead = self.reverseList(head.next) head.next.next = head head.next = None return newhead # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def reverseList(self, head: ListNode) -> ListNode: dummy = ListNode(0) curr = head while curr: next = curr.next curr.next = dummy.next dummy.next = curr curr = next return dummy.next</pre> Round 4 · Mid · Easy	<pre># Simplify # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next # Iterative approach to reverse the linked list. def reverseList(head): prev = None # Initially, there is no previous node current = head # Start with the head of the list while current: next_node = current.next # Temporarily store the next node current.next = prev # Reverse the current node's pointer prev = current # Move previous pointer one step forward current = next_node # Move to the next node in the list return prev # The new head of the reversed list # Recursive approach to reverse the linked list. def reverseListRecursive(head): # Base case: empty list or single node</pre> Round 4 · Mid · Easy	<pre>if not head or not head.next: return head new_head = reverseListRecursive(head.next) # Reverse the rest of the list head.next.next = head # Reverse the pointer for the current node head.next = None # Set the next pointer of the current node to None return new_head # Return the new head of the reversed list # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def reverseList(self, head: Optional[ListNode]) -> Optional[ListNode]: pre, p = None, head q = p.next # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def reverseListRecursive(head): # Base case: empty list or single node</pre> Round 4 · Mid · Easy
<pre>p.next = pre pre = p return pre class Solution(object): # Recursive def reverseList(self, root): if not root or not root.next: return root ret = self.reverseList(root.next) root.next.next = root # root.next is end of the newly reversed List ret root.next = None return ret class Solution: def reverseList(self, head: ListNode) -> ListNode: dummy = ListNode(0)</pre> Round 4 · Mid · Easy	<pre>curr = head while curr: next = curr.next curr.next = dummy.next dummy.next = curr curr = next return dummy.next</pre> Round 4 · Mid · Easy	Linked List #234 Palindrome Linked List LeetCodeDocs · SimplifyLeet · WalkCC · LeetCode Linked List · Two Pointers · Recursion Lists: Grid 169 Time Complexity: O(n) - each node is visited a constant number of times.Space Complexity: O(1) - only constant extra space is used (in-place reversal). Problem Given the head of a singly linked list, return true if it is a palindrome or false otherwise. Example 1: 1 → 2 → 2 → 1 Input: head = [1,2,2,1] Output: true Example 2: Round 4 · Mid · Easy	1 → 2 Input: head = [1,2] Output: false Constraints: - The number of nodes in the list is in the range [1, 105]. 0 <= Node.val <= 9 Follow up: Could you do it in O(n) time and O(1) space? Community Solutions (Python) • WalkCC Round 4 · Mid · Easy	<pre>class Solution: def isPalindrome(self, head: ListNode) -> bool: def reverseList(head: ListNode) -> ListNode: prev = None curr = head while curr: next_node = curr.next curr.next = prev prev = curr curr = next_node return prev slow = head fast = head while fast and fast.next: slow = slow.next fast = fast.next.next if fast:</pre> Round 4 · Mid · Easy	<pre>slow = slow.next slow = reverseList(slow) while slow: if slow.val != head.val: return False slow = slow.next head = head.next return True # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def isPalindrome(self, head: Optional[ListNode]) -> bool: slow, fast = head, head.next while fast and fast.next: slow = slow.next, fast = fast.next.next</pre> Round 4 · Mid · Easy
<pre>pre, cur = None, slow.next while cur: t = cur.next cur.next = pre pre = cur, t while pre: if pre.val != head.val: return False pre, head = pre.next, head.next return True # Simplify # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def isPalindrome(self, head: ListNode) -> bool: # Find the midpoint using slow and fast pointers slow, fast = head, head</pre> Round 4 · Mid · Easy	<pre>while fast and fast.next: slow = slow.next # Move slow pointer by 1 fast = fast.next.next # Move fast pointer by 2 # Reverse the second half of the list prev = None while slow: next_node = slow.next # Store the next node's pointer slow.next = prev # Reverse the current node's pointer prev = slow # Move prev to current node slow = next_node # Move to next node # Compare the first half and the reversed second half node by node left, right = head, prev while right != None: if left.val != right.val: return False # Mismatch found, not a palindrome left = left.next # Move left pointer right = right.next # Move right pointer</pre> Round 4 · Mid · Easy	<pre>return True # All nodes matched, it's a palindrome # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def isPalindrome(self, head: Optional[ListNode]) -> bool: slow, fast = head, head.next while fast and fast.next: slow, fast = slow.next, fast.next.next pre, cur = None, slow.next while cur: t = cur.next cur.next = pre pre = cur, t while pre: if pre.val != head.val: return False pre, head = pre.next, head.next return True</pre> Round 4 · Mid · Easy	Linked List #706 Design HashMap LeetCodeDocs · SimplifyLeet · WalkCC · LeetCode Array · Hash Table · Linked List · Design · Hash Function Lists: Denry Zhang Time Complexity: Average O(1) for put, get, and remove; worst-case O(n) when many keys hash to the same bucket.Space Complexity: O(n), where n is the number of key-value pairs stored. Problem Design a HashMap without using any built-in hash table libraries. Implement the MyHashMap class: - MyHashMap() initializes the object with an empty map. - void put(int key, int value) inserts a (key, value) pair into the HashMap. If the key already exists in the map, update the corresponding value. - int get(int key) returns the value to which the specified key is mapped, or -1 if this map contains no mapping for the key. - void remove(key) removes the key and its corresponding value if the map contains the mapping for the key. Example 1: Round 4 · Mid · Easy	<pre>Input: ["MyHashMap", "put", "put", "get", "get", "put", "get", "remove", "get"] [[], [1, 1], [2, 1], [1, 1], [3], [2, 1], [2], [2], [2]] Output: [null, null, 1, -1, null, 1, null, -1] Explanation MyHashMap myHashMap = new MyHashMap(); Constraints: 0 <= key, value <= 10^6 At most 10^4 calls will be made to put, get, and remove. Community Solutions (Python) # LeetCodeDocs class MyHashMap: def __init__(self): self.data = [-1] * 1000001 def put(self, key: int, value: int) -> None: self.data[key] = value def get(self, key: int) -> int: return self.data[key]</pre> Round 4 · Mid · Easy	<pre>def remove(self, key: int) -> None: self.data[key] = -1 # Your MyHashMap object will be instantiated and called as such: obj = MyHashMap() obj.put(key,value) obj.get(key) obj.remove(key) # Simplify # ListNode class for handling collisions in each bucket class ListNode: def __init__(self, key, value, next=None): self.key = key # Store key self.value = value # Store value self.next = next # Pointer to the next node class MyHashMap: def __init__(self): self.size = 1000 # Define the bucket size # Definition for singly-linked list. # class ListNode: # def __init__(self, key, value, next=None): # self.key = key # self.value = value # self.next = next class MyHashMap: # open addressing with linear probing</pre> Round 4 · Mid · Easy
<pre>self.buckets = [None] * self.size # Initialize buckets as an array of None def hash(self, key): # Simple modulo based hash function to map keys to bucket indices return key % self.size def put(self, key: int, value: int) -> None: index = self.hash(key) if self.buckets[index] is None: # If the bucket is empty, create a new node and place it here self.buckets[index] = ListNode(key, value) else: current = self.buckets[index] while True: if current.key == key: # If key exists, update its value current.value = value return if current.next is None: break current = current.next</pre> Round 4 · Mid · Easy	<pre>current = current.next # Append a new node at the end of the list if key not found current.next = ListNode(key, value) def get(self, key: int) -> int: index = self.hash(key) current = self.buckets[index] while current: if current.key == key: # Key found: return its value return current.value current = current.next # Key not found: return -1 return -1 def remove(self, key: int) -> None: index = self.hash(key) current = self.buckets[index] if current is None: return if current.key == key: self.buckets[index] = current.next return</pre> Round 4 · Mid · Easy	<pre>return True # All nodes matched, it's a palindrome # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def isPalindrome(self, head: Optional[ListNode]) -> bool: slow, fast = head, head.next while fast and fast.next: slow, fast = slow.next, fast.next.next pre, cur = None, slow.next while cur: t = cur.next cur.next = pre pre = cur, t while pre: if pre.val != head.val: return False pre, head = pre.next, head.next return True</pre> Round 4 · Mid · Easy	<pre>def remove(self, key: int) -> None: self.data[key] = -1 # Your MyHashMap object will be instantiated and called as such: obj = MyHashMap() obj.put(key,value) obj.get(key) obj.remove(key) # Simplify # hash to bucket def __init__(self): # Initialize your data structure here. self.size = 1000 self.buckets = [[] for _ in range(self.size)] def put(self, key: int, value: int) -> None: self.data[key] = value def get(self, key: int) -> int: return self.data[key]</pre> Round 4 · Mid · Easy	<pre>def hash(self, key: int) -> int: """ Generate a hash for a given key. """ return key % self.size def put(self, key: int, value: int) -> None: """ Value will always be non-negative. """ hash_key = self.hash(key) for i, (k, v) in enumerate(self.buckets[hash_key]): if k == key: self.buckets[hash_key][i] = (key, value) return self.buckets[hash_key].append((key, value)) def get(self, key: int) -> int: """ Returns the value to which the specified key is mapped, or -1 if this map contains no mapping for the key. """</pre> Round 4 · Mid · Easy	<pre>""" hash_key = self._hash(key) for k, v in self.buckets[hash_key]: if k == key: return v return -1 def remove(self, key: int) -> None: """ Removes the mapping of the specified value key if this map contains a mapping for the key. """ hash_key = self._hash(key) for i, (k, v) in enumerate(self.buckets[hash_key]): if k == key: del self.buckets[hash_key][i] return # open addressing with linear probing</pre> Round 4 · Mid · Easy
<pre>def __init__(self): self.capacity = 10000 self.data = [None] * self.capacity self.DELETED = (None, None) # Marker for deleted entries def hash(self, key): return key % self.capacity def put(self, key: int, value: int) -> None: idx = self._hash(key) while self.data[idx] not in (None, self.DELETED, key): idx = (idx + 1) % self.capacity self.data[idx] = (key, value) def get(self, key: int) -> int: idx, found, key = self._find(key) if found: return self.data[idx][1] return -1</pre> Round 4 · Mid · Easy	<pre>def remove(self, key: int) -> None: idx, found, key = self._find(key) if found: self.data[idx] = self.DELETED def _find(self, key): original_idx = idx = self._hash(key) while self.data[idx] is not None: if self.data[idx] == key: return idx, True idx = (idx + 1) % self.capacity if idx == original_idx: # Came full circle break return original_idx, False</pre> Round 4 · Mid · Easy	Linked List #876 Middle of the Linked List LeetCodeDocs · SimplifyLeet · WalkCC · LeetCode Linked List · Two Pointers Lists: Grid 169 Time Complexity: O(n), where n is the number of nodes in the list.Space Complexity: O(1), constant extra space. Problem Given the head of a singly linked list, return the middle node of the linked list. If there are two middle nodes, return the second middle node. Example 1: 1 → 2 → 3 → 4 → 5 Input: head = [1,2,3,4,5] Output: [3,4,5] Explanation: The middle node of the list is node 3. Example 2: 1 → 2 → 3 → 4 → 5 → 6 Round 4 · Mid · Easy	Input: head = [1,2,3,4,5,6] Output: [4,5,6] Explanation: Since the list has two middle nodes with values 3 and 4, we return the second one. Constraints: - The number of nodes in the list is in the range [1, 100]. 1 <= Node.val <= 100 Community Solutions (Python) • WalkCC <pre>class Solution: def middleNode(self, head: ListNode) -> ListNode: slow = head fast = head while fast and fast.next: slow = slow.next fast = fast.next.next return slow # LeetCodeDocs</pre> Round 4 · Mid · Easy	<pre># Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next def middleNode(self, head: ListNode) -> ListNode: slow = fast = head while fast and fast.next: slow = slow.next fast = fast.next.next return slow # Simplify # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def middleNode(self, head: ListNode) -> ListNode: # Initialize slow and fast pointers at the head of the list slow = fast = head</pre> Round 4 · Mid · Easy	<pre>fast = head # Loop until fast reaches the end of the list while fast and fast.next: # Move slow pointer one step slow = slow.next # Move fast pointer two steps fast = fast.next.next # When loop ends, slow pointer points to the middle node return slow # LeetCodeDocs # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def middleNode(self, head: Optional[ListNode]) -> Optional[ListNode]: slow, fast = head while fast and fast.next: slow = slow.next, fast = fast.next.next return slow</pre> Round 4 · Mid · Easy

Round 4 - Mid - Easy p.1795 Round 4 - Mid - Easy p.1796 Round 4 - Mid - Easy p.1797 Round 4 - Mid - Easy p.1798 Round 4 - Mid - Easy p.1799 Round 4 - Mid - Easy p.1800

Round 5 - Mid - Medium	p.1867	Round 5 - Mid - Medium	p.1868	Round 5 - Mid - Medium	p.1869	Round 5 - Mid - Medium	p.1870	Round 5 - Mid - Medium	p.1871	Round 5 - Mid - Medium	p.1872
------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------

Round 5 Mid-Medium p.1905

dummy.next = head

Dictionary to store prefix sum to node mapping

```
sum_to_node = {}
prefix_sum = 0
current = dummy
```

First pass: record the last occurrence of each prefix sum

```
while current:
    prefix_sum += current.val
    sum_to_node[prefix_sum] = current
    current = current.next
```

Second pass: remove nodes that are part of zero-sum sequences

```
prefix_sum = 0
current = dummy
while current:
    prefix_sum += current.val
    # Link current node's next pointer to skip the zero-sum subsequence
    current.next = sum_to_node[prefix_sum].next
    current = current.next
return dummy.next
```

Round 5 - Mid - Medium

p.1945

LC6a

Definition for singly-linked list.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next
class Solution:
    def removeZeroSumSublists(self, head: Optional[ListNode]) -> Optional[ListNode]:
        dummy = ListNode(next=head)
        while cur:
            s = cur.val
            last[s] = cur
            cur = cur.next
            s, cur = 0, dummy
            while cur:
                s += cur.val
                cur = cur.next
                if s in last:
                    cur = cur.next
                else:
                    cur = cur.next
            return dummy.next
```

Round 5 - Mid - Medium

p.1946

Stack

Round 5 - Mid - Medium - 14 questions

Round 5 - Mid - Medium

#143 Reorder List

LeetCode - SimplifyLeet - WalkCC - LeetCode

Linked List - Two Pointers - Stack - Recursion

Lists: Grid 169

Time Complexity: O(n) - Each of the three main steps (finding the middle, reversing, merging) takes O(n) time. Space Complexity: O(1) - The algorithm is done in-place with only a few pointers.

Problem

You are given the head of a singly linked-list. The list can be represented as:

```
1a - 11 -> ... - 1a - 1 - 1a
```

Reorder the list to be in the following form:

```
1b - 1a - 12 - 1a - 1 - 12 - 1a - 2 - ...
```

You may not modify the values in the list's nodes. Only nodes themselves may be changed.

Example 1:

Round 5 - Mid - Medium

p.1948

Diagram showing a linked list with nodes 1, 2, 3, 4. An arrow points from node 2 to node 4, illustrating a reordering operation.

Input: head = [1,2,3,4]
Output: [1,4,2,3]

Example 2:

Input: head = [1,2,3,4,5]
Output: [1,5,2,4,3]

Constraints:

Round 5 - Mid - Medium

p.1949

The number of nodes in the list is in the range [1, 5 * 10⁴].

n <= Node.val <= 1000

Community Solutions (Python)

WalkCC

```
class Solution:
    def reorderList(self, head: ListNode) -> None:
        def findMid(head: ListNode):
            slow = head
            fast = head
            while fast and fast.next:
                slow = slow.next
                fast = fast.next.next
            prev.next = None
            return slow
        def reverse(head: ListNode) -> ListNode:
            prev = None
            curr = head
            while curr:
                curr.next = prev
                prev = curr
                curr = curr.next
```

Round 5 - Mid - Medium

p.1950

next = curr.next
curr.next = prev
prev = curr
curr = next
return prev

merge(l1: ListNode, l2: ListNode) -> None

```
while l1 and l2:
    l1.next = l2
    l1 = l1.next
    l2 = l2.next
if not head or not head.next:
    return
mid = findMid(head)
reversed = reverse(mid)
merge(head, reversed)
```

LeetCode

Round 5 - Mid - Medium

p.1951

Definition for singly-linked list.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next
class Solution:
    def reorderList(self, head: Optional[ListNode]) -> None:
        while l1 and l2:
            fast = slow.next
            slow = slow.next
            pre = None
            while cur:
                t = cur.next
                cur.next = pre
                pre = cur
                cur = t
            while pre:
                t = pre.next
                pre.next = cur.next
                cur.next = pre
                pre = pre.next
                t = t.next
```

Round 5 - Mid - Medium

p.1952

SimplifyLeet

Definition for singly-linked list.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next
class Solution:
    def reorderList(self, head: Optional[ListNode]) -> None:
        while l1 and l2:
            fast = slow.next
            slow = slow.next
            pre = None
            while cur:
                t = cur.next
                cur.next = pre
                pre = cur
                cur = t
            while pre:
                t = pre.next
                pre.next = cur.next
                cur.next = pre
                pre = pre.next
                t = t.next
```

Round 5 - Mid - Medium

while curr:

```
next, temp = curr.next # Save next node.
curr.next = prev # Reverse current
prev = curr # Move prev to current.
curr = next, temp # Move to the next node.
# Step 3: Merge the two halves, alternating nodes.
first, second = head, prev
while second:
    temp1 = first.next # Save next node from first half.
    first.next = second # Save next node from reversed second half.
    second.next = first # Link first node to second list node.
    first = temp1 # Move pointer in first half.
    second = temp2 # Move pointer in second half.
```

LC6a

Round 5 - Mid - Medium

p.1954

Definition for singly-linked list.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next
class Solution:
    def reorderList(self, head: Optional[ListNode]) -> None:
        fast = slow = head
        while fast and fast.next:
            fast = fast.next.next
            slow = slow.next
        pre = None
        while cur:
            t = cur.next
            cur.next = pre
            pre = cur
            cur = t
        while pre:
            t = pre.next
            pre.next = cur.next
            cur.next = pre
            pre = pre.next
            t = t.next
```

Round 5 - Mid - Medium

p.1955

Stack

#150 Evaluate Reverse Polish Notation

LeetCode - SimplifyLeet - WalkCC - LeetCode

Array - Math - Stack

Lists: Grid 169

Time Complexity: O(n), where n is the number of tokens (each token is processed once). Space Complexity: O(n), in the worst-case scenario where all tokens are numbers and are stored in the stack.

Problem

You are given an array of strings tokens that represents an arithmetic expression in a Reverse Polish Notation. Evaluate the expression. Return an integer that represents the value of the expression.

Note that:

- The valid operators are '+', '-', '*', and '/'.
- Each operand may be an integer or another expression.
- The division between two integers always truncates toward zero.
- There will not be any division by zero.
- The input represents a valid arithmetic expression in a reverse polish notation.

Round 5 - Mid - Medium

p.1956

The answer and all the intermediate calculations can be represented in a 32-bit integer.

Example 1:

```
Input: tokens = ["12","3","+","45","*"]
Output: 9
Explanation: ((12 + 3) * 4) = 9
```

Example 2:

```
Input: tokens = ["4","13","5","/","+"]
Output: 6
Explanation: (4 + (13 / 5)) = 6
```

Example 3:

```
Input: tokens = ["10","6","9","3","+","11","*","/","+","12","*","5","*","+"]
Output: 6
Explanation: ((10 + (6 / (9 + 3) + 11) * 5) + ((12 * 5) + 9) * 3) = 6
```

Constraints:

- 1 <= tokens.length <= 104
- tokens[i] is either an operator '+', '-', '*', '/', or an integer in the range [-200, 200].

Brute Force (Python)

Round 5 - Mid - Medium

p.1957

Brute Force Approach

```
def evalRPN(self, tokens: List[str]) -> int:
    # Brute Force (stack is already optimal) ->
    simulate tokens by token
    stack = []
    ops = {'+': lambda a, b: a+b, '-': lambda a, b: a-b, '*': lambda a, b: a*b, '/': lambda a, b: int(a/b)}
    for tok in tokens:
        if tok in ops:
            b, a = stack.pop(), stack.pop()
            stack.append(ops[tok](a, b))
        else:
            stack.append(int(tok))
    return stack[0]
```

Community Solutions (Python)

WalkCC

Round 5 - Mid - Medium

p.1958

class Solution:

```
def evalRPN(self, tokens: List[str]) -> int:
    stack = []
    for token in tokens:
        if token in '+':
            b, a = stack.pop(), stack.pop()
            stack.append(a+b)
        elif token in '-':
            b, a = stack.pop(), stack.pop()
            stack.append(a-b)
        elif token in '*':
            b, a = stack.pop(), stack.pop()
            stack.append(a*b)
        elif token in '/':
            b, a = stack.pop(), stack.pop()
            stack.append(int(a/b))
    return stack[0]
```

LeetCode

Round 5 - Mid - Medium

import operator

```
def evalRPN(self, tokens: List[str]) -> int:
    ops = {
        '+': operator.add,
        '-': operator.sub,
        '*': operator.mul,
        '/': operator.truediv,
    }
    stack = []
    for token in tokens:
        if token in ops:
            s, append(int(ops[token](s.pop(), s.pop())))
        else:
            s.append(int(token))
    return s[0]
```

Round 5 - Mid - Medium

p.1960

class Solution:

```
def evalRPN(self, tokens: List[str]) -> int:
    nums = []
    for i in tokens:
        if len(i) > 1 or i.isdigit():
            nums.append(int(i))
        else:
            if i == "+":
                nums[-2] += nums[-1]
            elif i == "-":
                nums[-2] -= nums[-1]
            elif i == "*":
                nums[-2] *= nums[-1]
            elif i == "/":
                nums[-2] = int(nums[-2] / nums[-1])
    return nums[0]
```

SimplifyLeet

Round 5 - Mid - Medium

p.1961

def evalRPN(tokens: List[str]) -> int:

```
# Initialize a stack to hold numbers
stack = []
# Loop through each token in the input list
for token in tokens:
    # If token is "+", "-", "*", or "/"
    # Pop the two topmost values; note the order is important
    a = stack.pop()
    b = stack.pop()
    # Apply the operation based on the token
    if token == "+":
        result = a + b
    elif token == "-":
        result = a - b
    elif token == "*":
        result = a * b
    elif token == "/":
        result = int(a / b)
    # Use int division to truncate towards zero
    result = int(a / b)
    # Push the result back onto the stack
    stack.append(result)
```

Round 5 - Mid - Medium

p.1962

stack.append(result)

else:

Token is a number; push its integer value onto the stack

stack.append(int(token))

The final result is the only element left in the stack

return stack.pop()

Example usage:

```
tokens = ["12","3","+","45","*"]
print(evalRPN(tokens)) # Output: 9
```

LC6a

class Solution:

```
def evalRPN(self, tokens: List[str]) -> int:
    nums = []
    for i in tokens:
        if len(i) > 1 or i.isdigit():
            nums.append(int(i))
        else:
            if i == "+":
                nums[-2] += nums[-1]
            elif i == "-":
                nums[-2] -= nums[-1]
            elif i == "*":
                nums[-2] *= nums[-1]
            elif i == "/":
                nums[-2] = int(nums[-2] / nums[-1])
    return nums[0]
```

Round 5 - Mid - Medium

p.1963

nums[-2] += nums[-1]

elif i == "+":

nums[-2] += nums[-1]

nums[-2] = int(nums[-2] / nums[-1])

nums.pop()

return nums[0]

Round 5 - Mid - Medium

p.1964

Stack

#155 Min Stack

LeetCode - SimplifyLeet - WalkCC - LeetCode

Stack - Design

Lists: Grid 169

Time Complexity: O(1) per operation (push, pop, top, getMin). Space Complexity: O(n), where n is the number of elements in the stack, since an additional stack is used to keep track of minima.

Problem

Design a stack that supports push, pop, top, and retrieving the minimum element in constant time.

Implement the MinStack class:

- MinStack() initializes the stack object.
- void push(int val) pushes the element val onto the stack.
- void pop() removes the element on the top of the stack.
- int top() gets the top element of the stack.
- int getMin() retrieves the minimum element in the stack.

You must implement a solution with O(1) time complexity for each function.

Example 1:

Round 5 - Mid - Medium

Input:

```
["MinStack","push","push","push","pop","top","getMin"]
[[["1","2","3","4"],["1","2","3","4"]]]
```

Output:

```
[null,null,null,4,3,null,1,4,2]
```

Explanation:

- 1. push(1)
- 2. push(2)
- 3. push(3)
- 4. push(4)
- 5. pop()
- 6. top() returns 3
- 7. getMin() returns 1
- 8. push(2)
- 9. top() returns 2
- 10. pop()
- 11. top() returns 3
- 12. getMin() returns 1

Constraints:

- 1 <= ops.length <= 10⁴
- ops[i] is "push", "pop", "top", or "getMin"
- Values pushed into MinStack will be in the range [-2³¹, 2³¹ - 1]

Community Solutions (Python)

WalkCC

Round 5 - Mid - Medium

p.1966

class MinStack:

```
def __init__(self):
    self.stack = []
    self.minStack = []
def push(self, x: int) -> None:
    self.stack.append(x)
    self.minStack.append(x)
def pop(self) -> None:
    self.stack.pop()
    self.minStack.pop()
def top(self) -> int:
    return self.stack[-1]
def getMin(self) -> int:
    return self.minStack[-1]
```

Round 5 - Mid - Medium

p.1967

self.stk1.pop()

self.stk2.pop()

self.stk = []

def top(self) -> int:

return self.stk[-1]

def getMin(self) -> int:

return self.stk2[-1]

Your MinStack object will be instantiated and called as such:

```
obj = MinStack()
obj.push(1)
obj.push(2)
obj.top()
obj.pop()
obj.getMin()
```

SimplifyLeet

Python Implementation of MinStack with detailed comments

```
class MinStack:
    def __init__(self):
        # Main stack to store all values
        self.stack = []
        # Auxiliary stack to store minimum values
        self.min_stack = []
    def push(self, val: int) -> None:
        self.stack.append(val)
        self.min_stack.append(min(val, self.min_stack[-1] if self.min_stack else val))
    def pop(self) -> None:
        self.stack.pop()
        self.min_stack.pop()
```

Round 5 - Mid - Medium

p.1968

Push value onto main stack

self.stack.append(val)

If min_stack is empty or the new value is less than or equal to current minimum, push it onto min_stack

if not self.min_stack or val <= self.min_stack[-1]:

self.min_stack.append(val)

def pop(self) -> None:

Pop the top value from main stack

popped_value = self.stack.pop()

If the popped value is the current minimum, pop it from min_stack as well

if popped_value == self.min_stack[-1]:

self.min_stack.pop()

def top(self) -> int:

Return the top value from main stack without removing it

return self.stack[-1]

def getMin(self) -> int:

Return the minimum value from min_stack

return self.min_stack[-1]

Round 5 - Mid - Medium

p.1969

Example usage:

```
obj = MinStack()
obj.push(1)
obj.push(2)
obj.push(3)
obj.printMinStack() # -> 3
obj.printMinStack() # -> 2
obj.printMinStack() # -> 1
```

LC6a

class MinStack:

```
def __init__(self):
    self.stack = []
    self.minStack = []
def push(self, val: int) -> None:
    self.stack.append(val)
    self.minStack.append(min(val, self.minStack[-1] if self.minStack else val))
def pop(self) -> None:
    self.stack.pop()
    self.minStack.pop()
```

Round 5 - Mid - Medium

p.1970

If not self.sk:

return

self.sk.pop()

self.sk = []

def top(self) -> int:

return self.sk[-1]

def getMin(self) -> int:

return self.sk[-1]

Your MinStack object will be instantiated and called as such:

```
obj = MinStack()
obj.push(1)
obj.push(2)
obj.push(3)
obj.printMinStack() # -> 3
obj.printMinStack() # -> 2
obj.printMinStack() # -> 1
```

Round 5 - Mid - Medium

class MinStack:

```
def __init__(self):
    self.sk = []
    self.minStack = []
def push(self, val: int) -> None:
    self.sk.append(val)
    self.minStack.append(min(val, self.minStack[-1] if self.minStack else val))
def pop(self) -> None:
    self.sk.pop()
    self.minStack.pop()
def top(self) -> int:
    return self.sk[-1]
def getMin(self) -> int:
    return self.minStack[-1]
```

Round 5 - Mid - Medium

p.1972

def top(self) -> int:

return self.sk[-1]

def getMin(self) -> int:

return self.minStack[-1]

optimize above, using only 1 stack, with stack element as tuple (val, its associated min)

class MinStack:

```
def __init__(self):
    self.stack = []
def push(self, x: int) -> None:
    cur_min = self.getMin()
    if x < cur_min:
        self.stack.append((x, cur_min))
    else:
        self.stack.append((x, cur_min))
def pop(self) -> None:
    self.stack.pop()
```

Round 5 - Mid - Medium

p.1973

def top(self) -> int:

if not self.sk:

return None

else:

return self.sk[-1][0]

def getMin(self) -> int:

if not self.sk:

return float('inf')

else:

return self.sk[-1][1]

Inorder(root.left)

self.vals.append(root.val)

Inorder(root.right)

self.cur = 0

self.vals = []

return res

def hasNext(self) -> bool:

return self.cur < len(self.vals)

Your BSTIterator object will be instantiated and called as such:

```
obj = BSTIterator(root)
obj.next()
obj.hasNext()
obj.next()
obj.hasNext()
```

SimplifyLeet

Round 5 - Mid - Medium

p.1974

Stack

#173 Binary Search Tree Iterator

LeetCode - SimplifyLeet - WalkCC - LeetCode

Stack - Tree - Design - Binary Search Tree - Iterator

Lists: Deny Zhang

Time Complexity: O(1) on average per operation (amortized). Space Complexity: O(h), where h is the height of the tree.

Problem

Implement the BSTIterator class that represents an iterator over the in-order traversal of a binary search tree (BST):

- BSTIterator(TreeNode root) Initializes an object of the BSTIterator class. The root of the BST is given as part of the constructor. The pointer should be initialized to a non-existent number smaller than any element in the BST.
- boolean hasNext() Returns true if there exists a number in the traversal to the right of the pointer, otherwise returns false.
- int next() Moves the pointer to the right, then returns the number at the pointer.

Notice that by initializing the pointer to a non-existent smallest number, the first call to next() will return the smallest element in the BST.

Round 5 - Mid - Medium

p.1975

You may assume that next() calls will always be valid. That is, there will be at least a next number in the in-order traversal when next() is called.

Example 1:

```
graph TD
    7 --- 3
    7 --- 15
    7 --- 9
    15 --- 20
```

Round 5 - Mid - Medium

p.1976

Input:

```
["BSTIterator","next","next","hasNext","next","hasNext","next","hasNext","next","hasNext"]
[[{"root":1},[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10],[1,2,3,4,5,6,7,8,9,10]]
```

Explanation

BSTIterator BSTIterator = new BSTIterator([1, 2, 3, 4, 5, 6, 7, 8, 9, 10]);

Constraints:

- The number of nodes in the tree is in the range [1, 10⁵].
- 0 <= Node.val <= 10⁵.
- At most 10⁵ calls will be made to hasNext and next.

Follow up:

- Could you implement next() and hasNext() to run in average O(1) time and use O(h) memory, where h is the height of the tree?

Community Solutions (Python)

WalkCC

Round 5 - Mid - Medium

class BSTIterator:

```
def __init__(self, root: TreeNode | None):
    self.i = 0
    self.vals = []
    self._inorder(root)
def next(self) -> int:
    self.i += 1
    return self.vals[self.i - 1]
def hasNext(self) -> bool:
    return self.i < len(self.vals)
def _inorder(self, root: TreeNode | None) -> None:
    if not root:
        return
    self._inorder(root.left)
    self.vals.append(root.val)
    self._inorder(root.right)
```

Round 5 - Mid - Medium

p.1978

def hasNext(self) -> bool:

return self.stack

def pushLeftUntilNull(self, root: TreeNode | None) -> None:

while root:

self.stack.append(root)

root = root.left

LeetCode

Definition for a binary tree node.

```
class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val = val
        self.left = left
        self.right = right
class BSTIterator:
    def __init__(self, root: TreeNode):
        self.inorder = []
        self._inorder(root)
```

Round 5 - Mid - Medium

p.1979

Inorder(root.left)

self.vals.append(root.val)

Inorder(root.right)

self.cur = 0

self.vals = []

return res

def hasNext(self) -> bool:

return self.cur < len(self.vals)

Your BSTIterator object will be instantiated and called as such:

```
obj = BSTIterator(root)
obj.next()
obj.hasNext()
obj.next()
obj.hasNext()
```

SimplifyLeet

Round 5 - Mid - Medium

p.1980

Round 5 Mid-Medium LeetMastery Study-Order p.2049 Round 15 Mid-Medium 36-up Portrait 8x6

Input: maze = [[0,0,0,0],[1,1,0,1],[0,0,0,0],[0,1,0,0],[1,0,1,0,0,0]], start = [4,2], destination = [0,1] Output: -1 Constraints: - m == maze.length - n == maze[0].length 1 <= m, n <= 100 - maze[i][j] is 0 or 1 - start.length == 2 - destination.length == 2 0 <= startrow, destinationrow < m 0 <= startcol, destinationcol < n - Both the ball and the destination exist in an empty space, and they will not be in the same position initially. - The maze contains at least 2 empty spaces. Brute Force (Python)	<pre># Brute Force Approach class Solution: def shortestDistance(self, maze, start, destination): # Brute Force O(n log n) - sort repeatedly # Instead of heap m = len(maze) n = len(maze[0]) result = [] for i in range(m): for j in range(n): if maze[i][j] == 0: data.sort() result.append(data.pop(0)) return result</pre> Community Solutions (Python) <pre># LeetCode class Solution: def shortestDistance(self, maze: List[List[int]], start: List[int], destination: List[int]) -> int: m, n = len(maze), len(maze[0]) dirs = [-1, 0, 1, 0, -1] di, dj = start di, dj = destination q = deque([(di, sj)]) dist = [[inf] * n for _ in range(m)] dist[di][dj] = 0 while q: i, j = q.popleft() for a, b in pairs(maze[dirs]): x, y, k = i, j, dist[i][j] while 0 <= x < m and 0 <= y < n and maze[x][y] == 0: x, y, k = x + a, y + b, k + 1 if k < dist[x][y]: dist[x][y] = k q.append((x, y))</pre>	<pre>dist[i][j][s] = 0 while q: i, j = q.popleft() for a, b in pairs(maze[dirs]): x, y, k = i, j, dist[i][j] while 0 <= x < m and 0 <= y < n and maze[x][y] == 0: x, y, k = x + a, y + b, k + 1 if k < dist[x][y]: dist[x][y] = k q.append((x, y)) return -1 if dist[di][dj] == inf else dist[di][dj]</pre> SimpleTest <pre>import heapq def shortestDistance(maze, start, destination): m, n = len(maze), len(maze[0]) # Initialize distance matrix with infinity dist = [[float('inf')] * n for _ in range(m)] dist[start[0]][start[1]] = 0 # Priority queue (min-heap) storing tuples (distance, row, col) heap = [(0, start[0], start[1])] # Directions: up, down, left, right directions = [(-1, 0), (1, 0), (0, -1), (0, 1)] while heap: d, row, col = heapq.heappop(heap) # If we have reached the destination, return the corresponding distance if (row, col) == destination: return d # Skip if we already found a better path to (row, col) if d > dist[row][col]: continue for dr, dc in directions: next_row, next_col, count = row, col, 0 # Roll the ball until it hits a wall while 0 <= next_row + dr < m and 0 <= next_col + dc < n and maze[next_row + dr][next_col + dc] == 0: next_row = dr next_col = dc count += 1 # Check if the new distance is shorter if d + count < dist[next_row][next_col]: dist[next_row][next_col] = d + count heapq.heappush(heap, (d + count, next_row, next_col))</pre>	<pre>heapq.heappush(heap, (dist[next_row][next_col], next_row, next_col)) return -1</pre> LeetCode <pre>class Solution: def shortestDistance(self, maze: List[List[int]], start: List[int], destination: List[int]) -> int: m, n = len(maze), len(maze[0]) dirs = [-1, 0, 1, 0, -1] di, dj = start di, dj = destination q = deque([(di, sj)]) dist = [[inf] * n for _ in range(m)] dist[di][dj] = 0 while q: i, j = q.popleft() for a, b in pairs(maze[dirs]): x, y, k = i, j, dist[i][j] while 0 <= x < m and 0 <= y < n and maze[x][y] == 0: x, y, k = x + a, y + b, k + 1 if k < dist[x][y]: dist[x][y] = k q.append((x, y))</pre>	<pre>return -1 if dist[di][dj] == inf else dist[di][dj]</pre>	
---	--	--	--	---	--

Heap #621 Task Scheduler LeetCode - SimpleTest - WalKCC - LeetCode Array - Hash Table - Greedy - Heap - Counting Lists: Grid 169 Time Complexity: O(N) where N is the number of tasks (counting frequency, then iterating over constant 26 letters). Space Complexity: O(1) since the frequency count uses an array or hash map with fix Problem You are given an array of CPU tasks, each labeled with a letter from A to Z, and a number n. Each CPU interval can be idle or allow the completion of one task. Tasks can be completed in any order, but there's a constraint: there has to be a gap of at least n intervals between two tasks with the same label. Return the minimum number of CPU intervals required to complete all tasks. Example 1: Input: tasks = ["A","A","A","B","B","B"], n = 2 Output: 8 Explanation: A possible sequence is: A -> B -> idle -> A -> B -> idle -> A -> B	After completing task A, you must wait two intervals before doing A again. The same applies to task B. In the 3rd interval, neither A nor B can be done, so you idle. By the 4th interval, you can do A again as 2 intervals have passed. Example 2: Input: tasks = ["A","C","A","B","D","B"], n = 1 Output: 6 Explanation: A possible sequence is: A -> B -> C -> D -> A -> B With a cooling interval of 1, you can repeat a task after just one other task. Example 3: Input: tasks = ["A","A","A","B","B","B"], n = 3 Output: 10 Explanation: A possible sequence is: A -> B -> idle -> idle -> A -> B -> idle -> idle -> A -> B There are only two types of tasks, A and B, which need to be separated by 3 intervals. This leads to idling twice between repetitions of these tasks. Constraints: 1 <= tasks.length <= 104 - tasks[i] is an uppercase English letter. 0 <= n <= 100 Brute Force (Python)	<pre># Brute Force Approach class Solution: def leastInterval(self, tasks, n): # Brute Force O(n * intervals) - simulate the CPU schedule tick by tick from collections import Counter counts = Counter(tasks) time = 0 while counts: # Each cycle: pick up to (n+1) >= n most frequent tasks cycle = sorted(counts.keys()) key=lambda t: -counts[t](1) for i in range(1, n+1): counts[i] -= 1 if counts[i] == 0: del counts[i] time += 1 # If counts: # idle the rest of the cycle time += max(0, n + 1 - len(counts)) return time</pre> Community Solutions (Python) WalKCC	<pre>class Solution: def leastInterval(self, tasks: List[str], n: int) -> int: count = collections.Counter(tasks) maxfreq = max(count.values()) # Put the most frequent task in the slot first maxfreq -= 1 # Get the number of tasks with same frequency as maxfreq, we'll append them after the # 'maxfreqtasktask' maxfreq = sum(value == maxfreq for value in count.values()) # The most frequent task is frequent enough to force some idle slots, # The most frequent task is not frequent enough to force idle slots return max(maxfreq*taskscopy + n*maxfreq, len(tasks))</pre> LeetCode	<pre>class Solution: def leastInterval(self, tasks: List[str], n: int) -> int: count = Counter(tasks) x = max(count.values()) xsum = sum(x <= a <= n and 0 <= y <= n) maxfreq = max(count.values()) # Count how many tasks have the maximum frequency max_count = sum(1 for count in task_counts.values() if count == max_freq)</pre> Python Solution for Task Scheduler from collections import Counter <pre>def leastInterval(tasks, n): # Count the frequency of each task task_counts = Counter(tasks) # Find the maximum frequency among tasks max_freq = max(task_counts.values()) # Count how many tasks have the maximum frequency max_count = sum(1 for count in task_counts.values() if count == max_freq)</pre>	# Calculate the minimum intervals required based on the most frequent tasks part_count = max_freq - 1 # Number of parts between the most frequent task part_length = n - (max_count - 1) # Effective empty slots per part after placing max frequency tasks empty_slots = part_count * part_length # Total empty slots to fill with idle or other tasks available_tasks = len(tasks) - max_freq max_count # Remaining tasks to fill the empty slots idles = max(0, empty_slots - available_tasks) # Remaining idle slots if available tasks are not enough # The total intervals is the sum of all tasks and idle slots inserted return len(tasks) + idles # Example usage: <pre>if __name__ == "__main__": tasks = ["A","A","A","B","B","B","B"] n1 = 2 print(leastInterval(tasks, n1)) # Output: 8</pre> LeetCode
--	--	--	--	---	---

<pre>class Solution: def leastInterval(self, tasks: List[str], n: int) -> int: count = Counter(tasks) x = max(count.values()) xsum = sum(x <= a <= n and 0 <= y <= n) maxfreq = max(count.values()) # Count how many tasks have the maximum frequency max_count = sum(1 for count in task_counts.values() if count == max_freq)</pre>	Heap #658 Find K Closest Elements LeetCode - SimpleTest - WalKCC - LeetCode Array - Binary Search - Sorting - Heap - Two Pointers Lists: Grid 169 Time Complexity: O(n log n), where O(n log n) for binary search and O(n) for collecting results. Space Complexity: O(1), for storing the output. Problem Given a sorted integer array arr, two integers k and x, return the k closest integers to x in the array. The result should also be sorted in ascending order. An integer a is closer to x than an integer b: - a - x < b - x , or - a - x == b - x and a < b Example 1: Input: arr = [1,2,3,4,5], k = 4, x = 3 Output: [1,2,3,4] Example 2: Input: arr = [1,2,3,4,5], k = 4, x = -1 Output: [1,2,3,4] Constraints: 1 <= k <= arr.length	<pre># 1 <= arr.length <= 104 # arr is sorted in ascending order. # -104 <= arr[0], x <= 104 Brute Force (Python) # Brute Force Approach class Solution: def findKClosestElements(self, arr, k, x): # Brute Force O(n log n) - sort repeatedly # Instead of heap data = List(arr) result = [] for i in range(k): data.sort() result.append(data.pop(0)) return result</pre> Community Solutions (Python) WalKCC	<pre>class Solution: def findKClosestElements(self, arr: List[int], k: int, x: int) -> List[int]: l = 0 r = len(arr) - k while l < r: m = (l + r) // 2 if x - arr[m] < arr[m + k] - x: l = m + 1 else: r = m return arr[l:l + k]</pre> LeetCode <pre>class Solution: def findKClosestElements(self, arr: List[int], k: int, x: int) -> List[int]: arr.sort(key=lambda v: abs(v - x)) return sorted(arr[0:k])</pre> SimpleTest	<pre># Function to find K closest elements to x in a sorted array def findKClosestElements(arr, k, x): # l = 0 # r = len(arr) - k # while l < r: # m = (l + r) // 2 # if x - arr[m] < arr[m + k] - x: # l = m + 1 # else: # r = m # Return the k elements starting from index 'left' return arr[left:left + k]</pre> LeetCode <pre>class Solution: def findKClosestElements(self, arr: List[int], k: int, x: int) -> List[int]: arr.sort(key=lambda v: abs(v - x)) return sorted(arr[0:k])</pre> SimpleTest	<pre>class Solution: def findKClosestElements(self, arr: List[int], k: int, x: int) -> List[int]: left, right = 0, len(arr) - k while left < right: m = (left + right) // 2 if x - arr[m] < arr[m + k] - x: left = m + 1 else: right = m return arr[left:left + k]</pre> LeetCode
--	--	---	---	--	---

Heap #787 Cheapest Flights Within K Stops LeetCode - SimpleTest - WalKCC - LeetCode Dynamic Programming - DFS - BFS - Graph - Heap Lists: Grid 169 Problem There are n cities connected by some number of flights. You are given an array flights where flights[i] = (from, to, price) indicates that there is a flight from city from to city to with cost price. You are also given three integers src, dst, and k, return the cheapest price from src to dst with at most k stops. If there is no such route, return -1. Example 1:	<pre>Input: n = 4, flights = [[0,1,100],[1,2,100],[2,0,100],[1,3,600],[2,3,200]], src = 0, dst = 3, k = 1 Output: 700 Explanation: The graph is shown above. The optimal path with at most 1 stop from city 0 to 3 is marked in red and has cost 100 + 600 = 700. Note that the path through cities (0,1,2,3) is cheaper but is invalid because it uses 2 stops.</pre> Example 2:	<pre>Input: n = 3, flights = [[0,1,100],[1,2,100],[2,0,100],[1,3,600],[2,3,200]], src = 0, dst = 2, k = 1 Output: 200 Explanation: The graph is shown above. The optimal path with no stops from city 0 to 2 is marked in red and has cost 100 + 100 = 200.</pre> Example 3: <pre># 2 <= k <= 100 # 0 <= flights.length <= (n * (n - 1) / 2) # flights[i].length == 3 # 0 <= from, to <= n</pre>	<pre>Input: n = 3, flights = [[0,1,100],[1,2,100],[2,0,100],[1,3,600],[2,3,200]], src = 0, dst = 2, k = 1 Output: 200 Explanation: The graph is shown above. The optimal path with no stops from city 0 to 2 is marked in red and has cost 100 + 100 = 200.</pre> Example 3: <pre># 2 <= k <= 100 # 0 <= flights.length <= (n * (n - 1) / 2) # flights[i].length == 3 # 0 <= from, to <= n</pre>	<pre># from i to j # 1 <= price <= 104 # There will not be any multiple flights between two cities. # 0 <= src, dst, k <= n # src != dst Brute Force (Python) # Brute Force Approach class Solution: def findCheapestPrice(self, n, flights, src, dst, k): # Brute Force O(V*(K+2)) - DFS trying all paths with at most k stops from collections import defaultdict graph = defaultdict(list) for u, v, price in flights: graph[u].append((v, price)) self.res = float('inf') def dfs(node, stops, cost): if node == dst: self.res = min(self.res, cost) if stops > k: return if cost + price < self.res: dfs(node, stops + 1, cost + price) dfs(src, 0, 0) return self.res if self.res < float('inf') else -1</pre> Community Solutions (Python) WalKCC <pre>class Solution: def findCheapestPrice(self, n: int, flights: List[List[int]], src: int, dst: int, k: int) -> int: graph = {} for i in range(n): graph[i] = [] for u, v, price in flights: graph[u].append((v, price)) self.res = float('inf') def dfs(node, stops, cost): if node == dst: self.res = min(self.res, cost) if stops > k: return if cost + price < self.res: dfs(node, stops + 1, cost + price) dfs(src, 0, 0) return self.res if self.res < float('inf') else -1</pre>	<pre>if node == dst: self.res = min(self.res, cost) return if stops > k: return for nei, price in graph[node]: if cost + price < self.res: dfs(nei, stops + 1, cost + price) else -1</pre> Community Solutions (Python) WalKCC <pre>class Solution: def findCheapestPrice(self, n: int, flights: List[List[int]], src: int, dst: int, k: int) -> int: graph = {} for i in range(n): graph[i] = [] for u, v, price in flights: graph[u].append((v, price)) self.res = float('inf') def dfs(node, stops, cost): if node == dst: self.res = min(self.res, cost) if stops > k: return if cost + price < self.res: dfs(node, stops + 1, cost + price) dfs(src, 0, 0) return self.res if self.res < float('inf') else -1</pre>
---	--	---	---	---	--

<pre>for v, w in flights: graph[v].append((w, price)) return self._dijkstra(graph, src, dst, k)</pre> <pre>def _dijkstra(self, graph, list[graph], int, int): src, int, int dist = [math.inf] * n while minheap: d, u, stops = heapq.heappop(minheap) while minheap: d, u, stops = heapq.heappop(minheap)</pre>	<pre>if u == dst: return d if stops == 0 or d > dist[u]: continue for v, w in graph[u]: if d + price < dist[v]: dist[v] = d + price heapq.heappush(minheap, (dist[v], v, stops + 1)) return -1</pre> LeetCode <pre>class Solution: def findCheapestPrice(self, n: int, flights: List[List[int]], src: int, dst: int, k: int) -> int: INF = float('inf') dist = [INF] * n dist[src] = 0 minheap = [(0, src, 0)] while minheap: d, u, stops = heapq.heappop(minheap) if u == dst: return d if stops > k: continue for v, w in graph[u]: if d + price < dist[v]: dist[v] = d + price heapq.heappush(minheap, (dist[v], v, stops + 1))</pre>	<pre># Priority queue: (total_cost, current_city, stops so far) heapq.heappush(minheap, (0, src, 0)) # Dictionary to store the best cost to reach a city with a given stop count best = {} while heap: cost, city, stops = heapq.heappop(heap) # Return cost if destination is reached if city == dst: return cost</pre>	<pre># If the current number of stops exceeds k, skip further processing if stops > k: continue # Expand the neighboring flights for neighbor, price in graph[city]: new_cost = cost + price # Only proceed if this route is cheaper or not yet explored for this many stops if (neighbor, stops + 1) not in best or new_cost < best[(neighbor, stops + 1)]: best[(neighbor, stops + 1)] = new_cost heapq.heappush(heap, (new_cost, neighbor, stops + 1)) return -1</pre> Example usage: <pre>print(findCheapestPrice(4, [[0,1,100],[1,2,100],[2,0,100],[1,3,600],[2,3,200]], 0, 3, 1))</pre> LeetCode	<pre>class Solution: def findCheapestPrice(self, n: int, flights: List[List[int]], src: int, dst: int, k: int) -> int: INF = float('inf') dist = [INF] * n dist[src] = 0 minheap = [(0, src, 0)] while minheap: d, u, stops = heapq.heappop(minheap) if u == dst: return d if stops > k: continue for v, w in graph[u]: if d + price < dist[v]: dist[v] = d + price heapq.heappush(minheap, (dist[v], v, stops + 1))</pre>	Heap #973 K Closest Points to Origin LeetCode - SimpleTest - WalKCC - LeetCode Array - Math - Divide and Conquer - Sorting - Heap Lists: Grid 169 Time Complexity: O(n log n) with a sorting approach, O(n log k) with a heap approach, or average O(n) with a Quickselect approach. Space Complexity: O(n) if extra space is used for sorting, or O(1) to Problem Given an array of points where points[i] = [xi, yi] represents a point on the X-Y plane and an integer k, return the k closest points to the origin (0, 0). The distance between two points on the X-Y plane is the Euclidean distance (e.g., $\sqrt{1^2 + 2^2} = \sqrt{5}$). You may return the answer in any order. The answer is guaranteed to be unique (except for the order that it is in). Example 1:
---	--	--	--	---	---

Input: points = [[1,3],[-2,2]], k = 2 Output: [[1,3],[-2,2]] Explanation: The distance between (-2, 2) and the origin is $\sqrt{8}$. The distance between (1, 3) and the origin is $\sqrt{10}$. Since $\sqrt{8} < \sqrt{10}$, (-2, 2) is closer to the origin. We only need the closest k = 2 points from the origin, so the answer is just [[-2,2], [1,3]]. Example 2:	<pre>Input: points = [[3,1],[-1,-2]], k = 2 Output: [[3,1],[-1,-2]] Explanation: The distance between (-1, -2) and the origin is $\sqrt{5}$. The distance between (3, 1) and the origin is $\sqrt{10}$. Since $\sqrt{5} < \sqrt{10}$, (-1, -2) is closer to the origin. We only need the closest k = 2 points from the origin, so the answer is just [[-1,-2], [3,1]].</pre> Community Solutions (Python) WalKCC	<pre>class Solution: def kClosest(self, points: List[List[int]], k: int) -> List[List[int]]: # Sort the points based on their squared Euclidean distance from the origin. points.sort(key=lambda point: point[0]**2 + point[1]**2) return points[:k]</pre> Python Solution <pre>def kClosest(self, points: List[List[int]], k: int) -> List[List[int]]: # Sort the points based on their squared Euclidean distance from the origin. points.sort(key=lambda point: point[0]**2 + point[1]**2) return points[:k]</pre>	<pre># Python Solution def kClosest(self, points: List[List[int]], k: int) -> List[List[int]]: # Sort the points based on their squared Euclidean distance from the origin. points.sort(key=lambda point: point[0]**2 + point[1]**2) return points[:k]</pre> Example usage: <pre>points = [[1,3],[-1,-2]] k = 2 print(kClosest(points, k))</pre>	Heap #1057 Campus Bikes LeetCode - SimpleTest - WalKCC - LeetCode Array - Greedy - Sorting - Heap Lists: Premium 98 Time Complexity: O(n * log(n * m)) where n is the number of workers and m is the number of bikes. Space Complexity: O(n * m) for storing all worker-bike pairs. Problem On a campus represented on the X-Y plane, there are n workers and m bikes, with n <= m. You are given an array workers of length n where workers[i] = [xi, yi] is the position of the ith worker. You are also given an array of bikes of length m where bikes[i] = [xi, yi] is the position of the bike. All the given positions are unique. Assign a bike to each worker. Among the available bikes and workers, we choose the (workeri, bikei) pair with the shortest Manhattan distance between each other and assign the bike to that worker. If there are multiple (workeri, bikei) pairs with the same shortest Manhattan distance, we choose the pair with the smallest worker index. If there are multiple ways to do that, we choose the pair with the smallest bike index.	Repeat this process until there are no available workers. Return an array answer of length n, where answer[i] is the index (0-indexed) of the bike that the ith worker is assigned to. The Manhattan distance between two points p1 and p2 is $p1.x - p2.x + p1.y - p2.y$. Example 1:
---	--	--	--	---	---

<pre>class Solution: def pathSum(self, root: Treehead, sum: int) -> List[List[int]]: ans = [] def dfs(root: Treehead, sum: int, path: List[int]) -> None: if not root: return if root.val == sum and not root.left and not root.right: ans.append(path + [root.val]) return dfs(root, left, sum - root.val, path + [root.val]) dfs(root, right, sum - root.val, path + [root.val]) dfs(root, sum, []) return ans</pre> • LeetCode	<pre># Definition for a binary tree node. # class Treehead: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def pathSum(self, root: Optional[Treehead], targetSum: int) -> List[List[int]]: def dfs(node: int): if root is None: return s = root.val t.append(root.val) if root.left is None and root.right is None and s == targetSum: ans.append(t[:]) dfs(root, left, s) dfs(root, right, s) t.pop() ans = [] t = [] dfs(root, 0) return ans</pre> • SimplyLeet	<pre># Definition for a binary tree node. # class Treehead: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right def pathSum(root, targetSum): result = [] # This will store all valid paths if not root: return # Base case: reached the end of a path # Add the current node's value to the path current_path.append(node.val) # Check if it's a leaf and if the path sum equals targetSum if not node.left and not node.right and node.val == remaining_sum: result.append(list(current_path)) # Add a copy of the current path</pre>	<pre>else: # Continue the search in the left and right subtrees dfs(node, left, current_path, remaining_sum - node.val) dfs(node, right, current_path, remaining_sum - node.val) # Backtrack: remove the last element before returning to the caller current_path.pop() dfs(root, [], targetSum) return result</pre> • LC.ca <pre># Definition for a binary tree node. # class Treehead: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def pathSum(self, root: Optional[Treehead], targetSum: int) -> List[List[int]]: def dfs(root, s): if root is None: return</pre>	<pre>return s += root.val t.append(root.val) if root.left is None and root.right is None and s == targetSum: ans.append(t[:]) dfs(root, left, s) dfs(root, right, s) t.pop() ans = [] t = [] dfs(root, 0) return ans</pre>	Round 5 · Mid · Medium · 5 questions Greedy
Round 5 · Mid · Medium p.2269	Round 5 · Mid · Medium p.2270	Round 5 · Mid · Medium p.2271	Round 5 · Mid · Medium p.2272	Round 5 · Mid · Medium p.2273	Round 5 · Mid · Medium p.2274

<pre>Greedy #134 Gas Station MEDIUM LeetCode · SimplyLeet · WalkCC · LeetCode Array · Greedy Lists: Grid 169 Time Complexity: O(n), where n is the number of gas stations, as we traverse the list only once. Space Complexity: O(1), as no extra space is used other than a few variables. Explanation There are n gas stations along a circular route, where the amount of gas at the ith station is gas[i]. You have a car with an unlimited gas tank and it costs cost[i] of gas to travel from the ith station to its next (i + 1)th station. You begin the journey with an empty tank at one of the gas stations. Given two integer arrays gas and cost, return the starting gas station's index if you can travel around the circuit once in the clockwise direction, otherwise return -1. If there exists a solution, it is guaranteed to be unique. Example 1:</pre>	<pre>Input: gas = [1,2,3,4,5], cost = [3,4,5,1,2] Output: 3 Explanation: Start at station 3 (index 3) and fill up with 4 unit of gas. Your tank = 0 + 4 = 4 Travel to station 4. Your tank = 4 - 1 + 5 = 8 Travel to station 0. Your tank = 8 - 2 + 1 = 7 Travel to station 1. Your tank = 7 - 3 + 2 = 6 Travel to station 2. Your tank = 6 - 4 + 3 = 5 Example 2: Input: gas = [2,3,4], cost = [3,4,3] Output: -1 Explanation: You can't start at station 0 or 1, as there is not enough gas to travel to the next station. Let's start at station 2 and fill up with 4 unit of gas. Your tank = 0 + 4 = 4 Travel to station 0. Your tank = 4 - 3 + 2 = 3 Travel to station 1. Your tank = 3 - 4 + 3 = 2 You cannot travel back to station 2, as it requires 4 unit of gas but you only have 2.</pre> Constraints: - n == gas.length == cost.length 1 <= n <= 10⁵ 0 <= gas[i], cost[i] <= 10⁴ - The input is generated such that the answer is unique. Brute Force (Python)	<pre># Brute Force Approach class Solution: def canCompleteCircuit(self, gas: cost): # Brute Force O(n^2) - try starting at every station n = len(gas) for start in range(n): tank = 0 for step in range(n): i = (start + step) % n tank += gas[i] - cost[i] if tank < 0: break else: return start return -1</pre> Community Solutions (Python) • WalkCC	<pre>class Solution: def canCompleteCircuit(self, gas: List[int], cost: List[int]) -> int: n = len(gas) i = 1 cnt = s = 0 while cnt <= 0: cnt += gas[i] - cost[i] i = (i + 1) % n while s < 0 & cnt <= 0: return -1 if cnt < 0 else ans ans = i + 1 # Start from the next index.</pre> • LeetCode <pre>class Solution: def canCompleteCircuit(self, gas: List[int], cost: List[int]) -> int: n = len(gas) i = 1 cnt = s = 0 while cnt <= 0: cnt += gas[i] - cost[i] i = (i + 1) % n while s < 0 & cnt <= 0:</pre>	<pre>i = 1 s = gas[i] - cost[i] return -1 if s < 0 else i</pre> • SimplyLeet <pre># Define a function to find starting gas station index def canCompleteCircuit(gas, cost): total_surplus = 0 # Total gas surplus after completing the route current_surplus = 0 # Gas surplus while iterating from a candidate start station start_index = 0 # Candidate starting station index # Loop through each station for i in range(len(gas)): # Calculate net gas after leaving station i surplus = gas[i] - cost[i]</pre>	<pre>total_surplus += surplus current_surplus += surplus # If current surplus becomes negative, station i is not a valid start. if current_surplus < 0: # Reset starting station to the next station start_index = i + 1 current_surplus = 0 # Reset current surplus # Check if overall surplus is non-negative return start_index if total_surplus >= 0 else -1</pre> • LC.ca <pre># Example usage: gas = [1,2,3,4,5] cost = [3,4,5,1,2] print(canCompleteCircuit(gas, cost)) # Output: 3</pre>
Round 5 · Mid · Medium p.2275	Round 5 · Mid · Medium p.2276	Round 5 · Mid · Medium p.2277	Round 5 · Mid · Medium p.2278	Round 5 · Mid · Medium p.2279	Round 5 · Mid · Medium p.2280

<pre>class Solution: def canCompleteCircuit(self, gas: List[int], cost: List[int]) -> int: n = len(gas) i = 1 cnt = s = 0 while cnt <= 0: cnt += gas[i] - cost[i] i = (i + 1) % n while s < 0 & cnt <= 0: return -1 if cnt < 0 else i</pre>	<pre>Greedy #179 Largest Number MEDIUM LeetCode · SimplyLeet · WalkCC · LeetCode Array · String · Greedy · Sorting Lists: Grid 169 Time Complexity: O(n log n), where n is the number of elements in the array and k is the maximum number of digits in a number (due to string comparisons in the custom sort). Space Complexity: O(n) Problem Given a list of non-negative integers nums, arrange them such that they form the largest number and return it. Since the result may be very large, you need to return a string instead of an integer. Example 1: Input: nums = [10,2] Output: "210" Example 2: Input: nums = [3,30,34,5,0] Output: "534300" Constraints: 1 <= nums.length <= 100</pre>	<pre># 0 <= nums[i] <= 109 Brute Force (Python) # Brute Force Approach class Solution: def compare(self, x, y): # Brute Force O(n^2) - try all orderings, pick largest concatenation from itertools import permutations best = "" for perm in permutations(nums): candidate = ''.join(perm) if candidate >= best: best = candidate return best.lstrip('0') or '0'</pre> Community Solutions (Python) • WalkCC <pre>class LargestNumber(str): def __lt__(self, y: str) -> bool: return x + y > y + x class Solution: def largestNumber(self, nums: List[int]) -> str: return ''.join(sorted(map(str, nums), key=lambda key: LargestNumber(key)).lstrip('0') or '0')</pre> • LeetCode	<pre>class Solution: def largestNumber(self, nums: List[int]) -> str: nums = [str(v) for v in nums] nums.sort(key=cmp_to_key(lambda a, b: 1 if a + b < b + a else -1)) return ''.join(nums) if nums[0] != "0" else "" # SimplyLeet # Import cmp_to_key to convert a comparator function to a key function for sorting from functools import cmp_to_key # Define the comparator function def compare(x, y): # Compare two possible orders: xy and yx if x + y > y + x: return -1 # x should come before y elif x + y < y + x: return 1 # y should come before x</pre>	<pre>else: return 0 # both orders are equal def largestNumber(nums): # Convert all integers to strings num_str = [str(num) for num in nums] # Sort the strings using the custom comparator num_str.sort(key=cmp_to_key(compare)) # If the largest number is '0', the entire number is 0 so return '0' return ''.join(num_str) if num_str[0] != '0' else '0'</pre> • LC.ca <pre>class Solution: def largestNumber(self, nums: List[int]) -> str: nums = [str(v) for v in nums] nums.sort(key=cmp_to_key(lambda a, b: 1 if a + b < b + a else -1)) return ''.join(nums) if nums[0] != "0" else "" # SimplyLeet # Example usage: print(largestNumber([3, 30, 34, 5, 0])) # Output: "534300"</pre>	<pre>Greedy #280 Wiggle Sort MEDIUM LeetCode · SimplyLeet · WalkCC · LeetCode Array · Greedy · Sorting Lists: Premium 98 Time Complexity: O(n) - Only one pass through the array is needed. Space Complexity: O(1) - The modifications are done in-place without extra data structures. Problem Given an integer array nums, reorder it such that nums[0] <= nums[1] >= nums[2] <= nums[3]... You may assume the input array always has a valid answer. Example 1: Input: nums = [3,5,2,1,6,4] Output: [3,5,1,6,2,4] Explanation: [1,6,2,5,3,4] is also accepted. Example 2: Input: nums = [6,6,5,6,3,8] Output: [6,6,3,6,5,8] Constraints: 1 <= nums.length <= 5 * 10^4</pre>
Round 5 · Mid · Medium p.2281	Round 5 · Mid · Medium p.2282	Round 5 · Mid · Medium p.2283	Round 5 · Mid · Medium p.2284	Round 5 · Mid · Medium p.2285	Round 5 · Mid · Medium p.2286

<pre># 0 <= nums[i] <= 104 # It is guaranteed that there will be an answer for the given input nums. Follow up: Could you solve the problem in O(n) time complexity? Brute Force (Python) # Brute Force Approach class Solution: def wiggleSort(self, nums): # Brute Force O(n^2) - check all subsets/orders exhaustively from itertools import permutations best = float('inf') for perm in permutations(nums): cost = sum(perm) best = min(best, cost) return best</pre> Community Solutions (Python) • WalkCC	<pre>class Solution: def wiggleSort(self, nums: List[int]) -> None: # Iterate over the List starting from index 1 for i in range(1, len(nums)): # Check the condition based on the parity of the index if i % 2 == 1: # For odd index, if previous element is greater, swap them if nums[i] > nums[i-1]: nums[i], nums[i-1] = nums[i-1], nums[i] else: # For even index, if previous element is smaller, swap them if nums[i] < nums[i-1]: nums[i], nums[i-1] = nums[i-1], nums[i] return nums # Example usage: nums = [3,5,2,1,6,4] print(wiggleSort(nums))</pre> • LC.ca	<pre>""" Python solution for Wiggle Sort def wiggleSort(nums): # Iterate over the List starting from index 1 for i in range(1, len(nums)): # Check the condition based on the parity of the index if i % 2 == 1: # For odd index, if previous element is greater, swap them if nums[i] > nums[i-1]: nums[i], nums[i-1] = nums[i-1], nums[i] else: # For even index, if previous element is smaller, swap them if nums[i] < nums[i-1]: nums[i], nums[i-1] = nums[i-1], nums[i] return nums # Example usage: nums = [3,5,2,1,6,4] print(wiggleSort(nums))</pre> • LC.ca	<pre>""" nath prove: example [3, 5, 2, 1] when reaching 2, all good then meet 1, so here comes the question, will the number after 2 violating the wiggle rule? answer is no in example, when reaching 2: if [3, 5, 2, 18], so 18 is bigger than 2, then no swap needed according to the if (i) conditions if [3, 5, 2, 1], so previous round, guaranteed that 2 is smaller than 5. Add, now a swap needed meaning the number is smaller than 2, i.e. must be smaller than 5, so wiggle rule is still good. # Example usage: def wiggleSort(self, nums: List[int]) -> None: """ Do not return anything, modify nums in-place instead. """ for i in range(1, len(nums)): if (i % 2 == 1 and nums[i] >= nums[i - 1]) or (i % 2 == 0 and nums[i] <= nums[i - 1]): nums[i], nums[i - 1] = nums[i - 1], nums[i]</pre>	<pre>""" for i in range(1, len(nums)): if (i % 2 == 1 and nums[i] >= nums[i - 1]) or (i % 2 == 0 and nums[i] <= nums[i - 1]): nums[i], nums[i - 1] = nums[i - 1], nums[i] # Example usage: def wiggleSort(self, nums: List[int]) -> None: """ Do not return anything, modify nums in-place instead. """ for i in range(1, len(nums)): if (i % 2 == 1 and nums[i] >= nums[i - 1]) or (i % 2 == 0 and nums[i] <= nums[i - 1]): nums[i], nums[i - 1] = nums[i - 1], nums[i]</pre>	<pre>""" if n % 2 == 0 or nums[-1] <= nums[-2]: nums[-1], nums[-2] = nums[-2], nums[-1] ##### insert random class Solution: def wiggleSort(self, nums: List[int]) -> None: """ Do not return anything, modify nums in-place instead. """ if len(nums) <= 1: return # Find the median using quickselect n = len(nums) mid = self.quickselect(nums, 0, n-1, (n-1)//2) # Create an empty array with the same length as nums</pre>
Round 5 · Mid · Medium p.2287	Round 5 · Mid · Medium p.2288	Round 5 · Mid · Medium p.2289	Round 5 · Mid · Medium p.2290	Round 5 · Mid · Medium p.2291	Round 5 · Mid · Medium p.2292

<pre>ans = [None] * n # Assign the median to every other element i = 1 j = n-1 while i <= j: if n % 2 == 1: ans[i] = ans[j] i += 2 j -= 2 elif n % 2 == 0: ans[i] = ans[j] i += 2 j -= 2 # Copy the result back to nums nums[:] = ans def quickselect(self, nums, left, right, k): """</pre>	<pre>Returns the k-th smallest element in nums[left:right]. if left == right: return nums[left] # Partition the subarray around a pivot element pivot_idx = self.partition(nums, left, right) # Recursively select on the left or right subarray if k == pivot_idx: return nums[k] elif k < pivot_idx: return self.quickselect(nums, left, pivot_idx-1, k) else: return self.quickselect(nums, pivot_idx+1, right, k) def partition(self, nums, left, right): """ Partitions the subarray nums[left:right+1] using the first element as the pivot. Returns the final index of the pivot element.</pre>	<pre>""" pivot = nums[left] i, j = left+1, right while i <= j: if nums[i] <= pivot: i += 1 elif nums[j] >= pivot: j -= 1 else: nums[i], nums[j] = nums[j], nums[i] nums[left], nums[j] = nums[j], nums[left] return j</pre>	<pre>Greedy #954 Array of Doubled Pairs MEDIUM LeetCode · SimplyLeet · WalkCC · LeetCode Array · Hash Table · Greedy · Sorting Lists: CodeSignal Time Complexity: O(n log n) due to sorting. Space Complexity: O(n) for storing the frequency map. Problem Given an integer array of even length arr, return true if it is possible to reorder arr such that arr[2*i+1] = 2 * arr[2*i] for every 0 <= i < len(arr) / 2, or false otherwise. Example 1: Input: arr = [1,3,2,6] Output: false Example 2: Input: arr = [1,1,2,2,4,4] Output: true Example 3: Input: arr = [4,2,4,2,4] Output: true Explanation: We can take two groups, [2,4] and [4,2] to form [2,4,2,4] and [4,2,4,2].</pre>	<pre>Constraints: 2 <= arr.length <= 3 * 10^4 arr.length is even. -10^5 <= arr[i] <= 10^5 Brute Force (Python) # Brute Force Approach class Solution: def canReorderDoubled(self, arr): # Brute Force O(n^2) - check all subsets/orders exhaustively from itertools import permutations best = float('inf') for perm in permutations(arr): cost = sum(perm) best = min(best, cost) return best</pre> Community Solutions (Python) • WalkCC <pre>class Solution: def longestPalindrome(self, words: List[str]) -> int: n = len(words) count = [0] * 26 for i in range(26): for a in ord('a') - ord('a'): for b in ord('a') - ord('a'): if count[i][a] == count[i][b]: ans = min(ans, cnt[a][i] + cnt[b][i] + 2) ans += 2</pre>	<pre>class Solution: def canReorderDoubled(self, arr: List[int]) -> bool: from collections import Counter for key in sorted(Counter(keyvals).keys()): if count[key] % 2 != 0: return False return True # LeetCode class Solution: def canReorderDoubled(self, arr: List[int]) -> bool: freq = Counter(arr) for freq[a] <= 1: return False for x in sorted(freq.keys()): if freq[x] <= 1: return True freq[x] -= 1 freq[2*x] -= freq[x] return True # SimplyLeet</pre>
Round 5 · Mid · Medium p.2293	Round 5 · Mid · Medium p.2294	Round 5 · Mid · Medium p.2295	Round 5 · Mid · Medium p.2296	Round 5 · Mid · Medium p.2297	Round 5 · Mid · Medium p.2298

<pre>from collections import Counter def canReorderDoubled(arr): # Count frequency for each element in arr count = Counter(arr) # Sort the array based on the absolute value of elements for x in sorted(arr, key=abs): # If x or -x is left to be paired, skip to the next element if count[x] == 0: continue # Check if double the current number exists in sufficient frequency if count[2 * x] < count[x]: return False # Decrement the frequency for the double of x count[2 * x] -= count[x] return True # Example usage: print(canReorderDoubled([4,-2,-2,-4])) # Expected Output: True • LC.ca</pre>	<pre>class Solution: def canReorderDoubled(self, arr: List[int]) -> bool: freq = Counter(arr) for freq[a] <= 1: return False return False for x in sorted(freq, key=abs): if freq[x] <= 1: return False freq[x] -= 1 freq[2 * x] -= freq[x] return True</pre>	Greedy #2131 Longest Palindrome by Concatenating Two Letter Words MED LeetCode · SimplyLeet · WalkCC · LeetCode Array · Hash Table · String · Greedy · Counting Lists: CodeSignal Time Complexity: O(N), where n is the number of words, since we iterate through the list and perform constant time operations per word. Space Complexity: O(N), to store counts of words in the hash map Problem You are given an array of strings words. Each element of words consists of two lowercase English letters. Create the longest possible palindrome by selecting some elements from words and concatenating them in any order. Each element can be selected at most once. Return the length of the longest palindrome that you can create. If it is impossible to create any palindrome, return 0. A palindrome is a string that reads the same forward and backward. Example 1:	<pre>Input: words = ["lc","yt","lc","yt","ab"] Output: 8 Explanation: One longest palindrome is "yt" + "lc" + "lc" + "yt" = "ytlcylcylt", of length 8. Note that "lcytlc" is another longest palindrome that can be created.</pre> Example 2: <pre>Input: words = ["ab","ty","ty","lc","lc","ab"] Output: 8 Explanation: One longest palindrome is "ty" + "lc" + "lc" + "ty" = "tylcltyl", of length 8. Note that "lcytlc" is another longest palindrome that can be created, and so is "tyc".</pre> Constraints: 1 <= words.length <= 10⁵ - words[i].length == 2 - words[i] consists of lowercase English letters. Brute Force (Python)	<pre># Brute Force Approach class Solution: def longestPalindrome(self, words): # Brute Force O(n^2) - check all # subsets/orders exhaustively from itertools import permutations best = float('inf') for perm in permutations(words): cost = sum(perm) best = min(cost, best) return best</pre> Community Solutions (Python) • WalkCC <pre>class Solution: def longestPalindrome(self, words: List[str]) -> int: n = len(words) count = [0] * 26 for i in range(26): for a in ord('a') - ord('a'): for b in ord('a') - ord('a'): if count[i][a] == count[i][b]: ans = min(ans, cnt[a][i] + cnt[b][i] + 2) ans += 2</pre>	<pre>count[j][i] += 1 else: count[i][j] += 1 for i in range(26): if count[i][i]: return ans + 2 return ans</pre> • LeetCode <pre>class Solution: def longestPalindrome(self, words: List[str]) -> int: cnt = Counter(words) ans = 0 for k, v in cnt.items(): if k[0] == k[1]: ans += v // 2 * 2 else: ans += min(v, cnt[k[0]][k[1]]) * 2 # SimplyLeet</pre>
Round 5 · Mid · Medium	Round 5 · Mid · Medium	Round 5 · Mid · Medium	Round 5 · Mid · Medium	Round 5 · Mid · Medium	Round 5 · Mid · Medium

[illegible]

```

    if self.capacity <= 0:
        return
    if key in self.key_to_val_freq:
        # Update value and frequency if key
        exists.
        self.key_to_val_freq[key] = (value,
self.key_to_val_freq[key][1])
        self.update_freq(key)
    else:
        # If cache is full, evict the least
        frequently used (and least recently used) key.
        if len(self.key_to_val_freq) >=
self.capacity:
            # Remove the first key from the
lowest frequency list.

```

```

    key.remove() # self.freq[key] += 1
    popitem(last=False)
    del self.freq[key]
    self.key_to_val_freq[key] = (value, 1)
    if not in self.freq_to_keys:
        self.freq_to_keys[key] = 1
    OrderedDict()
    self.freq_to_keys[key] = None
    self.min_freq = 1 # Reset min_freq.

```

• **LC64**

from collections import defaultdict

```

class LRUCache:
    def __init__(self, capacity: int):
        self.capacity = capacity
        self.key_to_val = {}
        self.key_to_freq = defaultdict(int)
        self.freq_to_keys = {}
        defaultdict(OrderedDict)
        self.min_freq = 0

```

```
def get(self, key: int) -> int:
    if key not in self.key_to_value:
        return -1

    # Update the frequency
    self._update_frequency(key)
    return self.key_to_value[key]

def put(self, key: int, value: int) -> None:
    if self.capacity == 0:
        return

    if key in self.key_to_value:
        # Update the value and frequency
        self.key_to_value[key] = value
        self._update_frequency(key)
    else:
        if len(self.key_to_value) >= self.capacity:
            # Evict the least frequently used
            self._evict()
```

```
# Add the new key-value pair
self.freq_to_value[key] = value
self.freq_to_freq[key] = 1
self.freq_to_keys[key] = None
self.min_freq = 1

def update_frequency(self, key: int) -> None
    freq = self.freq_to_freq[key]
    del self.freq_to_keys[key]

    if not self.freq_to_keys[freq]:
        # If there are no keys with the
        # previous frequency, update min_freq
        if self.min_freq == freq:
            self.min_freq += 1
            del self.freq_to_keys[freq]

    freq += 1
    self.freq_to_freq[key] = freq
    self.freq_to_keys[freq[key]] = None
```

```
def _evict(self) -> None:
    keys = self._freq.to_keys[self.min_freq]
    self._keys = self._keys[self.min_freq:]
    del self._key_to_value[evict_key]
    del self._key_to_freq[evict_key]

# Your LRUcache object will be instantiated and
called as such:
# obj = LRUcache(capacity)
# param_1 = obj.get(key)
# obj.put(key,value)

#####

class Node:
    def __init__(self, key: int, value: int) ->
        None:
        self.key = key
        self.value = value
        self.next = None
```

```

    self.prev = None
    self.next = None

class DoublyLinkedList:
    def __init__(self) -> None:
        self.head = Node(-1, -1)
        self.tail = Node(-1, -1)
        self.head.next = self.tail
        self.tail.prev = self.head

    def add_first(self, node: Node) -> None:
        node.prev = self.head
        node.next = self.head.next
        self.head.next.prev = node
        self.head.next = node

    def remove(self, node: Node) -> None:
        node.next.prev = node.prev
        node.prev.next = node.next

```

```

node.next, node.prev = None, None
return node

def remove_last(self) -> Node:
    return self.remove(self.tail.prev)

def is_empty(self) -> bool:
    return self.head.next == self.tail

class IFUCase:
    def __init__(self, capacity: int):
        self.capacity = capacity
        self.min_freq = 0
        self.map = defaultdict(Node)
        self.freq_map = defaultdict(lambda: defaultdict(int))

    def get(self, key: int) -> int:
        if self.capacity == 0 or key not in self.map:
            return -1

```

```

node = self.map(key)
self.incr_freq(node)
return node.value

def put(self, key: int, value: int) -> None:
    if self.capacity == 0:
        return
    if key in self.map:
        node = self.map[key]
        node.value = value
    else:
        self.incr_freq(node)
        return
    if len(self.map) == self.capacity:
        ls = self.freq_map[self.min_freq]
        node = ls.remove_last()
        self.map.pop(node.key)
        node = Node(key, value)
        self.add_node(node)
        self.map[key] = node
        self.min_freq = 1

```

```

def incr_freq(self, node: Node) -> None:
    freq = node.freq
    ls = self.freq_map[freq]
    ls.remove(node)
    if ls is empty():
        self.freq_map.pop(freq)
    if freq == self.min_freq:
        self.min_freq = 1
    node.freq += 1

    self.add_node(node)

def add_node(self, node: Node) -> None:
    freq = node.freq
    ls = self.freq_map[freq]
    ls.add_first(node)
    self.freq_map[freq] = ls

# Your LFUCache object will be instantiated and
called as such:
# obj = LFUCache(capacity)
# param_1 = obj.get(key)
# obj.put(key,value)

```

Round 6 · Mid · Hard

Stack

Round 6 · Mid · Hard · 8 questions

Round 6 · Mid · Hard

Stack

#32 Longest Valid Parentheses

LeetCode · Simple/Leet · Walk/Code

LeetCode · Dynamic Programming · Stack

Lists/Count/Map

Time Complexity: $O(n)$ where n is the length of the string. Space Complexity: $O(n)$ for the stack data structure

Problem

Given a string containing just the characters "(" and ")", return the length of the longest valid (well-formed) parentheses substring.

Example 1:

Input: s = "(()"

Output: 2

Explanation: The longest valid parentheses substring is "()".

Example 2:

Input: s = "())(")

Output: 4

Explanation: The longest valid parentheses substring is "())(".

Example 3:

```

Input: s = ""
Output: 0

Constraints:
0 <= length <= 3 * 104
s[i] is '(', or ')', or '*'

Community Solutions (Python)

@wzschlcr
class Solution:
    def longestValidParentheses(self, s: str) -> int:
        s2 = ')' + s
        # dp[i] = the length of the longest valid
        # parentheses in the substring
        # s[1: i + 1]
        dp = [0] * len(s2)
        for i in range(1, len(s2)):
            if s2[i] == ')' and s2[i - 1] == '(':
                dp[i] = dp[i - 1] + dp[i - dp[i - 1] - 1] + 2
            return max(dp)
        return 0

```

```

class Solution:
    def longestValidParentheses(self, s: str) -> int:
        n = len(s)
        f = [0] * (n + 1)
        for i in enumerate(s, 1):
            if s[i] == '(':
                if i > 1 and s[i - 2] == ')':
                    f[i] = f[i - 2] + 2
                else:
                    j = i - f[i - 1] - 1
                    if j > 0 and s[j] == '(':
                        f[i] = f[i - 1] + 2 + f[j]
            return max(f)

class Solution:
    def longestValidParentheses(self, s: str) -> int:
        stack = [-1]
        ans = 0
        for i in range(len(s)):
            if s[i] == '(':
                stack.append(i)
            else:
                stack.pop()
            if not stack:

```

```

stack.append(i)
else:
    ans = max(ans, i - stack[-1])

return ans

# Simplified

# Python solution using a stack
def LongestValidParentheses(s: str) -> int:
    # Initialize the stack with the base index -1
    stack = [-1]
    max_length = 0

    # Iterate over the string with index
    for i, char in enumerate(s):
        # If char == '(', push the index of '(' onto the stack
        if char == '(':
            stack.append(i)
        else:
            # Pop the last index for ')'
            stack.pop()
            # If not stack:
            if not stack:
                # If stack is empty, push current
                # index as the new base
                stack.append(i)
            else:
                # Calculate the length of the
                # current valid substring
                current_length = i - stack[-1]

```

```

max_length = max(max_length,
current_length)

return max_length

# Example usage:
print(longestValidParentheses("{}(){}")) # Output:
4

class Solution:
    def longestValidParentheses(self, s: str) ->
int:
    left = right = 0
    res = 0
    for c in s: # from left to right, '('() =>
will never hit left==right
        if c == '(':
            left += 1
        else:
            right += 1
        if left == right:
            res = max(res, left + right)
    return res

```

```

    res = max(res, 2 + left)
    if left < right:
        left = right = 0

    left = right = 0 # dont forget to reset
    for c in reversed(s): # from right to left
        '()') == will never hit left=right
        if c == '(':
            left += 1
        else:
            right += 1

    if left == right:
        res = max(res, 2 + left)
        if left > right: # reverse '<' to '>'
            left = right = 0

    return res
#####

class Solution:

```

```
def longestValidParentheses(self, s: str) -> int:
    n = len(s)
    if n < 2:
        return 0
    dp = [0] * n
    for i in range(1, n):
        if s[i] == ')':
            if s[i - 1] == '(':
                dp[i] = 2 + dp[i - 2] if i > 1
            else:
                j = i - dp[i - 1] - 1
                if j >= 0 and s[j] == '(':
                    dp[i] = 2 + dp[i - 1] + dp[j - 1]
        return max(dp)

#####

s = "abcde"
print(*[s[i], c for i, c in enumerate(s, 1)])
```

```

1  # a
2  # b
3  # c
4  # d
5  # e
6  # f
7  # g
8  [None, None, None, None, None, None, None]
9
10 ...
11 ...
12
13 class Solution:
14     def longestValidParentheses(self, s: str) ->
15     int:
16         n = len(s)
17         f = [0] * (n + 1)
18         for i, c in enumerate(s, 1): # starting i
19             from 1, 8
20                 if c == "(":
21                     if i > 1 and s[i - 2] == "(":
22                         f[i] = f[i - 2] + 2
23                     else:
24                         j = i - 1
25                         if j > 1 and s[j - 1] == "(":
26                             f[i] = f[i - 1] + 2 + f[j -
27 1]
28         return max(f)

```

#42 Trapping Rain Water

Link: [SimplyLearn - WarmUpC - LeetCode](#)

Array - Two Pointers - Dynamic Programming - Stack - Monotonic Stack

Lists: [Grid 369](#)

Time Complexity: $O(n)$ Space Complexity: $O(1)$ when using the two-pointer approach

Problem

Given a non-negative integers representing an elevation map where the width of each bar is 1, compute how much water it can trap after raining.

Example 1:

Bar Index	Height	Water Trapped
0	0	0
1	1	1
2	4	0
3	2	2
4	6	0
5	3	3
6	5	0

```

Input: height = [0,1,2,1,3,1,2,1,2,1,2]
Output: 6
Explanation: The above elevation map (black sections) is
represented by array [0,1,2,1,3,1,2,1,2,1,2]. In this
case, 6 units of rain water (blue section) are being
trapped.

Example 2:
Input: height = [4,2,0,3,2,5]
Output: 9

Constraints:
n == height.length
1 <= n <= 104
0 <= height[i] <= 105

Brute Force Approach (Python)

# Brute Force Approach
class Solution:
    def trap(self, height):
        # Brute Force O(n^2) ~ for each bar scan
        left_ptr for max heights
        n = len(height)
        res = 0
        for i in range(n):
            left_max = max(height[:i+1])
            right_max = max(height[i:])
            res += min(left_max, right_max) - height[i]

```

```

    return res

```

Community Solutions (Python)

• WalkCC

```

class Solution:
    def trap(self, height: list[int]) -> int:
        n = len(height)
        l = [0] * n
        r = [0] * n
        for i, h in enumerate(height):
            l[i] = h if i == 0 else max(h, l[i - 1])
        for i, h in reversed(list(enumerate(height))):
            r[i] = h if i == n - 1 else max(h, (r[i + 1]))
        return sum(max(l[i], r[i]) - h
                    for i, h in enumerate(height))

```

```

class Solution:
    def trap(self, height: List[int]) -> int:
        if not height:
            return 0

        ans = 0
        l = 0
        r = len(height) - 1
        maxl = height[l]
        maxR = height[r]

        while l < r:
            if maxl < maxR:
                ans += maxl - height[l]
                l += 1
                maxl = max(maxl, height[l])
            else:
                ans += maxR - height[r]
                r -= 1
                maxR = max(maxR, height[r])

        return ans

```

```
class Solution:
    def trap(self, height: List[int]) -> int:
        n = len(height)
        left = [height[0]] * n
        right = [height[-1]] * n
        for i in range(1, n):
            left[i] = max(left[i - 1], height[i])
            right[n - i - 1] = max(right[n - i - 1],
                                   height[n - i - 1])
        return sum(min(left, right) - h for i, r, h
                    in zip(left, right, height))

# Simple Logic
# Python solution using the two pointers approach
def trap(height):
    # Initialize left and right pointers and water accumulator
    left, right = 0, len(height) - 1
    left_max, right_max = 0, 0
    water = 0

    # Traverse the elevation map from both ends
    while left < right:
        # Update left_max and right_max as we
        encounter new
```

```

    if height[left] < height[right]:
        # left side is the determining side
        left_max = height[left] # update
        left_max = max(left_max, # update
            left_max since current height is higher
            else:
                water = left_max - height[left] #
                water trapped at left position
                left = -- i move left pointer to the
                right
            else:
                # right side is the determining side
                right_max = height[right] # update
                right_max = max(right_max, # update
                    right_max since current height is higher
                    else:
                        water = right_max - height[right]
                        # water trapped at right position
                        right = -- i move right pointer to the
                        left
                return water
    # Example usage:
    print(trap([1,1,2,1,2,1,1,1,2,1,1])) # Expected
    output: 6

```

```

class Solution:
    def trap(self, height: List[int]) -> int:
        n = len(height)
        if n < 3:
            return 0

        lmx = [height[0]] * n
        rxm = [height[-1]] * n
        for i in range(1, n):
            lmx[i] = max(lmx[i - 1], height[i]) # self compare
            rxm[n - 1 - i] = max(rxm[n - 1 - i], height[n - 1 - i])

        # no negative, worst is, min(left,right)
        itself = 0
        return sum(min(lmx[i], rxm[i]) - height[i] for i in range(n))

#####

class Solution: # zip
    def trap(self, height: List[int]) -> int:
        n = len(height)

```

```

left = height[0] + 1
right = height[-1] + 1
for i in range(1, n):
    left[i] = max(left[i - 1], height[i])
    right[i - 1] = max(right[i - 1],
height[i] - i - 1)
return summin(left, r) - h for l, r, h in zip(left, right, height)

#####

class Solution: # find the highest bar first

    def trap(self, height: List[int]) -> int:
        if not height:
            return 0

        total_water = 0
        max_index = 0
        max_height = float('-inf')

        # Find the index of the maximum height
        for i in range(len(height)):

```

```

        if height[i] > max_height:
            max_height = height[i]
            max_index = i

    # Calculate water trapped on the left side
    # of the maximum height
    left_max = height[i]
    for i in range(1, max_index):
        if left_max < height[i]:
            left_max = height[i]
        total_water += left_max - height[i]

    # Calculate water trapped on the right side
    # of the maximum height
    right_max = height[-1]
    for i in range(len(height) - 2, max_index,
-1):
        if right_max < height[i]:
            right_max = height[i]
        total_water += right_max - height[i]

    return total_water

```

#84 Largest Rectangle in Histogram ★

LeetCode · SimplyLeetCode · WalkCC · LeetCode

Array · Stack · Monotonic Stack

Lists: Time: $O(N)$ Space: $O(N)$

Problem

Given an array of integers heights representing the histogram's bar height where the width of each bar is 1, return the area of the largest rectangle in the histogram.

Example 1:



Bar Index	Height
1	5
2	6
3	4
4	10
5	8

Input: heights = [2,1,5,6,2,3]
Output: 18
Explanation: The above is a histogram where width of each bar is 1.
The Largest rectangle is shown in the red area, which has an area = 18 units.

Example 2:

Input: heights = [2,4]
Output: 4

```

1 n <- heights.length - 105
2 o <- heights[i] <= 104

Brute Force (Python)

# Brute Force Approach
class Solution:
    def largestRectangleArea(self, heights):
        # Brute Force O(n^2) - fix left bar, expand
        right, track_min = 0, n
        for i in range(n):
            min_h = heights[i]
            for j in range(i, n):
                min_h = min(min_h, heights[j])
            res = max(res, min_h * (j - i + 1))
        return res

```

Community Solutions (Python)

- WalkCC

```
class Solution:
    def largestRectangleArea(self, heights: List[int]) -> int:
        ans = 0
        stack = []

        for i in range(len(heights) + 1):
            while stack and (i == len(heights) or heights[stack[-1]] > heights[i]):
                h = heights[stack.pop()]
                w = stack[-1] - 1 if stack else i - ans
                ans = max(ans, h * w)

            stack.append(i)

        return ans
```

• **LeetCode**

```
class Solution:
    def largestRectangleArea(self, heights: List[int]) -> int:
        n = len(heights)
        stk = []
        left = [-1] * n
        right = [n] * n
        for i in enumerate(heights):
            while stk and heights[stk[-1]] >= heights[i]:
                right[stk[-1]] = i
                stk.pop()
            left[i] = len(stk)
```

```

    if stk:
        left[i] = stk[-1]
        stk.append(i)
    return max(h * (right[i] - left[i] - 1) for
        i, h in enumerate(heights))

```

• **Simplifyst**

Python solution

```

def largestRectangleArea(heights):
    # Append a zero to flush out the remaining bars
    # in the stack
    heights.append(0)
    stack = [] # Stack to store indices of bars
    max_area = 0

    # Iterate over each index and bar height
    for i, h in enumerate(heights):

```

```

# Process bars that are taller than the
current bar
while stack and heights[stack[-1]] > h:
    height = heights[stack.pop()] # Height
    # of the bar at the index popped from the stack
    # Calculate width: if stack is empty,
    width is the current index; otherwise, it's
    the difference
    width = i if not stack else i -
    stack[-1] - 1
    max_area = max(max_area, height *
    width)
    stack.append(i)

return max_area

# Example usage:
if __name__ == '__main__':
    histogram = [1, 2, 1, 3, 4, 2, 3]
    print(largestRectangleArea(histogram))

```

```

***
##### h #####
right i

##### h = (right i - left i - 1)#####

class Solution:
    def largestRectangleArea(self, heights: List[int]) -> int:
        n = len(heights)
        stk = []
        left = [-1] * n

        right = [n] * n
        for i in enumerate(heights):
            while stk and heights[stk[-1]] >= h:
                right[stk[-1]] = i
                stk.append(i)
            if stk:
                left[i] = stk[-1]
            else:
                left[i] = -1
            stk.append(i)

        # valid for non-empty input [3]

```

```

        return max(h - (right[i] - left[i] - 1) * a)
    i, h in enumerate(heights)

#####

class Solution:
    def largestRectangleArea(self, heights: List[int]) -> int:
        if not heights:
            return 0

        heights.append(-1) # make for loop running
        stack = []
        ans = 0
        for i in range(0, len(heights)):
            while stack and heights[i] <
                heights[stack[-1]]:
                    currentLowerThanIndex =
                    stack.pop()
                    h = heights[currentLowerThanIndex]
                    # stack[-1] is after pop(). why?
                    l = currentLowerThanIndex
                    # because not working for the case
                    in the stack,
                    expected=6 but output=4 for input=[4,2,0,3,2,5].

```

```

# [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
right_i
# [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
right-left+i
# [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
index=[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
w = i - stack[-1] - 1 if stack else
i
ans = max(ans, h * w)
stack.append(i)
heights.pop() # restore, pop -1
return ans

```

#224 Basic Calculator HAR LeetCode - 'SimplexLeet' - WalkCC - LeetCode Math - String - Stack - Recursion Lists: Grid 169 Time Complexity: O(n) where n is the length of the input string, since we need process each character once. Space Complexity: O(n) in the worst-case scenario due to the use of a stack for nested parentheses Problem Given a string s representing a valid expression, implement a basic calculator to evaluate it, and return the result of the evaluation. Note: You are not allowed to use any built-in function which evaluates strings as mathematical expressions, such as eval(). Example 1: <pre>Input: s = "1 + 1" Output: 2</pre> Example 2: <pre>Input: s = "2-3+2*" Output: 3</pre> Example 3:	<pre>Input: s = "1+(4+5+2-3)+(6+8)" Output: 23</pre> Constraints: - s consists of digits, '+', '-', '*', '/', and '()'. - s represents a valid expression. '+' is not used as a unary operator (i.e., "+1" and "-(2 + 3)" is invalid). '-' could be used as a unary operator (i.e., "-1" and "-(2 + 3)" is valid). - There will be no two consecutive operators in the input. - Every number and running calculation will fit in a signed 32-bit integer. Community Solutions (Python) • WalkCC	<pre>class Solution: def calculate(self, s: str) -> int: ans = 0 num = 0 sign = 1 stack = [sign] + stack[-1]: the current environment's sign for c in s: if c.isdigit(): num = num * 10 + int(c) elif c == '(': stack.append(sign) elif c == ')': stack.pop() elif c == '+' or c == '-' or c == '*' or c == '/': ans = sign * num sign = (1 if c == '+' else -1) * stack[-1] num = 0 return ans + sign * num</pre> • LeetCode	<pre>class Solution: def calculate(self, s: str) -> int: stk = [] num, sign = 0, 1 while i < len(s): if s[i].isdigit(): x = x * 10 + int(s[i]) i += 1 elif s[i] == "+": sign = 1 elif s[i] == "-": sign = -1 elif s[i] == "*": num = num * sign elif s[i] == "/": num = num // sign else: stk.append(num) num, sign = 0, 1 i += 1 return ans</pre> • SimplyLeet	# Python solution for the Basic Calculator problem <pre>def calculate(s: str) -> int: # Stack to store pairs of (current result, current sign) before a '(' stack = [] result = 0 # Running total number = 0 # Current number being processed sign = 1 # Current sign (1 or -1) # Iterate through each character in the string for char in s: if char.isdigit(): # Build number digit by digit number = number * 10 + int(char) elif char in "+-*/": # Add the complete number with its sign result += sign * number # Reset number for the next potential number = 0 # Update the sign based on the operator sign = 1 if char in "+*" else -1 # Add the last number result += sign * number return result</pre>	<pre>sign = 1 if char == "+" else -1 elif char == "(": # Push the current result and sign onto the stack stack.append(result) stack.append(sign) # Reset result and sign for the new sub-expression result = 0 sign = 1 elif char == ")": # Complete the number before the parentheses close result = sign * number num = 0 # The top of the stack is the sign before the parenthesis prev_sign = stack.pop() # The next value on the stack is the result before the parenthesis result = stack.pop() # Combine the result of the previous expression with the sub-expression evaluated result = prev_result + prev_sign * result # Skip spaces implicitly when no if condition is met</pre>
---	---	---	--	--	--

Round 6 · Mid · Hard

p.2449

Round 6 · Mid · Hard

p.2450

Round 6 · Mid · Hard

p.2451

Round 6 · Mid · Hard

p.2452

Round 6 · Mid · Hard

p.2453

Round 6 · Mid · Hard

p.2454

Add any number left after the loop ends <pre>result += sign * number return result</pre> # Example usage: <pre>print(calculate("1+2")) # Expected output: 3 print(calculate("2+2+2")) # Expected output: 3 print(calculate("1+(4+5+2-3)+(6+8)") # Expected output: 23</pre> • LeetCode # only + and -, no *, no / <pre>class Solution: def calculate(self, s: str) -> int: stk = [] ans, sign = 0, 1 i = 0 while i < len(s): if s[i].isdigit(): num = 0 while i < len(s) and s[i].isdigit(): num = num * 10 + int(s[i]) i += 1 elif s[i] == '+': sign = 1 elif s[i] == '-': sign = -1 elif s[i] == '(': stack.append(sign) elif s[i] == ')': sign = stack.pop() else: continue result += sign * num sign = 1 if s[i] == '+' else -1 num = 0 i += 1 return ans + sign * num</pre>

Round 6 · Mid · Hard

p.2455

With this while, no need to do final calculation like below solution <pre>while j < n and s[j].isdigit(): x = x * 10 + int(s[j]) j += 1 sign = 1 elif s[j] == "+": sign = 1 elif s[j] == "-": sign = -1 elif s[j] == "(": stack.append(sign) elif s[j] == ")": sign = stack.pop() else: continue result += sign * x sign = 1 if s[j] == '+' else -1 x = 0 j += 1 return ans + sign * x</pre>
--

Round 6 · Mid · Hard

p.2456

<pre>class Solution: def calculate(self, s: str) -> int: ans = 0 num = 0 sign = 1 stack = [sign] + stack[-1]: current env's sign for c in s: if c.isdigit(): num = num * 10 + int(c) elif c == '(': stack.append(sign) elif c == ')': stack.pop() elif c == '+' or c == '-' or c == '*' or c == '/': ans = sign * num sign = (1 if c == '+' else -1) * stack[-1] num = 0 return ans + sign * num</pre>

Round 6 · Mid · Hard

p.2457

Stack #239 Sliding Window Maximum HAR LeetCode - 'SimplexLeet' - WalkCC - LeetCode Array - Queue - Sliding Window - Monotonic Queue Lists: Grid 169 Time Complexity: O(n) where n is the number of elements in nums, since each element is processed at most twice. Space Complexity: O(k), as the deque stores indices for at most k elements at any time. Problem You are given an array of integers nums, there is a sliding window of size k which is moving from the very left of the array to the very right. You can only see the k numbers in the window. Each time the sliding window moves right by one position. Return the max sliding window. Example 1: <pre>Input: nums = [1,3,-1,-3,5,3,4,7], k = 3 Output: [3,3,5,5,4,7]</pre> Explanation: Window position Max <pre>[1 3 -1] -> 3 [3 -1 -3] -> 3 [-1 -3 5] -> 5 [-3 5 3] -> 5 [5 3 4] -> 5 [3 4 7] -> 7</pre>
--

Round 6 · Mid · Hard

p.2458

Example 2: <pre>Input: nums = [1], k = 1 Output: [1]</pre> Constraints: 1 <= nums.length <= 105 -104 <= nums[i] <= 104 1 <= k <= nums.length Brute Force (Python) <pre># Brute Force Approach class Solution: def maxSlidingWindow(self, nums: List[int], k: int) -> List[int]: # Brute Force O(n^2) - simulate without stack using inner loop n = len(nums) result = [] for i in range(n - k + 1): max_val = -float('inf') for j in range(i, i + k): max_val = max(max_val, nums[j]) result.append(max_val) return result</pre> Community Solutions (Python) • WalkCC
--

Round 6 · Mid · Hard

p.2459

<pre>class Solution: def maxSlidingWindow(self, nums: List[int], k: int) -> List[int]: ans = [] n = len(nums) # If k is greater than the length of the array, return the entire array if k > n: return nums # Initialize a deque to store indices of elements in the current window deque = collections.deque() # Iterate over the array for i in range(n): # Remove elements from the back while the current number is larger while deque and nums[deque[-1]] < nums[i]: deque.pop() # Add the current index to the deque deque.append(i) # If the window size is k, append the current max to the result if i - deque[0] + 1 == k: ans.append(nums[deque[0]]) deque.popleft() return ans</pre> • LeetCode

Round 6 · Mid · Hard

p.2460

<pre>class Solution: def maxSlidingWindow(self, nums: List[int], k: int) -> List[int]: n = len(nums) if k > n: return nums # Create a deque to store indices of elements in the current window deque = collections.deque() result = [] for i in range(n): # Remove elements from the back while the current number is larger while deque and nums[deque[-1]] < nums[i]: deque.pop() # Add the current index to the deque deque.append(i) # If the window size is k, append the current max to the result if i - deque[0] + 1 == k: result.append(nums[deque[0]]) deque.popleft() return result</pre>

Round 6 · Mid · Hard

p.2461

<pre>deque.popleft() # Remove elements from the back while the current number is larger while deque and nums[deque[-1]] < nums[i]: deque.pop() # Append the current index to the deque deque.append(i) # If we have hit the window size, append the current max to result if i - deque[0] + 1 == k: result.append(nums[deque[0]]) deque.popleft() # Example usage: print(maxSlidingWindow([1,3,-1,-3,5,3,4,7], 3))</pre>

Round 6 · Mid · Hard

p.2462

<pre>from collections import deque class Solution: def maxSlidingWindow(self, nums: List[int], k: int) -> List[int]: n = len(nums) if k > n: return nums # Create a deque to store indices of elements in the current window deque = collections.deque() result = [] for i in range(n): # Remove elements from the back while the current number is larger while deque and nums[deque[-1]] < nums[i]: deque.pop() # Add the current index to the deque deque.append(i) # If the window size is k, append the current max to the result if i - deque[0] + 1 == k: result.append(nums[deque[0]]) deque.popleft() return result</pre>
--

Round 6 · Mid · Hard

p.2463

<pre>""" :type nums: List[int] :type k: int :rtype: List[int] If k is 0: return [] ans = [0 for i in range(len(nums) - k + 1)] stack = collections.deque() for i in range(k): while stack and nums[stack[-1]] < nums[i]: stack.pop() stack.append(i) ans[i] = nums[stack[0]] if i == k - 1: ans[k] = nums[stack[0]] for i in range(k, len(nums)): id = i - k if stack and stack[0] == id: stack.popleft() while stack and nums[stack[-1]] < nums[i]: stack.pop() stack.append(i) ans[i] = nums[stack[0]] return ans</pre>
--

Round 6 · Mid · Hard

p.2464

Stack #716 Max Stack HAR LeetCode - 'SimplexLeet' - WalkCC - LeetCode Stack - Design - Doubly-Linked List - Ordered Set Lists: Deney Zhang Time Complexity: Problem Design a max stack data structure that supports the stack operations and supports finding the stack's maximum element. Implement the MaxStack class: - MaxStack() Initializes the stack object. - void push(int x) Pushes element x onto the stack. - int pop() Removes the element on top of the stack and returns it. - int top() Gets the element on the top of the stack without removing it. - int peekMax() Retrieves the maximum element in the stack without removing it. - int popMax() Retrieves the maximum element in the stack and removes it. If there is more than one maximum element, only remove the top-most one. You must come up with a solution that supports O(1) for each top call and O(logn) for each other call.

Round 6 · Mid · Hard

p.2465

Example 1: <pre>Input ["MaxStack", "push", "push", "push", "top", "peekMax", "pop", "peekMax", "pop"] [[[]], [5], [1], [5], [1], [1], [1], [1], [1]] Output [null, null, null, null, 5, 5, 5, 5, 1, 5]</pre> Explanation MaxStack stk = new MaxStack(); Constraints: -105 <= x <= 107 - At most 105 calls will be made to push, pop, top, peekMax, and popMax. - There will be at least one element in the stack when pop, peekMax, or popMax is called. Community Solutions (Python) • SimplyLeet
--

Round 6 · Mid · Hard

p.2466

Python solution implementing the MaxStack data structure # We use collections.OrderedDict for demonstration # However, in Python we do not have a built-in balanced BST # One can use "sortedcontainers" or manually maintain a heap and dictionary. # For clarity, we simulate an ordered list with a TreeMap-like structure using sorted list of keys. # In production, one may use "SortedList" from sortedcontainers. from collections import defaultdict class Node: <pre>def __init__(self, val): self.val = val self.prev = None self.next = None</pre> class DoubleLinkedList: <pre>def __init__(self): # Create dummy head and tail nodes. self.head = Node(0) self.tail = Node(0)</pre>
--

Round 6 · Mid · Hard

p.2467

<pre>self.head.next = self.tail self.tail.prev = self.head def add_last(self, node): # Add node right before the tail. node.prev = self.tail.prev self.tail.prev = node self.tail.next = node self.tail = node def pop(self, node=None): # If no node is provided, pop from the end. if not node: node = self.tail.prev node.prev.next = node.next node.next.prev = node return node else: node.next.prev = node node.prev.next = node return node def top(self): # Return the last node's value.</pre>
--

Round 6 · Mid · Hard

p.2468

<pre>return self.tail.prev.val class MaxStack: def __init__(self): self.dl = DoubleLinkedList() # Dictionary mapping value to list of nodes self.valToNodes = defaultdict(list) # Sorted list to simulate ordered set of keys. self.sortedKeys = [] def push(self, x: int) -> None: node = Node(x) self.dl.add_last(node) self.valToNodes[x].append(node) # Insert x into sortedKeys if new, otherwise maintain count. if len(self.valToNodes[x]) == 1: # Binary insertion into sortedKeys lo, hi = 0, len(self.sortedKeys) while lo < hi: mid = (lo + hi) // 2 if self.sortedKeys[mid] < x: lo = mid + 1 else: hi = mid self.sortedKeys.insert(lo, x) def pop(self) -> int: node = self.dl.remove_last() self.valToNodes[node.val].remove(node) if not self.valToNodes[node.val]: self.sortedKeys.remove(node.val) return node.val def top(self) -> int: return self.sortedKeys[-1] if self.sortedKeys else -1</pre>
--

Round 6 · Mid · Hard

p.2469

<pre>if self.sortedKeys[-1] < x: lo = mid + 1 else: hi = mid self.sortedKeys.insert(lo, x) def pop(self) -> int: node = self.dl.remove_last() self.valToNodes[node.val].remove(node) if not self.valToNodes[node.val]: self.sortedKeys.remove(node.val) return node.val def top(self) -> int: return self.dl.remove_last().val def peekMax(self) -> int: # The maximum is the last element in sortedKeys.</pre>
--

Round 6 · Mid · Hard

p.2470

<pre>return self.sortedKeys[-1] def pop(self) -> int: max_val = self.peekMax() # Get the most recent node with max_val. node = self.valToNodes[max_val].pop() if not self.valToNodes[max_val]: self.sortedKeys.remove(max_val) return node.val def top(self) -> int: return self.sortedKeys[-1] def peekMax(self) -> int: return self.sortedKeys[-1].val def popMax(self) -> int: max_val = self.peekMax() # Get the most recent node with max_val. node = self.valToNodes[max_val].pop() if not self.valToNodes[max_val]: self.sortedKeys.remove(max_val) return node.val</pre>
--

Round 6 · Mid · Hard

p.2471

class MaxStack(object): <pre>def __init__(self): # Initialize your data structure here. self.stack = [] self.max_stack = [] def push(self, x): self.stack.append(x) self.max_stack.append(max(x, self.max_stack[-1] if self.max_stack else x)) def pop(self): self.stack.pop() self.max_stack.pop() def top(self): return self.stack[-1] def peekMax(self): return self.max_stack[-1] def popMax(self): max_val = self.max_stack.pop() # Find the index of the max_val in the stack index = self.stack.index(max_val) self.stack.pop(index)</pre>

Round 6 · Mid · Hard

p.2472

<pre>""" :rtype: int Input: s = "1+2" Output: 3 Example 2: Input: s = "4/2" Output: 2 Example 3: Input: s = "2+(3+5*(2*(3+8+2*8)))" Output: 21</pre> Constraints: 1 <= s.length <= 104 - s consists of digits, '+', '-', '*', '/', '(', and ')'. '+' is a valid expression. Community Solutions (Python) • WalkCC <pre>class Solution: def calculate(self, s: str) -> int: nums = [] ops = [] def calc(): b = nums.pop() a = nums.pop() op = ops.pop() if op == "+": nums.append(a + b) elif op == "-": nums.append(a - b) elif op == "*": nums.append(a * b) elif op == "/": nums.append(int(a / b)) def precedence(prev: str, curr: str) -> bool: """ Returns True if the previous character is a operator and the priority of the previous operator >= the priority of the current character (operator). """ if prev == "(": return False return prev in "+*" or curr in "+-*/" i = 0 hasPrevNum = False</pre>

Round 6 · Mid · Hard

p.2473

<pre>def popMax(self): """ :rtype: int Input: s = "1+2" Output: 3 Example 2: Input: s = "4/2" Output: 2 Example 3: Input: s = "2+(3+5*(2*(3+8+2*8)))" Output: 21</pre> Constraints: 1 <= s.length <= 104 - s consists of digits, '+', '-', '*', '/', '(', and ')'. '+' is a valid expression. Community Solutions (Python) • WalkCC <pre>class Solution: def calculate(self, s: str) -> int: nums = [] ops = [] def calc(): b = nums.pop() a = nums.pop() op = ops.pop() if op == "+": nums.append(a + b) elif op == "-": nums.append(a - b) elif op == "*": nums.append(a * b) elif op == "/": nums.append(int(a / b)) def precedence(prev: str, curr: str) -> bool: """ Returns True if the previous character is a operator and the priority of the previous operator >= the priority of the current character (operator). """ if prev == "(": return False return prev in "+*" or curr in "+-*/" i = 0 hasPrevNum = False</pre>

Round 6 · Mid · Hard

p.2474

<pre>def __init__(self, val=0): self.val = val self.prev = UnionNode, None) = None self.next = UnionNode, None) = None class DoubleLinkedList: def __init__(self): self.head = Node(0) self.tail = Node(0) def push(self, val): self.head.next = self.tail self.tail.prev = self.head self.tail = Node(val) self.head.next = self.tail self.tail.prev = self.head def pop(self): self.tail = self.tail.prev self.tail.next = None def peekMax(self): return self.tail.val def popMax(self): max_val = self.tail.val self.tail = self.tail.prev self.tail.next = None self.tail.next = self.tail self.tail.prev = self.head</pre>

Round 6 · Mid · Hard

p.2475

<pre>class Solution: def calculate(self, s: str) -> int: stk = [] num, sign = 0, 1 while i < len(s): if s[i].isdigit(): num = num * 10 + int(s[i]) elif s[i] == "+": sign = 1 elif s[i] == "-": sign = -1 elif s[i] == "*": num = num * sign elif s[i] == "/": num = num // sign else: stk.append(num) num, sign = 0, 1 i += 1 return ans + sign * num</pre>
--

Round 6 · Mid · Hard

p.2476

<pre>node = self.stk.append(x) self.stk.append(node) def pop(self) -> int: node = self.stk.pop() self.stk.remove(node) return node.val def top(self) -> int: return self.stk[-1].val def peekMax(self) -> int: return self.stk[-1].val def popMax(self) -> int: max_val = self.stk[-1].val node = self.stk.pop() self.stk.remove(node) return node.val</pre>
--

Round 6 · Mid · Hard

p.2477

Stack #772 Basic Calculator III HAR LeetCode - 'SimplexLeet' - WalkCC - LeetCode Math - String - Stack - Recursion Lists: Premium 98 Time Complexity: O(n) where n is the length of the string, as every character is processed. Space Complexity: O(n) due to the recursion stack or auxiliary stack used for intermediate results. Problem Implement a basic calculator to evaluate a simple expression string. The expression string contains only non-negative integers, '+', '-', '*', '/', and parentheses '(', ')'. The integer division should truncate toward zero. You may assume that the given expression is always valid. All intermediate results will be in the range of [-2^31, 2^31 - 1]. Note: You are not allowed to use any built-in function which evaluates strings as mathematical expressions, such as eval(). Example 1: <pre>Input: s = "1+(4+5+2+3)" Output: 15</pre>

Round 6 · Mid · Hard

p.2478

<pre>Input: s = "1+2" Output: 3 Example 2: Input: s = "4/2" Output: 2 Example 3: Input: s = "2+(3+5*(2*(3+8+2*8)))" Output: 21</pre> Constraints: 1 <= s.length <= 104 - s consists of digits, '+', '-', '*', '/', '(', and ')'. '+' is a valid expression. Community Solutions (Python) • WalkCC <pre>class Solution: def calculate(self, s: str) -> int: nums = [] ops = [] def calc(): b = nums.pop() a = nums.pop() op = ops.pop() if op == "+": nums.append(a + b) elif op == "-": nums.append(a - b) elif op == "*": nums.append(a * b) elif op == "/": nums.append(int(a / b)) def precedence(prev: str, curr: str) -> bool: """ Returns True if the previous character is a operator and the priority of the previous operator >= the priority of the current character (operator). """ if prev == "(": return False return prev in "+*" or curr in "+-*/" i = 0 hasPrevNum = False</pre>

Round 6 · Mid · Hard

p.2479

<pre>nums.append(a + b) elif op == "-": nums.append(a - b) elif op == "*": nums.append(a * b) elif op == "/": nums.append(int(a / b)) def precedence(prev: str, curr: str) -> bool: """ Returns True if the previous character is a operator and the priority of the previous operator >= the priority of the current character (operator). """ if prev == "(": return False return prev in "+*" or curr in "+-*/" i = 0 hasPrevNum = False</pre>

Round 6 · Mid · Hard

p.2480

<pre>while i < len(s): c = s[i] if c.isdigit(): num = int(c) while i + 1 < len(s) and s[i + 1].isdigit(): num = num * 10 + int(s[i + 1]) i += 1 stack.append(num) elif c == "(": stack.append("(") elif c == "+": stack.append("+") elif c == "-": stack.append("-") elif c == "*": stack.append("*") elif c == "/": stack.append("/") else: while stack and stack[-1] != "(": op = stack.pop() if op == "+": num1 = stack.pop() num2 = stack.pop() result = num2 + num1 elif op == "-": num1 = stack.pop() num2 = stack.pop() result = num2 - num1 elif op == "*": num1 = stack.pop() num2 = stack.pop() result = num2 * num1 elif op == "/": num1 = stack.pop() num2 = stack.pop() result = num2 / num1 stack.append(result) stack.pop() if op == "+": num1 = stack.pop() num2 = stack.pop() result = num2 + num1 elif op == "-": num1 = stack.pop() num2 = stack.pop() result = num2 - num1 elif op == "*": num1 = stack.pop() num2 = stack.pop() result = num2 * num1 elif op == "/": num1 = stack.pop() num2 = stack.pop() result = num2 / num1 stack.append(result) i += 1 return stack[-1]</pre>

Round 6 · Mid · Hard

p.2481

||
||
||

<pre>elif sign == '-': prev = stack.pop() stack.append(prev + num) elif sign == '/': prev = stack.pop() stack.append(int(prev / num)) # Truncate toward zero sign = char num = 0 # If a closing parenthesis is reached, end this level of recursion if char == ')': return sum(stack), i i += 1 return sum(stack), i result, _ = helper(0) return result # Example test print(calculate("2+(3+5*2)/(3+6/2+8)") • LC6</pre>	<pre># good one, based on solution of Basic Calculator if class Solution: def calculate(self, s: str) -> int: stack = [] num = 0 op = "+" i = 0 while i < len(s): if s[i] <= ' ': continue if s[i] in '+-*/': if op != '+': num = num * 10 + int(s[i]) else: num = num + int(s[i]) op = s[i] else: if s[i] == '(': self.calculate(self, s, str, i, int) -> int: elif s[i] == ')': return sum(stack) elif s[i] in '+-*/': def findClosing(self, s: str, i: int) -> int: level = 0 while i < len(s): if s[i] == '(': level += 1 elif s[i] == ')': level -= 1 elif level == 0: return i i += 1 return i self.calculate(self, s, str, i, int) -> int: op = s[i] stack.append(num) stack.append(-num) num = 0 i += 1 return i</pre>	<pre>##### class Solution: def calculate(self, s: str) -> int: res = stack.pop() if stack else 0 # Evaluate the expression till we get # ' ' or empty stack while stack and stack[-1] != '(': sign = stack.pop() if sign == '+': res = stack.pop() elif sign == '-': res = stack.pop() elif sign == '*': res = stack.pop() elif sign == '/': res = stack.pop() res = res // stack.pop() while stack and stack[-1] != '(': sign = stack.pop() if sign == '+': res = stack.pop() elif sign == '-': res = stack.pop() elif sign == '*': res = stack.pop() elif sign == '/': res = stack.pop() res = res // stack.pop() return res stack = [] # mix of num and operator i = len(s) while i < n: if s[i].isdigit(): # Get the complete number and push # it to the stack j = i while j < n and s[j].isdigit(): stack.append(int(s[i:j])) i = j + 1 elif s[i] in '+-*/': stack.append(s[i]) i = j + 1 elif s[i] == '(': # Evaluate the expression within # the parentheses res = evaluate_expression(stack) stack.pop() # Remove the opening # parenthesis stack.append(res)</pre>	<pre>i += 1 return evaluate_expression(stack) ##### class Solution: def calculate(self, s: str) -> int: if not s: return 0 # remove leading and trailing spaces and # white spaces s = s.strip().replace(" ", "") if not s: return 0 op, stack = [], [] num, stack = [], []</pre>								
Round 6 - Mid - Hard	p.2485	Round 6 - Mid - Hard	p.2486	Round 6 - Mid - Hard	p.2487	Round 6 - Mid - Hard	p.2488	Round 6 - Mid - Hard	p.2489	Round 6 - Mid - Hard	p.2490

<pre>i = 0 while i < len(s): if s[i].isdigit(): num = 0 while i < len(s) and s[i].isdigit(): num = num * 10 + int(s[i]) i += 1 stack.append(num) else: op = s[i] if not op_stack: op_stack.append(op) i += 1 elif op == '+': while op_stack[-1] != '(': self.calculate_helper(num, op_stack) op_stack.pop() i += 1 elif op == '-': self.calculate_helper(num, op_stack) i += 1 elif op == '*': self.calculate_helper(num, op_stack) i += 1 elif op == '/': self.calculate_helper(num, op_stack) i += 1 else: return num_stack[-1] def calculate_helper(self, num_stack, op_stack): num2 = num_stack.pop() num1 = num_stack.pop() op = op_stack.pop() if op == '+': ans = num1 + num2 elif op == '-': ans = num1 - num2 elif op == '*': ans = num1 * num2 elif op == '/': ans = int(num1 / num2) num_stack.append(ans)</pre>	<pre>self.calculate_helper(num, stack, op_stack) elif op == '+': top = op_stack[-1] if top == '+' or top == '*' or top == '-': op_stack.append(op) i += 1 self.calculate_helper(num, stack, op_stack) elif op == '-': self.calculate_helper(num, stack, op_stack) i += 1 self.calculate_helper(num, stack, op_stack) elif op == '*': self.calculate_helper(num, stack, op_stack) i += 1 self.calculate_helper(num, stack, op_stack) elif op == '/': self.calculate_helper(num, stack, op_stack) i += 1 self.calculate_helper(num, stack, op_stack) while op_stack: self.calculate_helper(num_stack, op_stack)</pre>	<pre>return num_stack[-1] def calculate_helper(self, num_stack, op_stack): num2 = num_stack.pop() num1 = num_stack.pop() op = op_stack.pop() if op == '+': ans = num1 + num2 elif op == '-': ans = num1 - num2 elif op == '*': ans = num1 * num2 elif op == '/': ans = int(num1 / num2) num_stack.append(ans)</pre>	Stack #895 Maximum Frequency Stack LeetCode - SimplexTest - WALKER - LeetCode Hash Table - Stack - Design Lists: Grid 169 Time Complexity: O(1) per push and pop. Space Complexity: O(n), where n is the number of elements pushed onto the stack. Problem Design a stack-like data structure to push elements to the stack and pop the most frequent element from the stack. Implement the <code>FrequencyStack</code> class: <code>FrequencyStack</code> constructs an empty frequency stack. <code>void push(int val)</code> pushes an integer <code>val</code> onto the top of the stack. <code>int pop()</code> removes and returns the most frequent element in the stack. If there is a tie for the most frequent element, the element closest to the stack's top is removed and returned. Example 1:	<pre>input ["FrequencyStack", "push", "push", "push", "push", "push", "push", "pop", "pop", "pop"] Output null, null, null, null, null, null, 5, 7, 5, 7, 5, 4] Explanation FrequencyStack freqStack = new FrequencyStack(); Constraints: 0 <= val <= 100 At most 2 * 10^4 calls will be made to push and pop. It is guaranteed that there will be at least one element in the stack before calling pop. Community Solutions (Python) = WALKER</pre>	<pre>class FrequencyStack: def __init__(self): self.freq = {} self.count = collections.Counter() self.countStack = {} self.defaultDict(list) def push(self, val: int) -> None: self.count[val] += 1 self.countStack[self.count[val]].append(val) self.freq[val] = max(self.freq, self.count[val]) def pop(self) -> int: val = self.countStack[self.freq].pop() self.count[val] -= 1 if not self.countStack[self.freq]: self.freq -= 1 return val = LeetCode</pre>						
Round 6 - Mid - Hard	p.2491	Round 6 - Mid - Hard	p.2492	Round 6 - Mid - Hard	p.2493	Round 6 - Mid - Hard	p.2494	Round 6 - Mid - Hard	p.2495	Round 6 - Mid - Hard	p.2496


<pre>class FrequencyStack: def __init__(self): self.ct = defaultdict(int) self.f = {} self.ts = 0 def push(self, val: int) -> None: self.ct[val] += 1 heappush(self.f, (-self.ct[val], -self.ts, val)) def pop(self) -> int: val = heappop(self.f)[2] self.ct[val] -= 1 return val # Your FrequencyStack object will be instantiated and # called as such: obj = FrequencyStack() obj.push(val) # param_2 = obj.pop()</pre> • SimpleTest	<pre># Python Implementation of FrequencyStack class FrequencyStack: def __init__(self): # Dictionary mapping value to its frequency self.freq = {} # Dictionary mapping frequency to a list # (stack) of values self.group = {} # Variable tracking the current maximum # frequency in the stack self.maxfreq = 0 def push(self, val: int) -> None: # Update frequency count for the value f = self.freq.get(val, 0) + 1 self.freq[val] = f # Update the maximum frequency if necessary if f > self.maxfreq: self.maxfreq = f # Append the value to the appropriate # frequency group if f not in self.group: self.group[f] = [] self.freq[val].append(val)</pre>	<pre>self.group[f] = [] self.group[f].append(val) def pop(self) -> int: # Remove the value from the stack of the # current maximum frequency val = self.group[self.maxfreq].pop() # Decrement the frequency count for the # value self.freq[val] -= 1 # If no more elements have the current max # frequency, decrease maxfreq if not self.group[self.maxfreq]: self.maxfreq -= 1 return val # LeetCode class FrequencyStack: def __init__(self): self.ct = defaultdict(int) self.f = defaultdict(list) self.mx = 0 def push(self, val: int) -> None: self.ct[val] += 1 self.f[self.ct[val]].append(val) self.mx = max(self.mx, self.ct[val]) # LeetCode</pre>	<pre>def pop(self) -> int: val = self.f[self.mx].pop() self.ct[val] -= 1 if not self.f[self.mx]: self.mx -= 1 return val # Your FrequencyStack object will be instantiated and # called as such: obj = FrequencyStack() obj.push(val) # param_2 = obj.pop()</pre>	Heap Round 6 - Mid - Hard - 9 questions	#23 Merge k Sorted Lists LeetCode - 'SimplexTest' - WALKER - LeetCode Linked List - Divide and Conquer - Heap - Merge Sort Lists: Grid 169 Time Complexity: O(N log k) where N is the total number of nodes across all lists and k is the number of lists. Space Complexity: O(k) due to the heap containing at most one node from each list. Problem You are given an array of k linked-lists lists, each linked-list is sorted in ascending order. Merge all the linked-lists into one sorted linked-list and return it. Example 1: Input: lists = [[1,4,5],[3,4,6]] Output: [1,1,2,3,4,4,5,6] Explanation: The linked-lists are: 1->4->5, 1->3->4->6, 2->6 Example 2:				
Round 6 - Mid - Hard	p.2497	Round 6 - Mid - Hard	p.2498	Round 6 - Mid - Hard	p.2500	Round 6 - Mid - Hard	p.2501	Round 6 - Mid - Hard	p.2502

| |

 |
--
--
--
--
--
-----------|
| <pre>Output: [] Example 3: Input: lists = [[]] Output: [] Constraints: k == lists.length 0 <= k <= 104 0 <= lists[i].length <= 500 -104 <= lists[i][j] <= 104 lists[i] is sorted in ascending order. The sum of lists[i].length will not exceed 104. Brute Force (Python) # Brute Force Approach class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Brute Force O(N log N) - collect all # values, sort, rebuild vals = [] for node in lists: while node: vals.append(node.val) node = node.next vals.sort()</pre> | <pre>curr = dummy for i in range(len(lists)): curr.next = lists[i].next curr = curr.next return dummy.next Community Solutions (Python) # LeetCode # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition
for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def
mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None):
self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list.
class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists:
List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode: def __init__(self, val=0, next=None): self.val = val self.next = next import heapq class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Definition for singly-linked list. class ListNode:</pre>
--
--
--
--
--
-----------|

<pre>class NodeWrapper: def __init__(self, node): self.node = node def __lt__(self, other): return self.node.val < other.node.val def __gt__(self, other): return self.node.val > other.node.val def __eq__(self, other): return self.node.val == other.node.val # override the comparison function, so the node # can be comparable # or else, error: TypeError: <' not supported # between instances of 'ListNode' and 'ListNode' # define 'gt' will also work, so either lt or gt # will do the compare job for ListNode # ListNode.__lt__ = lambda x, y: (x.val < y.val) # ListNode.__gt__ = lambda x, y: (x.val > y.val) # ListNode.__eq__ = lambda x, y: (x.val == y.val) class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Brute Force O(n log n) - collect all # values, sort, rebuild vals = [] for node in lists: while node: vals.append(node.val) node = node.next vals.sort() dummy = current = ListNode(0) heap = [] for i, node in enumerate(lists): if node: # Add node to heap heapq.heappush(heap, (node.val, i, node)) # While heap is not empty while heap: # Pop the smallest node from the heap val, id, node = heapq.heappop(heap) # Add the smallest node to the merged # list current.next = node current = current.next # If there is a next node in the list, # push it into the heap if node.next: heapq.heappush(heap, (node.next.val, id, node.next)) # Return the merged list return dummy.next</pre>	<pre>error: TypeError: <' not supported between instances of 'ListNode' and 'ListNode' heapq.heappush(heap, (node.val, node)) ''' tried to use node.val to order heap, but still got error: TypeError: <' not supported between instances of 'ListNode' and 'ListNode' ##### # based on merge 2 Lists # note for empty input class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: if lists is None or len(lists) == 0: return None return self.mergeKListsHelper(lists, 0, len(lists) - 1) def mergeKListsHelper(self, lists: List[ListNode], start: int, end: int) -> Optional[ListNode]: if start == end: return lists[start] mid = (start + end) // 2 left = self.mergeKListsHelper(lists, start, mid) right = self.mergeKListsHelper(lists, mid + 1, end) return self.mergeTwoLists(left, right) def mergeTwoLists(self, list1: Optional[ListNode], list2: Optional[ListNode]) -> Optional[ListNode]: dummy = current = dummy = ListNode(0) while list1 and list2: if list1.val < list2.val: current.next = list1 list1 = list1.next else: current.next = list2 list2 = list2.next current = current.next if list1: current.next = list1 if list2: current.next = list2 return dummy.next</pre>	<pre>current.next = list1 list1 = list1.next else: current.next = list2 list2 = list2.next current = current.next # print('merging result: ', dummy.next) return dummy.next ##### # Definition for singly-linked list. # class ListNode: # def __init__(self, val=0, next=None): # self.val = val # self.next = next class Solution: def mergeKLists(self, lists: List[ListNode]) -> Optional[ListNode]: # Create a min-heap min_heap = [] # Heap entry: (node value, unique id, node) # to handle duplicate values for i, node in enumerate(lists): if node: heapq.heappush(min_heap, (node.val, i, node)) # Dummy node to form the start of merged # list dummy = ListNode(0) current = dummy # While there are elements in the heap # while min_heap: # # Pop the smallest node from the heap # val, id, node = heapq.heappop(min_heap) # # Add the smallest node to the merged # # list # current.next = node # current = current.next # # If there is a next node in the list, # # push it into the heap # if node.next: # heapq.heappush(min_heap, (node.next.val, id, node.next)) # Return the merged list return dummy.next</pre>	<pre>-> ListNode: # = len(lists) # return None for i in range(n - 1): # this is O(N) times of merge, while if we use divide-and-conquer then it's # O(logN) times of merge lists[i + 1] = self.mergeTwoLists(lists[i], lists[i + 1]) return lists[0]</pre>								
Round 6 - Mid - Hard	p.2509	Round 6 - Mid - Hard	p.2510	Round 6 - Mid - Hard	p.2511	Round 6 - Mid - Hard	p.2512	Round 6 - Mid - Hard	p.2513	Round 6 - Mid - Hard	p.2514

<pre>if __name__ == '__main__': l1 = ListNode(1) l2 = ListNode(2) l3 = ListNode(3) l4 = ListNode(4) l5 = ListNode(5) l6 = ListNode(6) l7 = ListNode(7) l8 = ListNode(8) l9 = ListNode(9) l10 = ListNode(10) l11 = ListNode(11) l12 = ListNode(12) l13 = ListNode(13) l14 = ListNode(14) l15 = ListNode(15) l16 = ListNode(16) l17 = ListNode(17) l18 = ListNode(18) l19 = ListNode(19) l20 = ListNode(20) l21 = ListNode(21) l22 = ListNode(22) l23 = ListNode(23) l24 = ListNode(24) l25 = ListNode(25) l26 = ListNode(26) l27 = ListNode(27) l28 = ListNode(28) l29 = ListNode(29) l30 = ListNode(30) l31 = ListNode(31) l32 = ListNode(32) l33 = ListNode(33) l34 = ListNode(34) l35 = ListNode(35) l36 = ListNode(36) l37 = ListNode(37) l38 = ListNode(38) l39 = ListNode(39) l40 = ListNode(40) l41 = ListNode(41) l42 = ListNode(42) l43 = ListNode(43) l44 = ListNode(44) l45 = ListNode(45) l46 = ListNode(46) l47 = ListNode(47) l48 = ListNode(48) l49 = ListNode(49) l50 = ListNode(50) l51 = ListNode(51) l52 = ListNode(52) l53 = ListNode(53) l54 = ListNode(54) l55 = ListNode(55) l56 = ListNode(56) l57 = ListNode(57) l58 = ListNode(58) l59 = ListNode(59) l60 = ListNode(60) l61 = ListNode(61) l62 = ListNode(62) l63 = ListNode(63) l64 = ListNode(64) l65 = ListNode(65) l66 = ListNode(66) l67 = ListNode(67) l68 = ListNode(68) l69 = ListNode(69) l70 = ListNode(70) l71 = ListNode(71) l72 = ListNode(72) l73 = ListNode(73) l74 = ListNode(74) l75 = ListNode(75) l76 = ListNode(76) l77 = ListNode(77) l78 = ListNode(78) l79 = ListNode(79) l80 = ListNode(80) l81 = ListNode(81) l82 = ListNode(82) l83 = ListNode(83) l84 = ListNode(84) l85 = ListNode(85) l86 = ListNode(86) l87 = ListNode(87) l88 = ListNode(88) l89 = ListNode(89) l90 = ListNode(90) l91 = ListNode(91) l92 = ListNode(92) l93 = ListNode(93) l94 = ListNode(94) l95 = ListNode(95) l96 = ListNode(96) l97 = ListNode(97) l98 = ListNode(98) l99 = ListNode(99)</pre>	<pre>#218 The Skyline Problem LeetCode - 'SimplexTest' - WALKER - LeetCode Array - Divide and Conquer - Binary Indexed Tree - Segment Tree - Line Sweep - Heap - Ordered Set Lists: Deque, Queue Time Complexity: O(n log n) due to sorting events and heap operations for each building event. Space Complexity: O(n) for the event list and the heap used for processing active buildings. Problem A city's skyline is the outer contour of the silhouette formed by all the buildings in the city when viewed from a distance. Given the locations and heights of all the buildings, return the skyline formed by these buildings collectively. The geometric information of each building is given in the array buildings where buildings[i] = [lefti, righti, heighti]. lefti is the x coordinate of the left edge of the ith building. righti is the x coordinate of the right edge of the ith building. heighti is the height of the ith building.</pre>	points" sorted by their x-coordinate in the form [[x1,y1],[x2,y2],...]. Each key point is the left endpoint of some horizontal segment in the skyline except the last point in the list which always has a y-coordinate 0 and is used to mark the skyline's termination where the rightmost building ends. Any ground between the leftmost and rightmost buildings should be part of the skyline's contour. Note: There must be no consecutive horizontal lines of equal height in the output skyline. For instance, [[2,3],[4,3],[4,4],[5,4]] is not acceptable; the correct output is [[2,3],[4,4],[5,4]]. Example 1:	<pre>Input: buildings = [[1,2,3],[2,3,4],[3,4,5],[4,5,6],[5,6,7],[6,7,8],[7,8,9],[8,9,10],[9,10,11],[10,11,12],[11,12,13],[12,13,14],[13,14,15],[14,15,16],[15,16,17],[16,17,18],[17,18,19],[18,19,20],[19,20,21],[20,21,22],[21,22,23],[22,23,24],[23,24,25],[24,25,26],[25,26,27],[26,27,28],[27,28,29],[28,29,30],[29,30,31],[30,31,32],[31,32,33],[32,33,34],[33,34,35],[34,35,36],[35,36,37],[36,37,38],[37,38,39],[38,39,40],[39,40,41],[40,41,42],[41,42,43],[42,43,44],[43,44,45],[44,45,46],[45,46,47],[46,47,48],[47,48,49],[48,49,50],[49,50,51],[50,51,52],[51,52,53],[52,53,54],[53,54,55],[54,55,56],[55,56,57],[56,57,58],[57,58,59],[58,59,60],[59,60,61],[60,61,62],[61,62,63],[62,63,64],[63,64,65],[64,65,66],[65,66,67],[66,67,68],[67,68,69],[68,69,70],[69,70,71],[70,71,72],[71,72,73],[72,73,74],[73,74,75],[74,75,76],[75,76,77],[76,77,78],[77,78,79],[78,79,80],[79,80,81],[80,81,82],[81,82,83],[82,83,84],[83,84,85],[84,85,86],[85,86,87],[86,87,88],[87,88,89],[88,89,90],[89,90,91],[90,91,92],[91,92,93],[92,93,94],[93,94,95],[94,95,96],[95,96,97],[96,97,98],[97,98,99],[98,99,100]] Output: [[1,16],[2,16],[3,16],[4,16],[5,16],[6,16],[7,16],[8,16],[9,16],[10,16],[11,16],[12,16],[13,16],[14,16],[15,16],[16,16],[17,16],[18,16],[19,16],[20,16],[21,16],[22,16],[23,16],[24,16],[25,16],[26,16],[27,16],[28,16],[29,16],[30,16],[31,16],[32,16],[33,16],[34,16],[35,16],[36,16],[37,16],[38,16],[39,16],[40,16],[41,16],[42,16],[43,16],[44,16],[45,16],[46,16],[47,16],[48,16],[49,16],[50,16],[51,16],[52,16],[53,16],[54,16],[55,16],[56,16],[57,16],[58,16],[59,16],[60,16],[61,16],[62,16],[63,16],[64,16],[65,16],[66,16],[67,16],[68,16],[69,16],[70,16],[71,16],[72,16],[73,16],[74,16],[75,16],[76,16],[77,16],[78,16],[79,16],[80,16],[81,16],[82,16],[83,16],[84,16],[85,16],[86,16],[87,16],[88,16],[89,16],[90,16],[91,16],[92,16],[93,16],[94,16],[95,16],[96,16],[97,16],[98,16],[99,16],[100,16]]</pre>	<pre># Brute Force Approach class Solution: def getSkyline(self, buildings: List[List[int]]) -> List[List[int]]: # Brute Force O(n log n) - sort repeatedly # instead of heap data = [] for i in range(len(buildings)): left, right, height = buildings[i] data.append((left, right, height)) data.sort() result = [] for i in range(len(data)): left, right, height = data[i] if left > result[-1][0]: result.append([left, height]) elif left == result[-1][0]: if height > result[-1][1]: result[-1][1] = height else: if height > result[-1][1]: result[-1][1] = height else: result[-1][1] = height return result</pre>	<pre>Community Solutions (Python) = WALKER class Solution: def getSkyline(self, buildings: List[List[int]]) -> List[List[int]]: # Brute Force O(n log n) - sort repeatedly # instead of heap data = [] for i in range(len(buildings)): left, right, height = buildings[i] data.append((left, right, height)) data.sort() result = [] for i in range(len(data)): left, right, height = data[i] if left > result[-1][0]: result.append([left, height]) elif left == result[-1][0]: if height > result[-1][1]: result[-1][1] = height else: if height > result[-1][1]: result[-1][1] = height else: result[-1][1] = height return result</pre>	<pre>def merge(self, left: List[List[int]], right: List[List[int]]) -> List[List[int]]: ans = [] i = 0 j = 0 while i < len(left) and j < len(right): if left[i][0] < right[j][0]: ans.append(left[i]) i += 1 elif left[i][0] == right[j][0]: if left[i][1] > right[j][1]: ans.append(left[i]) else: ans.append(right[j]) i += 1 j += 1 else: ans.append(right[j]) j += 1 while i < len(left): ans.append(left[i]) i += 1 while j < len(right): ans.append(right[j]) j += 1 return ans</pre>
Round 6 - Mid - Hard	p.2515	p				

<pre> j = 1 while i < len(left): self._addPoint(ans, left[i][0], left[i][1]) i += 1 while j < len(right): self._addPoint(ans, right[j][0], right[j][1]) j += 1 return ans def _addPoint(self, ans: list[list[int]], x: int, y: int) -> None: if ans and ans[-1][0] == x: ans[-1][1] = y return if ans and ans[-1][1] == y: return ans.append((x, y)) </pre> •SimplyList	<pre> import heapq def getSkyLine(buildings): # List to store all events: (x, height, right) events = [] # Create events for all buildings: left edge (start) and right edge (end) for left, right, height in buildings: # For the start point, height is negative for proper sorting (start events come before and events) # Events.append((left, -height, right)) # For the end point, height is 0 to indicate removal of building from active heap events.append((right, 0, 0)) # Sort events by x coordinate. events.sort() # Max heap to store active buildings (using negative heights) result = [] # Initialize the heap with a dummy building of height 0 that extends infinitely heap = [(0, float('inf'))] </pre>	<pre> for x, neg_height, right in events: # Remove buildings from the heap that have ended by current x. while heap and heap[0][1] <= x: heapq.heappop(heap) # If event is a start event (neg_height != 0), push it into the heap. if neg_height != 0: heapq.heappush(heap, (neg_height, right)) # Current highest building height is at the top of the heap current_height = -heap[0][0] # If the result is empty or current height differs from last recorded height, add a new key value. if not result or current_height != result[-1][1]: result.append((x, current_height)) return result # Example usage: buildings = [[2,9,10],[3,7,15],[12,12],[15,20,10],[19,24,8]] print(getSkyLine(buildings)) # Expected output: [(2,10),(3,15),(7,12),(12,8),(15,18),(20,8),(24,0)] </pre>	<pre> Heap #272 Closest Binary Search Tree HAR LeetCode - SimplyList - WalkCC - LeetCode Two Pointers - Stack - Tree - DFS - BST - Heap Lists: Premium 98 Time Complexity: O(k * log n) - O(log n) to initialize the two stacks and O(n) to collect k elements. Space Complexity: O(log n) - due to the stack space in a balanced BST. Problem Given the root of a binary search tree, a target value, and an integer k, return the k values in the BST that are closest to the target. You may return the answer in any order. You are guaranteed to have only one unique set of k values in the BST that are closest to the target. Example 1: </pre>	 <pre> Input: root = [4,2,5,1,3], target = 3.74286, k = 2 Output: [4,3] Example 2: Input: root = [1], target = 0.00000, k = 1 Output: [1] Constraints: • The number of nodes in the tree is n. • 1 <= k <= n <= 104. • 0 <= Node.val <= 109 • -109 <= target <= 109 </pre>	Follow up: Assume that the BST is balanced. Could you solve it in less than O(n) runtime (where n = total nodes)? Brute Force (Python) <pre> # Brute Force Approach class Solution: def closestKValues(self, root: TreeNode, target: float, k: int): # Brute Force O(n log n) - sort repeatedly instead of heap data = List() result = [] for i in range(k): data.sort() result.append(data.pop()) return result </pre> Community Solutions (Python) •WalkCC
<pre> class Solution: def closestKValues(self, root: TreeNode None, target: float, k: int) -> list[int]: dq = collections.deque() def inorder(root: TreeNode None) -> None: if not root: return inorder(root.left) dq.append(root.val) inorder(root.right) inorder(root) while len(dq) > k: if abs(dq[0] - target) > abs(dq[-1] - target): dq.popleft() else: dq.pop() return list(dq) </pre> •LeetCode	<pre> # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def closestKValues(self, root: TreeNode, target: float, k: int) -> List[int]: def dfs(root): if root is None: return dfs(root.left) if len(q) < k: q.append(root.val) else: if abs(root.val - target) == abs(q[0] - target): # If node value is less or equal, push to prede and go right q.popleft() q.append(root.val) elif abs(root.val - target) < abs(q[0] - target): q.popleft() q.append(root.val) dfs(root.right) q = deque() dfs(root) return list(q) </pre> •SimplyList	<pre> # Python solution for Closest Binary Search Tree Value II # Definition for a binary tree node. class TreeNode: def __init__(self, val=0, left=None, right=None): self.val = val self.left = left self.right = right class Solution: def closestKValues(self, root: TreeNode, target: float, k: int): # Helper function to initialize predecessors stack def initPredecessor(node): while node: # If node value is less or equal, push to prede and go right if node.val <= target: prede.append(node) node = node.left else: node = node.left </pre>	<pre> # Helper function to initialize successors stack def initSuccessor(node): while node: # If node value is greater than target, push to succs and go left if node.val > target: succs.append(node) node = node.right else: node = node.right </pre> •Helper function to get next predecessor <pre> value def getNextPredecessor(): if not prede: return None node = prede.pop() # Traverse the right subtree: push nodes from left child then rightmost branch node = node.left while node: prede.append(node) </pre>	<pre> node = node.right return val # Helper function to get next successor value def getNextSuccessor(): if not succs: return None node = succs.pop() val = node.val # Traverse the left subtree: push nodes from right child then leftmost branch node = node.right while node: succs.append(node) node = node.left return val prede, succs = [], [] # Initialize the stacks with correct boundary values initPredecessor(root) initSuccessor(root) </pre>	<pre> result = [] # If the closest value from predecessor and successor are same, skip one to avoid duplicates. If prede and succs and prede[-1].val == succs[-1].val: getNextPredecessor() # Merge k closest values for i in range(k): if not prede: # If only successors left result.append(getNextSuccessor()) elif not succs: # Only predecessors left result.append(getNextPredecessor()) else: # Compare which candidate is closer to the target if abs(prede[-1].val - target) <= abs(succs[-1].val - target): result.append(getNextPredecessor()) else: result.append(getNextSuccessor()) return result </pre> •LC.ca
<pre> # Definition for a binary tree node. # class TreeNode: # def __init__(self, val=0, left=None, right=None): # self.val = val # self.left = left # self.right = right class Solution: def closestKValues(self, root: TreeNode, target: float, k: int) -> List[int]: def dfs(root): if root is None: return dfs(root.left) if len(q) < k: q.append(root.val) else: if abs(root.val - target) == abs(q[0] - target): # If node value is less or equal, push to stack and go right q.popleft() q.append(root.val) elif abs(root.val - target) < abs(q[0] - target): q.popleft() q.append(root.val) dfs(root.right) q = deque() dfs(root) return list(q) </pre>	<pre> q = deque() dfs(root) return list(q) ##### from collections import deque # Iteration class Solution: def closestKValues(self, root: TreeNode, target: float, k: int) -> List[int]: stack = [] q = deque() # Iterative in-order traversal while stack or root: while root: stack.append(root) root = root.left root = stack.pop() q.append(root.val) if abs(root.val - target) <= abs(q[0] - target): # If node value is less or equal, push to stack and go right q.popleft() q.append(root.val) root = root.right return list(q) </pre>	<pre> root = stack.pop() # Process current node if len(q) < k: q.append(root.val) else: if abs(root.val - target) < abs(q[0] - target): break q.popleft() q.append(root.val) else: # Early stop if the current value is farther than the first value in queue root = root.right return list(q) </pre>	<pre> Heap #295 Find Median from Data Stream HAR LeetCode - SimplyList - WalkCC - LeetCode Two Pointers - Design - Sorting - Heap Lists: Grid 169 Time Complexity: Problem The median is the middle value in an ordered integer list. If the size of the list is even, there is no middle value, and the median is the mean of the two middle values. • For example, for arr = [2,3,4], the median is 3. • For example, for arr = [2,3,4], the median is (2 + 3) / 2 = 2.5. Implement the MedianFinder class: • MedianFinder() initializes the MedianFinder object. • void addNum(int num) adds the integer num from the data stream to the data structure. • double findMedian() returns the median of all elements so far. Answers within 10⁻⁵ of the actual answer will be accepted. Example 1: </pre>	<pre> Input: ["MedianFinder", "addNum", "addNum", "findMedian", "addNum", "findMedian"] [[1], [1], [2], [1], [3], [1]] Output: [null, null, null, 1.5, null, 2.0] Explanation MedianFinder medianFinder = new MedianFinder(); // addNum(1) // addNum(2) // findMedian() // addNum(3) // findMedian() </pre> Constraints: 1 <= num <= 10⁵ - There will be at least one element in the data structure before calling findMedian. - At most 5 * 10⁴ calls will be made to addNum and findMedian. Follow up: - If all integer numbers from the stream are in the range [0, 100], how would you optimize your solution? - If 99% of all integer numbers from the stream are in the range [0, 100], how would you optimize your solution? Community Solutions (Python) •WalkCC	<pre> class MedianFinder: def __init__(self): self.maxheap = [] self.minheap = [] def addNum(self, num: int) -> None: if not self.maxheap or num <= -self.maxheap[0]: heapq.heappush(self.maxheap, -num) else: heapq.heappush(self.minheap, num) # Balance the two heaps s.t. # len(maxheap) == len(minheap) and len(maxheap) - len(minheap) <= 1. if len(self.maxheap) < len(self.minheap): heapq.heappush(self.maxheap, -heapq.heappop(self.minheap)) elif len(self.minheap) < len(self.maxheap) > 1: heapq.heappush(self.minheap, -heapq.heappop(self.maxheap)) def findMedian(self) -> float: if len(self.maxheap) == len(self.minheap): return -(self.maxheap[0] + self.minheap[0]) / 2.0 return -self.maxheap[0] </pre> •LeetCode
<pre> class MedianFinder: def __init__(self): self.min = [] self.max = [] def addNum(self, num: int) -> None: heapq.heappush(self.min, -num) -heapq.heappush(self.max, -num) if len(self.min) < len(self.max) > 1: heapq.heappush(self.max, -heapq.heappop(self.min)) def findMedian(self) -> float: if len(self.min) < len(self.max): return (self.min[0] - self.max[0]) / 2 return self.min[0] # Your MedianFinder object will be instantiated and called as such: # obj = MedianFinder() # obj.addNum(num) # param_2 = obj.findMedian() </pre> •SimplyList	<pre> import heapq class MedianFinder: def __init__(self): # max-heap for the lower half (store negatives to simulate max-heap) self.lowerHalf = [] # min-heap for the upper half self.upperHalf = [] def addNum(self, num: int) -> None: # Push to max-heap (simulate by pushing negative) heapq.heappush(self.lowerHalf, -num) # Ensure every element in lowerHalf is <= every element in upperHalf # Move maximum of lowerHalf to upperHalf heapq.heappush(self.upperHalf, -heapq.heappop(self.lowerHalf)) # Balance the heaps: if upperHalf exceeds lowerHalf in size if len(self.h2) > len(self.h1): len(self.lowerHalf): heapq.heappush(self.lowerHalf, -heapq.heappop(self.upperHalf)) </pre>	<pre> def findMedian(self) -> float: # If both heaps are balanced, median is average of both heaps' top elements if len(self.lowerHalf) == len(self.upperHalf): return (self.lowerHalf[0] + self.upperHalf[0]) / 2.0 # Otherwise, median is the top element of the larger heap return self.lowerHalf[0] # Example usage: # medianFinder = MedianFinder() # medianFinder.addNum(1) # medianFinder.addNum(2) # print(medianFinder.findMedian()) # Outputs 1.5 # medianFinder.addNum(3) # print(medianFinder.findMedian()) # Outputs 2.0 </pre> •LC.ca	<pre> from heapq import heappush, heapq class MedianFinder: def __init__(self): # The smaller half of the List, max heap (invert min-heap) self.lowerHalf = [] # The larger half of the List, min heap self.upperHalf = [] def addNum(self, num: int) -> None: # trick for smaller half, use -val # heapq in python does NOT have comparator like in Java heappush(self.lowerHalf, -num) heappush(self.lowerHalf, -num) heappush(self.lowerHalf, -num) heappush(self.lowerHalf, -num) # note: not self.lowerHalf.pop() if len(self.lowerHalf) < len(self.upperHalf): heappush(self.lowerHalf, -heapq.heappop(self.upperHalf)) </pre>	<pre> def findMedian(self) -> float: if len(self.lowerHalf) < len(self.upperHalf): return (-self.lowerHalf[0] + self.upperHalf[0]) / 2.0 else: return (self.lowerHalf[0] + self.upperHalf[0]) / 2.0 # Your MedianFinder object will be instantiated and called as such: # obj = MedianFinder() # obj.addNum(num) # param_2 = obj.findMedian() # follow up class MedianFinder: def __init__(self): self.counts = {} self.total = 0 def addNum(self, num: int) -> None: self.counts[num] += 1 self.total += 1 </pre>	<pre> self.counts[num] += 1 self.total += 1 def findMedian(self) -> float: self.total /= 2 # If even number of elements midIndex = self.total // 2 midIndex = midIndex + 1 count = 0 i = 0 for i in range(181): count += self.counts[i] if count >= midIndex and i == 0: i = 1 if count >= midIndex: i = 2 break return (i + i) / 2 else: # odd number of elements </pre>
<pre> middle = self.total // 2 + 1 count = 0 for i in range(181): count += self.counts[i] if count >= middle: return i ##### class MedianFinder: def __init__(self): # Initialize your data structure here. ... self.h1 = [] self.h2 = [] def addNum(self, num: int) -> None: heappush(self.h1, num) </pre>	<pre> heappush(self.h2, -heappop(self.h1)) if len(self.h2) - len(self.h1) > 1: heappush(self.h1, -heappop(self.h2)) def findMedian(self) -> float: if len(self.h2) > len(self.h1): return (self.h1[0] - self.h2[0]) / 2 # Your MedianFinder object will be instantiated and called as such: # obj = MedianFinder() # obj.addNum(num) # param_2 = obj.findMedian() </pre>	<pre> Heap #358 Rearrange String k Distance Apart HAR LeetCode - SimplyList - WalkCC - LeetCode Hash Table - String - Greedy - Sorting - Heap - Counting Lists: Premium 98 Time Complexity: O(n log C) where n is the length of s and C is the number of unique characters. Space Complexity: O(n) due to the storage used for the heap and wait queue. Problem Given a string s and an integer k, rearrange s such that the same characters are at least distance k from each other. If it is not possible to rearrange the string, return an empty string "". Example 1: Input: s = "ababc", k = 3 Output: "abacbc" Explanation: The same letters are at least a distance of 3 from each other. Example 2: Input: s = "aaabcc", k = 3 Output: "" Explanation: The same letters are at least a distance of 3 from each other. </pre>	<pre> Input: s = "aabbcc", k = 3 Output: "" Explanation: It is not possible to rearrange the string. Example 3: Input: s = "aaabbbcc", k = 2 Output: "abababcc" Explanation: The same letters are at least a distance of 2 from each other. Constraints: • 1 <= s.length <= 3 * 10⁵ • s consists of only lowercase English letters. • 0 <= k <= s.length Community Solutions (Python) •WalkCC class Solution: def rearrangeString(self, s: str, k: int) -> str: n = len(s) count = collections.Counter(s) valid = True for i in range(n): if count[i] > k: valid = False break if not valid: return "" def getNextLetter(self, int) -> str: """Returns the valid letter that has the most count.""" </pre>	<pre> maxCount = -1 bestLetter = '' for c in 'abcdefghijklmnopqrstuvwxyz': pq = [(v, c) for c, v in cnt.items()] heapq.heapify(pq) while pq: bestLetter = c maxCount = count(c) return bestLetter for i in range(n): c = getNextLetter(i) if c == '': return "" ans.append(c) count[c] -= 1 valid[i] += 1 if k return ''.join(ans) </pre> •LeetCode	<pre> class Solution: def rearrangeString(self, s: str, k: int) -> str: cnt = Counter(s) pq = [(v, c) for c, v in cnt.items()] heapq.heapify(pq) ans = [] while pq: v, c = heapq.heappop(pq) ans.append(c) if len(ans) > k: c = getNextLetter(len(ans)) if c == '': return "" ans.append(c) cnt[c] -= 1 valid[len(ans)] += 1 if k return ''.join(ans) </pre> •SimplyList
<pre> from collections import Counter, deque import heapq def rearrangeString(s: str, k: int) -> str: if k == 0: return s # Count the Frequency of each character char_count = Counter(s) # Build a max-heap using negative frequencies max_heap = [(-freq, ch) for ch, freq in char_count.items()] heapq.heapify(max_heap) # Queue to keep track of characters waiting for k distance wait_queue = deque() result = [] # Process the heap until it's empty while max_heap: </pre>	<pre> freq, ch = heapq.heappop(max_heap) result.append(ch) # Decrease frequency (remember freq is negative) freq += 1 # Add current char to the wait queue wait_queue.append((freq, ch)) # If we've placed k characters, we can re-insert the oldest one if needed if len(wait_queue) < k: continue freq_front, ch_front = wait_queue.popleft() if freq_front < 0: heapq.heappush(max_heap, (freq_front, ch_front)) rearranged = ''.join(result) return rearranged if len(rearranged) == len(s) else "" </pre> •LC.ca	<pre> from heapq import heappop class Solution: def rearrangeString(self, s: str, k: int) -> str: h = [(-v, c) for c, v in Counter(s).items()] heappop(h) ans = [] while h: v, c = heappop(h) ans.append(c) q.append((v + 1, c)) # enqueue even if 'v==0' # use example k=1, then q size is 2, then q.pop() one out if len(q) > k: # qsize: this is avoid you pick up same char in the same k-segment. v, c = q.popleft() heappush(h, (-v, c)) return "" if len(ans) != len(s) else ''.join(ans) </pre>	<pre> ##### import collections import heapq class Solution: def rearrangeString(self, s: str, k: int) -> str: if k == 0: return s counts = collections.Counter(s) pq = [] for ch, count in counts.items(): heapq.heappush(pq, (-count, ch)) sb = [] while pq: temp = [] </pre>	<pre> d = min(k, len(s)) for i in range(d): if not pq: return "" count, ch = heapq.heappop(pq) sb.append(ch) if count < -1: # pushed in as negated, so it's + if actual-positive-count > 1 temp.append((count+1, ch)) s = s[1:] for count, ch in temp: heapq.heappush(pq, (count, ch)) return ''.join(sb) </pre>	Heap #499 The Maze III HAR LeetCode - SimplyList - WalkCC - LeetCode Array - DFS - BFS - Graph - Matrix - Heap - Shortest Path Lists: Premium 98 Time Complexity: O(m * n * log(m * n)) where m and n are the maze dimensions. Space Complexity: O(m * n) Problem There is a ball in a maze with empty spaces (represented as 0) and walls (represented as 1). The ball can go through the empty spaces by rolling up, down, left or right, but it won't stop rolling until hitting a wall. When the ball stops, it could choose the next direction (must be different from last chosen direction). There is also a hole in this maze. The ball will drop into the hole if it rolls onto the hole. Given the m x n maze, the ball's position ball and the hole's position hole, where ball = (ballrow, ballcol) and hole = (holerow, holecol), return a string representing all the instructions that the ball should follow to drop in the hole with the shortest distance possible. If there are multiple valid instructions, return the lexicographically minimum one. If the ball can't drop in the hole, return "Impossible".

a b c d Input: board = ["a","b","c","d"], words = ["abcb"] Output: [] Constraints: - m == board.length - n == board[0].length 1 <= m, n <= 12 - board[i][j] is a lowercase English letter. 1 <= words.length <= 3 * 10^4 1 <= words[i].length <= 10 - words[i] consists of lowercase English letters.

All the strings of words are unique.

Brute Force (Python)

```
# Brute Force Approach
class Solution:
    def findWords(self, board, words):
        # Brute Force O(m * n * 4^L) - run
        # word-search for each word independently
        def exist(board, word):
            m, n = len(board), len(board[0])
            def dfs(r, c, i, seen):
                if i == len(word): return True
                if r < 0 or r == 0 or c < 0 or c == 0:
                    return False
                if (r, c) in seen or board[r][c] != word[i]: return False
                seen.add((r, c))
                ok = any(dfs(r+dr, c+dc, i+1, seen) for dr, dc in [(1, 0), (-1, 0), (0, 1), (0, -1)])
                seen.remove((r, c))
                return ok
            return any(dfs(r, c, 0, set()) for r in range(m) for c in range(n))
        return [w for w in words if exist(board, w)]
```

Community Solutions (Python)

Round 6 - Mid - Hard

p.2393

a

b

c

d

Input: board = ["a","b","c","d"], words = ["abcb"]
Output: []

Constraints:

- m == board.length
- n == board[0].length
- 1 <= m, n <= 12
- board[i][j] is a lowercase English letter.
- 1 <= words.length <= 3 * 10^4
- 1 <= words[i].length <= 10
- words[i] consists of lowercase English letters.

Round 6 - Mid - Hard

p.2394

a

b

c

d

Input: board = ["a","b","c","d"], words = ["abcb"]
Output: []

Constraints:

- m == board.length
- n == board[0].length
- 1 <= m, n <= 12
- board[i][j] is a lowercase English letter.
- 1 <= words.length <= 3 * 10^4
- 1 <= words[i].length <= 10
- words[i] consists of lowercase English letters.

Round 6 - Mid - Hard

p.2395

a

b

c

d

Input: board = ["a","b","c","d"], words = ["abcb"]
Output: []

Constraints:

- m == board.length
- n == board[0].length
- 1 <= m, n <= 12
- board[i][j] is a lowercase English letter.
- 1 <= words.length <= 3 * 10^4
- 1 <= words[i].length <= 10
- words[i] consists of lowercase English letters.

Round 6 - Mid - Hard

p.2396

a

b

c

d

Input: board = ["a","b","c","d"], words = ["abcb"]
Output: []

Constraints:

- m == board.length
- n == board[0].length
- 1 <= m, n <= 12
- board[i][j] is a lowercase English letter.
- 1 <= words.length <= 3 * 10^4
- 1 <= words[i].length <= 10
- words[i] consists of lowercase English letters.

Round 6 - Mid - Hard

p.2397

a

b

c

d

Input: board = ["a","b","c","d"], words = ["abcb"]
Output: []

Constraints:

- m == board.length
- n == board[0].length
- 1 <= m, n <= 12
- board[i][j] is a lowercase English letter.
- 1 <= words.length <= 3 * 10^4
- 1 <= words[i].length <= 10
- words[i] consists of lowercase English letters.

Round 6 - Mid - Hard

p.2398

a b c d board[i][j] = '#' # Mark the current cell as visited for dx, dy in [(0, 1), (1, 0), (0, -1), (-1, 0)]: ni, nj = i + dx, j + dy if 0 <= ni < m and 0 <= nj < n and board[ni][nj] != '#': dfs(ni, nj, next_node) board[i][j] = char # Restore the original character # Start DFS from each cell. for i in range(m): for j in range(n): dfs(i, j, root) return result *LC.ca
--

Round 6 - Mid - Hard

p.2399

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2400

a

b

c

d

idx = ord(board[i][j]) - ord('a')

if not node.children[idx] is None:

return

node = node.children[idx]

if not word:

ans.append(word)

c = board[i][j]

board[i][j] = '#' # Mark for visited

for a, b in [(0, -1), (0, 1), (1, 0), (-1, 0)]:

x, y = i + a, j + b

if 0 <= x < m and 0 <= y < n and board[x][y] != '#':

dfs(node, x, y)

board[i][j] = c

trie = Trie()

for w in words:

trie.insert(w)

ans = set()

m, n = len(board), len(board[0])

for i in range(m):

for j in range(n):

dfs(i, j, trie)

return ans

Round 6 - Mid - Hard

p.2401

a

b

c

d

for j in range(n):

dfs(0, j, 1)

return list(ans)

#####

class Trie:

def __init__(self):

self.children: List[Trie | None] = [None] * 26

self.ref: int = -1

def insert(self, w: str, ref: int):

node = self

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.ref = ref

return

Round 6 - Mid - Hard

p.2402

a

b

c

d

node.ref = ref

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

#####

class Trie:

def __init__(self):

self.children: List[Trie | None] = [None] * 26

self.ref: int = -1

def insert(self, w: str, ref: int):

node = self

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.ref = ref

return

Round 6 - Mid - Hard

p.2403

a

b

c

d

tree = Trie()

for i, w in enumerate(words):

tree.insert(w, i)

m, n = len(board), len(board[0])

ans = []

for i in range(m):

for j in range(n):

dfs(i, j, tree, 1)

return ans

#####

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

#####

class Trie:

def __init__(self):

self.children: List[Trie | None] = [None] * 26

self.ref: int = -1

def insert(self, w: str, ref: int):

node = self

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.ref = ref

return

Round 6 - Mid - Hard

p.2404

a b c d Input: words = ["abcd","dcba","lls","slls"] Output: [{"i":1,"j":0}, {"i":2,"j":2}] Explanation: The palindromes are ["dcba","dcba","lls","slls"] Example 2: Input: words = ["bat","tab","cat"] Output: [{"i":1,"j":1}] Explanation: The palindromes are ["battab","tabbat"] Example 3: Input: words = ["a","c"] Output: [{"i":0,"j":0}] Explanation: The palindromes are ["a","a"] Constraints: 1 <= words.length <= 5000 0 <= words[i].length <= 300 - words[i] consists of lowercase English letters. Brute Force (Python)
--

Round 6 - Mid - Hard

p.2405

a

b

c

d

Input: words = ["abcd","dcba","lls","slls"]
Output: [{"i":1,"j":0}, {"i":2,"j":2}]
Explanation: The palindromes are ["dcba","dcba","lls","slls"]

Example 2:

Input: words = ["bat","tab","cat"]
Output: [{"i":1,"j":1}]
Explanation: The palindromes are ["battab","tabbat"]

Example 3:

Input: words = ["a","c"]
Output: [{"i":0,"j":0}]
Explanation: The palindromes are ["a","a"]

Constraints:

- 1 <= words.length <= 5000
- 0 <= words[i].length <= 300
- words[i] consists of lowercase English letters.

Brute Force (Python)

Round 6 - Mid - Hard

p.2406

a

b

c

d

Input: words = ["abcd","dcba","lls","slls"]
Output: [{"i":1,"j":0}, {"i":2,"j":2}]
Explanation: The palindromes are ["dcba","dcba","lls","slls"]

Example 2:

Input: words = ["bat","tab","cat"]
Output: [{"i":1,"j":1}]
Explanation: The palindromes are ["battab","tabbat"]

Example 3:

Input: words = ["a","c"]
Output: [{"i":0,"j":0}]
Explanation: The palindromes are ["a","a"]

Constraints:

- 1 <= words.length <= 5000
- 0 <= words[i].length <= 300
- words[i] consists of lowercase English letters.

Brute Force (Python)

Round 6 - Mid - Hard

p.2407

a

b

c

d

Input: words = ["abcd","dcba","lls","slls"]
Output: [{"i":1,"j":0}, {"i":2,"j":2}]
Explanation: The palindromes are ["dcba","dcba","lls","slls"]

Example 2:

Input: words = ["bat","tab","cat"]
Output: [{"i":1,"j":1}]
Explanation: The palindromes are ["battab","tabbat"]

Example 3:

Input: words = ["a","c"]
Output: [{"i":0,"j":0}]
Explanation: The palindromes are ["a","a"]

Constraints:

- 1 <= words.length <= 5000
- 0 <= words[i].length <= 300
- words[i] consists of lowercase English letters.

Brute Force (Python)

Round 6 - Mid - Hard

p.2408

a

b

c

d

Input: words = ["abcd","dcba","lls","slls"]
Output: [{"i":1,"j":0}, {"i":2,"j":2}]
Explanation: The palindromes are ["dcba","dcba","lls","slls"]

Example 2:

Input: words = ["bat","tab","cat"]
Output: [{"i":1,"j":1}]
Explanation: The palindromes are ["battab","tabbat"]

Example 3:

Input: words = ["a","c"]
Output: [{"i":0,"j":0}]
Explanation: The palindromes are ["a","a"]

Constraints:

- 1 <= words.length <= 5000
- 0 <= words[i].length <= 300
- words[i] consists of lowercase English letters.

Brute Force (Python)

Round 6 - Mid - Hard

p.2409

a

b

c

d

Input: words = ["abcd","dcba","lls","slls"]
Output: [{"i":1,"j":0}, {"i":2,"j":2}]
Explanation: The palindromes are ["dcba","dcba","lls","slls"]

Example 2:

Input: words = ["bat","tab","cat"]
Output: [{"i":1,"j":1}]
Explanation: The palindromes are ["battab","tabbat"]

Example 3:

Input: words = ["a","c"]
Output: [{"i":0,"j":0}]
Explanation: The palindromes are ["a","a"]

Constraints:

- 1 <= words.length <= 5000
- 0 <= words[i].length <= 300
- words[i] consists of lowercase English letters.

Brute Force (Python)

Round 6 - Mid - Hard

p.2410

a b c d class Solution: def palindromePairs(self, words: List[str]) -> List[List[int]]: m = len(words) for i in range(m): for j in range(m): if words[i] + words[j] == words[j] + words[i]: ans.append((i, j)) return ans

Round 6 - Mid - Hard

p.2411

a

b

c

d

class Solution:

def palindromePairs(self, words: List[str]) -> List[List[int]]:

m = len(words)

for i in range(m):

for j in range(m):

if words[i] + words[j] == words[j] + words[i]:

ans.append((i, j))

return ans

Round 6 - Mid - Hard

p.2412

a

b

c

d

class Solution:

def palindromePairs(self, words: List[str]) -> List[List[int]]:

m = len(words)

for i in range(m):

for j in range(m):

if words[i] + words[j] == words[j] + words[i]:

ans.append((i, j))

return ans

Round 6 - Mid - Hard

p.2413

a

b

c

d

class Solution:

def palindromePairs(self, words: List[str]) -> List[List[int]]:

m = len(words)

for i in range(m):

for j in range(m):

if words[i] + words[j] == words[j] + words[i]:

ans.append((i, j))

return ans

Round 6 - Mid - Hard

p.2414

a

b

c

d

class Solution:

def palindromePairs(self, words: List[str]) -> List[List[int]]:

m = len(words)

for i in range(m):

for j in range(m):

if words[i] + words[j] == words[j] + words[i]:

ans.append((i, j))

return ans

Round 6 - Mid - Hard

p.2415

a

b

c

d

class Solution:

def palindromePairs(self, words: List[str]) -> List[List[int]]:

m = len(words)

for i in range(m):

for j in range(m):

if words[i] + words[j] == words[j] + words[i]:

ans.append((i, j))

return ans

Round 6 - Mid - Hard

p.2416

a b c d # Split the path by "/" and traverse the nodes parts = path.split("/") # Create the node if it does not exist for part in parts: node = node.children.get(part) # Return the target node and its name (last part of the path) return node, parts[-1] # Example usage: fs = FileSystem() print(fs.mkdir("/")) # prints [] fs.mkdir("/a/b/c") fs.addContentFile("/a/b/c", "hello") print(fs.listdir("/")) # prints ["a"] print(fs.readContentFromFile("/a/b/c/d")) # prints "hello" *LC.ca

Round 6 - Mid - Hard

p.2417

a

b

c

d

class Trie:

def __init__(self):

self.name = None

self.isFile = False

self.content = []

self.children = {}

def insert(self, path, isFile):

node = self

ps = path.split("/")

for p in ps[1:]:

if p not in node.children:

node.children[p] = Trie()

node = node.children[p]

node.isFile = isFile

def __lt__(self, other):

if self.time < other.time:

return self.time < other.time

def update(self, node) -> None:

if not node in self.top3:

self.top3.append(node)

self.top3.sort()

if len(self.top3) > 3:

self.top3.pop()

Round 6 - Mid - Hard

p.2418

a

b

c

d

class Trie:

def __init__(self):

self.name = None

self.isFile = False

self.content = []

self.children = {}

def insert(self, path, isFile):

node = self

ps = path.split("/")

for p in ps[1:]:

if p not in node.children:

node.children[p] = Trie()

node = node.children[p]

node.isFile = isFile

def __lt__(self, other):

if self.time < other.time:

return self.time < other.time

def update(self, node) -> None:

if not node in self.top3:

self.top3.append(node)

self.top3.sort()

if len(self.top3) > 3:

self.top3.pop()

Round 6 - Mid - Hard

p.2419

a

b

c

d

class Trie:

def __init__(self):

self.name = None

self.isFile = False

self.content = []

self.children = {}

def insert(self, path, isFile):

node = self

ps = path.split("/")

for p in ps[1:]:

if p not in node.children:

node.children[p] = Trie()

node = node.children[p]

node.isFile = isFile

def __lt__(self, other):

if self.time < other.time:

return self.time < other.time

def update(self, node) -> None:

if not node in self.top3:

self.top3.append(node)

self.top3.sort()

if len(self.top3) > 3:

self.top3.pop()

Round 6 - Mid - Hard

p.2420

a

b

c

d

class Trie:

def __init__(self):

self.name = None

self.isFile = False

self.content = []

self.children = {}

def insert(self, path, isFile):

node = self

ps = path.split("/")

for p in ps[1:]:

if p not in node.children:

node.children[p] = Trie()

node = node.children[p]

node.isFile = isFile

def __lt__(self, other):

if self.time < other.time:

return self.time < other.time

def update(self, node) -> None:

if not node in self.top3:

self.top3.append(node)

self.top3.sort()

if len(self.top3) > 3:

self.top3.pop()

Round 6 - Mid - Hard

p.2421

a

b

c

d

class Trie:

def __init__(self):

self.name = None

self.isFile = False

self.content = []

self.children = {}

def insert(self, path, isFile):

node = self

ps = path.split("/")

for p in ps[1:]:

if p not in node.children:

node.children[p] = Trie()

node = node.children[p]

node.isFile = isFile

def __lt__(self, other):

if self.time < other.time:

return self.time < other.time

def update(self, node) -> None:

if not node in self.top3:

self.top3.append(node)

self.top3.sort()

if len(self.top3) > 3:

self.top3.pop()

Round 6 - Mid - Hard

p.2422

a b c d Input: ["AutocompleteSystem", "input", "input", "input"] Output: [{"i":1,"j":0}, {"i":2,"j":2}] Explanation: The palindromes are ["dcba","dcba","lls","slls"] Example 2: Input: words = ["bat","tab","cat"] Output: [{"i":1,"j":1}] Explanation: The palindromes are ["battab","tabbat"] Example 3: Input: words = ["a","c"] Output: [{"i":0,"j":0}] Explanation: The palindromes are ["a","a"] Constraints: 1 <= words.length <= 5000 0 <= words[i].length <= 300 - words[i] consists of lowercase English letter, a hash '#', or space ' '. - Each tested sentence will be a sequence of characters 'c' that end with the Character '#' - Each tested sentence will have a length in the range [1, 200]. - The words in each input sentence are separated by single spaces. - At most 5000 calls will be made to input. Community Solutions (Python)
--

Round 6 - Mid - Hard

p.2423

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2424

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2425

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2426

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2427

a

b

c

d

class Trie:

def __init__(self):

self.children = [None] * 26

self.w = ''

minor adjust, not a boolean is_end, but the whole word

so it's easier for dfs to save the word

def insert(self, w):

dfs

for c in w:

idx = ord(c) - ord('a')

if not node.children[idx] is None:

node.children[idx] = Trie()

node = node.children[idx]

node.w = w

class Solution:

def findWords(self, board: List[List[str]], words: List[str]) -> List[str]:

dfs = dfs

dfs(0, 0, 1, set())

return ans

Round 6 - Mid - Hard

p.2428

<pre> queue = deque([beginIdx]) length = 0 while queue: length += 1 for k in range(1, len(queue)): top = queue.popleft() for nbr in getNeighbors(top, endIdx, wordList): if nbr not in distance: distance[nbr] = distance[top] + 1 queue.append(nbr) return distance def dfs(beginIdx, endIdx, wordList, path, res, distance): if beginIdx == endIdx: res.append(path + 1) return for nbr in getNeighbors(beginIdx, endIdx, wordList): if distance.get(nbr, -2) + 1 == distance[beginIdx]: path.append(nbr) </pre>	<pre> dfs(nbr, endIdx, wordList, path, res, distance) path.pop() res = [] distance = {nbr: endIdx, beginIdx, wordList} dfs(beginIdx, endIdx, wordList, (beginIdx, res, distance) return res </pre>	#996 Number of Squareful Arrays LeetCode - SimpleXtreme - Walccc - LeetCode Array - Math - Dynamic Programming - Backtracking Lists: Denny Zhang Time Complexity: $O(n \times 2^n)$ in the worst-case scenario due to exploring all maximal subsets with n elements and checking pairwise sums. Space Complexity: $O(n)$ for recursion and $O(n)$ for the visited $\mathbb{P}$. Problem An array is squareful if the sum of every pair of adjacent elements is a perfect square. Given an integer array nums, return the number of permutations of nums that are squareful. Two permutations perm1 and perm2 are different if there is some index i such that $perm1[i] \neq perm2[i]$. Example 1: <pre> Input: nums = [1,1,7,8] Output: 2 Explanation: [1,1,7,8] and [1,7,8,1] are the valid permutations. </pre> Example 2:	<pre> Input: nums = [2,2,2] Output: 1 Constraints: n == nums.length <= 12 0 <= nums[i] <= 109 </pre> Brute Force (Python) # Brute Force Approach <pre> class Solution: def squareful(self, nums): # Brute Force - exhaustive backtracking without pruning results = [] def backtrack(start, path): results.append(List(path)) for i in range(start, len(nums)): path.append(nums[i]) backtrack(i + 1, path) path.pop() backtrack(0, []) return results </pre> Community Solutions (Python) • Walccc	<pre> class Solution: def numSquarefulPerms(self, nums: List[int]) -> int: ans = 0 used = [False] * len(nums) def isSquare(num: int) -> bool: root = math.isqrt(num) return root * root == num def dfs(path: List[int]) -> None: nonlocal ans if len(path) == 1 and not isSquare(path[-1] + path[-2]): return if len(path) == len(nums): ans += 1 return for i, a in enumerate(nums): if used[i]: continue </pre>	<pre> if i > 0 and num[i] == num[i - 1] and not used[i - 1]: continue used[i] = True dfs(path + [a]) used[i] = False nums.sort() dfs([]) return ans </pre> • LeetCode <pre> class Solution: def numSquarefulPerms(self, nums: List[int]) -> int: n = len(nums) if n <= 1: return 1 for i in range(1, n): if i <= 1: continue for j in range(i + 1, n): if j >= i + 1: continue for k in range(j + 1, n): </pre>
Round 6 - Mid - Hard p.265	Round 6 - Mid - Hard p.266	Round 6 - Mid - Hard p.267	Round 6 - Mid - Hard p.268	Round 6 - Mid - Hard p.269	Round 6 - Mid - Hard p.2670
<pre> if (i >= k & i) and k <= i: s = nums[j] + nums[k] isInt(sqrt(s)) if i + k == s: f[i][j] = f[i - 1][j - 1] else: f[i][j] = 0 </pre> 11 <= j <= i ans = sum(f[i - 1][k - 1]) for j in range(n) for v in Counter(nums).values(): res += fact(n - v) / fact(n - 1 - v) return ans • SimpleXtreme from math import isqrt # Function to check if a number is a perfect square <pre> def is_square(num): root = isqrt(num) return root * root == num </pre> <pre> def numSquarefulPerms(nums): n = len(nums) ans, sort1 = 0, sorted(nums) return ans </pre>	<pre> visited = [False] * n result = 0 def dfs(last_index, count): nonlocal result if all elements have been used, we found a valid permutation if count == n: result += 1 return for i in range(1, n): if visited[i]: continue # Skip duplicates: if the current element is the same as the previous one and the previous one hasn't been used if i > 0 and nums[i] == nums[i - 1] and not visited[i - 1]: continue with the last element is a perfect square if last_index == -1 or is_square(nums[last_index] + nums[i]): visited[i] = True dfs(i, count + 1) visited[i] = False </pre>	<pre> dfs(-1, 0) return result # Example usage: n = 5 nums = [1, 1, 7, 8] print(numSquarefulPerms(1, 7, 8)) # Expected output: 2 print(numSquarefulPerms(2, 2, 2)) # Expected output: 1 </pre> <pre> class Solution: def numSquarefulPerms(self, nums: List[int]) -> int: n = len(nums) f = [0] * n for j in range(1, n): f[j] = 0 for i in range(1, j): if i >= 1: continue for k in range(j + 1, n): </pre>	<pre> if (i <= k & i) and k <= i: s = nums[j] + nums[k] isInt(sqrt(s)) if i + k == s: f[i][j] = f[i - 1][j - 1] else: f[i][j] = 0 </pre> 11 <= j <= i ans = sum(f[i - 1][k - 1]) for j in range(n) for v in Counter(nums).values(): res += fact(n - v) / fact(n - 1 - v) return ans	Round 6 - Mid - Hard p.2674	Round 6 - Mid - Hard p.2675
adjusting the next pointers... Reconnect the reversed group with the previous part of the list and update pointers to move to the next group. The approach leverages a dummy node for easier handling of head modifications and uses a helper function to fetch the kth node. The in-place reversal ensures that the extra memory usage is constant. #432 All Ome Data Structure [Hard] - Linked List Key Insights - Use a Doubly-Linked List (DLL) where each node holds a unique count value and a set of keys with that count. - Maintain a Hash Map (keyToNode) to quickly locate the node corresponding to each key. - Insert new nodes in the DLL when a key's count is incremented or decremented and the adjacent node does not have the target count. - Remove nodes from the DLL when no keys remain in that count. Space & Time Time Complexity: $O(n)$ average for inc, dec, getMinKey, and getMinKey. Space Complexity: $O(n)$ where n is the number of unique keys in the data structure.	Solution The solution uses a combination of a doubly-linked list and hash maps. Each node in the DLL represents a frequency and maintains a set of keys that have that frequency. A hash map maps keys to their corresponding nodes. When increment or decrement is called, we update the key's frequency and move the key to the appropriate node in the DLL. If the adjacent node with the required frequency doesn't exist, we create a new node and insert it in the correct position. Removal of a key from a node and deletion of empty nodes ensures that getMinKey and getMinKey are returned directly from the head and tail of the DLL. #460 LRU Cache [Hard] - Linked List Key Insights - Maintain a mapping from key to its value and frequency. - Use an additional mapping from frequency to keys (maintaining the order of insertion or recent use) for quick eviction. - Keep a global minfreq variable to track the lowest frequency present in the cache. - When a key is accessed or updated, increase its frequency and relocate it in the frequency mapping. - Evictions occur by removing the oldest key from the lowest frequency bucket.	Space & Time Time Complexity: $O(n)$ average for both get and put. Space Complexity: $O(capacity)$, where capacity is the maximum number of keys stored. Solution The solution utilizes two main data structures: - A hash map (keyToValRef) that maps keys to a pair of values (frequency, node). - A second hash map (freqToNodes) mapping frequencies to an ordered list/set of keys. A design preserves the order in which keys were added to allow removal of the least recently used key when multiple keys share the same frequency. When a key is accessed or updated, the key is removed from its current frequency list and placed in the next higher frequency list. If the frequency list for the minimal frequency becomes empty, minfreq is updated. This design guarantees that both get and put operations execute in constant time on average. #32 Longest Valid Palindromes [Hard] - Stack Key Insights - Use a stack to keep track of indices where potential valid substrings begin.	• Start by pushing a dummy index (-1) to handle edge cases. • For every j, push its index onto the stack. • For every i, pop from the stack. If the stack becomes empty, push the current index as a new base. Otherwise, compute the length of the valid substring using the current index minus the top index of the stack. • An alternative is the dynamic programming approach where $dp[i][j]$ represents the length of the longest valid substring ending at index i. Space & Time Time Complexity: $O(n)$ where n is the length of the string. Space Complexity: $O(n)$ for the stack data structure. Solution The stack-based solution works by maintaining indices for unmatched parentheses. Initially, a dummy index (-1) is pushed onto the stack to serve as the base for calculating subsequent valid substrings. As we iterate through the string: - If the character is $'('$, we push its index onto the stack. - If the character is $'>'$, we pop from the stack. If the stack is empty afterwards, that means there is no valid starting position, so we push the current index to the base. Otherwise, we calculate the length of the current valid substring by subtracting the current index with the new top index of the stack and update ans.	maximum length accordingly. #42 Trapping Rain Water [Hard] - Stack Key Insights - The water trapped at any index i is determined by the maximum of the maximum height on its left and right minus the height at that index. - A two-pointers approach can efficiently solve the problem in one pass by maintaining left and right boundaries. - Alternative approaches include dynamic programming with pre-computed left max and right max arrays, or using a monotonic stack to determine boundaries. Space & Time Time Complexity: $O(n)$ Space Complexity: $O(1)$ when using the two-pointer approach Solution We use a two-pointers strategy by initializing pointers at the beginning and the end of the array. Keep track of the maximum height seen so far from the left (left_max) and the right (right_max). At each step, move the pointer with the lesser height because the water trapped is determined by the shorter boundary. Compare the water between the current index and the index from the boundary (left_max or right_max) and the current height.	accumulating it into the total. This approach ensures linear runtime scanning with constant extra space. #4 Largest Rectangle in Histogram [Hard] - Stack Key Insights - Each bar can potentially extend left and right as long as the neighboring bars are not shorter. - A monotonic (increasing) stack can be used to efficiently track indices of bars. - When encountering a bar lower than the one on the top of the stack, pop the stack and calculate the area using the popped height as the smallest bar. The width for the rectangle is determined by the difference between the current index and the index from the stack (or the current index if the stack is empty). This Space & Time Time Complexity: $O(n)$ Space Complexity: $O(n)$ Solution The solution employs a monotonic stack to traverse the histogram once. At each bar, while the current bar's height is less than the height at the top index of the stack, pop from the stack and calculate the area using the popped height as the smallest bar. The width for the rectangle is determined by the difference between the current index and the index from the stack (or the current index if the stack is empty). This
effectively finds the maximum rectangular area possible. A sentinel value (0) is added at the end of the histogram to push any remaining bars from the stack. #224 Basic Calculator [Hard] - Stack Key Insights - Use a stack to save previous results and signs when encountering parentheses. - Process the string left-to-right by accumulating multi-digit numbers and applying the current sign. - When encountering a $'>'$, push the current result and sign onto the stack and reset them. - When encountering a $'>'$, complete the current sub-expression then pop the previous state to incorporate the computed value. - Handle whitespaces by simply skipping them. Space & Time Time Complexity: $O(n)$ where n is the length of the input string, since we process each character once. Space Complexity: $O(n)$ in the worst-case scenario due to the stack used for nested parentheses. Solution The solution uses an iterative approach with a stack: - Initialize variables: result to keep the running total, sign to track addition/subtraction, and index to iterate over the string. - As you iterate, build multi-digit numbers.	numbers by checking for consecutive numerical characters... Adjust the total by adding the product of the current number and its sign... When encountering a $'>'$, push the current result and sign onto the stack, then reset result and sign for the new sub-expression... When encountering a $'>'$, complete the sub-expression by popping the previous result and sign, then combine... Skip over spaces... The final result is the computed value after the end of the string. This approach effectively simulates recursion and correctly handles nested expressions and negation. #239 Sliding Window Maximum [Hard] - Stack Key Insights - Use a deque (double-ended queue) to maintain the indices of potential maximum elements in a decreasing order. - Ensure that the deque always has the current window's indices by removing elements that fall outside the current window. - Only add elements that are greater than the ones at the back of the deque, thus preserving a monotonic decreasing order. - The maximum for the current window is at the front of the deque. Space & Time	Time Complexity: $O(n)$ where n is the number of elements in nums, since each element is processed at most twice. Space Complexity: $O(k)$, as the deque stores indices for at most k elements at any time. Solution The solution uses a monotonic deque to maintain indices of potential maximum elements in the current window. As the window slides, we: - Remove indices from the front if they are out of the window. - Remove indices from the back if the current element is larger, because they cannot be the maximum if the current element is in the window. - Append the current index... After the first k elements, the element at the front of the deque is the maximum for that window. This approach ensures that each element is pushed and popped from the deque only once, achieving an overall $O(n)$ time complexity. #716 Max Stack [Hard] - Stack Key Insights - Use a doubly-linked list to support fast insertion and removal from the stack. - Maintain a balanced tree (or ordered dictionary/multiset) to quickly locate the maximum element in $O(\log n)$ time.	• Map each value to its corresponding node(s) in the doubly-linked list, so that when popMax is called, you can immediately remove the corresponding node from the list. • The double-linking allows removal of arbitrary nodes in $O(1)$, once you have the reference. Space & Time Time Complexity: $O(n)$ Space Complexity: $O(n)$ • push: $O(\log n)$ due to insertion in the ordered structure. • pop: $O(1)$ for removal from the doubly-linked list, plus $O(\log n)$ for updating the tree. • top: $O(1)$ • peekMax: $O(1)$ or $O(\log n)$ depending on the tree implementation. • popMax: $O(\log n)$ for pop looking up and removal from the tree, $O(1)$ for doubly-linked list deletion. Space Complexity: $O(n)$ • $O(n)$ for storing all nodes in the doubly-linked list and the tree structure mapping values to nodes. Solution We use two data structures: - A doubly-linked list to store the elements in sorted order. This supports fast push and pop operations and allows $O(1)$ removal when given a reference. - An ordered structure (like a balanced BST, TreeMap in Java, or SortedList in Python) that maps each value to a list of nodes that hold that value in the linked list. This allows us to quickly determine the maximum element. When there are duplicates, we remove the one closest to the top by storing nodes in order. The trick is to keep these structures synchronized. When an element is pushed, add its node to both the doubly-linked list and the ordered structure. When an element is removed (either via pop or popMax), remove its node from both structures.	or SortedList in Python) that maps each value to a list of nodes that hold that value in the linked list. This allows us to quickly determine the maximum element. When there are duplicates, we remove the one closest to the top by storing nodes in order. The trick is to keep these structures synchronized. When an element is pushed, add its node to both the doubly-linked list and the ordered structure. When an element is removed (either via pop or popMax), remove its node from both structures. #772 Basic Calculator III [Hard] - Stack Key Insights - Use recursion to handle nested expressions defined by parentheses. - A stack can be used to correctly evaluate the expression and respect operator precedence. - Multiplication and division have higher precedence than addition and subtraction. - When encountering an open parenthesis, recursively compute its value until a closing parenthesis is found. - Use immediate calculation for multiplication and division by updating the top of the stack before moving to the next operator. Space & Time Time Complexity: $O(n)$ where n is the length of the string, as every character is processed.	Space Complexity: $O(n)$ due to the recursion stack or auxiliary stack used for intermediate results. Solution We use a recursive approach combined with a stack to solve the problem. As we iterate through the string: - Convert digits into numbers... When encountering an operator or parentheses, process the previously accumulated numbers based on the operator. - For multiplication or division, pop the last number from the stack, apply the operation, and push the result back. - When a $'>'$ is encountered, recursively evaluate the subexpression until the corresponding $'>'$. After processing the subexpression, sum the values in the stack to get the final result. This method correctly handles both operator precedence and nested expressions. #895 Maximum Frequency Stack [Hard] - Stack Key Insights - Use a hash map to count the frequency of each element. - Maintain another hash map that maps frequencies to stacks (lists) of elements. - Track the current maximum frequency to enable $O(1)$ retrieval of the most frequent element. - When pushing an element, update its frequency and add it to the corresponding frequency stack.
• When popping an element, remove it from the stack corresponding to the maximum frequency and update the frequency count; if that stack becomes empty, decrease the current maximum frequency. Space & Time Time Complexity: $O(1)$ per push and pop. Space Complexity: $O(n)$, where n is the number of elements pushed onto the stack. Solution The solution involves using two main data structures: - A hash map (freq) to store the frequency of each value. - A hash map (group) that maps a frequency to a stack (list) of values that have that frequency. During a push: - Increment the frequency count of the value... Push the value onto the stack corresponding to its updated frequency... Update the maximum frequency if necessary. During a pop: - Pop the top element from the stack corresponding to the current maximum frequency... Decrement its frequency count in the freq map... If the frequency stack becomes empty after popping, decrement the current maximum frequency. - A hash map (group) that maps a frequency to a stack (list) of values that have that frequency. Space & Time Time Complexity: $O(n \log k)$ where N is the total number of nodes across all lists and k is the number of lists. Space Complexity: $O(k)$ due to the heap containing at most one node from each list. Solution We use a min-heap to always retrieve the smallest node among the current nodes in the linked lists. First, initialize the heap with the head of each list. Then, continuously extract the smallest node from the heap, attach it to the merged list, and if the extracted node has a next node, insert that into the heap. The process repeats until the heap is empty.	closest to the top. #23 Merge k Sorted Lists [Hard] - Heap Key Insights - Use a min-heap (priority queue) to efficiently extract the smallest value among the current heads of the lists. - By pushing the head of each non-empty list into the heap, we can pull the smallest node, then push that node's next element into the heap. - Alternatively, a divide and conquer approach can be used by recursively merging pairs of lists. - Careful management of pointers (or references) is key to constructing the new linked list. Space & Time Time Complexity: $O(N \log k)$ where N is the total number of nodes across all lists and k is the number of lists. Space Complexity: $O(k)$ due to the heap containing at most one node from each list. Solution We use a min-heap to always retrieve the smallest node among the current nodes in the linked lists. First, initialize the heap with the head of each list. Then, continuously extract the smallest node from the heap, attach it to the merged list, and if the extracted node has a next node, insert that into the heap. The process repeats until the heap is empty.	#218 The Skyline Problem [Hard] - Heap Key Insights - Use a line sweep approach to process building start and end events in sorted order. - Whenever there is a change in the height of the heap (i.e., the current maximum height), a key point is added to the result. This key point signifies a vertical change in the skyline. #722 Close Binary Search Tree Value II [Hard] - Heap Key Insights - The BST property allows efficient narrowing down of candidate nodes. - Using two stacks to track predecessors (values < current) and successors (values > target) can efficiently yield the closest values. - Modified in-order traversal helps in retrieving the next closest value in each possible direction (up/down). - Merging two sorted lists of candidate values based on absolute difference with the target is the key step. Space & Time Time Complexity: $O(k \log k)$ where N is the total number of elements across all lists. Space Complexity: $O(k)$ for the event list and the heap used for processing active buildings. Solution The solution uses the line sweep algorithm with a max-heap (or priority queue) to maintain the heights of active buildings. Each building contributes two events: one when building starts (adding its height) and one when it ends (removing its height). These events are	sorted primarily by their x-coordinate. For start events, we use negative height values to ensure they are processed before end events at the same x-coordinate. During the sweep, the heap is updated by adding new buildings heights and removing buildings that have ended. Whenever there is a change in the current height (i.e., the current maximum height), a key point is added to the result. This key point signifies a vertical change in the skyline. #722 Close Binary Search Tree Value II [Hard] - Heap Key Insights - The BST property allows efficient narrowing down of candidate nodes. - Using two stacks to track predecessors (values < current) and successors (values > target) can efficiently yield the closest values. - Modified in-order traversal helps in retrieving the next closest value in each possible direction (up/down). - Merging two sorted lists of candidate values based on absolute difference with the target is the key step. Space & Time Time Complexity: $O(k \log k)$ where N is the total number of elements across all lists. Space Complexity: $O(k)$ for the event list and the heap used for processing active buildings. Solution The solution uses the line sweep algorithm with a max-heap (or priority queue) to maintain the heights of active buildings. Each building contributes two events: one when building starts (adding its height) and one when it ends (removing its height). These events are	updated if necessary. This process continues until one of the lists is exhausted. #759 Employee Free Time [Hard] - Heap Key Insights - Flatten the schedule to combine all employees' intervals. - Sort the flattened intervals by start time. - Merge overlapping intervals to form a consolidated view of busy times. - Identify gaps between merged intervals as the common free time. - Ensure free intervals have strictly positive length. Space & Time Time Complexity: $O(n \log n)$ where N is the total number of intervals (due to sorting). Space Complexity: $O(n)$, used for the flattened list and merged intervals. Solution The solution leverages interval merging. First, all intervals from every employee are collected and sorted by start time. By iterating through the sorted intervals, overlapping intervals are merged into one consolidated busy period. Finally, the gaps between consecutive merged intervals are identified as free periods available to all employees. This approach efficiently handles the	intervals with a simple sort and a linear scan. #1425 Constrained Subsequence Sum [Hard] - Heap Key Insights - Use dynamic programming where $dp[i]$ represents the maximum sum of a valid subsequence ending at index i. - For each index i, consider taking $nums[i]$ alone or appending it to a valid subsequence ending at an index j (where $j < i$) that maximizes the sum. - To efficiently obtain the maximum $dp[j]$ in a sliding window of the last k indices, use a monotonic (decreasing) deque. - The idea is to maintain the window maximum and update it as we proceed through the array. Space & Time Time Complexity: $O(n)$ Space Complexity: $O(n)$ ($O(k)$ extra space for the deque, used to store array using $O(n)$) Solution We solve the problem by defining a dp array where $dp[i] = \text{maxsum}$ is the maximum sum of a valid subsequence ending at index i. The trick is to use a sliding window of size k to maintain the maximum dp values from previous sums that are negative. To access the maximum dp in the window in constant time, a monotonic deque is maintained that stores indices with their dp values in decreasing order.
Round 6 - Mid - Hard p.2695	Round 6 - Mid - Hard p.2696	Round 6 - Mid - Hard p.2697	Round 6 - Mid - Hard p.2698	Round 6 - Mid - Hard p.2699	Round 6 - Mid - Hard p.2694

At each index, we: - Remove elements from the front of the deque if they are out of the current window ($i - \text{index} > k$). Use the front of the deque (if non-empty) as the maximum dp value from the previous k indices. - Compute $\text{dp}[i]$ and update the global maximum answer. - Remove from the back of the deque all indices with dp values less than the current $\text{dp}[i]$ since they are not useful. - Insert the current index into the deque. #12 Word Search II [Hard] - Trie Key Insights - Use Depth-First Search (DFS) to explore possible words starting from each board cell. - Build a Trie (prefix tree) to store the words for $O(1)$ prefix checks and efficient pruning. - Mark visited cells and restore them after DFS to avoid revisiting in the current search path. - Prune search paths early if the current prefix is not part of any word in the Trie. Space & Time Time Complexity: $O(m \cdot n \cdot 4^L)$ in the worst case, where L is the maximum word length; however, using a Trie prunes unnecessary paths. Space Complexity: $O(k)$ for the Trie storage, where k is the total number of letters in all words, plus $O(m \cdot n)$ for the board.	auxiliary space for recursion and board marking. Solution We first insert all words into a Trie data structure to allow quick lookups of prefixes. Then, for each cell in the board, we perform DFS. During DFS, if the current path matches a Trie node that represents a complete word, we add that word to the result list and mark it as found to avoid duplicates. We continue exploring adjacent cells (up, down, left, right) while marking the cell as visited. After exploring, we restore the original letter for further DFS calls. This combination of Trie and DFS with backtracking efficiently finds valid words on the board. #336 Palindrome Pairs [Hard] - Trie Key Insights - A palindrome is a string that reads the same forwards and backwards. - For any given word, if you split it into two parts, one part (either prefix or suffix) might be a palindrome. - If the other part's reverse exists elsewhere in the array, then that reverse can be concatenated to yield a palindrome. - Carefully handle edge cases like empty strings, since an empty string is a palindrome by default. Space & Time	Time Complexity: $O(n \cdot k^2)$ in the worst case where n is the number of words and k is the maximum word length, but with the palindrome checking optimization this can be considered $O(m \cdot \text{word length})$. Each word is processed once and its split is checked in $O(k)$ time. Space Complexity: $O(n \cdot k)$ due to the hashmap storing all words and their indices. Solution We use a hashmap (dictionary) to store each word and its corresponding index. For every word, we iterate through every possible split position to divide the word into a prefix and a suffix. For each split: - If the prefix is a palindrome, we look for the reverse of the suffix in the hashmap. If found (and not the same word), then combining the reverse with the current word forms a palindrome. - Similarly, if the suffix is a palindrome, we look for the reverse of the prefix. We must be cautious with edge cases, especially when one part is empty, as the empty string is considered a palindrome. This method avoids checking every possible pair explicitly and leverages string reversal and palindrome checks to achieve efficiency. #588 Design In-Memory File System [Hard] - Trie Key Insights - Use a tree (trie) to represent directories and files.	Each node can be either a directory or a file. directories maintain a mapping of names to child nodes. - For f, if the given path is a file, return only its name. If f's directory, return the sorted list of names of its children. - mkdir must create all intermediate directories if they do not already exist. - File nodes store content and support content appending. Space & Time Time Complexity: $O(k \log k)$ where k is the number of entries in the directory (due to sorting), or $O(n)$ if traversing a long directory. - mkdir, addContentToFile, readContentFromFile: $O(d)$ where d is the depth of the file path. Space Complexity: $O(C)$ where C is the total number of characters stored in directory names and file contents. Solution The solution uses a tree-based approach where each node represents either a directory or a file. Each directory node stores its children in a hash table (or dictionary) mapping names to child nodes. File nodes store their content as a string and carry a flag indicating they are files. For the ls operation, check if the node is a	file - if so, return its name; otherwise, list and sort the names of all children in that directory. The mkdir operation traverses (or creates) nodes for each segment of the given path. The addContentToFile method accesses or creates the file node and appends the content. Finally, readContentFromFile retrieves the stored content from the file node. #642 Design Search Autocomplete System [Hard] - Trie Key Insights - Use a Trie to efficiently store and retrieve sentences. - For each prefix, maintain a list of suggestions (up to 3). - Maintain a mapping at each Trie node to record sentences (or their frequencies) that pass through that node. - Use sorting or a min-heap to select the top three sentences based on their frequency (hot degree) and lexicographical order if frequencies tie. - On receiving gs, update the Trie with the current sentence and reset the current search state. Space & Time Time Complexity: $O(L \cdot \log k)$ per character input query, where L is the length of the current prefix and k is 3 (constant factor), thus ensuring efficient autocomplete.	Space Complexity: $O(N \cdot L)$, where N is the number of unique sentences and L is the average sentence length, for maintaining the Trie. Solution The solution revolves around building a Trie where each node contains: - A mapping to its child nodes. - A hash map that records all sentences passing through the node along with their occurrence counts. For each character entered (except '\n'), the system: - Traverses the Trie to find the current prefix node. - Retrieves stored sentences at that node and sorts them based on the following criteria: descending by frequency and ascending lexicographically if frequencies are equal. - Returns the top three sentences from the sorted result. When the user inputs '\n', the current sentence (tracked as user input so far) is added or its frequency updated in the Trie, and the input state resets. #37 Sudoku Solver [Hard] - Backtracking Key Insights - Use backtracking to explore digit placements for each empty cell. - Validate placements by ensuring that the chosen digit is not already present in the corresponding row, column,
or 3×3 sub-box. - Employ recursion to fill the board incrementally and backtrack upon encountering invalid configurations. - Although the worst-case time complexity is exponential, the fixed board size (9×9) keeps the problem computationally manageable. Space & Time Time Complexity: In the worst-case scenario, the algorithm can explore up to $O(9^n)$ possibilities where n is the number of empty cells. However, since n is at most 81 and many branches are pruned early, the practical runtime is far less. Space Complexity: $O(n)$ due to the recursion stack, where n is the number of 3×3 cells given the board's divide size, this space is constant in practice. Solution The solution uses a backtracking approach. For each empty cell on the board, we attempt to place a digit from '1' to '9'. Before placing a digit, we check if the placement is valid by ensuring that: - The digit is not already present in the same row. - The digit is not already present in the same column. - The digit is not already present in the corresponding 3×3 sub-box. If a valid digit is found, we place it on the board and recursively attempt to solve the rest of the board. If no valid digit can be placed, the algorithm backtracks by	reverting the last move and trying a different digit. This recursive search continues until the board is completely filled with a valid Sudoku configuration. #51 N-Queens [Hard] - Backtracking Key Insights - Use backtracking to explore potential positions row by row. - Use sets to track which columns and diagonals are under attack. - Diagonals can be tracked by $(\text{row} - \text{col})$ and $(\text{row} + \text{col})$, ensuring that queens do not conflict along any diagonal. - Recursively build each valid board configuration and backtrack when a conflict arises. Space & Time Time Complexity: $O(n!)$ in the worst-case scenario, as the solution explores permutations for queen placements. Space Complexity: $O(n^2)$ for storing board configurations and $O(n)$ for recursion stack and conflict-tracking sets. Solution We use a backtracking algorithm that places queens row by row. For each row, we try placing a queen in each column. Before placing, we check if the column, main	diagonal (row - col), and anti-diagonal (row + col) are free using dedicated sets. If a queen can be safely placed, we mark the column and diagonals as occupied and recurse to the next row. Once all rows are processed, the board configuration is a valid solution and is added to the result. After that, we backtrack by unmarking the sets and removing the queen from the board. This systematic approach ensures all possible configurations are considered. #126 Word Ladder II [Hard] - Backtracking Key Insights - Use Breadth-First Search (BFS) to traverse level-by-level and capture only the shortest paths. - Build a parent mapping during BFS to record which words lead to each newly discovered word. - Once the shortest path is found via BFS, use backtracking (or DFS) from endWord to reconstruct all transformation sequences. - Remove words that are visited within a level to avoid unnecessary revisits and cycles. - The solution must handle multiple shortest paths, so maintaining a list of predecessors for each word is crucial. Space & Time Time Complexity: $O(N \cdot L \cdot 2^N)$ where N is the number of words in the wordlist and L is the length of each word.	This accounts for checking all possible one-letter transformations. Space Complexity: $O(N \cdot L)$ for storing the parent mapping and maintaining the BFS queue and other auxiliary data structures. Solution We solve the problem in two major phases: - Use BFS to explore from beginWord to endWord. During BFS, record all parents for each word encountered. This ensures we capture all possible predecessors that yield a shortest transformation. - Once the BFS completes (once endWord is reached), use backtracking (DFS) beginning from the endWord and moving backwards via the parent mapping to reconstruct all transformation sequences in reverse. Finally, reverse each sequence to present it from beginWord to endWord. - This two-phase approach guarantees that only the shortest paths are reconstructed, as BFS ensures level-by-level exploration. #996 Number of Squareful Arrays [Hard] - Backtracking Key Insights - The problem requires ensuring adjacent pairs sum up to a perfect square.	- Sorting the array helps in efficiently handling duplicates; when iterating in the backtracking, skip duplicate elements to avoid overcounting. - For each valid candidate, check that the sum with the previous number (if any) is a perfect square. - Use backtracking (DFS) to generate all valid permutations while maintaining a visited flag for each index. - Since the array may contain duplicates, extra care is taken to only use each occurrence in a controlled order (i.e., if two identical numbers exist, only the first unvisited instance can be chosen at a given recursive call). Space & Time Time Complexity: $O(n \cdot 2^n)$ in the worst-case scenario due to exploring all bitmask states with n elements and checking pairwise sums. Space Complexity: $O(n)$ for recursion and $O(n)$ for the visited flag, plus potentially $O(2^n \cdot n)$ for memoization if implemented. Solution The solution uses a backtracking algorithm to explore all permutations. The array is first sorted to handle duplicates. A helper function checks if a number is a perfect square and is used to validate that the sum of every adjacent pair is a perfect square. During DFS, a visited array is maintained to track elements included so	far. Skipping duplicate elements (unless the earlier duplicate was used) is essential to avoid overcounting. This approach ensures that every valid permutation is considered exactly once. Round 7 - Low - Easy
Dynamic Programming Round 7 - Low - Easy - 2 questions	#70 Climbing Stairs EAS LeetCode - Simplexlet - Wallice - LeetCode Math - Dynamic Programming - Memoization Lists: Grid 169 Time Complexity: $O(n)$ Space Complexity: $O(n)$ (can be optimized to $O(1)$ using constant space) Problem You are climbing a staircase. It takes n steps to reach the top. Each time you can either climb 1 or 2 steps. In how many distinct ways can you climb to the top? Example 1: <pre>Input: n = 2 Output: 2 Explanation: There are two ways to climb to the top. 1. 1 step + 1 step 2. 2 steps</pre> Example 2: <pre>Input: n = 3 Output: 3 Explanation: There are three ways to climb to the top. 1. 1 step + 1 step + 1 step 2. 1 step + 2 steps 3. 2 steps + 1 step</pre> Constraints: $1 \leq n \leq 45$ Brute Force (Python) <pre># Brute Force Approach class Solution: def climbStairs(self, n): # Brute Force O(2^n) - pure recursion, # recomputes identical subproblems def climb(n): if n <= 2: return n return climb(n - 1) + climb(n - 2) return climb(n)</pre> Community Solutions (Python) - Wallice	class Solution: <pre>def climbStairs(self, n: int) -> int: dp = [0] * (n + 1) dp[1] = 1 dp[2] = 2 for i in range(3, n + 1): dp[i] = dp[i - 1] + dp[i - 2] return dp[n]</pre> LeetCode <pre>class Solution: def climbStairs(self, n: int) -> int: prev1 = 1 prev2 = 2 for i in range(3, n + 1): dp = prev1 + prev2 prev1 = prev2 prev2 = dp return prev1</pre> Simplexlet <pre>class Solution: def climbStairs(self, n: int) -> int: a, b = 0, 1 for i in range(n): a, b = b, a + b return b</pre>	import numpy as np <pre>class Solution: def climbStairs(self, n: int) -> int: res = np.zeros((1, 2), np.dtype("O")) ap = np.zeros((1, 2), (1, 0)) np.dtype("O") while n: if n <= 1: res = factor factor = factor >>= 1 return res[(0, 0)]</pre> Simplexlet <pre># Define a function to compute the number of ways to climb stairs. def climbStairs(n): # Base case: if there is only one step, return 1. if n == 1: return 1 # Initialize the dp array with n+1 elements. dp = [0] * (n + 1) # There is 1 way to climb 1 step. dp[1] = 1 # There are 2 ways to climb 2 steps.</pre>	$\text{dp}[2] = 2$ - Compute the number of ways for each step from 3 to n. - for i in $\text{range}(n, 1)$: $\text{dp}[i] = \text{dp}[i - 1] + \text{dp}[i - 2]$ # Sum of ways from the previous two steps. - return $\text{dp}[n]$ Example Usage: <pre>print(climbStairs(3)) # Output: 3</pre> LC.ca <pre>class Solution: def climbStairs(self, n: int) -> int: a, b = 0, 1 for i in range(n): a, b = b, a + b return b</pre>	
Dynamic Programming #121 Best Time to Buy and Sell Stock EAS LeetCode - Simplexlet - Wallice - LeetCode Array - Dynamic Programming Lists: Grid 169 Time Complexity: $O(n)$ - requires one pass through the prices array. Space Complexity: $O(1)$ - only a few extra variables are used. Problem You are given an array prices where $\text{prices}[i]$ is the price of a given stock on the ith day. You want to maximize your profit by choosing a single day to buy one stock and choosing a different day in the future to sell that stock. Return the maximum profit you can achieve from this transaction. If you cannot achieve any profit, return 0. Example 1: <pre>Input: prices = [7,1,5,3,4,2] Output: 5 Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6 - 1 = 5. Note that buying on day 2 and selling on day 1 is not allowed because you must buy before you sell.</pre> Example 2: <pre>Input: prices = [7,6,4,3,1] Output: 0 Explanation: In this case, no transactions are done and the max profit = 0.</pre> Constraints: $1 \leq \text{prices.length} \leq 10^5$ $0 \leq \text{prices}[i] \leq 10^4$ Brute Force (Python) <pre># Brute Force Approach class Solution: def maxProfit(self, prices): # Brute Force O(n^2) - try every buy/sell pair n = len(prices) res = 0 for i in range(n): for j in range(i + 1, n): res = max(res, prices[j] - prices[i]) return res</pre> Community Solutions (Python) - Wallice	class Solution: <pre>def maxProfit(self, prices: List[int]) -> int: sellone = 0 min_price = -math.inf for price in prices: sellone = max(sellone, holdone + price) holdone = max(holdone, -price) return sellone</pre> LeetCode <pre>class Solution: def maxProfit(self, prices: List[int]) -> int: ans, mi = 0, inf for v in prices: ans = max(ans, v - mi) mi = min(mi, v) return ans</pre> Simplexlet <pre>def maxProfit(prices): # Initialize min_price as infinity and max_profit as 0 min_price = float('-inf') max_profit = 0 # Iterate through each price in the list for price in prices: # Update the minimum price if current price # is lower if price < min_price: min_price = price else: # Calculate current profit and update max_profit if it is higher max_profit = max(max_profit, price - min_price) return max_profit # Example usage: result = maxProfit([7,1,5,3,4,2]) print(result) # Output should be 5</pre> LC.ca	<pre>... >>> import math >>> max_math = -math.inf >>> inf = math.inf ... >>> a = float('-inf') >>> y = -math.inf >>> print(a - y) # Output: True True ... >>> z = -math.inf >>> z == -math.inf True ... class Solution: def maxProfit(self, prices: List[int]) -> int: ans, mi = 0, inf for v in prices: ans = max(ans, v - mi) mi = min(mi, v) return ans</pre>	<pre>mi = min(mi, v) ans = max(ans, v - mi) return ans ##### class Solution(object): def maxProfit(self, prices): # type: prices: List[int] :rtype: int --- if not prices: return 0 ans = 0 pre = prices[0] for i in range(1, len(prices)): ans = max(prices[i] - pre, ans) pre = prices[i] return ans</pre>		
Bit Manipulation Round 7 - Low - Easy - 6 questions	#67 Add Binary EAS LeetCode - Simplexlet - Wallice - LeetCode Math - String - Bit Manipulation - Simulation Lists: Grid 169 Time Complexity: $O(\max(m, n))$, where m and n are the lengths of the two binary strings. Space Complexity: $O(\max(m, n))$ for storing the resulting binary string. Problem Given two binary strings a and b, return their sum as a binary string. Example 1: <pre>Input: a = "11", b = "1" Output: "100"</pre> Example 2: <pre>Input: a = "1010", b = "1011" Output: "10101"</pre> Constraints: $1 \leq \text{a.length}, \text{b.length} \leq 10^4$ a and b consist only of '0' or '1' characters. - Each string does not contain leading zeros except for the zero itself.	Community Solutions (Python) Wallice <pre>class Solution: def addBinary(self, a: str, b: str) -> str: ans = [] i, j, carry = len(a) - 1, len(b) - 1, 0 while i >= 0 or j >= 0 or carry: carry += int(a[i]) if i >= 0: carry += int(b[j]) ans.append(str(carry % 2)) carry //= 2 i -= 1 j -= 1 return ''.join(reversed(ans))</pre> LeetCode <pre>class Solution: def addBinary(self, a: str, b: str) -> str: ans = [] i, j, carry = len(a) - 1, len(b) - 1, 0 while i >= 0 or j >= 0 or carry: carry += int(a[i]) if i >= 0: carry += int(b[j]) ans.append(str(carry % 2)) carry //= 2 i -= 1 j -= 1 return ''.join(reversed(ans))</pre> Simplexlet <pre># Function to find the single number in the list def singleNumber(nums): # Initialize result to 0; any number XOR 0 is the number itself result = 0 # Iterate through every number in the list for num in nums: # XOR the current result with the current number result ^= num # Return the unique number that did not cancel out return result</pre> Example Usage: <pre>nums = [4, 1, 2, 1, 2] print(singleNumber(nums)) # Output should be 4</pre> LC.ca	class Solution: <pre>def addBinary(a: str, b: str) -> str: ans = [] i, j, carry = len(a) - 1, len(b) - 1, 0 while i >= 0 or j >= 0 or carry: carry += int(a[i]) if i >= 0: carry += int(b[j]) ans.append(str(carry % 2)) carry //= 2 i -= 1 j -= 1 return ''.join(reversed(ans))</pre> LeetCode <pre>class Solution: def addBinary(self, a: str, b: str) -> str: ans = [] i, j, carry = len(a) - 1, len(b) - 1, 0 while i >= 0 or j >= 0 or carry: carry += int(a[i]) if i >= 0: carry += int(b[j]) ans.append(str(carry % 2)) carry //= 2 i -= 1 j -= 1 return ''.join(reversed(ans))</pre> Simplexlet <pre># Function to find the single number in the list def singleNumber(nums): # Initialize result to 0; any number XOR 0 is the number itself result = 0 # Iterate through every number in the list for num in nums: # XOR the current result with the current number result ^= num # Return the unique number that did not cancel out return result</pre> Example Usage: <pre>nums = [4, 1, 2, 1, 2] print(singleNumber(nums)) # Output should be 4</pre> LC.ca	<pre>if i >= 0: # If there is a digit left in total_sum, sum += int(a[i]) # Convert character to integer and add i = i - 1 # Move to the next digit if j >= 0: # If there is a digit left in b total_sum += int(b[j]) # Convert character to integer and add j = j - 1 # Move to the next digit # Append the remainder of total_sum divided by 2 (0 or 1) result.append(str(total_sum // 2)) carry = total_sum // 2 # Update the carry</pre> Reverse the result since we built it backwards and join to form a string <pre>return ''.join(result[::-1])</pre> Simple test cases <pre>print(addBinary("11", "1")) # Expected output: "100" print(addBinary("1010", "1011")) # Expected output: "10101"</pre> LC.ca	<pre>class Solution: def addBinary(self, a: str, b: str) -> str: ans = [] i, j, carry = len(a) - 1, len(b) - 1, 0 while i >= 0 or j >= 0 or carry: carry += int(a[i]) if i >= 0: carry += int(b[j]) ans.append(str(carry % 2)) carry //= 2 i -= 1 j -= 1 return ''.join(reversed(ans))</pre>
Bit Manipulation #136 Single Number EAS LeetCode - Simplexlet - Wallice - LeetCode Array - Bit Manipulation Lists: Grid 169 Time Complexity: $O(n)$ - We only traverse the array once. Space Complexity: $O(1)$ - Only a single extra variable is used regardless of input size. Problem Given a non-empty array of integers, every element appears twice except for one. Find that single one. You must implement a solution with a linear runtime complexity and use only constant extra space. Example 1: <pre>Input: nums = [2,2,1] Output: 1</pre> Example 2: <pre>Input: nums = [4,1,2,2,2] Output: 4</pre> Example 3: <pre>Input: nums = [1] Output: 1</pre>	Constraints: $1 \leq \text{nums.length} \leq 3 \cdot 10^4$ $-3 \cdot 10^4 \leq \text{nums}[i] \leq 3 \cdot 10^4$ - Each element in the array appears twice except for one element which appears only once. Brute Force (Python) <pre># Brute Force Approach class Solution: def singleNumber(self, nums): # Brute Force O(n^2) - for each element, count its occurrences for num in nums: if nums.count(num) == 1: return num</pre> Community Solutions (Python) Wallice <pre>class Solution: def singleNumber(self, nums: List[int]) -> int: return functools.reduce(operator.xor, nums, 0)</pre> LeetCode <pre>class Solution: def singleNumber(self, nums: List[int]) -> int: return reduce(xor, nums, 0)</pre> Simplexlet <pre># Function to find the single number in the list def singleNumber(nums): # Initialize result to 0; any number XOR 0 is the number itself result = 0 # Iterate through every number in the list for num in nums: # XOR the current result with the current number result ^= num # Return the unique number that did not cancel out return result</pre> Example Usage: <pre>nums = [4, 1, 2, 1, 2] print(singleNumber(nums)) # Output should be 4</pre> LC.ca	<pre>... >>> from functools import reduce >>> reduce(lambda x, y: x ^ y, [3, 5, 3]) ... from functools import reduce class Solution: def singleNumber(self, nums: List[int]) -> int: return reduce(lambda x, y: x ^ y, nums) ##### class Solution(object): def singleNumber(self, nums): :type nums: List[int] :rtype: int --- for i in range(1, len(nums)): nums[i] = nums[i] return nums[0]</pre>	Bit Manipulation #190 Reverse Bits EAS LeetCode - Simplexlet - Wallice - LeetCode Divide and Conquer - Bit Manipulation Lists: Grid 169 Time Complexity: $O(1)$ - We always process 32 bits regardless of the input. Space Complexity: $O(1)$ - Only constant extra space is used. Problem Reverse bits of a given 32 bits signed integer. Example 1: <pre>Input: n = 43261596 Output: 964176192 Explanation: Input: 1073748222 Output: 1073748222</pre> Constraints: $0 \leq n < 2^{31} - 1$ n is even. Follow up: If this function is called many times, how would you optimize it?	Community Solutions (Python) Wallice <pre>class Solution: def reverseBits(self, n: int) -> int: ans = 0 for i in range(32): ans = (n >> i) & 1 << (31 - i) return ans</pre> LeetCode <pre>class Solution: def reverseBits(self, n: int) -> int: ans = 0 for i in range(32): ans = (n >> i) & 1 << (31 - i) return ans</pre> Simplexlet <pre>def reverseBits(n): # Initialize result to 0 result = 0 # Iterate through each bit of the input for i in range(32): # Extract the i-th bit of n bit = (n >> i) & 1 # Shift the bit to its new position result = bit << (31 - i) return result</pre>	

Function to reverse bits of a 32-bit binary string.

```
def reverse_bits(s: str) -> int:
    # Reverse the binary string using slicing
    reversed_binary = s[::-1]
    # Convert the reversed binary string to an integer.
    result = int(reversed_binary, 2)
    return result
```

Example usage:

```
binary_input = "000000101001000001101001100"
print(reverse_bits(binary_input)) # Expected output: 964176192
```

LeetCode

class Solution:

```
def reverseBits(self, n: int) -> int:
    res = 0
    for i in range(32):
        res |= (n & 1) << (31 - i)
        n >>= 1
    return res
```

Round 7 · Low · Easy

Bit Manipulation

#191 Number of 1 Bits

LeetCode · SimplexLeet · WalkCC · LeetCode

Divide and Conquer · Bit Manipulation

Lists: Grid 169

Time Complexity: $O(N)$, where n is the number of set bits, worst-case $O(\log n)$ for $O(1)$ considering 32-bit integers. Space Complexity: $O(1)$.

Problem

Given a positive integer n , write a function that returns the number of set bits in its binary representation (also known as the Hamming weight).

Example 1:

```
Input: n = 11
Output: 3
Explanation: The input binary string 1011 has a total of three set bits.
```

Example 2:

```
Input: n = 128
Output: 1
Explanation: The input binary string 10000000 has a total of one set bit.
```

p.2737

Example 3:

```
Input: n = 2147483645
Output: 30
Explanation: The input binary string 11111111111111111111111111111101 has a total of thirty set bits.
```

Constraints:

- $1 \leq n \leq 2^{31} - 1$

Follow up: If this function is called many times, how would you optimize it?

Community Solutions (Python)

• WalkCC

class Solution:

```
def hammingWeight(self, n: int) -> int:
    ans = 0
    for i in range(32):
        res = (n & 1) << i
        ans += 1
    return ans
```

class Solution:

```
def hammingWeight(self, n: int) -> int:
    return n.bit_count()
```

Round 7 · Low · Easy

LeetCode

class Solution:

```
def hammingWeight(self, n: int) -> int:
    ans = 0
    while n:
        ans += n & 1
        n >>= 1
    return ans
```

• SimplexLeet

Function to count the number of set bits in a given integer n

```
def hammingWeight(n: int) -> int:
    count = 0
    # Initialize count of set bits
    while n:
        # Remove the lowest set bit from n
        n &= n - 1
        count += 1 # Increment count for each set bit removed
    return count
```

Example usage:

```
print(hammingWeight(11)) # Output: 3
```

• LC.ca

Round 7 · Low · Easy

class Solution:

```
def hammingWeight(self, n: int) -> int:
    ans = 0
    while n:
        ans += n & 1
        n >>= 1
    return ans
```

Round 7 · Low · Easy

Bit Manipulation

#268 Missing Number

LeetCode · SimplexLeet · WalkCC · LeetCode

Array · Hash Table · Math · Binary Search · Bit Manipulation

Lists: Grid 169

Time Complexity: $O(n)$ Space Complexity: $O(1)$

Problem

Given an array $nums$ containing n distinct numbers in the range $[0, n]$, return the only number in the range that is missing from the array.

Example 1:

```
Input: nums = [0,1]
Output: 2
Explanation:  $n = 3$  since there are 3 numbers, so all numbers are in the range  $[0, 3]$ . 2 is the missing number in the range since it does not appear in  $nums$ .

Example 2:



```
Input: nums = [0,1]
Output: 2
Explanation: $n = 2$ since there are 2 numbers, so all numbers are in the range $[0, 2]$. 2 is the missing number in the range
```


```

Round 7 · Low · Easy

since it does not appear in $nums$.

Example 3:

```
Input: nums = [0,6,4,2,3,5,0,1]
Output: 8
Explanation:  $n = 9$  since there are 9 numbers, so all numbers are in the range  $[0, 9]$ . 8 is the missing number in the range since it does not appear in  $nums$ .

Constraints:



- $n = \text{nums.length}$
- $1 \leq n \leq 10^4$
- $0 \leq \text{nums}[i] \leq n$



All the numbers of  $nums$  are unique.



Follow up: Could you implement a solution using only  $O(1)$  extra space complexity and  $O(n)$  runtime complexity?



Brute Force (Python)



# Brute Force Approach



```
def missingNumber(self, nums):
 # Brute Force $O(n^2)$ - for each $0, n$ check if it's in $nums$
 for i in range(len(nums) + 1):
 if i not in nums:
 return i
```


```

Round 7 · Low · Easy

Community Solutions (Python)

• WalkCC

class Solution:

```
def missingNumber(self, nums: List[int]) -> int:
    ans = len(nums)
    for i, num in enumerate(nums):
        ans ^= i ^ num
    return ans
```

• LeetCode

class Solution:

```
def missingNumber(self, nums: List[int]) -> int:
    return reduce(xor, (i ^ v for i, v in enumerate(nums, 1)))
```

class Solution:

```
def missingNumber(self, nums: List[int]) -> int:
    n = len(nums)
    return (1 + n) * n // 2 - sum(nums)
```

• SimplexLeet

Round 7 · Low · Easy

Function to find the missing number in the array

```
def missingNumber(nums):
    # Calculate n, where n is the length of the nums array
    n = len(nums)
    # Compute the expected total sum using the arithmetic sum formula for numbers 0 to n
    expected_sum = n * (n + 1) // 2
    # Compute the actual sum of the numbers in the array
    actual_sum = sum(nums)
    # The missing number is the difference between expected and actual sum
    return expected_sum - actual_sum
```

Example Usage

```
print(missingNumber([3, 0, 1])) # Output: 2
```

• LC.ca

class Solution:

```
def missingNumber(self, nums: List[int]) -> int:
    return reduce(xor, (i ^ v for i, v in enumerate(nums, 1)))
```

Round 7 · Low · Easy

Bit Manipulation

#338 Counting Bits

LeetCode · SimplexLeet · WalkCC · LeetCode

Dynamic Programming · Bit Manipulation

Lists: Grid 169

Time Complexity: $O(n)$ Space Complexity: $O(n)$

Problem

Given an integer n , return an array ans of length $n + 1$ such that for each $(0 \leq i \leq n)$, $ans[i]$ is the number of 1's in the binary representation of i .

Example 1:

```
Input: n = 2
Output: [0,1,1]
Explanation:
0 -> 0
1 -> 1
2 -> 10
```

Example 2:

```
Input: n = 5
Output: [0,1,1,2,1,2]
Explanation:
0 -> 0
1 -> 1
2 -> 10
3 -> 11
4 -> 100
5 -> 101
```

Round 7 · Low · Easy

Input: $n = 5$

Output: $[0,1,1,2,1,2]$

Explanation:

- $0 \rightarrow 0$
- $1 \rightarrow 1$
- $2 \rightarrow 10$
- $3 \rightarrow 11$
- $4 \rightarrow 100$
- $5 \rightarrow 101$

Constraints:

- $0 \leq n \leq 10^5$

Follow up:

It is very easy to come up with a solution with a runtime of $O(n \log n)$. Can you do it in linear time $O(n)$ and possibly in a single pass?

Can you do it without using any built-in function (i.e., like `builtin_popcount` in C++)?

Brute Force (Python)

Brute Force Approach

```
def countBits(self, n: int) -> List[int]:
    # Brute Force  $O(n^2)$  - iterate all candidates for i in range(2, n + 1)
    # If x is valid, pass
    return 0
```

Community Solutions (Python)

• WalkCC

class Solution:

```
def countBits(self, n: int) -> List[int]:
    # f(i) is i's number of 1s in binary
    # f(i) = f(i // 2) + i % 2
    ans = [0] * (n + 1)
    for i in range(1, n + 1):
        ans[i] = ans[i // 2] + i % 2
    return ans
```

• LeetCode

Round 7 · Low · Easy

Brute Force Approach

class Solution:

```
def countBits(self, n: int) -> List[int]:
    # Brute Force  $O(n^2)$  - iterate all candidates for i in range(2, n + 1)
    # If x is valid, pass
    return 0
```

Community Solutions (Python)

• WalkCC

class Solution:

```
def countBits(self, n: int) -> List[int]:
    # f(i) is i's number of 1s in binary
    # f(i) = f(i // 2) + i % 2
    ans = [0] * (n + 1)
    for i in range(1, n + 1):
        ans[i] = ans[i // 2] + i % 2
    return ans
```

• LeetCode

Round 7 · Low · Easy

class Solution:

```
def countBits(self, n: int) -> List[int]:
    return [i.bit_count() for i in range(n + 1)]
```

class Solution:

```
def countBits(self, n: int) -> List[int]:
    ans = [0] * (n + 1)
    for i in range(1, n + 1):
        ans[i] = ans[i // 2] + i % 2
    return ans
```

• SimplexLeet

```
def countBits(n):
    # Create a list to store the number of 1's for each number from 0 to n
    dp = [0] * (n + 1)
    # Loop over each number starting from 1, since 0 is already 0
    for i in range(1, n + 1):
        # dp[i] is computed as the count for i // 2 plus 1 if i is odd (i & 1)
        dp[i] = dp[i // 2] + (i & 1)
    return dp
```

Example usage:

```
print(countBits(5)) -> [0, 1, 1, 2, 1, 2]
```

• LC.ca

Round 7 · Low · Easy

class Solution:

```
def countBits(self, n: int) -> List[int]:
    ans = [0] * (n + 1)
    for i in range(1, n + 1):
        ans[i] = ans[i // 2] + i % 2
    return ans
```

Round 7 · Low · Easy

Math

Round 7 · Low · Easy · 6 questions

Round 7 · Low · Easy

Math

#9 Palindrome Number

LeetCode · SimplexLeet · WalkCC · LeetCode

Lists: Grid 169

Time Complexity: $O(\log_{10}(n))$ - Each iteration reduces the number by a factor of 10. Space Complexity: $O(1)$ - Only constant extra space is used.

Problem

Given an integer x , return `true` if x is a palindrome, and `false` otherwise.

Example 1:

```
Input: x = 121
Output: true
Explanation: 121 reads as 121 from left to right and from right to left.
```

Example 2:

```
Input: x = -121
Output: false
Explanation: From left to right, it reads -121. From right to left, it becomes 121-. Therefore it is not a palindrome.
```

Example 3:

```
Input: x = 10
Output: false
Explanation: 10 reads as 01 from right to left. Therefore it is not a palindrome.
```

Round 7 · Low · Easy

Input: $x = 10$

Output: `false`

Explanation: Reads 01 from right to left. Therefore it is not a palindrome.

Constraints:

- $-2^{31} \leq x \leq 2^{31} - 1$

Follow up: Could you solve it without converting the integer to a string?

Brute Force (Python)

Brute Force Approach

```
def isPalindrome(self, x):
    # Brute Force - iterate all candidates for i in range(2, n + 1)
    # If x is valid, pass
    return 0
```

Community Solutions (Python)

• WalkCC

Round 7 · Low · Easy

class Solution:

```
def isPalindrome(self, x: int) -> bool:
    if x < 0:
        return False
    rev = 0
    y = x
    while y:
        rev = rev * 10 + y % 10
        y //= 10
    return rev == x
```

• LeetCode

class Solution:

```
def isPalindrome(self, x: int) -> bool:
    if x < 0 or (x % 10 == 0 and x != 0):
        return False
    while y < x:
        y = y * 10 + x % 10
        x //= 10
    return x in (y, y // 10)
```

• SimplexLeet

Round 7 · Low · Easy

Function to check if a number is a palindrome without converting to a string.

```
def isPalindrome(n):
    # Reverse the number and compare with original
    reversed_n = 0
    while n > 0:
        digit = n % 10
        reversed_n = reversed_n * 10 + digit
        n //= 10
    return n == reversed_n
```

Example 1:

```
Input: n = 121
Output: True
```

Example 2:

```
Input: n = 10
Output: False
```

• LC.ca

Round 7 · Low · Easy

class Solution:

```
def isPalindrome(self, x: int) -> bool:
    if x < 0 or (x % 10 == 0 and x != 0):
        return False
    reversed_n = 0
    while n > 0:
        digit = n % 10
        reversed_n = reversed_n * 10 + digit
        n //= 10
    return n == reversed_n
```

Round 7 · Low · Easy

Math

#13 Roman to Integer

LeetCode · SimplexLeet · WalkCC · LeetCode

Hash Table · Math · String

Lists: Grid 169

Time Complexity: $O(n)$, where n is the length of the input string. Space Complexity: $O(1)$, since the mapping and additional variables use constant space.

Problem

Roman numerals are represented by seven different symbols: I, V, X, L, C, D, and M.

Symbol Value

I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two ones added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written from largest to smallest from left to right. However, the numeral for four is not

Round 7 · Low · Easy

III. Instead, the number four is written as IV. Because the one is before the five we subtract 1 making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Example 1:

```
Input: s = "III"
Output: 3
Explanation: III = 3.
```

Example 2:

```
Input: s = "LVIII"
Output: 58
Explanation: L = 50, V = 5, III = 3.
```

Example 3:

```
Input: s = "MCMXCIV"
Output: 1994
Explanation: M = 1000, CM = 900, XC = 90 and IV = 4.
```

Constraints:

- $1 \leq \text{length} \leq 15$

Round 7 · Low · Easy

s contains only the characters ('I', 'V', 'X', 'L', 'C', 'D', 'M').

It is guaranteed that s is a valid roman numeral in the range [1, 3999].

Brute Force (Python)

Brute Force Approach

```
def romanToInt(self, s: str) -> int:
    # Map each Roman numeral to its integer value
    roman_values = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}
    total = 0
    for i in range(1, len(s) + 1):
        if i < len(s) and roman_values[s[i]] < roman_values[s[i + 1]]:
            total -= roman_values[s[i]]
        else:
            total += roman_values[s[i]]
    return total
```

Community Solutions (Python)

• WalkCC

class Solution:

```
def romanToInt(self, s: str) -> int:
    ans = 0
    roman_values = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}
    for i in range(1, len(s) + 1):
        if i < len(s) and roman_values[s[i]] < roman_values[s[i + 1]]:
            ans -= roman_values[s[i]]
        else:
            ans += roman_values[s[i]]
    return ans
```

Round 7 · Low · Easy

ans = roman[s]

return ans + roman[s[1:]]

• LeetCode

class Solution:

```
def romanToInt(self, s: str) -> int:
    # Map each Roman numeral to its integer value
    roman_values = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}
    total = 0
    for i in range(1, len(s) + 1):
        if i < len(s) and roman_values[s[i]] < roman_values[s[i + 1]]:
            total -= roman_values[s[i]]
        else:
            total += roman_values[s[i]]
    return total
```

• SimplexLeet

Round 7 · Low · Easy

If $i + 1 \leq \text{len}(s)$ and $\text{roman_values}[s[i]] < \text{roman_values}[s[i + 1]]$:

```
total -= roman_values[s[i]]
else:
    total += roman_values[s[i]]
return total
```

Example usage:

```
print(romanToInt("MCMXCIV")) # Output: 1994
```

• LC.ca

class Solution:

```
def romanToInt(self, s: str) -> int:
    # Map each Roman numeral to its integer value
    roman_values = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}
    total = 0
    for i in range(1, len(s) + 1):
        if i < len(s) and roman_values[s[i]] < roman_values[s[i + 1]]:
            total -= roman_values[s[i]]
        else:
            total += roman_values[s[i]]
    return total
```

Round 7 · Low · Easy

Math

#504 Base 7

LeetCode · SimplexLeet · WalkCC · LeetCode

Lists: Denny Zhang

Time Complexity: $O(\log_7(n))$, where n is the absolute value of the number. Space Complexity: $O(\log_7(n))$ to store the digits of the number.

Problem

Given an integer num , return a string of its base 7 representation.

Example 1:

```
Input: num = 100
Output: "202"
Explanation: 100 = 2 * 7^2 + 0 * 7^1 + 2 * 7^0 = 202
```

Example 2:

```
Input: num = -7
Output: "-10"
Explanation: -7 = -1 * 7^1 + 0 * 7^0 = -10
```

Constraints:

- $-10^7 \leq \text{num} \leq 10^7$

Brute Force (Python)

Round 7 · Low · Easy

Brute Force Approach

class Solution:

```
def convertToBase7(self, num):
    # Special cases: If num is 0, return "0"
    if num == 0:
        return "0"
    # Work with the absolute value of the number
    n = abs(num)
    digits = []
    while n > 0:
        digit = n % 7
        digits.append(str(digit))
        n //= 7
    # Join the digits in reverse order
    return "".join(digits[::-1])
```

• SimplexLeet

Round 7 · Low · Easy

Python solution for converting an integer to its base 7 string representation.

```
def convertToBase7(self, num):
    # Special cases: If num is 0, return "0"
    if num == 0:
        return "0"
    # Work with the absolute value of the number
    n = abs(num)
    digits = []
    while n > 0:
        digit = n % 7
        digits.append(str(digit))
        n //= 7
    # Join the digits in reverse order
    return "".join(digits[::-1])
```

• SimplexLeet

Round 7 · Low · Easy

Update num by integer division by 7

```
num //= 7
```

Reverse the list to get digits in correct order

```
digits.reverse()
```

If original number was negative, attach the minus sign

```
if num < 0:
    digits.append('-')
    num = -num
```

Example usage:

```
print(convertToBase7(100)) # Expected output: "202"
```

• LC.ca

class Solution:

```
def convertToBase7(self, num: int) -> str:
    if num == 0:
        return "0"
    # Work with the absolute value of the number
    n = abs(num)
    digits = []
    while n > 0:
        digit = n % 7
        digits.append(str(digit))
        n //= 7
    # Join the digits in reverse order
    return "".join(digits[::-1])
```

Round 7 · Low · Easy

Math

#1056 Confusing Number

LeetCode · SimplexLeet · WalkCC · LeetCode

Math

Lists: Premium 98

Time Complexity: $O(d)$, where d is the number of digits in n (approximately $O(\log_{10} n)$). Space Complexity: $O(d)$, needed to store the rotated number string.

Problem

A confusing number is a number that when rotated 180 degrees becomes a different number than each digit valid.

We can rotate digits of a number by 180 degrees to form new digits.

When 0, 1, 6, 8, and 9 are rotated 180 degrees, they become 0, 1, 9, 6, and 8, respectively.

When 2, 3, 4, 5, and 7 are rotated 180 degrees, they become invalid.

Not that after rotating a number, we can ignore leading zeros.

For example, after rotating 8000, we have 0008 which is considered as just 8.

Given an integer n , return `true` if it is a confusing number, or `false` otherwise.

Round 7 · Low · Easy

Example 1:

6 rotate 9

Example 2:

8 rotate 68

Input: $n = 6$

Output: `true`

Explanation: We get 9 after rotating 6, 9 is a valid number, and 9 != 6.

Example 3:

Input: $n = 11$

Output: `false`

Explanation: We get 11 after rotating 11, 11 is a valid number but the value remains the same, thus 11 is not a confusing number.

Constraints:

- $0 \leq n \leq 10^9$

Community Solutions (Python)

• WalkCC

Round 7 · Low · Easy

Input: $n = 89$

Output: `true`

Explanation: We get 68 after rotating 89, 68 is a valid number and 68 != 89.

Example 3:

Input: $n = 11$

Output: `false`

Explanation: We get 11 after rotating 11, 11 is a valid number but the value remains the same, thus 11 is not a confusing number.

Constraints:

- $0 \leq n \leq 10^9$

Community Solutions (Python)

• WalkCC

Round 7 · Low · Easy

class Solution:

```
def confusingNumber(self, n: int) -> bool:
    s = str(n)
    rotated = [''] * len(s)
    for i in range(len(s) - 1, -1, -1):
        digit = s[i]
        if digit in '01689':
            rotated[i] = {'0': '0', '1': '1', '6': '9', '8': '6', '9': '8'}[digit]
        else:
            return False
    return s != "".join(rotated)
```

• LeetCode

class Solution:

```
def confusingNumber(self, n: int) -> bool:
    s = str(n)
    rotated = [''] * len(s)
    for i in range(len(s) - 1, -1, -1):
        digit = s[i]
        if digit in '01689':
            rotated[i] = {'0': '0', '1': '1', '6': '9', '8': '6', '9': '8'}[digit]
        else:
            return False
    return s != "".join(rotated)
```

• SimplexLeet

Round 7 · Low · Easy

Define the mapping for valid rotations

```
def isConfusingNumber(self, n: int) -> bool:
    # Map each digit to its rotated value
    mapping = {'0': '0', '1': '1', '6': '9', '8': '6', '9': '8'}
    # Convert the number to a string to process each digit
    original_str = str(n)
    rotated_str = ""
    # Process each digit in reverse order to simulate 180 degree rotation
    for digit in reversed(original_str):
        if digit not in mapping:
            return False
        rotated_str += mapping[digit]
    # If digit is not valid for rotation, return false immediately
    # If digit is not in rotation_map, return False
    # Append the rotated digit to the rotated string
    rotated_str += mapping[digit]
    # Convert rotated string to an integer (leading zeros are ignored)
    rotated_num = int(rotated_str)
    # The number is confusing if the rotated number is different from the original number
    return original_str != str(rotated_num)
```

Round 7 · Low · Easy

return rotated_num != n

Example usage:

```
print(isConfusingNumber(6)) # Expected output: True
print(isConfusingNumber(11)) # Expected output: False
```

• LC.ca

class Solution:

```
def confusingNumber(self, n: int) -> bool:
    # Map each digit to its rotated value
    mapping = {'0': '0', '1': '1', '6': '9', '8': '6', '9': '8'}
    # Convert the number to a string to process each digit
    original_str = str(n)
    rotated_str = ""
    # Process each digit in reverse order to simulate 180 degree rotation
    for digit in reversed(original_str):
        if digit not in mapping:
            return False
        rotated_str += mapping[digit]
    # If digit is not valid for rotation, return false immediately
    # If digit is not in rotation_map, return False
    # Append the rotated digit to the rotated string
    rotated_str += mapping[digit]
    # Convert rotated string to an integer (leading zeros are ignored)
    rotated_num = int(rotated_str)
    # The number is confusing if the rotated number is different from the original number
    return original_str != str(rotated_num)
```

Round 7 · Low · Easy

Math

#1228 Missing Number in Arithmetic Progression

LeetCode · SimplexLeet · WalkCC · LeetCode

Array · Math

Lists: Premium 98

Time Complexity: $O(n)$ Space Complexity: $O(1)$

Problem

In some array arr , the values were in arithmetic progression: the values $arr[i] - arr[i - 1]$ are all equal for every $0 < i < \text{length}(arr)$.

A value from arr was removed that was not the first or last value in the array.

Given arr , return the removed value.

Example 1:

```
Input: arr = [5,7,11,13]
Output: 9
Explanation: The previous array was [5,7,9,11,13].
```

Example 2:

```
Input: arr = [15,13,12]
Output: 14
Explanation: The previous array was [15,14,13,12].
```

Constraints:

Round 7 · Low · Easy

Share This Easy LeetMastery Study-Order 36-09-2024 14:56:06

Dynamic Programming #53 Maximum Subarray LeetCode - SimplexLeet - LeetCode Array - Dynamic Programming - Divide and Conquer Lists Grid 169 Time Complexity: O(n) Space Complexity: O(1) Problem Given an integer array nums, find the subarray with the largest sum, and return its sum. Example 1: Input: nums = [-2,1,-4,4,-1,2,1,-5,4] Output: 6 Explanation: The subarray [4,-1,2,1] has the largest sum 6. Example 2: Input: nums = [1] Output: 1 Explanation: The subarray [1] has the largest sum 1. Example 3: Input: nums = [5,4,-1,7,8] Output: 23 Explanation: The subarray [5,4,-1,7,8] has the largest sum 23.	Constraints: #1 <= nums.length <= 105 #-104 <= nums[i] <= 104 Follow up: If you have figured out the O(n) solution, try coding another solution using the divide and conquer approach, which is more subtle. Brute Force (Python) # Brute Force Approach class Solution: def maxSubArray(self, nums: List[int]) -> int: # Brute Force O(n^2) - compute sum of every contiguous subarray res = nums[0] for i in range(len(nums)): curr = 0 for j in range(i, len(nums)): curr += nums[j] res = max(res, curr) return res return res Community Solutions (Python) • WalcCC	class Solution: def maxSubArray(self, nums: List[int]) -> int: # dp[i] = the maximum sum subarray ending in i dp = [0] * len(nums) dp[0] = nums[0] for i in range(1, len(nums)): dp[i] = max(nums[i], dp[i-1] + nums[i]) return max(dp) class Solution: def maxSubArray(self, nums: List[int]) -> int: ans = math.inf sum = 0 for num in nums: sum = max(sum, sum + num) ans = max(ans, sum) return ans	from dataclasses import dataclass @dataclass(frozen=True) class T: sum: int # the sum of the subarray starting from the first number maxSubArrayLeft: int # the sum of the subarray ending in the last number maxSubArrayRight: int maxSubArraySum: int class Solution: def maxSubArray(self, nums: List[int]) -> int: def divideAndConquer(l: int, r: int) -> T: if l == r: return T(nums[l], nums[l], nums[l], n = (l + r) // 2 left = divideAndConquer(l, n) right = divideAndConquer(n+1, r) maxSubArraySumLeft = max(left.maxSubArraySumLeft, left.sum + right.maxSubArraySumLeft) maxSubArraySumRight = max(left.maxSubArraySumRight + right.sum, right.maxSubArraySumRight) maxSubArraySum = max(left.maxSubArraySumLeft, right.maxSubArraySumRight, maxSubArraySumLeft + maxSubArraySumRight) return T(sum, maxSubArraySumLeft, maxSubArraySumRight, maxSubArraySum) # LeetCode class Solution: def maxSubArray(self, nums: List[int]) -> int: ans = float('-inf') for i in range(1, len(nums)): f = max(f, 0) + nums[i] ans = max(ans, f) return ans	class Solution: def maxSubArray(self, nums: List[int]) -> int: def crossMaxSub(nums, left, mid, right): lsum = rsum = 0 lmax = rmax = -inf for i in range(mid, left - 1, -1): lsum += nums[i] lmax = max(lmax, lsum) for i in range(mid + 1, right + 1): rsum += nums[i] rmax = max(rmax, rsum) return lmax + rmax def maxSub(nums, left, right): if left == right: return nums[left] mid = (left + right) // 2 lsum = maxSub(nums, left, mid) rsum = maxSub(nums, mid + 1, right) csum = crossMaxSub(nums, left, mid, right) return max(lsum, rsum, csum) # Simplify def maxSubArray(self, nums: List[int]) -> int: ans = float('-inf') for i in range(1, len(nums)): f = max(f, 0) + nums[i] ans = max(ans, f) return ans							
Round 8 · Low · Medium	p.2809	Round 8 · Low · Medium	p.2810	Round 8 · Low · Medium	p.2811	Round 8 · Low · Medium	p.2812	Round 8 · Low · Medium	p.2813	Round 8 · Low · Medium	p.2814

<pre># Python solution using Kadane's Algorithm def maxSubArray(nums): # Initialize currentSum and maxSum to the first element current_sum = max_sum = nums[0] # Traverse through the array starting from the second element for num in nums[1:]: # If current_sum + num is less than num, # restart at num current_sum = max(num, current_sum + num) # Update max_sum if current_sum is greater max_sum = max(max_sum, current_sum) return max_sum # Example usage if __name__ == "__main__": sample = [-2,-1,-3,-4,-1,2,1,-5,-4] print(maxSubArray(sample)) # Output: 6</pre> +LeetCode <pre>class Solution: def maxSubArray(self, nums: List[int]) -> int: res = cur_sum = nums[0] for num in nums[1:]: cur_sum = num + max(cur_sum, 0) res = max(res, cur_sum) return res</pre>	Dynamic Programming #55 Jump Game LeetCode - SimplexLeet - LeetCode Array - Dynamic Programming - Greedy Lists: Grid 169 Time Complexity: O(n) where n is the length of the array. Space Complexity: O(1) Problem You are given an integer array nums. You are initially positioned at the array's first index, and each element in the array represents your maximum jump length at that position. Return true if you can reach the last index, or false otherwise. Example 1: <pre>Input: nums = [2,3,1,1,4] Output: true Explanation: Jump 1 step from index 0 to 1, then 3 steps to the last index.</pre> Example 2: <pre>Input: nums = [3,2,1,0,4] Output: false Explanation: Jump 1 step from index 0 to 1, then 3 steps to the last index.</pre> Community Solutions (Python) • WalCC	<pre>class Solution: def canJump(self, nums: List[int]) -> bool: i = 0 while i < len(nums) and i == reach: reach = max(reach, i + nums[i]) i += 1 return i == len(nums)</pre> +LeetCode <pre>class Solution: def canJump(self, nums: List[int]) -> bool: n = len(nums) for i, x in enumerate(nums): if x < 0: return False return True return True</pre> +Simplify	# Function to determine if you can reach the last index of the array <pre>def canJump(nums): # Initialize maxReach which is the max index reachable at start (index 0) maxReach = 0 # Iterate through each element and its index for i, jump in enumerate(nums): # If current index is greater than maxReach, return False # If i == maxReach, return False # Update maxReach with the maximum of current maxReach and i + jump length at index i maxReach = max(maxReach, i + jump) # If current maxReach is already at or beyond the last index, return True if maxReach == len(nums) - 1: return True # Return True if the end is reachable after processing all indices return True</pre> # Example usage: <pre>print(canJump([2,3,1,1,4])) # Expected output: True print(canJump([3,2,1,0,4])) # Expected output: False</pre>	+LeetCode <pre>class Solution: def canJump(self, nums: List[int]) -> bool: n = len(nums) for i, x in enumerate(nums): if x < 0: return False return True return True</pre> +Simplify							
Round 8 · Low · Medium	p.2815	Round 8 · Low · Medium	p.2816	Round 8 · Low · Medium	p.2817	Round 8 · Low · Medium	p.2818	Round 8 · Low · Medium	p.2819	Round 8 · Low · Medium	p.2820

Dynamic Programming #62 Unique Paths LeetCode - 'Simplex'Leet - LeetCode Math - Dynamic Programming - Combinatorics Lists: Grid 169 Time Complexity: O(m * n) Space Complexity: O(m * n) - can be optimized to O(n) using a 1D DP array. Problem There is a robot on an m x n grid. The robot is initially located at the top-left corner (i.e., grid[0][0]). The robot tries to move to the bottom-right corner (i.e., grid[m-1][n-1]). The robot can only move either down or right at any point in time. Given the two integers m and n, return the number of possible unique paths that the robot can take to reach the bottom-right corner. 1. Right -> Down -> Down 2. Down -> Down -> Right 3. Down -> Right -> Down The test cases are generated so that the answer will be less than or equal to 2^{109}. Example 1:	class Solution: <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> Community Solutions (Python) • WalcCC	class Solution: <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0] = 1 for i in range(1, m): for j in range(1, n): dp[i][j] = dp[i-1][j] + dp[i][j-1] return dp[m-1][n-1]</pre> LeetCode <pre>def uniquePaths(self, m: int, n: int) -> int: dp = [[0] * n for _ in range(m)] dp[0][0]</pre>
---	--	--

Round 8 - Low - Medium	p.2845	Round 8 - Low - Medium	p.2846	Round 8 - Low - Medium	p.2847	Round 8 - Low - Medium	p.2848	Round 8 - Low - Medium	p.2849	Round 8 - Low - Medium	p.2850
------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------

Round 8 · Low · Medium	p.2851	Round 8 · Low · Medium	p.2852	Round 8 · Low · Medium	p.2853	Round 8 · Low · Medium	p.2854	Round 8 · Low · Medium	p.2855	Round 8 · Low · Medium	p.2856
------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------

Round 8 - Low - Medium	p.2857	Round 8 - Low - Medium	p.2858	Round 8 - Low - Medium	p.2859	Round 8 - Low - Medium	p.2860	Round 8 - Low - Medium	p.2861	Round 8 - Low - Medium	p.2862
------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------	------------------------	--------

Round 8 - Low - Medium	a2863	Round 8 - Low - Medium	a2864	Round 8 - Low - Medium	a2865	Round 8 - Low - Medium	a2866	Round 8 - Low - Medium	a2867	Round 8 - Low - Medium	a2868
------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------

Round 2 - Low - Medium	n36C0	Round 2 - Low - Medium	n36T0	Round 2 - Low - Medium	n36T1	Round 2 - Low - Medium	n36T2	Round 2 - Low - Medium	n36T3	Round 2 - Low - Medium	n36T4
------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------

Round 8 • Low • Medium p.2875 Round 8 • Low • Medium p.2876 Round 8 • Low • Medium p.2877 Round 8 • Low • Medium p.2878 Round 8 • Low • Medium p.2879 Round 8 • Low • Medium p.2880

Round 8 · Low · Medium p.2911 Round 8 · Low · Medium p.2912 Sheet 8187 Medium p.2913 36-tp Portrait 8-1/2x6 p.2914 Round 8 · Low · Medium p.2915 Round 8 · Low · Medium p.2916

Sheet 82 of 87 LeetMastery Study-Order #2949 Round 36-up Portrait Low Medium 8x6

Based 0 - Low - Medium	n70C0	Based 0 - Low - Medium	n70C0	Based 0 - Low - Medium	n70C1	Based 0 - Low - Medium	n70C2	Based 0 - Low - Medium	n70C3	Based 0 - Low - Medium	n70C4
------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------	------------------------	-------

Group	Low	Medium	High	Overall
Group A	100	100	100	100
Group B	100	100	100	100
Group C	100	100	100	100
Group D	100	100	100	100
Group E	100	100	100	100
Group F	100	100	100	100
Group G	100	100	100	100
Group H	100	100	100	100
Group I	100	100	100	100
Group J	100	100	100	100
Group K	100	100	100	100
Group L	100	100	100	100
Group M	100	100	100	100
Group N	100	100	100	100
Group O	100	100	100	100
Group P	100	100	100	100
Group Q	100	100	100	100
Group R	100	100	100	100
Group S	100	100	100	100
Group T	100	100	100	100
Group U	100	100	100	100
Group V	100	100	100	100
Group W	100	100	100	100
Group X	100	100	100	100
Group Y	100	100	100	100
Group Z	100	100	100	100

[illegible]

	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
1																					
2																					
3																					
4																					
5																					
6																					
7																					
8																					
9																					
10																					
11																					
12																					
13																					
14																					
15																					
16																					
17																					
18																					
19																					
20																					
21																					
22																					
23																					
24																					
25																					
26																					
27																					
28																					
29																					
30																					
31																					
32																					
33																					

[illegible]

Use a dynamic programming approach by iterating through each house in the array. At each step, we consider two scenarios: either we rob the current house and add its money to the total from two houses ago or we skip it (keeping the optimal solution up to the previous house). By using two variables to store these intermediate results, we achieve an optimized space complexity of O(1). #256 Paint House [Medium] - Dynamic Programming Key Insights - The choice for painting each house depends on the previous house's color choices. - Use dynamic programming to accumulate the cost while ensuring adjacent houses do not have the same color. - The state of each house can be represented by the minimum cost when a house is painted a specific color, computed up to the total from two houses ago or we skip it (keeping the optimal solution up to the previous house). - The problem only requires updating the cost matrix in place for optimal space usage. Space & Time Time Complexity: O(n), where n is the number of houses. Round 8 - Low - Medium p.3025	Space Complexity: O(1) extra space if the input matrix is modified in place. Solution We use a dynamic programming approach with iterative end use of updating of the cost matrix. For each house starting from the second one, we update the cost for each color by adding the minimal cost of painting the previous house with either of the other two colors. This guarantees we never use the same color for adjacent houses while accumulating the minimal total cost. The final answer is the minimum value for the last house. #309 Best Time to Buy and Sell Stock with Cooldown [Medium] - Dynamic Programming Key Insights - Use Dynamic Programming to solve the problem. - Maintain three states to represent: 0: the state where you are ready to buy (not holding any stock). 1: the state where you are holding a stock. 2: the cooldown state encountered right after selling a stock. - Transition between states: - From initial 0 to come from staying in 0 or coming out from the cooldown state 2. Round 8 - Low - Medium p.3026	To enter s1, you either continue holding your stock, or buy a stock using the profit available from s0. - The only way to reach s2 is by selling the stock from s1. - The final answer is determined by the maximum profit when we are not holding a stock (i.e., max(s0, s2)). Space & Time Time Complexity: O(n), where n is the number of days. Space Complexity: O(1), since only a few variables are maintained for the states. Solution The solution involves updating three state variables for each day: - s0 (ready to buy) is updated as the maximum of the previous s0 and the previous cooldown s2 - s1 (holding a stock) is updated as the maximum of the previous s1 or buying today with the profit from s0 minus the current price, - s2 (cooldown) is updated by selling the stock held in s1 (i.e., previous s1 plus the current price). - At the end of the iteration, the maximum profit will be in state s0 (ready to buy) or s2 (cooldown), since remaining in s1 means we are holding a stock, which does not constitute a realized profit. #377 Combination Sum IV [Medium] - Dynamic Programming Key Insights - Transitions are made from a cell to its four adjacent cells. - If the ball moves out of bounds, it contributes to one valid path. - States can be moved out of bounds and contribute to optimize the recursive solution. Space & Time Time Complexity: O(n * m * m), since we compute each state at most once. Space Complexity: O(n * m * m) for the memoization table. Solution We solve this problem using a bottom-up dynamic programming approach. We create a 2D table dp[i][j] such that dp[i][j] stores the longest palindromic subsequence length for the substring s[0..j-1]. For any single character, dp[i][i] is 1. For substrings of length greater than 1, if the characters at positions i and j (s[i] and s[j]) match, then dp[i][j] = dp[i+1][j-1] + 2 (if they do not match, we take the maximum of dp[i+1][j] and dp[i][j-1]). Finally, the dp[0][n-1] holds the result for the entire string. #576 Out of Boundary Paths [Medium] - Dynamic Programming Key Insights - Use Dynamic Programming (DP) as the state is defined by (current row, current column, moves remaining). Round 8 - Low - Medium p.3032	Key Insights - Use dynamic programming to count the number of valid combinations. - The order in which numbers are picked matters, making this a permutation counting. - Initialize a DP table where dp[i] represents the number of ways to reach the sum i. - dp[0] is initialized to 1 since there is one way to form a sum of 0 (choosing nothing). - For each sum i from 1 to target, iterate over nums and update dp[i] based on dp[i - num] when i >= num. - For negative numbers, the problem becomes unbounded (infinite combinations), hence a constraint on the combination length is required to make it well-defined. Space & Time Time Complexity: O(target * n), where n is the length of nums. Space Complexity: O(target), for the array of size target + 1. Solution The problem is solved using a bottom-up dynamic programming approach. We create a DP array where each dp[i] represents the number of possible combinations to reach the sum i. We iterate from sum 1 up to target, and for each sum, we check every number in nums. If the Round 8 - Low - Medium p.3027	number can contribute to the current sum (i - num >= 0), we add the number of ways to form the remainder (i - num) to dp[i]. This ensures that every possible permutation is counted. When negative numbers are allowed in the input, the potential for an infinite number of combinations arises unless we impose additional constraints, such as limiting the length of the combination. #416 Partition Equal Subset Sum [Medium] - Dynamic Programming Key Insights - The total sum of the array must be even, otherwise, partitioning into two equal subsets is impossible. - The problem can be transformed into a "subset sum" problem where we need to check if there exists a subset of numbers that sums to half of the total sum. - A dynamic programming approach can efficiently decide if such a subset exists. Space & Time Time Complexity: O(n * target), where target is half of the total sum. Space Complexity: O(target), using a one-dimensional DP array. Solution Round 8 - Low - Medium p.3029	First, compute the total sum of the array. If the total is odd, return false since an odd sum cannot be equally partitioned. Next, set the target sum to half of the total. Use a dynamic programming array (dp) where dp[i] represents whether a subset with sum i is achievable. Initialize dp[0] as true because a subset sum of 0 is always possible. Then, for each number in the array, iterate through the array backwards from target to the number's value and update dp[i] to true if (dp[i - num]) is true. Ultimately, if dp[target] is true, the array can be partitioned into two subsets with equal sum. #435 Non-overlapping Intervals [Medium] - Dynamic Programming Key Insights - Sorting the array by start times is essential for greedy approach. - Use greedy approach: Always select the interval that ends the earliest, as it leaves maximum room for subsequent intervals. - The answer is the total number of intervals minus the count of intervals selected by this greedy approach. - Edge observation: Intervals that touch at the boundary are not overlapping, so the check uses ">=" instead of ">". Round 9 - Low - Medium p.3039
Space & Time Time Complexity: O(n log n) due to sorting the intervals. Space Complexity: O(1) (if considering the storage for the sorted list or O(n) if sorting in place). Solution The solution involves first sorting the intervals by their end time. Initialize a variable to track the end of the last chosen interval. Iterate through the sorted intervals: if the current interval's start is greater than or equal to the last chosen interval's end, update the last end and include this interval in the non-overlapping set. Otherwise, count the interval as one that must be removed. The final answer is the removal count, which is computed as the total number of intervals minus the count of non-overlapping intervals selected. #516 Longest Palindromic Subsequence [Medium] - Dynamic Programming Key Insights - The problem can be solved efficiently using dynamic programming. - A 2D DP table is used where dp[i][j] represents the length of the longest palindromic subsequence in the substring s[i..j]. - If the characters at the two ends of the substring match (s[i] == s[j]), they contribute to the palindrome Round 8 - Low - Medium p.3031	length. - Otherwise, the solution is the maximum sequence length after either excluding the left or the right character. - The approach builds the solution from smaller substrings (length 1) to the entire string. Space & Time Time Complexity: O(n^2) where n is the length of the string. Space Complexity: O(n^2) due to the usage of a 2D DP table. Solution We solve this problem using a bottom-up dynamic programming approach. We create a 2D table dp[i][j] such that dp[i][j] stores the longest palindromic subsequence length for the substring s[i..j-1]. For any single character, dp[i][i] is 1. For substrings of length greater than 1, if the characters at positions i and j (s[i] and s[j]) match, then dp[i][j] = dp[i+1][j-1] + 2 (if they do not match, we take the maximum of dp[i+1][j] and dp[i][j-1]). Finally, the dp[0][n-1] holds the result for the entire string. #576 Out of Boundary Paths [Medium] - Dynamic Programming Key Insights - Use Dynamic Programming (DP) as the state is defined by (current row, current column, moves remaining). Round 8 - Low - Medium p.3032	• Transitions are made from a cell to its four adjacent cells. - If the ball moves out of bounds, it contributes to one valid path. - States can be moved out of bounds and contribute to optimize the recursive solution. Space & Time Time Complexity: O(n * m * m), since we compute each state at most once. Space Complexity: O(n * m * m) for the memoization table. Solution We solve this problem using a bottom-up dynamic programming approach. We create a 2D table dp[i][j] such that dp[i][j] stores the longest palindromic subsequence length for the substring s[0..j-1]. For any single character, dp[i][i] is 1. For substrings of length greater than 1, if the characters at positions i and j (s[i] and s[j]) match, then dp[i][j] = dp[i+1][j-1] + 2 (if they do not match, we take the maximum of dp[i+1][j] and dp[i][j-1]). Finally, the dp[0][n-1] holds the result for the entire string. #576 Out of Boundary Paths [Medium] - Dynamic Programming Key Insights - Use Dynamic Programming (DP) as the state is defined by (current row, current column, moves remaining). Round 8 - Low - Medium p.3032	Key Insights - The problem is well-suited for a dynamic programming approach. - Use a 2D table where dp[i][j] stores the length of the longest common subsequence for text1[0..i-1] and text2[0..j-1]. - If the characters match at the current position, extend the subsequence by 1 from dp[i-1][j-1]; otherwise, take the maximum from dp[i-1][j] or dp[i][j-1]. - Filling the table in a bottom-up manner ensures that all subproblems are solved optimally. Space & Time Time Complexity: O(m * n), where m and n are the lengths of text1 and text2. Space Complexity: O(m * n) for maintaining the 2D DP table. Space can be optimized to O(min(m, n)) if needed. Solution The solution uses a dynamic programming approach with a 2D array dp to record the lengths of common subsequences at each substring pair. We initialize our dp array with zeros or null. We iterate over m and n are the lengths of text1 and text2. We iterate over both strings, comparing characters; if they match, we set dp[i][j] = dp[i-1][j-1] + 1, otherwise we choose the maximum from dp[i-1][j] and dp[i][j-1]. The final answer is found at dp[m][n]. Round 8 - Low - Medium p.3034	It works: - If n is negative, switch to 1/x and n to -n. Initialize the result as 1. Loop while n is greater than 0: If n is odd, multiply the result by x. Square the base. Divide n by 2 (using integer division). This iterative approach efficiently computes the power in logarithmic time. This approach can be implemented recursively. #380 Insert Delete GetRandom O(1) [Medium] - Math Key Insights - Use a dynamic array (or list) to store the elements to allow O(1) access by index. - Use a hash table (or dictionary) map to store the mapping from value to its index in the array. - For removal, swap the element to be removed with the last element in the array, then delete the last element. This avoids expensive shifting of elements. - getRandom can be implemented by generating a random index inside the array. Space & Time Time Complexity: O(1) on average for insert, remove, and getRandom operations. Space Complexity: O(n) where n is the number of elements stored in the data structure. Round 8 - Low - Medium p.3041	Solution The solution involves maintaining a list to store the values and a hash map to quickly check for the presence of a value and to know its index in the list. When an element is removed, swap it with the last element of the list and remove it map accordingly; then, remove the last element in O(1) time. This approach ensures that insert, remove, and getRandom can all be achieved in constant time on average. #1017 Convert to Base -2 [Medium] - Math Key Insights - Use division and remainder operations to simulate long division with a number and -2. - When working with a negative base (-2), the remainder can become negative; adjust the remainder by adding the base's

