

LeetMastery

DSA Reference - Print Edition

73 cards · 12 template categories · 4 tutorial sections

Table of Contents

Part 1 — DSA Templates

Binary Search (2 cards)

- Upper Middle (even → take upper)
- Lower Middle (even → take lower)

Bit Manipulation (5 cards)

- Sum of Submasks (SOS DP)
- Sum of Supermasks
- Largest Bit Set
- Lowest Bit Set
- Enumerate All Submasks of a Mask

Euler Path (1 cards)

- Hierholzer's Algorithm

Fenwick Tree (BIT) (1 cards)

- Binary Indexed Tree — 1-indexed

Graph Theory (9 cards)

- Preorder Traversal
- Inorder Traversal
- Postorder Traversal
- BFS (Breadth First Search)
- Bellman-Ford Algorithm
- Dijkstra's Algorithm
- Topological Sort (BFS)
- Kahn's Algorithm
- Disjoint Set Union (DSU / Union-Find)

Linked List (1 cards)

- Floyd's Fast & Slow Pointer

Manacher's Algorithm (1 cards)

- Palindromic Substrings — All Centers

Ordered Set (PBDS) (1 cards)

- GNU C++ Policy-Based Ordered Set

Prefix & Suffix Sum (4 cards)

- Prefix Sum (starts at index 0)
- Prefix Sum (1-indexed, starts at 0)
- Suffix Sum (starts at last index)
- Suffix Sum (1-indexed, starts at 0)

Segment Tree (1 cards)

- Segment Tree — Range Sum + Point Update

Sparse Table (1 cards)

- Sparse Table — $O(1)$ Range Queries

Two Pointers (1 cards)

- Two Pointers — Converging

Part 2 — Tutorials

Basic Topics

- Arrays (1)
- Backtracking (1)
- Binary Search (1)
- Brute Force (1)
- Greedy (1)
- Hash Map (1)
- Heap / Priority Queue (1)
- Kadane's Algorithm (1)
- Linear Search (1)
- Linked List (1)
- MOD ($1e9 + 7$) (1)
- Prefix Sum (1)
- Queue & Stack (2)
- Sliding Window (2)
- Sorting (4)
- Time Complexity (1)
- Trie (1)
- Two Pointers (1)

Graph Theory

- Tree Traversals (1)
- BFS (1)
- DFS (1)
- Bellman-Ford (1)
- Dijkstra's (1)
- DSU (1)
- Topological Sort (1)
- Binary Search Tree (1)
- Kruskal's MST (1)
- Tarjan's Algorithm (1)
- LCA (1)

Math

- Bit Manipulation (2)
- Combinatorics (1)
- Matrix Exponentiation (1)
- Number Theory (2)
- Prime Factors (2)

Strings

- Manacher's Algorithm (1)
- Palindrome (1)
- Z Algorithm (1)

Part 1 — DSA Templates

Binary Search · 2 cards

Upper Middle (even → take upper)

For even-length arrays, takes the upper middle element.

```
C++
int search(vector<int>& nums, int target) {
    int n = nums.size(), l = 0, r = n - 1;
    while (l < r) {
        // for even number of elements, take the upper one
        int m = l + (r - l + 1) / 2;
        if (target < nums[m]) r = m - 1;
        else l = m;
    }
    return nums[l] == target ? l : -1;
}
```

```
Java
int search(int[] nums, int target) {
    int n = nums.length, l = 0, r = n - 1;
    while (l < r) {
        // for even number of elements, take the upper one
        int m = l + (r - l + 1) / 2;
        if (target < nums[m]) r = m - 1;
        else l = m;
    }
    return nums[l] == target ? l : -1;
}
```

Lower Middle (even → take lower)

For even-length arrays, takes the lower middle element.

```
C++
int search(vector<int>& nums, int target) {
    int n = nums.size(), l = 0, r = n - 1;
    while (l < r) {
        // for even number of elements, take the lower one
        int m = l + (r - l) / 2;
        if (target > nums[m]) l = m + 1;
        else r = m;
    }
    return nums[l] == target ? l : -1;
}
```

Java

```
int search(int[] nums, int target) {  
    int n = nums.length, l = 0, r = n - 1;  
    while (l < r) {  
        // for even number of elements, take the lower one  
        int m = l + (r - l) / 2;  
        if (target > nums[m]) l = m + 1;  
        else r = m;  
    }  
    return nums[l] == target ? l : -1;  
}
```

Bit Manipulation · 5 cards

Sum of Submasks (SOS DP)

```
C++
template<typename T_out, typename T_in>
vector<T_out> submask_sums(int n, const vector<T_in> &values) {
    assert(int(values.size()) == 1 << n);
    vector<T_out> dp(values.begin(), values.end());
    for (int i = 0; i < n; i++)
        for (int base = 0; base < 1 << n; base += 1 << (i + 1))
            for (int mask = base; mask < base + (1 << i); mask++)
                dp[mask + (1 << i)] += dp[mask];
    return dp;
}
```

Sum of Supermasks

```
C++
template<typename T_out, typename T_in>
vector<T_out> supermask_sums(int n, vector<T_in> values) {
    reverse(values.begin(), values.end());
    vector<T_out> result = submask_sums<T_out>(n, values);
    reverse(result.begin(), result.end());
    return result;
}
```

Largest Bit Set

```
C++
int largest_bit(int x) {
    return x == 0 ? -1 : 31 - __builtin_clz(x);
}
```

Lowest Bit Set

```
C++
int lowest_bit(int x) {
    return x & (-x);
}

// Index of lowest bit (1-based)
int lowest_bit_index(int x) {
    return __builtin_ffs(x);
}
```

Enumerate All Submasks of a Mask

```
C++  
for (int s = m; s; s = (s - 1) & m) {  
    // use s  
}
```


Euler Path · 1 card

Hierholzer's Algorithm

Finds Euler path/circuit in a directed graph. Used in Reconstruct Itinerary (LC 332).

```
C++
void euler(unordered_map<string, queue<string>>& g,
          string src, vector<string>& ans) {
    while (!g[src].empty()) {
        string nxt = g[src].front();
        g[src].pop();
        euler(g, nxt, ans);
    }
    ans.push_back(src);
}

// Usage (LC 332 - Reconstruct Itinerary)
vector<string> findItinerary(vector<vector<string>>& tickets) {
    vector<string> ans;
    sort(tickets.begin(), tickets.end(),
        [](const vector<string>& x, const vector<string>& y) {
            return x[1] < y[1];
        });
    unordered_map<string, queue<string>> g;
    for (auto x : tickets) g[x[0]].push(x[1]);
    euler(g, "JFK", ans);
    reverse(ans.begin(), ans.end());
    return ans;
}
```

Fenwick Tree (BIT) · 1 card

Binary Indexed Tree — 1-indexed

Supports point update and range sum query in $O(\log n)$. Also supports range update via difference array trick.

```
C++
template <class T>
struct BIT { // 1-indexed
    int n;
    vector<T> t;

    BIT() {}
    BIT(int _n) { n = _n; t.assign(n + 1, 0); }

    T query(int i) {
        T ans = 0;
        for (; i >= 1; i -= (i & -i)) ans += t[i];
        return ans;
    }

    void upd(int i, T val) {
        if (i <= 0) return;
        for (; i <= n; i += (i & -i)) t[i] += val;
    }

    // Range update [l, r]
    void upd(int l, int r, T val) {
        upd(l, val);
        upd(r + 1, -val);
    }

    // Range query [l, r]
    T query(int l, int r) {
        return query(r) - query(l - 1);
    }
};
// BIT<int> bit(n);
```

Graph Theory · 9 cards

Preorder Traversal

Visit root → left → right.

```
C++
void preorder(TreeNode* node) {
    if (node == NULL) return;
    // process node->val here
    preorder(node->left);
    preorder(node->right);
}
```

```
Python
def preorder(node):
    if node is None: return
    # process node.val here
    preorder(node.left)
    preorder(node.right)
```

Inorder Traversal

Visit left → root → right. Gives sorted order for BSTs.

```
C++
void inorder(TreeNode* node) {
    if (node == NULL) return;
    inorder(node->left);
    // process node->val here
    inorder(node->right);
}
```

```
Python
def inorder(node):
    if node is None: return
    inorder(node.left)
    # process node.val here
    inorder(node.right)
```

Postorder Traversal

Visit left → right → root.

```
C++
void postorder(TreeNode* node) {
    if (node == NULL) return;
    postorder(node->left);
    postorder(node->right);
    // process node->val here
}
```

Python

```
def postorder(node):
    if node is None: return
    postorder(node.left)
    postorder(node.right)
    # process node.val here
```

BFS (Breadth First Search)

Explore all closest nodes first before going deeper.

Python

```
def bfs(root, targetValue):
    if root is None: return None
    currentLevel = [root]
    while len(currentLevel) > 0:
        nextLevel = []
        for node in currentLevel:
            if node is None: continue
            if node.val == targetValue: return node
            nextLevel.append(node.left)
            nextLevel.append(node.right)
        currentLevel = nextLevel
    return None
```

Bellman–Ford Algorithm

Shortest paths from single source. Handles negative weights.

C++

```
template<typename T_a3, typename T_vector>
void bellman_ford(T_a3 &g, T_vector &dist, int src, int mx_edges) {
    dist[src] = 0;
    for (int i = 0; i <= mx_edges; i++) {
        T_vector ndist = dist;
        for (auto x : g) {
            auto [from, to, cost] = x;
            ndist[to] = min(ndist[to], dist[from] + cost);
        }
        dist = ndist;
    }
}
```

Dijkstra's Algorithm

Shortest paths from single source. Non-negative weights only.

```

C++
template<typename T_pair, typename T_vector>
void dijkstra(T_pair &g, T_vector &dist, int start) {
    priority_queue<pair<int,int>, vector<pair<int,int>>,
        greater<pair<int,int>>> pq;
    dist[start] = 0;
    pq.push({start, 0});
    while (!pq.empty()) {
        auto [u_node, u_cost] = pq.top(); pq.pop();
        if (u_cost > dist[u_node]) continue;
        for (auto [v_node, v_cost] : g[u_node]) {
            if (dist[v_node] > dist[u_node] + v_cost) {
                dist[v_node] = dist[u_node] + v_cost;
                pq.push({v_node, dist[v_node]});
            }
        }
    }
}

```

Topological Sort (BFS)

Linear ordering of vertices in a DAG.

```

C++
struct TopologicalSort {
    int n, steps = 0, nodes = 0;
    vector<int> indegree, orders;
    vector<vector<int>> G;
    bool isTopologicalSorted = false;

    TopologicalSort(vector<vector<int>>& g, vector<int>& in) {
        G = g; n = G.size(); indegree = in;
        queue<int> q;
        for (int i = 0; i < n; i++)
            if (indegree[i] == 0) q.push(i);
        while (!q.empty()) {
            int sz = q.size();
            steps++; nodes += sz;
            for (int i = 0; i < sz; i++) {
                auto u = q.front(); q.pop();
                orders.push_back(u);
                for (auto v : G[u])
                    if (--indegree[v] == 0) q.push(v);
            }
        }
        isTopologicalSorted = nodes == n;
    }
};

```

Kahn's Algorithm

Alternative topological sort. Returns empty if cycle detected.

```

C++
template<typename T_vector, typename T_vector_vector>
T_vector kahn(int n, T_vector_vector &edges) {
    vector<int> ordering, indegree(n, 0);
    vector<vector<int>> g(n);
    for (auto e : edges) {
        --e[0]; --e[1];
        indegree[e[1]]++;
        g[e[0]].push_back(e[1]);
    }
    queue<int> q;
    for (int i = 0; i < n; i++)
        if (indegree[i] == 0) q.push(i);
    int visited = 0;
    while (!q.empty()) {
        int u = q.front(); q.pop();
        ordering.push_back(u);
        visited++;
        for (auto v : g[u])
            if (--indegree[v] == 0) q.push(v);
    }
    if (visited != n) return T_vector{};
    reverse(ordering.begin(), ordering.end());
    return ordering;
}

```

Disjoint Set Union (DSU / Union-Find)

Combines sets and checks connectivity in near $O(1)$ per operation.

```

C++
class dsu {
public:
    vector<int> root, rank;
    int n, cnt;

    dsu(int _n) : n(_n) {
        root.resize(n); rank.resize(n);
        for (int i = 0; i < n; i++) { root[i] = i; rank[i] = 1; }
        cnt = n;
    }

    int getCount() { return cnt; }

    int get(int x) {
        return x == root[x] ? x : (root[x] = get(root[x]));
    }

    bool unite(int x, int y) {
        x = get(x); y = get(y);
        if (x == y) return false;
        if (rank[x] > rank[y]) root[y] = x;
        else if (rank[x] < rank[y]) root[x] = y;
        else { root[y] = x; rank[x]++; }
        cnt--;
        return true;
    }
};

```

Linked List · 1 card

Floyd's Fast & Slow Pointer

Detects cycles and finds midpoints in linked lists.

```
C++
ListNode* slow = head;
ListNode* fast = head;
while (fast != nullptr && fast->next != nullptr) {
    // do something here
    slow = slow->next;
    fast = fast->next->next;
}
```

```
Java
ListNode slow = head, fast = head;
while (fast != null && fast.next != null) {
    // do something here
    slow = slow.next;
    fast = fast.next.next;
}
```


Manacher's Algorithm · 1 card

Palindromic Substrings — All Centers

Finds all palindromic substrings in $O(n)$. Converts even/odd cases by inserting # separators.

Python

```
def palindromicSubstrings(s: str) -> list[str]:
    if not s: return []
    # Insert # to handle even-length palindromes
    string = "#".join(s)
    pLengths = [0] * len(string)
    c = R = 0
    for i in range(len(string)):
        if i < R:
            pLengths[i] = min(R - i, pLengths[2 * c - i])
            while (i - pLengths[i] - 1 >= 0 and
                  i + pLengths[i] + 1 < len(string) and
                  string[i + pLengths[i] + 1] == string[i - pLengths[i] - 1]):
                pLengths[i] += 1
            if pLengths[i] + i > R:
                c, R = i, i + pLengths[i]
    result = []
    for i, p in enumerate(pLengths):
        s = string[i - p:i + p + 1].replace("#", "")
        if s: result.append(s)
    return result
```

C++

```
vector<string> palindromicSubstrings(string s) {
    if (s.empty()) return {};
    string str = "";
    for (int i = 0; i < (int)s.length() - 1; i++) {
        str += s[i]; str += "#";
    }
    str += s.back();
    int len = str.length();
    vector<int> pL(len, 0);
    int c = 0, R = 0;
    for (int i = 0; i < len; i++) {
        if (i < R) pL[i] = min(R - i, pL[2 * c - i]);
        while (i - pL[i] - 1 >= 0 && i + pL[i] + 1 < len &&
              str[i + pL[i] + 1] == str[i - pL[i] - 1])
            pL[i]++;
        if (pL[i] + i > R) { c = i; R = i + pL[i]; }
    }
    vector<string> res;
    for (int i = 0; i < len; i++) {
        string p = str.substr(i - pL[i], 2 * pL[i] + 1);
        string r = "";
        for (char ch : p) if (ch != '#') r += ch;
        res.push_back(r);
    }
    return res;
}
```

Ordered Set (PBDS) · 1 card

GNU C++ Policy-Based Ordered Set

$O(\log n)$ rank queries: $\text{order_of_key}(k) = \# \text{ elements} < k$, $\text{find_by_order}(k) = k\text{-th element}$.

```
C++
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

// less<int> → ascending order set
// greater<int> → descending order set
// less_equal<int> → allows duplicates (multiset)
tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update> oset;

void usage() {
    oset.insert(5);
    // # elements strictly less than k
    int rank = oset.order_of_key(5);
    // k-th element (0-indexed)
    auto it = oset.find_by_order(0);
}
```

Prefix & Suffix Sum · 4 cards

Prefix Sum (starts at index 0)

$\text{pref}[i]$ = sum of $a[0..i]$

```
C++
vector<int> pref(n);
pref[0] = a[0];
for (int i = 1; i < n; i++)
    pref[i] = pref[i - 1] + a[i];

// Query sum [l, r]:
// l == 0 ? pref[r] : pref[r] - pref[l - 1]
```

Prefix Sum (1-indexed, starts at 0)

$\text{pref}[i+1]$ = sum of $a[0..i]$. Clean range queries.

```
C++
vector<int> pref(n + 1, 0);
for (int i = 0; i < n; i++)
    pref[i + 1] = pref[i] + a[i];

// Query sum [l, r] (0-indexed):
// pref[r + 1] - pref[l]
```

Suffix Sum (starts at last index)

$\text{suff}[i]$ = sum of $a[i..n-1]$

```
C++
vector<int> suff(n);
suff[n - 1] = a[n - 1];
for (int i = n - 2; i >= 0; i--)
    suff[i] = suff[i + 1] + a[i];
```

Suffix Sum (1-indexed, starts at 0)

$\text{suff}[i]$ = sum of $a[i..n-1]$ with extra 0 at end.

```
C++
vector<int> suff(n + 1, 0);
for (int i = n - 1; i >= 0; i--)
    suff[i] = suff[i + 1] + a[i];

// Query sum [l, r] (0-indexed):
// suff[l] - suff[r + 1]
```

Segment Tree · 1 card

Segment Tree — Range Sum + Point Update

$O(\log n)$ point update and range sum query.

```
C++
struct segtree {
    vector<long long> sums;
    int size;

    void init(int n) {
        size = 1;
        while (size < n) size *= 2;
        sums.assign(size * 2, 0LL);
    }

    void set(int i, int v, int x, int lx, int rx) {
        if (rx - lx == 1) { sums[x] = v; return; }
        int m = (lx + rx) / 2;
        if (i < m) set(i, v, 2*x+1, lx, m);
        else      set(i, v, 2*x+2, m, rx);
        sums[x] = sums[2*x+1] + sums[2*x+2];
    }

    void set(int i, int v) { set(i, v, 0, 0, size); }

    long long sum(int l, int r, int x, int lx, int rx) {
        if (lx >= r || l >= rx) return 0;
        if (lx >= l && rx <= r) return sums[x];
        int m = (lx + rx) / 2;
        return sum(l, r, 2*x+1, lx, m) + sum(l, r, 2*x+2, m, rx);
    }

    long long sum(int l, int r) { return sum(l, r, 0, 0, size); }
} st;

// Usage:
// st.init(n);
// st.set(i, val);           // point update
// st.sum(l, r + 1);         // range sum [l, r] (exclusive r)
```

Sparse Table · 1 card

Sparse Table — $O(1)$ Range Queries

Static arrays only (no updates). Ideal for range min/max/gcd in $O(1)$ after $O(n \log n)$ build.

```
C++
template<typename it, typename bin_op>
struct sparse_table {
    using T = typename remove_reference<decltype(*declval<it>())>::type;
    vector<vector<T>> t;
    bin_op f;

    sparse_table(it first, it last, bin_op op) : t(1), f(op) {
        int n = distance(first, last);
        t.assign(32 - __builtin_clz(n), vector<T>(n));
        t[0].assign(first, last);
        for (int i = 1; i < (int)t.size(); i++)
            for (int j = 0; j < n - (1 << i) + 1; j++)
                t[i][j] = f(t[i-1][j], t[i-1][j + (1 << (i-1))]);
    }

    //  $O(1)$  range query  $f(a[l..r])$ 
    T query(int l, int r) {
        int h = floor(log2(r - l + 1));
        return f(t[h][l], t[h][r - (1 << h) + 1]);
    }
};

// Usage - range GCD:
// sparse_table g(a.begin(), a.end(), [](int x, int y){ return gcd(x, y); });
// g.query(l, r);
```

Two Pointers · 1 card

Two Pointers — Converging

l and r start at opposite ends and move toward each other.

```
C++
int f(vector<int>& v) {
    int ans = 0;
    int l = 0, r = (int)v.size() - 1;
    while (l < r) {
        // logic here
        if (/* condition */) l++;
        else r--;
    }
    return ans;
}
```

```
Java
int f(int[] v) {
    int ans = 0;
    int l = 0, r = v.length - 1;
    while (l < r) {
        // logic here
        if (/* condition */) l++;
        else r--;
    }
    return ans;
}
```

Part 2 — Tutorials

Basic Topics

Arrays · 1 card

Array Operations & Complexity

Arrays store collections in contiguous memory. Support $O(1)$ access by index but $O(n)$ insertion/deletion at arbitrary positions.

Access $O(1)$ · Insert/Delete middle $O(n)$ · Append $O(1)$ amortized

```
C++
// Sort ascending
sort(v.begin(), v.end());
// Sort descending
sort(v.begin(), v.end(), greater<int>());
// Custom comparator
sort(v.begin(), v.end(), [](const auto& a, const auto& b) {
    return a[0] != b[0] ? a[0] < b[0] : a[1] < b[1];
});
// Max / min / sum
int mx = *max_element(v.begin(), v.end());
int mn = *min_element(v.begin(), v.end());
int s = accumulate(v.begin(), v.end(), 0);
```

```
Python
# Sort ascending / descending
arr.sort()
arr.sort(reverse=True)
arr.sort(key=lambda x: x[1]) # by second element

# Max / min / sum
mx = max(arr)
mn = min(arr)
s = sum(arr)
```

Backtracking · 1 card

Backtracking Template

Explores all possible solutions by building candidates incrementally and abandoning ("backtracking") invalid paths. Uses DFS recursion.

Time $O(n!)$ worst case · Space $O(n)$ recursion depth


```

C++
vector<vector<int>>> ans;
vector<int> tmp;

void backtrack(vector<int>& nums, vector<bool>& used) {
    // Base case: solution complete
    if (tmp.size() == nums.size()) {
        ans.push_back(tmp);
        return;
    }
    for (int i = 0; i < nums.size(); i++) {
        if (used[i]) continue;
        // Choose
        used[i] = true;
        tmp.push_back(nums[i]);
        // Explore
        backtrack(nums, used);
        // Un-choose (backtrack)
        tmp.pop_back();
        used[i] = false;
    }
}

// LC 46: Permutations
vector<vector<int>>> permute(vector<int>& nums) {
    vector<bool> used(nums.size(), false);
    backtrack(nums, used);
    return ans;
}

```

```

Python
def permute(nums):
    ans, tmp = [], []
    used = [False] * len(nums)

    def backtrack():
        if len(tmp) == len(nums):
            ans.append(tmp[:])
            return
        for i in range(len(nums)):
            if used[i]: continue
            used[i] = True
            tmp.append(nums[i])
            backtrack()
            tmp.pop()
            used[i] = False

    backtrack()
    return ans

```

Binary Search · 1 card

Standard Binary Search

Efficiently locates elements in a sorted array by halving the search space each iteration. Requires sorted input.

Time $O(\log n)$ · Space $O(1)$

```
C++
int binarySearch(vector<int>& nums, int target) {
    int lp = 0, rp = nums.size() - 1;
    while (lp <= rp) {
        int mid = lp + (rp - lp) / 2; // avoids overflow
        if (nums[mid] == target) return mid;
        else if (nums[mid] < target) lp = mid + 1;
        else rp = mid - 1;
    }
    return -1;
}
```

```
Python
def binarySearch(nums, target):
    lp, rp = 0, len(nums) - 1
    while lp <= rp:
        mid = (lp + rp) // 2
        if nums[mid] == target: return mid
        elif nums[mid] < target: lp = mid + 1
        else: rp = mid - 1
    return -1
```

```
Java
int binarySearch(int[] nums, int target) {
    int lp = 0, rp = nums.length - 1;
    while (lp <= rp) {
        int mid = lp + (rp - lp) / 2;
        if (nums[mid] == target) return mid;
        else if (nums[mid] < target) lp = mid + 1;
        else rp = mid - 1;
    }
    return -1;
}
```

Brute Force · 1 card

Brute Force — Nested Loops

Try every possible combination without optimization. Use as a baseline before optimizing. $O(n^2)$ or worse.

Time $O(n^2)$ typical · Space $O(1)$

```

C++
// Count pairs with difference == k
int countPairs(vector<int>& nums, int k) {
    int count = 0;
    for (int i = 0; i < nums.size(); i++)
        for (int j = i + 1; j < nums.size(); j++)
            if (abs(nums[i] - nums[j]) == k)
                count++;
    return count;
}

// Running sum (brute force  $O(n^2)$  - optimize with prefix sum)
vector<int> runningSum(vector<int>& nums) {
    int n = nums.size();
    vector<int> ans(n);
    for (int i = 0; i < n; i++) {
        int sum = 0;
        for (int j = 0; j <= i; j++) sum += nums[j];
        ans[i] = sum;
    }
    return ans;
}

```

Greedy · 1 card

Greedy — Locally Optimal Choices

Makes the best immediate choice at each step hoping to reach the global optimum. Simple but not always optimal.

Usually $O(n \log n)$ with sorting · Space $O(1)$

```

C++
// LC 455: Assign Cookies
// Strategy: match smallest sufficient cookie to least greedy child
int findContentChildren(vector<int>& g, vector<int>& s) {
    sort(s.begin(), s.end());
    sort(g.begin(), g.end());
    int ans = 0;
    for (int j = 0; j < s.size() && ans < g.size(); j++)
        if (g[ans] <= s[j]) ans++;
    return ans;
}

// LC 605: Can Place Flowers
bool canPlaceFlowers(vector<int>& bed, int n) {
    int count = 0, sz = bed.size();
    for (int i = 0; i < sz && count < n; i++) {
        if (bed[i] == 0 &&
            (i == 0 || bed[i-1] == 0) &&
            (i == sz-1 || bed[i+1] == 0)) {
            bed[i] = 1;
            count++;
        }
    }
    return count >= n;
}

```

Hash Map · 1 card

Hash Map — $O(1)$ Lookup

Maps keys to values using a hash function. Enables $O(1)$ average insert/lookup vs $O(n)$ linear search.

Time $O(1)$ avg · Space $O(n)$

```

C++
// LC 1: Two Sum —  $O(n)$  with hash map
vector<int> twoSum(vector<int>& nums, int target) {
    unordered_map<int, int> mp; // value -> index
    for (int i = 0; i < nums.size(); i++) {
        int complement = target - nums[i];
        if (mp.count(complement))
            return {mp[complement], i};
        mp[nums[i]] = i;
    }
    return {};
}

// Frequency count
unordered_map<int, int> freq;
for (int x : nums) freq[x]++;
// Check if exists
if (freq.count(key)) { /* exists */ }
// Iterate
for (auto& [k, v] : freq) { /* use k, v */ }

```

```

Python
# Two Sum
def twoSum(nums, target):
    seen = {} # value -> index
    for i, num in enumerate(nums):
        if target - num in seen:
            return [seen[target - num], i]
        seen[num] = i
    return []

# Frequency count
from collections import Counter
freq = Counter(nums)
freq['a'] # 0 if not present (defaultdict behavior)

```

Heap / Priority Queue · 1 card

Min/Max Heap Operations

Efficiently retrieves minimum (or maximum) element in $O(\log n)$. Python `heapq` is min-heap; negate for max-heap. C++ `priority_queue` is max-heap by default.

Push/Pop $O(\log n)$ · Peek $O(1)$

```

Python
import heapq

# Min-heap
heap = []
heapq.heappush(heap, 3)
heapq.heappush(heap, 1)
smallest = heapq.heappop(heap) # 1

# Max-heap (negate values)
max_heap = []
heapq.heappush(max_heap, -10)
heapq.heappush(max_heap, -7)
largest = -heapq.heappop(max_heap) # 10

# Heapify in-place  $O(n)$ 
heapq.heapify(arr)

```

```

C++
// Max-heap (default)
priority_queue<int> max_pq;
max_pq.push(3);
int top = max_pq.top(); // 3
max_pq.pop();

// Min-heap
priority_queue<int, vector<int>, greater<int>> min_pq;

// Min-heap of pairs {cost, node}
priority_queue<pair<int,int>,
               vector<pair<int,int>>,
               greater<>> pq;
pq.push({cost, node});
auto [c, n] = pq.top(); pq.pop();

```

Kadane's Algorithm · 1 card

Maximum Subarray Sum

Finds the maximum sum of a contiguous subarray in $O(n)$. Resets the running sum to 0 whenever it goes negative.

Time $O(n)$ · Space $O(1)$

```

C++
// LC 53: Maximum Subarray
int maxSubArray(vector<int>& nums) {
    int globalSum = INT_MIN, localSum = 0;
    for (int x : nums) {
        localSum += x;
        globalSum = max(globalSum, localSum);
        if (localSum < 0) localSum = 0;
    }
    return globalSum;
}

```

```

Python
def maxSubArray(nums):
    global_sum = float('-inf')
    local_sum = 0
    for x in nums:
        local_sum += x
        global_sum = max(global_sum, local_sum)
        if local_sum < 0:
            local_sum = 0
    return global_sum

```

Linear Search · 1 card

Linear Search

Traverses every element checking against the target. Simplest search — no sorting required. $O(n)$ worst case.

Best $O(1)$ · Average/Worst $O(n)$

```
C++
// Generic linear search
int linearSearch(vector<int>& nums, int target) {
    for (int i = 0; i < nums.size(); i++)
        if (nums[i] == target) return i;
    return -1;
}

// LC 1295: Find Numbers with Even Digits
int findNumbers(vector<int>& nums) {
    int ans = 0;
    for (int x : nums) {
        int len = log10(x) + 1;
        if (len % 2 == 0) ans++;
    }
    return ans;
}
```

Linked List · 1 card

Linked List — Insert / Delete / Search

Nodes connected by next pointers. $O(1)$ insert/delete at head but $O(n)$ to access arbitrary elements.

Lookup $O(n)$ · Insert/Delete head $O(1)$ · Insert/Delete tail $O(n)$

```

C++
struct ListNode {
    int val; ListNode* next;
    ListNode(int x) : val(x), next(nullptr) {}
};

// Insert at head
ListNode* insertHead(ListNode* head, int val) {
    ListNode* node = new ListNode(val);
    node->next = head;
    return node;
}

// Delete head
ListNode* deleteHead(ListNode* head) {
    if (!head) return nullptr;
    ListNode* tmp = head;
    head = head->next;
    delete tmp;
    return head;
}

// Floyd's cycle detection / find mid
ListNode* findMid(ListNode* head) {
    ListNode* slow = head, *fast = head;
    while (fast && fast->next) {
        slow = slow->next;
        fast = fast->next->next;
    }
    return slow;
}

```

MOD (1e9 + 7) · 1 card

Modular Arithmetic

Apply % at each step to prevent overflow. 1e9+7 is prime, enabling modular inverse via Fermat's Little Theorem.

O(1) per operation · O(log n) for modular inverse


```

C++
const int MOD = 1e9 + 7;

// Correct: apply mod each step
long long factorial(int n) {
    long long fact = 1;
    for (int i = 2; i <= n; i++)
        fact = (fact * i) % MOD;
    return fact;
}

// Modular properties:
// (a + b) % m = (a%m + b%m) % m
// (a * b) % m = (a%m * b%m) % m
// (a - b) % m = (a%m - b%m + m) % m ← +m to avoid negatives

// Modular inverse (m must be prime): a^(m-2) mod m
long long power(long long base, long long exp, long long mod) {
    long long res = 1;
    base %= mod;
    while (exp > 0) {
        if (exp & 1) res = res * base % mod;
        base = base * base % mod;
        exp >>= 1;
    }
    return res;
}

long long modInverse(long long a) { return power(a, MOD - 2, MOD); }

```

Prefix Sum · 1 card

Prefix Sum — O(1) Range Queries

Pre-computes cumulative sums to answer range sum queries in O(1) after O(n) build.

Build O(n) · Query O(1) · Space O(n)

```

C++
// Build prefix sum (0-indexed, padded)
vector<int> buildPrefix(vector<int>& a) {
    int n = a.size();
    vector<int> pref(n + 1, 0);
    for (int i = 0; i < n; i++)
        pref[i + 1] = pref[i] + a[i];
    return pref;
}
// Range sum [l, r] (0-indexed):
// pref[r + 1] - pref[l]

// LC 303: Range Sum Query
class NumArray {
    vector<int> pref;
public:
    NumArray(vector<int>& nums) {
        pref.resize(nums.size() + 1, 0);
        for (int i = 0; i < nums.size(); i++)
            pref[i+1] = pref[i] + nums[i];
    }
    int sumRange(int l, int r) { return pref[r+1] - pref[l]; }
};

```

Queue & Stack · 2 cards

Stack — LIFO

Last In First Out. Use for matching brackets, monotonic problems, undo operations.

Push/Pop $O(1)$

```

Python
# LC 20: Valid Parentheses
def isValid(s: str) -> bool:
    stack = []
    pairs = {'(': ')', '[': ']', '{': '}' }
    for c in s:
        if c in "([{":
            stack.append(c)
        elif not stack or stack[-1] != pairs[c]:
            return False
        else:
            stack.pop()
    return len(stack) == 0

```

```

C++
// Stack operations
stack<int> st;
st.push(1); st.push(2);
int top = st.top(); st.pop();
bool empty = st.empty();

```

Queue — FIFO

First In First Out. Use for BFS, level-order traversal, sliding window problems.

Push/Pop $O(1)$

```
Python
from collections import deque
queue = deque()
queue.appendleft(1) # enqueue front
queue.appendleft(2)
val = queue.pop() # dequeue back
```

```
C++
// Queue operations
queue<int> q;
q.push(1); q.push(2);
int front = q.front(); q.pop();
bool empty = q.empty();

// Deque (double-ended)
deque<int> dq;
dq.push_front(1); dq.push_back(2);
dq.pop_front(); dq.pop_back();
```

Sliding Window · 2 cards

Sliding Window — Fixed Size

Maintains a window of fixed size k , sliding one element at a time. Avoids recomputing from scratch each step.

Time $O(n)$ · Space $O(1)$

```
C++
// Maximum sum of subarray of size k
int maxSumSubarray(vector<int>& nums, int k) {
    int windowSum = 0, maxSum = 0;
    for (int i = 0; i < k; i++) windowSum += nums[i];
    maxSum = windowSum;
    for (int i = k; i < nums.size(); i++) {
        windowSum += nums[i] - nums[i - k];
        maxSum = max(maxSum, windowSum);
    }
    return maxSum;
}
```

Sliding Window — Variable Size

Expands right pointer and shrinks left pointer based on a condition. Common for longest/shortest subarray problems.

Time $O(n)$ · Space $O(k)$ with hash map

```

C++
// Longest substring without repeating characters
int lengthOfLongestSubstring(string s) {
    unordered_map<char, int> last;
    int ans = 0, l = 0;
    for (int r = 0; r < s.size(); r++) {
        if (last.count(s[r]) && last[s[r]] >= l)
            l = last[s[r]] + 1;
        last[s[r]] = r;
        ans = max(ans, r - l + 1);
    }
    return ans;
}

```

```

Python
def lengthOfLongestSubstring(s: str) -> int:
    last = {}
    ans = l = 0
    for r, c in enumerate(s):
        if c in last and last[c] >= l:
            l = last[c] + 1
        last[c] = r
        ans = max(ans, r - l + 1)
    return ans

```

Sorting · 4 cards

Built-in Sort — Usage & Comparators

C++ `std::sort` is introsort ($O(n \log n)$). Python `sort` is Timsort (stable). Custom comparators allow multi-key sorting.

Time $O(n \log n)$ · Space $O(\log n)$

```

C++
// Sort ascending
sort(v.begin(), v.end());
// Descending
sort(v.begin(), v.end(), greater<int>());
// Custom: multi-key
sort(v.begin(), v.end(), [](const array<int,3>& x, const array<int,3>& y){
    return x[0] != y[0] ? x[0] < y[0] :
           x[1] != y[1] ? x[1] < y[1] : x[2] < y[2];
});

```

Bubble Sort

Repeatedly swaps adjacent out-of-order elements. Early termination with a flag. Simple but $O(n^2)$.

Time $O(n^2)$ · Space $O(1)$

```

C++
void bubbleSort(vector<int>& arr) {
    int n = arr.size();
    bool swapped = true;
    for (int i = 0; i < n - 1 && swapped; i++) {
        swapped = false;
        for (int j = 0; j < n - i - 1; j++) {
            if (arr[j] > arr[j+1]) {
                swap(arr[j], arr[j+1]);
                swapped = true;
            }
        }
    }
}

```

Merge Sort

Divide array in half, recursively sort each half, merge. Stable, $O(n \log n)$ all cases.

Time $O(n \log n)$ all cases · Space $O(n)$

```

C++
void merge(vector<int>& a, int l, int m, int r) {
    vector<int> L(a.begin()+l, a.begin()+m+1);
    vector<int> R(a.begin()+m+1, a.begin()+r+1);
    int i=0, j=0, k=l;
    while (i<L.size() && j<R.size())
        a[k++] = (L[i]<=R[j]) ? L[i++] : R[j++];
    while (i<L.size()) a[k++] = L[i++];
    while (j<R.size()) a[k++] = R[j++];
}
void mergeSort(vector<int>& a, int l, int r) {
    if (l >= r) return;
    int m = l + (r-l)/2;
    mergeSort(a, l, m);
    mergeSort(a, m+1, r);
    merge(a, l, m, r);
}

```

Tim Sort

Hybrid of insertion sort + merge sort. Used in Python `sort()` and Java `Arrays.sort()`. Splits into runs of size 32, sorts each with insertion sort, then merges.

Time $O(n \log n)$ · Space $O(1)$

```

C++
const int RUN = 32;

void insertionSort(vector<int>& nums, int l, int r) {
    for (int i = l+1; i <= r; i++) {
        int tmp = nums[i], j = i-1;
        while (j >= l && nums[j] > tmp) { nums[j+1]=nums[j]; j--; }
        nums[j+1] = tmp;
    }
}

void timMerge(vector<int>& nums, int l, int m, int r) {
    vector<int> L(nums.begin()+l, nums.begin()+m+1);
    vector<int> R(nums.begin()+m+1, nums.begin()+r+1);
    int i=0, j=0, k=l;
    while (i<L.size() && j<R.size()) nums[k++]=(L[i]<=R[j])?L[i++]:R[j++];
    while (i<L.size()) nums[k++]=L[i++];
    while (j<R.size()) nums[k++]=R[j++];
}

void timSort(vector<int>& nums) {
    int n = nums.size();
    for (int i=0; i<n; i+=RUN)
        insertionSort(nums, i, min(i+RUN-1, n-1));
    for (int sz=RUN; sz<n; sz*=2)
        for (int l=0; l<n; l+=2*sz) {
            int m=l+sz-1, r=min(l+2*sz-1, n-1);
            if (m<r) timMerge(nums, l, m, r);
        }
}

```

Time Complexity · 1 card

Input Size → Required Complexity

Use input size n to determine which algorithm complexity is fast enough. LeetCode typical time limit is $\sim 10^8$ operations/sec.

Reference

$n \leq 10$	→ $O(n!)$, $O(n^7)$, $O(n^6)$
$n \leq 20$	→ $O(2^n)$
$n \leq 80$	→ $O(n^4)$
$n \leq 400$	→ $O(n^3)$
$n \leq 7,500$	→ $O(n^2)$
$n \leq 10^6$	→ $O(n \log n)$, $O(n)$
$n > 10^6$	→ $O(\log n)$, $O(1)$

// Loop complexities:

$O(n)$	– single loop
$O(n*m)$	– nested loops
$O(\sqrt{n})$	– loop: $i*i \leq n$
$O(\log n)$	– halving each step (binary search)
$O(n \log n)$	– sort + single loop

Trie · 1 card

Trie — Insert / Search / StartsWith

Prefix tree for string storage and retrieval. Each node has 26 children (a-z) and an end-of-word flag.
 $O(m)$ per operation where m = word length.

Time $O(m)$ per op · Space $O(26 \times n \times m)$

```
C++
struct TrieNode {
    TrieNode* children[26];
    bool isEnd;
    TrieNode() : isEnd(false) {
        fill(children, children+26, nullptr);
    }
};

class Trie {
    TrieNode* root;
public:
    Trie() { root = new TrieNode(); }

    void insert(string word) {
        TrieNode* cur = root;
        for (char c : word) {
            int i = c - 'a';
            if (!cur->children[i])
                cur->children[i] = new TrieNode();
            cur = cur->children[i];
        }
        cur->isEnd = true;
    }

    bool search(string word) {
        TrieNode* cur = root;
        for (char c : word) {
            int i = c - 'a';
            if (!cur->children[i]) return false;
            cur = cur->children[i];
        }
        return cur->isEnd;
    }

    bool startsWith(string prefix) {
        TrieNode* cur = root;
        for (char c : prefix) {
            int i = c - 'a';
            if (!cur->children[i]) return false;
            cur = cur->children[i];
        }
        return true;
    }
};
```

Two Pointers · 1 card

Two Pointers — Converging

Start one pointer at each end, move inward based on condition. Common for sorted arrays.

Time $O(n)$ · Space $O(1)$

```
C++
// LC 977: Squares of Sorted Array
vector<int> sortedSquares(vector<int>& nums) {
    int l = 0, r = nums.size() - 1;
    vector<int> res;
    while (l <= r) {
        if (abs(nums[l]) > abs(nums[r])) {
            res.push_back(nums[l]*nums[l]); l++;
        } else {
            res.push_back(nums[r]*nums[r]); r--;
        }
    }
    reverse(res.begin(), res.end());
    return res;
}
```

```
Python
def sortedSquares(nums):
    l, r = 0, len(nums) - 1
    res = []
    while l <= r:
        if abs(nums[l]) > abs(nums[r]):
            res.append(nums[l]**2); l += 1
        else:
            res.append(nums[r]**2); r -= 1
    return res[::-1]
```


Graph Theory

Tree Traversals · 1 card

Preorder / Inorder / Postorder

Three DFS traversal orders. Preorder: Root→L→R. Inorder: L→Root→R (sorted for BST). Postorder: L→R→Root.

```
C++
void preorder(TreeNode* node) {
    if (!node) return;
    // process node->val
    preorder(node->left);
    preorder(node->right);
}

void inorder(TreeNode* node) {
    if (!node) return;
    inorder(node->left);
    // process node->val
    inorder(node->right);
}

void postorder(TreeNode* node) {
    if (!node) return;
    postorder(node->left);
    postorder(node->right);
    // process node->val
}
```

```
Python
def preorder(node):
    if not node: return
    # process node.val
    preorder(node.left); preorder(node.right)

def inorder(node):
    if not node: return
    inorder(node.left)
    # process node.val
    inorder(node.right)

def postorder(node):
    if not node: return
    postorder(node.left); postorder(node.right)
    # process node.val
```

BFS · 1 card

Breadth-First Search

Explores all nodes at current depth before going deeper. Uses a queue. Guarantees shortest path in unweighted graphs.

Time $O(V+E)$ · Space $O(V)$

Python

```
def bfs(root, target):
    if not root: return None
    level = [root]
    while level:
        next_level = []
        for node in level:
            if not node: continue
            if node.val == target: return node
            next_level.append(node.left)
            next_level.append(node.right)
        level = next_level
    return None
```

C++

```
// BFS on graph
vector<int> bfs(vector<vector<int>>& adj, int src, int n) {
    vector<int> dist(n, -1);
    queue<int> q;
    dist[src] = 0; q.push(src);
    while (!q.empty()) {
        int u = q.front(); q.pop();
        for (int v : adj[u]) {
            if (dist[v] == -1) {
                dist[v] = dist[u] + 1;
                q.push(v);
            }
        }
    }
    return dist;
}
```

DFS · 1 card

Depth-First Search

Explores one branch completely before backtracking. Uses recursion (implicit stack). Great for path finding, cycle detection, connected components.

Time $O(V+E)$ · Space $O(V)$

Python

```
def dfs(node):
    if not node: return 0
    left = dfs(node.left)
    right = dfs(node.right)
    return max(left, right) + 1 # max depth example
```

```

C++
// DFS on graph with visited set
void dfs(vector<vector<int>>& adj, vector<bool>& vis, int u) {
    vis[u] = true;
    // process u
    for (int v : adj[u])
        if (!vis[v]) dfs(adj, vis, v);
}

```

Bellman-Ford · 1 card

Bellman-Ford Algorithm

Shortest paths from single source. Handles negative weights. Runs $|V|-1$ relaxation passes over all edges.
 Time $O(V \times E)$ · Space $O(V)$

```

C++
template<typename T_a3, typename T_vector>
void bellman_ford(T_a3& g, T_vector& dist, int src, int mx_edges) {
    dist[src] = 0;
    for (int i = 0; i <= mx_edges; i++) {
        T_vector ndist = dist;
        for (auto x : g) {
            auto [from, to, cost] = x;
            ndist[to] = min(ndist[to], dist[from] + cost);
        }
        dist = ndist;
    }
}

```

```

Python
def bellman_ford(g, dist, src, mx_edges):
    dist[src] = 0
    for _ in range(mx_edges + 1):
        ndist = dist[:]
        for frm, to, cost in g:
            ndist[to] = min(ndist[to], dist[frm] + cost)
        dist = ndist
    return dist

```

Dijkstra's · 1 card

Dijkstra's Algorithm

Shortest paths from single source. Non-negative weights only. Uses min-heap priority queue.
 Time $O((V+E) \log V)$ · Space $O(V)$

```

C++
template<typename T_pair, typename T_vector>
void dijkstra(T_pair& g, T_vector& dist, int start) {
    priority_queue<pair<int,int>, vector<pair<int,int>>, greater<>> pq;
    dist[start] = 0;
    pq.push({0, start});
    while (!pq.empty()) {
        auto [u_cost, u] = pq.top(); pq.pop();
        if (u_cost > dist[u]) continue;
        for (auto [v, w] : g[u]) {
            if (dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                pq.push({dist[v], v});
            }
        }
    }
}

```

DSU · 1 card

Disjoint Set Union (Union-Find)

Tracks connected components. Two operations: Find (get root) and Union (merge sets). Path compression + union by rank gives near $O(1)$ per op.

$O(\alpha(n)) \approx O(1)$ per op with optimizations

```

C++
class DSU {
public:
    vector<int> root, rank_;
    int cnt;
    DSU(int n) : root(n), rank_(n, 1), cnt(n) {
        iota(root.begin(), root.end(), 0);
    }
    int find(int x) {
        return x == root[x] ? x : root[x] = find(root[x]);
    }
    bool unite(int x, int y) {
        x = find(x); y = find(y);
        if (x == y) return false;
        if (rank_[x] < rank_[y]) swap(x, y);
        root[y] = x;
        if (rank_[x] == rank_[y]) rank_[x]++;
        cnt--;
        return true;
    }
    bool connected(int x, int y) { return find(x) == find(y); }
};

```

Topological Sort · 1 card

Topological Sort (Kahn's BFS)

Linear ordering of a DAG where u comes before v for every edge (u,v) . Detects cycles if not all nodes are processed.

Time $O(V+E)$ · Space $O(V)$

```
C++
struct TopologicalSort {
    vector<int> orders;
    bool isSorted = false;
    int steps = 0;

    TopologicalSort(vector<vector<int>>& g, vector<int>& indegree) {
        int n = g.size(), nodes = 0;
        queue<int> q;
        for (int i = 0; i < n; i++)
            if (indegree[i] == 0) q.push(i);
        while (!q.empty()) {
            int sz = q.size(); steps++;
            nodes += sz;
            for (int i = 0; i < sz; i++) {
                int u = q.front(); q.pop();
                orders.push_back(u);
                for (int v : g[u])
                    if (--indegree[v] == 0) q.push(v);
            }
        }
        isSorted = nodes == n;
    }
};

// LC 207: Course Schedule
bool canFinish(int n, vector<vector<int>>& pre) {
    vector<vector<int>> g(n); vector<int> ind(n);
    for (auto& p : pre) { g[p[1]].push_back(p[0]); ind[p[0]]++; }
    TopologicalSort ts(g, ind);
    return ts.isSorted;
}
```

Binary Search Tree · 1 card

BST — Insert / Delete / Search

Left subtree < node < right subtree. All ops $O(n)$ worst case (unbalanced), $O(\log n)$ average.

Time $O(n)$ worst · $O(\log n)$ balanced

```

C++
TreeNode* insert(TreeNode* root, int key) {
    if (!root) return new TreeNode(key);
    if (key < root->val) root->left = insert(root->left, key);
    else root->right = insert(root->right, key);
    return root;
}

TreeNode* search(TreeNode* root, int key) {
    if (!root || root->val == key) return root;
    return key < root->val ? search(root->left, key)
        : search(root->right, key);
}

TreeNode* deleteNode(TreeNode* root, int key) {
    if (!root) return nullptr;
    if (key < root->val) root->left = deleteNode(root->left, key);
    else if (key > root->val) root->right = deleteNode(root->right, key);
    else {
        if (!root->left) return root->right;
        if (!root->right) return root->left;
        TreeNode* succ = root->right;
        while (succ->left) succ = succ->left;
        root->val = succ->val;
        root->right = deleteNode(root->right, succ->val);
    }
    return root;
}

```

Kruskal's MST · 1 card

Kruskal's Algorithm — Minimum Spanning Tree

Greedy MST: sort edges by weight, add edge if it doesn't form a cycle (using DSU). $O(E \log E)$.

Time $O(E \log E)$ · Space $O(V)$

```

C++
int kruskalMST(int n, vector<array<int,3>>& edges) {
    // edges: {weight, u, v}
    sort(edges.begin(), edges.end());
    DSU dsu(n);
    int total = 0;
    for (auto& [w, u, v] : edges)
        if (dsu.unite(u, v)) total += w;
    return total;
}

```

Tarjan's Algorithm · 1 card

Tarjan's — SCCs & Bridges

Finds Strongly Connected Components in $O(V+E)$. Also used to find bridges ($low[v] > tin[u]$) and articulation points.

Time $O(V+E)$ · Space $O(V)$

```
C++
struct Tarjan {
    int timer = 0;
    vector<int> tin, low;
    vector<bool> onStack;
    stack<int> stk;
    vector<vector<int>> sccs;

    void dfs(int u, vector<vector<int>>& g) {
        tin[u] = low[u] = timer++;
        stk.push(u); onStack[u] = true;
        for (int v : g[u]) {
            if (tin[v] == -1) { dfs(v, g); low[u] = min(low[u], low[v]); }
            else if (onStack[v]) low[u] = min(low[u], tin[v]);
        }
        if (low[u] == tin[u]) { // root of SCC
            vector<int> scc;
            while (stk.top() != u) {
                int v = stk.top(); stk.pop();
                onStack[v] = false; scc.push_back(v);
            }
            stk.pop(); onStack[u] = false; scc.push_back(u);
            sccs.push_back(scc);
        }
    }

    vector<vector<int>> run(int n, vector<vector<int>>& g) {
        tin.assign(n,-1); low.assign(n,-1); onStack.assign(n,false);
        for (int u = 0; u < n; u++) if (tin[u] == -1) dfs(u, g);
        return sccs;
    }
};
```

LCA · 1 card

Lowest Common Ancestor

Deepest node that has both x and y as descendants. $\text{dist}(x,y) = \text{depth}(x) + \text{depth}(y) - 2 \cdot \text{depth}(\text{LCA})$.

Time $O(n)$ · Space $O(n)$

```
C++
// LC 236: LCA of Binary Tree
TreeNode* lowestCommonAncestor(TreeNode* root, TreeNode* p, TreeNode* q) {
    if (!root || root == p || root == q) return root;
    TreeNode* left = lowestCommonAncestor(root->left, p, q);
    TreeNode* right = lowestCommonAncestor(root->right, p, q);
    if (left && right) return root; // p and q on opposite sides
    return left ? left : right;
}
```

Math

Bit Manipulation · 2 cards

Bit Operations Cheat Sheet

Direct binary manipulation. All operations $O(1)$. Essential for subset enumeration and optimization.

```
C++
// Common bit tricks
n & (n-1)      // remove lowest set bit (isPowerOfTwo: n>0 && !(n&(n-1)))
n & (-n)       // isolate lowest set bit
n | (1<<i)     // set bit i
n & ~(1<<i)    // clear bit i
(n >> i) & 1   // get bit i
n ^ n = 0     // XOR with self cancels
n ^ 0 = n     // XOR with 0 unchanged
__builtin_popcount(n) // count set bits
__builtin_ctz(n)     // count trailing zeros
31 - __builtin_clz(n) // index of highest set bit

// Enumerate all submasks of mask m:
for (int s = m; s; s = (s-1) & m) { /* use s */ }

// Subsets (bit masking):
for (int mask = 0; mask < (1<<n); mask++)
    for (int j = 0; j < n; j++)
        if ((mask>>j)&1) { /* j is in subset */ }
```

Bit Manipulation — Common Problems

XOR to find single number, Hamming weight, missing number, subsets.

```
C++
// Single Number (LC 136) – XOR cancels pairs
int singleNumber(vector<int>& nums) {
    int ans = 0;
    for (int x : nums) ans ^= x;
    return ans;
}

// Hamming Weight (LC 191)
int hammingWeight(uint32_t n) {
    int ans = 0;
    for (; n; n &= n-1) ans++; // remove lowest set bit each time
    return ans;
}

// Missing Number (LC 268)
int missingNumber(vector<int>& nums) {
    int n = nums.size(), ans = n;
    for (int i = 0; i < n; i++) ans ^= i ^ nums[i];
    return ans;
}
```


Combinatorics · 1 card

Combinatorics — nCr with Modular Inverse

$C(n,r) = n! / (r!(n-r)!)$. Use modular inverse for large values. Pascal's Triangle gives $C(n,r) = C(n-1,r) + C(n-1,r-1)$.

Precompute $O(n)$ · Query $O(1)$

```
C++
struct Comb {
    int mod;
    vector<long long> fact, inv_fact;

    Comb(int N, int mod = 1e9+7) : mod(mod), fact(N+1), inv_fact(N+1) {
        fact[0] = 1;
        for (int i = 1; i <= N; i++) fact[i] = fact[i-1] * i % mod;
        inv_fact[N] = power(fact[N], mod-2);
        for (int i = N-1; i >= 0; i--) inv_fact[i] = inv_fact[i+1] * (i+1) % mod;
    }

    long long power(long long a, long long b) {
        long long res = 1; a %= mod;
        for (; b > 0; b >>= 1, a = a*a%mod)
            if (b&1) res = res*a%mod;
        return res;
    }

    long long nCr(int n, int r) {
        if (r < 0 || r > n) return 0;
        return fact[n] % mod * inv_fact[r] % mod * inv_fact[n-r] % mod;
    }
};
// Comb c(1000000); c.nCr(100, 5);
```

Matrix Exponentiation · 1 card

Matrix Exponentiation — $O(\log n)$ Recurrences

Compute linear recurrences (e.g., Fibonacci) in $O(k^3 \log n)$ by using binary exponentiation on the transformation matrix.

Time $O(k^3 \log n)$ · Space $O(k^2)$

```

C++
const int MOD = 1e9+7;
using Mat = vector<vector<long long>>;

Mat multiply(const Mat& A, const Mat& B) {
    int n = A.size();
    Mat C(n, vector<long long>(n, 0));
    for (int i = 0; i < n; i++)
        for (int k = 0; k < n; k++) if (A[i][k])
            for (int j = 0; j < n; j++)
                C[i][j] = (C[i][j] + A[i][k] * B[k][j]) % MOD;
    return C;
}

Mat matpow(Mat A, long long p) {
    int n = A.size();
    Mat res(n, vector<long long>(n, 0));
    for (int i = 0; i < n; i++) res[i][i] = 1; // identity
    for (; p > 0; p >= 1, A = multiply(A, A))
        if (p & 1) res = multiply(res, A);
    return res;
}

// Fibonacci in O(log n)
long long fib(int n) {
    Mat T = {{1,1},{1,0}};
    Mat A = {{1},{0}};
    return multiply(matpow(T, n), A)[1][0];
}

```

Number Theory · 2 cards

Binary Exponentiation — $O(\log n)$ Powers

Efficiently computes a^n in $O(\log n)$ using the binary representation of the exponent. Each step squares the base and halves the exponent.

Time $O(\log n)$ · Space $O(1)$

```

C++
// Basic – computes base^exp
long long fastpow(long long base, long long exp) {
    long long res = 1;
    while (exp > 0) {
        if (exp & 1) res *= base;
        base *= base;
        exp >>= 1;
    }
    return res;
}

// With modulo – prevents overflow in modular arithmetic
long long modpow(long long base, long long exp, long long mod) {
    base %= mod;
    long long res = 1;
    while (exp > 0) {
        if (exp & 1) res = (res * base) % mod;
        base = (base * base) % mod;
        exp >>= 1;
    }
    return res;
}

// e.g., 3^13 mod 1e9+7
// modpow(3, 13, 1e9+7)

```

Sieve of Eratosthenes — All Primes $\leq N$

Finds all prime numbers up to N . Iteratively marks multiples of each prime as composite. Outer loop runs only to $\sqrt{N}$ — composites already marked by smaller primes.

Time $O(n \log \log n)$ · Space $O(n)$

```

C++
vector<bool> sieveOfEratosthenes(const int n) {
    vector<bool> isPrime(n + 1, true);
    isPrime[0] = isPrime[1] = false;
    for (int i = 2; i * i <= n; i++) {
        if (isPrime[i]) {
            for (int j = i * i; j <= n; j += i) {
                isPrime[j] = false;
            }
        }
    }
    return isPrime;
}

// Usage: count primes up to 10^6
// auto p = sieveOfEratosthenes(1e6);
// count(p.begin(), p.end(), true) → 78498

```

Prime Factors · 2 cards

Prime Factorization — Trial Division

A number has at most $\log(n)$ prime factors since $2^{\log(n)} \geq n$. Trial division up to $\sqrt{n}$ finds all factors.
Time $O(\sqrt{n})$ · Space $O(\log n)$

```
C++
vector<int> primeFactors(int n) {
    vector<int> factors;
    for (int i = 2; i * i <= n; i++) {
        while (n % i == 0) {
            factors.push_back(i);
            n /= i;
        }
    }
    if (n > 1) factors.push_back(n);
    return factors;
}
```

Sieve — $O(\log n)$ Factorization per Query

Precompute minimum prime factor for every number $\leq \text{MAX}$. Then factor any n in $O(\log n)$.
Sieve $O(\text{MAX})$ · Factorize $O(\log n)$ · Space $O(\text{MAX})$

```
C++
vector<int> buildSieve(int MAX) {
    vector<int> minP(MAX+1);
    iota(minP.begin(), minP.end(), 0);
    for (int i = 2; i*i <= MAX; i++)
        if (minP[i] == i) // i is prime
            for (int j = i*i; j <= MAX; j += i)
                minP[j] = min(minP[j], i);
    return minP;
}

vector<int> factorize(int n, vector<int>& minP) {
    vector<int> factors;
    while (n > 1) {
        factors.push_back(minP[n]);
        n /= minP[n];
    }
    return factors;
}
```

Strings

Manacher's Algorithm · 1 card

Manacher's — O(n) Palindrome Detection

Finds all palindromic substrings in O(n) by inserting # separators and reusing previously computed palindrome lengths via mirroring.

Time O(n) · Space O(n)

Python

```
def manachers(s: str) -> list[int]:
    # Insert # to unify odd/even cases
    t = '#'.join(s)
    n = len(t)
    p = [0] * n # palindrome radii
    c = r = 0
    for i in range(n):
        if i < r:
            p[i] = min(r - i, p[2*c - i])
            while i-p[i]-1 >= 0 and i+p[i]+1 < n and t[i-p[i]-1] == t[i+p[i]+1]:
                p[i] += 1
            if i + p[i] > r:
                c, r = i, i + p[i]
    return p # p[i] = radius of palindrome centered at t[i]
```

C++

```
string longestPalindrome(string s) {
    string t = "#";
    for (char c : s) { t += c; t += '#'; }
    int n = t.size();
    vector<int> p(n, 0);
    int c = 0, r = 0;
    for (int i = 0; i < n; i++) {
        if (i < r) p[i] = min(r-i, p[2*c-i]);
        while (i-p[i]-1 >= 0 && i+p[i]+1 < n && t[i-p[i]-1] == t[i+p[i]+1]) p[i]++;
        if (i+p[i] > r) { c=i; r=i+p[i]; }
    }
    int best = max_element(p.begin(), p.end()) - p.begin();
    return s.substr((best - p[best])/2, p[best]);
}
```

Palindrome · 1 card

Palindrome Check — Multiple Methods

A string reads the same forwards and backwards. Check by comparing from both ends inward.

Time O(n) · Space O(1)

```

C++
// Method 1: Two pointers
bool isPalindrome(string s) {
    int l = 0, r = s.size() - 1;
    while (l < r) {
        if (s[l] != s[r]) return false;
        l++; r--;
    }
    return true;
}

// Method 2: Reverse compare
bool isPalindrome2(string s) {
    string rev = s;
    reverse(rev.begin(), rev.end());
    return s == rev;
}

// Method 3: STL equal with reverse iterators
bool isPalindrome3(string s) {
    return equal(s.begin(), s.begin() + s.size()/2, s.rbegin());
}

```

```

Python
# All in one line
def isPalindrome(s: str) -> bool:
    return s == s[::-1]

# Two pointers
def isPalindrome2(s: str) -> bool:
    l, r = 0, len(s) - 1
    while l < r:
        if s[l] != s[r]: return False
        l += 1; r -= 1
    return True

```

Z Algorithm · 1 card

Z Algorithm — $O(n)$ Pattern Matching

Builds Z-array where $Z[i]$ = length of longest substring starting at i matching a prefix. $Z[0] = 0$ by convention.

Time $O(n)$ · Space $O(n)$

```

C++
vector<int> zFunction(string s) {
    int n = s.size();
    vector<int> z(n, 0);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i < r) z[i] = min(r-i, z[i-l]);
        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) z[i]++;
        if (i+z[i] > r) { l=i; r=i+z[i]; }
    }
    return z;
}

// Pattern matching: find all occurrences of pattern in text
// Concat: pattern + '$' + text, check z[i] == pattern.size()
vector<int> findPattern(string pat, string txt) {
    string s = pat + '$' + txt;
    auto z = zFunction(s);
    vector<int> matches;
    int m = pat.size();
    for (int i = m+1; i < s.size(); i++)
        if (z[i] == m) matches.push_back(i - m - 1);
    return matches;
}

```

```

Python
def z_function(s: str) -> list[int]:
    n = len(s)
    z = [0] * n
    l = r = 0
    for i in range(1, n):
        if i < r:
            z[i] = min(r - i, z[i - l])
        while i + z[i] < n and s[z[i]] == s[i + z[i]]:
            z[i] += 1
        if i + z[i] > r:
            l, r = i, i + z[i]
    return z

```