Home Content Contact

SWITCH CASES

Start

C++ SWITCH STATEMENT

A switch statement is used when:

- A variable is compared against many possible values
- The program chooses one block of code to execute

Switch makes the code:

- Cleaner
- Easier to read
- Easier to maintain

Instead of writing many else if, we use cases.

SWITCH STATEMENT SYNTAX

DEMO

ROLE OF BREAK

break stops the execution of the switch.

1. Example WITHOUT break(DEMO example 7)
   a. output would be: OneTwoThree
   b. Because without break, execution continues to the next cases.
   c. This is called **fall-through behavior**.
   d.

DEFAULT CASE

The default case runs when no cases match.

Example 8

Output would be: Invalid grade

WHEN TO USE SWITCH VS IF-ELSE

Use switch when:

1. Checking one variable
2. Comparing against fixed values

Example:

- Menu selection
- Day of week
- Grade classification

Use if-else when:

Conditions involve ranges

Example:

```
if(score >= 90)
```

switch cases can’t check ranges

SUMMARY

Key points:

- switch is used for multiple fixed choices
- Each choice is called a case
- break stops the execution
- default handles unmatched values
- switch makes code cleaner than many if-else statements

QUESTIONS?

ACTIVITY:
CREATE YOUR OWN SWITCH CASES.

- IT SHOULD HAVE 6 CASES
- A BREAK
- A DEFAULT
- ONCE YOU'RE DONE, SEND IT TO:

emmanueltuboran@spc.edu.ph

ACTIVITY:

1. CREATE A FUNCTION THAT ASK USER THEIR COURSE
2. CREATE A SWITCH CASE WITH DIFFERENT CHOICES
3. THE CHOICE WILL COME FROM THE FUNCTION RETURNED VALUE