FUNDAMENTALS AND MORE

PARAMETERS, ARGUMENTS, LOCAL SCOPE

Start

PARAMETERS AND ARGUMENTS

- In C++, functions are used to perform specific tasks
- Functions can receive data from the program
- This data is passed using parameters and arguments
- Parameters and arguments help make programs reusable and flexible

WHAT ARE PARAMETERS?

- Parameters are variables defined in a function
- They act as placeholders for values passed to the function
- Parameters receive values when the function is called
- Defined inside the function parentheses

Example:

```
void add(int a, int b){

}
```

WHAT ARE ARGUMENTS?

- Arguments are the actual values passed to a function
- They provide real data to the parameters
- Arguments are given when calling the function

```
add(5, 3);
```

GLOBAL AND LOCAL VARIABLES IN C++ (INTRODUCTION)

- Variables in C++ have a scope
- Scope decides where a variable can be used
- Two common types:
  - Global variables
  - Local variables
- Understanding scope helps avoid errors in programs

GLOBAL VARIABLES

- Declared outside all functions
- Can be accessed anywhere in the program
- Exist for the entire program execution

LOCAL VARIABLES

- Declared inside a function
- Can be used only inside that function
- Created when the function is called
- Destroyed when the function ends

QUESTIONS?