NorzAgapay Data Dictionary

Core data behind report submission, barangay coordination, MDRRMO dispatch, field response, and incident resolution.

Prepared 22 October 2026

This dictionary focuses on the key records in the NorzAgapay web incident cycle: submit a report, review and assign it, record field response, and close and track the incident. Standalone weather monitoring, public broadcasts, and internal notification queues are outside this scope. Table definitions are based on the checked-in schema and migrations.

Report records hold evidence references, response notes, and resolution details; uploaded media files themselves are stored in Supabase Storage. Assignment and history tables preserve who responded and how the incident progressed.

Table Groups

System Area	Tables	Purpose
Accounts and barangay context	4	These tables identify report submitters, response staff, and barangay jurisdictions.
Incident report records	2	These tables store reports from submission through review and resolution.
Responder units and rosters	3	These tables define available MDRRMO teams and the people assigned to each unit.
Dispatch, assignments, and crews	5	These tables link reports to MDRRMO or barangay responders and record selected crews.
Status and assignment history	3	These tables preserve report status changes and barangay handoff events.
Assistance and transport	3	These tables support requests for extra help and injured-person transport.

Reading the field tables

Allow Null is Yes when the SQL column permits NULL and No when it is required or is a primary key. A dash means that no explicit length, default, or key is declared. PK means primary key, FK identifies the referenced table and column, UQ means unique, and CHECK means the column has a database check constraint. PostgreSQL enum values are listed in the final section.

Source files: database/schema.sql and database/migrations/.sql; table usage was checked against the web dashboard and its backend.*

Detailed table definitions

Accounts and barangay context

These tables identify report submitters, response staff, and barangay jurisdictions.

resident_user

Resident account used to identify people who submit and track reports.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
full_name	text	—	No	—	—
phone	varchar	15	No	—	—
password_hash	text	—	No	—	—
barangay_name	text	—	No	'Poblacion'	—
role	text	—	No	'resident'	CHECK
status	text	—	No	'active'	—
verified	boolean	—	No	false	—
last_seen	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—
false_report_count	integer	—	No	0	—
username	text	—	Yes	—	UQ

users

MDRRMO staff and responder accounts used for dispatch and field actions.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
full_name	text	—	No	—	—
phone	varchar	15	No	—	—
password_hash	text	—	No	—	—
role	user_role	—	No	'responder'	—
unit_type	unit_type	—	Yes	—	—
status	user_status	—	No	'active'	—
verified	boolean	—	No	false	—
latitude	double precision	—	Yes	—	—
longitude	double precision	—	Yes	—	—
last_seen	timestamptz	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
created_at	timestamptz	—	No	now()	—
barangay_name	text	—	Yes	—	—
updated_at	timestamptz	—	No	now()	—
username	text	—	Yes	—	UQ

barangay_users

Barangay staff and responder accounts used for local assignments.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
barangay_id	uuid	—	Yes	—	FK barangays.id
full_name	text	—	No	''	—
phone	varchar	15	No	—	—
password_hash	text	—	No	''	—
role	barangay_role	—	No	'staff'	—
added_by	uuid	—	Yes	—	FK barangay_users.id
is_active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—
verification_status	varchar	32	Yes	'pending_document'	—
verification_ref_no	varchar	64	Yes	—	—
position_designation	text	—	Yes	—	—
username	text	—	Yes	—	UQ

barangays

Barangay names and locations used to route reports and coordinate response.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
flood_risk	risk_level	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
landslide_risk	risk_level	—	Yes	—	—
geometry	jsonb	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
municipality	text	—	No	'Norzagaray'	—
province	text	—	No	'Bulacan'	—
location_latitude	double precision	—	Yes	—	—
location_longitude	double precision	—	Yes	—	—
location_address	text	—	Yes	—	—
location_icon_url	text	—	Yes	—	—
location_icon_storage_path	text	—	Yes	—	—

Incident report records

These tables store reports from submission through review and resolution.

barangay_reports

Barangay incident record used for local response updates and resolution.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
type	text	—	No	'emergency'	—
title	text	—	No	—	—
specifics	text	—	Yes	—	—
description	text	—	Yes	—	—
latitude	double precision	—	No	0	—
longitude	double precision	—	No	0	—
address	text	—	Yes	—	—
incident_occurred_at	timestamptz	—	Yes	—	—
incident_time_precision	text	—	No	'unknown'	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
proof_url	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
proof_urls	text[]	—	No	'{}'	—
proof_type	text	—	No	'image'	—
proof_types	text[]	—	No	'{}'	—
evidence_status	text	—	No	'ready'	—
responder_media	jsonb	—	No	'[]'	—
reporter_id	uuid	—	Yes	—	FK resident_user.id
reporter_type	text	—	Yes	'resident'	—
reporter_name	text	—	Yes	—	—
reporter_phone	text	—	Yes	—	—
barangay_id	uuid	—	Yes	—	—
response_status	text	—	No	'pending'	—
response_notes	text	—	Yes	—	—
responder_name	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK barangay_users.id
responded_at	timestamptz	—	Yes	—	—
dispatcher_reviewed_by	uuid	—	Yes	—	FK barangay_users.id
dispatcher_reviewed_at	timestamptz	—	Yes	—	—
dispatched_by	uuid	—	Yes	—	FK barangay_users.id
dispatched_at	timestamptz	—	Yes	—	—
dispatch_notes	text	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
arrival_recorded_at	timestamptz	—	Yes	—	—
arrival_method	text	—	Yes	—	—
arrival_latitude	double precision	—	Yes	—	—
arrival_longitude	double precision	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
arrival_accuracy_m	double precision	—	Yes	—	—
arrival_distance_m	double precision	—	Yes	—	—
travel_distance_m	double precision	—	Yes	—	—
travel_distance_accuracy_m	double precision	—	Yes	—	—
travel_distance_fix_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK barangay_users.id
resolved_notes	text	—	Yes	—	—
resolution_pdf_status	text	—	No	'missing'	—
resolution_pdf_path	text	—	Yes	—	—
resolution_pdf_generated_at	timestamptz	—	Yes	—	—
review_outcome	text	—	Yes	—	—
review_reason	text	—	Yes	—	—
reviewed_by	uuid	—	Yes	—	FK barangay_users.id
reviewed_at	timestamptz	—	Yes	—	—
escalated_to_mdrrmo	boolean	—	No	false	—
escalated_at	timestamptz	—	Yes	—	—
mdrrmo_coordination_notes	text	—	Yes	—	—
dispatch_incident_id	uuid	—	Yes	—	—
lifecycle_revision	bigint	—	No	0	—
lifecycle_actor_id	uuid	—	Yes	—	—
lifecycle_actor_role	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
client_request_id	uuid	—	Yes	—	UQ
client_submitted_at	timestamptz	—	Yes	—	—
status	text	—	No	'pending'	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

mdrrmo_reports

MDRRMO report record with incident details, evidence references, status, and resolution data.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
source_type	text	—	No	'direct'	—
source_barangay_report_id	uuid	—	Yes	—	FK barangay_reports.id
type	text	—	No	'emergency'	—
title	text	—	No	—	—
specifics	text	—	Yes	—	—
description	text	—	Yes	—	—
latitude	double precision	—	No	0	—
longitude	double precision	—	No	0	—
address	text	—	Yes	—	—
incident_occurred_at	timestamptz	—	Yes	—	—
incident_time_precision	text	—	No	'unknown'	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
proof_url	text	—	Yes	—	—
proof_urls	text[]	—	No	'{}'	—
proof_type	text	—	No	'image'	—
proof_types	text[]	—	No	'{}'	—
evidence_status	text	—	No	'ready'	—
responder_media	jsonb	—	No	'[]'	—

Column Name	Type	Length	Nullable	Default	Key
reporter_id	uuid	—	Yes	—	—
reporter_type	text	—	Yes	'resident'	—
reporter_name	text	—	Yes	—	—
reporter_phone	text	—	Yes	—	—
barangay_id	uuid	—	Yes	—	—
barangay_name	text	—	Yes	—	—
response_status	text	—	No	'pending'	—
response_notes	text	—	Yes	—	—
coordination_notes	text	—	Yes	—	—
responder_name	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK users.id
responded_at	timestamptz	—	Yes	—	—
dispatcher_reviewed_by	uuid	—	Yes	—	FK users.id
dispatcher_reviewed_at	timestamptz	—	Yes	—	—
dispatched_by	uuid	—	Yes	—	FK users.id
dispatched_at	timestamptz	—	Yes	—	—
dispatch_notes	text	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
travel_distance_m	double precision	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK users.id
resolved_notes	text	—	Yes	—	—
map_closed_at	timestamptz	—	Yes	—	—
map_closed_by	uuid	—	Yes	—	FK users.id
resolution_pdf_status	text	—	No	'missing'	—
resolution_pdf_path	text	—	Yes	—	—
resolution_pdf_generated_at	timestamptz	—	Yes	—	—
dispatch_incident_id	uuid	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
lifecycle_revision	bigint	—	No	0	—
lifecycle_actor_id	uuid	—	Yes	—	—
lifecycle_actor_role	text	—	Yes	—	—
client_request_id	uuid	—	Yes	—	UQ
client_submitted_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

Responder units and rosters

These tables define available MDRRMO teams and the people assigned to each unit.

officers

Responder qualifications and officer details linked to MDRRMO unit rosters.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
phone	text	—	Yes	—	—
specialization	text	—	No	—	—
rank	text	—	Yes	—	—
status	text	—	No	'active'	—
created_at	timestamptz	—	No	now()	—

respond_units

MDRRMO response-unit name, specialization, availability, and activation state.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
unit_name	text	—	No	—	—
specialization	text	—	No	—	—
officer_ids	uuid[]	—	No	'{}'	—
status	text	—	No	'available'	—
is_active	boolean	—	No	false	—
activation_mode	text	—	Yes	—	CHECK
activated_by	uuid	—	Yes	—	FK users.id

Column Name	Type	Length	Nullable	Default	Key
activated_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

respond_unit_members

Officer and responder membership and roles within each response unit.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
unit_id	uuid	—	No	—	FK respond_units.id; UQ composite
officer_id	uuid	—	No	—	FK officers.id; UQ composite
responder_user_id	uuid	—	Yes	—	FK users.id
member_role	text	—	No	'unassigned'	—
is_active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

Dispatch, assignments, and crews

These tables link reports to MDRRMO or barangay responders and record selected crews.

mdrrmo_report_assignments

Links an MDRRMO report to assigned responders and tracks their response state.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	UQ composite; FK mdrrmo_reports.id
responder_id	uuid	—	No	—	FK users.id; UQ composite
assigned_by	uuid	—	Yes	—	FK users.id
status	text	—	No	'assigned'	—
assigned_at	timestamptz	—	No	now()	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
accepted_by	uuid	—	Yes	—	FK users.id
arrived_by	uuid	—	Yes	—	FK users.id

Column Name	Type	Length	Nullable	Default	Key
resolved_by	uuid	—	Yes	—	FK users.id
resolved_by_role	text	—	Yes	—	—
removed_by	uuid	—	Yes	—	FK users.id
removed_at	timestamptz	—	Yes	—	—

barangay_report_assignments

Links a barangay report to barangay responders and their response roles.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	FK barangay_reports.id; UQ composite
responder_id	uuid	—	No	—	FK barangay_users.id; UQ composite
role	text	—	No	'team_leader'	—
status	text	—	No	'assigned'	—
assigned_by	uuid	—	Yes	—	FK barangay_users.id
assigned_at	timestamptz	—	No	now()	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
removed_at	timestamptz	—	Yes	—	—
removed_by	uuid	—	Yes	—	FK barangay_users.id

mdrrmo_report_barangay_assignments

Tracks MDRRMO-to-barangay dispatch, arrival, response, and resolution.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	FK mdrrmo_reports.id

Column Name	Type	Length	Nullable	Default	Key
barangay_id	uuid	—	No	—	FK barangays.id
assignment_status	text	—	No	'active'	—
response_status	text	—	No	'pending'	—
assignment_notes	text	—	Yes	—	—
assigned_by	uuid	—	Yes	—	FK users.id
assigned_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—
dispatched_by	uuid	—	Yes	—	FK barangay_users.id
dispatched_at	timestamptz	—	Yes	—	—
responder_ids	uuid[]	—	No	'{}'	—
responder_name	text	—	Yes	—	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
response_notes	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK barangay_users.id
responded_at	timestamptz	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
arrival_method	text	—	Yes	—	—
arrival_latitude	double precision	—	Yes	—	—
arrival_longitude	double precision	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK barangay_users.id
resolved_at	timestamptz	—	Yes	—	—
resolved_notes	text	—	Yes	—	—
escalated_by	uuid	—	Yes	—	FK barangay_users.id
escalated_at	timestamptz	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
escalation_notes	text	—	Yes	—	—

mdrrmo_assignment_crew_members

Records the MDRRMO crew selected for a responder assignment.

Column Name	Type	Length	Nullable	Default	Key
assignment_id	uuid	—	No	—	FK mdrrmo_report_assignments.id; PK composite
unit_member_id	uuid	—	No	—	FK respond_unit_members.id; PK composite
member_name_snapshot	text	—	No	—	—
member_role_snapshot	text	—	No	—	—
selected_at	timestamptz	—	No	now()	—

mdrrmo_report_barangay_crew_members

Records barangay members selected for a coordinated response.

Column Name	Type	Length	Nullable	Default	Key
assignment_id	uuid	—	No	—	FK mdrrmo_report_barangay_assignments.id; PK composite
barangay_id	uuid	—	No	—	FK barangays.id
member_id	uuid	—	No	—	FK barangay_users.id; PK composite
member_name_snapshot	text	—	No	—	—
crew_role	text	—	No	—	CHECK
selected_at	timestamptz	—	No	now()	—

Status and assignment history

These tables preserve report status changes and barangay handoff events.

mdrrmo_report_lifecycle_history

Records the MDRRMO report status and action history.

Column Name	Type	Length	Nullable	Default	Key

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
report_id	uuid	—	No	—	FK mdrrmo_reports.id
event_type	text	—	No	—	—
actor_id	uuid	—	Yes	—	—
actor_role	text	—	Yes	—	—
occurred_at	timestamptz	—	No	now()	—
details	jsonb	—	No	{}	—

barangay_report_lifecycle_history

Records the barangay report status and action history.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
report_id	uuid	—	No	—	FK barangay_reports.id
event_type	text	—	No	—	—
actor_id	uuid	—	Yes	—	—
actor_role	text	—	Yes	—	—
occurred_at	timestamptz	—	No	now()	—
details	jsonb	—	No	{}	—

mdrrmo_report_barangay_assignment_events

Records barangay assignment, reassignment, recall, and coordination events.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	FK mdrrmo_reports.id
assignment_id	uuid	—	Yes	—	FK mdrrmo_report_barangay_assignments.id
from_barangay_id	uuid	—	Yes	—	FK barangays.id
to_barangay_id	uuid	—	Yes	—	FK barangays.id
event_type	text	—	No	—	CHECK
actor_id	uuid	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
actor_role	text	—	No	—	—
notes	text	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

Assistance and transport

These tables support requests for extra help and injured-person transport.

barangay_assistance_requests

Records a barangay request for responders, equipment, resources, or MDRRMO help.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
barangay_id	uuid	—	No	—	FK barangays.id
requested_by	uuid	—	No	—	FK barangay_users.id
incident_report_id	uuid	—	Yes	—	FK barangay_reports.id
incident_title	text	—	Yes	—	—
needs_more_manpower	boolean	—	No	false	—
needs_resources	boolean	—	No	false	—
needs_equipment	boolean	—	No	false	—
beyond_barangay_capability	boolean	—	No	false	—
explanation	text	—	No	—	—
status	text	—	No	'pending'	—
decision	text	—	Yes	—	—
dispatcher_notes	text	—	Yes	—	—
decided_by	uuid	—	Yes	—	FK barangay_users.id
decided_at	timestamptz	—	Yes	—	—
team_acknowledged	boolean	—	No	false	—
created_at	timestamptz	—	No	now()	—

resource_requests

Records resource requests submitted for dispatcher review.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
requested_by	uuid	—	No	—	FK users.id
request_type	text	—	No	—	—
sub_type	text	—	Yes	—	—
details	text	—	No	—	—
dispatcher_notes	text	—	Yes	—	—
incident_id	uuid	—	Yes	—	FK incidents.id
status	text	—	No	'pending'	—
created_at	timestamptz	—	No	now()	—
mdrrmo_report_id	uuid	—	Yes	—	FK mdrrmo_reports.id

hospital_directory

Stores hospital names and coordinates used to select nearby transport destinations.

Column Name	Type	Length	Nullable	Default	Key
id	text	—	No	—	PK
name	text	—	No	—	—
address	text	—	No	—	—
municipality	text	—	No	—	—
province	text	—	No	'Bulacan'	—
latitude	double precision	—	No	—	CHECK
longitude	double precision	—	No	—	CHECK
source_url	text	—	Yes	—	—
active	boolean	—	No	true	—
updated_at	timestamptz	—	No	now()	—

PostgreSQL enum values

These enumerated types appear in the fields listed above. Text fields may also have separate CHECK constraints.

Enum Type	Allowed Values
user_role	master_admin, admin, logistics, dispatcher, responder
unit_type	police, fire, medical, Rescue Officer, Swift Water Rescue Officer, Mountain Rescue Officer, Emergency Medical Responder (EMR), Ambulance Officer / EMS Personnel, Fire Response Officer, Evacuation Officer, Safety & Security Officer, Traffic & Road Clearing Officer, Communications Officer, Logistics Response Officer, Damage Assessment Officer
user_status	active, inactive, pending_verification, occupied, rejected
risk_level	low, moderate, high, critical
barangay_role	admin, dispatcher, responder, staff