NorzAgapay Data Dictionary

Database fields supporting public reporting, resident services, barangay coordination, MDRRMO response, emergency information, and municipal monitoring.

Prepared 22 October 2026

This reference describes the relational data used through the system's public pages and staff workspaces, from account access and incident intake to assignment, field response, resolution, public alerts, and map-based information. The table definitions follow the repository SQL schema and migrations; calculated dashboard totals and external service payloads are not database columns.

The main incident cycle links report records to assignments and response history. Barangay reports are tracked in barangay_reports, while MDRRMO reports are tracked in mdrrmo_reports. Assignment and crew tables record who responds; lifecycle records preserve status changes. Resolution PDF paths and responder media metadata are stored as database values, while uploaded files are kept in Supabase Storage.

Table groups

System area	Tables	Purpose
Accounts and verification	users, resident_user, barangays, barangay_users, barangay_dispatcher_verifications, account_usernames, account_mobile_numbers, certifications	Account identity, role, barangay membership, eligibility, and unique login identifiers.
Response units and command locations	officers, respond_units, respond_unit_members, mdrrmo_command_locations	Responder roster, unit activation, and command-office map data.
Incident reports and lifecycle	incident_reports, barangay_reports, mdrrmo_reports, incident_report_lifecycle_history, barangay_report_lifecycle_history, mdrrmo_report_lifecycle_history, incident_event_outbox, barangay_report_event_outbox, mdrrmo_report_event_outbox	Incident intake records, responder notes, resolution data, and the event history that supports live updates.

System area	Tables	Purpose
Assignments and response crews	mdrrmo_report_assignments, barangay_report_assignments, mdrrmo_assignment_crew_members, mdrrmo_report_barangay_assignments, mdrrmo_report_barangay_assignment_events, mdrrmo_report_barangay_crew_members	Assignment records connect reports to responders or barangays and preserve crew selections and handoff events.
Assistance, facilities, and routes	barangay_assistance_requests, resource_requests, evacuation_centers, hospital_directory, blocked_routes	Requests for outside support, shelters, hospital destinations, and route hazards.
Public information and alerts	public_broadcasts, weather_advisories, alerts, activity_feed	Published safety communications, advisories, and the activity stream shown to residents and staff.
Environmental monitoring and municipality map	weather_forecasts, hazard_zones, earthquakes, river_stations, river_levels, dam_stations, dam_levels, municipality_info, municipality_boundary_config, municipality_boundary_history	Weather, earthquake, river, dam, hazard-area, and boundary data shown on situation maps.

Reading the field tables

Allow Null is Yes when the SQL column permits NULL and No when it is required or is a primary key. A dash means that no explicit length, default, or key is declared. PK means primary key, FK identifies the referenced table and column, UQ means unique, and CHECK means the column has a database check constraint. PostgreSQL enum values are listed in the final section.

Schema coverage note

The web application reads and saves barangay_hotline_settings, including barangay_id and hotlines. No CREATE TABLE statement or migration for that table is present in the checked-in SQL files, so its data types, nullability, defaults, and keys cannot be verified here.

Source files: database/schema.sql and database/migrations/.sql. Table usage was cross-checked against backend/src and web-dashboard/src.*

Detailed table definitions

Accounts and verification

Account identity, role, barangay membership, eligibility, and unique login identifiers.

users

MDRRMO and system accounts used for staff access, responder assignment, and account verification.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
full_name	text	—	No	—	—
phone	varchar	15	No	—	—
password_hash	text	—	No	—	—
role	user_role	—	No	'responder'	—
unit_type	unit_type	—	Yes	—	—
status	user_status	—	No	'active'	—
verified	boolean	—	No	false	—
latitude	double precision	—	Yes	—	—
longitude	double precision	—	Yes	—	—
last_seen	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
barangay_name	text	—	Yes	—	—
updated_at	timestamptz	—	No	now()	—
username	text	—	Yes	—	UQ

resident_user

Resident accounts used by self-service registration, login, report submission, and report tracking.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
full_name	text	—	No	—	—
phone	varchar	15	No	—	—
password_hash	text	—	No	—	—
barangay_name	text	—	No	'Poblacion'	—
role	text	—	No	'resident'	CHECK
status	text	—	No	'active'	—
verified	boolean	—	No	false	—
last_seen	timestamptz	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—
false_report_count	integer	—	No	0	—
username	text	—	Yes	—	UQ

barangays

Barangay directory and map locations used for routing reports, selecting jurisdictions, and displaying offices.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
flood_risk	risk_level	—	Yes	—	—
landslide_risk	risk_level	—	Yes	—	—
geometry	jsonb	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
municipality	text	—	No	'Norzagaray'	—
province	text	—	No	'Bulacan'	—
location_latitude	double precision	—	Yes	—	—
location_longitude	double precision	—	Yes	—	—
location_address	text	—	Yes	—	—
location_icon_url	text	—	Yes	—	—
location_icon_storage_path	text	—	Yes	—	—

barangay_users

Barangay staff accounts, roles, and barangay membership.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
barangay_id	uuid	—	Yes	—	FK barangays.id

Column Name	Type	Length	Nullable	Default	Key
full_name	text	—	No	''	—
phone	varchar	15	No	—	—
password_hash	text	—	No	''	—
role	barangay_role	—	No	'staff'	—
added_by	uuid	—	Yes	—	FK barangay_users.id
is_active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—
verification_status	varchar	32	Yes	'pending_document'	—
verification_ref_no	varchar	64	Yes	—	—
position_designation	text	—	Yes	—	—
username	text	—	Yes	—	UQ

barangay_dispatcher_verifications

Barangay dispatcher account requests, supporting documents, and review decisions.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
user_id	uuid	—	Yes	—	—
barangay_id	uuid	—	No	—	FK barangays.id
full_name	text	—	No	''	—
password_hash	text	—	Yes	—	—
phone	varchar	20	Yes	—	—
position_designation	text	—	No	'Barangay Dispatcher'	—
punong_barangay_name	text	—	No	''	—
punong_barangay_position	text	—	No	'Punong Barangay'	—
reference_no	varchar	64	No	—	UQ
document_url	text	—	Yes	—	—
status	varchar	32	No	'pending_document'	—
rejection_reason	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
submitted_at	timestamptz	—	Yes	—	—
reviewed_at	timestamptz	—	Yes	—	—
reviewed_by	uuid	—	Yes	—	FK users.id
verification_history	jsonb	—	No	[]	—
is_active	boolean	—	No	false	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

account_usernames

Normalized username registry that enforces unique usernames across account types.

Column Name	Type	Length	Nullable	Default	Key
username_normalized	text	—	No	—	PK
account_table	text	—	No	—	CHECK; UQ composite
account_id	text	—	No	—	UQ composite
created_at	timestamptz	—	No	now()	—

account_mobile_numbers

Normalized phone-number registry that enforces unique mobile login numbers across account types.

Column Name	Type	Length	Nullable	Default	Key
phone_normalized	text	—	No	—	CHECK; PK composite
account_table	text	—	No	—	CHECK; PK composite; UQ composite
account_id	text	—	No	—	UQ composite
created_at	timestamptz	—	No	now()	—

certifications

Responder qualifications and verification information attached to staff accounts.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
user_id	uuid	—	No	—	FK users.id
cert_type	text	—	No	—	—
cert_number	text	—	Yes	—	—
file_url	text	—	Yes	—	—
verified	boolean	—	No	false	—

Column Name	Type	Length	Nullable	Default	Key
verified_by	uuid	—	Yes	—	FK users.id
verified_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

Response units and command locations

Responder roster, unit activation, and command-office map data.

officers

MDRRMO officer directory with contact, specialization, rank, and status.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
phone	text	—	Yes	—	—
specialization	text	—	No	—	—
rank	text	—	Yes	—	—
status	text	—	No	'active'	—
created_at	timestamptz	—	No	now()	—

respond_units

Response unit name, specialization, availability, and activation state.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
unit_name	text	—	No	—	—
specialization	text	—	No	—	—
officer_ids	uuid[]	—	No	'{}'	—
status	text	—	No	'available'	—
is_active	boolean	—	No	false	—
activation_mode	text	—	Yes	—	CHECK
activated_by	uuid	—	Yes	—	FK users.id
activated_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

respond_unit_members

Membership of officers and responder accounts in response units.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK

Column Name	Type	Length	Nullable	Default	Key
unit_id	uuid	—	No	—	FK respond_units.id; UQ composite
officer_id	uuid	—	No	—	FK officers.id; UQ composite
responder_user_id	uuid	—	Yes	—	FK users.id
member_role	text	—	No	'unassigned'	—
is_active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

mdrrmo_command_locations

Configured MDRRMO office point and map icon used by command screens.

Column Name	Type	Length	Nullable	Default	Key
location_key	text	—	No	—	PK; CHECK
latitude	double precision	—	No	—	CHECK
longitude	double precision	—	No	—	CHECK
address	text	—	Yes	—	—
icon_url	text	—	Yes	—	—
icon_storage_path	text	—	Yes	—	—
updated_by	uuid	—	Yes	—	FK users.id
updated_at	timestamptz	—	No	now()	—

Incident reports and lifecycle

Incident intake records, responder notes, resolution data, and the event history that supports live updates.

incident_reports

General incident intake record retained for report and dispatch compatibility.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
type	text	—	No	—	—
title	text	—	No	—	—
specifics	text	—	Yes	—	—
description	text	—	Yes	—	—
latitude	double precision	—	No	—	—

Column Name	Type	Length	Nullable	Default	Key
longitude	double precision	—	No	—	—
proof_url	text	—	Yes	—	—
proof_type	text	—	No	'image'	—
reporter_type	text	—	No	'resident'	—
reporter_id	uuid	—	Yes	—	FK users.id
reporter_name	text	—	Yes	—	—
reporter_phone	text	—	Yes	—	—
reporter_photo_url	text	—	Yes	—	—
address	text	—	Yes	—	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
dispatch_incident_id	uuid	—	Yes	—	FK incidents.id
status	report_status	—	No	'pending'	—
client_submitted_at	timestamptz	—	Yes	—	—
incident_occurred_at	timestamptz	—	Yes	—	—
incident_time_precision	text	—	No	'unknown'	—
created_at	timestamptz	—	No	now()	—
barangay_id	uuid	—	Yes	—	FK barangays.id
barangay_response_status	text	—	Yes	'pending'	—
barangay_response_notes	text	—	Yes	—	—
barangay_responded_by	uuid	—	Yes	—	FK barangay_users.id
barangay_responded_at	timestamptz	—	Yes	—	—
mdrrmo_coordination_notes	text	—	Yes	—	—
resolved_notes	text	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
mdrrmo_response_status	text	—	Yes	'pending'	—
mdrrmo_responded_at	timestamptz	—	Yes	—	—
mdrrmo_responded_by	uuid	—	Yes	—	FK users.id
mdrrmo_responder_name	text	—	Yes	—	—
mdrrmo_response_notes	text	—	Yes	—	—
proof_urls	text[]	—	Yes	—	—
proof_types	text[]	—	Yes	—	—
responder_media	jsonb	—	Yes	[]	—
send_to	text	—	Yes	'all'	—
dispatcher_reviewed_at	timestamptz	—	Yes	—	—
dispatched_at	timestamptz	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
travel_distance_m	double precision	—	Yes	—	—
travel_distance_accuracy_m	double precision	—	Yes	—	—
travel_distance_fix_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
arrival_recorded_at	timestamptz	—	Yes	—	—
arrival_method	text	—	Yes	—	—
arrival_latitude	double precision	—	Yes	—	—
arrival_longitude	double precision	—	Yes	—	—
arrival_accuracy_m	double precision	—	Yes	—	—
arrival_distance_m	double precision	—	Yes	—	—
review_outcome	text	—	Yes	—	—
review_reason	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
reviewed_by	uuid	—	Yes	—	FK users.id
reviewed_at	timestamptz	—	Yes	—	—
mdrrmo_dispatch_notes	text	—	Yes	—	—
lifecycle_revision	bigint	—	No	0	—
evidence_status	text	—	No	'ready'	—
client_request_id	uuid	—	Yes	—	UQ
barangay_resolved_notes	text	—	Yes	—	—
barangay_resolved_at	timestamptz	—	Yes	—	—
mdrrmo_resolved_notes	text	—	Yes	—	—
mdrrmo_resolved_at	timestamptz	—	Yes	—	—
barangay_dispatcher_reviewed_at	timestamptz	—	Yes	—	—
mdrrmo_dispatcher_reviewed_at	timestamptz	—	Yes	—	—
barangay_dispatched_at	timestamptz	—	Yes	—	—
mdrrmo_dispatched_at	timestamptz	—	Yes	—	—
barangay_accepted_at	timestamptz	—	Yes	—	—
mdrrmo_accepted_at	timestamptz	—	Yes	—	—
barangay_arrived_at	timestamptz	—	Yes	—	—
mdrrmo_arrived_at	timestamptz	—	Yes	—	—
resolution_pdf_path	text	—	Yes	—	—
resolution_pdf_generated_at	timestamptz	—	Yes	—	—
resolution_pdf_status	text	—	No	'missing'	CHECK

Column Name	Type	Length	Nullable	Default	Key
mdrrmo_dispatcher_reviewed_by	uuid	—	Yes	—	FK users.id
mdrrmo_dispatched_by	uuid	—	Yes	—	FK users.id
mdrrmo_accepted_by	uuid	—	Yes	—	FK users.id
mdrrmo_arrived_by	uuid	—	Yes	—	FK users.id
mdrrmo_resolved_by	uuid	—	Yes	—	FK users.id
lifecycle_actor_id	uuid	—	Yes	—	—
lifecycle_actor_role	text	—	Yes	—	—

barangay_reports

Barangay-managed report from intake through dispatch, field response, escalation, and resolution.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
type	text	—	No	'emergency'	—
title	text	—	No	—	—
specifics	text	—	Yes	—	—
description	text	—	Yes	—	—
latitude	double precision	—	No	0	—
longitude	double precision	—	No	0	—
address	text	—	Yes	—	—
incident_occurred_at	timestamptz	—	Yes	—	—
incident_time_precision	text	—	No	'unknown'	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
proof_url	text	—	Yes	—	—
proof_urls	text[]	—	No	'{}'	—
proof_type	text	—	No	'image'	—

Column Name	Type	Length	Nullable	Default	Key
proof_types	text[]	—	No	'{}'	—
evidence_status	text	—	No	'ready'	—
responder_media	jsonb	—	No	'[]'	—
reporter_id	uuid	—	Yes	—	FK resident_user.id
reporter_type	text	—	Yes	'resident'	—
reporter_name	text	—	Yes	—	—
reporter_phone	text	—	Yes	—	—
barangay_id	uuid	—	Yes	—	—
response_status	text	—	No	'pending'	—
response_notes	text	—	Yes	—	—
responder_name	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK barangay_users.id
responded_at	timestamptz	—	Yes	—	—
dispatcher_reviewed_by	uuid	—	Yes	—	FK barangay_users.id
dispatcher_reviewed_at	timestamptz	—	Yes	—	—
dispatched_by	uuid	—	Yes	—	FK barangay_users.id
dispatched_at	timestamptz	—	Yes	—	—
dispatch_notes	text	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
arrival_recorded_at	timestamptz	—	Yes	—	—
arrival_method	text	—	Yes	—	—
arrival_latitude	double precision	—	Yes	—	—
arrival_longitude	double precision	—	Yes	—	—
arrival_accuracy_m	double precision	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
arrival_distance_m	double precision	—	Yes	—	—
travel_distance_m	double precision	—	Yes	—	—
travel_distance_accuracy_m	double precision	—	Yes	—	—
travel_distance_fix_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK barangay_users.id
resolved_notes	text	—	Yes	—	—
resolution_pdf_status	text	—	No	'missing'	—
resolution_pdf_path	text	—	Yes	—	—
resolution_pdf_generated_at	timestamptz	—	Yes	—	—
review_outcome	text	—	Yes	—	—
review_reason	text	—	Yes	—	—
reviewed_by	uuid	—	Yes	—	FK barangay_users.id
reviewed_at	timestamptz	—	Yes	—	—
escalated_to_mdrrmo	boolean	—	No	false	—
escalated_at	timestamptz	—	Yes	—	—
mdrrmo_coordination_notes	text	—	Yes	—	—
dispatch_incident_id	uuid	—	Yes	—	—
lifecycle_revision	bigint	—	No	0	—
lifecycle_actor_id	uuid	—	Yes	—	—
lifecycle_actor_role	text	—	Yes	—	—
client_request_id	uuid	—	Yes	—	UQ

Column Name	Type	Length	Nullable	Default	Key
client_submitted_at	timestamptz	—	Yes	—	—
status	text	—	No	'pending'	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

mdrrmo_reports

MDRRMO report queue, including direct reports and reports coordinated from barangays.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
source_type	text	—	No	'direct'	—
source_barangay_report_id	uuid	—	Yes	—	FK barangay_reports.id
type	text	—	No	'emergency'	—
title	text	—	No	—	—
specifics	text	—	Yes	—	—
description	text	—	Yes	—	—
latitude	double precision	—	No	0	—
longitude	double precision	—	No	0	—
address	text	—	Yes	—	—
incident_occurred_at	timestamptz	—	Yes	—	—
incident_time_precision	text	—	No	'unknown'	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
proof_url	text	—	Yes	—	—
proof_urls	text[]	—	No	'{}'	—
proof_type	text	—	No	'image'	—
proof_types	text[]	—	No	'{}'	—
evidence_status	text	—	No	'ready'	—
responder_media	jsonb	—	No	'[]'	—
reporter_id	uuid	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
reporter_type	text	—	Yes	'resident'	—
reporter_name	text	—	Yes	—	—
reporter_phone	text	—	Yes	—	—
barangay_id	uuid	—	Yes	—	—
barangay_name	text	—	Yes	—	—
response_status	text	—	No	'pending'	—
response_notes	text	—	Yes	—	—
coordination_notes	text	—	Yes	—	—
responder_name	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK users.id
responded_at	timestamptz	—	Yes	—	—
dispatcher_reviewed_by	uuid	—	Yes	—	FK users.id
dispatcher_reviewed_at	timestamptz	—	Yes	—	—
dispatched_by	uuid	—	Yes	—	FK users.id
dispatched_at	timestamptz	—	Yes	—	—
dispatch_notes	text	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
travel_distance_m	double precision	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK users.id
resolved_notes	text	—	Yes	—	—
map_closed_at	timestamptz	—	Yes	—	—
map_closed_by	uuid	—	Yes	—	FK users.id
resolution_pdf_status	text	—	No	'missing'	—
resolution_pdf_path	text	—	Yes	—	—
resolution_pdf_generated_at	timestamptz	—	Yes	—	—
dispatch_incident_id	uuid	—	Yes	—	—
lifecycle_revision	bigint	—	No	0	—

Column Name	Type	Length	Nullable	Default	Key
lifecycle_actor_id	uuid	—	Yes	—	—
lifecycle_actor_role	text	—	Yes	—	—
client_request_id	uuid	—	Yes	—	UQ
client_submitted_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

incident_report_lifecycle_history

Append-only status and action history for general incident reports.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
report_id	uuid	—	No	—	FK incident_reports.id
event_type	text	—	No	—	—
actor_id	uuid	—	Yes	—	—
actor_role	text	—	Yes	—	—
occurred_at	timestamptz	—	No	now()	—
details	jsonb	—	No	{}	—

barangay_report_lifecycle_history

Append-only status and action history for barangay reports.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
report_id	uuid	—	No	—	FK barangay_reports.id
event_type	text	—	No	—	—
actor_id	uuid	—	Yes	—	—
actor_role	text	—	Yes	—	—
occurred_at	timestamptz	—	No	now()	—
details	jsonb	—	No	{}	—

mdrrmo_report_lifecycle_history

Append-only status and action history for MDRRMO reports.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK

Column Name	Type	Length	Nullable	Default	Key
report_id	uuid	—	No	—	FK mdrrmo_reports.id
event_type	text	—	No	—	—
actor_id	uuid	—	Yes	—	—
actor_role	text	—	Yes	—	—
occurred_at	timestamptz	—	No	now()	—
details	jsonb	—	No	{}	—

incident_event_outbox

Queued report-change events used to publish reliable live updates.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
event_id	uuid	—	No	gen_random_uuid()	UQ
report_id	uuid	—	No	—	FK incident_reports.id; UQ composite
revision	bigint	—	No	—	UQ composite
event_type	text	—	No	—	—
payload	jsonb	—	No	{}	—
created_at	timestamptz	—	No	now()	—
attempts	integer	—	No	0	—
available_at	timestamptz	—	No	now()	—
locked_until	timestamptz	—	Yes	—	—
published_at	timestamptz	—	Yes	—	—
last_error	text	—	Yes	—	—

barangay_report_event_outbox

Queued barangay-report change events used to publish reliable live updates.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
event_id	uuid	—	No	gen_random_uuid()	UQ
report_id	uuid	—	No	—	FK barangay_reports.id; UQ composite
revision	bigint	—	No	—	UQ composite

Column Name	Type	Length	Nullable	Default	Key
event_type	text	—	No	—	—
payload	jsonb	—	No	{}	—
created_at	timestamptz	—	No	now()	—
attempts	integer	—	No	0	—
available_at	timestamptz	—	No	now()	—
locked_until	timestamptz	—	Yes	—	—
published_at	timestamptz	—	Yes	—	—
last_error	text	—	Yes	—	—

mdrrmo_report_event_outbox

Queued MDRRMO-report change events used to publish reliable live updates.

Column Name	Type	Length	Nullable	Default	Key
id	bigserial	—	No	—	PK
event_id	uuid	—	No	gen_random_uuid()	UQ
report_id	uuid	—	No	—	FK mdrrmo_reports.id; UQ composite
revision	bigint	—	No	—	UQ composite
event_type	text	—	No	—	—
payload	jsonb	—	No	{}	—
created_at	timestamptz	—	No	now()	—
attempts	integer	—	No	0	—
available_at	timestamptz	—	No	now()	—
locked_until	timestamptz	—	Yes	—	—
published_at	timestamptz	—	Yes	—	—
last_error	text	—	Yes	—	—

Assignments and response crews

Assignment records connect reports to responders or barangays and preserve crew selections and handoff events.

mdrrmo_report_assignments

Assignment of a general incident report to an MDRRMO responder.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK

Column Name	Type	Length	Nullable	Default	Key
report_id	uuid	—	No	—	FK incident_reports.id; UQ composite; FK mdrrmo_reports.id
responder_id	uuid	—	No	—	FK users.id; UQ composite
assigned_by	uuid	—	Yes	—	FK users.id
status	text	—	No	'assigned'	—
assigned_at	timestamptz	—	No	now()	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
accepted_by	uuid	—	Yes	—	FK users.id
arrived_by	uuid	—	Yes	—	FK users.id
resolved_by	uuid	—	Yes	—	FK users.id
resolved_by_role	text	—	Yes	—	—
removed_by	uuid	—	Yes	—	FK users.id
removed_at	timestamptz	—	Yes	—	—

barangay_report_assignments

Assignment of a barangay report to a barangay responder and response role.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	FK barangay_reports.id; UQ composite
responder_id	uuid	—	No	—	FK barangay_users.id; UQ composite
role	text	—	No	'team_leader'	—
status	text	—	No	'assigned'	—
assigned_by	uuid	—	Yes	—	FK barangay_users.id

Column Name	Type	Length	Nullable	Default	Key
assigned_at	timestamptz	—	No	now()	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
resolved_at	timestamptz	—	Yes	—	—
removed_at	timestamptz	—	Yes	—	—
removed_by	uuid	—	Yes	—	FK barangay_users.id

mdrrmo_assignment_crew_members

Responder unit members selected for an MDRRMO assignment, with name and role snapshots.

Column Name	Type	Length	Nullable	Default	Key
assignment_id	uuid	—	No	—	FK mdrrmo_report_assignments.id; PK composite
unit_member_id	uuid	—	No	—	FK respond_unit_members.id; PK composite
member_name_snapshot	text	—	No	—	—
member_role_snapshot	text	—	No	—	—
selected_at	timestamptz	—	No	now()	—

mdrrmo_report_barangay_assignments

Barangay coordination assignment for an MDRRMO report, including dispatch, arrival, resolution, and escalation.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
report_id	uuid	—	No	—	FK mdrrmo_reports.id
barangay_id	uuid	—	No	—	FK barangays.id
assignment_status	text	—	No	'active'	—
response_status	text	—	No	'pending'	—
assignment_notes	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
assigned_by	uuid	—	Yes	—	FK users.id
assigned_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—
dispatched_by	uuid	—	Yes	—	FK barangay_users.id
dispatched_at	timestamptz	—	Yes	—	—
responder_ids	uuid[]	—	No	'{}'	—
responder_name	text	—	Yes	—	—
incident_type	text	—	Yes	—	—
severity	text	—	Yes	—	—
response_notes	text	—	Yes	—	—
responded_by	uuid	—	Yes	—	FK barangay_users.id
responded_at	timestamptz	—	Yes	—	—
accepted_at	timestamptz	—	Yes	—	—
arrived_at	timestamptz	—	Yes	—	—
arrival_method	text	—	Yes	—	—
arrival_latitude	double precision	—	Yes	—	—
arrival_longitude	double precision	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK barangay_users.id
resolved_at	timestamptz	—	Yes	—	—
resolved_notes	text	—	Yes	—	—
escalated_by	uuid	—	Yes	—	FK barangay_users.id
escalated_at	timestamptz	—	Yes	—	—
escalation_notes	text	—	Yes	—	—

mdrrmo_report_barangay_assignment_events

History of barangay assignment, reassignment, recall, and coordination events.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK

Column Name	Type	Length	Nullable	Default	Key
report_id	uuid	—	No	—	FK mdrrmo_reports.id
assignment_id	uuid	—	Yes	—	FK mdrrmo_report_barangay_assignments.id
from_barangay_id	uuid	—	Yes	—	FK barangays.id
to_barangay_id	uuid	—	Yes	—	FK barangays.id
event_type	text	—	No	—	CHECK
actor_id	uuid	—	Yes	—	—
actor_role	text	—	No	—	—
notes	text	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

mdrrmo_report_barangay_crew_members

Barangay staff selected for an MDRRMO coordination assignment, with their response roles.

Column Name	Type	Length	Nullable	Default	Key
assignment_id	uuid	—	No	—	FK mdrrmo_report_barangay_assignments.id; PK composite
barangay_id	uuid	—	No	—	FK barangays.id
member_id	uuid	—	No	—	FK barangay_users.id; PK composite
member_name_snapshot	text	—	No	—	—
crew_role	text	—	No	—	CHECK
selected_at	timestamptz	—	No	now()	—

Assistance, facilities, and routes

Requests for outside support, shelters, hospital destinations, and route hazards.

barangay_assistance_requests

Barangay requests for manpower, resources, equipment, or MDRRMO assistance.

Column Name	Type	Length	Nullable	Default	Key

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
barangay_id	uuid	—	No	—	FK barangays.id
requested_by	uuid	—	No	—	FK barangay_users.id
incident_report_id	uuid	—	Yes	—	FK barangay_reports.id
incident_title	text	—	Yes	—	—
needs_more_manpower	boolean	—	No	false	—
needs_resources	boolean	—	No	false	—
needs_equipment	boolean	—	No	false	—
beyond_barangay_capability	boolean	—	No	false	—
explanation	text	—	No	—	—
status	text	—	No	'pending'	—
decision	text	—	Yes	—	—
dispatcher_notes	text	—	Yes	—	—
decided_by	uuid	—	Yes	—	FK barangay_users.id
decided_at	timestamptz	—	Yes	—	—
team_acknowledged	boolean	—	No	false	—
created_at	timestamptz	—	No	now()	—

resource_requests

General responder or goods request sent for dispatcher review.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
requested_by	uuid	—	No	—	FK users.id
request_type	text	—	No	—	—
sub_type	text	—	Yes	—	—
details	text	—	No	—	—

Column Name	Type	Length	Nullable	Default	Key
dispatcher_notes	text	—	Yes	—	—
incident_id	uuid	—	Yes	—	FK incidents.id
status	text	—	No	'pending'	—
created_at	timestamptz	—	No	now()	—
mdrrmo_report_id	uuid	—	Yes	—	FK mdrrmo_reports.id

evacuation_centers

Evacuation-center directory, location, capacity, and active state.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
address	text	—	Yes	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
barangay_id	uuid	—	Yes	—	FK barangays.id
active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—
max_capacity	integer	—	No	100	—
is_active	boolean	—	No	true	—
created_by	uuid	—	Yes	—	FK barangay_users.id
updated_at	timestamptz	—	No	now()	—

hospital_directory

Hospital directory with coordinates used to show nearest transport destinations.

Column Name	Type	Length	Nullable	Default	Key
id	text	—	No	—	PK
name	text	—	No	—	—
address	text	—	No	—	—
municipality	text	—	No	—	—
province	text	—	No	'Bulacan'	—

Column Name	Type	Length	Nullable	Default	Key
latitude	double precision	—	No	—	CHECK
longitude	double precision	—	No	—	CHECK
source_url	text	—	Yes	—	—
active	boolean	—	No	true	—
updated_at	timestamptz	—	No	now()	—

blocked_routes

Reported road or route obstruction with its mapped location and active state.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
reported_by	uuid	—	Yes	—	FK users.id
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
description	text	—	Yes	—	—
active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

Public information and alerts

Published safety communications, advisories, and the activity stream shown to residents and staff.

public_broadcasts

Barangay or MDRRMO broadcasts, links, attachments, and publication metadata.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
barangay_id	uuid	—	Yes	—	FK barangays.id; UQ composite
author_id	uuid	—	Yes	—	FK barangay_users.id
category	varchar	50	No	'safety_advisory'	—
content	text	—	No	—	—
links	jsonb	—	Yes	[]	—
media	jsonb	—	Yes	[]	—

Column Name	Type	Length	Nullable	Default	Key
created_at	timestamptz	—	Yes	NOW()	—
updated_at	timestamptz	—	Yes	NOW()	—
author_user_id	uuid	—	Yes	—	FK users.id
is_mdrrmo	boolean	—	No	false	—
is_from_mdrrmo	boolean	—	No	false	—
is_pinned	boolean	—	No	false	—
reposted_by	text	—	Yes	—	—
reposted_from_id	uuid	—	Yes	—	FK public_broadcasts.id; UQ composite

weather_advisories

Weather or hazard advisory text, source, severity, activity, and expiry.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
title	text	—	No	—	—
type	alert_type	—	No	—	—
level	alert_level	—	No	'normal'	—
message	text	—	No	—	—
source	text	—	No	'system'	—
external_url	text	—	Yes	—	—
active	boolean	—	No	true	—
expires_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

alerts

Municipal alert record with severity, affected area, acknowledgement, and resolution.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
title	text	—	No	—	—
description	text	—	No	—	—
type	text	—	No	—	—
severity	risk_level	—	No	—	—
affected_area	text	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
data_source	text	—	No	—	—
status	alert_status	—	No	'active'	—
acknowledged_by	uuid	—	Yes	—	FK users.id
acknowledged_at	timestamptz	—	Yes	—	—
resolved_by	uuid	—	Yes	—	FK users.id
resolved_at	timestamptz	—	Yes	—	—
created_at	timestamptz	—	No	now()	—
updated_at	timestamptz	—	No	now()	—

activity_feed

Recent public-safety and monitoring events summarized for dashboard feeds.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
type	text	—	No	—	—
title	text	—	No	—	—
description	text	—	Yes	—	—
severity	risk_level	—	Yes	—	—
data_source	text	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

Environmental monitoring and municipality map

Weather, earthquake, river, dam, hazard-area, and boundary data shown on situation maps.

weather_forecasts

Forecast observations and conditions by forecast time.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
forecast_type	text	—	No	—	—
forecast_time	timestamptz	—	No	—	—
temperature	double precision	—	Yes	—	—
humidity	double precision	—	Yes	—	—
wind_speed	double precision	—	Yes	—	—

Column Name	Type	Length	Nullable	Default	Key
wind_direction	double precision	—	Yes	—	—
rainfall_probability	double precision	—	Yes	—	—
weather_condition	text	—	Yes	—	—
data_source	text	—	No	'open-meteo'	—
created_at	timestamptz	—	No	now()	—

hazard_zones

Named hazard areas and GeoJSON geometry for map overlays.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	—	—
type	text	—	No	—	—
severity	alert_level	—	No	—	—
geometry	jsonb	—	Yes	—	—
description	text	—	Yes	—	—
active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

earthquakes

Earthquake event details, coordinates, magnitude, intensity, and source.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
phivolcs_id	text	—	Yes	—	—
magnitude	double precision	—	No	—	—
depth	double precision	—	Yes	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
location	text	—	No	—	—
intensity	text	—	Yes	—	—
occurred_at	timestamptz	—	No	—	—
felt	boolean	—	No	false	—

Column Name	Type	Length	Nullable	Default	Key
source	text	—	No	'phivolcs'	—
external_url	text	—	Yes	—	—
created_at	timestamptz	—	No	now()	—

river_stations

River monitoring stations and warning or critical thresholds.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
station_name	text	—	No	—	—
station_code	text	—	No	—	—
river_name	text	—	No	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
warning_level	double precision	—	No	—	—
critical_level	double precision	—	No	—	—
status	alert_level	—	No	'normal'	—
active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

river_levels

Timestamped water-level observation and trend for a river station.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
station_id	uuid	—	No	—	FK river_stations.id
water_level	double precision	—	No	—	—
trend	text	—	Yes	—	—
level	alert_level	—	No	'normal'	—
recorded_at	timestamptz	—	No	—	—
created_at	timestamptz	—	No	now()	—

dam_stations

Dam monitoring station coordinates and operating thresholds.

Column Name	Type	Length	Nullable	Default	Key

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
dam_name	text	—	No	—	—
dam_code	text	—	No	—	—
latitude	double precision	—	No	—	—
longitude	double precision	—	No	—	—
warning_level	double precision	—	No	—	—
critical_level	double precision	—	No	—	—
normal_water_level	double precision	—	No	—	—
status	alert_level	—	No	'normal'	—
active	boolean	—	No	true	—
created_at	timestamptz	—	No	now()	—

dam_levels

Timestamped water-level and discharge observation for a dam.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
dam_id	uuid	—	No	—	FK dam_stations.id
water_level	double precision	—	No	—	—
discharge_rate	double precision	—	Yes	—	—
trend	text	—	Yes	—	—
level	alert_level	—	No	'normal'	—
recorded_at	timestamptz	—	No	—	—
created_at	timestamptz	—	No	now()	—

municipality_info

Municipality-level map reference point and current risk summary.

Column Name	Type	Length	Nullable	Default	Key
id	uuid	—	No	gen_random_uuid()	PK
name	text	—	No	'Norzagaray'	—

Column Name	Type	Length	Nullable	Default	Key
latitude	double precision	—	No	14.9042	—
longitude	double precision	—	No	121.0430	—
current_risk	risk_level	—	No	'low'	—
updated_at	timestamptz	—	No	now()	—

municipality_boundary_config

Current municipality boundary geometry and display revision.

Column Name	Type	Length	Nullable	Default	Key
municipality_key	text	—	No	—	PK
geometry	jsonb	—	Yes	—	—
is_enabled	boolean	—	No	false	—
revision	integer	—	No	0	CHECK
updated_by	uuid	—	Yes	—	—
updated_at	timestamptz	—	No	now()	—

municipality_boundary_history

Saved versions of municipality boundary geometry and display settings.

Column Name	Type	Length	Nullable	Default	Key
municipality_key	text	—	No	—	PK composite
revision	integer	—	No	—	PK composite
geometry	jsonb	—	No	—	—
is_enabled	boolean	—	No	—	—
updated_by	uuid	—	Yes	—	—
updated_at	timestamptz	—	No	now()	—

PostgreSQL enum values

These enumerated types appear in the fields listed above. Text fields may also have separate CHECK constraints.

Enum Type	Allowed Values
user_role	master_admin, admin, logistics, dispatcher, responder
unit_type	police, fire, medical, Rescue Officer, Swift Water Rescue Officer, Mountain Rescue Officer, Emergency Medical Responder (EMR), Ambulance Officer / EMS Personnel, Fire Response Officer, Evacuation Officer, Safety & Security Officer, Traffic & Road Clearing Officer, Communications Officer, Logistics Response Officer, Damage Assessment Officer

Enum Type	Allowed Values
user_status	active, inactive, pending_verification, occupied, rejected
report_status	pending, verified, rejected, responding, escalated, resolved
alert_level	normal, warning, critical
alert_type	weather, flood, earthquake, dam
alert_status	active, acknowledged, resolved
risk_level	low, moderate, high, critical
barangay_role	admin, dispatcher, responder, staff