



GROUND FLOOR PLAN SCALE 1:100

GENERAL NOTES AND SPECIFICATION

- Foundation: strip footing 675mm wide x 225mm thick, 1:3:6 concrete, base at 900mm. 4 courses of 9 inch blocks filled with concrete below DPC.
- Floor: 150mm oversite concrete 1:2:4 on DPM on 300mm laterite filling, walkway 100mm thick with 1:3 screed.
- Walls: 9 inch sandcrete blocks to all walls, 3.6m high. Lintel 225 x 225mm all round, 4 no. 12mm rods.
- Columns: 225 x 225mm, 14 no., 4 no. 12mm rods. Walkway posts 225 x 225mm, 7 no.
- Roof: mono-pitch, long-span aluminium 0.55mm on 2x6 inch hardwood rafters at 900mm and 2x4 inch purlins, roof covers walkway.
- Shop fronts: galvanised steel roller shutter 3.0 x 3.0m to each shop (6 no.).
- Finishes: cement screed floors to shops, ceramic tiles to WCs. Emulsion inside, textured paint outside. No ceiling to shops.
- Services: 2 WC, 2 basins, 1 no. 2000L tank. Per shop 2 light points, 3 double sockets and 1 prepaid meter. 1 distribution board.

DOOR SCHEDULE

- D2 Hardwood panel door 0.8 x 2.1m (WC): 2 no.
- Roller shutter 3.0 x 3.0m: 6 no.

WINDOW SCHEDULE

- W2 Louvre window 0.6 x 0.6m (WC): 2 no.
- Fanlight above shutters: 6 no. 3.0 x 0.4m

All dimensions in metres unless stated. Do not scale. Contractor to verify on site.

Obinna Okafor Architects
REGISTERED WITH ARCON

PROJECT

Row of Six Lock-up Shops

SITE

Plot 45, Ogui Road, Enugu, Enugu State

CLIENT

Mrs Ngozi Eze

DRAWING

Ground floor plan

DRAWING NO.

KS-05/A-101

SCALE

1:100 at A3

ARCHITECT

Obinna Okafor, MNIA

STATUS

For pricing



NORTH