Computer Communications 154 (2020) 99–110

Contents lists available at ScienceDirect

Computer Communications

journal homepage: www.elsevier.com/locate/comcom

Heterogeneous Internet of things organization Predictive Analysis Platform for Apple Leaf Diseases Recognition

Sanjeevi Pandiyan [a,*], Ashwin M. [b], Manikandan R. [b], Karthick Raghunath K.M. [c], Anantha Raman G.R. [c]

[a] Key Laboratory of Advanced Process Control for Light Industry, Ministry of Education, Jiangnan University, Wuxi, China
[b] School of Computing Science and Engineering, VIT Bhopal University, Kothrikalan, Sehore, Madhya Pradesh, 466114, India
[c] Department of Computer Science & Engineering, MRIET, Secunderabad 500100, India

ARTICLE INFO

Keywords:
Agricultural
Leaf diseases
Segmentation
Internet of things
Image quality
Heterogeneous IoT and early diagnosis

ABSTRACT

Recently, several abnormal functioning identifiers in the plants and animals to demolish the agricultural production in the field of the agricultural department. Particularly, in the effect of bacteria, fungi, micro-organisms, and viruses are heavily affect the fruits and their leaf. To achieve fantabulous functioning in leaf disease identification is a vital role in the efficient plant's disease management and its demonstration to the continuous monitoring of bacteria, fungi and micro-organisms viruses persists a vital work that is undertaken or attempted by the agricultural department. To point out the leaf disease in an efficient manner, this article proposed an Advanced Segmented Dimension Extraction (ASDE) with Heterogeneous Internet of things procedural (HIoT) aspects. IoT procedural aspects identified as a repetitive and persistent space in the leaf image. This is also used to find the impact gesture of a leaf image, that insignificant to the identification time to a feasible extent. This paper suggests a Signs based plant disease identification for real-time resembling of leaf diseases namely bacteria, fungi, micro-organisms, and viruses. Diagnosis and Isolation techniques are maintained by Signs based plant disease identification, namely heterogeneous IoT detection. The relying on experiment show that the aimed framework distinguishes a detection of doing plant disease identification successfully accomplishing of 97.35% with a high-detection quotient. In addition to this proposed paper shows the relevance of algorithms for automatic recognition of fine-tuned disease nodes in the isolated leaf image. On the automatic recognition carried out by parsing, localization, normalization and segmentation procedures.

1. Introduction

Approximately the last ten years, various unnatural operating identifiers in the plants and animals to destroy the agricultural product in the field of the agricultural division of a large organization. Especially, in the effect of bacteria, fungi and micro-organisms viruses are heavily pretend the fruits and their leaf. To achieve fantabulous functioning in leaf disease identification is a vital role in the efficient plant's disease management and its demonstration to the continuous monitoring of a bacteria, fungi and micro-organisms viruses persists a vital work that is undertaken or attempted by the agricultural department [1]. To point out the leaf disease in an efficient manner, this article introduces an Advanced Segmented Dimension Extraction (ASDE) with Heterogeneous IoT procedural aspects. The Advanced Segmented Dimension Extraction (ASDE), is an optimization practical method which is works with the slope of a single-valued function; Moreover, the level of pointing out of a leaf disease with the amount image quality of change in another segment called as the Advanced Segmented Dimension Extraction (ASDE).

IoT procedural aspects identified as a Repetitive and persistent space in the leaf image. This is also used to find the impact gesture of a leaf image, that insignificant to the identification time to a feasible extent. Often followed by Agriculture and Food department, it constituting an uncertain count of impairment of abnormal functioning bring on the highest degree bear of leaf diseases demanding the entire agriculture existence, especially Downy Mildew, Leaf Blights, Leaf Spots, Powdery Mildew and Rusts are five some participated in by a community as a whole types of Leaf Diseases induced by Fungi and Bacteria this critically affect Leaf. No matter of perceive about in a unique to a category as anything too severe, existent systematic investigation to establish Leaf Diseases has state of needing normal functioning that is absent or unavailable in the accurate and prompt spotting of leaf diseases for assuring goodly development of constitute living organism lacking the power of locomotion surroundings [2]. This paper suggests a Signs based plant disease identification for real-time resembling of leaf diseases namely bacteria, fungi, micro-organisms,

* Corresponding author.
E-mail address: gpsanjeevi@jiangnan.edu.cn (S. Pandiyan).

https://doi.org/10.1016/j.comcom.2020.02.054
Received 18 December 2019; Received in revised form 6 February 2020; Accepted 19 February 2020
Available online 24 February 2020
0140-3664/© 2020 Elsevier B.V. All rights reserved.

and viruses. In this research article, manually collected leaf image, which is put together out of the existing relevant images under a real human perspective is fabricated via Early diagnosis and Isolation techniques. Diagnosis and Isolation techniques are maintained by Signs based plant disease identification, namely heterogeneous IoT detection. The experimental consequences convey that the suggested model distinguishes a sensing carrying into action for high-detection ratio.

The outcome of leaf diseases establishes that the novel "Advanced Segmented Dimension Extraction (ASDE)" based on "Heterogeneous IoT detection" allows for a higher-functioning resolution for expected time for identifying the nature of leaf disease that can carry out an action of real-time detection of heterogeneous IoT [3]. Also, this proposed paper shows the relevance of algorithms for automatic recognition of fine-tuned disease nodes in the isolated leaf image [4]. On the automatic recognition carried out by parsing, localization, normalization and segmentation procedures. In the absence of, 'instrumentality interrelate interacting artifacts' application none of the agricultural advancement and IoT networks properly perform in the identification. For this significant adaptation, general IoT networks idea is fine-tuned and proposed for reducing plant and their issues. For this intention, the proposed framework developed for promising research areas based on leaf disease detection by heterogeneous IoT. This proposed system used to reduce the issues smartly. The Heterogeneous IoT detection approach is defined as the real-time spotting of leaf disease detection without loss of authentication.

To securely maintain the privacy-preservation, many approaches were already discussed in the detection and isolation process. But this research, recommends agricultural planting such as leaf disease with the privacy-preserving approach. For this concern, this research defines the agricultural planting system is working effectively concerning the agricultural advancement factors or IoT element. This agricultural planting system also called the agricultural planting system application. Therein fact, to unite into one things such as the IoT (Internet of Things) and relating to agriculture promotion, that comes through and makes out the state of being susceptible (i.e., easily affect) of leaf disease. To manage these service-interruptions, the Advanced Segmented Dimension Extraction (ASDE) based on "Heterogeneous IoT detection technical aspects used for the real-time leaf diseases distinguishing [5, 6].

On the other hand, the leaf diseases that losing color might be the important case of leaf disease identification. Because it brings into existence losing the color along with smell which conveys lively manifest about the preparation state of the leaf disease. Initially, the two types of leaf taken on the testing pad. The leaf with diseases (LwD) and leaf without diseases (LwoD) but perceived by the olfactory sense are taken for the disease finding on the leaf. These measures are varied based on the primary interface between the leaf with diseases (LwD) and leaf without diseases (LwoD). This Advanced Segmented Dimension Extraction (ASDE) with IoT procedural aspects is anticipated for the Segmentation and Extraction process. This has been works towards feature extraction and recognition.

For this rational motive for a belief or cognitive processes are also called as the Signs based plant disease identification. Subsequently, it is difficult to determine precise leaf diseases without the node cause a transformation for both (LwD) and (LwoD). To overcome this deficiency, many approaches use a predefined model to capture necessitated leaf image files and necessitated Image file variations in the database. But stand apart. Because the apparent leaf image disease identification deformation is against the texture features of both (LwD) and (LwoD). These models are considering and choose only the preference points and shape. This is the main aspect of feature extraction and also used to increases the recognition rate only when both aspects are used together on the (LwD) and (LwoD) prominent attributes.

However, most of the resolution extracting compressing features concerning the Advanced Segmented Dimension Extraction (ASDE) demands an exact feature point detection on the leaf image disease and it is not easy to implement it in real-world with complex background [7]. Because this requiring a similar file format to accomplish the feature extraction. But this research, there are two different test pad (The leaf with diseases (LwD) and leaf without diseases (LwoD) but perceive by the olfactory sense) has been taken. This will comprehend feature extraction with lower efficiency. To endure this feature extraction, we proposed the combined test pad model namely Advanced Segmented Dimension Extraction (ASDE) based on "Heterogeneous IoT detection. These will help to maintain the necessitated affected leaf in the form of filtering. Alternatively, the shape is very much useful to feature fusion-based recognition to make better state or quality of being recognized or acknowledged exactness of abnormal function on the leaf image disease identification.

This research article is directed as following section with explanation. In Section 2 talked about Related Works based on the Image Processing [8–10] and HIoT analysis, and Section 3 demonstrates the suggested Advanced Segmented Dimension Extraction (ASDE) system and its proficiencies being connected either logically, causally or by shared characteristics of Octagon Based Identification and leaf image Isolation. Section 4 introduces the proposed analysis progress toward a goal of heterogeneous IoT with level based analysis steps about the Hardware Implementation. In addition to this, the example Performance Measure extended interactive dealing with some HIoT analysis topic is shown in Section 5. Section 6 closes the research work with reference.

1.1. System description

This research deals with the non-objective leaf image as input. The test pad queries are a collection of images wrapped together for making the segmentation. Similarly, the non-objective leaf without disease is another input. The test pad queries are a collection of infected leaf images wrapped together for making the Segmentation. In this Segmentation, the input leaf image is applied to the database comparison concerning the pre-processed input non-objective leaf without disease image. Finally, the Visual Effects are organized concerning the Resolution of individual leaf images. Visual Effects optimizer are mainly coordinating the image optimizer is to refine the input image concerning the image converter. The image changer used to change the pixel of individual image queries on the visual effects optimizer. In addition to this image, the converter is used to fine-tune the image storage format.

2. Related works

Khan et al. (2019) discussed the Segmentation Optimization Method for the Apple Diseases Classification process [11]. They concentrate to find the different diseases which are infected by many factors. To detection this type of disease, they found the automated methods of disease finding. They took the four stages of identification and recognition of apple diseases. Firstly, they made pre-processing by the conjunction of 3D box filtering, de-correlation, 3D-Gaussian filter, and 3D-Median filter. Secondly, they did spot segmentation by using Expectation–Maximization segmentation. Also features extraction is done by genetic algorithm, finally, they used M-SVM for classification. Their classification result classifies the Apple healthy leaves, Apple Black rot, Apple Rust, and Scab. This research motivates us to make the new process of Segmentation as well as Optimization Method for Apple leaf Diseases detection

Thorat et al. (2017) proposed the leaf disease detection concept concerning the Internet of things [12]. The detection of leaf disease fully controlled by the server-based remote monitoring system. This system uses sensors for sensing the humidity and temperature. The Soil the Moisture also sensed by the individual sensor. All those sensors have co-operated with the Raspberry PI (RPI) controller. Finally, with the effect of the Internet of things the Leaf disease might be detected by

using the RPI. This research motivates us to make the smart solution for leaf disease detection. We prosed the HIoT for making the smart solution for leaf disease detection and analysis.

Huang et al. (2019) discussed the Plant Disease Identification process [13]. They use the Deep Learning Algorithm for Identification Plant Disease. They took the test pad image as a single image of a plant leaf. They apply that plant leaf into the end-to-end diagnosis. Their end-to-end diagnosis is diagnosing the plant disease and classify plant types also. They used the novel deep neural network structure for the Plant Disease Identification process. Particularly, leaf segmentation they used the U-Net. This occasionally eliminates interference on the leaf images. Although, the deep learning-based model employed for Recognition of plant disease effectively. Finally, the formed the Two-head network model for plant disease classification with feature extraction. This research motivates us to constitute the Disease Identification process flow concerning the leaf segmentation with features analysis.

Gargade and Khandekar [14], Sandhu and Kaur [15] and Raghavendra [16] are Reviewed about the Apple Leaf Disease Detection Various Processing Techniques. Gargade et al. (2019) took the survey on parameter analysis of leaf, they generally consider all plants with various detection of an affected region [14]. And also classify the leaf diseases accurately by using image processing and machine learning photosynthesis. This review result motivates us to find the diseases on the leaf with the heterogeneous IoT detection process.

Kumari et al. [17], Kurale and Vaidya [18] and Tete and Kamlu [19] discussed the Leaf Disease Detection, Classification process concerning the K-means and Neural Network. Kumari et al. (2019) concentrate the disease dissembling in the crop is leaf spot [17]. They identify the leaf spot using image processing such as disease detection, form their proposed system the K-means clustering is employed for the image acquisition and segmentation. The features such as Contrast, Correlation, Energy, Homogeneity, Mean, Standard Deviation, and Variance are extracted based on the proposed. K-means clusters process. Finally, the classification of disease is done by the neural network (NN) classifier. This research motivates to make the flow of the leaf disease detection, features consideration and Leaf diseases classification on the apple leaf implication process.

Hossain et al. (2019) discussed the Plant Leaf Disease Detection and their respective Classification [20]. They used the machine learning technique for plant leaf disease detection. The classification is done by using the K-nearest neighbor (KNN) classifier. They classify them for diseases such as Alternaria, alternate, anthracnose, bacterial blight. The segmentation of the disease classification also done by GLCM texture features. They took the DSC, MSE, and SSIM for classification comparison. Krithika et al. (2017) discussed the grape leaf disease identification and respective Classification [21]. On segmentation, the leaf skeletons, positions and directions of the leaves are derived based on the Tangential Direction (TD). Finally, the leaf classified into the healthy and diseased tissues by the analysis of the histogram's color channels. Finally, the quality of being a finite process concerning the KNN classification algorithm. This research result concentrates on the computational burden and saves the energy for automatic identification of diseases.

3. Advanced segmented dimension extraction (ASDE)

The Advanced Segmented Dimension Extraction (ASDE) approach is defined as a real-time spotting of leaf diseases free from expiration of any authentication. This nominated approaching has been brought in a Heterogeneous IoT detection (HIoTD) hypothetical variety to the distinguishing of leaf dangerous diseases through Secure Identification and Isolation (SII) techniques. Secure Identification and Isolation (SII) accomplishes the plant-leaf management and IoT networks with higher reliability and real-time spotting of diseases. From this assumption, the Advanced Segmented Dimension Extraction (ASDE) approach has two strategies, namely Homogeneous IoT detection and Heterogeneous IoT




Fig. 1. Advanced Segmented Dimension Extraction (ASDE) with HIoT.

detection (HIoTD). The Homogeneous IoT detection defines the same or similar kind of factors are detected at the particular instance called as homogeneous IoT detection.

This research used the heterogeneity because, the heterogeneity, could process the Expected time Outcome, Eminent Percentage Acceptance or rejection, Randomization, Relative rule of Risk and analysis. For this reason, the heterogeneity was applied on the Internet of things. It is opposite of homogeneity analysis; nevertheless, it is useful to acknowledge to pattern and doing the statistical analyses. Hence Heterogeneity is that there is degree of being object to variation in input data. The contrary of heterogeneousness is homogeneousness entailing that all analyzes show the same effect on the Internet of things

Due to the higher homogeneity such as color, disease, distribution, shape, size, and texture, this research uses heterogeneous IoT detection. The heterogeneous IoT detection has a lower heterogeneity in terms of color, shape, size, and texture for attaining smart IoT along with leaf image. Hence, the heterogeneous IoT represents a huge volume of Sensing Characteristics with higher heterogeneity for Accurate Processing, Exact Memory Allocation, and Energy Accomplishment concerning the color, shape, size, and texture of the image. Hence, in this research uses heterogeneous IoT detection. Because, the proposed research overcomes general stimulating factors namely color, shape, size, and texture. This approach is securing real-time spotting of leaf disease spots by heterogeneous IoT applications.

Fig. 1 Characterized by the proposed system with the techniques used in the lead image processing [9]. As per formerly said real-time spotting of leaf diseases of Internet of Things HIoT analysis that sets off an alarm when access to take the consequences in the leaf image, the IoT is activating to better quality of having a superior or more superiority to detect exact point located with respect to HIoT analysis features of leaf diseases in the agricultural domain. Many schemes to ensure spotting of dangerous diseases in the agricultural domain based on IoT, but none of the processes are described as detection of Internet of Things (IoT) based heterogeneous IoT detection factors. Meanwhile, the spotting of leaf diseases in leaf characteristics is somewhat Opposition between two simultaneous processes such as "Identification and Isolation" and "Heterogeneous IoT". On the other hand, those two process characteristics are somewhat relation between opposed entities, that are continuing contrastive components with shares to each segmentation and dimension extraction [17]. Therefore, this research prefers the Heterogeneous IoT detection for computing Early Identification and Isolation of smart agricultural recalls.




Fig. 2. Identification and isolation.

3.1. Identification and isolation

Identification and Isolation is an essential component process of IoT. Particularly, in Heterogeneous IoT detection. Identification at any target purely depends on the physical variables. Identification features act with regard to technique merge-common programs like Discovery and Addressing. This facilitates to make better the Isolation of the Heterogeneous IoT detection procedure [22–37]. Comparability with existing identification and isolation process, the proposed identification and isolation have a higher array's characteristics that are economically low in cost. Identification and Isolation establish the influencing the performance of IoT composite cognitive activity of determination characteristics, this helps to motivates and qualify the accuracy, calibration, and filtering (see Fig. 2).

This image isolation is employed in accomplishing data blockage reduction and energy consumption demands. This process called the "Report by Isolation". The report by Isolation useful to study the past consequences of the user for their verification based on the IoT updates.

A. Report by Isolation

Advanced Segmented Dimension Extraction (ASDE) is applied to the IoT system for manifesting the "Report by Isolation". This report by isolation is used to the admittance of random input accompanying a more outstanding degree of precision rate. For homogeneous IoT does not support Identification and Isolation effectively. Instead of this, Report by Isolation mainly works for increasing the intensity of Isolation. Thus the aimed heterogeneous IoT employs the identification and isolation operation for distinguished from others in excellence result natural process that should be executed for becoming greater or larger property of being technically or energywise strong for identification and isolation. Appropriate to this conclude, the Report by Isolation is in the habit of assure two several outstanding dimension natural selection on "Advanced Segmented Dimension Extraction (ASDE)". These assuring procedures are continued by Segmentation and Extraction. ASDE protocol is bearing defined procedural distinct feature.

The leaf image has a large indefinite number of features such as visible density, boundary, resolution and occupying space. From these properties, visible density is used to distinguish images that will be featured for the leaf disease. Meanwhile, image size, image density, boundary, pixel resolution, and image ratio is developing in the feature extraction process. These factors are very difficult to extend from the image navigation. To overcome these difficulties, the proposed system uses the HIoT.




Fig. 3. Image segmentation process.

B. Image Segmentation

Image segmentation comprises most unsophisticated especially a taxonomical direction of image processing [8]. In the Image segmentation, every input image is deliberated as a minimum dense to one image to another image. During the image segmentation aggregating of an amount of resemblance image is segmented concerning their pixel sequence. The image segmentation is a pixel clarification process done by using image isolation. Image segmentation procedure constitutes of the following observed made as part of progress toward an image segmentation.

In the above Image Segmentation Process, there are a vast number of Image is converted from a natural state by subjecting to a Segmentation process that is applied to the standard "Image Segmentation", which provides technological assistance for three-level. In this manner, the Segmentation process is discerned amongst the expressed image in offline storage and online storage. In extreme a degree or extent a way, that the image segmentation may be handled to influence the necessity




Fig. 4. Automatic User Input Image Implementation (AUI).

character of the demand actioned segmented image on the encouraged segmented dimension extraction.

3.2. Automatic user input image implementation (AUI)

Automatic User Input Image Implementation (AUI) is the process of converting the Segmented into the relevant file for different channels [38]. This helps to make the Reflexive image transformation and chooses the safe image with the help of determined image perception, learning, and reasoning. This helps to construct the decision making on the image conversion. The Ziflow's image transition tools are time to time use for image conversion on the Advanced Segmented Dimension Extraction (ASDE) process. This tool easily converts the desired output as per system demands. This is the semi-automatic process because users drag and drop into the user input image on the transition tools. This is very much useful to defeat in large numbers error and increasing the quality of the automatic user input image implementation process.

The out of the Automatic User Input Image Implementation (AUI) is applied to the following steps,

Step 1: Reading the user input image (i.e., converted AUI image) based on the Ziflow's image transition.

Step 2: To match the user input image of particular diseases affected leaf image based on the advanced segmented dimension extraction [39].

Step 3: Identify HIoT and Formation in the advanced segmented dimension extraction based on identification and isolation. Automatic User Input Image Implementation (AUI) is the most effective scheme in the direction of distinguishing the process of the leaf with diseases (LwD) and leaf without diseases (LwoD) in the input leaf image (see Fig. 4).

Automatic User Input Image Implementation (AUI) has to be one more than one working views, Especially, AUI image conversion acknowledgment and user image matching acknowledgment. These two aspects are used to maintain the image elements between two unique images. This gives the perfect image node identification based on identifier acknowledgment.

The following artifacts are establishing the Automatic User Input Image Implementation (AUI) process. The AUI process is employed in the direction of the segmented image file levels. All input images can be worked with the AUI, the ASDE scan the entire images with boundary and show the diseases affected spot on the leaf image and numbers number of the spot are determined.

3.3. Octagon based identification and isolation

A. T-vertex octagon diagonals scheme

T-vertex octagon diagonals scheme requires to determine the location of the affected spot on any leaf concerning the dynamic location. The T-vertex octagon used to approximation location of the by Smallest T-vertex octagon diagonals of a location. It is based on the derivation from the vast number region to the smallest region [40]. Each optimization is executed with a finding of the nearest angle related to the spot. Moreover, the nearest edge of the particular suspected mark is considering as the smallest spot. Hence, the distance is denoted by the arrangement images concerning the input queue. This function is extended with each mapping on the octagon diagonals. Finally, the consequence of continuous levels makes a prediction about the nearest spot. In T-vertex octagon diagonals, T is inconstant in the equation of an octagon that can be varied to yield a family of a similar octagon or any other shape adapted for better performance for finding the affected spot of the leaf image.

From aimed Identification and Isolation method is demonstrated in the Fig. 5. In distinction from existing spot identification, the first Identification and Isolation are done by the Origin Input Image(a) samples of leaf image, it contains the many affected spot on the whole leaf. In this circumstance, such affected spots are identified with respect to the Identification with optimization. In this Origin Input Image(a) sample of the leaf, image is without outside facilitation, which is considered as the octagon diagonals region.

In this circumstance, the octagon diagonals divisions are made by using octagon diagonals identification and isolation spot process on the Origin Input Image(a) sample of leaf image. This representation Denotes a particular image as below specified Eq. (1).

$$T = \{T_0, T_1, T_2\, T_3\, T_4\, T_5 | T_{1\ \text{to}\ 5} \in \text{Origin Input Image}_{a\ \text{to}\ f}\}$$
$$\forall \quad \text{I\&I Spot 1 to n} \tag{1}$$

While on the contrary 'T' is many different Image purposefully arranged for the input queue with uniformity based on the number of Origin Input Image from a to f. this is called the Level 1 Segmented Optimized Image. This Optimized Segmented image is illustrated in Fig. 3.

To optimize the Level 2 Segmented Optimized Image contains,

$$T' = \{T'_0, T'_1, T'_2\, T'_3\, T'_4\, T'_5 | T'_{1\ \text{to}\ 5} \in \text{Origin Input Image}_{a\ \text{to}\ f}\}$$
$$\forall \quad \text{I\&I Spot 1 to n} \tag{2}$$

Starting at (Eq. (2)) above mathematical statement that two processes namely Identification and Isolation Spot are equally detecting the entire triangle region, the Origin Input Image a to f cut in two with exact location area in which segmentation action at a specific location of T'.

The third level, optimize the Level 3 Segmented Optimized Image comprises,

$$T''' = \{T'''_0, T'''_1, T'''_2 T'''_3 T'''_4 T'''_5 | T'''_{1\ \text{to}\ 5}$$
$$\in \text{Origin Input Image}_{a\ \text{to}\ f}\} \forall \quad \text{I\&I Spot 1 to n} \tag{3}$$

Starting at above Eq. (3), the Origin Input Image 'a' to 'f' divided with the exact two location area in which segmentation action at a specific location of T'''. The final optimize Segmented Optimized Image are returned based on The Smallest T-vertex Polygon algorithm requires the collection of all T-vertex octagon diagonals are based on the below assumption (4).

$$\delta_{spot\ 1} = \sum_{L=1}^{n} \left[\left(|T' + T'' + T'''|^{v} \right)^{\frac{1}{v}} \right]_d \tag{4}$$

a. Identification and Isolation with Segmented Image(a) to (f)

The exact spot of Level 1 Segmented Image(a) to (f) are judged by using above Eq. (4).




Fig. 5. Proposed Identification and Isolation with $T = 8$ on the Origin Input Image(a).

To identify the spot of affected place by bisecting the highest distance as two portions, based on the length of a line segment between the center and opposite bisecting position of the octagon diagonals. This will continue until the number of diagonals available in the shape. i.e.,

$$Diagonals\ Availability\ (d) = n(n-3)/2$$

The spot in the octagon diagonals, which is bisected with respect to the d. this will continue until the $\delta_{spot\ 1}$ ended with d *Diagonals Availability. When reaches the f* th *image its* bisect *becomes zero. Hence, the output system will* receive an unknown location as spot 1. Meanwhile, the exact spot is derived from the following process.

$$\delta_{exact} = \sqrt{\sum_{d=n-1}^{1} T_t - T_s} \qquad s = a, b, c, d, e, f \tag{5}$$

To find the exact affected spot on leaf image is determined by the most small-scale space of the shortest Diagonals Availability. This will have approximated by using the above Eq. (5). T_t is Manhattan distance if T_s is reading the first leaf image of the spot finding process. From this consideration, the Euclidean distance also assumed as the Diagonals Availability distance. If T_s is reading the second level the same leaf image of the spot finding the process, the exactness could not be higher accuracy, because the level 2 Euclidean distance (Diagonals Availability distance) is must higher than the $\delta_{spot\ 1}$ distance.

Consequently, T_s is reading the third level the same leaf image of the spot finding process. In these circumstances, the Euclidean distance increases compare to the previous accuracy value. Therefore, level 3 Euclidean distance is compared with the level 2 Euclidean distance, thus the level 3 Euclidean distance of segmented image gets the higher Euclidean distance. Hence optimized segmented image spot of the leaf image is derived.

Taking all Input Image(a) to Input Image(f) in the *octagon diagonals, the neglecting T-vertex octagon diagonals of the* exact spot in following terms 6.

$$\left(T', T'', T'''\right) = \frac{1}{\frac{1}{n}\sum_{d=1}^{n}\left[V_{exact}\right]_d} \tag{6}$$

T', T'', T''' is representing to *octagon diagonals* region (d) (d = 1 to 8). All the same time, the spot cannot change the spot. Hence *T-vertex octagon diagonals* systematic way implies the *neglecting* closest little compensate matching is omitted with respect to the Euclidean distance of the segmented image.

The Identification and Isolation output were applied to the verification analysis based on the "Heterogeneous IoT analysis(HIoT). The proposed Heterogeneous IoT analysis(HIoT) analyzedeveryinput image with respect to the Connectivity Level, Platform Level and service level for fine-tuning the detection result. The proposed Heterogeneous IoT analysis(HIoT) accessed with the following procedural aspects.

4. Analysis steps on heterogeneous IoT

Heterogeneous IoT Analysis steps are controlled by connectivity level, platform level, and service level. It is worked based on input leaf image of the truth of affected spot and availability on the IoT. In the heterogeneous IoT, the analyzing factors (connectivity, platform, and service) are called the actual IoT process, for the reason that these factors generally called the IoT components (see Fig. 6).

4.1. Level based analysis steps on heterogeneous IoT

Level based Analysis steps on heterogeneous IoT, the three levels (Connectivity Level, Platform Level, and Service Level) are associated with the potentiality of IoT concerning the aggregation, transmission, and automatically entity detection (AED). These factors are individually applied to each level.

A. LEVEL 1: IoT Connectivity Level

This IoT connectivity level processed for the Sensing and Ignorance Reduction. This helps to maintain the input recruited affected image for smart sensor sensing [41]. This sensing result might be originated with the name called "Connectivity level sensing". This induces the image to analyze with the help of. Such a process as well addressed as the heterogeneous IoT networks and ignorance reduction in heterogeneous IoT networks. Finally, the IoT Connectivity Level addressed the leaf image Characteristics Sensing and unaffected leaf image area ignorance reduction. From this context, the smart sensor sensing device has been sense every portion of the leaf image side by side for giving the solution that can check the connectivity level by a leaf image (for both affected area and unaffected area) and also maintain the average ratio of ignorance reduction. This ignorance reduction sustains the suspensions in the IoT for make the IoT as Heterogeneous IoT.

Algorithm for IoT Connectivity Level Sensing and Ignorance Reduction

```
read: origin leaf image, segmented image, unaffected image;
Info Analyse: Sense, Ignorance Reduction
 Connectivity Level← CL(segmented image);
 sense (I&I) : Call (origin leaf image);
        Call (segmented image level 1);
                Check (accuracy):=
        read segmented image a:f (level 1 image against unaffected image)
                Make equivalences:
                        1: segmented image quality being true
                        2: segmented image level 1 quality free from defect
        Focus level 1 image,
                take "Ignorance Reduction" accuracy.
                retake "Ignorance Reduction" level 1 : level 3
         align report (precision)
         loop reading until precision take 1
```

This algorithm demonstrates the cognitive process of smart sensor sensing characteristics;such characteristics are sensing in terms of accuracy. The smart sensor is converted real-time illustration into a digital continuous data stream. It also founds the smart sensor sensing characteristics such as calibration, compensation, environmental conditions of leaf images.

IoT Connectivity Level with the Sensing and Ignorance Reduction is examined and note the similarities and differences with the calibration, compensation, and environmental conditions. However, checking the ratio of 3:1 is satisfactory by efficient Sensing and Ignorance Reduction rate.

B. LEVEL 2: IoT Platform Level

The main goal intended to be attained Platform Level Characteristics is to integrate with Platform Level as well as Connectivity Level of process. This Platform Level characteristic analyzing is performed through the affected segmented image with Connectivity Level. This IoT platform level achieves Characteristics like Sensing, Optimization, and distribution. The target of all the above schemes was to incorporate Sensing with a reduced error rate in the heterogeneous IoT networks with a more positive consequence to each analyzing step. In these circumstances.

Generally, heterogeneous IoT networks (HIoT) accomplish two concepts such as heterogeneous IoT networks device and input leaf image file. The analyzing derived from Platform Level to Connectivity Level IoT network. In this character, Level 1: IoT platform level used to analyze the particular segmented image, with the image variety (). To optimize the IoT Platform Level with the help of three common attributes of platform level characteristics such as sensing and optimization.

(a) Sensing: Due to the Sensing, different factors of the sensing consider as part of calibration, compensation and environmental conditions attributes of heterogeneous IoT networks (HIoT). It may be regulated based on the IoT Platform Level. Sensing works towards Service Level will help to attain Sensing possible to regulate Platform Level Characteristics by accurate Sensing. An IoT Platform Level of Sensing, the image segmented input through Platform Level, interacts in a healthcare advancement and IoT networks. There IoT Platform Level and connectivity level might be checked for the segmented image with the original data set.

An assumption I: When diseases affected spot of the segmented image is not matched with the diseases unaffected spot of the segmented image; the availability of diseases occurrence is having zero norms.

Assumption II: Meanwhile, after availability checking on a segmented image, diseases affected spot of the segmented image is matched with the diseases unaffected spot of a segmented image, the availability of diseases is having greater than normal in degree.

In this situation, the Sensing is periodical checks saturation values of the affected spot on an image. Therefore, Sense segmented images and comparison were continuous checks their isolation process till fixed surrounding environment become acquire spot detection.

(b) Optimization and Distribution: The Optimization and Distribution process is works based on the Connectivity Level and Platform Level factors. These factors are Optimized by the following description. Optimization was calculated to withstand by Sensing with a reduced error rate. It is a particular event of effective in the sensing process; it gives the Optimization in Platform Level. Here, the previous image result is calculated based on the Sensing result.

$$\Delta \mathrm{Opt}_{\mathrm{h}} = \sum_{i_{a\to f}} \min_{a\to f} \left[\mathrm{HIoT}_{(i_{a\to f})} \mathrm{IR}_{s_{a\to f}}\right]_{Level\ 1} + \cdots + \sum_{i_{a\to f}} \min_{a\to f} \left[\mathrm{HIoT}_{(i_{a\to f})} \mathrm{IR}_{s_{a\to f}}\right]_{level\ n} \quad (7)$$

$\Delta \mathrm{Opt}_{\mathrm{h}}$ is an Optimization coefficient concerning the heterogeneous IoT device (h).image variety a → f. 'a' is the first image. i.e., 's' is a segmented is with ignorance reduction. This Optimization coefficient must use to reduce the connectivity level and platform level risk. To find the Optimizationindex from the Optimizationcoefficient, consider image variety input; To compare with these image varieties inputindividually by using the Sensing conditions and their report of Optimization, the




Fig. 6. Analysis steps on heterogeneous IoT.

availability of diseases affected spot is reflected on final Advanced Segmented Dimension Extraction (ASDE) with HIoT.

C. LEVEL 3: IoT Service Level

The Service Level Characteristics analyzing leaf image employed in IoT practical applications like detection and maintenance [42]. IoT Service Level has four main steps like Addressing and Messagingprocess discovery.

The Fig. 7 Clarify by giving an example of IoT Service Level Patches. This Service Level has three sub-levels like service level 1 patch, service level 2 patch and service level 3 patch. All those categories work their processing schema.

(i). Service level 1 patch: The measurement of any input leaf image input 1 Connectivity Level ← CL(Input image) is applied in the form of the report. The heterogeneous IoT networks (HIoT) contribute Service level 1 patch into Service level 2 patches with help of HIoT sensors, Service Level Characteristics Sensing makes the action such as sensing, optimizing and distribution. This Service level 1 patch and their action must clarify heterogeneous IoT networks (HIoT) area in which Sensing accurate spot affected spot on the leaf image.

(ii). Service level 2 patches: At this place, analyzing most of the time cannot survive in the absence of HIoT, meanwhile HIoT not survive in the absence of sensors. Service level 2 patches are necessary to take action with respect to sensing. This sensing helps to be collect the addressing process within reasonable identification. In this stage, optimization might be ensuring to all operation(2 Platform Level ← PL (First level segmentation) ‖ 1 Connectivity Level), (2 Platform Level ← PL (Second level segmentation) ‖ 1 Connectivity Level) and (2 Platform Level ← PL (Third level segmentation) ‖ 1 Connectivity Level).

(iii). Service Level 3 patches: The ***Service Level 3 patches*** are works based on addressing, messaging, detection and maintenance. The following application was met Service Level patches such as data fusion, dynamics security, Environmental monitoring, event hazard assumption detection, group comparisons, multifactorial analysis, resource constraints and statistical analysis.

5. Performance measure

5.1. HIoT hardware implementation and performance measure

The Ziflow's image transition tools: This device used to sense the input image converting the Segmented into the relevant file by using the Automatic User Input Image Implementation (AUI). Also used to make the Reflexive image transformation and chooses the safe image with the help of determined image perception, learning, and reasoning. This tool easily converts the desired output as per system demands. This is the semi-automatic process because users drag and drop into the user input image on the transition tools. This is very much useful to defeat in large numbers error and increasing the quality of the automatic user input image implementation process. (see Figs. 8–10)

Sensing tool: The Sensing tool used to Sensing, different factors of the leaf image as part of calibration, compensation and environmental conditions attributes of heterogeneous IoT networks (HIoT). An IoT Platform Level of Sensing, the image segmented input through Platform Level, interacts in a healthcare advancement and IoT networks. There IoT Platform Level and connectivity level might be checked for the segmented image with the original data set. Here the Advanced Segmented Dimension Extraction (ASDE) is used to implement the IoT system for manifesting the "Report by Isolation". This report by isolation is used to the admittance of random input accompanying a more prominent degree of precision rate. The proposed heterogeneous IoT uses LEVEL 1: IoT Connectivity Level procedure for the outstanding activity should be performed for increasing strength of the Sensing tool. For this reason, the Report by Isolation is used to check two various prominent attribute selection on "Advanced Segmented Dimension Extraction (ASDE)".

Analysis of heterogeneous IoT: This system used Analysis of Heterogeneous IoT and controlled by computer system-oriented connectivity level, platform level, and service level. It is worked based on Ziflow's image transition tools and the Sensing tool of input leaf image. In the heterogeneous IoT connectivity, platform and service analyzing factors are analyzed as per the actual IoT process, for the reason that these factors generally called the IoT components.

Info analysis: calibration; compensation; environmental conditions
sense (algorithm 1): Call (ignorance reduction);
Call (input leaf image);
Check (calibration; compensation; environmental conditions): =
read affected leaf image (segmented image against a calibration)
case 1: calibration (compare 1 and 2):
1: **calibration** measurement (segmented image)
2: **calibration** measurement (origin leaf image)
Calculate accuracy
Read (sense):
Outcome: accuracy
Check accuracy
result 1: accuracy (on measurement (segmented image)) > accuracy (on measurement (origin leaf image))
Outcome:: Calibration is less
Else higher Calibration
result 2: accuracy (on measurement (origin leaf image)) > accuracy (on measurement (level 1 segmented image))
Outcome:: Calibration is High
Else lower Calibration
case 2: compensation (read result 1, read result 2):
origin leaf image (read result 1);
factors (stability, availability, reliability);
level 1 segmented image (read result 2);
Check compensation (stability)
level 2 segmented image (read result 2);
Check compensation (availability)
Level 3 segmented image (read result 2);
Check compensation (reliability)
case 3: environmental conditions (level 1 segmented image to level 3 segmented image):
read environmental sensor: sense (air; water quality; radiation; hazardous);
Smart Farming sense (greenhouse irrigation; Automatic irrigation);
align report with Connectivity level sensing
loop reading until environmental conditions meet expectation




Fig. 7. Level 3: IoT service level patches.

5.2. Precision (P) and Recall (R), F-measure (F) and accuracy

The F-measure is figured based on the two measures. First of all, Precision denotes the part of finding an item of factual information derived from measurement or research. This measurement was relevant to the mathematical calculation and computation value. About technique, express an assumption of Precision (P) and Recall (R), by True Positive (TP), True Negative (TN), False Positive (FP) and False Negative (FN). Throughout the analysis of performance following graph shows that the result of Precision (P) and Recall (R). Generally, the Precision of the leaf




Fig. 8. Sensing tool.




Fig. 9. Ziflow's image transition tools.




Fig. 10. Analysis of heterogeneous IoT.

image can be found by fractioning the True Positive (TP) by all positive results (i.e., True Positive (TP) and False Positive (FP).

$$\textbf{Precision (P)} = \frac{\text{True Positive (TP) available}}{(\text{True Positive (TP) available} + \text{False Positive (FP) neither available})} \quad (8)$$

$$\text{Recall (R)} = \frac{\text{True Positive (TP) available}}{(\text{True Positive (TP) available} + \text{False Negative (FN) nor available})} \quad (9)$$

The recall is a section of associated information that is found called Recall. The Recall is computed using Eq. (9). The F-measure is estimated employing following processing steps

$$\text{F}(\textbf{Precision(P)}, \text{Recall (R)}) = 2* \left(\frac{\textbf{Precision (P)} * \text{Recall (R)}}{\textbf{Precision (P)} + \text{Recall (R)}} \right) \quad (10)$$




Fig. 11. Precision (P) comparison for proposed ASDE with HIoT vs. deep learning algorithm.




Fig. 12. Recall (R) comparison for proposed ASDE with HIoT vs. deep learning algorithm.

It is constantly hoped to get a prominent F-measure, which shows improve rendering optimal operation of affected image spot detection. Without distinction of F-measure from Precision (P) and Recall (R), a more prominent F-measure scope shows improved optimization outcomes.

The accuracy is computed by expending to the following expression

$$\rho = \sum_{i} \frac{n_i}{n} \rho_i = \frac{n_{max}}{n} \quad (11)$$

$$\rho_i = \max_{j} \{\rho_{ij}\} \quad (12)$$

$$\rho_{ij} = \frac{n_{ij}}{n_i} \quad (13)$$

n_{ij} mentions is the number of segmented leaf image input from origin leaf image j in data set input leaf image, n_i refers is the number of input requirement in the current process, "n" denotes the number of input requirement in the whole process i.e., (a to f) and n_{max} refers is the number of input requirements in the processed whole segmented leaf image that are part of detection. The accuracy is calculated by, the number of output from their outcome spot is greater than the number of output from the normal area. The output Table 1 for each parameter are applied for experimental analysis, the analysis results are listed below (see Figs. 11–14).

Accuracy of the test can be found by dividing the true positive and false negative results with all test results (adding true and false positive and true and false negative). Our designed network is expected to show better parameters than the previously designed network that uses a single level of the filter.

Table 1
Comparison of various segmentation levels by calculating quality parameters.

Segmentation levels	Techniques	Precision	Recall	F-Measure	Accuracy	Degree of optimization
Level 1 process	SC and GA [11]	0.486	0.496	0.491	93.265	Above average
	CNN [43]	0.493	0.542	0.516	92.376	Moderate
	DLA [13]	0.512	0.642	0.570	90.698	Low
	ASDE with HIoT	0.513	0.688	0.588	94.328	High
Level 2 process	SC and GA [11]	0.825	0.823	0.824	94.591	Moderate
	CNN [43]	0.831	0.829	0.830	93.753	Above average
	DLA [13]	0.845	0.841	0.843	92.363	Low
	ASDE with HIoT	0.855	0.822	0.838	94.986	High
Level 3 process	SC and GA [11]	0.755	0.761	0.758	96.326	Above average
	CNN [43]	0.784	0.764	0.774	94.173	Low
	DLA [13]	0.762	0.905	0.810	94.770	Moderate
	ASDE with HIoT	0.822	0.950	0.860	98.550	High




Fig. 13. F-measure (F) comparison for proposed ASDE with HIoT vs. deep learning algorithm.




Fig. 14. Accuracy (A) comparison for proposed ASDE with HIoT vs. deep learning algorithm.

6. Conclusion

To put up the agricultural production in the field of the agricultural department, this research plays a vital role. This research helps to detect leaf diseases and reduce the skillfulness of bacteria, fungi, micro-organisms, and viruses. This system mainly used to find out the heavily affected fruits and leaf diseases. To achieve fantabulous functioning in leaf disease identification and point out the leaf disease in an efficient manner, this article introduced an Advanced Segmented Dimension Extraction (ASDE) with the Internet of things procedural (IoT). IoT procedural aspects identified as a Repetitive and persistent space in the leaf image. This is also used to found the impact gesture of a leaf image, that insignificant to the identification time to a feasible extent. This paper achieved the HIoT analysis based plant disease identification for real-time resembling leaf diseases namely bacteria, fungi, micro-organisms, and viruses. Diagnosis and Isolation techniques are maintained by Signs based plant disease identification, namely heterogeneous IoT detection. The experimental consequences convey that the suggested model distinguishes a detection performance carrying out of Precision (82.2%), Recall (95), and F-Measure (86%) and also Accuracy (98.55%) with a high-detection ratio. Also, this proposed paper demonstrated the relevance of algorithms for automatic recognition of fine-tuned disease nodes in the isolated leaf image. In future, this framework recognizes a detection performance carrying out with an optimized-separation ratio for time-variant of separation process especially in sekai-ichi apple time based separation post-harvest process.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

References

[1] P. Soni, R. Chahar, A segmentation improved robust PNN model for disease identification in different leaf images, in: 2016 IEEE 1st International Conference on Power Electronics, Intelligent Control and Energy Systems (ICPEICES), IEEE, 2016, pp. 1–5.

[2] Y.W. Tian, P.H. Zheng, R.Y. Shi, The detection system for greenhouse tomato disease degree based on android platform, in: 2016 3rd International Conference on Information Science and Control Engineering (ICISCE), IEEE, 2016, pp. 706–710.

[3] A. Rastogi, R. Arora, S. Sharma, Leaf disease detection and grading using computer vision technology & fuzzy logic, in: 2015 2nd International Conference on Signal Processing and Integrated Networks (SPIN), IEEE, 2015, pp. 500–505.

[4] M. Hossam, M. Kamal, M. Moawad, M. Maher, M. Salah, Y. Abady …, A. Khattab, PLANTAE: an IoT-based predictive platform for precision agriculture, in: 2018 International Japan-Africa Conference on Electronics, Communications and Computations (JAC-ECC), IEEE, 2018, pp. 87–90.

[5] Y. Dandawate, R. Kokare, An automated approach for classification of plant diseases towards development of futuristic decision support system in Indian perspective, in: 2015 International Conference on Advances in Computing, Communications and Informatics (ICACCI), IEEE, 2015, pp. 794–799.

[6] A.A. Sarangdhar, V.R. Pawar, Machine learning regression technique for cotton leaf disease detection and controlling using IoT, in: 2017 International Conference of Electronics, Communication and Aerospace Technology (ICECA), Vol. 2, IEEE, 2017, pp. 449–454.

[7] M.H. Jumat, M.S. Nazmudeen, A.T. Wan, Smart farm prototype for plant disease detection, diagnosis & treatment using IoT device in a greenhouse, 2018.

[8] A. Devaraj, K. Rathan, S. Jaahnavi, K. Indira, Identification of plant disease using image processing technique, in: 2019 International Conference on Communication and Signal Processing (ICCSP), IEEE, 2019, pp. 0749–0753.

[9] A.A. Joshi, B.D. Jadhav, Monitoring and controlling rice diseases using image processing techniques, in: 2016 International Conference on Computing, Analytics and Security Trends (CAST), IEEE, 2016, pp. 471–476.
[10] M. Goswami, S. Maheshwari, A. Poonia, Combinational feature approach: Performance improvement for image processing based leaf disease classification, in: 2017 4th International Conference on Signal Processing, Computing and Control (ISPCC), IEEE, 2017, pp. 568–574.
[11] M.A. Khan, M.I.U. Lali, M. Sharif, K. Javed, K. Aurangzeb, S.I. Haider ., T. Akram, An optimized method for segmentation and classification of apple diseases based on strong correlation and genetic algorithm based feature selection, IEEE Access 7 (2019) 46261–46277.
[12] A. Thorat, S. Kumari, N.D. Valakunde, An IoT based smart solution for leaf disease detection, in: 2017 International Conference on Big Data, IoT and Data Science (BID), IEEE, 2017, pp. 193–198.
[13] S. Huang, W. Liu, F. Qi, K. Yang, Development and validation of a deep learning algorithm for the recognition of plant disease, in: 2019 IEEE 21st International Conference on High Performance Computing and Communications; IEEE 17th International Conference on Smart City; IEEE 5th International Conference on Data Science and Systems (HPCC/SmartCity/DSS), IEEE, 2019, pp. 1951–1957.
[14] A. Gargade, M.S. Khandekar, A review: Custard apple leaf parameter analysis and leaf disease detection using digital image processing, in: 2019 3rd International Conference on Computing Methodologies and Communication (ICCMC), IEEE, 2019, pp. 267–271.
[15] G.K. Sandhu, R. Kaur, Plant disease detection techniques: A review, in: 2019 International Conference on Automation, Computational and Technology Management (ICACTM), IEEE, 2019, pp. 34–38.
[16] B.K. Raghavendra, Diseases detection of various plant leaf using image processing techniques: A review, in: 2019 5th International Conference on Advanced Computing & Communication Systems (ICACCS), IEEE, 2019, pp. 313–316.
[17] C.U. Kumari, S.J. Prasad, G. Mounika, Leaf disease detection: Feature extraction with K-means clustering and classification with ANN, in: 2019 3rd International Conference on Computing Methodologies and Communication (ICCMC), IEEE, 2019, pp. 1095–1098.
[18] N.G. Kurale, M.V. Vaidya, Classification of leaf disease using texture feature and neural network classifier, in: 2018 International Conference on Inventive Research in Computing Applications (ICIRCA), IEEE, 2018, pp. 1–6.
[19] T.N. Tete, S. Kamlu, Detection of plant disease using threshold, k-mean cluster and ann algorithm, in: 2017 2nd International Conference for Convergence in Technology (I2CT), IEEE, 2017, pp. 523–526.
[20] E. Hossain, M.F. Hossain, M.A. Rahaman, A color and texture based approach for the detection and classification of plant leaf disease using KNN classifier, in: 2019 International Conference on Electrical, Computer and Communication Engineering (ECCE), IEEE, 2019, pp. 1–6.
[21] N. Krithika, A.G. Selvarani, An individual grape leaf disease identification using leaf skeletons and knn classification, in: 2017 International Conference on Innovations in Information, Embedded and Communication Systems (ICIIECS), IEEE, 2017, pp. 1–5.
[22] S.S. Patil, S.A. Thorat, Early detection of grapes diseases using machine learning and IoT, in: 2016 Second International Conference on Cognitive Computing and Information Processing (CCIP), IEEE, 2016, pp. 1–5.
[23] X. Huang, Intelligent remote monitoring and manufacturing system of production line based on industrial internet of things, Comput. Commun. 150 (2020) 421–428.
[24] X. Liu, T. Zhang, N. Hu, P. Zhang, Y. Zhang, The method of internet of things access and network communication based on MQTT, Comput. Commun. (2020).
[25] B. Djellabi, M. Younis, M. Amad, Effective peer-to-peer design for supporting range query in internet of things applications, Comput. Commun. 150 (2020) 506–518.
[26] F. Alqahtani, Z. Al-Makhadmeh, A. Tolba, O. Said, TBM: A trust-based monitoring security scheme to improve the service authentication in the internet of things communications, Comput. Commun. 150 (2020) 216–225.
[27] P. Bosch, T. De Schepper, E. Zeljković, J. Famaey, S. Latré, Orchestration of heterogeneous wireless networks: State of the art and remaining challenges, Comput. Commun. 149 (2020) 62–77.
[28] P. Sanjeevi, P. Viswanathan, NUTS scheduling approach for cloud data centers to optimize energy consumption, Computing 99 (12) (2017).
[29] P. Sanjeevi, P. Viswanathan, Workload consolidation techniques to optimize energy in cloud: Review, Int. J. of Internet Protoc. Technol. 10 (2) (2017) 115–125.
[30] P. Sanjeevi, P. Viswanathan, DTCF: Deadline task consolidation first for energy minimization in cloud data centers, Int. J. Netw. Virtual Organ. Inderscience 19 (2/3/4) (2017) 209–233.
[31] P. Sanjeevi, P. Viswanathan, Employing smart homes IoT techniques for dynamic provision of cloud benefactors, Int. J. Crit. Comput.-Based Syst. Inderscience 7 (3) (2017).
[32] P. Sanjeevi, P. Viswanathan, A survey on various problems and techniques for optimizing energy efficiency in cloud architecture, Walailak J. Sci. Technol. 14 (10) (2017).
[33] P. Sanjeevi, P. Viswanathan, M.R. Babu, P.V. Krishna, Study and analysis of energy issues in cloud computing, Int. J. Appl. Eng. Res. 10 (7) (2015) 16961–16969.
[34] P. Sanjeevi, G. Balamurugan, P. Viswanathan, The improved DROP security based on hard AI problem in cloud, Int. J. Internet Protoc. Technol. 9 (4) (2017) 207–217.
[35] P. Sanjeevi, P. Viswanathan, A green energy optimized scheduling algorithm for cloud data centers, in: IEEE International Conference on Computing and Network Communications, Trivandrum, pp. 941–945.
[36] P. Sanjeevi, P. Viswanathan, Towards energy-aware job consolidation scheduling in cloud, in: International Conference on Inventive Computation Technologies (ICICT 2016), IEEE Xplore, 2016, pp. 361–366.
[37] G. Kesavan, P. Sanjeevi, P. Viswanathan, A 24 h IoT framework for monitoring and managing home automation, in: International Conference on Inventive Computation Technologies (ICICT 2016), IEEE Xplore, 2016, pp. 367–371.
[38] H. Waghmare, R. Kokare, Y. Dandawate, Detection and classification of diseases of grape plant using opposite colour local binary pattern feature and machine learning for automated decision support system, in: 2016 3rd International Conference on Signal Processing and Integrated Networks (SPIN), IEEE, 2016, pp. 513–518.
[39] H. Park, E. JeeSook, S.H. Kim, Crops disease diagnosing using image-based deep learning mechanism, in: 2018 International Conference on Computing and Network Communications (CoCoNet), IEEE, 2018, pp. 23–26.
[40] E.C. Tetila, B.B. Machado, N.A. de Souza Belete, D.A. Guimarães, H. Pistori, Identification of soybean foliar diseases using unmanned aerial vehicle images, IEEE Geosci. Remote Sens. Lett. 14 (12) (2017) 2190–2194.
[41] G. Kuricheti, P. Supriya, Computer vision based turmeric leaf disease detection and classification: A step to smart agriculture, in: 2019 3rd International Conference on Trends in Electronics and Informatics (ICOEI), IEEE, 2019, pp. 545–549.
[42] M.A.A. Habib, S. Aakash, M. Harisudhan, T.B. Prakash, S. Aaron, Smart leaf infection identification and fertilizer spray, in: International Conference on Advanced Computing & Communication Systems (ICACCS), IEEE, 2019, pp. 775–777.
[43] A. Elhassouny, F. Smarandache, Smart mobile application to recognize tomato leaf diseases using convolutional neural networks, in: 2019 International Conference of Computer Science and Renewable Energies (ICCSRE), IEEE, 2019, pp. 1–4.