

ONE COMMUNITY

Phase 1 Upgrade Implementation Plan

Version 1.2 | 29 September 2026

Service visibility in Cameroon: unified public/provider mobile, mobile-first public web, separate admin, trust, analytics and launch readiness.

Revision decision

This revised plan supersedes version 1.1 and earlier project notes wherever location consent, nearby discovery, repository boundaries or deployment sequencing conflict. The original PDF remains preserved. This is a requirements revision, not a claim that the changes are implemented.

Decision	Version 1.2 requirement
Provider account	Explicit GPS-use consent and successful operating-location capture are mandatory before account creation completes.
Skill creation	Use the saved provider location by default. No repeated GPS-consent checkbox or mandatory fresh capture for every skill.
Public discovery	Web and mobile share nearby-listing behavior after public-user location permission; manual location search remains available.
Public web	Mobile-first, listing-led home. Remove the category-card section; keep a compact optional filter.
Delivery	Two MVP repositories; feature branches, local tests, release, OVH verification, then main.

Document map

1 Product direction | 2 Platforms and repositories | 3 Scope | 4 Unified mobile | 5 Public web and search | 6 Location and consent | 7 Provider onboarding | 8 Trust | 9 Analytics | 10 EN/FR | 11 Performance and operations | 12 Roadmap and acceptance | 13 Future phases

1-3. Product direction, platforms and scope

Phase 1 tests whether public service visibility solves a real discovery problem in Cameroon. People find local providers by service, city, area and related terms, then contact them through WhatsApp, phone or email inquiry. Public discovery never requires an account.

Repository	Role
one-community-mobile-mvp	One Expo app: public discovery first; authenticated provider mode within the same app.
one-community-web-mvp	Public/provider web, separate admin UI/API and the services required for skill visibility.

Preserve 1community_app, one-community-public-mobile-app, one-community-provider-mobile and one-community-admin as source references. Do not delete or move their histories. Admin tools stay outside public/provider mobile and behind separate web access controls.

Service boundaries

Skill visibility is one domain in a future microservice ecosystem. Build only required shared capabilities now, including identity, search and notifications as justified. Repository boundaries are not service boundaries. The imported foundation still couples identity and admin SQL to the skill database; deliberate API contracts and database ownership must replace that coupling.

In scope

- Unified mobile provider tools; approved mobile cards/detail retained; public web parity and mobile-first nearby discovery.
- Mandatory provider onboarding GPS consent and saved operating location; inherited listing locations and opt-in public Near Me.
- Cameroon location structure; moderated reviews and incident reports; consistent analytics; English/French system UI.
- Optimized media, reliable low-bandwidth behavior, migration-based databases, local tests and launch monitoring.

Out of scope

Payments, subscriptions, paid placement, restaurants, hotels, rentals, drivers, real estate and AI/voice search remain future phases. Advanced maps and route planning are excluded; compact distance-based Near Me is included now.

4. Unified mobile app strategy

The mobile app opens in public discovery mode. Become a Provider and Provider Dashboard provide a clear path into provider tools without forcing visitors to register.

Area	Required behavior
Home and results	Search services, browse eligible listings, enable nearby discovery voluntarily, open skill details.
Skill detail	Gallery, description, area/city, provider profile, contact actions, all provider listings, similar listings, reviews and report issue.
Provider account	Create account only after mandatory GPS-use consent, operating-location capture and email verification. Sign in to manage an existing account.
Provider dashboard	Manage profile, skills, photos, status and analytics. No admin moderation powers.

Preserve the approved design

- Keep the approved two-column mobile skill cards where they remain readable: image, short title, area/city/category and an evidence-based trust label.
- Retain the current skill-detail journey; do not redesign it without a concrete requirement.
- Full provider detail belongs on the detail/profile screen, not on every card.
- Never label a provider approved or verified merely because the account exists or GPS was captured.

Photo viewer

Tap a listing image to open a full-screen photo viewer. Support swiping, pinch-to-zoom where available and closing back to the same detail position. Keep provider details and contact buttons outside the viewer. Load larger images only when requested.

Nearby parity

Both public clients use the same location-permission states, radius rules, eligible-listing filters and distance ranking. A visitor who declines location can still browse and search by town or area. Existing mobile search/detail functionality does not prove nearby discovery is already implemented.

5. Mobile-first public web and search parity

The public web home should lead directly into service discovery, using the mobile experience as its functional baseline. Remove the large category-card section from the landing experience. Categories remain searchable metadata and may be exposed through a compact optional filter.

Home and nearby results

- Place one intelligent search field, a concise location/Near Me control and service-listing cards near the top of the page.
- Offer an explanation and Use my location action before the first browser permission request. Once consent and permission are available, load nearby eligible listings using the shared API.
- On later visits, use the saved location preference and available permission to refresh nearby results. Do not silently reactivate a preference the user disabled.
- If permission is denied, unavailable or times out, show manual city/area search and useful general listings. Clearly label general results; do not present them as nearby.
- Use distance ranking for an empty nearby query. Text searches use the same documented relevance/distance rules on web and mobile. No result must not silently expand the radius; offer expansion explicitly.

Responsive requirements

Design for phone-width screens first. Keep touch targets practical, avoid horizontal overflow and fit cards to the available width: use the approved two-column approach when readable, otherwise one column. Wider screens may add columns. Keep filters secondary and avoid large decorative sections displacing listings.

Search and detail

Support phrases such as plumber Emana Yaounde, tailor Bonaberi and carpenter Douala. Match service fields, provider name, tags, category and structured location through one shared search endpoint. Display area before city. Paginate compact results.

Detail feature	Acceptance
Gallery and provider	Images, provider profile and truthful trust status match mobile.
Related discovery	All provider listings opens correctly; show 3-4 similar listings when available.
Contact and trust	WhatsApp, phone when available, email inquiry, report issue and approved reviews work consistently.

6. Cameroon location and GPS consent

6.1 Provider consent belongs to account onboarding

A provider must explicitly agree to GPS use for saving an operating location and making their services discoverable nearby. Consent is not preselected. Without consent, the server must refuse provider account creation; disabling a button alone is insufficient. Also require successful device location capture and confirmation that the captured place represents the operating location before account completion.

If device permission is denied, positioning fails or the device is offline, keep onboarding incomplete and provide retry instructions. Do not invent coordinates or fall back to an IP-derived position. Email verification must not bypass the consent/location check. GPS capture is not proof of a business address.

6.2 Saved profile location and listing inheritance

Each new skill inherits the saved provider operating location automatically. It does not ask for GPS consent again or require a fresh device location capture. Retain a location snapshot on each listing so an optional listing-specific override and later profile edits remain predictable.

A provider may choose another operating location for a listing or update the profile location. Device permission may still be requested by the operating system when a fresh capture is chosen; that is not a new per-skill consent requirement. Address-only edits must not leave coordinates pointing to an unrelated location. Show which location will be used.

Profile location changes must not silently move all existing listings. Offer an explicit update for selected listings. Consent withdrawal disables provider publication/discovery until consent is restored; account access needed to manage or close the account remains available. This is a proposed implementation policy for the new consent rule.

Field	Requirement
Country; region; division	Cameroon fixed; region and division required controlled lists.
Subdivision	Recommended; filtered list with Other/free-text fallback.
Town/city; area/quarter	Required; free text initially, autocomplete later.
Latitude; longitude	Required on provider onboarding. Listings inherit coordinates by default.
Capture and consent	Store accuracy, capture time/source, consent time/version and withdrawal state.

6.3-7. Data model and provider onboarding

Entity	Planned fields and behavior
Provider profile	default_country, default_region, default_division, default_subdivision, default_city, default_area, default_lat, default_lng, location_accuracy_m, location_captured_at, location_source.
Consent record	provider_id, purpose/version, accepted_at, source surface, withdrawn_at; server-recorded timestamps. Link consent evidence to verified registration.
Pending registration	Retain validated consent evidence and captured location through OTP verification; final creation checks both again.
Skill/listing	country, region, division, subdivision, city, area, lat, lng, location_source and profile-location version/snapshot reference. Sources: provider_profile, edited_for_listing, gps_current_location.

Public-user location

Public location sharing remains optional and separate from provider consent. Use visitor coordinates for the current nearby request; do not retain exact coordinates in analytics or logs. Return area and approximate distance without exposing exact provider coordinates in public payloads by default. A map is not required.

7.1 Provider journey

- Choose Become a Provider; enter account details and default operating address.
- Read and explicitly accept GPS-use disclosure; grant device permission, capture location and confirm it is the operating location.
- Verify email and complete account creation only after the server validates consent and location.
- Create a first skill with the saved location already filled in; no new consent step.
- Add optimized photos and submit for admin review. Only eligible approved providers/listings become publicly searchable.
- Return to the dashboard to manage skills, profile and analytics.

7.2 Management and existing providers

Support create/edit, photo upload/reorder/removal, preview and allowed pause/reactivate actions. Listing states: draft, pending review, active, rejected, paused and suspended. Existing providers need an explicit onboarding/backfill step before the new public pilot; missing consent must never be silently marked accepted. Plan the cutover without deleting existing records.

8. Reviews, incident reports and trust

8.1 Moderated reviews

- Public users may submit a rating, comment, optional name and optional contact.
- New reviews are pending. Admins approve, reject or hide them; only approved reviews are public.
- Providers can see approved reviews. Provider replies may be added later.
- Apply abuse controls and keep moderation actions auditable. Do not expose private contact details.

8.2 Report an incident or listing

A report is linked to the listing/provider and creates a record for the separate admin queue. Preserve existing useful support flows while introducing explicit review/report state transitions.

Reason	Examples	Admin response
Wrong information	Wrong phone, service or area	Request correction or temporarily hide.
Fake listing	Misrepresented service/provider	Investigate; suspend if justified.
Unsafe behavior	Threatening or abusive conduct	Escalate and consider suspension during review.
Inappropriate content	Images or language violating standards	Remove content or reject listing.
Other	Issue outside named categories	Triage and record outcome.

Trust and authorization

Approval, suspension and moderation are admin-only powers. Public/provider APIs must enforce ownership and role checks. GPS capture and consent are onboarding requirements; neither is a verification badge. Listings from ineligible or suspended providers must be excluded from public search and detail access according to the moderation policy.

9. Analytics review and refinement

Audit current events and tables before building dashboards. Keep useful signals, reconcile names across clients and services, and distinguish activity ratios from attributed conversion funnels. The pilot should answer whether people find services and contact providers.

Event group	Required signals
Search	search_submitted, search_no_results: query, tokens, category, coarse region/division/city/area, result_count, language, surface, query_id and mode.
Discovery	listing_impression with position/query_id; listing_view with source; provider_profile_view; all_provider_listings_click; similar_listing_click.
Contact	whatsapp_click, phone_click, email_inquiry_sent with listing/provider IDs. Count inquiry success after server acceptance.
Trust	review_submitted and incident_report_submitted; moderation outcomes where needed, without private narrative/contact data in analytics.
Provider funnel	onboarding_started, consent_step_completed, location_capture_failed, provider_registered, listing_created, listing_approved. Store coarse failure categories only.
Nearby	nearby_requested and nearby_results with outcome, radius bucket and result count; no exact visitor coordinates.

Correctness and delivery

- Record search outcomes after successful execution. Separate failed searches from zero-result searches.
- Do not collapse unrelated anonymous visitors into one user when deduplicating. Use bounded privacy-conscious event/session IDs.
- Use stable event IDs, idempotent ingestion, occurrence timestamps, bounded batches and retries. Analytics must not block discovery.
- Make ingestion failures observable. Apply retention rules and avoid exact GPS coordinates, passwords, OTPs and private inquiry/report contents.

Dashboards

Admin operations: queues, approvals, reports and suspensions. Demand: searches, no-results, coarse area/category demand and attributed contacts. Providers: their listing views, contact actions, inquiries and status. Pilot: active providers, listings, searches, contacts, issues and weekly growth.

10-11. Language, bandwidth and search

10. English/French system UI

Extract strings into translation keys. Provide EN/FR controls and persist the selected language locally. Translate search, location explanations, GPS consent, provider forms, permission errors, details, reviews/reports and common errors. Provider-written content stays in its original language. Admin translation may be deferred; automatic translation is future work.

11.1 Cameroon low-bandwidth requirements

- Use explicit search submission, compact pagination and detail-on-demand. Cancel obsolete requests and avoid duplicate fetches.
- Render small thumbnails lazily, reserve image space and load gallery originals only on demand. Optimize the inherited web illustrations before pilot use.
- Initial engineering budgets: 12-result JSON ≤ 25 KB compressed, thumbnails ≤ 30 KB, normal detail images ≤ 150 KB, initial public route JavaScript ≤ 200 KB compressed. Verify with realistic fixtures and devices.
- Cache bounded public results/reference data with age labels and revalidation. Distinguish offline, empty and failed states; do not mislabel cached nearby results as a fresh location fix.
- Compress uploads, send one image at a time initially, retain drafts, and retry failed work with bounded backoff. Use idempotency for retried mutations.
- Keep private drafts isolated by account and clear them appropriately at logout. Do not cache admin/private report content as public data.
- Test on low-end Android and throttled connections. No autoplay video or mandatory map download.

11.2 Search architecture

Begin with a tested shared search contract and indexed PostgreSQL queries. Use Meilisearch for product discovery as the required scope justifies it; update the index from authoritative service data and enforce current visibility rules. OpenSearch in this MVP is primarily for operational logs, separate from Meilisearch product search. More advanced ranking/AI follows observed demand.

Index status, provider eligibility, category and structured location fields. Implement bounded radius/distance queries and pagination for Near Me. Define identical ranking and fallback rules for web and mobile. Track slow queries and search failures.

11.3. Local operations and deployment

Use versioned migrations to build fresh local Docker databases and later provision OVH. Migration history is checksummed and transactional; preserve data and test backups/restores. A compatibility baseline is not a safe automatic upgrade for an unknown production schema.

Layer	MVP direction
Local runtime	Docker Compose plus Traefik. Keep admin, email testing and management endpoints restricted. Wi-Fi API exposure is a deliberate development override.
Monitoring	Node Exporter, Prometheus and Grafana for host/service metrics and dashboards.
Logs	OpenSearch and OpenSearch Dashboards with a log collector as needed; redact sensitive values and bound retention/resource use.
Media	Test local object-storage behavior, then OVH Object Storage. Validate types/sizes, generate image variants and control object access.
Public preview	Namecheap domain with Cloudflare Tunnel after readiness checks. Configure HTTPS, allowed origins and cookies for actual hostnames; do not publish local Mailpit or monitoring/admin tools openly.
Cloud deployment	OVH deployment from approved release. Evaluate Swarm with Traefik for PC/OVH when justified. Add deployment CI/CD near launch, using environment secrets and rollback.

Repository workflow

Clone under /c/Users/User/projects. Work on feature branches and open PRs to release. Run automated checks, provide pull/startup commands and complete local browser/device acceptance before merge. Deploy the approved release to OVH, verify it, then promote that deployed revision to main. Do not merge or publish merely because a planning document changed.

Scope discipline

Only services necessary for skill visibility belong in this pilot. Keep future ecosystem interfaces deliberate, but avoid starting every proposed microservice before its need is demonstrated.

12. Implementation sequence

Order	Workstream	Outcome
1	Approve revised baseline	Use v1.2 requirements and reconcile conflicting older notes before more feature changes.
2	Foundation acceptance	Finish web/mobile checks and review foundation PRs for release; preserve originals.
3	Identity and onboarding	Service contracts, mandatory account-level consent/capture, email verification, provider profile and existing-account transition.
4	Unified provider mode	Integrate provider screens and skill management; inherit saved location without repeat consent.
5	Nearby and public web	Shared nearby behavior, mobile-first listing-led home, no category-card section, compact filters.
6	Detail and media parity	Provider profiles, all listings, similar listings, gallery viewer and optimized storage/uploads.
7	Trust workflows	Incident reports, moderated reviews, approval/visibility rules and admin audits.
8	Analytics and EN/FR	Fix event semantics, ingestion and dashboards; translate all core flows including consent.
9	Performance and operations	Bandwidth budgets, monitoring/logging, backups and search reliability.
10	Pilot launch	Device-tested installable app, HTTPS public web/API, limited users, feedback; OVH rollout and rollback checks.

Current implementation audit - 29 September 2026

The checked provider registration endpoint reads email, phone, password, method and display name. It contains no GPS-consent or location gate. Current mobile is the public foundation with provider reference screens not yet integrated. Account-level GPS consent is therefore missing, not already satisfied.

Web and mobile foundation CI passed, and the user tested web registration/login, mobile search and opening a listing over Wi-Fi. These checks do not establish completion of nearby search, unified onboarding, consent or the revised public web design. This revision changes the document only.

12.2. Acceptance and regression tests

Area	Required evidence
Registration denial	Unchecked/missing/false consent is rejected server-side; direct API and OTP-finalization bypass attempts cannot create an account.
Registration success	Explicit consent plus valid captured operating location and verified email creates an account; store purpose/version and timestamps.
Permission failure	Denied, unavailable, timed-out or offline capture keeps onboarding incomplete with retry; no invented coordinates.
Listing inheritance	New skill inherits the saved location with no new consent UI or forced GPS request. Optional override stores the chosen snapshot.
Location lifecycle	Range/finite validation; profile updates do not silently relocate listings; consent withdrawal and existing-provider backfill are tested.
Nearby parity	Same eligible results/ranking for equivalent web/mobile inputs. Consent denial keeps manual search usable; no exact GPS in analytics.
Mobile-first web	No category-card section; listings and primary search visible on phone widths; no horizontal overflow; optional filters remain usable.
Detail and provider	Gallery, profile, all/similar listings and contacts work; only authorized providers can manage their records.
Trust and language	Moderation controls publication; reviews/reports work; EN/FR covers core public/provider flows.
Pilot readiness	Analytics consistency, slow-network budgets, migration/restore tests, monitoring, device build and HTTPS deployment checks pass.

Test both normal and denied-permission paths. Client-side validation is not a substitute for server enforcement. Record observed results and unresolved limitations; do not describe planned features as completed.

13. Future phases and developer notes

Future domains - outside this pilot

Domain	Examples and direction
Food and places	Restaurants, vendors, bars, menus, hotels, beaches and recreation; separate domain ownership.
Transportation	Car rentals, drivers and transport services; distinct domain when demand justifies it.
Vacation rentals	Short stays, guest houses and vacation homes; separate listing requirements.
Real estate	Apartment/home rentals and land sales; separate service/data model with stronger verification and reporting.
Shared reviews	Cross-domain ratings and moderation may later become a shared service.
AI assistant	Natural-language/voice orchestration over real search APIs; never invent listings.

Real estate and AI

Rental records need price, rooms, amenities, photos, availability, contacts and verification. Land records need size, location, price, title/ownership checks and permitted documents. These domains have distinct fraud risks and must not enter service-visibility Phase 1 by accident.

An eventual assistant may interpret "hotels near Down Beach Limbe" into structured domain/location filters and call the appropriate search API. Add voice only after structured data and text search are reliable.

Implementation notes and revision precedence

- Keep public/provider and admin permissions separate; share versioned API contracts without exposing admin endpoints to public clients.
- Plan migrations for consent/profile location, listing snapshots, Cameroon hierarchy, reviews/reports and analytics metadata.
- The v1.1 optional provider coordinates and future-only Near Me language are replaced by this version.
- Earlier notes requiring fresh consent/capture for every skill are replaced: consent and required capture happen during provider onboarding; skill creation inherits the saved location.
- Source reference: One_Community_Phase1_Upgrade_Implementation_Plan_v1_1.pdf (13 pages), with the user decisions recorded in this project through 29 September 2026.