Computer Organization Floating Point Coprocessor

Instruction Set Specification

Guillermo Briceño Rene Nicklich Austin Lantz

February 28, 2019

1 Introduction

This document describes the instruction set architecture for a 32-bit floating-point coprocessor. Each instruction is described with its assembler syntax in section 2.

1.1 Instruction Encoding

The twenty-three instructions can be grouped by their instruction encoding formats. The keywords rd, rs1, and rs2 stand for the 4-bit register addresses from 0000_2 to 1111_2 , corresponding to a destination register, the first source register, and second source register respectively. In single-source or immediate mode addressing, the keyword rs is used instead. Bit 31 is used to specify register or immediate addressing mode for double-operand ALU operations.

		30	25	21	17	13 0
Double-Operand	r-type:	0 opcode	rd	rs1	rs2	0
\mathbf{ALU}	i-type:	1 opcode	rd	rs		18-bit immediate
Single-Operand ALU	EXP:	0 opcode	rd	22-bit immediate		
		0 opcode	rd	0		
Load, Store,		0 opcode	rd	rs		0
Move						
Branching	В:	0 opcode	rd			22-bit immediate
		0 opcode	rd			0
No-Operation and Halt		0 opcode				0
Hall						

2 Instruction Set Specification

NOP No operation

Opcode: 00000 Syntax: NOP

Purpose: Perform no operations.

SET

Set register to floating-point value

Opcode: 00001

Syntax r-type: SET rd, #<32-bit FP value>

Purpose: Assign a 32-bit floating point value to rd.

Operation: $rd \leftarrow FPvalue$

LOAD

Load value from memory

Opcode: 00010

Syntax r-type: LOAD rd, rs

Purpose: Assign rd the value from the memory address in rs.

Operation: $rd \leftarrow M[rs]$

STORE

Store value to memory

Opcode: 00011

Syntax r-type: STORE rd, rs

Purpose: Assign memory location specified in rd to value in rs.

Operation: $M[rd] \leftarrow rs$

MOVE

Copy value from a register to another

Opcode: 00100

Syntax r-type: MOVE rd, rs

Purpose: Assign rd the value in rs.

Operation: $rd \leftarrow rs$

FADD

Add 32-bit floating-point value

Opcode: 00101

Syntax r-type: FADD rd, rs1, rs2

Syntax i-type: FADD rd, rs1, #<32-bit ? immediate>

Purpose: Performs addition on two 32-bit floating-point values from rs1 and

rs2, or an immediate in place of rs2, and stores the result in rd.

Operation: $rd \leftarrow rs1 + rs2$ or $rd \leftarrow rs1 + immediate$

Condition Codes: $\frac{NZV}{x x x}$

FSUB

Subtract 32-bit floating-point values

Opcode: 00110

Syntax r-type: FSUB rd, rs1, rs2

Syntax i-type: FSUB rd, rs1, #<32-bit ? immediate>

Purpose: Performs subtraction on two 32-bit floating-point values from rs1 and

rs2, or an immediate in place of rs2, and stores the result in rd.

Operation: $rd \leftarrow rs1 - rs2$ or $rd \leftarrow rs1 - immediate$

Condition Codes: $\frac{NZV}{x x x}$

FNEG

Negate a 32-bit floating-point value

Opcode: 00111

Syntax: FNEG rd, rs

Purpose: Performs negation on a 32-bit floating-point value from rs and

stores the result in rd.

Operation: $rd \leftarrow -rs$

Condition Codes: $\frac{N Z V}{}$

х х -

FMUL

Multiply two 32-bit floating-point values

Opcode: 01000

Syntax r-type: FMUL rd, rs1, rs2

Syntax i-type: FMUL rd, rs1, #<32-bit ? immediate>

Purpose: Performs multiplication on two 32-bit floating-point values from rs1

and rs2, or an immediate in place of rs2, and stores the result in rd.

Operation: $rd \leftarrow rs1 * rs2$ or $rd \leftarrow rs1 * immediate$

Condition Codes: $\frac{NZV}{x x x}$

FDIV

Divide two 32-bit floating-point values

Opcode: 01001

Syntax r-type: FDIV rd, rs1, rs2

Syntax i-type: FDIV rd, rs1, #<32-bit ? immediate>

Purpose: Performs division on two 32-bit floating-point values from rs1

and rs2, or an immediate in place of rs2, and stores the result in rd.

Operation: $rd \leftarrow rs1 \div rs2$ or $rd \leftarrow rs1 \div immediate$

Condition Codes: $\frac{N Z V}{x x x}$

FLOOR

Compute the floor function

Opcode: 01010

Syntax r-type: FLOOR rd, rs

Purpose: Rounds the value in rs to the nearest lowest integer and stores the

result in rd.

Operation: $rd \leftarrow |rs|$

Condition Codes: $\frac{N Z V}{x x x}$

CEIL

Compute the ceiling function

Opcode: 01011

Syntax: CEIL rd, rs

Purpose: Rounds the value in rs to the nearest highest integer and stores the

result in rd.

Operation: $rd \leftarrow \lceil rs \rceil$

Condition Codes: $\frac{N Z V}{x - x}$

ROUND Round a value

Opcode: 01100

Syntax: ROUND rd, rs

Purpose: Rounds the value in rs and stores the result in rd.

Operation: $rd \leftarrow round(rs)$

Condition Codes: $\frac{N Z V}{x - x}$

FABS

Compute the absolute value

Opcode: 01101

Syntax: FABS rd, rs

Purpose: Find the absolute value in rs and stores the result

in rd.

Operation: $rd \leftarrow |rs|$

Condition Codes: $\frac{N Z V}{x - x}$

MIN Find the smallest value

Opcode: 01110

Syntax: MIN rd, rs1, rs2

Purpose: Finds the smallest value between rs1 and rs2 and stores

the result in rd.

Operation: $rd \leftarrow min(rs1, rs2)$

Condition Codes: $\frac{N Z V}{x - x}$

 ${f MAX}$ Find the largest

Opcode: 01111

Syntax: MAX rd, rs1, rs2

Purpose: Finds the largest value between rs1 and rs2 and store the

result in rd.

Operation: $rd \leftarrow max(rs1, rs2)$

Condition Codes: $\frac{N Z V}{x - x}$

POW Compute the power

Opcode: 10000

Syntax: POW rd, rs, #<integer-value>

Purpose: Finds rs1 raised to an integer value and stores the

result in rd.

Operation: $rd \leftarrow rs^{integer-value}$

Condition Codes: $\frac{N Z V}{x - x}$

EXP Compute the exponent

Opcode: 10001

Syntax: EXP rd, rs

Purpose: Finds e raised to the value in rs and stores the

result in rd.

Operation: $rd \leftarrow e^{rs}$

Condition Codes: $\frac{NZV}{V_{z}V_{z}}$

SQRT

Compute the square root of a value

Opcode: 10010

Syntax: SQRT rd, rs

Purpose: Finds the square root of the value in rs and stores the

result in rd.

Operation: $rd \leftarrow \sqrt{rs}$

Condition Codes: $\frac{N Z V}{x - x}$

\mathbf{B}

Branch unconditionally

Branch if zero

Opcode: 10011

Syntax: B rd

Purpose: Set the program counter to the value in memory addressed

by rd.

10100

Operation: $PC \leftarrow M[rd]$

Condition Codes: $\frac{NZV}{x-x}$

BZ

Opcode:

Syntax: BZ rd, <LABEL>

Purpose: Branch to the label specified in the assembly program if

rd is equal to zero.

Operation: if (rd == 0):

 $PC \leftarrow LABEL$

Condition Codes: $\frac{N Z V}{x - x}$

 ${f BN}$ Branch if negative

Opcode: 10101

Syntax: BN rd, <LABEL>

Purpose: Branch to the label specified in the assembly program if

rd is less than zero.

Operation: if (rd < 0):

 $PC \leftarrow LABEL$

Condition Codes: $\frac{NZV}{Y-Y}$

HALT Stop program

Opcode: 10110 Syntax: HALT

Purpose: Stop the program.