Compiling Across the FHE/MPC Boundary

A continuation-based compiler architecture for programs whose cheapest backend changes mid-computation

Principal Investigator: [FILL: PI full name], [FILL: title]
Departamento de Engenharia de Computação e Sistemas Digitais (PCS), Escola Politécnica, USP — LARC
[FILL: PI institutional e-mail] • [FILL: PI ORCID / Lattes]
Co-investigator: Eduardo Morais, [FILL: role and affiliation]

Topic: *Compilers and development tools for FHE and MPC* • **Secondary:** *Privacy-preserving AI inference and training on encrypted or distributed data*

Artifact: `https://github.com/emmorais/baru` — open source, Apache-2.0

---

1 The architectural gap

Heir [?] is, by its own account and by community adoption, the de facto compiler infrastructure for homomorphic encryption: an MLIR-based stack with dialects spanning `secret`, `bgv`, `ckks`, `cggi`, library APIs for OpenFHE, Lattigo, TFHE-rs and Jaxite, and hardware targets. We take that as given. **This proposal is not an attempt to produce faster homomorphic code than Heir; inside Heir's domain that would be an engineering result, not a scientific one.**

What interests us is the boundary of that domain, which Heir's own paper draws precisely. Three consequences of a static, FHE-only lowering pipeline:

- **Secret-dependent control flow is eliminated, not executed.** `convert-if-to-select` rewrites a secret-dependent branch into `arith.select` — so both arms are evaluated. Loops with secret-dependent bounds are unsupported; `convert-secret-for-to-static-for` requires a user-supplied static upper bound.
- **Every nonlinearity must be approximated**, and the approximation is not inferred: Heir lists polynomial approximation requiring user annotation for degree and interval among its stated limitations.
- **There is no interactive protocol anywhere in the stack.** No dialect models secret sharing, garbled circuits, message rounds, or a party.

None of these is a defect. They are the correct design consequences of targeting FHE, where a ciphertext genuinely cannot branch and a comparison genuinely is not an arithmetic circuit. But together they fix a boundary, and the boundary has a cost that nobody has measured, because measuring it requires a system on both sides of it.

> **Thesis.** For an important class of programs — machine-learning inference above all — the cheapest and the *most accurate* backend changes at points *inside* the program, and the switch itself is cheap. A compiler that can only lower a whole program to one paradigm must pay the worse option everywhere. Representing the switch requires an execution model in which "the rest of the computation" is a first-class object; it is awkward in a static SSA dataflow IR and natural in a continuation-based one.

Why ML is the right witness, not an arbitrary application. A convolutional network is literally an alternation of the two regimes. Linear layers are depth-shallow, massively parallel and pack into ciphertext slots — the regime FHE was built for. Nonlinearities (ReLU, max-pool, argmax) are comparisons, which FHE cannot do and must approximate, and which secret sharing computes exactly in a few rounds. The optimal program for a CNN is therefore neither an FHE nor an MPC program but an alternation, switching at every layer boundary — and the alternation is forced by the network architecture rather than contrived by us.

2 The architecture, and what is already built

Baru is a working research compiler and runtime: one Lisp-like source language over four backends — plain interpreter, 3-party MPC (ABY3-style replicated sharing, with a malicious-with-abort mode), FHE (BFV/BGV, TFHE-rs, and a CKKS arm on OpenFHE), and ZK proofs (Binius64) — with values crossing between MPC shares and FHE ciphertexts mid-computation without being exposed.

Its evaluator is a defunctionalized continuation machine: an explicit `Continuation` algebraic data type, an `Eval/Apply` task trampoline over an explicit stack, and a step budget. Two properties follow, and we distinguish sharply between what this already delivers and what it enables.

Already delivered. *(i)* A secret-dependent conditional is a continuation frame (`If`, then `IfResultNormalize`, which reconciles a numeric result into a share of the right width and owner), so it is executed under a protocol rather than compiled into a select. *(ii)* Backend choice is per-operation, by dynamic dispatch through a `Backend`

trait, rather than fixed by whole-program lowering — which makes a mid-program scheme switch an ordinary operation, not an escape hatch. The flagship result rests on this: the MPC round trip a ReLU already requires *also* re-randomises the FHE ciphertext, so an arbitrarily deep network runs with **zero FHE bootstraps** on an engine supporting one multiplication.

Enabled, and proposed here (Thrust 3). Continuations are not yet serialized nor used to suspend at a round boundary — the transport backend blocks synchronously. Making the continuation a value turns "the rest of the protocol" into data, permitting *dynamic* round scheduling: k independent subcomputations interleaved on one party, each resumed as its message arrives. The static scheduler already shows the prize — exchange count stayed at 32 for every batch size from 1 to 8 — but only for statically known dependency graphs. We propose to generalise it and measure against the scheduler it subsumes.

3 What the boundary costs: five measured results

Full tables in Appendix A. All figures are measured elapsed times on one machine with both arms checked against the same plaintext reference.

1. The crossover is measured, and it runs both ways. In October 2026 we completed the HEIR baseline described in §4, and it produced the result this proposal is really about. Both arms evaluate the same MLP on the same weights with x^2 activation — the same function — at `HEStd_128_classic`, on one machine, each verified against the same plaintext reference.

`64x32x10`, depth 3	**Heir (CKKS)**	**2PC, LAN**	**2PC, WAN**
one inference	167.0 ms	**14 ms**	2113 ms

On LAN secret sharing wins by 11.9×**; on WAN Heir wins by** 12.7× — a **151× swing from the network profile alone**, on an identical program with nothing about the cryptography changed. Appendix A.1 has the full depth sweep. This is the first time our record has shown FHE beating the MPC arm, and it is the thesis working rather than against it: §VI.10–VI.12 measured LeNet-5 at depth 11 with secret sharing ahead by 32× on latency and 885× past the level budget. Both are true. *"Is MPC or FHE faster"* is not well-posed, and a compiler that cannot model the difference cannot make the choice.

2. The boundary is a capability cliff, not a crossover in time. At multiplicative depth 10 the HEIR pipeline dies with **SIGSEGV during key generation** — at 554 MB peak resident against the 564 MB of the depth-9 run that succeeds, so *not* an out-of-memory kill, and with no "cannot find secure parameters" message either. Depth 9 completes; depth 10 does not run at all, while the secret-sharing curve continues as a straight line (+7 ms per layer on LAN). We have not isolated whether the fault lies in HEIR's parameter selection or in OpenFHE 1.5.1; both are candidates and both are being reported upstream.

3. Approximation returns the wrong answer, at depths that occur. This is the result that makes the thesis more than a performance argument. On a depth sweep of LeNet-5, **the CKKS arm returned the wrong class at 13 levels** — the reference top-two margin was 2 quanta and the worst logit error was 15. The exact (secret-sharing) arm returned the reference class at all five depths, including margins of one and two quanta. Approximate arithmetic accumulates error through every rescale and key switch; stochastic truncation's error is a carry in the last fixed-point bit, unbiased, so it does not systematically add. Since polynomial approximation of the nonlinearity is the *only* route available to an FHE-only compiler, this is a correctness consequence of the architectural boundary, not a tuning issue.

4. The performance margin is a choice of regime — so a compiler must model the regime.

Regime (LeNet-5, same network, same machine)	**2-party SS**	**CKKS**	**Margin**
Latency, one inference (50 ms RTT, 100 Mbps)	1.41 s	43.8 s	32×
Throughput, batch 8 (after operand fusion)	0.363 s	2.86 s	∼8×
Level budget exceeded (forced to bootstrap)	1.52 s	1345.1 s	885×

There is also a discontinuity *below* the bootstrap cliff: 13 to 15 levels forces ring $2^{15} \to 2^{16}$ and cost 61.1 → 160.0 s — 2.6× for two levels, while multiplication count moves 1.9%. Security parameters, not work. Over the same sweep the secret-sharing curve is a straight line. A line against a staircase: that shape is the compiler's decision surface.

5. The language surface determines round complexity. Writing the same CNN in BARU the way one writes a CNN in a scalar language — a loop over sliding windows, comparison per activation — costs **507 920**

messages. Exposing already-existing batched primitives (`lt_batch`, `mul_batch`, `a2b_batch`) to the *language*, then fusing ReLU with rescale, takes the identical computation to **33 106 messages** and the private diagnosis from 794 508 ms to **911 ms** — 872×, with every integer path bit-identical throughout. The frontend, not the protocol, was the cost. This is the clearest evidence we have that the language/IR design is the object of study here.

What this does not establish. The CNN margins (result 4) come from *our own* CKKS arm, 15× off Orion at 3.5% slot utilisation; only the MLP rows above are against external code. And the Lisp layer costs real time — the same network as a Baru program on the plain interpreter takes 299 ms against 268 ms for the hand-written Rust pipeline *with image and model encrypted*. Reducing it is Thrust 3's secondary objective.

4 The Heir comparison, in three tiers

The comparison must be designed so that the architectural claim is separable from implementation quality on either side. We propose three tiers, and we regard Tier A as a precondition for reporting B or C at all.

Tier A — Parity, as a control condition. ***Done for MLPs; outstanding for CNNs.*** The control is that Baru must be within a small constant factor of Heir-generated OpenFHE code at matched security: **if our FHE arm is slow, then "switching to MPC helps" is an artifact of a weak baseline rather than a property of the architecture**, and no Tier B or C number is attributable. For dense MLPs this is now measured, and §3 reports what it found — including Heir beating us outright on wide-area MLPs, which is the control doing its job. Extending it to the convolutional networks of §VI.10 requires the multi-channel packing of Thrust 1.

Tier B — Expressiveness. Programs Heir cannot express, each with its mechanism cited rather than asserted: exact ReLU and max-pool (no comparison in any target scheme); secret-dependent loop bounds (`convert-secret-for-to-static-for` requires static bounds); any mid-program FHE↔MPC transition (no interactive dialect). We report Baru's measured cost and record Heir as *not expressible*, naming the pass. A reviewer will object that this compares against a tool not claiming the capability — that is the point, stated that way: we quantify what the exclusion costs on the canonical workload, which needs a system spanning both sides.

Tier C — Crossover. Programs whose optimal assignment is mixed: show the per-region selector finds it and both pure strategies lose. §3 already establishes the crossover exists in both directions; what remains is showing a compiler can *predict* which side a given program falls on.

Two gates already enforced in code, because an unfair comparison is worse than none. *(i)* A public Heir issue reports an MNIST MLP at ∼30 s / 3 GB under OpenFHE's `HEStd_NotSet` — no security level at all — against ∼6 min / 26 GB at the secure ring dimension: a 12× factor between an insecure and a secure baseline. To be exact, and fair to Heir: that insecure run was the reporter's choice, not a Heir default — Heir's emitted C++ sets only multiplicative depth and plaintext modulus, leaving OpenFHE's default `HEStd_128_classic` in force, which we verified by reading the generated code. The gate exists because a baseline harness must *verify* the parameter it reports rather than assume it in either direction, and ours refuses to emit a latency unless the run reports `HEStd_{128,192,256}_classic`. *(ii)* Both arms must evaluate one fixture, with a test asserting the float evaluation reproduces the quantized classification.

5 Thrusts, and what the award buys

T1 — Multi-channel packing for the FHE arm. Reach Orion-class slot utilisation so Tier A extends to CNNs and all margins are over the state of the art. Adversarial to our own prior numbers; we will report the shrunken figures.

T2 — Extending the Heir comparison (where the AWS credits go). The baseline now runs, and building it corrected our own estimate of what it needs: we had deferred it believing secure parameters required ∼26 GB, and the secure `784x32x10` baseline in fact peaks at 532 MB. So the credits are *not* requested for memory. Two gaps remain that a single machine cannot close. *(i)* Every wide-area figure we have, on both arms, comes from a transport that really sleeps rather than a real link — and §3 shows the network profile is worth 151×, so this is the largest uncontrolled variable in the whole comparison. Multi-region deployment (`sa-east-1` ↔ `us-east-1` ↔ `eu-west-1`) replaces it with measured intercontinental RTTs. *(ii)* Separating the depth-10 cliff into "Heir chose bad parameters," "OpenFHE has a bug," and "this regime needs bootstrapping" requires the larger instances where secure CKKS bootstrapping is tractable.

T3 — Serializable continuations and dynamic round scheduling. Make the continuation a value; schedule rounds dynamically by resuming whichever subcomputation's message arrives; measure against the static scheduler it generalises, on programs whose dependency graph is not statically known. Secondary objective: close the interpreter overhead reported in §3.

T4 — The per-region backend selector, validated by exhaustive comparison against measured runs of every assignment on small programs. The research question is not whether a cost model can be written but *how coarse a model suffices*, with "suffices" defined by measurement.

Deliverables. The open-source tool; a reproducible matched-threat-model benchmark suite spanning MPC and FHE, which the field lacks; two publications (compiler/systems on the architecture and backend selection; applied-crypto on switch-as-bootstrap); **[FILL: N]** student theses.

6 Required questions

Theoretical or applied; domain. Applied, with a compiler-architecture contribution and a measurement-methodology contribution. Domain: compilers and tooling for privacy-preserving computation, evaluated on private ML inference.

Applications, including for Amazon. Multi-organization collaboration on data that cannot be pooled — an AWS Clean Rooms-shaped problem, and a listed topic in this call. A cost model spanning MPC and FHE answers a provisioning question: *given this workload and this network, which privacy technology, and therefore how much compute?* §3 shows the answer inverts with the deployment network alone. Secondarily, deciding when cryptography beats a hardware enclave for a given program region. LGPD-driven demand for private analytics in Latin America is served from `sa-east-1` — exactly the wide-area shape we measure.

Assumptions and factors that could undermine the results.

- *Our own FHE arm is not state of the art* (15× off Orion, 3.5% slot utilisation), so every CNN margin in §VI.10 is a margin over our implementation. The MLP results in §3 do not have this problem — that arm is HEIR-generated OpenFHE, not ours — which is exactly why Tier A matters. T1 extends the same footing to CNNs and will reduce our headline margins.
- *Single-machine provenance.* Wide-area latency is injected by a sleeping transport, not a real link — and §3 shows the profile is worth 151×. T2 replaces it; it is the largest uncontrolled variable we have.
- *The depth/precision sweep uses an untrained fixture*, whose tight class margins are a fixture property. The *mechanism* is supported; a quantitative accuracy claim for trained networks needs a trained fixture.
- *Threat models are matched but not identical in kind.* FHE lets the client go offline; 2PC needs it present throughout. Matching the adversary model does not remove this, and it may dominate for some deployments.
- *Risk to the thesis.* If a well-packed FHE arm wins in every regime the selector degenerates and the claim weakens to expressiveness alone; the experiment is designed so that outcome is publishable.
- *Risk to the comparison.* HEIR is a moving target; we pin a release, report its commit, and treat Tier A as a control, not a scoreboard.

Tool: license, materials, maintenance. License: **Apache-2.0** (`LICENSE`, and declared in `Cargo.toml`). Materials: a language reference, a complete experimental record including negative and withdrawn results (`docs/experiments.md`), a cross-paradigm survey with methodology, and a performance handoff written to be read cold. Maintenance: 129 commits in three months; three contributors, one from USP; 831 tests green; CI on every push. *Discipline:* every engine *attests* what it implements, and asking for more is an error, not a silent downgrade. We have exercised it: all ZKP results predating 2026-07-31 were withdrawn when the shipped verifier proved not to check constraint satisfaction, and an FHE scheme was deleted rather than caveated when our own analysis found it insecure at the needed parameters.

7 Community, students, and budget

Based at LARC (PCS, Escola Politécnica da USP), which teaches an undergraduate cryptography course (*Fundamentos de Criptografia*) and supervises graduate work in applied cryptography; the award supports **[FILL: N]** MSc/PhD students and **[FILL: N]** undergraduate scholars. A compiler project absorbs students unusually well — backends, cost models, gadget libraries and benchmark suites parallelize into defensible individual theses with measurable results — and the matched-threat-model benchmark suite is itself a community contribution whose absence caused a comparison we had to withdraw. Applied-cryptography funding concentrates in North America, Europe and Israel; USP is Latin America's leading research university, and this supports a group training Brazilian students in a subfield where the region is under-represented.

Budget (unrestricted, excluding overhead; **[FILL: confirm amounts against USP/FUSP scholarship rates]**). Graduate student support (**[FILL: N]**, 12 mo.) **[FILL: amt]**; undergraduate *iniciação científica* scholarships (**[FILL: N]**, 12 mo.) **[FILL: amt]**; conference travel, open-access charges and local compute **[FILL: amt]**. **Total unrestricted [FILL: ≤ 80,000] USD. AWS promotional credits** (**[FILL: ≤ 40,000]**) are requested for Thrust 2 specifically, per §5.

References. [1] HEIR Contributors. *HEIR: A Compiler Infrastructure for Homomorphic Encryption.* arXiv:2508.11095, 2025. [2] A. Ebel, G. Garimella, B. Reagen. *Orion: A Fully Homomorphic Encryption Framework for Deep Learning.* ASPLOS, 2025.

Appendix A — Measurement detail

Provenance. Every figure is an elapsed wall-clock time or an instrumented counter from a real run on one machine, recorded in `docs/experiments.md` alongside the command that produced it. No figure is composed from a cost model or extrapolated. Where a result has not been measured it is described as outstanding rather than estimated.

A.1 Heir vs. 2-party MPC, same function, same machine

OpenFHE 1.5.1 from source; `heir-py` 2026.8.1; every row reports `HEStd_128_classic` and reproduced the plaintext classification, so both §4 gates passed. Activation x^2 on both arms. HEIR `eval` excludes keygen; MPC `online` excludes preprocessing. MPC rows are the `dealer` *lower bound*; deployable `lowgear` totals are given below. LAN is 0 ms / 10 Gbit/s, WAN 50 ms one-way / 100 Mbit/s.

Network	Depth	Heir eval	keygen	MPC LAN	MPC WAN	Rounds
`64x32x10`	3	167.0 ms	91.7 ms	14 ms	2113 ms	41
`784x32x10`	3	178.0 ms	105.3 ms	26 ms	2167 ms	41
`64x32x32x10`	5	659.3 ms	271.2 ms	20 ms	3044 ms	59
`64x32x32x32x10`	7	1051.3 ms	347.6 ms	27 ms	3978 ms	77
`64x32x32x32x32x10`	9	1493.4 ms	436.3 ms	34 ms	4909 ms	95
`64x32(×5)x10`	10	**SIGSEGV**	—	41 ms	5842 ms	113

Deployable `lowgear` totals including preprocessing: `64x32x10` 264 ms LAN / 3264 ms WAN; `784x32x10` 388 ms LAN / 3791 ms WAN. Measured slopes per added hidden layer: HEIR ≈440 ms, MPC ≈930 ms on WAN but ≈7 ms on LAN.

Four things this does not say. *(i)* These are dense MLPs, not the convolutional LeNet-5 of §A.2–A.3; the two sets compare only within themselves. *(ii)* `dealer` is a lower bound — against `lowgear` totals the LAN comparison is roughly a tie (264 ms vs. 167 + 92 ms), and the defensible LAN claim is the *online* one. *(iii)* The interaction asymmetry is unchanged: HEIR's client can go offline, ours cannot. *(iv)* Our arm computes the argmax inside the protocol and reveals only the class, while HEIR returns the full logit vector — strictly more work, strictly less disclosure.

A.2 Depth sweep: a line against a staircase

LeNet-5 with additional dense-plus-activation blocks (two levels each), one variable.

Levels	Exch	MiB	MPC, 50 ms WAN	Ring	CKKS	Ratio
11	32	4.82	1517 ms	2^{15}	43.8 s	29×
13	36	4.96	1683 ms	2^{15}	61.1 s	36×
15	40	5.10	1804 ms	2^{16}	160.0 s	89×
17	44	5.23	1937 ms	—	—	
19	48	5.37	2110 ms	—	—	

A.3 Precision: where approximation returns the wrong class

Margins in units of the fixed-point quantum (2^{-8}).

Levels	Ref. class	Margin	CKKS worst error	CKKS verdict	MPC
11	6	58 q	16 q	agrees	6
13	0	**2 q**	15 q	**wrong class (7)**	**0**
15	8	10 q	21 q	agrees, fortuitously	8
17	2	**1 q**	—	—	**2**
19	3	72 q	—	—	3

A.4 The frontend determines round complexity (872×)

MedMNIST pneumonia, one diagnosis, same weights, every integer path bit-identical.

Version	Plaintext, 10 img	Private (image)	Messages
Scalar Lisp	3465 ms	794 508 ms	507 920
+ batched vector primitives	322 ms	6446 ms	33 181
+ fused `vrelu`	299 ms	4326 ms	33 154
+ garbled nonlinearity	—	**911 ms**	33 106
Improvement	**11.6×**	**872×**	**15.4×**

A.5 Backend-aware transformations, each selected by a probe

Transformation	Why it is a backend-aware decision	Measured
Argmax as tournament, not fold	same comparisons, $n-1 \to \lceil \log_2 n \rceil$ depth	1.67×
Rescale by truncation pair	query-independent; crosses the online/offline line	3.67×
All-pairs argmax	spends bandwidth headroom to buy constant depth	1.47×
Open each operand once	reuse appears only at batch > 1	10.8× traffic
LeNet-5, wide-area, cumulative		**7.76 s → 1.41 s**

All-pairs argmax is the thesis in miniature: it performs 45 comparisons instead of 9, and is correct *only* because a separate measurement showed that workload had bandwidth headroom. On a bandwidth-bound link the opposite lowering wins, so both are kept and selected by cost model — a decision a single-paradigm compiler has no basis to make.

Appendix B — Capability matrix

Rows are sourced to Heir's paper (arXiv:2508.11095); none is inferred.

Capability	Heir	Baru
FHE schemes	BGV/BFV, CKKS, CGGI	BFV/BGV, CKKS (OpenFHE), TFHE-rs
Backend libraries	OpenFHE, Lattigo, TFHE-rs, Jaxite	OpenFHE; own NTT
Hardware targets	several (`pisa`, accelerators)	none
Secret sharing / MPC	not present	ABY3; malicious-with-abort
Garbled circuits	not present	yes (nonlinearity lowering)
FHE ↔ MPC switch	not present	both directions
Exact ReLU / max-pool	not expressible (no comparison)	exact
Nonlinearity route	polynomial approx., user-annotated	exact, or approx. by choice
Secret-dependent branch	`convert-if-to-select` (both arms)	executed under protocol
Secret-dependent loop bound	unsupported (static bound required)	executed under protocol
BGV/BFV bootstrapping	unsupported (no backend)	avoided via switch-as-bootstrap
Measured depth ceiling	SIGSEGV at mult. depth 10	no depth budget; linear in depth
Maturity, ecosystem, adoption	**substantially ahead**	research prototype

The last row is not a formality. Heir is production-grade infrastructure with institutional backing, multiple hardware targets and a community; Baru is a research prototype by a small group. The claim in this proposal is confined to the rows above it, and specifically to what the architecture makes *expressible* — which is why Tier A parity is a precondition rather than a result.