MOBSF

ANDROID STATIC ANALYSIS REPORT



LewicowYT (1.9-beta)

File Name:	lewicowYT-1.9-beta-arm64.apk

Package Name:	pl.lewicowyt.notifier
Scan Date:	Nov. 10, 2026, 8:44 p.m.
App Security Score:	55/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	17	2	3	1

FILE INFORMATION

File Name: lewicowYT-1.9-beta-arm64.apk
Size: 14.57MB
MD5: 351b8fce1c6adef53c71b2af40041d96
SHA1: d9c6372abb74020eec393f88541f168ea422e13e
SHA256: b2b9ea7e0f3f7079f33075f4a16b2f93e9023c2a999458137bda1abe6aa71b60

APP INFORMATION

App Name: LewicowYT
Package Name: pl.lewicowyt.notifier
Main Activity: pl.lewicowyt.notifier.MainActivity
Target SDK: 36
Min SDK: 26
Max SDK:
Android Version Name: 1.9-beta
Android Version Code: 20

APP COMPONENTS

Activities: 5
Services: 11
Receivers: 14
Providers: 3
Exported Activities: 1
Exported Services: 2

Exported Receivers: 4
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=Tobiasz Owczarek, OU=-, O=-, L=DDZ, ST=Dolny Śląsk, C=PL
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-07-24 18:07:54+00:00
Valid To: 2051-07-18 18:07:54+00:00
Issuer: CN=Tobiasz Owczarek, OU=-, O=-, L=DDZ, ST=Dolny Śląsk, C=PL
Serial Number: 0x1
Hash Algorithm: sha256
md5: fbcb2f33072910a745f26182b7737f06
sha1: 36f0c2af05564e1be06395e2f62f719c888674a4
sha256: 2d242f3390a37913459085f86edf96484f2ccc3866e327325d2915c74a8e980a
sha512: f0edcbc07089bbb0329e614340b1a0567247f064866075150c200139780ea6266d205e7dce8c4e7fd49752f1cdc19a23bff19739ac34a5ac3e62a79cca2e8012
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 0fc8c5676061daf4a4c97990fa78a71baf9a66d748d75187a729bf94775c6aed
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".
android.permission.FOREGROUND_SERVICE_MEDIA_PLAYBACK	normal	enables foreground services for media playback.	Allows a regular application to use Service.startForeground with the type "mediaPlayback".
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
pl.lewicowyt.notifier.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>351b8fce1c6adef53c71b2af40041d96.apk</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Manipulator Found</td><td>Resources Confusion</td></tr>
</table>
</td></tr>
<tr><td>classes.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check</td></tr>
<tr><td>Compiler</td><td>r8</td></tr>
</table>
</td></tr>
</table>

NETWORK SECURITY

HIGH: 1 | WARNING: 1 | INFO: 0 | SECURE: 0

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	high	Base config is insecurely configured to permit clear text traffic to all domains.
2	*	warning	Base config is configured to trust system certificates.

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **0** | WARNING: **8** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 8.0, minSdk=26]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
3	Service (pl.lewicowyt.notifier.audio.AudioPlaybackService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Broadcast Receiver (pl.lewicowyt.notifier.community.push.CommunityPushReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
6	Activity (androidx.media3.session.BluetoothValidationActivity) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BLUETOOTH_PRIVILEGED [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
7	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
8	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
9	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 1 | WARNING: 7 | INFO: 2 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	defpackage/ck3.java defpackage/da5.java defpackage/e5.java defpackage/ea3.java defpackage/f00.java defpackage/if0.java defpackage/kz2.java defpackage/l4.java defpackage/l7.java defpackage/l70.java defpackage/lo5.java defpackage/lz3.java defpackage/mi5.java defpackage/nq0.java defpackage/o8.java defpackage/or3.java defpackage/po5.java defpackage/q61.java defpackage/tn5.java defpackage/to5.java defpackage/ud1.java defpackage/vb4.java defpackage/vo5.java defpackage/vt0.java defpackage/w35.java defpackage/ws3.java defpackage/x81.java defpackage/xh5.java defpackage/xk4.java defpackage/xo5.java defpackage/ya.java defpackage/yd1.java defpackage/yk4.java defpackage/yr1.java defpackage/z22.java defpackage/zh5.java defpackage/zk4.java defpackage/zl0.java defpackage/zn5.java defpackage/zq3.java defpackage/zt3.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/b81.java defpackage/jd.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/lq0.java defpackage/o1.java defpackage/r71.java defpackage/r81.java defpackage/ra3.java defpackage/sg3.java defpackage/z04.java
3	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/vt0.java defpackage/yv2.java
4	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	defpackage/ak1.java defpackage/dh.java defpackage/em4.java defpackage/mq1.java defpackage/nz.java defpackage/o15.java defpackage/o52.java defpackage/op1.java defpackage/qd0.java defpackage/qz1.java defpackage/ry.java defpackage/wl1.java
5	The file or SharedPreference is World Writable. Any App can write to the file	high	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/qg.java pl/lewicowyt/notifier/community/push/EmbeddedPushService.java
6	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	defpackage/cl.java defpackage/nc2.java defpackage/tr1.java defpackage/va1.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	defpackage/hg1.java defpackage/ip3.java defpackage/jg1.java defpackage/js0.java defpackage/nj2.java defpackage/nq0.java defpackage/t95.java defpackage/vq2.java defpackage/vu3.java defpackage/wf2.java defpackage/z22.java
8	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	defpackage/be3.java defpackage/g54.java defpackage/gj0.java defpackage/he0.java defpackage/n54.java defpackage/qk5.java defpackage/qq.java defpackage/r54.java defpackage/rg2.java defpackage/sk5.java defpackage/u23.java defpackage/vo3.java defpackage/z74.java
9	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/nc2.java
10	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	defpackage/p3.java
11	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	defpackage/b13.java defpackage/q62.java defpackage/wl1.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libtorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libtor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__strlcat_chk', '__strlcpy_chk', '__strchr_chk', '__strrchr_chk', '__memset_chk', '__read_chk', '__FD_SET_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libzstd-jni-1.5.7-6.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/liblewicowyt_avif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libsqliteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/liblewicowyt_jxl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/liblewicowyt_mozjpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libtorjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/libtor.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__strlcat_chk', '__strlcpy_chk', '__strchr_chk', '__strrchr_chk', '__memset_chk', '__read_chk', '__FD_SET_chk', '__FD_CLR_chk', '__FD_ISSET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libzstd-jni-1.5.7-6.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/liblewicowyt_avif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libsqliteJni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/liblewicowyt_jxl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/liblewicowyt_mozjpeg.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00028	Read file from assets directory	file	defpackage/bl.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	defpackage/aj0.java defpackage/d8.java defpackage/dh.java defpackage/mi5.java defpackage/od.java defpackage/vj1.java defpackage/xk5.java pl/lewicowyt/notifier/updates/UpdateInstallActivity.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	defpackage/mi5.java defpackage/vj1.java
00036	Get resource file from res/raw directory	reflection	defpackage/bk3.java defpackage/dh.java defpackage/mi5.java defpackage/vj1.java defpackage/xj2.java defpackage/xk5.java
00191	Get messages in the SMS inbox	sms	defpackage/m7.java
00022	Open a file from given absolute path of the file	file	defpackage/bn0.java defpackage/dh.java defpackage/fx.java defpackage/hc.java defpackage/ix.java defpackage/kb0.java defpackage/n92.java defpackage/nc2.java defpackage/o91.java defpackage/qz1.java defpackage/yv2.java

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	defpackage/ak1.java defpackage/bk3.java defpackage/da5.java defpackage/dh.java defpackage/dv0.java defpackage/ia1.java defpackage/j80.java defpackage/k40.java defpackage/k90.java defpackage/ke3.java defpackage/kg2.java defpackage/kl5.java defpackage/pt3.java defpackage/rg1.java defpackage/rg3.java defpackage/ru0.java defpackage/ug3.java defpackage/vh0.java defpackage/vm0.java defpackage/vt0.java defpackage/zi4.java
00089	Connect to a URL and receive input stream from the server	command network	defpackage/e5.java defpackage/np0.java defpackage/va1.java
00109	Connect to a URL and get the response code	network command	defpackage/e5.java defpackage/np0.java defpackage/va1.java
00162	Create InetSocketAddress object and connecting to it	socket	defpackage/ea3.java defpackage/gb0.java defpackage/rb.java
00163	Create new Socket and connecting to it	socket	defpackage/ea3.java defpackage/gb0.java defpackage/rb.java

RULE ID	BEHAVIOUR	LABEL	FILES
00012	Read data and put it into a buffer stream	file	defpackage/dh.java defpackage/dv0.java defpackage/pt3.java
00091	Retrieve data from broadcast	collection	defpackage/ck3.java defpackage/mi5.java defpackage/x81.java defpackage/z50.java pl/lewicowyt/notifier/messaging/FeedMessagingService.java
00014	Read file into a stream and put it into a JSON object	file	defpackage/kl5.java defpackage/vt0.java
00009	Put data in cursor to JSON object	file	defpackage/hg1.java defpackage/kl5.java defpackage/nq0.java defpackage/vt0.java
00024	Write file after Base64 decoding	reflection file	defpackage/vt0.java
00178	Execute Linux commands via ProcessBuilder	command	defpackage/lq.java
00005	Get absolute path of file and put it to JSON object	file	defpackage/nc2.java
00004	Get filename and put it to JSON object	file collection	defpackage/kl5.java defpackage/nc2.java defpackage/qg.java
00096	Connect to a URL and set request method	command network	defpackage/e5.java defpackage/np0.java
00030	Connect to the remote server through the given URL	network	defpackage/np0.java

RULE ID	BEHAVIOUR	LABEL	FILES
00094	Connect to a URL and read data from it	command network	defpackage/np0.java
00108	Read the input stream from given URL	network command	defpackage/np0.java
00025	Monitor the general action to be performed	reflection	defpackage/ck3.java
00079	Hide the current app's icon	evasion	defpackage/r53.java
00114	Create a secure socket connection to the proxy address	network command	defpackage/fg0.java
00132	Query The ISO country code	telephony collection	defpackage/s.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/510352833254/namespaces/firebase:fetch?key=AIzaSyAPN6xq02PWSxdh8Xd_o4uszs51uv6k6rg. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.REQUEST_INSTALL_PACKAGES, android.permission.WAKE_LOCK, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WRITE_EXTERNAL_STORAGE

TYPE	MATCHES	PERMISSIONS
Other Common Permissions	2/44	android.permission.FOREGROUND_SERVICE, com.google.android.c2dm.permission.RECEIVE

Malware Permissions:
Top permissions that are widely abused by known malware.
Other Common Permissions:
Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
api-zxsxrppk7a-lm.a.run.app	ok	**IP:** 34.143.76.2 **Country:** United States of America **Region:** Texas **City:** Houston **Latitude:** 29.941401 **Longitude:** -95.344498 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
xml.org	ok	**IP:** 188.114.97.11 **Country:** Spain **Region:** Madrid, Comunidad de **City:** Madrid **Latitude:** 40.416500 **Longitude:** -3.702560 **View:** Google Map
emmunioo.github.io	ok	**IP:** 185.199.111.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
apache.org	ok	**IP:** 151.101.2.132 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
developers.google.com	ok	**IP:** 142.250.120.138 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
2019.www.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map
example.com	ok	**IP:** 172.66.147.243 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.google.comwww.mit.eduwww.yahoo.comwww.slashdot.org	ok	**IP:** 104.18.4.215 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
i.ytimg.com	ok	**IP:** 192.178.40.6 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
bugs.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map
blog.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map
developer.apple.com	ok	**IP:** 17.253.107.204 **Country:** Denmark **Region:** Hovedstaden **City:** Ballerup **Latitude:** 55.731651 **Longitude:** 12.363280 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
goo.gle	ok	**IP:** 67.199.248.12 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map
default.url	ok	No Geolocation information available.
ns.adobe.com	ok	No Geolocation information available.
aomedia.org	ok	**IP:** 185.199.110.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
youtu.be	ok	**IP:** 142.250.109.91 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
g.co	ok	**IP:** 142.250.120.138 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.youtube.com	ok	**IP:** 142.251.156.4 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
developer.android.com	ok	**IP:** 142.250.130.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
firebase.google.com	ok	**IP:** 142.251.98.138 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
support.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map
freehaven.net	ok	**IP:** 128.31.0.34 **Country:** United States of America **Region:** Massachusetts **City:** Cambridge **Latitude:** 42.365078 **Longitude:** -71.104523 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
dns.adguard-dns.com	ok	**IP:** 0.0.0.0 **Country:** - **Region:** - **City:** - **Latitude:** 0.000000 **Longitude:** 0.000000 **View:** Google Map
www.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
firebaseinstallations.googleapis.com	ok	**IP:** 172.217.119.4 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
schemas.microsoft.com	ok	**IP:** 150.171.109.53 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map
issuetracker.google.com	ok	**IP:** 142.250.120.138 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
api.github.com	ok	**IP:** 140.82.121.6 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	**IP:** 140.82.121.4 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
community.torproject.org	ok	**IP:** 204.8.99.144 **Country:** United States of America **Region:** Pennsylvania **City:** Chester **Latitude:** 39.846901 **Longitude:** -75.376503 **View:** Google Map
www.googleapis.com	ok	**IP:** 172.217.113.4 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.slf4j.org	ok	**IP:** 159.100.250.151 **Country:** Switzerland **Region:** Vaud **City:** Lausanne **Latitude:** 46.515999 **Longitude:** 6.632820 **View:** Google Map

EMAILS

EMAIL	FILE
u0013android@android.com0 u0013android@android.com	defpackage/fo5.java
tor-relays@lists.torproject bad-relays@lists.torproject	lib/arm64-v8a/libtor.so
tor-relays@lists.torproject bad-relays@lists.torproject	apktool_out/lib/arm64-v8a/libtor.so

HARDCODED SECRETS

POSSIBLE SECRETS
"google_crash_reporting_api_key" : "AIzaSyAPN6xq02PWSxdh8Xd_o4uszs51uv6k6rg"
"google_api_key" : "AIzaSyAPN6xq02PWSxdh8Xd_o4uszs51uv6k6rg"
86254750241babac4b8d52996a675549
1cbd3130fa23b59692c061c594c16cc0
a-95ed6082-b8e9-46e8-a73f-ff56f00f5d9d

SCAN LOGS

Timestamp	Event	Error
2026-11-10 20:44:35	Generating Hashes	OK

2026-11-10 20:44:35	Extracting APK	OK
2026-11-10 20:44:35	Unzipping	OK
2026-11-10 20:44:35	Parsing APK with androguard	OK
2026-11-10 20:44:35	Extracting APK features using aapt/aapt2	OK
2026-11-10 20:44:35	Getting Hardcoded Certificates/Keystores	OK
2026-11-10 20:44:37	Parsing AndroidManifest.xml	OK
2026-11-10 20:44:37	Extracting Manifest Data	OK
2026-11-10 20:44:37	Manifest Analysis Started	OK
2026-11-10 20:44:37	Reading Network Security config from network_security_config.xml	OK
2026-11-10 20:44:37	Parsing Network Security config	OK
2026-11-10 20:44:37	Performing Static Analysis on: LewicowYT (pl.lewicowyt.notifier)	OK
2026-11-10 20:44:37	Fetching Details from Play Store: pl.lewicowyt.notifier	OK

2026-11-10 20:44:38	Checking for Malware Permissions	OK
2026-11-10 20:44:38	Fetching icon path	OK
2026-11-10 20:44:38	Library Binary Analysis Started	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/libtorjni.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/libtor.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/libzstd-jni-1.5.7-6.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/liblewicowyt_avif.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/libsqliteJni.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/liblewicowyt_jxl.so	OK
2026-11-10 20:44:38	Analyzing lib/arm64-v8a/liblewicowyt_mozjpeg.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/libtorjni.so	OK

2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/libtor.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/libzstd-jni-1.5.7-6.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/liblewicowyt_avif.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/libsqliteJni.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/liblewicowyt_jxl.so	OK
2026-11-10 20:44:38	Analyzing apktool_out/lib/arm64-v8a/liblewicowyt_mozjpeg.so	OK
2026-11-10 20:44:38	Reading Code Signing Certificate	OK
2026-11-10 20:44:38	Running APKiD 3.1.0	OK
2026-11-10 20:44:40	Updating Trackers Database....	OK
2026-11-10 20:44:40	Detecting Trackers	OK
2026-11-10 20:44:41	Decompiling APK to Java with JADX	OK

2026-11-10 20:45:02	Converting DEX to Smali	OK
2026-11-10 20:45:02	Code Analysis Started on - java_source	OK
2026-11-10 20:45:06	Android SBOM Analysis Completed	OK
2026-11-10 20:45:20	Android SAST Completed	OK
2026-11-10 20:45:20	Android API Analysis Started	OK
2026-11-10 20:45:33	Android API Analysis Completed	OK
2026-11-10 20:45:34	Android Permission Mapping Started	OK
2026-11-10 20:45:47	Android Permission Mapping Completed	OK
2026-11-10 20:45:51	Android Behaviour Analysis Started	OK
2026-11-10 20:46:04	Android Behaviour Analysis Completed	OK
2026-11-10 20:46:04	Extracting Emails and URLs from Source Code	OK
2026-11-10 20:46:25	Email and URL Extraction Completed	OK

2026-11-10 20:46:25	Extracting String data from APK	OK
2026-11-10 20:46:25	Extracting String data from SO	OK
2026-11-10 20:46:25	Extracting String data from Code	OK
2026-11-10 20:46:25	Extracting String values and entropies from Code	OK
2026-11-10 20:46:36	Performing Malware check on extracted domains	OK
2026-11-10 20:46:39	Saving to Database	OK

Report Generated by - MobSF v4.5.1

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.