



Tackling Sparse Facts for Temporal Knowledge Graph Completion

Yuchao Zhang
Zhejiang University of Technology
College of Computer Science and
Technology
Hangzhou, China
yuchao.z@outlook.com

Xiangjie Kong*
Zhejiang University of Technology
College of Computer Science and
Technology
Hangzhou, China
Zhejiang Key Laboratory of Visual
Information Intelligent Processing
Hangzhou, China
xjkong@ieee.org

Kailun Ye
Zhejiang University of Technology
College of Computer Science and
Technology
Hangzhou, China
yekailun@zjut.edu.cn

Guojiang Shen
Zhejiang University of Technology
College of Computer Science and
Technology
Hangzhou, China
Zhejiang Key Laboratory of Visual
Information Intelligent Processing
Hangzhou, China
gjshen1975@zjut.edu.cn

Shangfei Zheng
Zhejiang Sci-Tech University
School of Computer Science and
Technology
Hangzhou, China
zsf@zstu.edu.cn

Abstract

Temporal knowledge graph completion (TKGC) seeks to develop more comprehensive knowledge representations by addressing missing relationships and entities within temporal knowledge graphs (TKGs), thereby enhancing reasoning and predictive capabilities in downstream tasks. Nonetheless, real-world knowledge—such as the progression of social network interactions and the unfolding of news events—is inherently dynamic, resulting in substantial sparsity issues in TKGs that profoundly impair the performance of TKGC models. To overcome this challenge, we introduce the **Adaptive Neighborhood Enhancement Layer (ANEL)**, a novel module that can be effortlessly integrated into existing TKGC models to substantially elevate the representation quality of sparse entities. ANEL first derives initial entity embeddings through a base model and then uncovers concealed semantic relationships between entities via a latent relation module, enriching the explicit relationships within the knowledge graph. Furthermore, ANEL incorporates an adaptive latent information adjustment component, which dynamically calibrates the influence of latent information based on the entity's relational structure: entities with fewer connections derive greater benefit from latent information, while entities with denser connections become less dependent on latent

augmentation, ensuring precise and resilient representations. We conducted comprehensive experiments on four prominent benchmark datasets, and the results underscore the effectiveness and superiority of ANEL in TKGC tasks.

CCS Concepts

• **Computing methodologies** → **Temporal reasoning**.

Keywords

Knowledge Representation, Temporal Knowledge Graph Completion, Fact Sparsity

ACM Reference Format:

Yuchao Zhang, Xiangjie Kong, Kailun Ye, Guojiang Shen, and Shangfei Zheng. 2025. Tackling Sparse Facts for Temporal Knowledge Graph Completion. In *Proceedings of the ACM Web Conference 2025 (WWW '25)*, April 28-May 2, 2025, Sydney, NSW, Australia. ACM, New York, NY, USA, 10 pages. <https://doi.org/10.1145/3696410.3714839>

1 Introduction

Knowledge graphs (KGs) utilize a graph-based framework to reveal intricate relationships within data, emerging as vital tools for the structured representation and organization of knowledge. By encoding real-world information in the form of triples—comprising a subject entity, a relation, and an object entity—KGs construct a network that facilitates the in-depth analysis of complex inter-entity interactions. This architecture endows KGs with formidable semantic representation and reasoning capabilities, significantly boosting performance across various downstream tasks. Their applications span a wide array of fields, including question-answering systems [1], recommendation engines [2–4], and information retrieval systems [5]. However, in practice, KGs often grapple with significant information gaps and incomplete data, which can severely hamper their ability to faithfully represent real-world knowledge, thereby

*Corresponding authors.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

WWW '25, Sydney, NSW, Australia

© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 979-8-4007-1274-6/25/04
<https://doi.org/10.1145/3696410.3714839>

diminishing their efficacy in various applications. To address this challenge, KG Completion (KGC) plays a crucial role [6]. KGC employs machine learning and inference techniques to predict and fill in missing triples, thereby enriching and expanding KGs while bolstering their performance across a wide range of applications.

KGC, as a critical downstream task within KGs, has garnered significant attention from the research community due to its focus on inferring missing facts by identifying patterns and rules within existing KG data. A variety of KGC approaches leverage KG embeddings (KGEs) to project high-dimensional data into lower-dimensional spaces, facilitating the creation of a mapping function between entities and their relationships. This mapping function is then used to evaluate the plausibility of predicted facts. While these methods demonstrate strong performance in predicting missing facts, real-world knowledge is often subject to temporal shifts, such as those observed in news updates and evolving social dynamics. To maintain accuracy, each dataset is typically annotated with timestamps. For instance, Donald Trump served as President of the United States from November 9, 2016, to January 11, 2021 (*Trump, Is President of, United States, 20161109-20210111*). Addressing these temporal changes, Temporal KGs (TKGs) have been introduced, linking events to specific timestamps. However, the recurrence of similar events in different temporal contexts creates distinct facts. For example, the ICEWS dataset [7] records the same event with different timestamps: (*Angola, Make a visit, China, 2014-06-06*) and (*Angola, Make a visit, China, 2015-06-23*). This added temporal complexity poses substantial challenges for the task of temporal KGC (TKGC).

Despite the significant advancements made by current TKGC models, accurately predicting entities with sparse relationships or newly introduced entities within TKGs remains a formidable challenge. We conducted an in-depth analysis of widely utilized benchmark datasets in the TKG domain, such as ICEWS14 [8], ICEWS18 [9], GDEL T [10], and ICEWS05-15 [9], with particular attention to the impact of neighboring entities on prediction performance (e.g., MRR). Using the REGCN [11] TKGC model, we evaluated entity prediction across various temporal subgraphs under different neighbor counts. To consolidate our findings, we categorized entities by their neighbor counts and calculated the average MRR for each group, leading to the final analytical insights. As shown in Figure 1, the blue bar chart illustrates the distribution of entities by neighbor count within TKGs, revealing that entities with only one neighbor form the largest group, emphasizing the pervasive sparsity within TKGs—a limitation that restricts the available information for fact completion. The accompanying light blue bar chart depicts the relationship between neighbor count and the prediction performance of entities with missing facts. Our analysis demonstrates a positive correlation between the number of neighbors and enhanced prediction accuracy, underscoring the crucial influence of neighbor count on prediction outcomes.

In this work, we propose a model-agnostic Adaptive Neighborhood Enhancement Layer (ANEL) specifically designed to address the challenge of fact sparsity in TKGs. This enhancement layer can be seamlessly integrated with any TKGC model, improving the representation of entities with limited neighbors and consequently boosting prediction accuracy for missing facts. When entities have




Figure 1: The influence of varying entity neighbor quantities on entity prediction efficacy across the ICEWS14, ICEWS18, ICEWS05-15, and GDEL T benchmark datasets utilizing the REGCN model.

a large number of neighbors, the framework enhances their representations by aggregating information from surrounding entities; in contrast, when neighbors are sparse, the enhancement layer leverages latent neighbor information to enrich these entities with essential data. Extensive experiments conducted on widely recognized benchmark datasets, such as ICEWS and GDEL T, demonstrate that our proposed ANEL framework markedly improves entity prediction performance, especially in scenarios characterized by sparse neighbor connections. Our principal contributions are as follows:

- We systematically analyzed and quantified the influence of entity neighbor count on prediction performance within TKGs, uncovering the critical impact neighbor count has on overall model effectiveness.
- We introduced a novel, model-agnostic ANEL module that can be effortlessly incorporated into any existing TKGC model, substantially improving the representation of entities with limited neighbors.
- We carried out extensive experimental validation on four widely recognized TKG benchmark datasets, showcasing the efficacy of our proposed enhancement layer.

2 Related Work

Existing TKGC models can be broadly divided into two categories: non-neural models and Neural network-based TKGE models [12].

Non-neural models typically extend traditional KG embedding approaches by incorporating temporal information into the representations of entities and relations, using transformed distances to assess the plausibility of facts. For instance, the t-transE [13], HyTE [14] and ChronoR [15]. Another subset of non-neural network methods uses tensor decomposition to evaluate the plausibility of quadruples, as seen in models like T-DistMult [16], TNTComplex [17], TeLM [18], Cont [19], and TuckERTNT [16]. To address uncertainties in the representations of entities and relations and enhance the model's expressiveness, the AtISE [20] models entity embeddings as Gaussian distributions, and the RE-NET framework

[9] uses conditional probability distributions to describe the patterns of fact occurrence. Additionally, the DBKGE [21] applies the mean and variance of Gaussian distributions to entity embeddings to capture embedding uncertainties and improve representation quality. Despite being intuitively designed and relatively simple, these models often produce embeddings with limited quality due to their simplicity and limited parameterization.

Neural network-based TKGE models excel in representation learning and the capture of temporal information, effectively handling time dependencies and dynamic evolution within KGs. A key advantage of these models is their ability to reveal complex entity relationships and their evolution over time through various architectures. Specifically, the REGCN model [11] also utilizes Relational graph convolutional network (RGCN) to capture the effects of neighboring entity interactions, while an autoregressive GRU is used to model the associations between temporal facts. Moreover, emerging technologies such as Capsule Networks [22–24], Transformers [25, 26], Bert [27, 28], Meta-Learning [29–31], Reinforcement Learning [32, 33], and Large Language Models [34, 35] have also been widely applied to TKGC tasks, providing robust support for further enhancing model performance. Although graph neural network-based TKGC methods can predict missing information using the neighborhood information of target nodes, sparse neighborhood information can hinder the update of entity representations and affect model performance. Zhang et al. [36] introduced a latent relation learning approach; however, it inadequately delves into the richness of existing entity information, making it susceptible to incorporating superfluous noise. Moreover, it lacks adaptability, thereby restricting its applicability across diverse models. Conversely, Mirtaheri et al. [37] proposed a TKGC model related to entity degree that affords a degree of flexibility. Nevertheless, this method overlooks the structural intricacies and contextual semantics of latent entity relations, both of which are pivotal for refining entity embeddings and bolstering predictive accuracy.

3 Preliminary and Definition

In this section, we systematically introduce the basic definitions of temporal knowledge graphs (TKGs) and provide a detailed description of the key symbols and the process involved in TKG completion (TKGC) tasks.

TKGC involves predicting or filling in previously missing factual data as the KG evolves over time. These tasks are commonly known as extrapolation and interpolation. This paper primarily focuses on the extrapolation task within TKGs. A TKG consists of multiple graph snapshots taken at different time points $\mathbf{G} = (\mathcal{G}_1, \mathcal{G}_2, \dots, \mathcal{G}_t)$, where each snapshot $\mathcal{G}_t = (\mathcal{F}_t, \mathcal{E}_t, \mathcal{R}_t)$ reflects the set of facts \mathcal{F}_t formed by interactions between entities in the entity set \mathcal{E}_t and relationships in the relationship set \mathcal{R}_t at time step t . Each fact can be represented as a quadruple $\mathcal{F}_t = (s, r, o, t)$, where s and o are the subject and object entities, respectively, r denotes the relationship between them, and t is the timestamp of the interaction. Unlike static knowledge graphs (KGs), TKG extrapolation places significant emphasis on real-time data updates.

The TKGC model treats the prediction task as a sequence of tasks across multiple time steps $T = (T_1, T_2, \dots, T_n)$. Each sub-task T_i includes mutually exclusive training data $D_{\text{train}i} \in G_t$, testing

data $D_{\text{test}i} \in G_t$, and validation data $D_{\text{val}i} \in G_t$ to ensure unbiased evaluation. The model starts by learning from the training data $D_{\text{train}1}$ at the first time step, using the validation data $D_{\text{val}1}$ to tune hyperparameters. In each subsequent time step, the model builds on the parameters from previous steps, iteratively updating them to enhance prediction accuracy for future data.

4 Adaptive Neighborhood Enhancement Layer

TKGs are characterized by dynamic structures, where some entities may frequently engage in relationships during certain periods while remaining inactive during others. This temporal imbalance leads to sparse connections for certain entities at specific time steps. Additionally, as TKGs evolve, entities and relationships are continuously expanded and updated. Newly introduced entities may receive attention and connections in certain parts of the graph, while being neglected in others, resulting in insufficient connections and representations. These sparsely connected entities typically have lower-quality representations within the KGs, resulting in suboptimal performance of TKGC models when tasked with predictions involving these entities.

We propose an Adaptive Neighborhood Enhancement Layer (ANEL), a module that can be seamlessly integrated into any temporal knowledge graph completion (TKGC) model. Its purpose is to enhance the embedding representations of sparsely connected and low-activity entities by enriching their latent structural information and semantic context. First, the TKGC model is used to extract the basic features of the entities, generating their initial representations. Then, the ANEL module systematically explores and adaptively supplements the latent structural and semantic information based on the sparsity of the entity relationships. Through this process, ANEL effectively improves the base model's ability to represent sparsely connected and low-activity entities. According to the format outlined in [37], the entity representations processed by ANEL are as follows:

$$e_{s,t} = f(s) + \phi(s)g(s) \quad (1)$$

In this formulation, $e_{s,t}$ signifies the ultimate representation of the query entity s at time t , whereas $f(s)$ denotes the embedding of entity s produced by the underlying TKGC model. The entity activity function $\phi(s)$ is defined as $\frac{1}{1+\exp(-|\mathcal{N}_s^t|)}$, where $|\mathcal{N}_s^t|$ represents the number of interacting neighbors of entity s at time t , reflecting the entity's activity level at that particular moment. A lower value of $\phi(s)$ indicates heightened activity of the entity at timestamp t , characterized by frequent interactions with other entities. For such highly active entities, supplementary information is generally redundant due to the richness of interaction data. Conversely, for less active entities with sparse interaction data, it may be necessary to explore potential interactions to enhance the quality of their representations. The enhancement of entity representations through latent neighborhoods involves three principal stages: the construction of a latent graph $g(s)$, temporal neighbor sampling, and the aggregation of latent neighborhoods.

4.1 Latent graph construction

For the prediction task ($T_1 = (s, r, ?, t_1)$), we begin by selecting a candidate set of potentially related entities $C_{t_1}^s = \{o_i \in G_{t_1}\}$ through




Figure 2: Illustration of the proposed ANEL integrated with the base model, which first generates initial embeddings, refines entity features through a latent neighbor graph, and combines the adaptive information component's output with the base model's entity features for entity prediction.

filtering those that do not directly interact with entity s at the current timestamp t_1 , as entities appearing within the same timeframe are seldom coincidental and often exhibit latent connections. For example, events such as (*Russia, militaryintervention, Ukraine, 2022-02*) and (*UK, aid, Ukraine, 202202*) are likely intertwined due to their temporal alignment.

Subsequently, a base model encoder is utilized to initialize the candidate entities' features, embedding structural information into their respective feature representations, as demonstrated by the equation $h_{o_i} = \text{Encoder}(o_i)$. This step enhances the model's capacity to uncover intricate relationship patterns within the temporal graph. Finally, the Pearson correlation coefficient is utilized to quantify the linear relationships between the features of the candidate entities and the target entity, providing a more sophisticated understanding of their interconnections.

$$d(s, o_i) = \text{PearsonSimilarity}(h_s, h_{o_i}) \quad (2)$$

To refine the precision of identifying entities with potential interaction relationships and optimize the model's computational efficiency, we employ the K-Nearest Neighbors algorithm [38] to select the top k entities most similar to the query entity based on their feature embeddings. These selected entities are then integrated as new neighbors to construct the potential graph structure. The edges in the potential graph \mathcal{G}^l are defined as:

$$\mathcal{G}^l = \begin{cases} 1, & \text{if } d(s, o) \in \text{top-}K(C_{t_1}^s) \\ 0, & \text{otherwise} \end{cases} \quad (3)$$

When an entity has few links at time t or is a new entity, and the number of potential neighbors in the current temporal subgraph is less than k , we supplement the potential neighbors by searching from the previous temporal subgraph at $t - 1$. Since the appearance of entities at the same time is often non-random, suggesting some

underlying interaction or shared context, we prioritize selecting entities that co-occur with the target entity at the same time. This ensures that the potential neighbors are temporally relevant and likely to share meaningful interactions.

4.2 Latent Neighbourhood Repretation Aggregation

To fully exploit the rich relational information embedded in the potential graph, we execute relation-aware propagation and aggregation operations within the latent neighborhood graph of the target entity [36, 39, 40]. By utilizing relation-aware propagation, the target entity assimilates varied relational information from its surrounding entities, enriching its representation with enhanced contextual semantics. The entity representation, updated through the incorporation of latent neighborhood information, is expressed as:

$$\mathbf{h}_o^{(l)} = \sigma \left(\sum_{(s,r,o) \in \mathcal{G}^l} \alpha_{sro} \mathbf{W}_r^{(l)} (\mathbf{h}_s^{(l)} + \mathbf{h}_r) + \mathbf{W}_o^{(l)} \mathbf{h}_o^{(l-1)} \right) \quad (4)$$

Here, $\mathbf{h}_o^{(l)}$ denotes the embedding of entity o at layer l , and \mathbf{h}_o refers to its representation. The function σ corresponds to the *ReLU* activation function, while $\mathbf{W}_o^{(l)}$ and $\mathbf{W}_r^{(l)}$ represent the learnable parameters for entities and relations, respectively, in the l -th layer of the learning process. The attention weight α_{sro} is used to distinguish the significance of entity o in relation to entity s within the potential graph. Following the approach outlined in [39], the attention score α_{sro} for each fact is normalized, with the softmax function applied to calculate the relative importance of entity o to entity s within the potential graph \mathcal{G}^l :

$$\begin{aligned}
\alpha_{sro} &= \text{softmax}(w_{sro}) \\
w_{sro} &= \frac{\exp(w_{sro})}{\sum_{w \in \mathcal{N}_o} \exp(w_{wro})} \\
w_{sro} &= \alpha^{(l)} \text{LeakyReLU} \left(\mathbf{W}_{att}^{(l)} \left[\mathbf{h}_s^{(l-1)} \parallel \mathbf{h}_r^{(l-1)} \parallel \mathbf{h}_o^{(l-1)} \right] \right), \\
\forall (s, o) &\in \mathcal{G}^l
\end{aligned} \tag{5}$$

where $\alpha^{(l)}$ and $\mathbf{W}_{att}^{(l)}$ represent the learnable parameters for the subject entity, relation, and object entity at layer l , respectively. The \parallel denotes the concatenation of different vectors. The vectors $\mathbf{h}_s^{(l-1)}$, $\mathbf{h}_o^{(l-1)}$, and $\mathbf{h}_r^{(l-1)}$ represent the hidden representations of the subject entity, object entity, and relation at layer $l - 1$, respectively. The set \mathcal{N}_o denotes the set of entities that have interacted with entity o in potential graph.

5 Experiments

In this section, we assess the efficacy of the proposed adaptive neighborhood enhancement layer (ANEL) for entity prediction in TKGC, utilizing four prominent TKG datasets. The research questions are as follows:

- **RQ1:** How does the performance of the TKGC model integrated with ANEL compare to baseline models?
- **RQ2:** How do variations in model weight parameters influence the performance of the TKGC model when ANEL is applied?
- **RQ3:** What are the individual contributions of the ANEL components to the overall performance in TKGC tasks?

5.1 Experiment Settings

In our experimental validation, we use the state-of-the-art TKGC model TiRGN [41], which performs best on extrapolation tasks, and the second-best performing model REGCN [11] as our base models to validate the effectiveness of our proposed ANEL method.

5.1.1 Datasets. To validate the efficacy of our proposed ANEL, we employed four widely recognized benchmark datasets in the domain of TKGs: ICEWS14 [8], ICEWS05-15 [9], ICEWS18 [9], and GDELT [10]. The first three datasets, sourced from the Integrated Crisis Early Warning System (ICEWS), chronicle interactions between geopolitical entities for the years 2014, 2005-2015, and 2018, respectively. Conversely, the GDELT dataset records global news events from 1979 onwards, encompassing data from worldwide news broadcasts and online media. We processed the datasets following the methodology outlined in [9], partitioning each into training, validation, and test sets with an 80%, 10%, and 10% split, respectively. Detailed dataset statistics are presented in Table 1.

Table 1: Common TKGE benchmarks and their attributes

Datasets	Entities	Relations	Facts	Train Facts	Time Steps
ICEWS14	7128	230	90730	74845	365
ICEWS05-15	10488	251	479329	368868	4017
ICEWS18	23033	256	468558	373018	304
GDELT	7691	240	3419607	1734399	366

5.1.2 Evaluation Metrics. For the evaluation metrics, we use two widely recognized measures to assess model performance in TKGC tasks: Hit@k and Mean Reciprocal Rank (MRR). Hit@k measures the percentage of cases where the correct entity appears in the top k predicted results, providing insight into the accuracy of the model's top-ranked predictions. MRR calculates the average of the reciprocal ranks of correct predictions, offering a more granular evaluation of model ranking performance across all tasks. In this study, we employ Hit@1,3,10 to evaluate model performance. We report both our results and those from the baseline experiments, using the same time-aware filtering method as applied by Li et al. [41], to ensure a fair and consistent comparison.

5.1.3 Baselines. In our baseline model setup, we select several high-performing static and TKGC models as benchmarks. The static KGC models include DistMult [42], ConvE [43], RotatE [44], and ComplEx [45]. These models handle only entities and relations without considering temporal information. In contrast, the TKGC models include TNTComplEx [17], RE-NET [46], CyGNet [47], xERTE [48], TITer [49], REGCN [11], TiRGN [41] and CENET [50]. These models incorporate temporal information, allowing them to better capture and predict evolving relationships and entities over time.

- **DistMult** [42] represents relationships between entities in a KG by performing bilinear dot products between the embeddings of the head entity, relation, and tail entity.
- **ConvE** [43] captures complex relationships in KGs by transforming entity and relation embeddings into 2D matrices and applying convolutional neural networks to them.
- **RotatE** [44] models relationships by rotating the head entity vector to the tail entity vector in the complex space, representing triplet relationships in KGs.
- **ComplEx** [45] embeds entities and relations in the complex space and uses the complex dot product to model symmetric, antisymmetric, and complex relational patterns.
- **TNTComplEx** [17] is a TKGE method that represents temporal data as fourth-order tensors in the complex space, leveraging complex numbers to efficiently model the interaction between entities, relations, and time.
- **RE-NET** [46] captures dynamic interactions between entities and relations over time by using a recurrent neural network (RNN) combined with a relational graph convolutional network (RGCN) to model temporal evolution.
- **CyGnet** [47] predicts new facts by leveraging historical and cyclic events within a temporal context, focusing on the recurrence of specific event types over time.
- **xERTE** [48] is an interpretable model that predicts new events by using subgraphs and attention mechanisms to focus on relevant historical information for explaining predictions.
- **TITer** [49] is a reinforcement learning-based model that predicts future facts by selecting optimal time paths—sequences of events that unfold over time—using reinforcement learning. The model learns to navigate historical temporal data and identifies key event sequences that are most likely to influence future predictions, optimizing its path selection through iterative feedback.
- **REGCN** [11] uses a graph convolutional network (GCN) to learn structural features in KGs and combines it with an RNN to model

temporal sequences, capturing dynamic relationships between entities over time.

- **TiRGN** [41] models evolving entity relationships in dynamic KGs by using a local encoder to capture dependencies between historical facts and a global encoder to capture repeating historical patterns over time.
- **CENET** [50] is a contrastive learning-based TKGC model that uses contrastive learning to decide whether historical information should be used to predict new facts.

5.1.4 Implementation Details. We implemented the proposed ANEL using the PyTorch framework and the PyG library on a node with A800 GPUs. For optimization, we chose the Adam optimizer with a learning rate set to 0.001, and the embedding dimensions were fixed at 200.

For hyperparameter tuning in the ANEL, we used grid search on the validation set to ensure optimal performance. The search range for k was 3, 6, 9, 12, 15, 18, 21 and the dropout parameter was searched within 0.2, 0.4, 0.6. For the four benchmark datasets employed in the experiment—ICEWS14, ICEWS05-15, ICEWS18, and GDELT—the optimal k values for REGCN-ANEL and TiRGN-ANEL were determined to be 6, 9, 6, 12, and 15, 15, 3, 9, respectively. Furthermore, a dropout rate of 0.4 was applied in each layer. With these parameters, we present the experimental outcomes of our proposed ANEL model after integrating it with the baseline architecture. For the other comparison experiments, we used the default model parameters.

5.2 Main Results (RQ1)

Table 2 presents a comparison of various models' performance on entity prediction tasks within a benchmark dataset. To highlight the flexibility and effectiveness of our ANEL framework, we incorporated it into two leading TKGC models. We chose the TiRGN model, which achieved the highest entity prediction accuracy, and the REGCN model, which secured the second position. By integrating ANEL, we developed two hybrid models—TiRGN-ANEL and REGCN-ANEL—to evaluate their performance in entity prediction tasks.

As demonstrated in Tables 2, the TiRGN-ANEL and REGCN-ANEL models significantly surpass static models in entity prediction tasks, primarily because static models are incapable of capturing essential temporal dynamics in KGC. Moreover, both TiRGN-ANEL and REGCN-ANEL exceed their original base architectures. This advancement is largely attributable to the REGCN model's dependency on the most recent entity representations, which overlooks wider global dependencies that evolve over time. While the TiRGN model accounts for these global dependencies, its approach remains somewhat constrained. ANEL refines this by dynamically adjusting the integration of global dependencies based on the number of neighboring entities. In contrast, models like RE-NET and CyGNET underperform due to their inability to fully leverage temporal information within the same time step. Likewise, xERTE and TITER, which depend on path-searching strategies for entity prediction, struggle when critical paths are absent for certain entities.

Tables 3 and 4 illustrate the performance enhancements in MRR and $H@1,3,10$ metrics for entity prediction following the integration of the proposed ANEL with the baseline models. The findings

indicate that the REGCN-ANEL model increases the average entity prediction accuracy by 4.13% across four benchmark datasets, surpassing the base REGCN model, while TiRGN-ANEL achieves a 2.54% improvement. The variance in accuracy gains arises from the fact that the TiRGN model leverages not only the original TKG but also historical interaction data between entities as input. Consequently, the TiRGN model has already incorporated latent information to some degree to enhance the original TKG, whereas the REGCN model relies solely on the TKG data as input.

5.3 Facts Sparsity Study (RQ1)

To evaluate the influence of data sparsity on the predictive performance of our TiRGN-ANEL and REGCN-ANEL models, we randomly removed between 10% and 90% of the facts from the ICEWS14 training set and assessed the models using the complete test set. Figure 3 provides a comparative analysis of MRR and Hits@10 in entity prediction tasks across four models: the ANEL-augmented TiRGN and REGCN, alongside the top-performing base models, TiRGN and REGCN. As the figure shows, the performance of all models declines with reduced training data. However, our TiRGN-ANEL and REGCN-ANEL models consistently outperform their base counterparts, exhibiting greater robustness to fact sparsity due to the integration of the ANEL mechanism.




Figure 3: The performance comparison of entity prediction between the ANEL-enhanced REGCN/TiRGN completion model and the base model on the sparsified ICEWS14 dataset.

Table 2: ICEWS14, ICEWS05-15, ICEWS18 and GDELT. Best results are in bold.

Model	ICEWS14			ICEWS05-15			ICEWS18			GDELT		
	MRR	Hit@1	Hit@10	MRR	Hit@1	Hit@10	MRR	Hit@1	Hit@10	MRR	Hit@1	Hit@10
DistMult [42]	25.31	17.83	42.20	18.39	11.16	30.32	16.59	10.01	31.69	15.64	9.37	29.33
ConvE [43]	31.23	21.20	50.37	30.40	20.21	49.96	24.16	15.47	44.32	17.03	10.21	33.17
RotatE [44]	27.41	18.53	47.46	19.47	10.32	38.91	15.33	6.90	32.82	5.43	1.87	13.64
ComplEx [45]	31.79	22.91	51.43	22.55	14.22	40.96	18.76	11.39	25.73	12.07	8.24	20.29
TNTComplEx [17]	30.02	23.33	49.11	27.52	19.50	42.85	21.21	13.26	36.89	19.51	12.38	33.39
RE-NET [46]	38.21	28.43	54.11	42.77	30.89	63.29	28.83	19.07	47.53	19.65	12.45	34.07
CyGnet [47]	37.32	27.14	57.49	39.95	28.91	60.96	26.35	16.23	44.71	19.72	11.83	33.21
xERTE [48]	40.69	32.65	57.26	46.57	37.76	63.87	29.28	21.01	45.56	18.75	11.92	32.45
TITer [49]	41.70	32.71	58.44	47.61	38.33	64.89	29.97	22.04	44.86	18.20	11.62	31.23
REGCN [11]	41.75	31.59	61.46	46.44	35.99	66.45	32.2	22.08	51.98	19.63	12.34	33.78
TiRGN [41]	43.67	33.09	62.21	49.36	38.73	69.72	33.26	22.87	53.64	21.66	13.61	37.68
CENET [50]	41.25	32.23	58.16	47.05	37.16	67.57	29.63	19.87	48.12	19.67	11.94	34.96
REGCN-ANEL (Ours)	43.28	32.93	<u>63.11</u>	49.22	38.4	<u>69.89</u>	<u>33.57</u>	<u>23.15</u>	53.31	20.38	12.88	35.02
TiRGN-ANEL (Ours)	44.74	34.4	64.66	50.59	39.69	71.27	34.04	23.53	54.71	22.06	13.85	38.33

Table 3: Performance comparison of REGCN and REGCN + ANEL (Ours) on Benchmark datasets.

Dataset	Model	MRR	H@1	H@3	H@10
ICEWS14	REGCN	41.75	31.59	46.43	61.46
	REGCN-ANEL (Ours)	43.28	32.93	48.03	63.11
	Δ improve	3.67%	4.24%	3.45%	2.69%
ICEWS18	REGCN	32.20	22.08	36.25	51.98
	REGCN-ANEL (Ours)	33.57	23.15	37.40	53.31
	Δ improve	4.26%	4.85%	3.17%	2.56%
ICEWS05-15	REGCN	46.44	35.99	52.08	66.45
	REGCN-ANEL (Ours)	49.22	38.4	55.15	69.89
	Δ improve	5.99%	6.7%	5.9%	5.18%
GDELT	REGCN	19.63	12.34	20.91	33.78
	REGCN-ANEL (Ours)	20.38	12.88	21.77	35.02
	Δ improve	3.82%	4.38%	4.12%	3.67%

Table 4: Performance comparison of TiRGN and TiRGN + ANEL (Ours) on Benchmark datasets.

Dataset	Model	MRR	H@1	H@3	H@10
ICEWS14	TiRGN	43.67	33.09	48.11	62.21
	TiRGN-ANEL (Ours)	44.74	34.4	49.82	64.66
	Δ improve	2.5%	3.96%	3.55%	3.94%
ICEWS18	TiRGN	33.26	22.87	37.58	53.64
	TiRGN-ANEL (Ours)	34.04	23.53	38.41	54.71
	Δ improve	2.35%	2.89%	2.21%	2.0%
ICEWS05-15	TiRGN	49.36	38.73	55.27	69.72
	TiRGN-ANEL (Ours)	50.59	39.69	56.67	71.27
	Δ improve	2.49%	2.48%	2.53%	2.22%
GDELT	TiRGN	21.66	13.61	23.28	37.68
	TiRGN-ANEL (Ours)	22.06	13.85	23.76	38.33
	Δ improve	1.85%	1.76%	2.06%	1.73%

5.4 Sensitivity Analysis (RQ2)

In the proposed ANEL, the parameter k determines the number of neighbors associated with the current entity in the latent graph, which is built upon filtered neighbors. The relationships between these neighbors in the latent graph are essential for updating the current entity’s representation. To examine the effect of different k values on the entity prediction MRR for the ANEL model and the base models REGCN/TiRGN, we conducted experiments with various k values (3, 6, 9, 12, 15, 18, 21) to observe their impact on model performance (When k is 0, it refers to the prediction result of the baseline model). As depicted in Figures 4 and 5, the results demonstrate how varying k influences the model’s MRR metric.

The experimental results reveal that as the value of k increases, the MRR of the ANEL fusion completion model initially rises and then declines. This is because, at lower k values, a moderate number of potential neighbors provides valuable information, enhancing the representation of the current entity and improving model performance. However, when k exceeds a certain threshold, the inclusion of too many potential neighbors introduces noise, which deteriorates the quality of the entity representation. This finding underscores that while the ANEL fusion completion model is adept at extracting rich information from potential neighbors to strengthen entity representation, careful selection of the number of neighbors is essential to prevent noise interference and sustain the model’s effectiveness.

5.5 Ablation Study (RQ3)

The integration of the ANEL model with diverse base architectures surpasses the baseline models in entity prediction tasks across standard benchmark datasets. To evaluate the contribution of each component within ANEL, we performed an ablation study. In particular, we sequentially omitted the adaptive information (AI) module, the latent neighborhood aggregation module, and the attention mechanism from the REGCN-ANEL and TiRGN-ANEL models, assessing these modified versions on four datasets: ICEWS14, ICEWS05-15, ICEWS18, and GDELT.




Figure 4: Performance of REGCN-ANEL model under different k value in the ICEWS14, ICEWS18, ICEWS05-15, and GDELT benchmark.

As illustrated in Tables 5 and 6, the fully integrated ANEL model, when paired with the base models, delivers superior performance compared to the ANEL variants with individual components removed, underscoring the significance of each module. Notable observations include:

- **Latent Neighbourhood Aggregation Component:** The Latent Neighborhood Aggregation (LNA) component strengthens the model's capacity to represent sparse entities by extracting potential neighborhood information. To validate the LNA component's impact on entity prediction tasks, we excluded it from the model and compared the prediction performance across various datasets with the complete model. The results revealed a notable decline in accuracy when the LNA component was omitted (w/o LNA), confirming that LNA aids the model in capturing additional latent temporal relationships by enriching neighborhood information, thereby boosting overall prediction performance.
- **Attention Mechanism Component:** To assess the contribution of the attention mechanism, we excluded it and examined its impact on the performance of the base models integrated with ANEL (w/o AM). The results indicate that the full model outperforms the variant lacking the attention mechanism, confirming that the attention mechanism effectively identifies and distinguishes the significance of various latent entities. This differentiation enhances the base models' capacity to deliver more accurate entity predictions.

Table 5: Performance of different variants of REGCN-ANEL on various datasets

Model	ICEWS14	ICEWS05-15	ICEWS18	GDELT
w/o AI	42.24	48.48	32.67	20.21
w/o LNA	42.03	48.44	32.82	20.08
w/o AM	42.39	48.64	32.93	20.12
REGCN-ANEL	43.28	49.22	33.57	20.28




Figure 5: Performance of TiRGN-ANEL model under different k value in the ICEWS14, ICEWS18, ICEWS05-15, and GDELT benchmark.

Table 6: Performance of different variants of TiRGN-ANEL on various datasets

Model	ICEWS14	ICEWS05-15	ICEWS18	GDELT
w/o AI	42.52	50.14	33.77	21.83
w/o LNA	44.07	49.92	33.54	21.81
w/o AM	44.17	49.89	33.39	21.73
TiRGN-ANEL	44.71	50.59	34.04	22.06

6 Conclusion

In this paper, we introduce ANEL to address the pervasive issue of sparsity in TKGC tasks. Our approach begins by generating an initial embedding for each entity through a base model. We then incorporate a latent relation module that captures supplementary latent information for entities inadequately defined by their observed relationships. This is followed by an adaptive latent information component, which dynamically adjusts the level of latent information based on the observed data: entities with fewer direct relations are enriched with additional latent information, while those with denser relational data rely less on latent augmentation. The refined entity embeddings are then utilized for entity prediction tasks. Extensive experiments and analyses across four benchmark datasets demonstrate the efficacy and superiority of our proposed ANEL in TKGC.

Acknowledgments

This work was supported in part by the National Natural Science Foundation of China under Grant 62476247, 62402447, 62073295 and 62072409, in part by the "Pioneer" and "Leading Goose" R&D Program of Zhejiang under Grant 2024C01214, and in part by the Zhejiang Provincial Natural Science Foundation under Grant LR21F020003 and LQN25F020005.

References

- [1] Weiqiang Jin, Biao Zhao, Hang Yu, Xi Tao, Ruiping Yin, and Guizhong Liu. Improving embedded knowledge graph multi-hop question answering by introducing relational chain reasoning. *Data Mining and Knowledge Discovery*, 37:255–288, 2023.
- [2] Na Zhao, Zhen Long, Jian Wang, and Zhi-Dan Zhao. Agre: A knowledge graph recommendation algorithm based on multiple paths embeddings rnn encoder. *Knowledge-Based Systems*, 259:110078, 2023.
- [3] Xiangjie Kong, Zhiyu Chen, Jianxin Li, Junhui Bi, and Guojian Shen. Kgnext: Knowledge-graph-enhanced transformer for next poi recommendation with uncertain check-ins. *IEEE Transactions on Computational Social Systems*, 2024.
- [4] Lianghao Xia, Chao Huang, Yong Xu, Peng Dai, Xiyue Zhang, Hongsheng Yang, Jian Pei, and Liefeng Bo. Knowledge-enhanced hierarchical graph transformer network for multi-behavior recommendation. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 4486–4493, 2021.
- [5] Anitha Velu and Menakadevi Thangavelu. Ontology based ocean knowledge representation for semantic information retrieval. *Computers, Materials & Continua*, 70, 2022.
- [6] Jiapu Wang, Boyue Wang, Junbin Gao, Shirui Pan, Tengfei Liu, Baocai Yin, and Wen Gao. Made: Multicurvature adaptive embedding for temporal knowledge graph completion. *IEEE Transactions on Cybernetics*, 2024.
- [7] E Boschee, J Lautenschlager, S O'Brien, S Shellman, J Starz, and M Ward. Integrated crisis early warning system (icews) coded event data. URL: <https://dataverse.harvard.edu/datasetview/icews>, 2015.
- [8] Alberto García-Durán, Sebastián Dumančić, and Mathias Niepert. Learning sequence encoders for temporal knowledge graph completion. *arXiv preprint arXiv:1809.03202*, 2018.
- [9] Woojeong Jin, Meng Qu, Xisen Jin, and Xiang Ren. Recurrent event network: Autoregressive structure inference over temporal knowledge graphs. *arXiv preprint arXiv:1904.05530*, 2019.
- [10] Kalev Leetaru and Philip A Schrodtt. Gdelt: Global data on events, location, and tone, 1979–2012. In *ISA annual convention*, volume 2, pages 1–49. Citeseer, 2013.
- [11] Zixuan Li, Xiaolong Jin, Wei Li, Saiping Guan, Jiafeng Guo, Huawei Shen, Yuanzhuo Wang, and Xueqi Cheng. Temporal knowledge graph reasoning based on evolutionary representation learning. In *Proceedings of the 44th international ACM SIGIR conference on research and development in information retrieval*, pages 408–417, 2021.
- [12] Yuchao Zhang, Xiangjie Kong, Zhehui Shen, Jianxin Li, Qiuhua Yi, Guojian Shen, and Bo Dong. A survey on temporal knowledge graph embedding: Models and applications. *Knowledge-Based Systems*, page 112454, 2024.
- [13] Tingsong Jiang, Tianyu Liu, Tao Ge, Lei Sha, Sujian Li, Baobao Chang, and Zhifang Sui. Encoding temporal information for time-aware link prediction. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pages 2350–2354, 2016.
- [14] Shib Sankar Dasgupta, Swayambhu Nath Ray, and Partha Talukdar. Hyte: Hyperplane-based temporally aware knowledge graph embedding. In *Proceedings of the 2018 conference on empirical methods in natural language processing*, pages 2001–2011, 2018.
- [15] Ali Sadeghian, Mohammadreza Armandpour, Anthony Colas, and Daisy Zhe Wang. Chronor: Rotation based temporal knowledge graph embedding. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 6471–6479, 2021.
- [16] Pengpeng Shao, Dawei Zhang, Guohua Yang, Jianhua Tao, Feihu Che, and Tong Liu. Tucker decomposition-based temporal knowledge graph completion. *Knowledge-Based Systems*, 238:107841, 2022.
- [17] Timothée Lacroix, Guillaume Obozinski, and Nicolas Usunier. Tensor decompositions for temporal knowledge base completion. *arXiv preprint arXiv:2004.04926*, 2020.
- [18] Chengjin Xu, Yung-Yu Chen, Mojtaba Nayyeri, and Jens Lehmann. Temporal knowledge graph completion using a linear temporal regularizer and multivector embeddings. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2569–2578, 2021.
- [19] Yunpu Ma, Volker Tresp, and Erik A Daxberger. Embedding models for episodic knowledge graphs. *Journal of Web Semantics*, 59:100490, 2019.
- [20] Chenjin Xu, Mojtaba Nayyeri, Fouad Alkhoury, Hamed Yazdi, and Jens Lehmann. Temporal knowledge graph completion based on time series gaussian embedding. In *The Semantic Web—ISWC 2020: 19th International Semantic Web Conference, Athens, Greece, November 2–6, 2020, Proceedings, Part I* 19, pages 654–671. Springer, 2020.
- [21] Siyuan Liao, Shangsong Liang, Zaiqiao Meng, and Qiang Zhang. Learning dynamic embeddings for temporal knowledge graphs. In *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, pages 535–543, 2021.
- [22] Guirong Fu, Zhao Meng, Zhen Han, Zifeng Ding, Yunpu Ma, Matthias Schubert, Volker Tresp, and Roger Wattenhofer. Tempcaps: a capsule network-based embedding model for temporal knowledge graph completion. In *Proceedings of the Sixth Workshop on Structured Prediction for NLP*, pages 22–31. Association for Computational Linguistics, 2022.
- [23] Sensen Zhang, Xun Liang, Zhiying Li, Junlan Feng, Xiangping Zheng, and Bo Wu. Biqcap: A biquaternion and capsule network-based embedding model for temporal knowledge graph completion. In *International Conference on Database Systems for Advanced Applications*, pages 673–688. Springer, 2023.
- [24] Sensen Zhang, Xun Liang, Hui Tang, Xiangping Zheng, Alex X. Zhang, and Yuefeng Ma. Ducape: Dual quaternion and capsule network-based temporal knowledge graph embedding. *ACM Transactions on Knowledge Discovery from Data*, 17(7):1–19, 2023.
- [25] Haohai Sun, Shangyi Geng, Jialun Zhong, Han Hu, and Kun He. Graph hawkes transformer for extrapolated reasoning on temporal knowledge graphs. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 7481–7493, 2022.
- [26] Zhiyu Fang, Shuai-Long Lei, Xiaobin Zhu, Chun Yang, Shi-Xue Zhang, Xu-Cheng Yin, and Jingyan Qin. Transformer-based reasoning for learning evolutionary chain of events on temporal knowledge graph. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 70–79, 2024.
- [27] Luyi Bai, Xiuting Song, and Lin Zhu. Joint multi-feature information entity alignment for cross-lingual temporal knowledge graph with bert. *IEEE Transactions on Big Data*, 2024.
- [28] Zhihua Yan and Xijin Tang. Narrative graph: Telling evolving stories based on event-centric temporal knowledge graph. *Journal of Systems Science and Systems Engineering*, 32(2):206–221, 2023.
- [29] Yuwei Xia, Mengqi Zhang, Qiang Liu, Shu Wu, and Xiao-Yu Zhang. Metatkg: Learning evolutionary meta-knowledge for temporal knowledge graph reasoning. *arXiv preprint arXiv:2302.00893*, 2023.
- [30] Liqin Wang, Hang Chu, Yongfeng Dong, Enhai Liu, and Linhao Li. Learning neighborhood-based embedding sequence for link prediction in temporal knowledge graphs. *Journal of Intelligent & Fuzzy Systems*, 43(6):7983–7994, 2022.
- [31] Zifeng Ding, Jingpei Wu, Zongyue Li, Yunpu Ma, and Volker Tresp. Improving few-shot inductive learning on temporal knowledge graphs using confidence-augmented reinforcement learning. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 550–566. Springer, 2023.
- [32] Zixuan Li, Xiaolong Jin, Saiping Guan, Wei Li, Jiafeng Guo, Yuanzhuo Wang, and Xueqi Cheng. Search from history and reason for future: Two-stage reasoning on temporal knowledge graphs. *arXiv preprint arXiv:2106.00327*, 2021.
- [33] Luyi Bai, Die Chai, and Lin Zhu. Rlat: Multi-hop temporal knowledge graph reasoning based on reinforcement learning and attention mechanism. *Knowledge-Based Systems*, 269:110514, 2023.
- [34] Dong-Ho Lee, Kian Ahrabian, Woojeong Jin, Fred Morstatter, and Jay Pujara. Temporal knowledge graph forecasting without knowledge using in-context learning. *arXiv preprint arXiv:2305.10613*, 2023.
- [35] Ruotong Liao, Xu Jia, Yangzhe Li, Yunpu Ma, and Volker Tresp. Gentkg: Generative forecasting on temporal knowledge graph with large language models. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 4303–4317, 2024.
- [36] Mengqi Zhang, Yuwei Xia, Qiang Liu, Shu Wu, and Liang Wang. Learning latent relations for temporal knowledge graph reasoning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12617–12631, 2023.
- [37] Mehrnoosh Mirtaheri, Ryan A Rossi, Sungchul Kim, Kanak Mahadik, Tong Yu, Xiang Chen, and Mohammad Rostami. Tackling long-tail entities for temporal knowledge graph completion. In *Companion Proceedings of the ACM on Web Conference 2024*, pages 497–500, 2024.
- [38] Jie Chen, Haw-ren Fang, and Yousef Saad. Fast approximate knn graph construction for high dimensional data via recursive lanczos bisection. *Journal of Machine Learning Research*, 10(9), 2009.
- [39] Zhaoxuan Tan, Zilong Chen, Shangbin Feng, Qingyue Zhang, Qinghua Zheng, Jundong Li, and Minnan Luo. Kract: Contrastive learning with graph context modeling for sparse knowledge graph completion. In *Proceedings of the ACM Web Conference 2023*, pages 2548–2559, 2023.
- [40] Zhiwen Xie, Runjie Zhu, Jin Liu, Guangyou Zhou, and Jimmy Xiangji Huang. Target: A time-aware relational graph attention model for temporal knowledge graph embedding. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 31:2246–2258, 2023.
- [41] Yujia Li, Shiliang Sun, and Jing Zhao. Tirgn: Time-guided recurrent graph network with local-global historical patterns for temporal knowledge graph reasoning. In *IJCAI*, pages 2152–2158, 2022.
- [42] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. *arXiv preprint arXiv:1412.6575*, 2014.
- [43] Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.
- [44] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. *arXiv preprint*

- arXiv:1902.10197*, 2019.
- [45] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International conference on machine learning*, pages 2071–2080. PMLR, 2016.
 - [46] Woojeong Jin, Meng Qu, Xisen Jin, and Xiang Ren. Recurrent event network: Autoregressive structure inference over temporal knowledge graphs. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6669–6683, 2020.
 - [47] Cunchao Zhu, Muhao Chen, Changjun Fan, Guangquan Cheng, and Yan Zhang. Learning from history: Modeling temporal knowledge graphs with sequential copy-generation networks. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 4732–4740, 2021.
 - [48] Zhen Han, Peng Chen, Yunpu Ma, and Volker Tresp. Explainable subgraph reasoning for forecasting on temporal knowledge graphs. In *International conference on learning representations*, 2020.
 - [49] Haohai Sun, Jialun Zhong, Yunpu Ma, Zhen Han, and Kun He. Timetraveler: Reinforcement learning for temporal knowledge graph forecasting. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 8306–8319, 2021.
 - [50] Yi Xu, Junjie Ou, Hui Xu, and Luoyi Fu. Temporal knowledge graph reasoning with historical contrastive learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 4765–4773, 2023.