

Admin Dashboard API Documentation

This document provides details on the available endpoints for the Admin Dashboard and examples of how to interact with them using `curl`.

Base URL

The API is available under: `http://pg.mmgbpay.com/api/` or `http://pg.mmgbpay.com/`

Authentication

The Admin Dashboard API uses **JWT (JSON Web Token) Authentication**.

1. Login

To get an access token and a refresh token, send a `POST` request with your admin credentials.

- **Endpoint:** `POST /api/admin/login/`
- **Payload:** `{"username": "your_admin_user", "password": "your_password"}`

Example Request

```
curl -X POST http://localhost:8000/api/admin/login/ \
-H "Content-Type: application/json" \
-d '{"username": "admin", "password": "password123"}'
```

Example Response

```
{
  "access": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9...",
  "refresh": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9..."
}
```

2. Token Refresh

If the access token expires, use the refresh token to get a new one.

- **Endpoint:** `POST /api/admin/token/refresh/`
- **Payload:** `{"refresh": "<your_refresh_token>"}`

3. Using the Token

Include the access token in the `Authorization` header for all protected endpoints: `Authorization: Bearer <your_access_token>`

[!IMPORTANT] Admin JWT vs Service App Token

- **Admin JWT:** Used for Dashboard API. Uses `Bearer` + JWT Token: `Authorization: Bearer <JWT>`.
- **Service App Token:** Used for H5/Merchant API. Uses `Bearer` + static API token: `Authorization: Bearer <API_TOKEN>`. These two systems use the same header prefix (`Bearer`) but different tokens. The system will automatically distinguish them based on the endpoint and validation logic.

1. Dashboard Summary

Returns aggregated statistics for providers and service apps.

- **Endpoint:** `GET /api/admin/dashboard/summary/`
- **Description:** Provides total balance per provider (KBZ Pay, Wave Pay, AYA Pay) and total exported balance.

Example Request

```
curl -X GET http://localhost:8000/api/admin/dashboard/summary/ \
-H "Authorization: Token 9944b09199c62bcf9418ad846dd0e4bbdfc6ee4b"
```

Example Response

```
{
  "provider_balances": [
    {"provider": "kbzpay", "total_amount": "50000.00"},
    {"provider": "wavepay", "total_amount": "32000.00"},
    {"provider": "ayapay", "total_amount": "15000.00"}
  ],
  "total_exported_balance": "10000.00",
  "service_app_stats": [
    {"id": 1, "name": "YoursMusic", "total_transactions": "45000.00"},
    {"id": 2, "name": "MAS", "total_transactions": "22000.00"}
  ]
}
```

2. Transactions

List and filter transaction records.

- **Endpoint:** GET /api/admin/transactions/
- **Query Params:**
 - [service_app](#): (Optional) Filter by Service App ID.
- **Methods:** GET, POST, PUT, DELETE, PATCH

Example Request (List All)

```
curl -X GET http://localhost:8000/api/admin/transactions/ \
-H "Authorization: Bearer <your_access_token>"
```

Example Request (Filter by Service App)

```
curl -X GET "http://localhost:8000/api/admin/transactions/?service_app=1" \
-H "Authorization: Bearer <your_access_token>"
```

3. Service Apps

Manage service applications integrated with MGPay.

- **Endpoint:** GET | POST /api/admin/service-apps/
- **Endpoint:** GET | PUT | PATCH | DELETE /api/admin/service-apps/<id>/

Example Request (Create)

```
curl -X POST http://localhost:8000/api/admin/service-apps/ \
-H "Content-Type: application/json" \
-H "Authorization: Bearer <your_access_token>" \
-d '{
  "name": "NewServiceApp",
  "callback_url": "https://api.newservice.com/callback"
}'
```

4. Balance Exports (Drawouts)

Track money drawn out from the system for specific service apps.

- **Endpoint:** GET | POST /api/admin/balance-exports/

Example Request (Create)

```
curl -X POST http://localhost:8000/api/admin/balance-exports/ \
-H "Content-Type: application/json" \
-H "Authorization: Bearer <your_access_token>" \
-d '{
  "service_app": 1,
  "amount": "5000.00"
}'
```

5. Allowed Hosts

Manage dynamic CORS origins for service apps.

- **Endpoint:** GET | POST /api/admin/allowed-hosts/

Example Request

```
curl -X POST http://localhost:8000/api/admin/allowed-hosts/ \
-H "Content-Type: application/json" \
-H "Authorization: Bearer <your_access_token>" \
-d '{
  "service_app": 1,
  "host_name": "https://yoursmusic.com",
  "is_active": true
}'
```

6. Logs & Callbacks

System logs for monitoring and troubleshooting.

- **Endpoints:**
 - GET /api/admin/api-logs/ : List all provider API request/response logs.
 - GET /api/admin/callbacks/ : List all incoming payment callback logs.

Example Request (API Logs)

```
curl -X GET http://localhost:8000/api/admin/api-logs/ \
-H "Authorization: Bearer <your_access_token>"
```