2026-02-05 EVENING / Debian 13

Description	Type	CPU TYPE	VCPU	RAM	Price	cpu_single_eps	cpu_multi_eps	ram_mib_s	disk_read_iops	disk_write_iops	docker_build_seconds	):laravel_hey_co	p_laravel_hey_avg_secon	p_laravel_hey_p95_seconds
	CX33	X86	4	8 GB	4.99€	1409.49	5636.58	5262.56	37047.130191	15945.203653	521	200	0.1019	0.1605
	CX43	X86	8	16 GB	8.99€	1359.16	10830.63	4852.77	23881.511849	10270.472953	545	200	0.0693	0.0994
	CAX21	Arm64	4	8 GB	5.99€	1258.90	5016.65	4545.86	44990.100660	19355.842944	624	200	0.0975	0.1369
Cost Optimized	CAX31	Arm64	8	16 GB	11.99€	1260.74	10053.17	4506.85	44321.011933	19067.062196	623	200	0.0537	0.0754
	CPX32	X86	4	8 GB	10.49€	1657.74	6613.01	6415.43	57718.318779	24811.945870	512	200	0.0512	0.0877
Regular Performance	CPX42	X86	8	16 GB	19.49€	1605.82	11664.64	6164.21	47091.927205	20258.616092	513	200	0.0421	0.0753
	CCX13	X86	2	8 GB	11.99€	1664.22	1807.62	6641.46	57104.526365	24548.830078	510	200	0.1534	0.1851
General Purpose	CCX23	X86	4	16 GB	23.99€	1653.41	3609.25	6627.03	55755.749617	23974.768349	516	200	0.0794	0.1184

2026-02-06 MORNING / Debian 13

Description	Type	CPU TYPE	VCPU	RAM	Price	cpu_single_eps	cpu_multi_eps	ram_mib_s	disk_read_iops	disk_write_iops	docker_build_seconds	):laravel_hey_co	p_laravel_hey_avg_secon	p_laravel_hey_p95_secon	p_laravel_hey_fastest_second	p_laravel_hey_slowest_secon	php_laravel_hey_total_seconds	odoo_hey_avg_seconds	o_hey_p95_seco	hey_fastest_sec	hey_slowest_sec	hey_total_seco	_locust_median	doo_locust_avg	mloo_locust_min	mloo_locust_max	mdoo_locust_req	odoo_locust_p95	SCORE	SCORE / PRICE
	CX33	X86	4	8 GB	4.99€	1412.63	5653.32	5289.52	29953.54	12885.84	524	2000	0.0922	0.1359	0.0320	0.2020	18.5925	0.5595	0.7411	0.2017	4.7410	113.1069	180	229.94	22.92	910.27	29.27	580	66 – Minimum	58
	CX43	X86	8	16 GB	8.99€	1421.94	11353.91	5437.32	37693.33	16223.54	507	2000	0.0427	0.0665	0.0252	0.1009	8.9817	0.2835	0.4610	0.1927	2.3813	58.0587	130	146.78	23.84	519.85	30.91	310	74 - Usable, but Odoo feels the limits	71 - OK low-mid
	CX53	X86	16	32 GB	16.99€	1414.85	22461.54	5407.18	37621.06	16189.49	513	2000	0.0343	0.0421	0.0247	0.0752	6.9680	0.2817	0.3373	0.2151	1.9357	57.0949	130	130.99	22.56	564.71	31.20	270	74 - Usable, but with jitter	78 - Overkill
	CAX21	Arm64	4	8 GB	5.99€	1255.49	5022.55	4520.19	43937.67	18900.97	628	2000	0.1064	0.1589	0.0377	0.2456	21.4905	0.8521	0.8336	0.2338	5.7790	131.7803	350.0	407.71	31.50	1706.47	25.83	910	70 - 4 vCPU ARM = limit for Odoo	69 - Minimum ARM
	CAX31	Arm64	8	16 GB	11.99€	1256.26	10055.06	4527.40	38101.36	16399.53	619	2000	0.0514	0.0764	0.0342	0.1081	10.5290	0.3253	0.5369	0.2301	2.9907	67.1614	160	160.12	28.93	517.01	30.50	330	86 - Stable, affordable, slightly weaker peak	92 - Cheap and good
Cost Optimized	CAX41	Arm64	16	32 GB	23.99€	1258.58	19805.26	4540.43	39208.89	16876.51	645	2000	0.0432	0.0489	0.0365	0.0902	8.6986	0.3474	0.4081	0.2810	2.3656	69.9470	170	160.26	31.89	575.62	30.79	310	83 - OK, but unnecessarily large	66 - Unnecessarily large
	CPX32	X86	4	8 GB	10.49€	1649.24	6636.33	6819.79	53841.61	23153.72	516	2000	0.0511	0.0722	0.0172	0.1280	10.2936	0.4051	0.5309	0.1438	4.2573	82.3024	110	137.62	16.57	764.74	30.97	340	90 - Perfect balance, minimal difference vs CPX42	100
	CPX42	X86	8	16 GB	19.49€	1652.63	13215.27	6572.05	55864.64	24016.40	504	2000	0.0278	0.0442	0.0167	0.0995	5.9629	0.2357	0.3852	0.1475	2.9106	47.7716	130.0	146.54	17.53	589.83	30.71	330	93 - Lowest latency, top p95	76
Regular Performance	CPX52	X86	12	24 GB	27.99€	1657.89	19727.62	6558.58	50886.64	21807.01	504	2000	0.0218	0.0327	0.0164	0.0869	4.5589	0.2346	0.3220	0.1388	1.6486	47.9765	130	161.52	17.66	493.52	30.91	360	82 - Performance OK, price not worth it	63
	CCX13	X86	2	8 GB	11.99€	1660.46	1809.05	6642.52	53808.27	23137.90	515	2000	0.1711	0.2133	0.0203	0.2955	34.4103	1.0878	1.2825	0.1559	9.2462	218.5807	1300.0	1243.08	33.29	2620.91	17.22	2100	45 - Not suitable for Odoo	38
	CCX23	X86	4	16 GB	23.99€	1662.64	3616.65	6670.99	50040.66	21532.60	511	2000	0.0794	0.1123	0.0192	0.1788	16.0566	0.5429	0.6853	0.1654	5.1935	110.2815	170.0	220.11	17.99	984.93	28.98	580	70 - Dedicated # better	59
General Purpose	CCX33	x86	8	32 GB	47.99€	1660.56	7206.31	6654.86	45606.73	19623.03	508	2000	0.0407	0.0605	0.0187	0.1247	8.2103	0.2598	0.3768	0.1423	2.4577	54.2369	110.0	149.39	16.04	564.89	31.00	370	72 - Dedicated, but worse latency	50

SCORING

Methodology

Weights:
•Odoo (Hey + Locust) → 60%
•Laravel (Hey) – 25%
•CPU / RAM / Disk → 15%

Maximum score = 100 points

TEST SUMMARY

EXECUTED BENCHMARKS

CPU – sysbench (single-core and multi-core performance)

Memory – sysbench (sequential memory throughput)

Disk I/O – fio (NVMe read/write IOPS)

Docker build – full application image build time

Laravel (PHP) – HTTP benchmark using hey (average latency, p95)

Odoo (Python) – HTTP benchmark using hey (average latency, p95)

Odoo (Python) – Load testing using Locust (concurrent users, p95, max latency, throughput)

EVALUATION

The results show that application-level latency and p95 stability are more important than raw synthetic benchmarks, especially for Odoo workloads.

Shared x86 performance instances (CPX series) consistently provided the best balance between responsiveness, throughput, and scalability.

Dedicated CPU instances showed no clear advantage for application latency, while ARM-based instances were cost-efficient but reached limits under higher concurrency.

CPX42 offers additional performance headroom for concurrent applications, background jobs, and future growth, making it the preferred choice for this workload.