


Dynamic documents in Python

reproducible research with Quarto

2026-07-30



Artwork from “Hello, Quarto” keynote by Julia Lowndes and Mine Çetinkaya-Rundel, presented at RStudio Conference 2022. Illustrated by Allison Horst.

```
---
title: "ggplot2 demo"
author: "Norah Jones"
date: "5/22/2021"
format:
  html:
    fig-width: 8
    fig-height: 4
    code-fold: true
---
```

Source

```
## Air Quality
```

```
@fig-airquality further explores the impact of
temperature on ozone level.
```

```
```{r}
#| label: fig-airquality
#| fig-cap: Temperature and ozone level.
#| warning: false
```

```
library(ggplot2)
```

```
ggplot(airquality, aes(Temp, Ozone)) +
 geom_point() +
 geom_smooth(method = "loess"
)
```
```



ggplot2 demo

Norah Jones

May 22nd, 2021

Output

Air Quality

[Figure 1](#) further explores the impact of temperature on ozone level.

► Code





Figure 1: Temperature and ozone level.

Quarto




Dynamic: code and text in same document

Reproducible: re-run your analysis, re-render your document



Flexible: output to different formats easily

Rendering



Your Turn 1

Create a new Quarto file. Use the Command Palette (Cmd/ctrl + Shift + P) in VS Code to create a new Quarto document. Save the file and run the Render command.




```
1  ---
2  title: "Untitled"
3  format: html
4  jupyter: python3
5  ---
6
7  ## Quarto
8
9  Quarto enables you to weave together content and executable code into a finished document.
10 To learn more about Quarto see <https://quarto.org>.
11
12 ## Running Code
13
14 When you click the **Render** button a document will be generated that includes both content and the output of embedded code.
15 You can embed code like this:
16
17 ▶ Run Cell | Run Next Cell
18 ```{python}
19 1 + 1
20 ```
21
22 You can add options to executable code like this
23
24 ▶ Run Cell | Run Above
25 ```{python}
26 #| echo: false
27 2 * 2
28 ```
29
30 The `echo: false` option disables the printing of code (only output is displayed).
```

← document metadata

plain text

code chunks (cells)

Quarto
Prose
Code
Metadata




Quarto


Prose = *Markdown*

Code

Metadata



the Visual Editor



Overview

There are three types of library you'll generally use with OJS:

1. [Observable core libraries](#) automatically available in every document.
2. Third-party JavaScript libraries from [npm](#) and [ObservableHQ](#).
3. Custom libraries you and/or your colleagues have created

In this document we'll provide a high-level overview of the core libraries and some examples of using third-party libraries ([D3](#) and [Arquero](#)). Creating your own libraries is covered in the article on [Code Reuse](#).

Basic Markdown Syntax

`*italic*` `**bold**`

`_italic_` `__bold__`

Basic Markdown Syntax

Header 1

Header 2

Header 3

Basic Markdown Syntax

`http://example.com`

`[linked phrase](http://example.com)`

Learn more about Markdown Syntax with the ten-twenty minute tutorial on markdown at <https://commonmark.org/help/tutorial>.

Your Turn 2 (open **exercises.qmd**)

Read this short introduction to the Visual Editor:

<https://quarto.org/docs/visual-editor/vscode/>


Use the Visual Editor to stylize the text from the Gapminder website below. Experiment with bolding, italicizing, making lists, etc.

Quarto

Prose

Code = *Python code chunks*


Metadata



Code chunks

```
```{python}
#| label: howl
#| echo: false
(my_generation
 .select('best_minds')
 .filter(pl.col('destroyed') == 'by madness'))
```
```

Code chunks




The diagram illustrates the components of a code chunk. It features a code block enclosed in three backticks. An orange arrow points from the text 'code fences (three backticks)' to the opening backticks. A blue arrow points from the text 'code engine' to the opening curly brace of the code block. The code block contains a YAML header and a Python code snippet.

```
```{python}  
#| label: howl
#| echo: false
(my_generation
 .select('best_minds')
 .filter(pl.col('destroyed') == 'by madness'))
```
```

Code chunks

```
chunk options
```{python}
#| label: howl
#| echo: false
(my_generation
 .select('best_minds')
 .filter(pl.col('destroyed') == 'by madness'))
```
```

option values



Code chunks

code chunk comments

↓
``{python}
#| label: howl
#| echo: false
(my_generation
 .select('best_minds')
 .filter(pl.col('destroyed') == 'by madness'))
``

Chunk options

| Option | Effect |
|----------------------------------|--|
| <code>include: false</code> | run the code but don't print it or results |
| <code>eval: false</code> | don't evaluate the code |
| <code>echo: false</code> | run the code and output but don't print code |
| <code>message: false</code> | don't print messages (e.g. from a function) |
| <code>warning: false</code> | don't print warnings |
| <code>fig-cap: "Figure 1"</code> | caption output plot with "Figure 1" |



See the [Quarto documentation](#)

Other languages

First-class support for R, Julia, and Observable JS

Supports Jupyter notebooks

Insert code chunks with **cmd/ctrl + alt/option + I**, Command Palette, or Visual Editor



Start typing and press **tab** to autocomplete chunk options

▷ Run Cell | Run Next Cell | Run Above

```
```{python}
#| label: setup
#| echo:
import echo
import polars.selectors as cs
import seaborn as sns
import matplotlib.pyplot as plt
from gapminder import gapminder
from great_tables import GT
```

▷ Run Cell | Run Next Cell | Run Above

```
```{python}
#| label: setup
#| echo:
import polars as pl
import polars.fused
import seaborn as sns
import matplotlib.pyplot as plt
from gapminder import gapminder
from great_tables import GT
```

Your Turn 3

Create a code chunk. You can type it in manually, use the keyboard short-cut (Cmd/Ctrl + Option/Alt + I), or use the “Insert” button above. Put the following code in it:

```
1 GT(gapminder.head())
```

Render the document

Your Turn 4

Add `echo: false` to the code chunk you created and re-render. What's the difference in the output?

Inline Code

who wept at the romance of the
streets with their pushcarts full of
onions and bad music,
who sat in boxes breathing in the
darkness under the bridge, and rose
up to build `{python}`
`instruments.select('harpsichord')` in
their lofts,
who coughed on the `{python}`
`len(floors)` floor of Harlem crowned
with flame under the tubercular sky
surrounded by orange crates of
theology,
who scribbled all night rocking and
rolling over lofty incantations which
in the yellow morning were stanzas of
gibberish,

Inline Code

who wept at the romance of the
streets with their pushcarts full of
onions and bad music,
who sat in boxes breathing in the
darkness under the bridge, and rose
up to build `{python}` any Python code
`instruments.select('harpsichord')` in
their lofts,
who coughed on the `{python}`
`len(floors)` floor of Harlem crowned
with flame under the tubercular sky
surrounded by orange crates of
theology,
who scribbled all night rocking and
rolling over lofty incantations which
in the yellow morning were stanzas of
gibberish,

single
backtick
+ `{python}`

Your Turn 5

Remove `eval: false` so that Quarto evaluates the code.

Fill in the column name to use `.select()` and `to_numpy()` to get the the number of unique `years` in `gapminder` as a scalar.

Save the results as `n_years`.


Use inline code to describe the data set in the text below the code chunk and re-render.

Quarto

Prose

Code

Metadata = *YAML*



YAML Metadata

```
1 ---
2 title: "Howl"
3 author: "Allen Ginsberg"
4 date: "March 18, 1956"
5 format:
6   html: default
7   pdf:
8     toc: true
9     number-sections: true
10 ---
```

Output formats

Format	Outputs
<code>html</code>	HTML
<code>pdf</code>	PDF
<code>word</code>	Word <code>.docx</code>
<code>odt</code>	OpenOffice <code>.odt</code>
<code>gfm</code>	GitHub-flavored Markdown
<code>revealjs</code>	Reveal Slides (HTML)
<code>beamer</code>	Beamer Slides (PDF)
<code>pptx</code>	Powerpoint Slides

Your Turn 6

Set figure chunk options to the code chunk below, such as **dpi**, **fig-width**, and **fig-height**.

Add your name to the YAML header using **author: Your Name**.

Change **format: html** to use the **toc: true** and **code-fold: true** options and re-render

Parameters

```
1 #| tags: [parameters]
2 param1 = x
3 param2 = y
4 data = df
```

Calling parameters in Python

```
1 param1
2 param2
3 data
```

From the Command Line

```
1 quarto render document.qmd -P param1:0.2 -P param2:0.3
```

Your Turn 7

Change the **params** option in the YAML header to use a different continent. Re-render.

```
1 gapminder_filtered = gapminder.filter(pl.col("continent") == continent)
2
3 sns.lineplot(
4     data=gapminder_filtered,
5     x="year",
6     y="lifeExp",
7     hue="country",
8     palette="Spectral",
9     linewidth=1,
10    legend=False
11 )
12 plt.title(f"Continent: {continent}")
13 sns.set_theme(style="whitegrid")
```

Bibliographies and citations

Bibliography files: .bib, Zotero, others

Citation styles: .csl

[@citation-label]

Visual Editor's citation wizard can help!

Including bibliography files in YAML

```
1 ---  
2 bibliography: file.bib  
3 csl: file.csl  
4 ---
```

the Visual Editor can also manage this for you.

Your turn 8

Cite Causal Inference in text below. Using the citation wizard, find the right citation under My sources > Bibliography.

Add the American Journal of Epidemiology CSL to the YAML using csl: [aje.csl](#)

Re-render

Make cool stuff in Quarto!

- Books
- Blogs
- These slides!

See the Gallery for inspiration

Resources

Quarto Documentation: A comprehensive but friendly introduction to Quarto. Written in Quarto!