

**МИНОБРНАУКИ РОССИИ**  
**САНКТ-ПЕТЕРБУРГСКИЙ ГОСУДАРСТВЕННЫЙ**  
**ЭЛЕКТРОТЕХНИЧЕСКИЙ УНИВЕРСИТЕТ**  
**«ЛЭТИ» ИМ. В.И. УЛЬЯНОВА (ЛЕНИНА)**  
**Кафедра МО ЭВМ**

**ОТЧЕТ**  
**по лабораторной работе №5**  
**по дисциплине «Объектно-ориентированное программирование»**  
**Тема: "Добавление врагов"**

Студент гр. 9383

\_\_\_\_\_

Корсунов А.А.

Преподаватель

\_\_\_\_\_

Жангиров Т.Р.

Санкт-Петербург

2020

### **Цель работы.**

Написать программу в ООП стиле согласно заданию. Углубить знания об ООП, по возможности изучить предложенные паттерны.

### **Задание.**

Создать шаблонный класс врага. Параметр шаблона должен определять поведение врага (параметров шаблона может быть несколько, например отдельный параметр для политики передвижения и для политики атаки). Класс врага должен препятствовать игроку. Класс игрока должен иметь возможность взаимодействовать с врагом и наоборот.

Обязательные требования:

- Создан шаблонный класс врага
- Создано не менее 3 типа поведения врагов
- Взаимодействие происходит через перегруженный оператор

Дополнительные требования:

- Передача хода между игроком и врагами происходит с использованием паттерна Состояния в классе игры

### **Выполнение работы.**

Для выполнения работы использовалась библиотека SFML, предназначенная для работы с 2D графикой.

Был создан Шаблонный класс Opponents, для которого используются классы поведения (Behavior, Behavior\_steal\_people, Behavior\_steal\_alco, Behavior\_to\_start). Класс Behavior – абстрактный (определена чисто виртуальная функция, в которой перегружается унарный оператор '-');

Предложенные паттерны не используются.




Рисунок 1 — Пример работы программы (рыцарь — игрок, лестница — вход, ворота — выход, кролик — объект, который нужно спасти, грибы повышают здоровья, гоблины — отнимают здоровье, щит — добавляет брони, фляга — добавляет очки опьянения, плиты и колонны соответственно проходимые и непроходимые клетки, маги - враги).

```
logs:
log: Игрок установлен в: 0, 0

log: Кролики установлены в: 3, 1

log: Кролики установлены в: 28, 1

log: Кролики установлены в: 1, 8

log: Гоблины установлены в: 6, 3
```

Рисунок 2 — Пример вывода логов в файл.




Рисунок 3

На рисунке 3 изображена UML-диаграмма новых классов, реализованных в данной работе.

### Выводы.

Написана программа в ООП стиле согласно заданию. Углублены знания об ООП, реализованы некоторые из паттернов.

## ПРИЛОЖЕНИЕ А

### ИСХОДНЫЙ КОД ПРОГРАММЫ

#### Файл main.cpp

```
#include "Game_Manager.h"

int main()
{
    Game_Manager play;
    play.start_Game();
    play.draw_and_move();
    return 0;
}
```

#### Файл Cell.h

```
#pragma once
#include "1_Player.h"
#include "Element.h"
#include "Opponents.h"
#include "Behavior_people.h"
#include "Behavior_steal_alco.h"
#include "Behavior_to_start.h"
#include "Behavior.h"

class Cell
{
private:
    bool pass;
    bool out;
    bool in;
    bool player_1;
```

```
bool people;  
bool alcogol;  
bool enemy;  
bool medicine;  
bool armor;  
bool b1;  
bool b2;  
bool b3;
```

```
Element* element;  
Player_1* player_11;  
Opponents<Behavior>* opponents;  
Behavior_people* behavior_people;  
Behavior_steal_alco* behavior_steal_alco;  
Behavior_to_start* behavior_to_start;
```

```
public:
```

```
Cell();  
~Cell();
```

```
void set_unpass(bool value);  
void set_out(bool value);  
void set_in(bool value);  
void set_player_1(bool value);  
void set_people(bool value);  
void set_alcogol(bool value);  
void set_enemy(bool value);  
void set_medicine(bool value);  
void set_armor(bool value);
```

```

void set_b1(bool);
void set_b2(bool);
void set_b3(bool);

bool get_pass();
bool get_out();
bool get_in();
bool get_player_1();
bool get_people();
bool get_alcogol();
bool get_enemy();
bool get_medicine();
bool get_armor();
bool get_b1();
bool get_b2();
bool get_b3();
void set_Element(Element* elem);
void set_Player_1(Player_1* player);
void set_Opponents(Opponents<Behavior>* opponents);
void set_Behavior_people(Behavior_people*);
void set_Behavior_steal_alco(Behavior_steal_alco*);
void set_Behavior_to_start(Behavior_to_start*);
Element* get_Element();
Behavior_people* get_Behavior_people();
Behavior_steal_alco* get_Behavior_steal_alco();
Behavior_to_start* get_Behavior_to_start();
Opponents<Behavior>* get_Opponents();
};

```

**Файл Cell.cpp**

```
#include "Cell.h"
```

```
Cell::Cell()
```

```
{  
    this->pass = true;  
    this->in = false;  
    this->out = false;  
    this->player_1 = false;  
    this->element = nullptr;  
    this->people = false;  
    this->alcogol = false;  
    this->armor = false;  
    this->enemy = false;  
    this->medicine = false;  
    this->player_11 = nullptr;  
    this->opponents = nullptr;  
    this->behavior_people = nullptr;  
    this->behavior_steal_alco = nullptr;  
    this->behavior_to_start = nullptr;  
    this->b1 = false;  
    this->b2 = false;  
    this->b3 = false;  
}
```

```
Cell::~Cell(){};
```

```
void Cell::set_unpass(bool val)
```

```
{  
    this->pass = val;
```



```
    this->in = false;
    this->out = false;
}
```

```
void Cell::set_in(bool val)
{
    this->pass = true;
    this->in = val;
    this->out = false;
}
```

```
void Cell::set_out(bool val)
{
    this->pass = true;
    this->in = false;
    this->out = val;
}
```

```
void Cell::set_player_1(bool val)
{
    this->player_1 = val;
}
```

```
void Cell::set_people(bool val)
{
    this->people = val;
}
```

```
void Cell::set_alcogol(bool val)
```

```
{  
    this->alcogol = val;  
}
```

```
void Cell::set_armor(bool val)  
{  
    this->armor = val;  
}
```

```
void Cell::set_enemy(bool val)  
{  
    this->enemy = val;  
}
```

```
void Cell::set_medicine(bool val)  
{  
    this->medicine = val;  
}
```

```
bool Cell::get_pass()  
{  
    return this->pass;  
}
```

```
bool Cell::get_in()  
{  
    return this->in;  
}
```

```
bool Cell::get_out()
{
    return this->out;
}
```

```
bool Cell::get_player_1()
{
    return this->player_1;
}
```

```
void Cell::set_Element(Element* elem)
{
    this->element = elem;
}
```

```
void Cell::set_Player_1(Player_1* player)
{
    this->player_1 = player;
}
```

```
void Cell::set_Opponents(Opponents<Behavior>* opponents)
{
    this->opponents = opponents;
}
```

```
void Cell::set_Behavior_people(Behavior_people* behavior_people)
{
    this->behavior_people = behavior_people;
}
```

```

void Cell::set_Behavior_steal_alco(Behavior_steal_alco*
behavior_steal_alco)
{
    this->behavior_steal_alco = behavior_steal_alco;
}

```

```

void Cell::set_Behavior_to_start(Behavior_to_start* behavior_to_start)
{
    this->behavior_to_start = behavior_to_start;
}

```

```

bool Cell::get_alcogol()
{
    return this->alcogol;
}

```

```

bool Cell::get_armor()
{
    return this->armor;
}

```

```

bool Cell::get_enemy()
{
    return this->enemy;
}

```

```

bool Cell::get_medicine()
{

```

```
    return this->medicine;  
}
```

```
bool Cell::get_people()  
{  
    return this->people;  
}
```

```
Element* Cell::get_Element()  
{  
    return this->element;  
}
```

```
void Cell::set_b1(bool val)  
{  
    b1 = val;  
}
```

```
void Cell::set_b2(bool val)  
{  
    b2 = val;  
}
```

```
void Cell::set_b3(bool val)  
{  
    b3 = val;  
}
```

```
bool Cell::get_b1()
```

```
{  
    return b1;  
}
```

```
bool Cell::get_b2()  
{  
    return b2;  
}
```

```
bool Cell::get_b3()  
{  
    return b3;  
}
```

```
Opponents<Behavior>* Cell::get_Opponents()  
{  
    return opponents;  
}
```

```
Behavior_people* Cell::get_Behavior_people()  
{  
    return behavior_people;  
}
```

```
Behavior_steal_alco* Cell::get_Behavior_steal_alco()  
{  
    return behavior_steal_alco;  
}
```

```

Behavior_to_start* Cell::get_Behavior_to_start()
{
    return behavior_to_start;
}

```

### **Файл Field.h**

```

#pragma once
#include "Cell.h"
#include "1_Player.h"

class Field
{
private:
    Cell** ptr = nullptr;
    int width, height;
    static Field* object;

    Field(int width, int height);
    ~Field();
    Field(const Field& ref_Field);
    Field& operator=(const Field& ref_Field);
    Field(Field&& ref_Field);
    Field& operator=(Field&& ref_Field);

public:
    static Field* get_Field(int x, int y);
    void In(int x, int y, bool val);
    void Out(int x, int y, bool val);
    void Unpass(int x, int y, bool val);
    void Player_1(int x, int y, bool val);
}

```

```
void del_Player_1(int x, int y, bool val);
```

```
friend class Game_Manager;
```

```
friend class Iterator;
```

```
};
```

**Файл Field.cpp**

```
#include "Field.h"
```

```
Field* Field::object = nullptr;
```

```
Field::Field(int x, int y) : width(x), height(y)
```

```
{  
    this->ptr = new Cell* [this->width];  
    for (int i = 0; i < this->width; i++)  
    {  
        this->ptr[i] = new Cell [this->height];  
    }  
}
```

```
Field::~~Field()
```

```
{  
    for (int i = 0; i < this->width; i++)  
    {  
        delete[] this->ptr[i];  
    }  
    delete[] this->ptr;  
}
```

```
Field* Field::get_Field(int x, int y)
```



```

{
    object = new Field(x, y);
    return object;
}

```

```

void Field::In(int x, int y, bool val)
{
    if (x >= 0 && x < this->width && y >= 0 && y < this->height)
    {
        this->ptr[x][y].set_in(val);
    }
}

```

```

void Field::Out(int x, int y, bool val)
{
    if (x >= 0 && x < this->width && y >= 0 && y < this->height)
    {
        this->ptr[x][y].set_out(val);
    }
}

```

```

void Field::Unpass(int x, int y, bool val)
{
    if (x >= 0 && x < this->width && y >= 0 && y < this->height)
    {
        this->ptr[x][y].set_unpass(0);
    }
}

```

```

void Field::Player_1(int x, int y, bool val)
{
    if (x >= 0 && x < this->width && y >= 0 && y < this->height)
    {
        this->ptr[x][y].set_player_1(1);
    }
}

```

```

void Field::del_Player_1(int x, int y, bool val)
{
    if (x >= 0 && x < this->width && y >= 0 && y < this->height)
    {
        this->ptr[x][y].set_player_1(0);
    }
}

```

```

Field::Field(const Field& ref_Field)
{
    this->width = ref_Field.width;
    this->height = ref_Field.height;
    this->ptr = new Cell* [ref_Field.width];
    for (int i = 0; i < ref_Field.width; i++)
    {
        this->ptr[i] = new Cell[ref_Field.height];
        for (int j = 0; j < ref_Field.height; j++)
        {
            this->ptr[i][j] = ref_Field.ptr[i][j];
        }
    }
}

```

```
}
```

```
Field& Field::operator=(const Field& ref_Field)
```

```
{
```

```
    if (&ref_Field == this)
```

```
    {
```

```
        return *this;
```

```
    }
```

```
    if (this != &ref_Field){
```

```
        for (int i = 0; i < this->width; i++)
```

```
        {
```

```
            delete[] this->ptr[i];
```

```
        }
```

```
        delete[] this->ptr;
```

```
    }
```

```
    this->width = ref_Field.width;
```

```
    this->height = ref_Field.height;
```

```
    this->ptr = new Cell* [ref_Field.width];
```

```
    for (int i = 0; i < ref_Field.width; i++)
```

```
    {
```

```
        this->ptr[i] = new Cell[ref_Field.height];
```

```
        for (int j = 0; j < ref_Field.height; j++)
```

```
        {
```

```
            this->ptr[i][j] = ref_Field.ptr[i][j];
```

```
        }
```

```
    }
```

```
    return *this;
```

```
}
```

```
Field::Field(Field&& ref_Field)
```

```
{  
    this->ptr = ref_Field.ptr;  
    this->width = ref_Field.width;  
    this->height = ref_Field.height;  
    ref_Field.ptr = nullptr;  
    ref_Field.width = 0;  
    ref_Field.height = 0;  
}
```

```
Field& Field::operator=(Field&& ref_Field)
```

```
{  
    if (&ref_Field == this)  
    {  
        return *this;  
    }  
  
    if (this != &ref_Field){  
        for (int i = 0; i < this->width; i++)  
        {  
            delete[] this->ptr[i];  
        }  
        delete[] this->ptr;  
    }  
  
    this->ptr = ref_Field.ptr;  
    this->width = ref_Field.width;
```

```

    this->height = ref_Field.height;
    ref_Field.ptr = nullptr;
    ref_Field.width = 0;
    ref_Field.height = 0;
    return *this;
}

```

### **Файл FieldIterator.h:**

```

#pragma once
#include "Field.h"

class Iterator
{
private:
    int cell_x, cell_y;
    int width, height;
    const Field* field;

public:
    Iterator(const Field* f);
    Iterator(int i = 0, int j = 0);
    Iterator begin();
    Iterator end();

    void operator++();
    void operator--();
    bool operator==(const Iterator& field_2);
    bool operator!=(const Iterator& field_2);
    Cell& operator*();

```

```

Cell& get_Cell();

void next();
void back();
void up();
void down();
void left();
void right();
};

```

#### **Файл FieldIterator.cpp:**

```
#include "FieldIterator.h"
```

```

Iterator::Iterator(const Field* f)
{
    this->field = f;
    for (int i = 0; i < f->width; i++)
    {
        for (int j = 0; j < f->height; j++)
        {
            this->cell_x = i;
            this->cell_y = j;
        }
    }
}

```

```

Iterator::Iterator(int i, int j)
{

```

```

    this->cell_x = i;
    this->cell_y = j;
}

```

Iterator Iterator::begin()

```

{
    for (int i = 0; i < this->width; i++)
    {
        for (int j = 0; j < this->height; j++)
        {
            if (this->field->ptr[i][j].get_in())
            {
                return Iterator(i,j);
            }
        }
    }
}

```

Iterator Iterator::end()

```

{
    for (int i = 0; i < this->width; i++)
    {
        for (int j = 0; j < this->height; j++)
        {
            if (this->field->ptr[i][j].get_out())
            {
                return Iterator(i,j);
            }
        }
    }
}

```

```

    }
}

void Iterator::next()
{
    if ((this->cell_y + 1) == this->height && (this->cell_x + 1) == this-
>width)
    {
        return;
    }
    if ((this->cell_y + 1) < this->height)
    {
        this->cell_y++;
    }
    else
    {
        this->cell_x++;
    }
}

void Iterator::back()
{
    if ((this->cell_y + 1) == 1 && (this->cell_x + 1) == 1)
    {
        return;
    }
    if ((this->cell_y + 1) > 1)
    {
        this->cell_y--;
    }
}

```



```

    }
    else
    {
        this->cell_x--;
    }
}

void Iterator::up()
{
    if (this->cell_y > 0 && this->field->ptr[this->cell_x][this->cell_y -
1].get_pass())
    {
        this->cell_y--;
    }
}

void Iterator::down()
{
    if (this->cell_y < this->height && this->field->ptr[this->cell_x][this-
>cell_y + 1].get_pass())
    {
        this->cell_y++;
    }
}

void Iterator::left()
{
    if (this->cell_x > 0 && this->field->ptr[this->cell_x - 1][this-
>cell_y].get_pass())

```

```

        {
            this->cell_x--;
        }
    }

    void Iterator::right()
    {
        if (this->cell_x < this->width && this->field->ptr[this->cell_x + 1][this-
>cell_y].get_pass())
        {
            this->cell_x++;
        }
    }

    void Iterator::operator++()
    {
        this->next();
    }

    void Iterator::operator--()
    {
        this->back();
    }

    bool Iterator::operator==(const Iterator& field_2)
    {
        return this->cell_x == field_2.cell_x && this->cell_y == field_2.cell_y
&& this->field == field_2.field;
    }

```

```

bool Iterator::operator!=(const Iterator& field_2)
{
    return this->cell_x != field_2.cell_x || this->cell_y != field_2.cell_y || this-
>field != field_2.field;
}

```

```

Cell& Iterator::get_Cell()
{
    return Field::object->ptr[this->cell_x][this->cell_y];
}

```

```

Cell& Iterator::operator*()
{
    return this->get_Cell();
}

```

### **Файл 1\_Player.h:**

```
#pragma once
```

```

class Player_1
{
private:
    int hp;
    int pos_x, pos_y;
    int armor;
    int zomb;
    int alco;
    int saved_people;
}

```

```

public:
    Player_1();

    int get_hp();
    int get_pos_x();
    int get_pos_y();
    int get_armor();
    int get_zomb();
    int get_alco();
    int get_saved_people();

    void change_place(int, int);
    void steal_hp();
    void add_hp();
    void steal_armor();
    void add_armor();
    void steal_zomb();
    void add_zomb();
    void steal_alco();
    void add_alco();
    void add_saved_people();

    void restart();
};

```

**Файл 1\_Player.cpp:**

```
#include "1_Player.h"
```

```
Player_1::Player_1()
{
    this->hp = 3;
    this->pos_x = 0;
    this->pos_y = 0;
    this->armor = 0;
    this->zomb = 0;
    this->alco = 0;
    this->saved_people = 0;
}
```

```
void Player_1::restart()
{
    this->hp = 3;
    this->pos_x = 0;
    this->pos_y = 0;
    this->armor = 0;
    this->zomb = 0;
    this->alco = 0;
    this->saved_people = 0;
}
```

```
int Player_1::get_hp()
{
    return this->hp;
}
```

```
int Player_1::get_pos_x()
```

```
{  
    return this->pos_x;  
}
```

```
int Player_1::get_pos_y()  
{  
    return this->pos_y;  
}
```

```
int Player_1::get_armor()  
{  
    return this->armor;  
}
```

```
int Player_1::get_zomb()  
{  
    return this->zomb;  
}
```

```
int Player_1::get_alco()  
{  
    return this->alco;  
}
```

```
int Player_1::get_saved_people()  
{  
    return this->saved_people;  
}
```

```
void Player_1::change_place(int x, int y)
{
    this->pos_x = x;
    this->pos_y = y;
}
```

```
void Player_1::steal_hp()
{
    if (this->hp > 0)
    {
        this->hp--;
    }
}
```

```
void Player_1::add_hp()
{
    if (this->hp < 3)
    {
        this->hp++;
    }
}
```

```
void Player_1::steal_armor()
{
    if (this->armor > 0)
    {
        this->armor--;
    }
}
```

```

void Player_1::add_armor()
{
    if (this->armor < 3)
    {
        this->armor++;
    }
}

```

```

void Player_1::steal_zomb()
{
    if (this->zomb > 0)
    {
        this->zomb--;
    }
}

```

```

void Player_1::add_zomb()
{
    if (this->zomb < 5)
    {
        this->zomb++;
    }
}

```

```

void Player_1::steal_alco()
{
    if (this->alco > 0)
    {

```



```

        this->alco--;
    }
}

```

```

void Player_1::add_alco()
{
    if (this->alco < 3)
    {
        this->alco++;
    }
}

```

```

void Player_1::add_saved_people()
{
    if (this->saved_people < 3)
    {
        this->saved_people++;
    }
}

```

### **Файл Element.h:**

```
#pragma once
```

```
#include "1_Player.h"
```

```
class Element
```

```
{
```

```
public:
```

```
    virtual void operator+(Player_1&) = 0;
```

```
};
```

**Файл Element.cpp:**

```
#include "Element.h"
```

**Файл Medicine.h:**

```
#pragma once
```

```
#include "Element.h"
```

```
class Medicine:public Element
{
public:
    void operator+(Player_1&);
};
```

**Файл Medicine.cpp:**

```
#include "Medicine.h"
```

```
void Medicine::operator+(Player_1& player_1)
{
    player_1.add_hp();
}
```

**Файл Armor.h:**

```
#pragma once
```

```
#include "Element.h"
```

```
class Armor:public Element
{
public:
```

```
void operator+(Player_1&);  
};
```

#### **Файл Armor.cpp:**

```
#include "Armor.h"
```

```
void Armor::operator+(Player_1& player_1)  
{  
    player_1.add_armor();  
}
```

#### **Файл People.h:**

```
#pragma once
```

```
#include "Element.h"
```

```
class People:public Element  
{  
public:  
    void operator+(Player_1&);  
};
```

#### **Файл People.cpp:**

```
#include "People.h"
```

```
void People::operator+(Player_1& player_1)  
{  
    player_1.add_saved_people();  
}
```

Файл Alcogol.h:

```
#pragma once
#include "Factory_Elements.h"
#include "Alcogol.h"

class Factory_Alcogol:public Factory_Element
{
public:
    Element* createElement();
};
```

Файл Alcogol.cpp:

```
#include "Factory_Alcogol.h"

Element* Factory_Alcogol::createElement()
{
    return new Alcogol;
}
```

Файл Factory\_Elements.h:

```
#pragma once
#include "Element.h"

class Factory_Element
{
public:
    virtual Element* createElement() = 0;
};
```

Файл Factory\_Elements.cpp:

```
#include "Factory_Elements.h"
```

Файл Factory\_Medicine.h:

```
#pragma once
```

```
#include "Factory_Elements.h"
```

```
#include "Medicine.h"
```

```
class Factory_Medicine:public Factory_Element
```

```
{
```

```
public:
```

```
    Element* createElement();
```

```
};
```

Файл Factory\_Medicine.cpp:

```
#include "Factory_Medicine.h"
```

```
Element* Factory_Medicine::createElement()
```

```
{
```

```
    return new Medicine;
```

```
}
```

Файл Factory\_People.h:

```
#pragma once
```

```
#include "Factory_Elements.h"
```

```
#include "People.h"
```

```

class Factory_People:public Factory_Element
{
public:
    Element* createElement();
};

```

Файл Factory\_People.cpp:

```

#include "Factory_People.h"

```

```

Element* Factory_People::createElement()
{
    return new People;
}

```

Файл Factory\_Enemy.h:

```

#pragma once
#include "Factory_Elements.h"
#include "Enemy.h"

```

```

class Factory_Enemy:public Factory_Element
{
public:
    Element* createElement();
};

```

**Файл Factory\_Enemy.cpp:**

```

#include "Enemy.h"

```

```

void Enemy::operator+(Player_1& player_1)

```

```

{
    if (player_1.get_armor() == 0)
    {
        player_1.steal_hp();
    }
    else
    {
        player_1.steal_armor();
    }
}

```

#### **Файл Factory\_Armor.h:**

```

#pragma once
#include "Factory_Elements.h"
#include "Armor.h"

class Factory_Armor:public Factory_Element
{
public:
    Element* createElement();
};

```

#### **Файл Factory\_Armor.cpp:**

```

#include "Factory_Armor.h"

Element* Factory_Armor::createElement()
{
    return new Armor;
}

```

Файл Factory\_Alcohol.h:

```
#pragma once
#include "Factory_Elements.h"
#include "Alcohol.h"

class Factory_Alcohol:public Factory_Element
{
public:
    Element* createElement();
};
```

Файл Factory\_Alcohol.cpp:

```
#include "Factory_Alcohol.h"

Element* Factory_Alcohol::createElement()
{
    return new Alcohol;
}
```

**Файл Game\_Manager.h:**

```
#include "Field.h"
#include <SFML/Graphics.hpp>
#include "FieldIterator.h"
#include "1_Player.h"
#include "Factory_Alcohol.h"
#include "Factory_Armor.h"
#include "Factory_Enemy.h"
```



```

#include "Factory_Medicine.h"
#include "Factory_People.h"
#include "Log_player.h"
#include "Log_print_file.h"
#include "Opponents.h"
#include "Behavior.h"
#include "Behavior_people.h"
#include "Behavior_steal_alco.h"
#include "Behavior_to_start.h"

```

```

class Game_Manager

```

```

{

```

```

public:

```

```

    void start_Game();

```

```

    void draw_and_move();

```

```

private:

```

```

    Field* field = Field::get_Field(30, 10);

```

```

    Behavior_people behavior_people;

```

```

    Behavior_steal_alco behavior_steal_alco;

```

```

    Behavior_to_start behavior_to_start;

```

```

    Player_1 man;

```

```

    Factory_People factory_people; //0 - условные номера для вызовов в

```

функциях

```

    Factory_Alcohol factory_alcohol; //1

```

```

    Factory_Armor factory_armor; //2

```

```

    Factory_Enemy factory_enemy; //3

```

```
Factory_Medicine factory_medicine; //4
```

```
Log_print_file logs;
```

```
Log_player logs_change;
```

```
void set_Field();
```

```
void set_Player_and_Elements_and_Logs();
```

```
void set_Player_and_logs(int, int);
```

```
void set_Elements_and_logs(int, int, int);
```

```
void change_move_player(int, int);
```

```
void change_move_player_help(int);
```

```
void helper_draw(sf::RenderWindow, sf::Sprite);
```

```
void helper_draw(sf::RenderWindow, sf::Sprite, int, int, int, int);
```

```
void check_behavior();
```

```
int w = 32;
```

```
int x = 0;
```

```
int y = 0;
```

```
};
```

### **Файл Game\_Manager.cpp:**

```
#include "Game_Manager.h"
```

```
using namespace sf;
```

```
void Game_Manager::start_Game()
```

```
{
```

```
    set_Field();
```

```
    set_Player_and_Elements_and_Logs();
```

```

    }

    void Game_Manager::draw_and_move()
    {
        RenderWindow app(VideoMode(32 * field->width, 32 * (field-
>height+2)), "Cool game :)");
        Texture t;
        Sprite s(t);
        Font font;
        Text Player_1_info;
        t.loadFromFile("C:/Users/Eldorado/Documents/qwe/oop/govno/fantasy-
tileset.png");
        font.loadFromFile("19849.ttf");
        Player_1_info.setFont(font);
        Player_1_info.setCharacterSize(20);
        Player_1_info.setFillColor(Color::Red);
        Player_1_info.setStyle(Text::Bold);
        Player_1_info.setPosition(Vector2f(0,(field->height)*32));

        while (app.isOpen())
        {
            app.clear();
            for (int i = 0; i < field->width; i++)
            {
                for (int j = 0; j < field->height; j++)
                {
                    if (!field->ptr[i][j].get_in() && !field->ptr[i][j].get_out() &&
field->ptr[i][j].get_pass())
                    {

```

```

        s.setTextureRect(IntRect(0, 1 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
        //проходимая
    }
    if (field->ptr[i][j].get_in())
    {
        s.setTextureRect(IntRect(5 * w, 1 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
        //ВХОД
    }
    if (field->ptr[i][j].get_out())
    {
        s.setTextureRect(IntRect(1 * w, 3 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
        //ВЫХОД
    }
    if (!field->ptr[i][j].get_pass())
    {
        s.setTextureRect(IntRect(0 * w, 3 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
        //непроходимая
    }
    if (field->ptr[i][j].get_player_1())
    {
        s.setTextureRect(IntRect(5 * w, 18 * w, w, w));

```

```

        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_people())
    {
        s.setTextureRect(IntRect(1 * w, 20 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_enemy())
    {
        s.setTextureRect(IntRect(0 * w, 18 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_medicine())
    {
        s.setTextureRect(IntRect(0 * w, 20 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_armor())
    {
        s.setTextureRect(IntRect(7 * w, 13 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_alcogol())
    {

```

```

        s.setTextureRect(IntRect(6 * w, 5 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
    if (field->ptr[i][j].get_b1() || field->ptr[i][j].get_b2() || field-
>ptr[i][j].get_b3())
    {
        s.setTextureRect(IntRect(7 * w, 18 * w, w, w));
        s.setPosition(i*w, j*w);
        app.draw(s);
    }
}

if (man.get_hp() == 0)
{
    Player_1_info.setString("Game over\nYou saved " +
std::to_string(man.get_saved_people()) + " rabbits");
    app.draw(Player_1_info);
}
else if (man.get_saved_people() == 3 && x == field->width-1 && y
== field->height-1)
{
    Player_1_info.setString("Victory\nYou saved everyone");
    app.draw(Player_1_info);
}
else
{

```

```

        Player_1_info.setString("Hp: " + std::to_string(man.get_hp()) +
"\tarmor:  " + std::to_string(man.get_armor()) + "\tsaved  poeple:  " +
std::to_string(man.get_saved_people()) + "\talco:      " +
std::to_string(man.get_alco()));
        app.draw(Player_1_info);
    }
    Event e;

while(app.pollEvent(e))
{
    if (e.type == Event::Closed)
        app.close();
    if (e.type == Event::KeyPressed)
    {
        if (e.key.code == Keyboard::Escape) app.close();
        if (e.key.code == Keyboard::Left)
        {
            if ((x-1) >= 0)
            {
                if (field->ptr[x-1][y].get_pass())
                {
                    change_move_player(-1, 0);
                }
            }
        }
        if (e.key.code == Keyboard::Right)
        {
            if ((x+1) < field->width)
            {

```

```

        if (field->ptr[x+1][y].get_pass())
        {
            change_move_player(1, 0);
        }
    }
}

if (e.key.code == Keyboard::Up)
{
    if ((y-1) >= 0)
    {
        if (field->ptr[x][y-1].get_pass())
        {
            change_move_player(0, -1);
        }
    }
}

if (e.key.code == Keyboard::Down)
{
    if ((y+1) < field->height)
    {
        if (field->ptr[x][y+1].get_pass())
        {
            change_move_player(0, 1);
        }
    }
}

if (e.key.code == Keyboard::R)
{
    field->del_Player_1(x,y,0);
}

```



```

        field->ptr[x][y].set_player_1(0);
        x = 0;
        y = 0;
        man.restart();
        start_Game();
    }
}
app.display();
}
}

void Game_Manager::change_move_player_help(int way)
{
    *(field->ptr[x][y].get_Element()) + man;
    switch(way)
    {
        case 0:
            field->ptr[x][y].set_people(0);
            logs_change.print_params(&logs, 4);
            break;
        case 1:
            field->ptr[x][y].set_enemy(0);
            logs_change.print_params(&logs, 3);
            break;
        case 2:
            field->ptr[x][y].set_medicine(0);
            logs_change.print_params(&logs, 0);
            break;
    }
}

```

```

case 3:
    field->ptr[x][y].set_armor(0);
    logs_change.print_params(&logs, 1);
    break;
case 4:
    field->ptr[x][y].set_alcohol(0);
    logs_change.print_params(&logs, 2);
    break;
}
}

void Game_Manager::change_move_player(int x_change, int y_change)
{
    x = x + x_change;
    y = y + y_change;
    man.change_place(x, y);
    field->ptr[x][y].set_Player_1(&man);
    field->Player_1(x,y,1);
    field->del_Player_1(x-x_change,y-y_change,0);
    logs_change.print_params(&logs, 5);
    if (field->ptr[x][y].get_people())
    {
        change_move_player_help(0);
    }
    if (field->ptr[x][y].get_enemy())
    {
        change_move_player_help(1);
    }
    if (field->ptr[x][y].get_medicine())

```

```

    {
        change_move_player_help(2);
    }
    if (field->ptr[x][y].get_armor())
    {
        change_move_player_help(3);
    }
    if (field->ptr[x][y].get_alcogol())
    {
        change_move_player_help(4);
    }
    if (field->ptr[x][y].get_b1() || field->ptr[x][y].get_b2() || field->ptr[x]
[y].get_b3())
    {
        check_behavior();
    }
}

```

```

void Game_Manager::check_behavior()
{
    if (field->ptr[x][y].get_b1())
    {
        field->ptr[x][y].set_b1(0);
        *(field->ptr[x][y].get_Behavior_people()) - man;
        logs_change.print_params(&logs, 6);
    }
    if (field->ptr[x][y].get_b3())
    {
        field->ptr[x][y].set_b3(0);
    }
}

```

```

        *(field->ptr[x][y].get_Behavior_to_start()) - man;
        field->del_Player_1(x,y,0);
        field->ptr[x][y].set_player_1(0);
        x = man.get_pos_x();
        y = man.get_pos_y();
        field->ptr[x][y].set_player_1(1);
        logs_change.print_params(&logs, 8);
    }
    if (field->ptr[x][y].get_b2())
    {
        field->ptr[x][y].set_b2(0);
        *(field->ptr[x][y].get_Behavior_steal_alco()) - man;
        logs_change.print_params(&logs, 7);
    }
}

```

```

void Game_Manager::set_Field()
{
    for (int i = 2; i < 30; i++)
    {
        field->Unpass(i, 0, 0);
    }
    for (int i = 0; i < 8; i++)
    {
        field->Unpass(29, i, 0);
    }
    for (int i = 1; i < 10; i++)
    {
        field->Unpass(0, i, 0);
    }
}

```

```

    }
    for (int i = 1; i < 29; i++)
    {
        field->Unpass(i, 9, 0);
    }
    field->In(0,0,1);
    field->Player_1(0,0,1);
    field->Out(29,9,1);
    field->Unpass(7,2,0);
    field->Unpass(7,3,0);
    field->Unpass(7,4,0);
    field->Unpass(4,5,0);
    field->Unpass(4,6,0);
    field->Unpass(4,7,0);
    field->Unpass(4,8,0);
    field->Unpass(2,6,0);
    field->Unpass(2,7,0);
    field->Unpass(6,6,0);
    field->Unpass(6,7,0);
    field->Unpass(1,4,0);
    field->Unpass(4,7,0);
    for (int i = 9; i < 29; i++)
    {
        field->Unpass(i, 2, 0);
    }
    field->Unpass(10,6,0);
    for (int i = 11; i < 28; i++)
    {
        field->Unpass(i, 6, 0);
    }

```

```

    }
    field->Unpass(10,3,0);
    field->Unpass(10,4,0);
    field->Unpass(9,4,0);
    field->Unpass(9,5,0);
    field->Unpass(9,6,0);
    field->Unpass(4,8,0);
    field->Unpass(2,4,0);
    field->Unpass(4,4,0);
    field->Unpass(6,5,0);
    field->Unpass(2,0,0);
    field->Unpass(2,1,0);
    field->Unpass(2,2,0);
    field->Unpass(3,2,0);
    field->Unpass(4,2,0);
    field->Unpass(5,2,0);
    field->Unpass(6,2,0);
    field->Unpass(6,4,0);
}

```

```

void Game_Manager::set_Player_and_logs(int x, int y)
{
    field->ptr[x][y].set_Player_1(&man);
    logs_change.set_player(&man);
    logs.add_logs("Игрок установлен в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
}

```

```

void Game_Manager::set_Elements_and_logs(int x, int y, int log)

```

```

{
    switch(log)
    {
    case 0:
        field->ptr[x][y].set_Element(factory_people.createElement());
        field->ptr[x][y].set_people(1);
        logs.add_logs("Кролики установлены в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
        break;
    case 1:
        field->ptr[x][y].set_Element(factory_enemy.createElement());
        field->ptr[x][y].set_enemy(1);
        logs.add_logs("Гоблины установлены в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
        break;
    case 2:
        field->ptr[x][y].set_Element(factory_medicine.createElement());
        field->ptr[x][y].set_medicine(1);
        logs.add_logs("Аптечки установлены в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
        break;
    case 3:
        field->ptr[x][y].set_Element(factory_armor.createElement());
        field->ptr[x][y].set_armor(1);
        logs.add_logs("Броня установлена в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
        break;
    case 4:
        field->ptr[x][y].set_Element(factory_alcogol.createElement());

```

```

        field->ptr[x][y].set_alcogol(1);
        logs.add_logs("Бутыль установлена в: " + std::to_string(x) + ", " +
std::to_string(y) + "\n");
        break;
    case 5:
        field->ptr[x][y].set_Behavior_people(&behavior_people);
        field->ptr[x][y].set_b1(1);
        logs.add_logs("Врагу установлено поведение b1 (кража кролика) в
позиции: " + std::to_string(x) + ", " + std::to_string(y) + "\n");
        break;
    case 6:
        field->ptr[x][y].set_Behavior_steal_alco(&behavior_steal_alco);
        field->ptr[x][y].set_b2(1);
        logs.add_logs("Врагу установлено поведение b2 (кража бутылки) в
позиции: " + std::to_string(x) + ", " + std::to_string(y) + "\n");
        break;
    case 7:
        field->ptr[x][y].set_Behavior_to_start(&behavior_to_start);
        field->ptr[x][y].set_b3(1);
        logs.add_logs("Врагу установлено поведение b3 (отправка в начало)
в позиции: " + std::to_string(x) + ", " + std::to_string(y) + "\n");
        break;
    }
}

void Game_Manager::set_Player_and_Elements_and_Logs()
{
    set_Player_and_logs(0, 0);
    set_Elements_and_logs(3, 1, 0);
}

```



```

    set_Elements_and_logs(28, 1, 0);
    set_Elements_and_logs(1, 8, 0);
    set_Elements_and_logs(6, 3, 1);
    set_Elements_and_logs(3, 8, 1);
    set_Elements_and_logs(7, 5, 1);
    set_Elements_and_logs(1, 5, 2);
    set_Elements_and_logs(9, 3, 2);
    set_Elements_and_logs(7, 7, 3);
    set_Elements_and_logs(10, 5, 3);
    set_Elements_and_logs(28, 3, 4);
    set_Elements_and_logs(9, 7, 5);
    set_Elements_and_logs(10, 7, 6);
    set_Elements_and_logs(11, 7, 7);
}

```

### **Opponents.h:**

```
#pragma once
```

```
template <class T> class Opponents{};
```

### **Opponents.cpp:**

```
#include "Opponents.h"
```

### **Behavior.h:**

```
#pragma once
```

```
#include "1_Player.h"
```

```
class Behavior
```

```
{
```

```
public:
```

```
    virtual void operator-(Player_1&) = 0;
```

```
    virtual ~Behavior() {};  
};
```

### **Behavior.cpp:**

```
#include "Behavior.h"
```

### **Behavior\_steal\_people.h:**

```
#pragma once
```

```
#include "Behavior.h"
```

```
class Behavior_people:public Behavior  
{  
public:  
    void operator-(Player_1&);  
};
```

### **Behavior\_steal\_people.cpp:**

```
#include "Behavior_people.h"
```

```
void Behavior_people::operator-(Player_1& player_1)  
{  
    player_1.steal_people();  
}
```

### **Behavior\_steal\_alco.h:**

```
#pragma once
```

```
#include "Behavior.h"
```

```
class Behavior_steal_alco:public Behavior  
{  
public:  
    void operator-(Player_1&);  
};
```

**Behavior\_steal\_alco.cpp:**

```
#include "Behavior_steal_alco.h"
```

```
void Behavior_steal_alco::operator-(Player_1& player_1)
{
    player_1.steal_alco();
}
```

**Behavior\_to\_start.h:**

```
#pragma once
```

```
#include "Behavior.h"
```

```
class Behavior_to_start:public Behavior
{
public:
    void operator-(Player_1&);
};
```

**Behavior\_to\_start.cpp:**

```
#include "Behavior_to_start.h"
```

```
void Behavior_to_start::operator-(Player_1& player_1)
{
    player_1.change_place(0, 0);
}
```