

# MIA – Medical Image Analysis

## Shape Modelling

MSCV – University of Girona  
2013-2014

# Shape Modelling: overview

2

- Aim:
  - ▣ A popular approach in order to distinguish objects from background: **solve the segmentation problem.**
  - ▣ There are some other approaches:
    - **Threshold** techniques, which make decisions based on local pixel information.
    - **Edge-based** methods: focused around contour detection.
    - **Region-based** methods: the image is partitioned into connected regions by grouping neighboring pixels of similar intensity levels.
    - Connectivity-preserving relaxation-based segmentation method: The main idea is to start with some initial boundary shape represented in the form of spline curves, and iteratively modify it by applying various shrink/expansion operations according to some energy function: **active contour model.**

# Shape Modelling: approaches

3

## □ Tim Cootes

- Professor of Computer Vision
- Imaging Sciences and the Biomedical Imaging Institute
- The University of Manchester
- Research Interests:
  - Statistical models of shape and appearance
  - Model matching algorithms
  - Methods of computing correspondence across sets of shapes and images
  - Applications in medical image analysis and face image interpretation



# Shape Modelling: approaches

4

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches


5

- **Statistical Models.**
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

6

## □ Statistical Models.



# Shape Modelling: approaches




7

## □ Statistical Models: initial image processing


### □ Selection of landmarks:

- Well defined corners
- 'T' junctions
- Easily located biologic landmarks


### □ Creation of a set of vectors for each object



Cootes (Active Shape tutorial)



(a)



(b)

Double-Edge Detection of Radiographic Lumbar Vertebrae Images Using Pressurized Open DGVF Snakes. Texas Tech University, Lubbock, Texas, USA.


# Shape Modelling: approaches

8

- Statistical Models: initial image processing
  - ▣ Alignment. Basic coregistration of the shape in the same coordinate system.
  - ▣ Procrustes analysis.
  - ▣ Creation of parameterised model.



Aligning shapes



# Shape Modelling: approaches

9

- Statistical Models: initial image processing
  - ▣ Procrustes analysis:
    - The Procrustes distance is a least-squares type shape metric that requires two aligned shapes with one-to-one point correspondence.
    - The alignment part involves four steps:
      - Compute the centroid of each shape.
      - Re-scale each shape to have equal size.
      - Align w.r.t. position the two shapes at their centroids.
      - Align w.r.t. orientation by rotation.

# Shape Modelling: approaches

10

- Statistical Models: initial image processing
  - ▣ Procrustes analysis: for 2 vectors, find transformation which minimizes


$$|x_1 - T(x_2)|^2$$

- ▣ for n vectors, minimize:

$$\sum |m - T_i(x_i)|^2$$

$$\mathbf{m} = \frac{1}{n} \sum T_i(\mathbf{x}_i) \quad |\mathbf{m}|=1$$

- ▣ Resulting shapes have
  - Identical centre of gravity
  - Approximately the same scale and orientation



# Shape Modelling: approaches

11

- Statistical Models: initial image processing
  - ▣ Parameterised model


$$\mathbf{x} = f_{shape}(\mathbf{b}) \longrightarrow \mathbf{x} = \bar{\mathbf{x}} + \mathbf{P}\mathbf{b}$$

- $\bar{\mathbf{x}}$  is calculated in procrustes analysis
- $\mathbf{P}$  is the model parameters
- We have only to find  $\mathbf{P}$

# Shape Modelling: approaches

12

## □ Statistical Models: training data set



MR of heart, training set



Surfaces of data set images

“...a training set consists of an **input vector** and an answer vector, and is used together with a **supervised learning** method to train a knowledge database...”

- Wikipedia

# Shape Modelling: approaches

13

- Statistical Models: variation model
  - ▣ Given: S – number of aligned vectors (shapes in the training set)  
N – number of landmarks  
D – dimensions of the problem (1D, 2D, or 3D)
  - ▣ Reduce dimension (PCA) form ND

$$\mathbf{x} \approx \bar{\mathbf{x}} + \mathbf{P}\mathbf{b}$$


Where  $\mathbf{P}$  contains the  $t$  eigenvectors, corresponding to  $t$  largest eigenvalues  $\mathbf{b}$ -vectors of parameters.

# Shape Modelling: approaches

14

- Statistical Models: variation model
  - Example:

$$\mathbf{x} \approx \bar{\mathbf{x}} + \mathbf{P}\mathbf{b}$$



Labeled brain MR image



Varying the most significant parameter  $b_1$



Varying the most significant parameter  $b_2$

# Shape Modelling: approaches

15

- Statistical Models: variation model
  - ▣ Generating new example shapes:
    - Shapes of training set approximated by  $\mathbf{x} = \bar{\mathbf{x}} + \mathbf{P}\mathbf{b}$ , where  $\mathbf{P} = (\mathbf{p}_1 \mathbf{p}_2 \dots \mathbf{p}_t)$  is the matrix of the first  $t$  eigenvectors and  $\mathbf{b} = (b_1 b_2 \dots b_t)^T$  is a vector of weights.
    - Vary  $b_k$  within suitable limits for similar shapes.

$$-3\sqrt{\lambda_k} \leq b_k \leq 3\sqrt{\lambda_k}$$

# Shape Modelling: approaches

16

## □ Statistical Models: variation model

### □ Heart Example

- 66 examples
- 96 points
  - Left ventricle
  - Right ventricle
  - Left atrium
- Traced by cardiologists



# Shape Modelling: approaches

17

## □ Statistical Models: variation model

### □ Heart Example

- 66 examples
- 96 points
  - Left ventricle
  - Right ventricle
  - Left atrium
- Traced by cardiologists





Eigenvalues of the Covariance Matrix Derived from a Set of Heart Ventricle Shapes

Eigenvalue	$\frac{\lambda_i}{\lambda_T} \times 100\%$
$\lambda_1$	37%
$\lambda_2$	17%
$\lambda_3$	13%
$\lambda_4$	7%
$\lambda_5$	6%
$\lambda_6$	4%

# Shape Modelling: approaches

18

- Statistical Models: variation model
  - Heart Example



# Shape Modelling: approaches

19

- Statistical Models: experimental data set
  - ▣ Fitting a model to new points:
    - By minimizing the sum of square distances between corresponding model and image points in the iterative approach.
    - Iteratively generate plausible models and apply to find a match to the image.

# Shape Modelling: approaches

20

- Statistical Models: evaluating
  - ▣ Testing how well the model generalizes:
    - Leave-one-out experiment
    - S training shapes: S-1 are used to generate the model.  
1 as an example to fit the model to and record the error.  
Repeat for all S shapes.

# Shape Modelling: approaches

21

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

22

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

23

- Active Shape Models (ASMs)
  - ▣ Suppose we have a statistical shape model
    - Trained from sets of examples
  - ▣ How do we use it to interpret new images?
  - ▣ Use an “Active Shape Model”
  - ▣ Iterative method of matching model to image.

# Shape Modelling: approaches


24

- Active Shape Models (ASMs)
  - ▣ Assume we have an initial estimate for the pose and shape parameters (e.g. the mean shape):  $\mathbf{x} = \bar{\mathbf{x}} + \mathbf{P}\mathbf{b}$
  - ▣ The model points are defined in a model coordinate frame.
  - ▣ Must apply global transformation  $\mathbf{T}$  to place in image.

# Shape Modelling: approaches

25

- Active Shape Models (ASMs)
  - ▣ Must apply global transformation  $T$  to place in image.



where  $(\mathbf{X}_c, \mathbf{Y}_c)$  is the position of the centre of the model in the image frame, rotated by  $\theta$  and scaled by  $s$ .

# Shape Modelling: approaches



26

- Active Shape Models (ASMs): how it works

- Match shape model to new image

- Require:

- Statistical shape model
    - Model of image structure at each point/training set




# Shape Modelling: approaches

27

## □ Active Shape Models (ASMs): how it works



### ■ Algorithm

- Examine a region of the image around each point  $(X_i, Y_i)$  to find the best nearby match.
- Update parameters  $(X_t, Y_t, s, \theta, b)$  to best fit the new found points.
- Repeat until convergence.



# Shape Modelling: approaches

28

- Active Shape Models (ASMs): how it works
    - ▣ Improved efficiency
      - Multi-resolution framework: gaussian image pyramid formed by repeated smoothing and sub-sampling.
      - All shapes.
      - Useful to classify objects based on shape or appearance, which have well defined shape.
      - Useful when approximate location of target object is known.
- 
- Level 2  
Level 1  
Level 0
- Each level half the size of the one below
- 
- Level 2  
Level 1  
Level 0

# Shape Modelling: approaches

29

- Active Shape Models (ASMs): how it works
  - ▣ Limitations
    - Can fail if the initial guess is too far from the target.
    - Problems when position/size/orientation of targets is not known approximately.
    - Doesn't work with widely varying shapes.
    - The model can only deform in ways observed in the training set. If is not there, the model will not fit to it.



Initial guess





Search result

# Shape Modelling: approaches

30


- Active Shape Models (ASMs): example
  - ▣ Hip radiograph



# Shape Modelling: approaches

31

- Active Shape Models (ASMs): example
  - ▣ Spine



# Shape Modelling: approaches

32

- Statistical Models.
- Active Shape Models (ASMs).
- **Active Appearance Models (AAMs).**
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

33

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

34

- Active Appearance Models (AAMs)
  - ▣ Suppose we have a statistical shape model
    - Trained from sets of examples
  - ▣ How do we use it to interpret new images?
  - ▣ Use an “Active Appearance Model”
  - ▣ Iterative method of matching model to image.
  - ▣ The Active Appearance Model (AAM) is a **generalization** of the Active Shape Model approach, but uses **all the information in the image** region covered by the target object, rather than just near modeled edges.

# Shape Modelling: approaches

35

- Active Appearance Models (AAMs): Method
  - ▣ Since statistical shapes model the shape change of an object, why not construct a similar statistical model to represent the intensity variation across a region?
  - ▣ Method: given a set of training images, labeled with landmark points, we can use image warping to deform each image so that the object has the mean shape, then build a statistical model of the grey-levels across the object.


Ex: the central image  
is the mean



# Shape Modelling: approaches

36

- Active Appearance Models (AAMs): Method
  - ▣ For each example, extract a shape vector



Shape,  $\mathbf{x} = (x_1, y_1, \dots, x_n, y_n)^T$


- ▣ Built a statistical shape model:

$$\mathbf{x} = \bar{\mathbf{x}} + \mathbf{P}_s \mathbf{b}_s$$

# Shape Modelling: approaches

37

- Active Appearance Models (AAMs): Method
  - For each example, extract a texture vector



# Shape Modelling: approaches

38

- Active Appearance Models (AAMs): Method
  - ▣ Warping texture
    - Problem:
      - Given corresponding points in two images, how do we warp one into the other?
    - Two common solutions:
      - Piece-wise linear using triangle mesh
      - Thin-plate spline interpolation

# Shape Modelling: approaches

39

- Active Appearance Models (AAMs): Method
  - ▣ Warping texture



- Normalise vectors (as for eigenfaces)
- Build eigen-model

$$\mathbf{g} = \bar{\mathbf{g}} + \mathbf{P}_g \mathbf{b}_g$$

# Shape Modelling: approaches

40

- Active Appearance Models (AAMs): Method
  - ▣ Shape and texture often correlated
    - When smile, shadows change (texture) and shape changes
  - ▣ Learning this correlation leads to more compact (and specific) model.

$$\mathbf{x} = \bar{\mathbf{x}} + \mathbf{P}_s \mathbf{b}_s \quad \mathbf{g} = \bar{\mathbf{g}} + \mathbf{P}_g \mathbf{b}_g$$


- ▣ Varying  $\mathbf{c}$  changes both shape and texture:

$$\boxed{\begin{aligned}\mathbf{x} &= \bar{\mathbf{x}} + \mathbf{Q}_s \mathbf{c} \\ \mathbf{g} &= \bar{\mathbf{g}} + \mathbf{Q}_g \mathbf{c}\end{aligned}}$$

# Shape Modelling: approaches

41

## □ Active Appearance Models (AAMs): Example






A face model built from 400 images. The figures shows frames from an AAM search for a new face, each starting with the mean model displaced from the true face centre.

# Shape Modelling: approaches

42


- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI (courtesy of Milan Sonka, The University of Iowa).



# Shape Modelling: approaches

43

- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: mean shape and mean grey level
    - Modelling of shape: represented by landmark points
    - Represent the shape borders of objects as a collection of corresponding points
    - Modelling of texture: represented by pixel intensities



# Shape Modelling: approaches

44

- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: mean shape and mean grey level
    - Each example can be expressed by two vectors

$$b_s \approx P_s^T (x - \bar{x})$$


$$b_g \approx P_g^T (g - \bar{g})$$

- $b_s$  and  $b_g$  can be concatenated and PCA applied

# Shape Modelling: approaches

45

- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: mean shape and mean grey level



# Shape Modelling: approaches


46

- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: matching
  - ▣ Matching the AAM to the image requires
    - A criterion function
      - The RMS error of the ‘difference image’ between the model and the underlying image patch
    - A minimization procedure
    - Derivatives of the criterion function with respect to all ‘optimizable’ parameters
      - Can be estimated using multiple linear regression
      - Using examples of derivative images

# Shape Modelling: approaches

47


- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: results



# Shape Modelling: approaches

48

- Active Appearance Models (AAMs): Example
  - ▣ Cardiac MRI: results
    - However, appearance matching may lock on incorrect features and get stuck in a local minimum.



# Shape Modelling: approaches

49

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

50

- Statistical Models.
- Active Shape Models (ASMs).
- Active Appearance Models (AAMs).
- Active Contour Models, also called snakes.

# Shape Modelling: approaches

51

- Active Contour Models.
  - ▣ Connectivity-preserving relaxation-based segmentation method.
  - ▣ The main idea is to start with some initial boundary shape represented in the form of spline curves, and iteratively modify it by applying various shrink/expansion operations according to some energy function: **active contour model**.



# Shape Modelling: approaches

52

- **Active Contour Models: energy minimization**
  - ▣ **Objective:** find the minimum value for a given energy function.
  - ▣ **Energy function contains two terms:**
    - One term penalizes the solutions inconsistent with the observed data.
    - The other term enforces the spatial coherence.
  - ▣ **Several energy minimization techniques:**
    - Iterated Conditional Modes
    - Graph Cuts
    - Snakes
    - Gradient Vector Flow

# Shape Modelling: approaches

53

- Active Contour Models: algorithm overview
  - ▣ Snakes (active contours) are curves defined within an image domain which can move under the influence of **internal forces coming from** within **the curve** itself, and **external forces computed from the image data**.
  - ▣ Algorithm overview:
    - First, a spline is initialized on the image.
    - Then, the energy function is minimized to make it cover only the desired object.
    - A snake falls into the closest local energy minima.
    - The process iterates.



# Shape Modelling: approaches

54

- Active Contour Models: algorithm overview
  - ▣ Snakes are active models and exhibits dynamic behaviour.
  - ▣ Suitable for objects of changing shapes (e.g. lips, eyes,...)



# Shape Modelling: approaches

55

- Active Contour Models: algorithm
  - ▣ The active contour model algorithm deforms a contour to lock onto features of interest within in an image.
  - ▣ Usually, the features are lines, edges, and/or object boundaries.
  - ▣ The authors (Kass et al.) named their algorithm “snakes” because the deformable contours resemble snakes as they move.
  - ▣ Given an approximation of the boundary of an object in an image, an active contour model can be used to find the “actual” boundary.

# Shape Modelling: approaches

56

## □ Active Contour Models: algorithm

- An active contour is an ordered collection of  $n$  points in the image plane:

$$V = \{v_1, \dots, v_n\}$$

$$v_i = (x_i, y_i) \quad i = \{1, \dots, n\}$$

- The points in the contour iteratively approach the boundary of an object through the solution of an energy minimization problem. For each point in the neighborhood of  $v_i$ , an energy term is computed:

$$E_i = \alpha E_{int}(v_i) + \beta E_{ext}(v_i)$$

# Shape Modelling: approaches

57

- Active Contour Models: algorithm
  - For each point in the neighborhood of  $v_i$ , an energy term is computed:

$$E_i = \alpha E_{int}(v_i) + \beta E_{ext}(v_i)$$

where  $E_{int}(v_i)$  is an energy function **dependent on the shape of the contour**, and  $E_{ext}(v_i)$  is an energy function **dependent on the image properties**, such as the gradient, near point  $v_i$ .

$\alpha$  and  $\beta$  are constants providing the relative weighting of the energy terms.


$E_i$ ,  $E_{int}$ , and  $E_{ext}$  are matrices. The value at the center of each matrix corresponds to the contour energy at point  $v_i$ .

# Shape Modelling: approaches

58

## □ Active Contour Models: algorithm

- Each point  $v_i$  is moved to the point  $v_i'$  corresponding to the location of the minimum value in  $E_i$ .
- If the energy functions are chosen correctly, the contour  $V$  should approach and stop at the object boundary.



# Shape Modelling: approaches

59

- Active Contour Models: internal energy
  - The **internal energy function** is intended to **enforce a shape on the deformable contour** and to maintain a constant distance between the points in the contour. Additional terms can be added to influence the motion of the contour.
  - An example of the internal energy function could be

$$\alpha E_{int}(v_i) = cE_{cont}(v_i) + bE_{bal}(v_i)$$

where  $E_{cont}(v_i)$  is the **continuity energy** that enforces the shape of the contour, and  $E_{bal}(v_i)$  is a **balloon force** that causes the contour to grow (balloon) or shrink.  $c$  and  $b$  provide the relative weighting of the energy terms.

# Shape Modelling: approaches

60

- □ Active Contour Models: internal energy
    - Continuity energy: in the absence of other influences, the continuity energy term coerces an open deformable contour into a straight line and a closed deformable contour into a circle.
- The energy term  $c_{jk}(v_i)$  for each element is defined as:

$$c_{jk}(v_i) = \frac{1}{l(V)} \|p_{jk}(v_i) - \gamma (v_{i-1} + v_{i+1})\|^2$$

where  $p_{jk}(v_i)$  is the point in the image that corresponds to energy matrix  $c_{jk}(v_i)$ .

# Shape Modelling: approaches

61

## □ Active Contour Models: internal energy

### ■ Continuity energy:

$$c_{jk}(v_i) = \frac{1}{l(V)} \|p_{jk}(v_i) - \gamma (v_{i-1} + v_{i+1})\|^2$$

where  $l(V)$  is the normalization factor (the average distance between points in  $V$ ) and  $\gamma$  a parameter:

- $\gamma = 0.5$  for an open contour. In this case, the minimum energy point is the point exactly half the way between  $v_{i-1}$  and  $v_{i+1}$ .
- For the case of a closed contour,  $V$  is given a modulus of  $n$ . Therefore,  $v_{n+i} = v_i \cdot \gamma$  is then defined as  $\gamma = \frac{1}{2 \cos(\frac{2\pi}{n})}$

# Shape Modelling: approaches

62


## □ Active Contour Models: internal energy

### ■ Continuity energy:

$$c_{jk}(v_i) = \frac{1}{l(V)} \|p_{jk}(v_i) - \gamma(v_{i-1} + v_{i+1})\|^2$$

Here, the point of minimum energy of  $E_{cont}(v_i)$  is pushed outwards so that  $V$  becomes a circle.


The point  $v'_i$  is the location of minimum energy because it lies on the circle connecting  $v_{i-1}$  and  $v_{i+1}$ .



# Shape Modelling: approaches

63

- Active Contour Models: internal energy
  - ▣ Balloon force: a balloon force can be used on a closed deformable contour to force the contour to expand (or shrink) in the absence of external influences.
  - ▣ A contour initialized within a uniform image object will expand under the influence of a balloon force until it nears the object boundary (at which point the external energy function affects its motion).



# Shape Modelling: approaches

64

- Active Contour Models: internal energy
  - Balloon force: usually an adaptive balloon force that varies inversely proportionally to the image gradient magnitude is used.
  - The adaptive balloon force is strong in homogeneous regions and weak near object boundaries, edges, and lines.
  - The energy term  $c_{jk}(v_i)$  for each element in the matrix  $E_{ball}(v_i)$  could be expressed as a dot product:

$$c_{jk}(v_i) = n_i \cdot (v_i - p_{jk}(v_i))$$

# Shape Modelling: approaches

65

- Active Contour Models: internal energy
  - Balloon force:

$$c_{jk}(v_i) = n_i \cdot (v_i - p_{jk}(v_i))$$

where  $n_i$  is the outward unit normal of  $V$  at point  $v_i$ , and  $p_{jk}(v_i)$  is the point in the neighborhood of  $v_i$  corresponding to entry  $c_{jk}(v_i)$  in the energy matrix. Therefore, the balloon energy is smallest at points farthest from  $v_i$  in the direction of  $n_i$ .

$n_i$  can be found by rotating the tangent vector  $t_i$  by  $90^\circ$ . Adaptive balloon forces are scaled by the image gradient magnitude at point  $v_i$ .

# Shape Modelling: approaches

66

- Active Contour Models: external energy
  - The **external energy** function **attracts the deformable contour to interesting features**, such as object boundaries, in an image.
  - Any energy expression that accomplishes this attraction can be considered for use.
  - Image gradient and intensity are obvious and easy characteristics to look at.
  - Another characteristics could be object size or shape.

$$\beta E_{ext}(v_i) = mE_{mag}(v_i) + gE_{grad}(v_i)$$

# Shape Modelling: approaches

67

- Active Contour Models: external energy

$$\beta E_{ext}(v_i) = mE_{mag}(v_i) + gE_{grad}(v_i)$$

where  $E_{mag}(v_i)$  is an expression that attracts the contour to high or low intensity regions, and  $E_{grad}(v_i)$  is an energy term that moves the contour towards edges.

$m$  and  $g$  are constants provided to adjust the relative weights of the terms.

# Shape Modelling: approaches

68

- □ Active Contour Models: external energy

$$\beta E_{ext}(v_i) = mE_{mag}(v_i) + gE_{grad}(v_i)$$

- □ Image intensity energy: each element in the intensity energy matrix  $E_{mag}(v_i)$  is assigned the intensity value of the corresponding image point in the neighborhood of  $v_i$ .

$$c_{jk}(v_i) = I(p_{jk}(v_i))$$

Then, if  $m$  is positive, the contour is attracted to regions of low intensity, and viceversa.

# Shape Modelling: approaches

69

## □ Active Contour Models: external energy

$$\beta E_{ext}(v_i) = mE_{mag}(v_i) + gE_{grad}(v_i)$$

- Image gradient energy: the image gradient energy function attracts the deformable contour to edges in the image. An energy expression proportional to the gradient magnitude will attract the contour to any edge:

$$c_{jk}(v_i) = -|\nabla I(p_{jk}(v_i))|$$


When active contours are used to find object boundaries, an energy expression that discriminates between edges of adjacent objects is desirable. The key to such an expression is that the gradients at the edges of the objects have different directions.

# Shape Modelling: approaches

70

## □ Active Contour Models: external energy

Because the gradient direction at the edge of the object of interest is similar to the outward unit normal direction of the contour, the active contour algorithm moves the snake point from  $v_i$  to  $v'_i$ , even though the gradient magnitudes at both points are similar.



# Shape Modelling: approaches

71

- □ Active Contour Models: external energy
  - Image gradient energy: the value for each element in the directional gradient energy matrix  $E_{grad}(v_i)$  can therefore be defined by a dot product between the unit normal of the deformable contour and the image gradient:

$$c_{jk}(v_i) = -n_i \cdot |\nabla I(p_{jk}(v_i))|$$

where  $n_i$  is the unit normal of the contour at point  $v_i$ , as defined.

# Shape Modelling: approaches

72

## □ Active Contour Models: regularization

$$E_i = \alpha E_{int}(v_i) + \beta E_{ext}(v_i)$$

- The energy functions should be scaled so that the neighborhood matrices contain comparable values. This process is referred to as regularization.

$$\alpha E_{int}(v_i) = c E_{cont}(v_i) + b E_{bal}(v_i)$$

$$\beta E_{ext}(v_i) = m E_{mag}(v_i) + g E_{grad}(v_i)$$

- Each of the energy functions is adjusted to the range [0,1].

# Shape Modelling: approaches

73

- □ Active Contour Models: regularization
  - Continuity energy: at each point in the deformable contour, the elements in neighborhood matrix for the continuity energy are simply scaled to the range [0,1].

$$c'_{jk}(v_i) = \frac{c_{jk}(v_i) - c_{min}(v_i)}{c_{max}(v_i) - c_{min}(v_i)}$$

where  $c_{min}(v_i)$  and  $c_{max}(v_i)$  are the minimum and maximum valued elements, respectively, in  $E_{cont}(v_i)$ .

# Shape Modelling: approaches

74

- □ Active Contour Models: regularization
- Balloon energy: the balloon energy is scaled to the range [0,1], then adapted to the image gradient intensity:

$$c'_{jk}(v_i) = \frac{c_{jk}(v_i) - c_{min}(v_i)}{c_{max}(v_i) - c_{min}(v_i)} \cdot \left( 1 - \frac{|\nabla I(v_i)|}{|\nabla I|_{max}} \right)$$

where  $|\nabla I|_{max}$  is the maximum gradient magnitude in the entire image.

# Shape Modelling: approaches

75

- Active Contour Models: regularization
  - Intensity energy: a parameter  $\delta I$  is added to the intensity energy term for regularization:

$$c'_{jk}(v_i) = \frac{c_{jk}(v_i) - c_{min}(v_i)}{\max(c_{max}(v_i) - c_{min}(v_i), \delta I \cdot I_{max})}$$

where  $I_{max}$  is the maximum intensity in the entire image and  $\delta I$  has a range of  $[0, \infty]$ . Therefore,  $\delta I$  determines the sensitivity of the active contour to local variations in image intensity.

# Shape Modelling: approaches

76

- Active Contour Models: regularization
  - Gradient energy: this term is regularized in the same manner as the intensity energy term:


$$c'_{jk}(v_i) = \frac{c_{jk}(v_i) - c_{min}(v_i)}{\max(c_{max}(v_i) - c_{min}(v_i), \delta G \cdot |\nabla I|_{max})}$$

where  $\delta G$  has a range of  $[0, \infty]$ . A large  $\delta G$  results in an active contour that is insensitive to weak edges.

# Shape Modelling: approaches

77

- Active Contour Models: drawbacks
  - ▣ Extremely sensitive to parameters
  - ▣ Small capture range




- ▣ No external influences on points which are far away from the boundary
  - ▣ Convergence is dependent on initial position

# Shape Modelling: approaches

78

## □ Active Contour Models: drawbacks

- Fails to detect concave boundaries. External energy can't pull control points into boundary concavity.



# Shape Modelling: approaches

79


- Active Contour Models: modifications
  - Gradient Vector Flow (GVF): a new external force for snakes.
  - It detects shapes with boundary concavities.
  - Large capture range.
- 
- Chenyang Xu and Jerry L. Prince , "Snakes, Shape, and Gradient Vector Flow“, IEEE Transactions on Image Processing, 1998.
  - C. Xu and J.L. Prince, “Gradient Vector Flow: A New External Force for Snakes”, Proc. IEEE Conf. on Comp. Vis. Patt. Recog. (CVPR), Los Alamitos: Comp. Soc. Press, pp. 66-71, June 1997.

# Shape Modelling: approaches


80

- Active Contour Models: modifications

- Traditional force



- GVF force




# Shape Modelling: approaches


81

- Active Contour Models: modifications

Traditional  
snake





GVF  
snake



# Shape Modelling: approaches

82

- Active Contour Models: modifications
  - ▣ The contour can also be initialized across the boundary of object (something not possible with traditional snakes).



# Shape Modelling: approaches

83

- Active Contour Models: modifications
  - ▣ However, using GVF makes the final result even more sensitive to the choice of parameters.
  - ▣ It is extremely dependent on the initial location of the contour.
  - ▣ It is very slow. Finding GVF field is computationally expensive.

# Shape Modelling: approaches

84

- Active Contour Models: applications
  - ▣ Segmentation of contours
  - ▣ Medical image segmentation from MRI, X-Ray or CT images
  - ▣ Lip tracking for lip synchronization and speech recognition
  - ▣ Real-time object tracking
  - ▣ Face recognition and expression generation

# Shape Modelling: approaches

85

- Active Contour Models: examples




# Shape Modelling: approaches

86

## □ Active Contour Models: examples


- Magnetic resonance image of the left ventricle of human heart.
- Notice the poor quality of the image, even with sampling artifacts.



# Shape Modelling: approaches

87


- Active Contour Models: summary
  - An energy minimizing spline guided by external constraint forces and pulled by image forces towards features:
    - Edge detection
    - Subjective contours
    - Motion tracking
    - Stereo matching



# Shape Modelling: approaches

88

- Active Contour Models: summary
  - ▣ A snake falls into the closest local energy minimum.
  - ▣ Rely on some mechanism to place them near the desired contour.
  - ▣ Snakes try to match a deformable model to an image by means of energy minimization.
  - ▣ In the end, it completely “shrink-wraps” around the object.



Images taken from the GVF website:  
<http://iacl.ece.jhu.edu/projects/gvf/>

# References

89

- “Active Shape Models – Their Training and Application”. T.F. Cootes et al. Computer Vision and Image Understanding Vol. 61, no. 1, January, pp. 38-59, 1995.
- “Active Appearance Models”. T.F. Cootes et al. Proc. European Conference on Computer Vision 1998, Vol. 2, pp. 484-498, 1998.
- “Snakes: Active Contour Models”. M. Kass et al. International Journal of Computer Vision, 321-331, 1988.
- “3-D Active Appearance Models: Segmentation of Cardiac MR and Ultrasound Images”. S.C. Mitchell et al. IEEE Transactions on Medical Imaging, vol. 21, no. 9, 1167-1178, September 2002.
- “Double-edge detection of radiographic lumbar vertebrae images using pressurized open DGVF snakes”. S. Kamalakannan et al. IEEE Transactions on Biomedical Engineering, vol. 57, no. 6, pp. 1325-1334, June 2010.
- “A Brief Introduction to Statistical Shape Analysis”. Mikkel B. Stegmann and David Delgado. Technical University of Denmark, DTU. 2002.
- “Snakes, Shape, and Gradient Vector Flow”. Chenyang Xu and Jerry L. Prince. IEEE Transactions on Image Processing, vol. 7, no. 3, pp. 359-368, March 1998.
- “Gradient Vector Flow: A New External Force for Snakes”, C. Xu and J.L. Prince. IEEE Proc. Conf. on Comp. Vis. Patt. Recog. (CVPR'97), pp. 66-71, June 1997.

Concepts of medical image post-processing

# WORK & DISCUSSION

**Shape Modelling**  
**Active Contour Models - Snakes**

Christian Mata

[Christian.Mata-Miquel@u-bourgogne.fr](mailto:Christian.Mata-Miquel@u-bourgogne.fr)

# Shape Modelling: To discuss and work

91

## □ Active Contour Models

### ▫ WORK

- In order to understand how the snake algorithm is performed, you should download a demo developed in MATLAB to test the main functionalities.
  
- Use the following Snake-Demo example:
  - <http://www.iacl.ece.jhu.edu/static/gvf/snakedemo/>
- Information about the Snake-Demo:
  - <http://www.iacl.ece.jhu.edu/static/gvf/>

# Shape Modelling: To discuss and work

92

- SNAKE-DEMO
  - Start-up Window




# Shape Modelling: To discuss and work

93

## □ SNAKE-DEMO

- Start-up Window
- Loading image




# Shape Modelling: To discuss and work

94

## SNAKE-DEMO

- Start-up Window
- Loading image
- Initializing a contour




# Shape Modelling: To discuss and work

95

## SNAKE-DEMO

- Start-up Window
- Loading image
- Initializing a contour
- Finishing manual initialization




# Shape Modelling: To discuss and work

96

## SNAKE-DEMO

- Start-up Window
- Loading image
- Initializing a contour
- Finishing manual initialization
- Deforming the GVF snake



# Shape Modelling: To discuss and work

97

## SNAKE-DEMO

- Start-up Window
- Loading image
- Initializing a contour
- Finishing manual initialization
- Deforming the GVF snake
- Final result of the GVF snake

