


IMAGE PROCESSING I

Intuon Lertrundachakul

Tutorial III: Spatial Filtering

Intro...

2



Outline

3

- Perform Different Filtering

(observe the effect to the image quality)

- ▣ Manually
- ▣ By built-in command (e.g. fspecial, medfilt2, conv2, filter2, etc.)
- ▣ By your own code

Practical Session

4

6	6	6	6	6	6	6
5	5	5	5	5	5	5
4	4	4	4	4	4	4
3	3	3	10	3	3	3
2	2	2	2	2	2	2
1	1	1	1	1	1	1
0	0	0	0	0	0	0

A Digital Image

Perform LPF (Mean Filtering)

$$* \begin{array}{|c|c|c|} \hline 1 & 1 & 1 \\ \hline 1 & 1 & 1 \\ \hline 1 & 1 & 1 \\ \hline \end{array} / 9$$

A Convolution Mask

Practical Session

5

6	6	6	6	6	6	6
5	5	5	5	5	5	5
4	4	4	4	4	4	4
3	3	3	10	3	3	3
2	2	2	2	2	2	2
1	1	1	1	1	1	1
0	0	0	0	0	0	0

A Digital Image

Perform LPF
(Weighted Averaging Filtering)

$$* \begin{array}{|c|c|c|} \hline 1 & 2 & 1 \\ \hline 2 & 4 & 2 \\ \hline 1 & 2 & 1 \\ \hline \end{array} / 16$$

A Convolution Mask

Sample Code

6

%Define an image

```
img=[ 6 6 6 6 6 6 6; 5 5 5 5 5 5 5;  
      4 4 4 4 4 4 4; 3 3 3 10 3 3 3;  
      2 2 2 2 2 2 2; 1 1 1 1 1 1 1;0 0 0 0 0 0 0]
```

%Define a mask for filtering


```
mask=fspecial('average',3) OR  
mask=[1 1 1; 1 1 1; 1 1 1]/9
```

%Filtering in two ways

```
output=filter2(mask,img,'same') OR  
output=conv2(img,mask,'same')
```

Effect of Low Pass Filtering

7



Practical Session

8

Perform LPF (**Median Filtering**)

Example 1

5	5	5	5	5
4	4	4	4	4
3	3	10	3	3
2	2	2	2	2
1	1	1	1	1

Practical Session

9

Perform LPF (**Median Filtering**)

Example 2

0	0	0	0	0
0	0	0	0	0
0	0	10	10	10
0	0	10	10	10
0	0	10	10	10

Practical Session

10

LPF (Median Filtering)

Example 3

10	10	0	10	10
10	10	0	10	10
10	10	0	10	10
10	10	0	10	10
10	10	0	10	10

Practical Session

11

LPF (Median Filtering)

Example 4

0	0	10	0	0
0	0	10	0	0
0	0	10	0	0
0	0	10	0	0
0	0	10	0	0

Sample Code

12

```
% Define an image
```

```
img=[5 5 5 5 5; 4 4 4 4 4; 3 3 10 3 3; 2 2 2 2 2; 1  
     1 1 1 1]
```


```
% Median filtering
```

```
output=medfilt2(img,[3 3],'symmetric')
```

.

Effect of Median Filtering

13



a b c

FIGURE 3.37 (a) X-ray image of circuit board corrupted by salt-and-pepper noise. (b) Noise reduction with a 3×3 averaging mask. (c) Noise reduction with a 3×3 median filter. (Original image courtesy of Mr. Joseph E. Pascente, Lixi, Inc.)

HPF (Gradient-based)

14

a
b c
d e
f g

FIGURE 10.8

A 3×3 region of an image (the z 's are gray-level values) and various masks used to compute the gradient at point labeled z_5 .

z_1	z_2	z_3
z_4	z_5	z_6
z_7	z_8	z_9

-1	0	0	-1
0	1	1	0

Roberts

-1	-1	-1	-1	0	1
0	0	0	-1	0	1
1	1	1	-1	0	1

Prewitt

-1	-2	-1	-1	0	1
0	0	0	-2	0	2
1	2	1	-1	0	1

Sobel

Practical Session

15

Perform HPF
(Gradient-based)
Prewitt Operators

0	0	0	0	0	0	0
0	0	0	0	0	0	1
0	0	0	0	0	1	1
0	0	0	0	1	1	1
0	0	0	1	1	1	1
0	0	1	1	1	1	1
0	1	1	1	1	1	1

Sample Code

16

```
% Call the Prewitt operators
```

```
mask1=fspecial('Prewitt')
```

```
mask2=mask1'
```

```
% Filtering
```

```
tmp1=conv2(img,mask1,'same');
```

```
tmp2=conv2(img,mask2,'same');
```

```
% Calculate the magnitude
```


```
mag=sqrt(tmp1.^2+tmp2.^2);
```

```
% Display it as an image
```

```
imshow(mat2gray(mag))
```


Edge Detection by Sobel Operators

17



a b

FIGURE 3.45

Optical image of contact lens (note defects on the boundary at 4 and 5 o'clock).

(b) Sobel gradient.

(Original image courtesy of Mr. Pete Sites, Perceptics Corporation.)

HPF (Laplacian-based)

18

0	1	0	1	1	1
1	-4	1	1	-8	1
0	1	0	1	1	1

0	-1	0	-1	-1	-1
-1	4	-1	-1	8	-1
0	-1	0	-1	-1	-1

a	b
c	d

FIGURE 3.39

(a) Filter mask used to implement the digital Laplacian, as defined in Eq. (3.7-4).

(b) Mask used to implement an extension of this equation that includes the diagonal neighbors. (c) and (d) Two other implementations of the Laplacian.

Practical Session

19

0	0	0	0	0	0	0
0	0	0	0	0	0	1
0	0	0	0	0	1	1
0	0	0	0	1	1	1
0	0	0	1	1	1	1
0	0	1	1	1	1	1
0	1	1	1	1	1	1

Perform HPF
(Laplacian Operators)

*

1	1	1
1	-8	1
1	1	1

Sample Code

20

```
% Call the Laplacian operator  
mask=fspecial('Laplacian')
```

```
% Filtering  
tmp=conv2(img,mask,'same');
```

```
% Display it as an image  
imshow(mat2gray(tmp))
```

```
% Enhancement  
tmp=img-tmp*0.1
```

```
% Display the enhanced image  
imshow(mat2gray(tmp))
```

Image Enhancement by Laplacian

21

a b
c d

FIGURE 3.40

(a) Image of the North Pole of the moon.
(b) Laplacian-filtered image.
(c) Laplacian image scaled for display purposes.
(d) Image enhanced by using Eq. (3.7-5).
(Original image courtesy of NASA.)



Assignment

22

- Add 'Gaussian' and 'Salt&Pepper' noise to your image separately. Then, apply Averaging filters and Median filters to the noisy images.
- Apply the Sobel and Laplacian filters to your original facial image separately. Also attempt to enhance your image using the Laplacian filter.

Additional Material

23

Sample Results
From Gaussian Noisy Image

Original Image



Noisy Image (Gaussian)



Averaging Filtered



Median Filtered



Additional Material

24

Sample Results
From Salt & Pepper Noisy Image

Original Image



Noisy Image (Salt&Pepper)



Averaging Filtered



Median Filtered



Additional Material

25

Sample Results
From laplacian Enhancement


Original Image



Sobel Filtered



Laplacian Filtered



Enhanced Image

