

Comparative Performance Evaluation of Hadoop on PaaS Proposals by Leveraging HiBench

Uluer Emre Özdil^{a,b,*}, Serkan Ayvaz^{a,c,*}

^a*Bahçeşehir Üniversitesi, Beşiktaş - İstanbul, Turkey*

^b*School of Engineering, Big Data Analytics and Management*

^c*Department of Software Engineering*

Abstract

The advent of Big Data emerged in any data-driven domain and scaled up the extent as well as the depth of data and its handling. In an ongoing maturing process, new approaches leaning on enhanced distributed storage and computing paradigms are invented helping overcome management and running analytics challenges. In this context Hadoop is embraced in a wide scale by beneficiaries both from industry and academia since its first release in 2005. The commercialization of Cloud Computing started a grand migration movement towards cloud, applying also for Hadoop transferring its presence from on-premises to virtual machines stored and tamed in large data center facilities by global Cloud Service Providers. The CSPs' response to result-focused analytics purposes emerged a service called managed systems where the hard workload of multi node cluster implementation is overtaken by the contractor providing a pre-configured Hadoop package simplifying the installation process to a matter of property selection thus eliminating technical know-how requirements on such an implementation. Converting the concept of cloud based Hadoop from IaaS to PaaS apparently reduced costs commercially presented as pay-as-you-go or pay-per-use. There is a payoff, though, managed Hadoop systems do present a black-box behavior to the end user who cannot be clear on the inner perfor-

*Corresponding authors

Email addresses: ulueremre@gmail.com (Uluer Emre Özdil),
serkan.ayvaz@eng.bau.edu.tr (Serkan Ayvaz)

mance dynamics, hence the benefits by leveraging them. In the study we selected three global providers (GCP, Azure, and Alibaba Cloud), activated their Hadoop PaaS services (Dataproc, HDInsight, and e-MapReduce, respectively) within same geographical region and by promise apparently same computing specifications, and executed several Hadoop workloads of the HiBench Benchmark Suite. The results yield that apparently same computation specs among CSPs' services do not necessarily guarantee equal or close performance outputs to each other. Our assumption is that the pre-configuration work of managed systems done by the contractor play a weighing role on their performance.

Keywords: `elsarticle.cls`, Benchmark Hadoop PaaS, HiBench, Performance evaluation

2010 MSC: 00-01, 99-00

1. Introduction

Big Data. An indispensable aspect for enterprises and academia of the information era to deal with is the term Big Data. As the estimated global internet access rate covers a weighing majority of roughly 63% of the global human population by 2020 [1], mobile technology devices become democratized, sensors and IoT devices the more occupy daily life, ongoing scientific researches produce vast amounts of data outputs the Big Data phenomenon gathered itself by means of overwhelming size with Volume, ever accelerating growth rate with Velocity, and diverse data structures with Variety, new approaches were forced to mature in order to ease the maintenance of Big Data and enable extracting valuable insights from it leveraging complex statistical formulae.

Hadoop [2]. Frameworks for distributed storage and computation sparked up first by search engines were inherited and developed further by the open source community yielding what is known as Hadoop and its ecosystem today. Considering the complexity of dealing with big data Hadoop represents a modern analytics framework decreasing management efforts and duration of analytics operations to an acceptable level by means of affordable commodity computers.

Hadoop comprises three for its core functionality: HDFS filesystem for storing
 very large data among cluster of nodes, the MapReduce framework developed
 20 for distributed computation, and YARN

HDFS. Hadoop’s native file system is inherited from the principles guidelined in
 a whitepaper in 2003 [3] and leveraged to store Petabyte scale data in production
 environment. Figure 1 depicts the main architecture enabling distributed file
 system among a cluster.




Figure 1: HDFS File System

25 *MapReduce.* Figure 2

YARN.

Cloud Computing. The commercialization of Cloud Computing in the early
 2000’s [5] delivered utilization of storage and computing resources to the end
 users saving them high investments on hardware technology that is soon going
 30 to be obsolete and is expensive to maintain. As the migration to the cloud is an
 ongoing process, Hadoop also slips out from its residence on on-prem infrastruc-
 ture to the cloud by being implemented on virtual machine instances provided as




Figure 2: MapReduce paradigm as implemented in Hadoop (recreated from source [4])

IaaS platforms by many providers. The Cloud Service Providers embraced the need of eliminating Hadoop’s complex implementation process on multi-node
 35 VMs by providing managed Hadoop systems commercially packaged as PaaS, which are pre-installed and pre-configured Hadoop clusters allowing the installation of tens to hundreds of nodes in a matter of minutes simply by determining some settings like hardware specs and node numbers prior the installation. The Managed Hadoop system is both a blessing and a curse, by leaving the hard
 40 implementation part which is not necessarily related with the main analysis objective to a contractor the end user saves time and efforts including a payoff, though: By definition, managed systems are prepackaged solutions provided in black-box nature. CSP apply behind-the-scenes tweaks in terms of reaching better performance results on selected approaches like memory intensive or
 45 compute intensive applications.

GCP Dataproc [6]. Google’s managed Spark and Hadoop solution namely Dataproc is a preconfigured Hadoop on PaaS service built upon preinstalled VM instances on Compute Engine [7] which is another service offering of GCP. An OS spectrum comprising Debian and/or ubuntu was offered at the date of the
 50 study which are proposed as preinstalled images during Dataproc installation process. While Hadoop core elements HDFS, YARN, and MapReduce reside as default frameworks, a variety of elements belonging to Hadoop ecosystem

are offered as well. The end user is also offered to leverage Cloud Storage [8], Google’s proprietary cloud storage service to keep data in a longer term where
55 Dataproc cluster is meant to be terminated after usage. By means of Web UI or local CLI via API the end user can access the Dataproc cluster as well as single VM instances within Compute Engine. Google offers a large number of data centers around the globe.

Azure HDInsight [9].

60 *Alibaba Cloud e-MapReduce [10].*

HiBench [11]. Introduced to the benchmark community in 2004 and ever since

2. Related Work

HiBench is a tool to measure a specific systems performing behaviour during execution. The conceptualization of conducting a benchmark may arise from
65 different soils. Based on the conductors motivation; a benchmarks use case could be an inner evaluation of a systems performance before and after some configuration tweaks are set, comparison of rival / complementary systems, or putting CSPs cloud infrastructure services on scale. Following literature has been searched with finding different use cases of HiBench benchmarking suite
70 in mind.

Poggi et al. [12] Characterizing BigBench

Poggi et al. [13] the state of SQL on Hadoop [53]

Samadi et al. [14] conduct an experimental comparison between Spark and Hadoop installed on virtual machines on Amazon EC2 by leveraging nine among
75 the provided HiBench workloads. Accuracy reasons led the conductors run the workloads three times concluding input data scales of 1, 3, and 5 GB respectively. Based on the outputs comprising duration, throughput, speed up, and CPU/memory consumption, the conclusion draws Spark consuming less CPU and performing better on all workload results over Hadoop.

80 Ahn et al. [15] put Spark on YARNs performance on test with HiBench in terms of handling a deluge of data generated by IoT devices. The experiment is run on a cluster with one master and 3 worker nodes each node possessing Intel Xeon processor with 20 cores and 128GB main memory meaning 60 cores and 384GB memory in total. HiBenchs workloads Micro (comprising Sort, TeraSort, 85 and Wordcount), SQL (comprising Aggregation, Join, and Scan), and Machine Learning (comprising Bayes, Logistic Regression, Gradient Boosting Tree, Random Forest, and Linear Regression) are leveraged by a chosen data scale of 30 GB. Spark occupies memory during the whole job execution which in result reduces IOs negative impact on processor performance. For optimizing resource 90 usage the conductors modified YARNs minimum memory allocation and Spark executor settings so that the Spark executors overall loads remain below total system memory. Alongside with HiBenchs duration and throughput report, CPU / memory utilization and disk throughput are profiled as well. Finding of this paper points out that Spark guarantees performance when provided with 95 enough memory.

Han et al. [16] study the impact of memory size on big data processing by means of Hadoop and Spark performance comparison leveraging HiBenchs k-Means workload as the only benchmark. For each of the specified memory sizes of 4, 8, and 12 GB, iterating through a data scale of 1 to 8 GB, with 1GB 100 increment inbetween, k-Means benchmark for Hadoop and Spark is executed. The results depict Sparks overperforming Hadoop unless the total input data size is smaller than 33.5% of the total memory size assigned to worker nodes. After reaching that ratio Spark suffers with insufficient memory resources and is led to interoperate with HDFS causing a sharp decrease in its performance 105 and brings Hadoop in throughput and duration performance to the front. The conductors make a second experiment to find out if Sparks performance can be improved by tweaking the allocation setting for storage memory and shuffle memory while remaining within the specified memory limitations of 4, 8 and 12 GB. Executing HiBenchs k-means benchmark outputs a report interpreted 110 by the conductors as Spark show a 5-10%, and 15% maximum improvement in

processing time.

Ivanov et al. [17] compare the performances of two enterprise grade applications, DataStax Enterprise (DSE), a production level implementation of Apache Cassandra with extended features like in memory computing and advanced security to name but two, and Clouderas Distribution of Hadoop (CDH) comprising core Hadoop elements HDFS and YARN integrated with elements belonging to the Hadoop ecosystem. DSEs HDFS compatible file system CSF lets Hadoop applications run without any modification. The conductors installed the latest stable releases of both softwares on equal CPU, memory and network infrastructure configuration. For both installations, default system parameters have been left with their defaults. HiBenchs three chosen workloads (CPU-bound wordcount, IO-bound dfsioe, and mixed HiveBench) are executed three times, the average values have been taken for representativeness. Several conclusions of their study proclaim linearly scaling of both systems by the increase of data size, while CDH outperforms DSE in read intensive workloads, DSE performs better in write intensive workloads. Leveraging HiBench is where the study differs in approach related to other studies using YCSB benchmark suite. HiBenchs results confirm the latters output as well.

3. Method

In the study we benchmarked Hadoop on PaaS services of three CSPs in terms of comparing their performances to each other: GCP Dataproc, Azure HDInsight, and Alibaba Cloud e-MapReduce, each recognized in Gartner’s 2020 Magic Quadrant for Cloud Infrastructure and Platform Services [18] either in leading or in niche section.

We structured the benchmark study in two use cases:

Use Case 1 aims to map the overall performance behaviors of respective CSPs within HiBench’s predefined data scales huge and gigantic. The following benchmarks have been executed on the clusters of the respective providers: Micro (Sort, Terasort, Wordcount, and Dfsioe), Sql (Scan, Join, and Aggregation),

140 ML (Bayes and Kmeans), and Websearch (Pagerank).

Use Case 2. We picked one benchmark of IO bound character (Sort), one benchmark of CPU bound character (Wordcount), and executed these in data scale increasing in order tiny, small, large, huge, and gigantic. The largest predefined HiBench data scale bigdata would cross the storage limits of the
145 installed clusters, hence we left it off the execution.

Bound by availability of their respective hardware and software options we selected by providers' promise apparently same or close settings. With respect to our aim benchmarking managed systems as they come out of the box, we put two basic rules to stick for each provider in order to align initial circumstances prior
150 to benchmark execution: Among the CSPs, respective data center's geographic location shall be same or close (1), processor number and memory capacity (by providers' promise) shall be same or as close as possible. Thus Frankfurt is selected as location for all providers data center, within given options we selected 8 CPUs/64GB RAM for master node and 4 CPU's/32GB RAM for
155 each worker node totaling in 12 CPUs and 96GB compute power for the cluster. Specified cluster installation options and details are given in Table 1. Without applying any performance tweak operation to the respective preconfigurations we immediately executed several Hadoop benchmarks from HiBench's micro, sql, ml, and websearch categories. We only modified default cluster's configuration
160 in cases where the benchmark was detained from running which is reported in Discussion section.

During the benchmark execution we collected system utilization records on each worker node of the cluster. This approach enabled us a visualization of an overview to the system utilization on each worker node within the cluster over
165 the respective benchmark's execution time.

4. Results

Table 2 and Table 3 summarize HiBench benchmark execution outputs.

Table 1: Selected configurations on CSPs' managed Hadoop services

| | GCP | Azure | Alibaba Cloud |
|--------------|----------------|---------------------------|----------------------|
| Service | Dataproc | HDInsight | e-MapReduce |
| Region | europe-west3-a | Germany West Central | eu-central-1 |
| Location | Frankfurt | Frankfurt | Frankfurt |
| Image | 1.4-ubuntu18 | HDI 3.6 | EMR-3.32.0 |
| OS | ubuntu18.04 | ubuntu 16.04 | Aliyun Linux 2 |
| Hadoop v. | 2.9 | 2.7.3 | 2.8.5 |
| Java | 1.8.0_275 | 1.8.0_275 | 1.8.0_252 |
| MASTER NODE | | | |
| Machine Type | e2-highmem-8 | A8m v2 | ecs.se1.2xlarge |
| Processors | 8 vCPU | 8 cores | 8 vCPU |
| Memory | 64 GB RAM | 64 GB RAM | 64 GB RAM |
| WORKER NODES | | | |
| # Nodes | 3 | 3 | 3 |
| Machine Type | e2-highmem-4 | A4m v2 | ecs.se1.xlarge |
| Processors | 4 vCPU | 4 cores | 4 vCPU |
| Memory | 32 GB RAM | 32 GB RAM | 32 GB RAM |
| Storage | HDFS 1000 GB | WASB | HDFS 1000 GB |
| Replication | 2 | <i>Azure blob storage</i> | 2 |
| Block size | 128 MB | | 128 MB |

Table 2: Use Case 1 benchmark outputs

Data Scale: Huge

| Benchmark | IDS | Dataproc | | HDInsight | | e-MapReduce | |
|-------------|-------|-----------|--------------|-----------|--------------|-------------|--------------|
| | | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ |
| Sort | 3.28 | 70 | 47.11 | 131 | 25.08 | 111 | 29.42 |
| Terasort | 32.00 | 667 | 47.99 | 858 | 37.28 | 1054 | 30.37 |
| Wordcount | 32.85 | 978 | 33.60 | 1470 | 22.34 | 889 | 36.95 |
| Dfsioe-r | 26.99 | 294 | 91.77 | 662 | 40.79 | 245 | 110.21 |
| Dfsioe-w | 27.16 | 379 | 71.73 | 658 | 41.30 | 281 | 96.49 |
| Scan | 2.01 | 73 | 27.63 | 157 | 12.83 | 74 (*) | 27.19 (*) |
| Join | 1.92 | 181 | 10.61 | 356 | 5.39 | 175 (*) | 10.95 (*) |
| Aggregation | 0.37 | 97 | 3.86 | 215 | 1.73 | 97 (*) | 3.85 (*) |
| Bayes | 1.88 | 2604 | 0.72 | 6120 | 0.31 | 3017 | 0.62 |
| Kmeans | 20.08 | 2321 | 8.65 | 2313 | 8.68 | 2070 | 9.70 |
| Pagerank | 2.99 | 1544 | 1.94 | 3334 | 0.90 | 2458 | 1.22 |

Data Scale: Gigantic

| Benchmark | IDS | Dataproc | | HDInsight | | e-MapReduce | |
|-------------|--------|-----------|--------------|-----------|--------------|-------------|--------------|
| | | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ |
| Sort | 32.85 | 715 | 45.94 | 787 | 41.72 | 896 | 36.68 |
| Terasort | 320.00 | 9821 | 32.58 | —(**) | —(**) | 9660 | 33.13 |
| Wordcount | 328.49 | 10131 | 32.42 | 13596 | 24.16 | 8671 | 37.88 |
| Dfsioe-r | 216.03 | 915 | 236.11 | 1886 | 114.54 | 660 | 327.29 |
| Dfsioe-w | 217.33 | 1347 | 161.39 | 1914 | 113.57 | 1060 | 205.12 |
| Scan | 20.10 | 457 | 43.96 | 514 | 39.09 | 407 (*) | 49.38 (*) |
| Join | 19.19 | 595 | 32.27 | 761 | 25.24 | 594 (*) | 32.32 (*) |
| Aggregation | 3.69 | 523 | 7.05 | 594 | 6.20 | 565 (*) | 6.52 (*) |
| Bayes | 3.77 | 5350 | 0.70 | 12589 | 0.30 | 6363 | 0.60 |
| Kmeans | 40.16 | 4541 | 8.84 | 4042 | 9.94 | 4034 | 9.96 |
| Pagerank | 19.93 | 8371 | 2.38 | 11779 | 1.70 | 13893 | 1.43 |

IDS: Input Data Size (GB); $D_{(s)}$: Duration (sec); $T_{(MB/s)}$: Throughput (MB/sec)

(*) Benchmark succeeds after modifying preconfiguration, more on this in Discussion

(**) System failure due to insufficient space on HDFS, more on this in Discussion

Table 3: Use Case 2 benchmark outputs

| Benchmark | Dataproc | | | HDInsight | | e-MapReduce | |
|---------------|-----------|-----------|--------------|-----------|--------------|-------------|--------------|
| | IDS | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ | $D_{(s)}$ | $T_{(MB/s)}$ |
| Sort (t) | 39.30 KB | 36 | 0.0012 | 69 | 0.0006 | 32 | 0.0012 |
| Wordcount(t) | 38.65 KB | 38 | 0.001 | 68 | 0.0006 | 31 | 0.0012 |
| Sort (s) | 3.28 MB | 36 | 0.09 | 70 | 0.0471 | 31 | 0.105 |
| Wordcount (s) | 348.29 MB | 50 | 6.51 | 98 | 3.34 | 47 | 7.06 |
| Sort (l) | 328.50 MB | 42 | 7.86 | 81 | 4.07 | 42 | 7.74 |
| Wordcount (l) | 3.28 GB | 129 | 25.45 | 269 | 12.20 | 120 | 27.27 |
| Sort (h) | 3.28 GB | 70 | 47.08 | 141 | 23.36 | 107 | 30.69 |
| Wordcount (h) | 32.85 GB | 952 | 34.51 | 1487 | 22.10 | 888 | 37.00 |
| Sort (g) | 32.85 GB | 694 | 47.30 | 699 | 47.00 | 883 | 37.20 |
| Wordcount (g) | 328.49 GB | 9749 | 33.70 | 13286 | 24.73 | 8622 | 38.10 |

IDS: Input Data Size; $D_{(s)}$: Duration (sec); $T_{(MB/s)}$: Throughput (MB/sec)
(t): tiny, (s): small, (l): large, (h): huge, (g): gigantic

Analysis. HiBench’s Hadoop related benchmarks in groups micro (Sort, Tera-
sort, Dfsioe, and Wordcount), sql (Scan, Join, and Aggregation), ml (Bayes and
170 Kmeans), and websearch (Pagerank) have been executed on all three CSPs man-
aged Hadoop services. During benchmark runtime resource utilization on worker
nodes have been captured. The resulting multiplots are suggested to be read
as follows: Top-left, top-right, and bottom-left plots represent CPU (user%),
Memory, and IO utilization on each worker node of the respective cluster over
175 time. CPU utilization lines are given in blue tones, Memory utilization lines
are given in fuchsia tones, IO-read and IO-write tps’ are represented with or-
ange tones and green tones, respectively. Even though the coloring convention
might sound confusing, it gives a clear overview in terms of resource utilization
of the total benchmark process over time. The left hand side x-axis measures
180 CPU/Memory usage in percent, the right hand side x-axis measures IO-read
or IO-write transfers in byte per second. The bottom-right plot represents the
comparative benchmark performance outputs of the respective CSP. Duration

Table 4: Use Case 1 Comparative benchmark outputs

| Data Scale: Huge | | | | | |
|----------------------|-------------|---------|---------|---------|----------|
| Benchmark | First | Second | -Perf.% | Third | -Perf.% |
| Sort | GCP | Alibaba | -58.57% | Azure | -87.14% |
| Terasort | GCP | Azure | -28.64% | Alibaba | -58.02% |
| Wordcount | Alibaba | GCP | -10.01% | Azure | -65.35% |
| Dfsioe-r | Alibaba | GCP | -20.00% | Azure | -170.20% |
| Dfsioe-w | Alibaba | GCP | -34.88% | Azure | -134.16% |
| Scan | GCP | Alibaba | -1.37% | Azure | -115.07% |
| Join | Alibaba | GCP | -3.43% | Azure | -103.43% |
| Aggregation | GCP-Alibaba | — | — | Azure | -121.65% |
| Bayes | GCP | Alibaba | -15.86% | Azure | -135.02% |
| Kmeans | Alibaba | Azure | -11.74% | GCP | -12.13% |
| Pagerank | GCP | Alibaba | -59.20% | Azure | -115.93% |
| Data Scale: Gigantic | | | | | |
| Benchmark | First | Second | -Perf.% | Third | -Perf.% |
| Sort | GCP | Azure | -10.07% | Alibaba | -25.31% |
| Terasort | Alibaba | GCP | -1.67% | Azure | — |
| Wordcount | Alibaba | GCP | -16.84% | Azure | -56.80% |
| Dfsioe-r | Alibaba | GCP | -38.64% | Azure | -185.76% |
| Dfsioe-w | Alibaba | GCP | -27.08% | Azure | -80.57% |
| Scan | Alibaba | GCP | -12.29% | Azure | -26.29% |
| Join | Alibaba | GCP | -0.17% | Azure | -28.11% |
| Aggregation | GCP | Alibaba | -8.03% | Azure | -13.58% |
| Bayes | GCP | Alibaba | -18.93% | Azure | -135.31% |
| Kmeans | Alibaba | Azure | -0.20% | GCP | -12.57% |
| Pagerank | GCP | Azure | -40.71% | Alibaba | -65.97% |

measure in seconds is expected to be perceived as "lower is better" while Throughput which is the amount of processed data per second in bytes is expected to be perceived as "higher is better".

USE CASE 1:

Sort - Huge. Figure 3; CPU utilization in GCP and Alibaba condenses around 80% to 98% whereas in Azure the range widens up between 50% to 90%. Memory loads in GCP and Alibaba among the worker nodes display a harmonic behavior between 20% to 40% and 90% to 100% respectively, whereas the memory load in Azure's worker nodes vary between 10% and 50%. In the second half of the benchmark execution IO write transfers in GCP and Alibaba show peaks at about 500 tps where in Azure it is limited with 100 tps. Resulting in GCP carrying out the highest Throughput, thus reaching the shortest Duration of 70 seconds.

Sort - Gigantic. Figure 4; switching the data scale for Sort benchmark to gigantic, GCP's processor load condenses around 80% - 95% where its memory load rises to range 80% - 100%; IO write transfers behave at about 500 tps where IO reads reach 1000 tps in the second half of the benchmark process. Azure's processor and memory performances depict a looser behavior not utilizing the maximum potential whereas IO-read and IO-write tps' reach their maximum at 200 and 350, respectively. Alibaba's resource utilization depicts a high memory load of 90% - 100% dropping to 70% and about 83% on partial nodes in the second half. As so with the processor load behaving between 80% and 100% in the first half dropping to about 50% in the second half where IO write reaches peak at 800 tps. Resulting in GCP embarking highest and Azure the second highest Throughput, respective Durations output in 715 and 758 seconds.

Terasort - Huge. Figure 5; GCP depicts a high utilization on processors at a range of 80% - 100%, memory moving from 80% to 100%, and IO behavior 500 tps in overall and peaking at 1000 tps in IO-read resulting in highest Throughput in 667 seconds response time among other CSPs. Azure's processor and memory

utilization fluctuate in overall where memory performance incrementally reach 100% in one node, a stable IO-write in overall process at about 70 tps peaking at 250 tps reaches the second highest Throughput in 858 seconds. Alibaba with
215 high memory and processor utilization, and varying IO tps's in overall process falls back in embarking Throughput and resulting in 1054 seconds response time.

Terasort - Gigantic. Figure 6; switching the scale to gigantic causes dramatic changes on resource utilization on all CSPs. During all benchmark process GCP depicts very condensed high utilization on processor at a broad range
220 of 30% to about 95%, memory consumption between 95% and 100% and IO read transfer varying between 800 to 1100 tps. Azure on the other side, fails to complete the benchmark on 3 attempts; suffering from YARN insufficient HDFS allocation requested for bringing the job further. IO scores drop to null and task raises failure. Alibaba Cloud's resource utilization goes within maximum levels
225 where processor utilization depicts a consumption of 80% to 90% in the overall, memory utilization at it highest during all process, IO reads and writes moving along the 600 tps' and peaking around 1600 tps. With a slicely higher value in Throughput, Alibaba performs best with 9660 seconds, followed by GCP with 9821 seconds. Azure disqualifies this session.

230 *Wordcount - Huge.* Figure 7; GCP performing processor utilization of 75% to 100% with a memory consumption between 80% to 95% where IO transfers move along 60 tps peaking at about 150 tps reaches second highest Throughput with 978 seconds response time. Azure's processor utilization moving along 70% to about 100% where memory depicts 30% to 50% utilization and lower
235 IO transfers peaking at about 60 tps reaches the lowest throughput hance the longest duration of 1470 seconds. Alibaba depicting high processor and memory load moving in ranges 70% to 100% and 80% to slightly over 90% with IO transfers moving along 200 tps peaking at 300tps to 350tps reaches the highest Throughput hence shortest execution time of 889 seconds.

240 *Wordcount - Gigantic*. Figure 8; GCP utilizing processor and memory sources at their maximum during the overall process, for CPU within 60% up to pushing 100%, memory utilization varying between 60% to 100%, and IO-read and IO-write transfers moving along 90 tps and 250 tps respectively, reaches second highest Throughput load resulting in 10131 seconds response time. Azure shows
 245 a dens processor utilization varying between 40% and close to 100%, memory consumption is somehow oppressed to stay within range 20% up to 50%, IO behavior reacts seldomly over 60 tps resulting in the lowest Throughput and longest Duration of 13596 seconds. Alibaba depicting a high processor utilization within range 85%-100%, a relatively more stable memory consumption in
 250 range 85% to 100% and IO transfers mostly about 300 tps thus performing highest Throughput hence shortest response time of 8671 seconds.

Dfsioe-read - Huge. Figure 9; GCP's processor utilization moving roughly between 80% to 95% accompanied by memory utilization within range slightly below and over 70%, IO transfers peaking at 400 tps mostly go along 100 tps
 255 and 250 tps performs second highest Throughput resulting in 294 seconds of Duration. Azure's processor utilization is rather limited to between 60% and 90% whereas the memory utilization behaves between 10% to 50%, generally low IO transfers with two markable IO-read and IO-write condensences reaching peaks at 2000 tps and 1500 tps respectively results in the lowest Throughput
 260 and 662 seconds of response time. Alibaba with 245 seconds Duration displays a similar resoure utilization pattern with GCP where it differentiates in memory utilization moving around 90%.

Dfsioe-read - Gigantic. Figure 10; processor utilization in GCP cloud concentrates within range of 80% to 90%, memory utilization moves around 95% to
 265 100% whereas IO read transfers moving along about 500 tps brings its performance to second highest Throughput with 915 seconds Duration. Azure displays a performance within a range of 55% up to 90% in CPU utilization, 20% to 55% in memory utilization, and IO-write activity moving along 70 tps, IO-read showing peak at about 470 tps reaching the lowest performance in Through-

270 put outputting 1886 seconds response time. Alibaba system utilization moves along 80%-90% range for processing performance, 90%-100% for memory load and a behavior up to 1700 tps IO-write placing its performance to the highest Throughput with 660 seconds duration.

Dfsioe-write - Huge. Figure 11; in GCP processor utilization moves between 275 70% and 90%, memory load increments from 20% up to 70% whereas IO-write transfers move along 500 tps resulting in second shortest response time 379 seconds. Azure's CPU utilization around 60% to 90%, memory load moves between 20% and 40% whereas IO-write transfers vary about 20 tps to 80 tp peaking at about 120 tps by a Duration output of 658 seconds. Alibaba with 280 processor utilization 80% and 95%, incrementing memory load from about 40% up to 90%-100%, and IO-write transfers at about 100 tps to 600 tps peaking at about 800 tps performs the heaviest Throughput thus reaching the shortest response time with 281 seconds.

Dfsioe-write - Gigantic. Figure 12; GCP processor utilization moves along a 285 broad range hitting up to 90% load, memory load quickly rises to 95%-100% range and keeps its position in overall execution, IO-writes move along 500 tps to 600 tps placing GCP to the second best performance with 1347 seconds response time. Azure shows a CPU utilization in a range 60% up to 90% until it drops to about 25% in the 2/3th of the overall process, memory load moves along 290 lower 20% to upper 50% until its sudden drop to upper 15% simultaneously with CPU utilization where IO-write transfers peak at about 120 tps resulting in 1914 seconds response time. Alibaba performing the shortest response time with 1060 seconds displays a similar memory and processor utilization behaviour with GCP where it differs in IO-write transfers peaking at about 900 tps.

295 *Scan - Huge.* Figure 13; GCP processor utilization condenses between about 80% and 90% during benchmark execution, memory load depicts movement between 20% and 40% accompanied by an IO-write transfer reaching over 500 tps which brings GCP to the leading performance within this benchmark with

73 seconds. On Azure's side processor utilization moves along 80%-90% range
300 whereas memory load increments from the 15% to the 30%, relatively low
IO-write transfer peaking at about 85 tps results in lowest Throughput and
157 seconds Duration. Alibaba follows a similar pattern like GCP in resource
utilization with about 90% CPU load, 15% to below 40% memory utilization
but a less dense IO-write transfer peaking at about 550 tps and so reaching a
305 close Throughput to GCP resulting in 74 seconds response time.

Scan - Gigantic. Figure 14; GCP's CPU utilization varying between 50% and
90% with a convergence at about 80%, memory load showing similar range
with utilization reaching up 100% and IO-write transfers moving between 500
tps and 600 tps results in second highest Throughput by a 457 seconds response
310 time. Azure's CPU utilization condenses between 80% and 90% and memory
load incrementing two times from 20% to 40%, IO-write transfer moving along
50 tps to 60 tps peaking at about 200 tps results in 514 seconds Duration.
Alibaba's processor utilization moves in a relatively higher range between 80%
and 95%, an incrementing memory load range from 40%-50% to 80%-100%
315 during runtime, and IO-write transfers peaking at about over 500 tps results in
highest Throughput thus shortest Duration of 407 seconds.

Join - Huge. Figure 15; GCP processor load moves mainly between 80% and
over 90%, memory utilization moves along about 20% and 30%, IO-writes
behaving at about 150 tps brings outputs 181 seconds response time. Azures
320 resource utilization shows range between 80% and 90% for CPU, varying mem-
ory loads moving along below 20% and below 60%, IO-write transfers behave
below 60 tps with a peak of 100 tps resulting in a lower throughput and response
time of 356 seconds. Resource utilization at Alibaba behaves similar to GCP in
processor and memory load whereas IO-write peaks at about 260 tps, reaching
325 highest Throughput and a Duration of 175 seconds.

Join - Gigantic. Figure 16; CPU load in GCP moves along 70% to 90% in over-
all whereas RAM utilization among worker nodes takes a path within 50% to

90% range, IO-write transfers observed in behaviour about 100 tps resulting in a Throughput outputting 595 seconds of response time. Azure's resource utilization dynamics show a utilization of 80% to 90% with decreasing utilization on some worker nodes in later stage, memory utilization moving along the range 20% up to 60% and IO-write transfer observations peaking at 120 tps provide the lowest Throughput hence the longest response time of 761 seconds. Alibaba performing a processor utilization of about below 90% to below 100%, memory load behavior moving along 50% to below 70%, and IO-write observation peaking at 350 tps performs a slightly higher Throughput than GCP hence slightly shorter Duration of 594 seconds.

Aggregation - Huge. Figure 17; GCP processor utilization moving around 80% to about 95%, memory load behaving between 15% to 40%, and IO-write transfer observed at about 150 tps results in 97 seconds Duration. Azure's CPU utilization behaves between 80% and 90% whereas memory load moves along from 10% to varying utilizations among worker nodes up to 30% and below 60%, and IO-write transfers peaking at about 180 tps performs a relatively small Throughput resulting in 215 seconds completion time. Alibaba resource utilization moving along between 80% and 90% for CPU, 10% to 40% in memory, and IO-write transfer average of 26 tps show close performance to GCP resulting in same completion time of 97 seconds.

Aggregation - Gigantic. Figure 18; processor utilization moving between 80% and 90% in overall execution, memory load between 50% and 70% peaking to below 100%, IO-write transfers reaching a dense behavior at the end reaching 500 tps results in highest Throughput and 523 seconds response time. Azure displays a CPU utilization of below 80% to above 90%, mild RAM utilization moving along 30% to 60%, IO-write transfers behaving about 100 tps result in a relative low Throughput and 594 seconds of Duration to complete. Alibaba's processor load moves along 80% to below 100%, IO-write transfer behavior scaling from about 50 tps to 400 tps results in 565 seconds response time.

Bayes - Huge. Figure 19; GCP in processor behavior moving along about 70%
to below 100%, memory load at about 30% with a short peak to below 100%
at te first half, an IO-write transfer behavior about 500 tps resulting in high-
360 est Throughput thus fastest response time of 2604 seconds. Azure showing a
splitted bevhavior in CPU utilization among worker nodes where one load moves
along about 80% to lower 100% and one node depict a movement along mini-
mum to about 20%, memory loads also varying from each other by about 20%
load difference at the beginning however meeting the similar range starting at
365 the second half, IO observations depict a low range with exception at the high
IO-write transfer at about 3200 tps at the initial state of the execution result in
a relatively low Throughput hence longest Duration of 6120 seconds. Alibaba
CPU utilization shows varieties among worker nodes in load ranges, RAM uti-
lization condences at higher levels ove 80%, IO ttrransfers moving along 100tps
370 to observable 450 tps resulting in 3017 seconds response time.

Bayes - Gigantic. Figure 20; GCP's processor utilization moving along 70% to
below 100%, accompanied by memory load incrementing from 40%
to 70% becoming stable at 50%
s, and IO-write transfers moving along 500 tps results
in the highest Throughput and 5350 seconds of response time. Azure's resource
375 utilization shows distinction in CPU and memory among worker nodes while two
nodes depict higher utilization at about 70% to below 100% for processing and
40%-50% for memory, one node staying at lower levels for respective resources,
the observed IO-write transfer move along 100 tps where IO-read transfer peaks
at about 650 tps resulting in a lowest performance of 12589 seconds Duration.
380 Alibaba depicting different utilization ranges among worker nodes for process-
ing, the memory consumption follows a more balanced load among worker nodes
with IO-write transfer moving aong 200 tps a relatively lower Throughput hence
relatively longer Duration of 6363 seconds, with respect to GCP.

Kmeans - Huge. Figure 21;

385 *Kmeans - Gigantic.* Figure 22;

Pagerank - Huge. Figure 23;

Pagerank - Gigantic. Figure 24;

Overview to benchmarks executed in data scale Huge/. Figure 25;

Overview to benchmarks executed in data scale Gigantic. Figure 26;

390 USE CASE 2:

Sort. Figure 27;

Sort - Small. Figure 28;

Sort - Large. Figure 29;

Sort - Huge. Figure 30;

395 *Sort - Gigantic.* Figure 31;

Wordcount. Figure 32;

Wordcount - Small. Figure 33;

Wordcount - Large. Figure 34;

Wordcount - Huge. Figure 35;

400 *Wordcount - Gigantic.* Figure 36;

 Wordcount results in scale

Overview of Sort benchmark varying data scales. Figure 37;

Overview of Wordcount benchmark varying data scales. Figure 38;




Figure 3: UC1 - Sort (Huge; 3.2 GB)




Figure 4: UC1 - Sort (Gigantic; 32 GB)




Figure 5: UC1 - Terasort (Huge; 320 MB)




Figure 6: UC1 - Terasort (Gigantic; 3.2 GB)




Figure 7: UC1 - Wordcount (Huge; 32 GB)




Figure 8: UC1 - Wordcount (Gigantic; 320 GB)




Figure 9: UC1 - Dfsioe-read (Huge; No of Files: 256, File size: 100 MB)




Figure 10: UC1 - Dfsioe-read (Gigantic; No of Files: 512, File size: 400 MB)




Figure 11: UC1 - Dfsioe-write (Huge; No of Files: 256, File size: 100 MB)




Figure 12: UC1 - Dfsioe-write (Gigantic; No of Files: 512, File size: 400 MB)




Figure 13: UC1 - Scan (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 14: UC1 - Scan (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)




Figure 15: UC1 - Join (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 16: UC1 - Join (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)




Figure 17: UC1 - Aggregation (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 18: UC1 - Aggregation (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)




Figure 19: UC1 - Bayes (Huge; PAGES: 500,000 CLASSES: 100 NGRAMS: 2)




Figure 20: UC1 - Bayes (Gigantic; PAGES: 1,000,000 CLASSES: 100 NGRAMS: 2)




Figure 21: UC1 - Kmeans (Huge; CLUSTERS: 5 DIMENSIONS: 20 SAMPLES: 100,000,000 SAMP PER INPUT: 20,000,000 MAX IT: 5 K: 10 CONVERGEDIST: 0.5)




Figure 22: UC1 - Kmeans (Gigantic; CLUSTERS: 5 DIMENSIONS: 20 SAMPLES: 200,000,000 SAMP PER INPUT: 40,000,000 MAX IT: 5 K: 10 CONVERGEDIST: 0.5)




Figure 23: UC1 - Pagerank (Huge; PAGES: 5,000,000 NUM ITERATIONS: 3 BLOCK: 0 BLOCK WIDTH: 16)




Figure 24: UC1 - Pagerank (Gigantic; PAGES: 30,000,000 NUM ITERATIONS: 3 BLOCK: 0 BLOCK WIDTH: 16)




Figure 25: Use Case 1 - Hadoop benchmark comparisons in huge data scale




Figure 26: Use Case 1 - Hadoop benchmark comparisons in gigantic data scale

Figure 27: UC2 - Sort (Tiny; 32 KB)




Figure 28: UC2 - Sort (Small; 3.2 MB)




Figure 29: UC2 - Sort (Large; 320 MB)




Figure 30: UC2 - Sort (Huge; 3.2 GB)




Figure 31: UC2 - Sort (Gigantic; 32 GB)




Figure 32: UC2 - Wordcount (Tiny; 32 KB)




Figure 33: UC2 - Wordcount (Small; 320 MB)




Figure 34: UC2 - Wordcount (Large; 3.2 GB)




Figure 35: UC2 - Wordcount (Huge; 32 GB)





Figure 36: UC2 - Wordcount (Gigantic; 320 GB)






Figure 37: Use Case 2 - Sort performances along data scales




Figure 38: Use Case 2 - Wordcount performances along data scales

5. Discussion

405 *Limitations, workarounds, failures.* One major limitation of the study has been the high-cost of benchmark executions’ total running time which is charged in a pay-per-use manner which led the conductors to halt benchmarks at only one successful execution for each workload. This is not fitting the best practice, though, where a benchmark would be executed thrice for each workload and
410 the average performance results were taken. Following the best practise would have provided more stable outcomes especially in cases where there occurs very tiny difference between successive performances of respective providers. Hence, we recommend the study to be understood in terms of an attempt trying to bring more clarity to black-box nature managed Hadoop proposals’ performance
415 behavior by means of resource utilization dynamics, and as the managed services come out of the box without applying any performance tweaking configurations. We do not recommend the study to be understood as a grading board for the business values provided by respective CSPs.

HiBench comes with dependencies downloaded during its compilation process by Apache Maven. The Hive engine is one of those dependencies leveraged
420 by HiBench for running SQL workloads Scan, Join, and Aggregation. Alibaba’s e-Mapreduce comprises a ready made Hive hook trigerring a Java file to run post executional transactions for other services within the package. However this preconfiguration prevented HiBench from starting with respective bench-
425 marks’ execution since the HiBench based Hive engine does not include the aforementioned jar file defined for e-MapReduce’s specific environment. Disabling the predefined Hive hook from Alibaba e-MapReduce’s UI management console apparently solved this issue and enabled HiBench’s SQL workloads to run, but the impact of this modification on the respective performance values
430 remains unknown, hence the need to annotate it here. With GCP and Azure issues of this kind did not occur.

In Azure environment the Terasort benchmark running in data scale gigantic failed to complete in all three attempts we conducted where about 20% of

maps were completed. As distinct from GCP and Alibaba where the end user
435 is liberate to chose HDFS or respective providers storage system as the cluster's file system, Azure obligates the user to go with WASB file system among other Azure storage services with a promise to Peta-scale. However, after inspecting the failure it turned out that the exception is not due the WASB file system. Even though WASB is predefined as the cluster's file system, during
440 the application's run time YARN still leverages the cluster's HDFS file system for storing intermediary results failing to allocate free space on HDFS reaching specific levels of maps operators. The conductors marked this failure as a structural bottleneck, since all end users running Terasort operation at this scale would face the same error, and since resource utilization can be tracked
445 up to the failure point and after, we kept this benchmark as disqualified. Figure 6 displays system resource utilization on Azure including the point where the failure occurs.

6. Conclusion

The results yield that Hadoop PaaS offerings by vendor's promise side perform and system utilizations may highly vary among CSPs.
450

References

- [1] World Internet Users Statistics and 2020 World Population Stats.
URL <https://www.internetworldstats.com/stats.htm>
- [2] Apache Hadoop.
455 URL <https://hadoop.apache.org/>
- [3] S. Ghemawat, H. Gobioff, S.-T. Leung, The Google file system, in: Proceedings of the nineteenth ACM symposium on Operating systems principles, Vol. 37, 2003, pp. 29–43, issue: 5. doi:10.1145/1165389.945450.
- [4] a. A. T. H. Schtzle, Martin Przyjaciol-Zablocki, Giant Data: MapReduce
460 and Hadoop ADMIN Magazine.

URL <http://www.admin-magazine.com/HPC/Articles/MapReduce-and-Hadoop>

- [5] Announcing Amazon Elastic Compute Cloud (Amazon EC2) - beta.

URL <https://aws.amazon.com/about-aws/whats-new/2006/08/24/announcing-amazon-elastic-compute-cloud-amazon-ec2---beta/>

- [6] Dataproc.

URL <https://cloud.google.com/dataproc>

- [7] Compute Engine: Virtual Machines (VMs).

URL <https://cloud.google.com/compute>

- [8] Cloud Storage.

URL <https://cloud.google.com/storage>

- [9] Azure HDInsight - Hadoop, Spark, & Kafka Service | Microsoft Azure.

URL <https://azure.microsoft.com/en-us/services/hdinsight/>

- [10] E-MapReduce Service: Big Data Processing and Analysis Solution - Alibaba Cloud.

URL <https://www.alibabacloud.com/product/emapreduce>

- [11] Intel-bigdata/HiBench, original-date: 2012-06-12T07:56:57Z (Jan. 2021).

URL <https://github.com/Intel-bigdata/HiBench>

- [12] N. Poggi, A. Montero, D. Carrera, Characterizing bigbench queries, hive, and spark in multi-cloud environments, Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) 10661 LNCS (2018) 55–74. doi:10.1007/978-3-319-72401-0_5.

- [13] N. Poggi, J. L. Berral, T. Fenech, D. Carrera, J. Blakeley, U. F. Minhas, N. Vujic, The state of SQL-on-Hadoop in the cloud, in: 2016 IEEE International Conference on Big Data (Big Data), 2016, pp. 1432–1443. doi:10.1109/BigData.2016.7840751.

- [14] Y. Samadi, M. Zbakh, C. Tadonki, Performance comparison between hadoop and spark frameworks using HiBench benchmarks, *Concurrency Computation* 30 (12). doi:10.1002/cpe.4367.
- [15] H. Ahn, H. Kim, W. You, Performance Study of Spark on YARN Cluster Using HiBench, 2018. doi:10.1109/ICCE-ASIA.2018.8552137.
- [16] S. Han, W. Choi, R. Muwafiq, Y. Nah, Impact of memory size on bigdata processing based on hadoop and spark, Vol. 2017-January, 2017, pp. 275–280. doi:10.1145/3129676.3129688.
- [17] T. Ivanov, R. Niemann, S. Izberovic, M. Rosselli, K. Tolle, R. V. Zicari, Performance Evaluation of Enterprise Big Data Platforms with HiBench, in: 2015 IEEE Trustcom/BigDataSE/ISPA, Vol. 2, 2015, pp. 120–127. doi:10.1109/Trustcom.2015.570.
- [18] Gartner Reprint.
URL <https://www.gartner.com/doc/reprints?id=1-1ZDZDMTF&ct=200703&st=sb>