

# Comparative Performance Evaluation of Hadoop on PaaS Proposals by Leveraging HiBench

Uluer Emre Özdil<sup>a,b,\*</sup>, Serkan Ayvaz<sup>a,c,\*</sup>

<sup>a</sup>*Bahçeşehir Üniversitesi, Beşiktaş - İstanbul, Turkey*

<sup>b</sup>*School of Engineering, Big Data Analytics and Management*

<sup>c</sup>*Department of Software Engineering*

---

## Abstract

The advent of Big Data emerged in any data-driven domain and scaled up the extent as well as the depth of data and its handling. In an ongoing maturing process, new approaches leaning on enhanced distributed storage and computing paradigms are invented helping overcome management and running analytics challenges. In this context Hadoop is embraced in a wide scale by beneficiaries both from industry and academia since its first release in 2005. The commercialization of Cloud Computing started a grand migration movement towards cloud, applying also for Hadoop transferring its presence from on-premises to virtual machines stored and tamed in large data center facilities by global Cloud Service Providers. The CSPs' response to result-focused analytics purposes emerged a service called managed systems where the hard workload of multi node cluster implementation is overtaken by the contractor providing a pre-configured Hadoop package simplifying the installation process to a matter of property selection thus eliminating technical know-how requirements on such an implementation. Converting the concept of cloud based Hadoop from IaaS to PaaS apparently reduced costs commercially presented as pay-as-you-go or pay-per-use. There is a payoff, though, managed Hadoop systems do present a black-box behavior to the end user who cannot be clear on the inner perfor-

---

\*Corresponding authors

*Email addresses:* [ulueremre@gmail.com](mailto:ulueremre@gmail.com) (Uluer Emre Özdil),  
[serkan.ayvaz@eng.bau.edu.tr](mailto:serkan.ayvaz@eng.bau.edu.tr) (Serkan Ayvaz)

mance dynamics, hence the benefits by leveraging them. In the study we selected three global providers (GCP, Azure, and Alibaba Cloud), activated their Hadoop PaaS services (Dataproc, HDInsight, and e-MapReduce, respectively) within same geographical region and by promise apparently same computing specifications, and executed several Hadoop workloads of the HiBench Benchmark Suite. The results yield that apparently same computation specs among CSPs' services do not necessarily guarantee equal or close performance outputs to each other. Our assumption is that the pre-configuration work of managed systems done by the contractor play a weighing role on their performance.

*Keywords:* `elsarticle.cls`, Benchmark Hadoop PaaS, HiBench, Performance evaluation

*2010 MSC:* 00-01, 99-00

---

## 1. Introduction

*Big Data.* An indispensable aspect for enterprises and academia of the information era to deal with is the term Big Data. As the estimated global internet access rate covers a weighing majority of roughly 63% of the global human population by 2020 [1], mobile technology devices become democratized, sensors and IoT devices the more occupy daily life, ongoing scientific researches produce vast amounts of data outputs the Big Data phenomenon gathered itself by means of overwhelming size with Volume, ever accelerating growth rate with Velocity, and diverse data structures with Variety, new approaches were forced to mature in order to ease the maintenance of Big Data and enable extracting valuable insights from it leveraging complex statistical formulae.

*Hadoop* [2]. Frameworks for distributed storage and computation sparked up first by web indexing engines were inherited and developed further by the open source community yielding what is known as Hadoop and its ecosystem today. Considering the complexity of dealing with big data Hadoop represents a modern analytics framework decreasing management efforts and duration of analytics operations to an acceptable level by means of affordable commodity computers.

Hadoop comprises three for its core functionality: HDFS filesystem for storing very large data across a cluster of nodes, the MapReduce framework developed for distributed computation, and YARN for allocating available resources for the requested tasks.

*HDFS.* Hadoop Distributed File System which stands for HDFS is developed with inspiration from the guidelines described in a whitepaper about Google's Filesystem (GFS), a distributed storage paradigm to handle petabyte and larger scale data volumes within a cluster robust to machine failures, published in 2003 [3]. Big data volumes are chunked and stored within 128 MB blocks, each block is replicated to different nodes by a factor of 3, these values are the defaults and can be changed. When the data file is requested, related blocks are constructed from the nodes across the cluster. The redundancy of the blocks guarantees availability, in a case where one or more nodes become out of service, requested data blocks are gathered from the available redundant copies stored on other nodes. HDFS is a co-existing file system on the nodes it is installed, it provides a global distributed view to the files across the cluster, thus listing an HDFS directory is possible from within all nodes, the files on HDFS are listed as they exist on a local filesystem, but the physical parts of the files reside on other physical locations. Figure 1 depicts an overview to HDFS. The architecture of HDFS comprises Namenode which is a dedicated machine to keep track of the files and folders and respective metadata like block locations across the cluster, and a number of datanodes on which the data blocks are residing [4]. Namenode is a single-point-of-failure meaning if the namenode is down, the whole Hadoop system is down. To overcome this issue starting with version 2 Hadoop matured to a High Availability configuration depicted in Figure 2 where there exists two namenodes, one active namenode and one standby namenode communicating with the data nodes and storing edit logs in a shared folder. As their naming convention refers, active namenode is in charge whereas the standby node behaves more like a shadow system. Whenever the active namenode breaks down, the shadow node gets activated resulting in no

service breakage for the end user.

*MapReduce.* Similar to HDFS, Hadoop's MapReduce is the open source implementation of the MapReduce framework described in a paper [5] published in 2004. Depicted in Figure 3, a MR flow starts with assigning blocks from HDFS as input splits to mappers, computed intermediate results are then shuffled and passed to reducers where outputs are send back to the client. Nodes running mappers and reducers provide parallel processing which can be scaled by simply adding new commodity computers. The computation is made on nodes where related data blocks reside, which explains the term data locality bringing computation to the data thus eliminating the need for moving data across nodes for computation.

*YARN.* Hadoop version 2.x includes major architectural improvements in terms of resource managing. Version 1.x of Hadoop suffered shortcomings due to an overload of its resource management duties which was handled within MRv1 where job tracker node and task tracker nodes were running the organizational load of MapReduce executions. YARN standing for "Yet Another Resource Negotiator" emerging as an intermediate layer between HDFS and MapReduce taking over some of the load that was previosly carried out by MRv1 also become a gate to other batch, stream, interactive and graph processing engines to leverage HDFS file system (Figure 4). After YARN, MRv1 has become MRv2 isolated from resource managerial duties regarding previous version hence more efficient with processing oriented focus. YARN innovates Hadoop by brining the architectural elements resource manager, which is one node dedicated to track resources across the cluster by availability, and node managers which reside inside each worker node and monitor containers.

*Cloud Computing.* The commercialization of Cloud Computing in the midst 2000's [7] delivered utilization of storage and computing resources to the end users saving them high investments on hardware technology that is soon going to be obsolete and is expensive to maintain. As the migration to the cloud




Figure 1: Hadoop Distributed File System




Figure 2: Hadoop High Availability




Figure 3: MapReduce execution (recreated from source [6])




Figure 4: YARN (recreated from source [5])

is an ongoing process, Hadoop also slips out from its residence on on-prem infrastructure to the cloud by being implemented on virtual machine instances provided as IaaS platforms by many providers. The Cloud Service Providers  
80 embraced the need of eliminating Hadoop’s complex implementation process on multi-node VMs by providing managed Hadoop systems commercially packaged as PaaS, which are pre-installed and pre-configured Hadoop clusters allowing the installation of tens to hundreds of nodes in a matter of minutes simply by determining some settings like hardware specs and node numbers prior the  
85 installation. The Managed Hadoop system is both a blessing and a curse, by leaving the hard implementation part which is not necessarily related with the main analysis objective to a contractor the end user saves time and efforts including a payoff, though: By definition, managed systems are prepackaged solutions provided in black-box nature. CSPs apply behind-the-scenes tweaks in  
90 terms of reaching better performance results on selected approaches like memory intensive or compute intensive applications.

*GCP Dataproc [8].* Google’s managed Spark and Hadoop solution, namely Dataproc, is a preconfigured Hadoop on PaaS service built upon preinstalled VM instances on Compute Engine [9] which is another service offering of GCP. An  
95 OS spectrum comprising Debian and/or ubuntu was offered at the date of the study which are proposed as preinstalled images during Dataproc installation process. While Hadoop core elements HDFS, YARN, and MapReduce reside as default frameworks, a variety of elements belonging to Hadoop ecosystem are offered as well. The end user is also offered to leverage Cloud Storage [10],  
100 Google’s proprietary cloud storage service to keep data in a longer term where Dataproc cluster is meant to be terminated after usage. By means of Web UI or local CLI via API the end user can access the Dataproc cluster as well as single VM instances within Compute Engine. Google offers a large number of data centers around the globe.

105 *Azure HDInsight [11].* Azure’s solution to managed Hadoop and Spark platform is a product of the collaboration Azure’s with Hortonworks bringing Horton-

works Data Platform (HDP) to a cloud platform [12]. As being so, HDInsight differs in architecture with respect to its conjugates, by not being a Hadoop cluster installed on the cloud VM service layer, namely Azure Virtual Machines, instead it is an HDP platform optimised for the cloud. Another difference is that HDInsight obligates WASB, the Azure blob system as the storage system including an option to leverage Data Lake Storage, excluding Hadoop’s native file system HDFS which apparently led one benchmark task to fail. At the date of the study Azure was obligating Hadoop to use in in High Availability mode with 2 master nodes hence leaving hardware selection to the end user.

*Alibaba Cloud e-MapReduce [13].* Alibaba Cloud’s managed Hadoop service e-MapReduce leveraging Apache Hadoop and Apache Spark is placed as a service layer on its Elastic Compute Service (ECS), a similar approach to the one of GCP’s. Alibaba’s number of provided data center locations beyond Mainland China are not as numerous as its conjugates hence available in the United States, Europe, Middle East and Asia Pacific. Alibaba Cloud’s managed service distincts from others in that its preinstalled Operating System Aliyun Linux 2 by the date of the study was developed by Alibaba Cloud, a linux distribution based on CentOS, the open source version of RedHat Linux. AliyunOS is claimed to provide a stable and reliable environment functioning deeply optimized with the Alibaba Cloud infrastructure, and be open source on its GitHub repository [14]. e-MapReduce offers a wide scale of machine types with different specifications for specific purposes like CPU intensive or memory intensive tasks. As with GCP, on Alibabacloud e-MapReduce the type of storage whether it shall be HDFS or leverage Alibaba cloud storage can be specified by the end user.

*HiBench [15].* Introduced to the community in 2010 [16], the open source HiBench implementation is motivated by the aim to provide a comprehensive and representative benchmark for Hadoop helping evaluate different big data frameworks in terms of speed, throughput, and system utilization. At the date of the study current version of HiBench is 7.1, comprising 29 benchmarks categorized



Table 1: HiBench 7.1 - Hadoop-related Workloads

Category	Workload
Micro	Sort, Terasort, Wordcount, Dfsioe, Sleep
SQL	Scan, Join, Aggregation
ML	Bayes, Kmeans
Websearch	Nutchindexing, Pagerank

in 6 sections which are: Micro, Machine Learning, SQL, Websearch, Graph, and Streaming benchmarks.

Leveraged HiBench version of the study is HiBench 7.1.1 [17] Here is another HiBench citation [18]

140 Table 1 lists the Hadoop related workloads in HiBench 7.1

## 2. Related Work

HiBench is a tool to measure a specific systems performing behaviour during execution. The conceptualization of conducting a benchmark may arise from different soils. Based on the conductors motivation; a benchmarks use case  
 145 could be an inner evaluation of a systems performance before and after some configuration tweaks are set, comparison of rival / complementary systems, or putting CSPs cloud infrastructure services on scale. Following literature has been searched with finding different use cases of HiBench benchmarking suite in mind.

150 Poggi et al. [19] Characterizing BigBench

Poggi et al. [20] the state of SQL on Hadoop [53]

Samadi et al. [21] conduct an experimental comparison between Spark and Hadoop installed on virtual machines on Amazon EC2 by leveraging nine among the provided HiBench workloads. Accuracy reasons led the conductors run the  
 155 workloads three times concluding input data scales of 1, 3, and 5 GB respectively. Based on the outputs comprising duration, throughput, speed up, and CPU/memory consumption, the conclusion draws Spark consuming less CPU and performing better on all workload results over Hadoop.

Ahn et al. [22] put Spark on YARNs performance on test with HiBench in  
 160 terms of handling a deluge of data generated by IoT devices. The experiment is  
 run on a cluster with one master and 3 worker nodes each node possessing Intel  
 Xeon processor with 20 cores and 128GB main memory meaning 60 cores and  
 384GB memory in total. HiBenchs workloads Micro (comprising Sort, TeraSort,  
 and Wordcount), SQL (comprising Aggregation, Join, and Scan), and Machine  
 165 Learning (comprising Bayes, Logistic Regression, Gradient Boosting Tree, Ran-  
 dom Forest, and Linear Regression) are leveraged by a chosen data scale of 30  
 GB. Spark occupies memory during the whole job execution which in result  
 reduces IOs negative impact on processor performance. For optimizing resource  
 usage the conductors modified YARNs minimum memory allocation and Spark  
 170 executor settings so that the Spark executors overall loads remain below to-  
 tal system memory. Alongside with HiBenchs duration and throughput report,  
 CPU / memory utilization and disk throughput are profiled as well. Finding of  
 this paper points out that Spark guarantees performance when provided with  
 enough memory.

175 Han et al. [23] study the impact of memory size on big data processing  
 by means of Hadoop and Spark performance comparison leveraging HiBenchs  
 k-Means workload as the only benchmark. For each of the specified memory  
 sizes of 4, 8, and 12 GB, iterating through a data scale of 1 to 8 GB, with 1GB  
 increment inbetween, k-Means benchmark for Hadoop and Spark is executed.  
 180 The results depict Sparks overperforming Hadoop unless the total input data  
 size is smaller than 33.5% of the total memory size assigned to worker nodes.  
 After reaching that ratio Spark suffers with insufficient memory resources and  
 is led to interoperate with HDFS causing a sharp decrease in its performance  
 and brings Hadoop in throughput and duration performance to the front. The  
 185 conductors make a second experiment to find out if Sparks performance can  
 be improved by tweaking the allocation setting for storage memory and shuffle  
 memory while remaining within the specified memory limitations of 4, 8 and  
 12 GB. Executing HiBenchs k-means benchmark outputs a report interpreted  
 by the conductors as Spark show a 5-10%, and 15% maximum improvement in

190 processing time.

Ivanov et al. [24] compare the performances of two enterprise grade applications, DataStax Enterprise (DSE), a production level implementation of Apache Cassandra with extended features like in memory computing and advanced security to name but two, and Clouderas Distribution of Hadoop (CDH) comprising  
195 core Hadoop elements HDFS and YARN integrated with elements belonging to the Hadoop ecosystem. DSEs HDFS compatible file system CSF lets Hadoop applications run without any modification. The conductors installed the latest stable releases of both softwares on equal CPU, memory and network infrastructure configuration. For both installations, default system parameters have  
200 been left with their defaults. HiBenchs three chosen workloads (CPU-bound wordcount, IO-bound dfsioe, and mixed HiveBench) are executed three times, the average values have been taken for representativeness. Several conclusions of their study proclaim linearly scaling of both systems by the increase of data size, while CDH outperforms DSE in read intensive workloads, DSE performs better  
205 in write intensive workloads. Leveraging HiBench is where the study differs in approach related to other studies using YCSB benchmark suite. HiBenchs results confirm the latters output as well.

### 3. Method

In the study we benchmarked Hadoop on PaaS services of three CSPs in  
210 terms of comparing their performances accompanied by respective resource utilization across the worker nodes: GCP Dataproc, Azure HDInsight, and Alibaba Cloud e-MapReduce, each recognized in Gartner’s 2020 Magic Quadrant for Cloud Infrastructure and Platform Services [25] either in leading or in niche section.

215 We constructed the benchmark study in two use cases: Use Case 1 aims to map the overall performance behaviors of respective CSPs within HiBench’s predefined data scales huge and gigantic. The following benchmarks have been executed on the clusters of the respective providers: Micro (Sort, Terasort,

Wordcount, and Dfsioe), Sql (Scan, Join, and Aggregation), ML (Bayes and  
220 Kmeans), and Websearch (Pagerank).

Use Case 2. We picked one benchmark of IO bound character (Sort), one  
benchmark of CPU bound character (Wordcount), and executed these in in-  
creasing data scales HiBench’s: Tiny, Small, Large, Huge, and Gigantic. The  
largest predefined HiBench data scale namely Bigdata would cross the storage  
225 limits of the installed clusters, hence we left it off the execution.

Bound by availability of their respective hardware and software options we  
selected by providers’ promise apparently same or close settings. With respect  
to our aim benchmarking managed systems as they come out-of-the-box, we put  
two basic rules to stick for each provider in order to align initial circumstances  
230 prior to benchmark execution: Among the CSPs, respective data center’s ge-  
ographic location shall be same or close (1), processor number and memory  
capacity (by providers’ promise) shall be same or as close as possible. Thus  
Frankfurt is selected as location for all providers data center, within given op-  
tions we selected 8 CPUs/64GB RAM for master node and 4 CPU’s/32GB RAM  
235 for each worker node totaling in 12 CPUs and 96GB worker compute power for  
the cluster. Specified cluster installation options and details are given in Ta-  
ble 2. Without applying any performance tweak operation to the respective  
preconfigurations we immediately executed several Hadoop benchmarks from  
HiBench’s Micro, Sql, ML, and Websearch categories. We only modified default  
240 cluster’s configuration in cases where the benchmark was detained from running  
which is reported in Discussion section.

During the benchmark execution we collected system utilization records on  
each worker node of the cluster. This approach enabled us the visualization of  
an overview to the system utilizations on each worker node within the cluster  
245 over the respective benchmark’s execution time.

Table 2: Selected configurations on CSPs’ managed Hadoop services

	<b>GCP</b>	<b>Azure</b>	<b>Alibaba Cloud</b>
Service	Dataproc	HDInsight	e-MapReduce
Region	europe-west3-a	Germany West Central	eu-central-1
Location	Frankfurt	Frankfurt	Frankfurt
Image	1.4-ubuntu18	HDI 3.6	EMR-3.32.0
OS	ubuntu18.04	ubuntu 16.04	Aliyun Linux 2
Hadoop v.	2.9	2.7.3	2.8.5
Java	1.8.0_275	1.8.0_275	1.8.0_252
MASTER NODE			
Machine Type	e2-highmem-8	A8m v2	ecs.se1.2xlarge
Processors	8 vCPU	8 cores	8 vCPU
Memory	64 GB RAM	64 GB RAM	64 GB RAM
WORKER NODES			
# Nodes	3	3	3
Machine Type	e2-highmem-4	A4m v2	ecs.se1.xlarge
Processors	4 vCPU	4 cores	4 vCPU
Memory	32 GB RAM	32 GB RAM	32 GB RAM
Storage	HDFS 1000 GB	WASB	HDFS 1000 GB
Replication	2	<i>Azure blob storage</i>	2
Block size	128 MB		128 MB

## 4. Results

HiBench’s Hadoop related benchmarks in groups micro (Sort, Terasort, Dfsioe, and Wordcount), sql (Scan, Join, and Aggregation), ml (Bayes and Kmeans), and websearch (Pagerank) have been executed on all three CSPs managed  
250 Hadoop services. HiBench 7.1 benchmark execution reports for Use Case 1 are listed in Table 3, execution reports for Use Case 2 are listed in Table 4.

*Plots.* During benchmark runtime resource utilization on worker nodes have been captured. The plots are suggested to perceived read as follows: Top-left, top-right, and bottom-left plots represent CPU (user%), Memory (%memused),  
255 and IO utilization (read transfers and write transfers per second) on each worker node of the respective cluster over time. CPU utilization lines are given in blue tones, Memory utilization lines are given in fuchsia tones, IO-read and IO-write tps’ are represented with orange tones and green tones, respectively. Even though the coloring convention might sound confusing, it gives a clear  
260 overview in terms of utilization behavior of the total benchmark process over time. The left hand side x-axis measures CPU/Memory usage in percent, the right hand side x-axis measures IO-read and IO-write transfers per second. The bottom-right plot represents the comparative benchmark performance outputs of the respective CSPs. Duration measure in seconds is expected to perceived  
265 as ”lower is better” while Throughput which is the amount of processed data per second in bytes is expected to perceived as ”higher is better”.

For each use case we provided spider charts, a.k.a. radar plots, to give a comparative overview for system utilization vs. benchmark performances of relevant CSPs. In these plots normalized average values of the captured CPU,  
270 Memory, and IO data on the worker nodes have been taken and averaged a second time in order to get scalar CPU, Memory and IO values representing the cluster’s average performance. Combining the aforementioned values with normalized Duration and Throughput report values of HiBench resulting the spider plots of the paper. Nevertheless, for the spider plots our recommendation  
275 for both perceptions of Throughput and Duration shall be ”Higher is better”.

Table 3: Use Case 1 benchmark outputs

Data Scale: Huge

Benchmark	IDS	Dataproc		HDInsight		e-MapReduce	
		$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$
Sort	3.28	70	47.11	131	25.08	111	29.42
Terasort	32.00	667	47.99	858	37.28	1054	30.37
Wordcount	32.85	978	33.60	1470	22.34	889	36.95
Dfsioe-r	26.99	294	91.77	662	40.79	245	110.21
Dfsioe-w	27.16	379	71.73	658	41.30	281	96.49
Scan	2.01	73	27.63	157	12.83	74 (*)	27.19 (*)
Join	1.92	181	10.61	356	5.39	175 (*)	10.95 (*)
Aggregation	0.37	97	3.86	215	1.73	97 (*)	3.85 (*)
Bayes	1.88	2604	0.72	6120	0.31	3017	0.62
Kmeans	20.08	2321	8.65	2313	8.68	2070	9.70
Pagerank	2.99	1544	1.94	3334	0.90	2458	1.22

Data Scale: Gigantic

Benchmark	IDS	Dataproc		HDInsight		e-MapReduce	
		$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$
Sort	32.85	715	45.94	787	41.72	896	36.68
Terasort	320.00	9821	32.58	—(**)	—(**)	9660	33.13
Wordcount	328.49	10131	32.42	13596	24.16	8671	37.88
Dfsioe-r	216.03	915	236.11	1886	114.54	660	327.29
Dfsioe-w	217.33	1347	161.39	1914	113.57	1060	205.12
Scan	20.10	457	43.96	514	39.09	407 (*)	49.38 (*)
Join	19.19	595	32.27	761	25.24	594 (*)	32.32 (*)
Aggregation	3.69	523	7.05	594	6.20	565 (*)	6.52 (*)
Bayes	3.77	5350	0.70	12589	0.30	6363	0.60
Kmeans	40.16	4541	8.84	4042	9.94	4034	9.96
Pagerank	19.93	8371	2.38	11779	1.70	13893	1.43

IDS: Input Data Size (GB);  $D_{(s)}$ : Duration (sec);  $T_{(MB/s)}$ : Throughput (MB/sec)

(\*) Benchmark succeeds after modifying preconfiguration, more on this in Discussion

(\*\*) System failure due to insufficient space on HDFS, more on this in Discussion

Table 4: Use Case 2 benchmark outputs

Benchmark	Dataproc			HDInsight		e-MapReduce	
	IDS	$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$	$D_{(s)}$	$T_{(MB/s)}$
Sort (t)	39.30 KB	36	0.0012	69	0.0006	32	0.0012
Wordcount(t)	38.65 KB	38	0.001	68	0.0006	31	0.0012
Sort (s)	3.28 MB	36	0.09	70	0.0471	31	0.105
Wordcount (s)	348.29 MB	50	6.51	98	3.34	47	7.06
Sort (l)	328.50 MB	42	7.86	81	4.07	42	7.74
Wordcount (l)	3.28 GB	129	25.45	269	12.20	120	27.27
Sort (h)	3.28 GB	70	47.08	141	23.36	107	30.69
Wordcount (h)	32.85 GB	952	34.51	1487	22.10	888	37.00
Sort (g)	32.85 GB	694	47.30	699	47.00	883	37.20
Wordcount (g)	328.49 GB	9749	33.70	13286	24.73	8622	38.10

IDS: Input Data Size;  $D_{(s)}$ : Duration (sec);  $T_{(MB/s)}$ : Throughput (MB/sec)  
(t): tiny, (s): small, (l): large, (h): huge, (g): gigantic

Even though the Duration is of lower is better nature, for the sake of proper visualization we needed to display the shortest duration as the most visible among other CSPs.

#### USE CASE 1:

280 *Sort - Huge.* Figure 5; CPU utilization in GCP and Alibaba condense around 80% to 98% whereas in Azure the range widens up between 50% to 90%. Memory loads in GCP and Alibaba among the worker nodes display a harmonic behavior between 20% to 40% and 90% to 100% respectively, whereas the memory load in Azure's worker nodes vary between 10% and 50%. In the second  
285 half of the benchmark execution IO write transfers in GCP and Alibaba show peaks at about 500 tps where in Azure it is limited with 100 tps. Resulting in GCP carrying out the highest Throughput, thus reaching the shortest Duration of 70 seconds.

*Sort - Gigantic.* Figure 6; switching the data scale for Sort benchmark to gigantic, GCP's processor load condenses around 80% - 95% where its memory load  
290



Table 5: Use Case 1 Comparative benchmark outputs

Data Scale: Huge					
Benchmark	First	Second	-Perf.%	Third	-Perf.%
Sort	GCP	Alibaba	-58.57%	Azure	-87.14%
Terasort	GCP	Azure	-28.64%	Alibaba	-58.02%
Wordcount	Alibaba	GCP	-10.01%	Azure	-65.35%
Dfsioe-r	Alibaba	GCP	-20.00%	Azure	-170.20%
Dfsioe-w	Alibaba	GCP	-34.88%	Azure	-134.16%
Scan	GCP	Alibaba	-1.37%	Azure	-115.07%
Join	Alibaba	GCP	-3.43%	Azure	-103.43%
Aggregation	GCP-Alibaba	—	—	Azure	-121.65%
Bayes	GCP	Alibaba	-15.86%	Azure	-135.02%
Kmeans	Alibaba	Azure	-11.74%	GCP	-12.13%
Pagerank	GCP	Alibaba	-59.20%	Azure	-115.93%
Data Scale: Gigantic					
Benchmark	First	Second	-Perf.%	Third	-Perf.%
Sort	GCP	Azure	-10.07%	Alibaba	-25.31%
Terasort	Alibaba	GCP	-1.67%	Azure	—
Wordcount	Alibaba	GCP	-16.84%	Azure	-56.80%
Dfsioe-r	Alibaba	GCP	-38.64%	Azure	-185.76%
Dfsioe-w	Alibaba	GCP	-27.08%	Azure	-80.57%
Scan	Alibaba	GCP	-12.29%	Azure	-26.29%
Join	Alibaba	GCP	-0.17%	Azure	-28.11%
Aggregation	GCP	Alibaba	-8.03%	Azure	-13.58%
Bayes	GCP	Alibaba	-18.93%	Azure	-135.31%
Kmeans	Alibaba	Azure	-0.20%	GCP	-12.57%
Pagerank	GCP	Azure	-40.71%	Alibaba	-65.97%

risers to range 80% - 100%; IO write transfers behave at about 500 tps where IO reads reach 1000 tps in the second half of the benchmark process. Azure's processor and memory performances depict a looser behavior not utilizing the maximum potential whereas IO-read and IO-write tps' reach their maximum at 200 and 350, respectively. Alibaba's resource utilization depicts a high memory load of 90% - 100% dropping to 70% and about 83% on partial nodes in the second half. As so with the processor load behaving between 80% and 100% in the first half dropping to about 50% in the second half where IO write reaches peak at 800 tps. Resulting in GCP embarking highest and Azure the second highest Throughput, respective Durations output in 715 and 758 seconds.

*Terasort - Huge.* Figure 7; GCP depicts a high utilization on processors at a range of 80% - 100%, memory moving from 80% to 100%, and IO behavior 500 tps in overall and peaking at 1000 tps in IO-read resulting in highest Throughput in 667 seconds response time among other CSPs. Azure's processor and memory utilization fluctuate in overall where memory performance incrementally reach 100% in one node, a stable IO-write in overall process at about 70 tps peaking at 250 tps reaches the second highest Throughput in 858 seconds. Alibaba with high memory and processor utilization, and varying IO tps's in overall process falls back in embarking Throughput and resulting in 1054 seconds response time.

*Terasort - Gigantic.* Figure 8; switching the scale to gigantic causes dramatic changes on resource utilization on all CSPs. During all benchmark process GCP depicts very condensed high utilization on processor at a broad range of 30% to about 95%, memory consumption between 95% and 100% and IO read transfer varying between 800 to 1100 tps. Azure on the other side, fails to complete the benchmark on 3 attempts; suffering from YARN insufficient HDFS allocation requested for bringing the job further. IO scores drop to null and task raises failure. Alibaba Cloud's resource utilization goes within maximum levels where processor utilization depicts a consumption of 80% to 90% in the overall, memory utilization at it highest during all process, IO reads and writes moving along the 600 tps' and peaking around 1600 tps. With a slicely higher value in

Throughput, Alibaba performs best with 9660 seconds, followed by GCP with 9821 seconds. Azure disqualifies this session.

*Wordcount - Huge.* Figure 9; GCP performing processor utilization of 75% to 100% with a memory consumption between 80% to 95% where IO transfers  
325 move along 60 tps peaking at about 150 tps reaches second highest Throughput with 978 seconds response time. Azure's processor utilization moving along 70% to about 100% where memory depicts 30% to 50% utilization and lower IO transfers peaking at about 60 tps reaches the lowest throughput hence the longest duration of 1470 seconds. Alibaba depicting high processor and memory  
330 load moving in ranges 70% to 100% and 80% to slightly over 90% with IO transfers moving along 200 tps peaking at 300tps to 350tps reaches the highest Throughput hence shortest execution time of 889 seconds.

*Wordcount - Gigantic.* Figure 10; GCP utilizing processor and memory sources at their maximum during the overall process, for CPU within 60% up to push-  
335 ing 100%, memory utilization varying between 60% to 100%, and IO-read and IO-write transfers moving along 90 tps and 250 tps respectively, reaches second highest Throughput load resulting in 10131 seconds response time. Azure shows a dens processor utilization varying between 40% and close to 100%, memory consumption is somehow oppressed to stay within range 20% up to 50%, IO  
340 behavior reacts seldomly over 60 tps resulting in the lowest Throughput and longest Duration of 13596 seconds. Alibaba depicting a high processor utilization within range 85%-100%, a relatively more stable memory consumption in range 85% to 100% and IO transfers mostly about 300 tps thus performing highest Throughput hence shortest response time of 8671 seconds.

345 *Dfsioe-read - Huge.* Figure 11; GCP's processor utilization moving roughly between 80% to 95% accompanied by memory utilization within range slightly below and over 70%, IO transfers peaking at 400 tps mostly go along 100 tps and 250 tps performs second highest Throughput resulting in 294 seconds of Duration. Azure's processor utilization is rather limited to between 60% and

350 90% whereas the memory utilization behaves between 10% to 50%, generally  
low IO transfers with two markable IO-read and IO-write condensences reaching  
peaks at 2000 tps and 1500 tps respectively results in the lowest Throughput  
and 662 seconds of response time. Alibaba with 245 seconds Duration displays  
a similar resource utilization pattern with GCP where it differentiates in memory  
355 utilization moving around 90%.

*Dfsioe-read - Gigantic.* Figure 12; processor utilization in GCP cloud concentrates within range of 80% to 90%, memory utilization moves around 95% to 100% whereas IO read transfers moving along about 500 tps brings its performance to second highest Throughput with 915 seconds Duration. Azure displays  
360 a performance within a range of 55% up to 90% in CPU utilization, 20% to 55% in memory utilization, and IO-write activity moving along 70 tps, IO-read showing peak at about 470 tps reaching the lowest performance in Throughput outputting 1886 seconds response time. Alibaba system utilization moves along 80%-90% range for processing performance, 90%-100% for memory load  
365 and a behavior up to 1700 tps IO-write placing its performance to the highest Throughput with 660 seconds duration.

*Dfsioe-write - Huge.* Figure 13; in GCP processor utilization moves between 70% and 90%, memory load increments from 20% up to 70% whereas IO-write transfers move along 500 tps resulting in second shortest response time 379  
370 seconds. Azure's CPU utilization around 60% to 90%, memory load moves between 20% and 40% whereas IO-write transfers vary about 20 tps to 80 tps peaking at about 120 tps by a Duration output of 658 seconds. Alibaba with processor utilization 80% and 95%, incrementing memory load from about 40% up to 90%-100%, and IO-write transfers at about 100 tps to 600 tps peaking  
375 at about 800 tps performs the heaviest Throughput thus reaching the shortest response time with 281 seconds.

*Dfsioe-write - Gigantic.* Figure 14; GCP processor utilization moves along a broad range hitting up to 90% load, memory load quickly rises to 95%-100%

range and keeps its position in overall execution, IO-writes move along 500 tps to  
 380 600 tps placing GCP to the second best performance with 1347 seconds response  
 time. Azure shows a CPU utilization in a range 60% up to 90% until it drops  
 to about 25% in the 2/3th of the overall process, memory load moves along  
 lower 20% to upper 50% until its sudden drop to upper 15% simultaneously  
 385 in 1914 seconds response time. Alibaba performing the shortest response time  
 with 1060 seconds displays a similar memory and processor utilization behaviour  
 with GCP where it differs in IO-write transfers peaking at about 900 tps.

*Scan - Huge.* Figure 15; GCP processor utilization condenses between about  
 80% and 90% during benchmark execution, memory load depicts movement  
 390 between 20% and 40% accompanied by an IO-write transfer reaching over 500  
 tps which brings GCP to the leading performance within this benchmark with  
 73 seconds. On Azure's side processor utilization moves along 80%-90% range  
 whereas memory load increments from the 15% to the 30%, relatively low  
 IO-write transfer peaking at about 85 tps results in lowest Throughput and  
 395 157 seconds Duration. Alibaba follows a similar pattern like GCP in resource  
 utilization with about 90% CPU load, 15% to below 40% memory utilization  
 but a less dense IO-write transfer peaking at about 550 tps and so reaching a  
 close Throughput to GCP resulting in 74 seconds response time.

*Scan - Gigantic.* Figure 16; GCP's CPU utilization varying between 50% and  
 400 90% with a convergence at about 80%, memory load showing similar range  
 with utilization reaching up 100% and IO-write transfers moving between 500  
 tps and 600 tps results in second highest Throughput by a 457 seconds response  
 time. Azure's CPU utilization condenses between 80% and 90% and memory  
 load incrementing two times from 20% to 40%, IO-write transfer moving along  
 405 50 tps to 60 tps peaking at about 200 tps results in 514 seconds Duration.  
 Alibaba's processor utilization moves in a relatively higher range between 80%  
 and 95%, an incrementing memory load range from 40%-50% to 80%-100%

during runtime, and IO-write transfers peaking at about over 500 tps results in highest Throughput thus shortest Duration of 407 seconds.

410 *Join - Huge.* Figure 17; GCP processor load moves mainly between 80% and over 90%, memory utilization moves along about 20% and 30%, IO-writes behaving at about 150 tps brings outputs 181 seconds response time. Azures resource utilization shows range between 80% and 90% for CPU, varying memory loads moving along below 20% and below 60%, IO-write transfers behave  
415 below 60 tps with a peak of 100 tps resulting in a lower throughput and response time of 356 seconds. Resource utilization at Alibaba behaves similar to GCP in processor and memory load whereas IO-write peaks at about 260 tps, reaching highest Throughput and a Duration of 175 seconds.

*Join - Gigantic.* Figure 18; CPU load in GCP moves along 70% to 90% in over-  
420 all whereas RAM utilization among worker nodes takes a path within 50% to 90% range, IO-write transfers observed in behaviour about 100 tps resulting in a Throughput outputting 595 seconds of response time. Azure's resource utilization dynamics show a utilization of 80% to 90% with decreasing utilization on some worker nodes in later stage, memory utilization moving along the range  
425 20% up to 60% and IO-write transfer observations peaking at 120 tps provide the lowest Throughput hence the longest response time of 761 seconds. Alibaba performing a processor utilization of about below 90% to below 100%, memory load behavior moving along 50% to below 70%, and IO-write observation peaking at 350 tps performs a slightly higher Throughput than GCP hence  
430 slightly shorter Duration of 594 seconds.

*Aggregation - Huge.* Figure 19; GCP processor utilization moving around 80% to about 95%, memory load behaving between 15% to 40%, and IO-write transfer observed at about 150 tps results in 97 seconds Duration. Azure's CPU utilization behaves between 80% and 90% whereas memory load moves along  
435 from 10% to varying utilizations among worker nodes up to 30% and below 60%, and IO-write transfers peaking at about 180 tps performs a relatively

small Throughput resulting in 215 seconds completion time. Alibaba resource utilization moving along between 80% and 90% for CPU, 10% to 40% in memory, and IO-write transfer average of 26 tps show close performance to GCP  
440 resulting in same completion time of 97 seconds.

*Aggregation - Gigantic.* Figure 20; processor utilization moving between 80% and 90% in overall execution, memory load between 50% and 70% peaking to below 100%, IO-write transfers reaching a dense behavior at the end reaching 500 tps results in highest Throughput and 523 seconds response time. Azure  
445 displays a CPU utilization of below 80% to above 90%, mild RAM utilization moving along 30% to 60%, IO-write transfers behaving about 100 tps result in a relative low Throughput and 594 seconds of Duration to complete. Alibaba's processor load moves along 80% to below 100%, IO-write transfer behavior scaling from about 50 tps to 400 tps results in 565 seconds response time.

450 *Bayes - Huge.* Figure 21; GCP in processor behavior moving along about 70% to below 100%, memory load at about 30% with a short peak to below 100% at the first half, an IO-write transfer behavior about 500 tps resulting in highest Throughput thus fastest response time of 2604 seconds. Azure showing a splitted behavior in CPU utilization among worker nodes where one load moves  
455 along about 80% to lower 100% and one node depicts a movement along minimum to about 20%, memory loads also varying from each other by about 20% load difference at the beginning however meeting the similar range starting at the second half, IO observations depict a low range with exception at the high IO-write transfer at about 3200 tps at the initial state of the execution result in  
460 a relatively low Throughput hence longest Duration of 6120 seconds. Alibaba CPU utilization shows varieties among worker nodes in load ranges, RAM utilization condenses at higher levels over 80%, IO transfers moving along 100 tps to observable 450 tps resulting in 3017 seconds response time.

*Bayes - Gigantic.* Figure 22; GCP's processor utilization moving along 70% to  
465 below 100%, accompanied by memory load incrementing from 40% to 70%

becoming stable at 50%, and IO-write transfers moving along 500 tps results in the highest Throughput and 5350 seconds of response time. Azure's resource utilization shows distinction in CPU and memory among worker nodes while two nodes depict higher utilization at about 70% to below 100% for processing and 40%-50% for memory, one node staying at lower levels for respective resources, the observed IO-write transfer move along 100 tps where IO-read transfer peaks at about 650 tps resulting in a lowest performance of 12589 seconds Duration. Alibaba depicting different utilization ranges among worker nodes for processing, the memory consumption follows a more balanced load among worker nodes with IO-write transfer moving along 200 tps a relatively lower Throughput hence relatively longer Duration of 6363 seconds, with respect to GCP.

*Kmeans - Huge.* Figure 23;

*Kmeans - Gigantic.* Figure 24;

*Pagerank - Huge.* Figure 25;

*Pagerank - Gigantic.* Figure 26;

*Overview to benchmarks executed in data scale Huge/.* Figure 27;

*Overview to benchmarks executed in data scale Gigantic.* Figure 28;

## USE CASE 2:

*Sort.* Figure 29;

*Sort - Small.* Figure 30;

*Sort - Large.* Figure 31;

*Sort - Huge.* Figure 32;

*Sort - Gigantic.* Figure 33;

*Wordcount.* Figure 34;






Figure 5: UC1 - Sort (Huge; 3.2 GB)




Figure 6: UC1 - Sort (Gigantic; 32 GB)




Figure 7: UC1 - Terasort (Huge; 320 MB)




Figure 8: UC1 - Terasort (Gigantic; 3.2 GB)




Figure 9: UC1 - Wordcount (Huge; 32 GB)




Figure 10: UC1 - Wordcount (Gigantic; 320 GB)




Figure 11: UC1 - Dfsioe-read (Huge; No of Files: 256, File size: 100 MB)




Figure 12: UC1 - Dfsioe-read (Gigantic; No of Files: 512, File size: 400 MB)




Figure 13: UC1 - Dfsioe-write (Huge; No of Files: 256, File size: 100 MB)




Figure 14: UC1 - Dfsioe-write (Gigantic; No of Files: 512, File size: 400 MB)




Figure 15: UC1 - Scan (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 16: UC1 - Scan (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)




Figure 17: UC1 - Join (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 18: UC1 - Join (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)




Figure 19: UC1 - Aggregation (Huge; USERVISITS: 10,000,000 PAGES: 1,200,000)




Figure 20: UC1 - Aggregation (Gigantic; USERVISITS: 100,000,000 PAGES: 12,000,000)






Figure 21: UC1 - Bayes (Huge; PAGES: 500,000 CLASSES: 100 NGRAMS: 2)




Figure 22: UC1 - Bayes (Gigantic; PAGES: 1,000,000 CLASSES: 100 NGRAMS: 2)




Figure 23: UC1 - Kmeans (Huge; CLUSTERS: 5 DIMENSIONS: 20 SAMPLES: 100,000,000 SAMP PER INPUT: 20,000,000 MAX IT: 5 K: 10 CONVERGEDIST: 0.5)




Figure 24: UC1 - Kmeans (Gigantic; CLUSTERS: 5 DIMENSIONS: 20 SAMPLES: 200,000,000 SAMP PER INPUT: 40,000,000 MAX IT: 5 K: 10 CONVERGEDIST: 0.5)




Figure 25: UC1 - Pagerank (Huge; PAGES: 5,000,000 NUM ITERATIONS: 3 BLOCK: 0 BLOCK WIDTH: 16)




Figure 26: UC1 - Pagerank (Gigantic; PAGES: 30,000,000 NUM ITERATIONS: 3 BLOCK: 0 BLOCK WIDTH: 16)




Figure 27: Use Case 1 - Hadoop benchmark comparisons in huge data scale




Figure 28: Use Case 1 - Hadoop benchmark comparisons in gigantic data scale

490 *Wordcount - Small.* Figure 35;

*Wordcount - Large.* Figure 36;

*Wordcount - Huge.* Figure 37;

*Wordcount - Gigantic.* Figure 38;

Wordcount results in scale

495 *Overview of Sort benchmark varying data scales.* Figure 39;

*Overview of Wordcount benchmark varying data scales.* Figure 40;

## 5. Discussion

*Limitations, workarounds, failures.* One major limitation of the study has been the high-cost of benchmark executions' total running time charged in a pay-per-use manner which led the conductors keeping benchmarks at only one successful  
500 execution for each workload. This is not fitting the best practice, though, where a benchmark would have been executed thrice for each workload and the average performance results were taken. Following the best practise would have provided more stable outcomes especially in cases where there occurs very tiny difference  
505 between successive performances of respective providers. Another result of the aforementioned limitation is that we also left off the largest predefined data scale of HiBench, namely Bigdata. Execution of this benchmark would have provide us performance outputs in a very large data scale like 300 GB for Sort, 1.6 TB for Wordcount, and 12.000.000 Pages by 1.000.000.000 Uservisits for Aggregation,  
510 to name but three. Hence, we recommend the study to be understood in terms of an attempt trying to bring more clarity to black-box nature managed Hadoop proposals' performance behavior by means of resource utilization dynamics, and as the managed services come out-of-the-box without any performance tweaking configurations applied. We do not recommend the study to be understood as a  
515 grading board for the business values provided by respective CSPs.




Figure 29: UC2 - Sort (Tiny; 32 KB)




Figure 30: UC2 - Sort (Small; 3.2 MB)




Figure 31: UC2 - Sort (Large; 320 MB)




Figure 32: UC2 - Sort (Huge; 3.2 GB)






Figure 33: UC2 - Sort (Gigantic; 32 GB)




Figure 34: UC2 - Wordcount (Tiny; 32 KB)




Figure 35: UC2 - Wordcount (Small; 320 MB)




Figure 36: UC2 - Wordcount (Large; 3.2 GB)




Figure 37: UC2 - Wordcount (Huge; 32 GB)




Figure 38: UC2 - Wordcount (Gigantic; 320 GB)




Figure 39: Use Case 2 - Sort performances along data scales




Figure 40: Use Case 2 - Wordcount performances along data scales

HiBench comes with dependencies downloaded during its compilation process by Apache Maven. The Hive engine is one of those dependencies leveraged by HiBench for running SQL workloads Scan, Join, and Aggregation. Alibaba's e-Mapreduce comprises a ready made Hive hook triggering a Java file to run post  
520 executional transactions for other services within the package. However this preconfiguration prevented HiBench from starting with respective benchmarks' execution since the HiBench based Hive engine does not include the aforementioned jar file defined for e-MapReduce's specific environment. A workaround attempt, copying the related jar file to an appropriate directory within HiBench  
525 made the jar file available, however this time HiBench's Hive engine of an older version did not support the hook "hive.exec.post.hooks" defined in Alibaba's Hive configuration. At this point disabling the respective Hive hook from Alibaba e-MapReduce's UI management console apparently solved this issue and enabled HiBench's SQL workloads to run, but the impact of this modification on  
530 the respective performance values remains unknown, hence the need to annotate it here. With GCP and Azure issues of this kind did not occur.

In Azure environment the Terasort benchmark running in data scale gigantic failed to complete in all three attempts we conducted where about 20% of maps operations were reached. Showing distinction to GCP and Alibaba where the  
535 end user is liberate in choosing HDFS or respective provider's cloud storage service as the cluster's file system, Azure obligates the user to go with WASB file system among other Azure storage services with a promise to Peta-scale. However, after inspecting the failure it turned out that the exception is not due the WASB file system. Even though WASB is predefined as the cluster's  
540 file system, during the application's run time YARN still leverages the cluster's HDFS file system for storing intermediary results failing to allocate free space on HDFS reaching specific levels of maps operators. The conductors marked this failure as a structural bottleneck, since all end users running Terasort operation at this scale would face the same error, and since resource utilization can be  
545 tracked up to the failure point and after, we kept this benchmark by marking as incomplete. Figure 8 displays system resource utilization on Azure including

the point where the failure occurs.

## 6. Conclusion and Future Work

Managed Hadoop systems are by CSPs provided cloud service proposals comprising pre-installed and pre-configured Hadoop clusters in order to eliminate the hard work on planning and installing Hadoop clusters manually on VM instances hence reducing the cluster installation to a matter of property selection and letting end users focus only to applications that will run on the cluster. As managed systems come in a black-box nature respective pre-configurations and their impacts on the cluster performance remains unclear to the end user. In the study we conducted HiBench benchmarks against Hadoop clusters on PaaS in their proposed form as they come out-of-the-box, provided by respective CSPs. For each CSP, among the proposed installation specifications, we selected same geographical location as region and by-promise apparently same CPU and Memory properties. Our aim is to compare those systems' performance behaviors by leveraging HiBench Benchmark Suite. We executed Hadoop related benchmarks on all three Hadoop on PaaS services and captured system resource utilization data in the meanwhile. The results yield that Hadoop PaaS offerings by vendor's promise do not necessarily utilize system resources in similar ways hence may highly distinct in some cases. Our assumption is that the pre-configuration choices applied by CSPs highly impact performance results even with apparently same hardware settings. The end users shall be aware of their use cases' requirements and truly understand what CSPs configuration proposals and their respective outcome.

Based on the gained experience the study might varied in an approach more sensitive in balancing small performance differences among CSPs. As HiBench offers benchmarks for Spark, graph and streaming frameworks as well, the comparison can be made from within the respective perspective, putting also other global CSP players into the scope.

575 **References**

- [1] World Internet Users Statistics and 2020 World Population Stats.  
URL <https://www.internetworldstats.com/stats.htm>
- [2] Apache Hadoop.  
URL <https://hadoop.apache.org/>
- 580 [3] S. Ghemawat, H. Gobioff, S.-T. Leung, The Google file system, in: Proceedings of the nineteenth ACM symposium on Operating systems principles, Vol. 37, 2003, pp. 29–43, issue: 5. doi:10.1145/1165389.945450.
- [4] T. White, Hadoop: the definitive guide, fourth edition Edition, O'Reilly, Beijing, 2015, oCLC: ocn904818464.
- 585 [5] J. Dean, S. Ghemawat, MapReduce: Simplified data processing on large clusters, 2004, pp. 137–149.
- [6] a. A. T. H. Schtzle, Martin Przyjacieli-Zablocki, Giant Data: MapReduce and Hadoop ADMIN Magazine.  
URL [http://www.admin-magazine.com/HPC/Articles/](http://www.admin-magazine.com/HPC/Articles/MapReduce-and-Hadoop)  
590 [MapReduce-and-Hadoop](http://www.admin-magazine.com/HPC/Articles/MapReduce-and-Hadoop)
- [7] Announcing Amazon Elastic Compute Cloud (Amazon EC2) - beta.  
URL <https://aws.amazon.com/about-aws/whats-new/2006/08/24/announcing-amazon-elastic-compute-cloud-amazon-ec2---beta/>
- [8] Dataproc.  
595 URL <https://cloud.google.com/dataproc>
- [9] Compute Engine: Virtual Machines (VMs).  
URL <https://cloud.google.com/compute>
- [10] Cloud Storage.  
URL <https://cloud.google.com/storage>

- 600 [11] Azure HDInsight - Hadoop, Spark, & Kafka Service | Microsoft Azure.  
URL <https://azure.microsoft.com/en-us/services/hdinsight/>
- [12] Announcing general availability of Azure HDInsight 3.6.  
URL <https://azure.microsoft.com/en-us/blog/announcing-general-availability-of-azure-hdinsight-3-6/>
- 605 [13] What is E-MapReduce? - Product Introduction| Alibaba Cloud Documentation Center.  
URL <https://www.alibabacloud.com/help/doc-detail/28068.htm?spm=a2c63.128256.b99.4.65e270b2YXyKDV>
- [14] Alibaba Cloud Linux OS.  
610 URL <https://alibaba.github.io/cloud-kernel/os.html>
- [15] Intel-bigdata/HiBench, original-date: 2012-06-12T07:56:57Z (Jan. 2021).  
URL <https://github.com/Intel-bigdata/HiBench>
- [16] S. Huang, J. Huang, J. Dai, T. Xie, B. Huang, The HiBench benchmark suite: Characterization of the MapReduce-based data analysis, in: 2010 IEEE 26th International Conference on Data Engineering Workshops (ICDEW 2010), 2010, pp. 41–51. doi:10.1109/ICDEW.2010.5452747.  
615
- [17] Release HiBench-7.1.1 Intel-bigdata/HiBench.  
URL [/Intel-bigdata/HiBench/releases/tag/v7.1.1](https://github.com/Intel-bigdata/HiBench/releases/tag/v7.1.1)
- [18] L. Yi, J. Dai, Experience from Hadoop Benchmarking with HiBench: From Micro-Benchmarks Toward End-to-End Pipelines, in: T. Rabl, N. Raghunath, M. Poess, M. Bhandarkar, H.-A. Jacobsen, C. Baru (Eds.), Advancing Big Data Benchmarks, Vol. 8585, Springer International Publishing, Cham, 2014, pp. 43–48, series Title: Lecture Notes in Computer Science. doi:10.1007/978-3-319-10596-3\_4.  
620
- 625 URL [http://link.springer.com/10.1007/978-3-319-10596-3\\_4](http://link.springer.com/10.1007/978-3-319-10596-3_4)
- [19] N. Poggi, A. Montero, D. Carrera, Characterizing bigbench queries, hive, and spark in multi-cloud environments, Lecture Notes in Computer Sci-



- ence (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) 10661 LNCS (2018) 55–74. doi:10.1007/978-3-319-72401-0\_5.
- [20] N. Poggi, J. L. Berral, T. Fenech, D. Carrera, J. Blakeley, U. F. Minhas, N. Vujic, The state of SQL-on-Hadoop in the cloud, in: 2016 IEEE International Conference on Big Data (Big Data), 2016, pp. 1432–1443. doi:10.1109/BigData.2016.7840751.
- [21] Y. Samadi, M. Zbakh, C. Taddonki, Performance comparison between hadoop and spark frameworks using HiBench benchmarks, Concurrency Computation 30 (12). doi:10.1002/cpe.4367.
- [22] H. Ahn, H. Kim, W. You, Performance Study of Spark on YARN Cluster Using HiBench, 2018. doi:10.1109/ICCE-ASIA.2018.8552137.
- [23] S. Han, W. Choi, R. Muwafiq, Y. Nah, Impact of memory size on bigdata processing based on hadoop and spark, Vol. 2017-January, 2017, pp. 275–280. doi:10.1145/3129676.3129688.
- [24] T. Ivanov, R. Niemann, S. Izberovic, M. Rosselli, K. Tolle, R. V. Zicari, Performance Evaluation of Enterprise Big Data Platforms with HiBench, in: 2015 IEEE Trustcom/BigDataSE/ISPA, Vol. 2, 2015, pp. 120–127. doi:10.1109/Trustcom.2015.570.
- [25] Gartner Reprint.  
URL <https://www.gartner.com/doc/reprints?id=1-1ZDZDMTF&ct=200703&st=sb>