

# Unit 4 - Lesson 3: Dictionaries Mastery

## Quick Reference Guide

### Safe Access with .get()

**The Problem:** Accessing a missing key crashes your program!

```
song = {"title": "Blinding Lights", "artist": "The Weeknd"}
print(song["genre"]) # 🌟 KeyError: 'genre'
```

**The Solution:** Use `.get()` for safe access

```
# Returns None if key missing
genre = song.get("genre")           # None

# Returns default if key missing
genre = song.get("genre", "Unknown") # "Unknown"

# Returns value if key exists (default ignored)
title = song.get("title", "No title") # "Blinding Lights"
```

**When to use each:**

Syntax	Use When
<code>dict["key"]</code>	Key MUST exist (required field)
<code>dict.get("key")</code>	Key MIGHT be missing (optional field)
<code>dict.get("key", default)</code>	Need a fallback value

# Dictionary Methods

```
song = {"title": "Blinding Lights", "artist": "The Weeknd", "plays": 3500000}
```

Method	Returns	Example
<code>.keys()</code>	All keys	<code>dict_keys(['title', 'artist', 'plays'])</code>
<code>.values()</code>	All values	<code>dict_values(['Blinding Lights', 'The Weeknd', 3500000])</code>
<code>.items()</code>	(key, value) pairs	<code>dict_items([('title', 'Blinding Lights'), ...])</code>

## Useful patterns:

```
# Sum all values
stats = {"views": 1000, "likes": 150, "shares": 25}
total = sum(stats.values()) # 1175

# Check if key exists
if "genre" in song:
    print(song["genre"])
```

---

## Looping Through Dictionaries

### Loop through keys (default):

```
for key in song:
    print(key) # title, artist, plays
```

### Loop through values:

```
for value in song.values():
    print(value) # Blinding Lights, The Weeknd, 3500000
```

### Loop through items (most useful!):

```
for key, value in song.items():  
    print(f"{key}: {value}")
```

Output:

```
title: Blinding Lights  
artist: The Weeknd  
plays: 3500000
```

---

## + Updating Dictionaries

**Add or update single key:**

```
song["genre"] = "Synth-pop" # Add new key  
song["plays"] = 4000000     # Update existing key
```

**Update multiple keys at once:**

```
song.update({"genre": "Synth-pop", "year": 2020})
```

⚠️ `.update()` modifies the original dictionary!

---

## ✨ Dictionary Comprehensions

**Basic syntax:**

```
{key_expression: value_expression for item in iterable}
```

**Transform values:**

```
menu = {"latte": 4.50, "mocha": 5.00, "espresso": 3.00}

# Add 8% tax to all prices
with_tax = {item: price * 1.08 for item, price in menu.items()}
# {'latte': 4.86, 'mocha': 5.4, 'espresso': 3.24}
```

## Filter with comprehension:

```
scores = {"Alice": 95, "Bob": 67, "Charlie": 82}


# Keep only passing scores
passing = {name: score for name, score in scores.items() if score >= 70}
# {'Alice': 95, 'Charlie': 82}
```

## Compare to list comprehensions:

List	Dict
[expr for item in list]	{key: value for item in iterable}
[expr for item in list if cond]	{key: value for k, v in dict.items() if cond}

## ⚠️ Modify vs Return New

Operation	Modifies Original?	Returns
dict.get(key)	❌ No	Value or None
dict.get(key, default)	❌ No	Value or default
dict.keys()	❌ No	Keys
dict.values()	❌ No	Values
dict.items()	❌ No	(key, value) pairs
dict.update(other)	✅ Yes	None
dict["key"] = value	✅ Yes	None
del dict["key"]	✅ Yes	None

Operation	Modifies Original?	Returns
<code>{...}</code> comprehension	 No	<b>New</b> dict

---

## Key Takeaways

1. Use `.get()` for safe access - never crashes on missing keys
2. Use `.items()` for looping - gives both key and value
3. Dict comprehensions follow list patterns - `if` at END filters
4. Know what modifies vs returns - `.update()` modifies, comprehensions create new

---

## Common Patterns

### Safe access with default:

```
username = user.get("username", "Anonymous")
```

### Loop and filter:

```
for name, score in scores.items():
    if score >= 70:
        print(f"{name} passed!")
```

### Transform all values:

```
doubled = {k: v * 2 for k, v in prices.items()}
```

### Filter dictionary:

```
filtered = {k: v for k, v in data.items() if v > 0}
```

### Check before access:

```
if "email" in user:  
    send_email(user["email"])
```