

Week 8: Python IR Pipeline Investigation Report

Date: January 31, 2026

Investigator: AI Assistant

Status: ISSUES IDENTIFIED - FIXES IN PROGRESS

Executive Summary

The Python pipeline (`tools/spec_to_ir.py`) generates **incorrect IR format** that does not match the `stunir_ir_v1` schema used by Rust and SPARK implementations. The main issue is in the `steps` array structure within function definitions.

Investigation Findings

1. Schema Comparison

Top-Level Structure CORRECT

All three implementations (Rust, SPARK, Python) generate the correct top-level structure:

```
{
  "schema": "stunir_ir_v1",
  "ir_version": "v1",
  "module_name": "mavlink_handler",
  "docstring": "...",
  "types": [],
  "functions": [...]
```

Status: Python implementation is CORRECT at the top level.

2. Steps Format INCORRECT

Expected Format (per `stunir_ir_v1.schema.json`)

According to `/home/ubuntu/stunir_repo/schemas/stunir_ir_v1.schema.json`, steps should have:

```
{
  "op": "assign|return|call|error", // Required
  "target": "variable_name",      // Optional
  "value": "expression"           // Optional (any type)
}
```

Rust Pipeline Output CORRECT

File: `/home/ubuntu/stunir_repo/test_outputs/rust_pipeline/ir.json`

```
{
  "op": "assign",
  "target": "msg_type",
  "value": "buffer[0]"
}
```

Status: CORRECT - Matches schema exactly.

SPARK Pipeline Output ACCEPTABLE



File: /home/ubuntu/stunir_repo/test_outputs/spark_pipeline/ir.json

```
{
  "op": "noop"
}
```

Status: SIMPLIFIED but valid - Uses minimal “noop” operations. Does not fully capture statement semantics but is schema-compliant.

Python Pipeline Output INCORRECT

File: /home/ubuntu/stunir_repo/test_outputs/python_test/ir.json








```
{
  "kind": "var_decl", //  Wrong field name - should be "op"
  "data": "{ 'type': 'var_decl', 'var_name': 'msg_type', 'var_type': 'u8', 'init': 'buffer[0]'}" //  Stringified dict - should be separate fields
}
```

Issues:

1. Uses "kind" instead of "op" field
2. Uses "data" field containing a stringified Python dict
3. Does not use structured "target" and "value" fields
4. The "data" field is not part of the stunir_ir_v1 schema

3. Type Conversion Differences

Type Mapping

| Spec Type | Python Output | Rust Output | Expected |
|-----------|---|---|--|
| byte[] | bytes | byte[] | byte[]  |
| u8 | u8  | u8  | u8  |
| i32 | i32  | i32  | i32  |

Issue: Python converts byte[] to bytes, while Rust keeps it as byte[].

Root Cause Analysis

Location: `tools/spec_to_ir.py` , lines 143-158

```
# Convert body - preserve original structure with kind/data fields
steps = []
for stmt in func_spec.get("body", []):
    # If statement has 'type' field, convert to 'kind' and preserve in 'data'
    if "type" in stmt:
        step = {
            "kind": stmt.get("type", "nop"), # ✗ Should be "op"
            "data": str(stmt) # ✗ Should parse stmt into target/value
        }
    else:
        # Fallback for simpler format
        step = {"op": stmt.get("op", "nop")} # ✓ This branch is correct
        if "target" in stmt:
            step["target"] = stmt["target"]
        if "value" in stmt:
            step["value"] = stmt["value"]
    steps.append(step)
```

Root Cause:

The first branch (lines 146-150) uses the wrong field names and stringifies the entire statement instead of extracting structured fields.

Required Fixes

Fix 1: Update `convert_spec_to_ir()` Function

File: `tools/spec_to_ir.py` , lines 143-158

Current Code (WRONG):

```
if "type" in stmt:
    step = {
        "kind": stmt.get("type", "nop"),
        "data": str(stmt)
    }
```

Fixed Code:

```

if "type" in stmt:
    # Map statement type to IR op
    stmt_type = stmt.get("type", "nop")
    op_map = {
        "var_decl": "assign",
        "assign": "assign",
        "return": "return",
        "call": "call",
        "comment": "nop",
        "if": "call",
        "loop": "call"
    }

    step = {"op": op_map.get(stmt_type, "nop")}

    # Extract target from var_name or target field
    if "var_name" in stmt:
        step["target"] = stmt["var_name"]
    elif "target" in stmt:
        step["target"] = stmt["target"]

    # Extract value from init, value, or other fields
    if "init" in stmt:
        step["value"] = stmt["init"]
    elif "value" in stmt:
        step["value"] = stmt["value"]
    elif "func_name" in stmt:
        step["value"] = stmt["func_name"]

```

Fix 2: Update Type Conversion

File: tools/spec_to_ir.py, lines 65-83

Current Code:

```
"byte[]": "bytes", # ❌ Wrong
```

Fixed Code:

```
"byte[]": "byte[]", # ✅ Keep original type
```

Testing Plan

Test 1: Generate IR with Python

```

cd /home/ubuntu/stunir_repo
python3 tools/spec_to_ir.py \
  --spec-root spec/ardupilot_test \
  --out test_outputs/python_pipeline/ir.json \
  --lockfile local_toolchain.lock.json

```

Test 2: Compare Outputs

```
# Compare Python vs Rust
jq '.functions[0].steps' test_outputs/python_pipeline/ir.json
jq '.functions[0].steps' test_outputs/rust_pipeline/ir.json

# Validate against schema
ajv validate -s schemas/stunir_ir_v1.schema.json -d test_outputs/python_pipeline/ir.json
```

Test 3: Test ir_to_code

```
python3 tools/ir_to_code.py \
  --ir test_outputs/python_pipeline/ir.json \
  --out test_outputs/python_pipeline/output.c \
  --target c
```

Expected Outcomes After Fix

- ✓ Python generates "op" field instead of "kind"
- ✓ Python generates structured "target" and "value" fields
- ✓ Python output matches Rust IR structure
- ✓ Python IR validates against stunir_ir_v1.schema.json
- ✓ ir_to_code.py can parse Python-generated IR

Priority Ranking

1. **HIGH:** Fix step format (kind → op , structured fields)
2. **MEDIUM:** Fix type conversion (bytes → byte[])
3. **LOW:** Add validation against schema in Python pipeline
4. **LOW:** Add tests for Python IR generation

Next Steps

1. ✓ Document investigation findings (this file)
2. 🔧 Apply fixes to tools/spec_to_ir.py
3. ⌚ Test Python IR generation
4. ⌚ Investigate ir_to_code.py compatibility
5. ⌚ Add missing templates
6. ⌚ Complete end-to-end Python pipeline test

References

- Schema: `/home/ubuntu/stunir_repo/schemas/stunir_ir_v1.schema.json`
 - Python Tool: `/home/ubuntu/stunir_repo/tools/spec_to_ir.py`
 - Rust Output: `/home/ubuntu/stunir_repo/test_outputs/rust_pipeline/ir.json`
 - SPARK Output: `/home/ubuntu/stunir_repo/test_outputs/spark_pipeline/ir.json`
 - Python Output: `/home/ubuntu/stunir_repo/test_outputs/python_test/ir.json`
-

Report Status: Complete

Next Action: Apply fixes to Python implementation