

# STUNIR Semantic IR Validation Guide

**Version:** 1.0.0

**Status:** Implementation Complete

**Last Updated:** 2026-01-30

## Overview

This guide explains the validation framework for STUNIR Semantic IR, including schema validation, semantic checks, and multi-language validation support.

## Validation Layers

The Semantic IR validation framework operates at four levels:

### 1. Schema Validation (Structural)

Validates IR JSON against JSON Schema definitions:

```
from semantic_ir.validator import SemanticIRValidator

validator = SemanticIRValidator()
result = validator.validate_file("my_ir.json")

if result.status == ValidationStatus.VALID:
    print("✓ Schema validation passed")
else:
    print(f"✗ Validation failed: {result.message}")
```

### 2. Type Validation (Semantic)

Checks type compatibility and operator semantics:

```
from semantic_ir.validation import check_binary_op_types
from semantic_ir.nodes import PrimitiveTypeRef
from semantic_ir.ir_types import BinaryOperator, IRPrimitiveType, TypeKind

left_type = PrimitiveTypeRef(kind=TypeKind.PRIMITIVE, primitive=IRPrimitiveType.I32)
right_type = PrimitiveTypeRef(kind=TypeKind.PRIMITIVE, primitive=IRPrimitiveType.I32)

result = check_binary_op_types(BinaryOperator.ADD, left_type, right_type)
assert result.status == ValidationStatus.VALID
```

### 3. Reference Validation (Consistency)

Ensures all node references resolve correctly:

```

from semantic_ir.validation import validate_node_id

# Valid node ID
result = validate_node_id("n_func_add")
assert result.status == ValidationStatus.VALID

# Invalid node ID
result = validate_node_id("invalid_id")
assert result.status == ValidationStatus.INVALID

```

## 4. Module Validation (Complete)

Validates entire module structure:

```

from semantic_ir.modules import IRModule
from semantic_ir.validation import validate_module

module = IRModule(
    node_id="n_mod_test",
    kind=IRNodeKind.MODULE,
    name="test_module"
)

result = validate_module(module)
if result.status == ValidationStatus.VALID:
    print("✓ Module is valid")

```

## Multi-Language Validation

### Python (Pydantic)

Automatic validation on instantiation:

```

from semantic_ir.expressions import IntegerLiteral
from semantic_ir.ir_types import IRNodeKind, IRPrimitiveType
from semantic_ir.nodes import PrimitiveTypeRef, TypeKind

try:
    lit = IntegerLiteral(
        node_id="n_lit_42",
        kind=IRNodeKind.INTEGER_LITERAL,
        type=PrimitiveTypeRef(
            kind=TypeKind.PRIMITIVE,
            primitive=IRPrimitiveType.I32
        ),
        value=42
    )
    print("✓ Node created and validated")
except ValidationError as e:
    print(f"✗ Validation failed: {e}")

```

### Rust (Compile-Time)

Type safety enforced at compile time:

```

use stunir_semantic_ir::*;

// Compile-time type checking
let lit = IntegerLiteral {
  base: ExpressionNode {
    base: IRNodeBase::new(
      "n_lit_42".to_string(),
      IRNodeKind::IntegerLiteral
    ),
    expr_type: TypeReference::PrimitiveType {
      primitive: IRPrimitiveType::I32,
    },
  },
  value: 42,
  radix: 10,
};

// Type errors caught at compile time
// let invalid = IntegerLiteral {
//   value: "not a number", // Compile error!
// };

```

## Ada SPARK (Formal Verification)

Formal contracts with proof:

```

with Semantic_IR.Validation;

procedure Validate_Node is
  Node_ID : constant Node_ID := To_Bounded_String ("n_test_123");
  Result : Validation_Result;
begin
  Result := Validate_Node_ID (Node_ID);

  if Result.Status = Valid then
    Put_Line ("✓ Node ID valid");
  else
    Put_Line ("✗ " & To_String (Result.Message));
  end if;
end Validate_Node;

```

## Haskell (Type-Level)

Type-safe validation:

```

import STUNIR.SemanticIR.Validation

validateIR :: NodeID -> IO ()
validateIR nodeId = do
  let result = validateNodeID nodeId
  case valStatus result of
    Valid -> putStrLn "✓ Valid"
    Invalid -> putStrLn $ "✗ " ++ T.unpack (valMessage result)

```

## Validation Rules

### Node ID Rules

1. **Format:** Must match `^n_[a-zA-Z0-9_]+$`
2. **Uniqueness:** Each node ID must be unique within a module
3. **Reference:** All node ID references must resolve

```
# Valid
validate_node_id("n_func_add")      # ✓
validate_node_id("n_lit_42")        # ✓
validate_node_id("n_type_Point3D")  # ✓

# Invalid
validate_node_id("func_add")         # x Missing 'n_' prefix
validate_node_id("n_")               # x Too short
validate_node_id("n-func-add")       # x Invalid character '-'
```

### Hash Rules

1. **Format:** Must match `^sha256:[a-f0-9]{64}$`
2. **Computation:** Deterministic from node content
3. **Consistency:** Same content → same hash

```
# Valid
validate_hash("sha256:" + "a" * 64) # ✓

# Invalid
validate_hash("sha256:abc")          # x Too short
validate_hash("md5:" + "a" * 32)     # x Wrong algorithm
validate_hash("invalid")              # x Wrong format
```

### Type Compatibility Rules

#### Arithmetic Operators (+, -, \*, /, %)

- Require numeric types (i8..i64, u8..u64, f32, f64)
- Both operands must be numeric

```
check_binary_op_types(Op.ADD, i32, i32) # ✓
check_binary_op_types(Op.MUL, f32, f32) # ✓
check_binary_op_types(Op.ADD, i32, bool) # x bool not numeric
```

#### Comparison Operators (==, !=, <, <=, >, >=)

- Require compatible types
- Types must match exactly

```
check_binary_op_types(Op.EQ, i32, i32) # ✓
check_binary_op_types(Op.LT, f64, f64) # ✓
check_binary_op_types(Op.EQ, i32, f32) # x Type mismatch
```

#### Logical Operators (&&, ||)

- Require boolean operands

- Both must be bool

```
check_binary_op_types(Op.AND, bool, bool) # ✓
check_binary_op_types(Op.OR, i32, i32)    # ✗ i32 not bool
```

## Bitwise Operators (&, |, ^, <<, >>)

- Require integer types
- Both operands must be integers

```
check_binary_op_types(Op.BIT_AND, i32, i32) # ✓
check_binary_op_types(Op.SHL, u64, u64)    # ✓
check_binary_op_types(Op.BIT_OR, f32, f32)  # ✗ f32 not integer
```

## Validation Workflow

### Step 1: Load and Parse

```
import json
from pathlib import Path

# Load IR file
ir_path = Path("my_module.json")
with open(ir_path, 'r') as f:
    ir_json = json.load(f)
```

### Step 2: Schema Validation

```
from semantic_ir.validator import SemanticIRValidator

validator = SemanticIRValidator()
result = validator.validate_json(ir_json)

if result.status != ValidationStatus.VALID:
    print(f"Schema errors: {result.message}")
    exit(1)
```

### Step 3: Pydantic Validation

```
from semantic_ir.modules import IRModule

try:
    module = IRModule(**ir_json["root"])
except ValidationError as e:
    print(f"Pydantic validation failed: {e}")
    exit(1)
```

## Step 4: Semantic Validation

```
from semantic_ir.validation import validate_module

result = validate_module(module)
if result.status != ValidationStatus.VALID:
    print(f"Semantic validation failed: {result.message}")
    exit(1)
```

## Step 5: Generate Report

```
report = validator.generate_report()
print(report)
```

## CI/CD Integration

### GitHub Actions

See `.github/workflows/semantic_ir_validation.yml`:

```
- name: Validate IR files
  run: |
    for file in examples/semantic_ir/*.json; do
      python tools/semantic_ir/validator.py "$file" || exit 1
    done
```

### Pre-commit Hook

```
#!/bin/bash
# .git/hooks/pre-commit

for file in $(git diff --cached --name-only | grep '\.json$'); do
    if [[ $file == examples/semantic_ir/* ]]; then
        python tools/semantic_ir/validator.py "$file"
        if [ $? -ne 0 ]; then
            echo "Validation failed for $file"
            exit 1
        fi
    fi
done
```

# Testing Validation

## Unit Tests

```
import pytest
from semantic_ir.validation import validate_node_id, ValidationStatus

def test_valid_node_id():
    result = validate_node_id("n_test_123")
    assert result.status == ValidationStatus.VALID

def test_invalid_node_id():
    result = validate_node_id("invalid")
    assert result.status == ValidationStatus.INVALID
    assert "must start with 'n_'" in result.message
```

## Integration Tests

```
def test_round_trip_validation():
    # Create module
    module = IRModule(
        node_id="n_mod_test",
        kind=IRNodeKind.MODULE,
        name="test"
    )

    # Serialize
    json_str = module.model_dump_json()

    # Deserialize
    json_dict = json.loads(json_str)
    reconstructed = IRModule(**json_dict)

    # Validate
    result = validate_module(reconstructed)
    assert result.status == ValidationStatus.VALID
```

## Common Validation Errors

### Error: “Invalid node ID”

**Cause:** Node ID doesn’t match required pattern

**Solution:**

```
# Wrong
node_id = "func_add"

# Correct
node_id = "n_func_add"
```

### Error: “Type mismatch in binary operation”

**Cause:** Operand types incompatible with operator

**Solution:**

```
# Wrong: bool + bool
BinaryExpr(op=Op.ADD, left=bool_var, right=bool_var)

# Correct: i32 + i32
BinaryExpr(op=Op.ADD, left=int_var, right=int_var)
```

## Error: “Unresolved reference”

**Cause:** Node ID reference doesn’t exist

**Solution:**

```
# Ensure referenced nodes exist
statements = [
    VarDeclStmt(node_id="n_var_x", name="x", ...),
    AssignStmt(target="n_var_x", ...) # Valid: n_var_x exists
]
```

## Validation Best Practices

---

1. **Validate Early:** Check IR immediately after generation
2. **Validate Often:** Re-validate after each transformation
3. **Use Type System:** Leverage language type systems (Rust, SPARK)
4. **Write Tests:** Create comprehensive validation tests
5. **Check Examples:** Validate all example files in CI/CD
6. **Document Errors:** Provide clear error messages

## See Also

---

- [Schema Guide](#) (SEMANTIC\_IR\_SCHEMA\_GUIDE.md)
- [Examples](#) (../examples/semantic\_ir/README.md)
- [Specification](#) (SEMANTIC\_IR\_SPECIFICATION.md)