

House Stats API (0.1)

Download OpenAPI specification: [Download](#)

Authentication

Login and registration endpoints

Register a new user

Creates a new user account with email and password authentication and initialises billing.

REQUEST BODY SCHEMA: `application/json`
required

<code>email</code> required	string (Email)
<code>password</code> required	string (Password)
<code>first_name</code> required	string (First Name)
<code>last_name</code> required	string (Last Name)

Responses

> **200** Successful Response

— **400** A user has already been created with that email

> **422** Validation Error

POST /auth/register

Request samples

Payload

Content type

application/json

Copy

```
{
  "email": "string",
  "password": "string",
  "first_name": "string",
  "last_name": "string"
}
```

Response samples

200

400

422

Content type

application/json

Copy

```
{
  "msg": "Successfully created user, please login to continue"
}
```

User login

Authenticates a user using email and password and returns a JWT access token while setting a refresh token cookie.

REQUEST BODY SCHEMA: application/json
required

email	string (Email)
required	

password
required

string (Password)

Responses

> **200** Successful Response

— **400** Incorrect email or password provided

> **422** Validation Error

POST /auth/login

Request samples

Payload

Content type

application/json

Copy

```
{
  "email": "string",
  "password": "string"
}
```

Response samples

200

400

422

Content type

application/json

Copy

```
{
  "access_token": "string"
}
```

Refresh access token

Uses the refresh token cookie to generate a new JWT access token.

COOKIE PARAMETERS

refresh_token	string (Refresh Token)
---------------	------------------------

Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/refresh

Response samples

200

422

Content type

application/json

Copy

```
{  
  "access_token": "string"  
}
```

Logout user

Revokes the refresh token associated with the current session and logs the user out.

COOKIE PARAMETERS

refresh_token

string (Refresh Token)

Responses

- > 200 Successful Response
- > 422 Validation Error

POST /auth/logout

Response samples

200

422

Content type
application/json

null

Copy

Create API token

Generates a new API token for the authenticated user for programmatic access (e.g., MCP integrations).

AUTHORIZATIONS: > HTTPBearer

REQUEST BODY SCHEMA: application/json
required

name
required

string (Name)

expiry
required

integer (Expiry)

Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/token/create

Request samples

Payload

Content type
application/json

Copy

```
{
  "name": "string",
  "expiry": 0
}
```

Response samples

200

422

Content type
application/json

Copy

```
{
  "token": "string",
  "expiry": "string"
}
```

Revoke API token

Revokes an API token belonging to the authenticated user so it can no longer be used for authentication.

AUTHORIZATIONS: > HTTPBearer

REQUEST BODY SCHEMA: application/json
required

token_id required	string (Token Id)
----------------------	-------------------

Responses

- > 200 Successful Response
- > 422 Validation Error

POST /auth/token/delete

Request samples

Payload

Content type
application/json

Copy

```
{
  "token_id": "string"
}
```

Response samples

200

422

Content type
application/json

Copy

```
{
  "msg": "Successfully revoked token"
}
```

List Api Tokens

AUTHORIZATIONS: > HTTPBearer

Responses

> 200 Successful Response

GET /auth/token/list

Response samples

200

Content type
application/json

null

Copy

Users

User management operations

Miscellaneous

Miscellaneous endpoints

Health

Responses

> 200 Successful Response

GET /health/

Response samples

200

Content type

application/json

Copy

```
{
  "status": "ok"
}
```

Billing

Get API usage for a user

Returns usage records for the authenticated user between the provided start and end timestamps.

AUTHORIZATIONS: > *HTTPBearer*

QUERY PARAMETERS

start required	string <date-time> (Start) Start datetime for the usage window
end required	string <date-time> (End) End datetime for the usage window

Responses

> **200** Successful Response

> **422** Validation Error

GET /billing/api-usage

Response samples

200

422

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "api_route": "string",
    "tokens": 0,
    "timestamp": "string"
  }
]
```

Get billing history

Returns the user's billing ledger entries showing past billing periods and token usage.

AUTHORIZATIONS: > *HTTPBearer*

QUERY PARAMETERS

limit	integer (Limit) Default: 12 Maximum number of billing periods to return
-------	--

Responses

- > 200 Successful Response
- > 422 Validation Error

GET /billing/billing/history

Response samples

200

422

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": "string",
    "total_tokens": 0,
    "period_start": "string",
    "period_end": "string",
    "timestamp": "string",
    "stripe_event_id": "string"
  }
]
```

Get current billing period summary

Returns usage summary for the current billing period (last 28 days).

AUTHORIZATIONS: >

HTTPBearer

Responses

> 200 Successful Response

GET /billing/billing/current-period

Response samples

200

Content type
application/json

Copy

```
{
  "current_period_tokens": 0,
  "period_start": "string",
  "period_end": "string",
  "estimated_cost": 0
}
```

Get usage summary

Returns aggregated usage statistics for the specified period.

AUTHORIZATIONS: >

HTTPBearer

QUERY PARAMETERS

days	integer (Days) Default: 30 Number of days to analyze
------	--

Responses

> 200 Successful Response

> 422 Validation Error

GET /billing/billing/usage/summary

Response samples

200

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "total_tokens": 0,
  "total_requests": 0,
  "average_tokens_per_request": 0,
  - "top_routes": [
    { }
  ],
  "period_days": 0
}
```

Get usage trends

Returns daily usage trends over the specified date range.

AUTHORIZATIONS: > HTTPBearer

QUERY PARAMETERS

start required	string <date-time> (Start) Start date for trends
-------------------	---

end
required

string <date-time> (End)
End date for trends

Responses

> 200 Successful Response

> 422 Validation Error

GET /billing/billing/usage/trends

Response samples

200

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "trends": [
    + { ... }
  ]
}
```

Statistics

List supported sales statistics

AUTHORIZATIONS: > HTTPBearer

Responses

> 200 Successful Response

GET /stats/sales

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  - "supported_stats": [
    "string"
  ]
}
```

Queue sales statistics task

AUTHORIZATIONS: > HTTPBearer

REQUEST BODY SCHEMA: application/json
required

stats required	Array of strings (Stats)
area required	string (Area)
area_type required	string (Area Type)
start_date >	Start Date (string) or Start Date (null) (Start Date)
end_date >	End Date (string) or End Date (null) (End Date)

Responses

> **202** Successful Response

> **422** Validation Error

POST /stats/sales/tasks

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "stats": [
    "string"
  ],
  "area": "string",
  "area_type": "string",
  "start_date": "2019-08-24",
  "end_date": "2019-08-24"
}
```

Response samples

202

422

Content type

application/json

Copy

```
{
  "task_id": "string",
  "status": "PENDING"
}
```


Get sales statistics task result

AUTHORIZATIONS: > HTTPBearer

PATH PARAMETERS

task_id
required

string <uuid> (Task Id)

Responses

> 200 Successful Response

> 422 Validation Error

GET /stats/sales/tasks/{task_id}

Response samples

200

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "task_id": "736fde4d-9029-4915-8189-01353d6982cb",
  "status": "string",
  "result": { },
  "error": "string"
}
```