

## Regis University – Physics 305A – Fall 2019

### Lab 2: Understanding Vectors

Note: Today's lab is abnormally short because one section will have less time than usual due to the Mass of the Holy Spirit.

Our goal for today is to become very comfortable interpreting and manipulating vectors, both mathematically and graphically. You'll make measurements with some large-scale table-sized graph paper in this lab. It is laminated, so you can draw on it with dry-erase markers as needed.

Like our first lab, this lab does not really have any "data" to collect and interpret. However, I do ask that you submit a lab report for this lab. Try to think of this (somewhat unconventional) report as a summary of techniques for yourself; illustrate how you solved each problem with words, sketches, and/or math. You may do so in whatever format is convenient, but be clear enough that future-you and present-me can fully understand

1. First, please choose an origin for the coordinate system, and draw a set of  $x$  and  $y$  coordinate axes on it with a dry-erase marker. For today, all of our vectors will have a  $z$  component equal to 0.
2. Throw a bolt (object 1) at one quadrant of your coordinate system and a nut (object 2) at a different quadrant. For simplicity, move them to the closest grid points to where they land on the paper.
3. Draw a **vector** (an arrow) from the origin to object 1. Label it as  $\vec{r}_1$ . Notice that this symbol has an arrow drawn over it, which is your indication that it is a vector.
4. Draw a vector from the origin to object 2 and label it as  $\vec{r}_2$ .
5. Measure the  $x$  and  $y$  **components** of the vectors  $\vec{r}_1$  and  $\vec{r}_2$  by counting squares from the tail of the arrow to the tip. If you put the objects in two different quadrants of the coordinate system, at least one of these components must be negative, and at least one must be positive. Please remember to record the units with the values that you measure. When you record the values of these components, you can give them the names  $r_{1x}$ ,  $r_{1y}$ ,  $r_{2x}$ , and  $r_{2y}$ . Notice that the names of the components do *not* have arrows drawn over them; they are just numbers.
6. Use a ruler to measure the graph paper to determine the conversion factor between units of "squares" and units of "cm."
7. Convert the values you measured for  $r_{1x}$ ,  $r_{1y}$ ,  $r_{2x}$ , and  $r_{2y}$  into units of cm.
8. Now, write  $\vec{r}_1$  and  $\vec{r}_2$  as three-component vectors. (For example, if you measured  $r_{1x} = 1$  square,  $r_{1y} = 2$  squares, and a conversion factor of 3.2 cm/square, you might write " $\vec{r}_1 = [3.2, 6.4, 0]$  cm.")
9. Calculate the difference  $\Delta\vec{r} = \vec{r}_2 - \vec{r}_1$  by subtracting one component at a time. (For example,  $[9.6, 3.2, 0]$  cm  $- [3.2, 6.4, 0]$  cm  $= [6.4, -3.2, 0]$  cm.)
10. Find a place to draw  $\Delta\vec{r}$  on your coordinate system in a way that forms a closed triangle with  $\vec{r}_1$  and  $\vec{r}_2$ . It does *not* need to have one end at the origin of the coordinate system. Carefully describe the physical meaning of  $\Delta\vec{r}$  in terms of the bolt and the nut (objects 1 and 2).
11. The **magnitude** of  $\vec{r}_1$  is defined by  $r_1 = |\vec{r}_1| = \sqrt{r_{1x}^2 + r_{1y}^2 + r_{1z}^2}$ . Notice that you can indicate the operation of computing the magnitude just by dropping the arrow from above the name of the vector; that's one reason to be very careful to draw the arrow there when it is needed, and only when it is needed. Calculate the magnitudes  $r_1 = |\vec{r}_1|$ ,  $r_2 = |\vec{r}_2|$ , and  $|\Delta\vec{r}|$ .

12. Use a ruler (or meter stick) to measure the lengths of the three arrows on your graph paper. How well do these distances agree with the magnitudes that you calculated? (They should agree pretty well.)
13. Draw a vertical line from the tip of  $\vec{r}_1$  to the  $x$  axis, and draw a horizontal line from the tip of  $\vec{r}_1$  to the  $y$  axis. You should be able to find a right triangle that will let you use trigonometry that you know (think “SOH-CAH-TOA”) to calculate the angle that  $\vec{r}_1$  makes with the  $x$  axis, and another right triangle to find the angle that it makes with the  $y$  axis. Do this for both  $\vec{r}_1$  and  $\vec{r}_2$ .
14. Use a protractor to measure the angles that  $\vec{r}_1$  and  $\vec{r}_2$  make with the  $x$  and  $y$  axes. How well do these angles agree with your calculations? (They should agree pretty well.)
15. Apply the same calculation technique to find the angle that  $\Delta\vec{r}$  makes with the  $x$  and  $y$  coordinate axes. Then, to measure the angles with the protractor, you can think of “sliding” a copy of  $\Delta\vec{r}$  so that its tail is at the origin, or you can think of “sliding” the coordinate axes over so that the origin is at the tail of  $\Delta\vec{r}$ . Again, how well do your calculated and measured angles agree?
16. Leaving the bolt and the nut where they are, erase all of the marks that you have drawn on the paper. Draw a new set of coordinate axes that are offset by a few squares in each direction from where they used to be. As you did before, find the vectors  $\vec{r}_1$  and  $\vec{r}_2$  in this new coordinate system; they should have different values than they did before.
17. Now, subtract to find  $\Delta\vec{r}$  using the values you measured in the new coordinate system. Can you explain how your result supports the general rule that well-defined vectors are independent of the choice of the origin of the coordinate system? This is the idea that allows you to draw vectors with their tails at any point, not only at the origin.