

Fleet Branch and Supplier Directory APIs

Guide version: 1.0 · **API schema versions:** 1.0 · **Last updated:** 27 September 2026

Owner: KPFC Admin operations team · **Tracking:** KB-325

These read-only APIs let KPFC Fleet retrieve authoritative branch and supplier directories. They never expose database names, Google Sheet IDs, contacts, payment details, notes, pricing, sync metadata, credentials, or tokens.

1. Environments and endpoints

Environment	OAuth token URL	Branch directory	Supplier directory
Staging	https://admin-staging.kpfcbuilders.com/oauth/token	https://admin-staging.kpfcbuilders.com/api/v1/fleet/shops	https://admin-staging.kpfcbuilders.com/api/v1/fleet/suppliers
Production	https://admin.kpfcbuilders.com/oauth/token	https://admin.kpfcbuilders.com/api/v1/fleet/shops	https://admin.kpfcbuilders.com/api/v1/fleet/suppliers

Staging and production use different credentials. Production access is not ready until the production rollout prerequisites in section 11 are complete.

2. Authentication

Use OAuth 2.0 client credentials from Fleet's server. Never request tokens from browser JavaScript or a mobile client. Each directory has an independently rotatable client and scope:

Directory	Required scope	Credential
Branches	fleet:branches	Branch-directory client ID and secret
Suppliers	fleet:suppliers	Supplier-directory client ID and secret

Request a branch token

```
curl --fail-with-body --request POST \  
  --url https://admin-staging.kpfcbuilder.com/oauth/token \  
  --user '<branch-client-id>:<branch-client-secret>' \  
  --header 'Accept: application/json' \  
  --data 'grant_type=client_credentials' \  
  --data 'scope=fleet:branches'
```

Request a supplier token

```
curl --fail-with-body --request POST \  
  --url https://admin-staging.kpfcbuilder.com/oauth/token \  
  --user '<supplier-client-id>:<supplier-client-secret>' \  
  --header 'Accept: application/json' \  
  --data 'grant_type=client_credentials' \  
  --data 'scope=fleet:suppliers'
```

Successful token response

```
{  
  "token_type": "Bearer",  
  "expires_in": 900,  
  "access_token": "<short-lived-access-token>"  
}
```

Cache each token server-side until shortly before `expires_in`. Request a fresh token after expiry. Do not log or persist access tokens in application records.

3. Call the directories

Branches

```
curl --fail-with-body \  
  --url https://admin-staging.kpfcbuilder.com/api/v1/fleet/shops \  
  --header 'Accept: application/json' \  
  --header 'Authorization: Bearer <branch-access-token>'
```

Suppliers

```
curl --fail-with-body \  
  --url https://admin-staging.kpfcbuilder.com/api/v1/fleet/suppliers \  
  --header 'Accept: application/json' \  
  --header 'Authorization: Bearer <supplier-access-token>'
```

Both endpoints return active records by default. Append `?include_inactive=true` only when Fleet needs the historical directory. Accepted values are `true`, `false`, `1`, and `0`.

4. Branch response schema v1.0

```
{
  "data": [
    {
      "id": 12,
      "name": "example-shop",
      "display_name": "Example Shop",
      "is_active": true,
      "latitude": -1.286389,
      "longitude": 36.817223,
      "updated_at": "2026-09-26T12:00:00.000000Z"
    }
  ],
  "meta": {
    "schema_version": "1.0",
    "generated_at": "2026-09-26T12:05:00.000000Z",
    "count": 1,
    "include_inactive": false
  }
}
```

Field	Type	Meaning
id	integer	Stable KPFC Admin shop identifier.
name	string	Machine-oriented shop name.
display_name	string	Human-readable branch name.
is_active	boolean	Whether the branch is active in Admin.
latitude, longitude	number or null	Optional WGS84 coordinates. Both are populated or both are null.
updated_at	ISO 8601 string	Last central shop-record update.

Results are unpaginated and ordered by Admin shop sort order, then name, then id.

5. Supplier response schema v1.0

```
{
  "data": [
    {
      "id": 42,
      "name": "Example Supplier",
      "is_active": true,
      "latitude": -1.292066,
      "longitude": 36.821946,
      "updated_at": "2026-09-26T12:00:00.000000Z"
    }
  ],
  "meta": {
    "schema_version": "1.0",
    "generated_at": "2026-09-26T12:05:00.000000Z",
    "count": 1,
    "include_inactive": false
  }
}
```

Field	Type	Meaning
id	integer	Stable KPFC Admin supplier identifier.
name	string	Supplier's business name.
is_active	boolean	Whether the supplier is active in Admin.
latitude, longitude	number or null	Optional WGS84 coordinates. Both are populated or both are null.
updated_at	ISO 8601 string	Last central supplier-record update.

Results are unpaginated and ordered by name, then id.

6. Errors and limits

Status	Error	Action
400	https_required	Use HTTPS. Plain HTTP is accepted only for direct loopback traffic.
401	invalid_token	Obtain a new token and confirm the correct Authorization header.
403	insufficient_access	Use the client and scope assigned to that directory.
422	validation error	Use a documented <code>include_inactive</code> value.
429	too many requests	Back off and retry. Do not request a token for every directory call.
500	directory_data_invalid	Supplier coordinates failed server validation. Escalate to KPFC Admin operations.
503	service_unavailable	The directory client is not configured in that environment. Escalate to KPFC Admin operations.

Limits: 30 authentication attempts per minute per source IP and 60 authenticated directory requests per minute per service client. Successful reads and denied access are audited.

7. Integration behavior

- Treat `id` as the stable external key. Names may change.
- Accept `null` coordinates. Location capture is optional in Admin.
- Replace the local directory from each successful full response; responses are complete and unpaginated.
- Do not delete local historical references solely because a record is absent from the active-only response. Use `include_inactive=true` for reconciliation.
- Do not call either API from a browser, mobile app, or other untrusted client.
- Use exponential backoff for 429 and temporary 5xx responses.

8. Credential delivery and storage

1. KPFC Admin operations creates separate credentials per directory and environment.
2. The secret is delivered once through the approved password manager or protected file transfer—not chat or source control.
3. Fleet stores the client ID and secret in its server-side secret manager or environment configuration.
4. Fleet restricts access to the application runtime and authorized operators.
5. Fleet must never print credentials or access tokens in logs, errors, screenshots, or telemetry.

9. Zero-downtime credential rotation

1. KPFC Admin operations creates a replacement client for the affected directory.
2. Admin temporarily permits both old and new client IDs.
3. The replacement ID and secret are delivered securely to Fleet.
4. Fleet obtains a token with the required scope and verifies the relevant staging or production endpoint.
5. Fleet switches its deployed secret and confirms normal synchronization.
6. Admin removes and revokes the old client. Existing tokens from that client stop working.

10. Onboarding and verification checklist

1. Receive the staging credentials for each required directory through the approved secure channel.
2. Request a token with the exact matching scope.
3. Call the active-only endpoint and confirm `meta.schema_version` is `1.0`.
4. Confirm every object has exactly the documented fields.
5. Confirm populated coordinates are paired and within valid latitude/longitude ranges.
6. Call with `include_inactive=true` and confirm Fleet handles inactive records.
7. Confirm expired tokens are refreshed and secrets never appear in logs.
8. Send staging consumption evidence to KPFC Admin operations against KB-325.

11. Production rollout prerequisites

- KB-324 and KB-327 are validated in staging.
- Gatonye confirms both staging contracts are consumable.
- The code is promoted through the Jenkins production pipeline.
- Separate production client-credentials clients are created and allowlisted.
- Production credentials are delivered securely and stored server-side in Fleet.
- Live production token, active-only, inactive-inclusive, cross-scope rejection, and safe-field checks pass.

12. Troubleshooting and escalation

- Confirm the environment, client ID, secret, and requested scope belong together.
- Confirm Fleet's clock is synchronized and the token has not expired.
- Confirm requests use HTTPS and the exact documented URL.
- For 403, do not broaden scopes; verify the directory-specific credential.
- For persistent 429, cache tokens and reduce polling frequency.
- For 500 or 503, contact KPFC Admin operations and include the environment, endpoint, UTC timestamp, HTTP status, and response error code. Never include secrets or tokens.

Change history

Date	Guide version	Change
27 September 2026	1.0	Initial combined branch and supplier directory integration guide.