

SLURREX MA

An oxidizing emulsion in bulk manufactured for mechanized charging by pumping. Used mainly for open pit mining, for very large diameter boreholes. Non-explosive until it is sensitized at the site, resulting in a powerful blasting agent.

Recommendations for use:

- This emulsion is not sensitive to booster.
- Must be used with ANFO to form heavy blends in the required proportion.
- Boreholes with water must contain heavy ANFO always, at rates equal to or higher than 60% of this emulsion.

Technical Characteristics

Technical Specifications	Units	Slurrex MA
Density	g/cm ³	1.31 ± 3%
Detonation velocity	m/s	Not applicable
RBS**	% kcal/lt	120
Water resistance	hour	72

** Calculated with TERMODET simulation program.

Presentation and Packaging

Matrix emulsion is carried in 24-30 ton bulk tank trucks especially fitted for ground transportation. Stored in 30-90 ton silos.

Ask Exsa for other presentation formats.

Storage and Warranty

Kept in its original packaging and stored under normal temperature and moisture conditions, in accordance with applicable laws and provisions, the product is warranted for 6 months from the manufacturing date.

Transportation

CLASS: 5.1 UN 3375



DISCLAIMER OF LIABILITY

These explosives have been inspected and found to be in good condition prior to packaging and/or delivery thereof. These explosives must be stored in a cool, dry and well-ventilated place, and be handled and transported in accordance with applicable laws. Accordingly, as from being delivered to the purchasers, the manufacturer shall not be liable for the safety of these explosives or for obtaining any results sought, whether express or implied. As from the delivery of these explosives, the purchasers thereof shall be liable for any and all risks and liability, regardless of their nature, for any accidents, losses, property or personal damages (including death), whether direct, indirect, special and/or consequential or of any other nature arising from the use of these explosives.

