

VIMPERATOR QUICK REFERENCE CARD

Frequently used Vimpr commands – Version v1.2 August 2014

A short introduction into vimperator may be found at: www.linuxjournal.com/article/10636

Page & Tab Movements

Page Movements

move commands work as you would expect them to do from VIM. See `:h motion` for detailed documentation.

`h j k l` move left, down, up, right
`g g` `G` move to top, bottom of page
`^ f ^ d ^ e` move screen, page, line down
`^ b ^ u ^ y` move screen, page, line up
`/ ?` search in page, backwards
`n N` jump to next, previous search result

Tab & Buffer Movements

`bn` switch to open buffer *n* from list
`g t` *or* `^ n` go to next tab
`g T` *or* `^ p` go to previous tab
`g 0` `g $` `g @` go to first, last, first app tab
`g h` `g H` open own defined homepage, new tab
`g u` `g U` move up one path, all to root
⇒ `g u http://www.vimperator.org/system/app/:`
moves up to `http.or.org/system`
`go[aA-zZ0-9]` jump to previously marked web page

Basic Commands

General Keybinds

refer to `:h :open`

`d u` close current, undo last tab
`w W` open new window with empty, current url
`t T` id. but new tab

`o O` id. but in current tab
`y Y` copy url, selected text to clipboard
`p P` paste from clipboard in current, new tab
`H L` go to previous, next page in history
`m M` set local, global mark at cursor, url
`a A` add, toggle bookmark
`i I` ignore any, specific vimpr keybind
`[[]]` switch to previous, next page on multipage websites
`+ -` zoom in, out by 25 % on page in focus
`n z z` zoom page to *n*% (100 if *n* is omitted)
`ZZ ZQ` exit browser, clear history before

Command Line

Basic Exe commands

works with tab completion

`:addons` show addons in current window
`:bmark` `:delbmarks url`
add, delete bookmark
`:emenu` `<tab>`. command-line access to Firefox menubar
`:history` pull up recent 10 online & local pages
`:pclose` close preview window, eg. history
`:preferences` show preferences
`:restart` restart Firefox immediately
`:tabonly` close all other tabs
`:saveas` save current web page to disk.

Command Settings

invoke with `:set`, to disable: prepend *no* to command

`apptab` set current tab as app window
`defsearch` ... set default search engine (*g* → google)

Modes

Panorama Mode (Tab Group Management)

start tabgroup management with `:tabgroup <subcom>`

Most important subcommands ..

<code>add</code>	create new tab group
<code>list</code>	list current tab groups
<code>rm</code>	remove group with groupname
<code>pull- or pushtab</code>	pull tab from <i>or</i> move to group
<code>switch</code>	switch to groupname
<code>stash</code>	move current tab to groupname

QuickHint Mode (*f*)

Hints are the way in which Vimperator allows you to follow links on a page. By providing each link with a suitable hint, you can access them via a set of hotkeys. Pressing *f* once triggers *QuickHint Mode* and simulates a mouseselection with labeled marks on a web page.

ExtendedHint Mode (;)

This mode is useful for performing operations on hinted elements other than the default left mouse click. If you want to yank the location of hint 24, press ;y to start this hint mode. Then press 24 to copy the hint location.

ExtendedHint Commands

list all extended mode commands `:h extended-hints`

here are a few ..

; `c` imitates mouse hovering, right click (⇒ contextual menu) on a link object
`s S` download link, object
`i I` open media object (in new tab)
`y Y` copy URL, label description to clipboard

Plugins

<https://github.com/vimpr/vimperator-plugins/tree/3.6>

github.com/emzap79/QRCs

emzap79@gmail.com

This TeXfile is based on Gabriel B. Burcas © git-qrc.tex and has then been modified to my own requirements, with permission!