

## GIT QUICK REFERENCE CARD

Most frequently used GIT commands – Version v1.1 May 2014

### Main commands

<b>add</b> ..... Add file contents to the index	<b>-A</b> [:/] adds all file changes including deletions to the staging area [for the whole tree]	<b>-f</b> allow adding otherwise ignored files	<b>-p</b> choose hunks of patch between the index and the work tree and add them to the index
<b>am</b> ..... Apply a series of patches from a mailbox			
<b>archive</b> ..... Create an archive of files from a named tree			
<b>bisect</b> ..... Find by binary search the change that introduced a bug			
⇒ <b>search for existence of file in last commits:</b>	<b>bisect run test -f file.txt</b>		
<b>branch</b> ..... List, create, or delete branches	<b>-a</b> lists all branches including the remote branches	<b>-d</b> delete ... <b>branch</b>	<b>-m</b> rename branch: ... <b>old_name new_name</b>
	<b>-v</b> lists more information about the branches		
<b>bundle</b> ..... Move objects and refs by archive			
<b>checkout</b> ..... checkout a branch or paths to the working tree (prepend -- before path to avoid ambiguity).	<b>-b</b> create a branch <b>new_name</b> and switch to it instantly		
⇒ <b>restore working tree and reset index:</b>	<b>checkout HEAD - - dir</b>		
<b>cherry-pick</b> . can be used to change order of commits			
<b>citool</b> ..... Graphical alternative tocommit			
<b>clean</b> ..... Remove untracked files from the working tree	<b>-f</b> force (required!)	<b>-x</b> include hidden files	
			<b>-d</b> directories as well
<b>clone</b> ..... Clone a repository into a new directory			
<b>commit</b> ..... Record changes to the repository	<b>-a</b> adding changes of files known by the Git repository to the commit	<b>-m</b> Set comment for commitment – correct it with prepending <b>--amend</b> to argument	
<b>describe</b> ..... Show the most recent tag that is reachable from a commit			
<b>diff</b> ..... Show changes between commits, commit and working tree, etc.	<b>--cached</b> compare stage area with last commit		
<b>fetch</b> ..... Download objects and refs from another repository			
<b>format-patch</b> Prepare patches for e-mail submission			
<b>gc</b> ..... Cleanup unnecessary files and optimize the local repository			
<b>grep</b> ..... Print lines matching a pattern			
<b>gui</b> ..... A portable graphical interface to Git			
<b>init</b> ..... Create an empty git repository or reinitialize an existing one			
<b>log</b> ..... Show commit logs (prepend -- before path to avoid ambiguity)	<b>-p</b> show diffs of each commit	<b>--stat</b> precise output with some stats	<b>--abbrev-commit</b> shorten (but unique) SHA-1 values for the commit objects
		<b>--oneline</b> show logs as shortened oneliner	<b>--reverse</b> reverse log-history output
		<b>--follow</b> entire history including renames	<b>--graph</b> show visual timeline
⇒ <b>show all files that ever existed in HEAD:</b>	<b>git log --pretty=format: --name-status   cut -f2-   sort -u</b>		
<b>merge</b> ..... Join two or more development histories together			
			<b>-s</b> specify your merge strategy (see <b>man git-merge</b> )
			<b>-X</b> apply option to strategy (eg. <i>ours</i> , <i>theirs</i> )
	<b>--ff</b> only update the branch pointer, without creating a merge commit (default)		
<b>mv</b> ..... Move or rename a file, a directory, or a symlink			
<b>notes</b> ..... Add/inspect commit notes			
<b>pull</b> ..... Fetch from and merge with another repository or a local branch			
<b>push</b> ..... Update remote refs along with associated objects	⇒ <b>delete branch in remote repo called origin:</b>	<b>push origin :testbranch</b>	
<b>rebase</b> ..... Forward-port local commits to the updated upstream head	<b>-i</b> rebase interactively		
	<b>--autosquash</b>	When the commit log message begins with "squash! ..." (or "fixup! ..."), automatically modify the todo list of <b>rebase -i</b>	
	<b>reset</b> ..... Reset current HEAD to the specified state (Remove a <i>file</i> from staging area)	<b>--soft</b> move HEAD pointer only	<b>--mixed</b> resets staging area to new HEAD (default!)
		<b>--hard</b> resets staging area and working tree to new HEAD	
	<b>revert</b> ..... Revert an existing commit		
	<b>rm</b> ..... Remove files from the working tree and from the index	<b>-r</b> remove recursive – for removing additionally from repo, add <b>--cached *</b>	
	<b>shortlog</b> ..... Summarize git log output		
	<b>show</b> ..... Show various types of objects		
	<b>stash</b> ..... Stash the changes in a dirty working directory away		
	<b>status</b> ..... Show the working tree status		
	<b>submodule</b> ... Initialize, update, add or inspect submodules		

**--recurse-submodules**  
 pull changes from main repo + submodules  
 tag..... Create, list, delete or verify a tag object signed with GPG  
 gitk..... The git repository browser

## Manipulators

---

**config**..... Get and set repository or global options  
**fast-export**.. Git data exporter  
**fast-import**.. Backend for fast Git data importers  
**filter-branch**  
 Rewrite branches  
**mergetool**... Run merge conflict resolution tools to resolve merge conflicts  
**pack-refs**... Pack heads and tags for efficient repository access  
**prune**..... Prune all unreachable objects from the object database  
**reflog**..... Manage reflog information  
**relink**..... Hardlink common objects in local repositories  
**remote**..... Manage set of tracked repositories  
     **-v** show details about the remotes  
 ⇒     **remove all branches which are not in the remote anymore: remote update --prune**  
**repack**..... Pack unpacked objects in a repository  
**replace**..... Create, list, delete refs to replace objects

## Interrogators

---

**annotate**.... Annotate file lines with commit information  
**blame**..... Show what revision and author last modified each line of a file  
**cherry**..... Find commits not merged upstream  
**count-objects**  
 Count unpacked number of objects and their disk consumption

**difftool**.... Show changes using common diff tools  
**fsck**..... Verifies the connectivity and validity of the objects in the database  
**get-tar-commit-id**  
 Extract commit ID from an archive created using archive  
**help**..... Display help information about git  
**instaweb**.... Instantly browse your working repository in gitweb  
**merge-tree**.. Show three-way merge without touching index  
**rerere**..... Reuse recorded resolution of conflicted merges  
**rev-parse**... Pick out and massage parameters  
**show-branch**.. Show branches and their commits  
**verify-tag**.. Check the GPG signature of tags  
**whatchanged**.. Show logs with difference each commit introduces

## Interacting with Others

---

**archimport**.. Import an Arch repository into git  
**cvsexportcommit**  
 Export a single commit to a CVS checkout  
**cvsimport**... Salvage your data out of another SCM people love to hate  
**cvsserver**... A CVS server emulator for git  
**imap-send**... Send a collection of patches from stdin to an IMAP folder  
**quiltimport**.. Applies a quilt patchset onto the current branch  
**request-pull** Generates a summary of pending changes  
**send-email**.. Send a collection of patches as emails  
**svn**..... Bidirectional operation between a Subversion repository and git

## Manipulators (plumbing)

---

**apply**..... Apply a patch to files and/or to the index  
**checkout-index**  
 Copy files from the index to the working tree  
**commit-tree**.. Create a new commit object  
**hash-object**.. Compute object ID and optionally creates a blob from a file  
**index-pack**.. Build pack index file for an existing packed archive  
**merge-file**.. Run a three-way file merge  
**merge-index**.. Run a merge for files needing merging  
**mktag**..... Creates a tag object  
**mktree**..... Build a tree-object from ls-tree formatted text  
**pack-objects** Create a packed archive of objects  
**prune-packed** Remove extra objects that are already in pack files  
**read-tree**... Reads tree information into the index  
**symbolic-ref** Read and modify symbolic refs  
**unpack-objects**  
 Unpack objects from a packed archive  
**update-index** Register file contents in the working tree to the index  
**update-ref**.. Update the object name stored in a ref safely  
**write-tree**.. Create a tree object from the current index

## Interrogators (plumbing)

---

**cat-file**.... Provide content or type and size information for repository objects  
**diff-files**.. Compares files in the working tree and the index  
**diff-index**.. Compares content and mode of blobs between the index and repository  
**diff-tree**... show files which have been changed by last commit  
     **--name-only**  
     show only names of files

`-r` recursively

`for-each-ref` Output information on each ref

`ls-files.....` Show information about files in the index and the working tree

`ls-remote ...` List references in a remote repository

`ls-tree.....` List the contents of a tree object

⇒ `list all files for specific branch: ls-tree -r master --name-only`

`merge-base ..` Find as good common ancestors as possible for a merge

`name-rev.....` Find symbolic names for given revs

`pack-redundant`  
Find redundant pack files

`rev-list.....` Lists commit objects in reverse chronological order

`show-index ..` Show packed archive index

`show-ref.....` List references in a local repository

`unpack-file.` Creates a temporary file with a blobs contents

`var.....` Show a git logical variable

`verify-pack.` Validate packed git archive files

## Synching repositories

---

`daemon.....` A really simple server for git repositories

`fetch-pack ..` Receive missing objects from another repository

`http-backend` Server side implementation of Git over HTTP

`send-pack ...` Push objects over git protocol to another repository

`update-server-info`  
Update auxiliary info file to help dumb servers

## Helper commands

---

`http-fetch ..` Download from a remote git repository via HTTP

`http-push ...` Push objects over HTTP/DAV to another repository

`parse-remote` Routines to help parsing remote repository access parameters

`receive-pack` Receive what is pushed into the repository

`shell .....` Restricted login shell for only SSH access

`upload-archive`  
Send archive back to archive

`upload-pack .` Send objects packed back to `fetch-pack`

## Internal helper commands

---

`check-attr ..` Display git attributes information

`check-ref-format`  
Ensures that a reference name is well formed

`fmt-merge-msg`  
Produce a merge commit message

`mailinfo.....` Extracts patch and authorship from a single e-mail message

`mailsplit ...` Simple UNIX mbox splitter program

`merge-one-file`  
The standard helper program to use with `merge-index`

`patch-id.....` Compute unique ID for a patch

`sh-setup.....` Common git shell script setup code

`strip-space ..` Filter out empty lines

---

<http://github.com/emzap79/QRCS>  
emzap79@gmail.com

This TeXfile is based on Gabriel B. Burcas © git-qrc.tex and has then been modified to my own use.