

VIMPERATOR QUICK REFERENCE CARD

Frequently used VIMPERATOR commands – Version v1.3 July 2014

Page & Tab Movements

Short introduction to Vimperator can be found at:
<http://www.linuxjournal.com/article/10636>

Page Movements

Move commands work as you would expect them to do from VIM. See `:h motion` for detailed documentation.

`h j k l` move left/down/up/right
`g g` `G` move to top/bottom of page
`^ f ^ d ^ j` move screen/page/line down
`^ b ^ u ^ k` move screen/page/line up
`/ ?` search in page, backwards
`n N` jump to next/previous search result

Tab & Buffer Movements

`bn` switch to open buffer *n* from list
`g t` *or* `^ n` go to next tab
`g T` *or* `^ p` go to previous tab
`g 0` `g $` go to first/last tab
`g h` `g H` open own defined homepage, new tab
`g u` `g U` move up one path/all to root
`⇒ g u` <http://www.vimperator.org/system/app/> :
moves up to <http...or.org/system>
`g o` [`aA-zZ0-9`] jump to previously marked web page

General Keybinds

see: `:h :open`

`o t` open url in current/new tab
`d u` close current/undo last tab
`y Y` copy current url/selection to clipboard
`p P` paste from clipboard, in a new tab
`t T` open new tab, with current url
`H L` go to previous/next page in history

`m M` Set local/global mark at cursor/url
`a A` add/toggle bookmark
`i I` ignore any/specific **vimperator** keybind
`[[]]` switch to previous/next page on multipage websites
`+ -` zoom in/out by 25 % on page in focus
`n z z` zoom page to *n*% (100 if *n* is omitted)
`Z Z` `Z Q` exit browser, clear history before

Exe commands

Works with tab completion

`:addons` show addons in current window
`:bmark` `:delbmarks` *url*
add/delete bookmark
`:emenu` *<tab>*. command-line access to Firefox menubar
`:history` pull up recent 10 online & local pages
`:pclose` close preview window, eg. history
`:preferences` show preferences
`:restart` restart Firefox immediately
`:tabonly` close all other tabs
`:saveas` save current web page to disk.
`:set` *(no)* `apptab`
set, unset current tab as app window

Panorama Mode (Tab Group Management)

Start tabgroup management with `:tabgroup subcom`

Some subcommands ...

<code>add</code>	create new tab group
<code>list</code>	list current tab groups
<code>rm</code>	remove group with groupname
<code>pull-</code> <i>or</i> <code>pushtab</code>	pull tab from <i>or</i> move to group
<code>switch</code>	switch to groupname

Hint-Modes

Hints are the way in which Vimperator allows you to follow links on a page. By providing each link with a suitable hint, you can access them via a set of hotkeys.

QuickHint Mode (*f*)

Simulates mouseselection with labeled links on web page.
To run new tab in background change to uppercase *F*.

ExtendedHint Mode (*; ;*)

This mode is useful for performing operations on hinted elements other than the default left mouse click. If you want to yank the location of hint 24, press `;y` to start this hint mode. Then press 24 to copy the hint location.

`:h extended-hints`
list all extended mode commands

here are a few ...

`; ;` imitates mouse-hovering a link object
`s S` save link/object
`i I` open media object (in new tab)
`y Y` copy URL/label description to clipboard

github.com/emzap79/QRCs

emzap79@gmail.com

This TeXfile is based on Gabriel B. Burcas © `git-qrc.tex` and has then been modified to my own requirements.