

VIM QUICK REFERENCE CARD

Frequently used VIM commands – Version v1.3 July 2014

:viusage ... Show a summary of all commands

Movements

h l k j character left, right; line up, down
b w word/token left, right
ge e end of word/token left, right
{ } beginning of previous, next paragraph
() beginning of previous, next sentence
[[]] go to previous, next function
[{ }] beginning, end of current block
0 ^ \$ beginning, first, last character of line
nG ngg line *n*, default the last, first
n| column *n* of current line
% match of next brace, bracket, comment, **#define**
- + line up, down on first non-blank character
B W space-separated word left, right
gE E end of space-separated word left, right
g0 gm beginning, middle of *screen* line
g^ g\$ first, last character of *screen* line
fc Fc next, previous occurrence of character *c*
tc Tc before next, previous occurrence of *c*

Jumps

:jumps print the jump list
:ta ^[..... jump to tag (under cursor)
^O ^I jump to older/newer location btw buffers
ng; ng, go to *n* older/newer position in change list
'. jump back on last edited line
'' toggle back/forward to previous/next position

Insertion & Replace → insert mode

i a insert before, after cursor
I A insert at beginning, end of line
gi gI insert text on last edited line / first column
o O open a new line below, above the current line
rc replace character under cursor with *c*
grc like **r**, but without affecting layout
R replace characters starting at the cursor
gR like **R**, but without affecting layout
sc substitute char. *c* under cursor
cm change text of movement command *m*
cc or S change current line
C change to the end of line

Deletion

x X delete character under, before cursor
dm delete text of movement command *m*
dd D delete current line, to the end of line
dgn delete the next search pattern match
J gJ join current line with next, without space
:rd delete range *r* lines
:rdx delete range *r* lines into register *x*
qxq empty register *x*
:g/pattern/d x | let @+ = @x
delete lines with pattern *c* into Register *x* and copy to clipboard afterwards.

Insert/ Command Mode

^Vc ^Vn insert char *c* literally, decimal value *n*
^Vn insert decimal value of character
^A insert previously inserted text
^@ same as **^A** and stop insert → command mode

^Rx ^R^Rx ... insert content of register *x*, literally
^R^W content under cursor to command mode
^N ^P text completion before, after cursor
^W delete word before cursor
^U delete to start of current line
^D ^T shift left, right one shift width
^Oc execute *c* in temporary command mode
^X^E ^X^Y ... scroll up, down
<esc> or ^] or ^C abandon edition → command mode

Search & Substitution

/s↔ ?s↔ ... search forward, backward for *s*
/s/o↔ ?s?o↔
search fwd, bwd for *s* with offset *o*
n or /↔ repeat forward last search
N or ?↔ repeat backward last search
* search backward, forward for word under cursor
g# g* same, but also find partial matches
gd gD local, global definition of symbol under cursor
:rs/f/t/x ... substitute *f* by *t* in range *r*
:rco a :rm a
copy, move range *r* below line *a*
:rs x repeat substitution with new *r* & *x*
:rg/p/c :rv/p/c
execute *Ex c* on range *r* where *p* matches, not matches
:rg/p/-1j .. join all lines in *r* containing pattern *p* with prevline
:rg/p/s/q/y/g
for every line in *r* containing *p*, substitute *q* with *y*
: 'a, 'bg/p/j . join any line containing the string *p* to its subsequent line, if it lies between the *a* and *b* marks

Misc Ex Commands (↔)

:help holy-grail

:e *f* edit file *f*, reload current file if no *f*

:rw *f* write range *r* to file *f* (current file if no *f*)

:rw >> *f* append range *r* to file *f*

:q :q! quit and confirm, quit and discard changes

:wq *or* :x *or* ZZ write to current file and exit

:r *f* insert content of file *f* below cursor

:r! *c* insert output of command *c* below cursor

Ex Ranges

, ; separates line numbers, set to first line

n an absolute line number *n*

. \$ the current line, the last line in file

% * entire file, visual area

'*t* position of mark *t*

/p/ ?*p*? the next, previous line where *p* matches

-*n* +*n* preceding/appending line number

Standard Mode Formatting/ Filtering

Leave out *m* for visual mode commands

gqm gqq format movement *m*/current paragraph

:rce *w* center lines in range *r* to width *w*

:rri *w* rightalign lines in range *r* to width *w*

:rle *i* left align lines in range with indent *i*

!mc↔ filter lines of movement *m* through command *c*

n!!c↔ filter *n* lines through command *c*

:r!c filter range *r* lines through command *c*

~ switch case and advance cursor

g~*m* gum gUm switch case, lc, uc on movement *m*

guu gUU lower-/uppercase line

< *m* > *m* .. shift left, right text of movement *m*

n << *n* >> .. shift *n* lines left, right

^A ^X increment/decrement number under cursor

Visual Mode

:h object-select

v V ^V start/stop highlighting characters, lines, block

o exchange cursor position with start of highlighting

gv start highlighting on previous visual area

aw as ap ... select a word, a sentence, a paragraph

ab aB select a block (), a block { }

g^G Count words, character lines and bytes of selection

Undoing, Repeating & Registers

u U undo last command, restore last changed line

. ^R repeat last changes, redo last undo

n. repeat last changes with count replaced by *n*

qc qC record, append typed characters in register *c*

q stop recording

@c execute the content of register *c*

@@ repeat previous @ command

:@c execute register *c* as an *Ex* command

Copying

"*x* use register *x* for next delete, yank, put

:reg show the content of all registers

:reg *x* show the content of registers *x*

ym yank the text of movement command *m*

yy *or* Y yank current line into register

p P put register after, before cursor position

]p [p like p, P with indent adjusted

gp gP like p, P leaving cursor after new text

Patterns (differences to Perl)

:help pattern

\< \> start, end of word

\i \k \I \K an identifier, keyword; excludigits

\f \p \F \P a file name, printable char.; excludigits

\e \t \r \b <esc>, <tab>, <←>, <↵>

\= * \+ match 0..1, 0..∞, 1..∞ of preceding atoms

\{*n,m*> match *n* to *m* occurrences

\{-> non-greedy match

\| separate two branches (≡ *or*)

\(\) group patterns into an atom

\& \1 the whole matched pattern, 1st () group

\u \l upper, lowercase character

\c \C ignore, match case on next pattern

\%x match hex character

\@= \@! *char*(?=pattern) *char*(?!pattern)

\@<= \@<! (?=pattern)*char* (?!pattern)*char*

\@> (?>pattern)

_^ _\$. start-of-line/end-of-line, anywhere in pattern

\. any single char, including end-of-line

\zs \ze set start/end of pattern

\%^ \%\$ match start/end of file

\%V match inside visual area

\'m match with position of mark *m*

\%(\) unnamed grouping

\[] collection with end-of-line included

\%[] sequence of optionally matched atoms

\v very magic: patterns almost like perl

Spell Checking

:set spell spelllang=de_20
activate spellcheck

]s [s next, previous misspelled word

zg zG add good word (to internal word list)

zug zuG..... undo the addition of a word to the dictionary

zw zW mark bad word (to internal word list)

z= suggest corrections

Marks, Motions, and Tags

mc mark current position with mark $c \in [a..Z]$

:marks print the active marks list

‘c ‘C go to mark c in current, C in any file

‘0..9 go to last exit position

‘‘ ‘" go to position before jump, at last edit

‘[‘] go to start, end of previously operated text

n^O go to n^{th} older position in jump list

n^I go to n^{th} newer position in jump list

^] ^T jump to the tag under cursor, return from tag

:ts t list matching tags and select one for jump

:tj t jump to tag or select one if multiple matches

:tags print tag list

Multiple Files / Buffers (↔)

:tab ball .. show buffer tablist

:buffers ... show list of buffers

:on make current window one on screen

:new :vnew . create new empty window (vert.)

:bn switch to buffer n

:bnext :bprev :bfirst :blast
buffer movement

:bdn delete buffer n (also with filename)

:badd f.txt load file into new buffer

:sbn Split window and edit buffer n from the bufflist

Buffer Shortcuts

:h ctrl-w

:bd *.ext ^A Deletes all Buffers with Extension ‘ext’

^~ toggle between the current and the last window

^Wf gf open file under cursor in new/current window

^Ww ^W^W move to window below, above (wrap)

^Wj ^Wk move to window below, above

^Wt ^Wb move to top/bottom window

^Wc ^Wo close current/all other window(s)

^Ws ^Wv split window in two (vert.)

^Wx swap open buffer windows

^Wn+ ^Wn- ... increase/decrease window size by n lines

^Wn > ^Wn < increase/decrease window width

^W = Make all windows equally high and wide

^W n_ set window height to n (default: very high)

^W n| set current window width to n

Tab Management

:tabs list all tabs including their displayed windows

:tabfirst .. go to first tab

:tablast ... go to last tab

:tabnew open a new empty tab page

:tabc close current tab page

:wqa :qa ... (save and) quit all tabs

:tabo close all other tabs

gt gT go to next/previous Tab

ngt goto tab in position n

Advanced Scrolling

n^Y n^E..... Scroll window n lines up-/downwards

^D ^U scroll half a page up, down

^F ^B scroll page up, down

zt zz zb ... current line to top, center, bottom of win.

zh zl scroll one character to the right, left

zH zL scroll half a screen to the right, left

Completion

^X^L..... whole lines

^X^N ^X^I..... keywords in current file, plus included files

^X^K ^X^N..... keywords in dictionary, thesaurus

^X^] tags

^X^F..... file names

^X^D..... definitions or macros

^X^V..... vim command line

^X^U..... user defined completion

^X^O..... omni completion

Folding

zfm create fold of movement m

:rfo create fold for range r

zd zE delete fold at cursor, all in window

zo zc zO zC open, close one fold; recursively

[z]z move to start, end of current open fold

zj zk move down, up to start, end of next fold

zm zM fold more, close all folds

zr zR fold less, open all folds

zn zN zi ... fold non, fold normal, invert folding
:set foldcolumn=*n*
show foldcolumn *n*

Compiling

:compiler *c* set/show compiler plugins
:make run makeprg, jump to first error
:cope navigate errors from make
:cn :cp display the next, previous error
:cl :cf list all errors, read errors from file

Indentation

:set fdm=indent
indent-foldmethod

n> *n*< = ... indent/unindent *n* levels, reindent
n>> *n*<< .. indent/dedent *n* lines
G=gg auto (re)indent entire document

Vim Start-Options

vimdiff *f*₁ *f*₂
diff *file*₁ + *file*₂ using synchronized
split windows

vim -o/-O *f*₁ *f*₂
open *files* in horiz/vert split mode

vim +*n file* . open *file* at *n*th line (eof if *n* omitted)
vim +/s *file* open *file* and search for *string*
vim -S *name* reload vim-session *name*

Miscellaneous

:digraphs *or* :h digraph-table
complete list of all digraphs

^K*c*₁*c*₂ *or* *c*₁←*c*₂
enter digraph {*c*₁, *c*₂}

:rhardcopy *rw!lp*
sending *r* to printer (printout)

:rhardcopy > file.ps
print range to ps file
:mkview [*f*] :loadview [*f*]
save/load configuration

:mks [*f*] :so [*f*]
save/load session

:set ff=dos convert file to dos eol format
:e ++ff=unix reopen file in unix eol format
:sh :!*c* start shell, execute command *c* in shell
K run keywordprg (manpage) on word
under cursor
^L redraw screen
^R = 5*5 insert 25 into text
ga show ASCII value of character under
cursor
gf open filename under cursor

Usefull Helpsections

:h /zero-width
matches with ‘zero-width’ {*@!*} patterns

github.com/emzap79/QRCS

emzap79@gmail.com

This TeXfile is based on Gabriel B. Burcas © git-qrc.tex and has
then been modified to my own requirements.