

## VIM QUICK REFERENCE CARD

**:viusage** .....Show a summary of all commands

### Movements

**h l k j** .....character left, right; line up, down  
**b w** ..... word/token left, right  
**ge e** .....end of word/token left, right  
**{ }** .....beginning of previous, next paragraph  
**( )** ..... beginning of previous, next sentence  
**O ^ \$** ..... beginning, first, last character of line  
**nG ngg** ..... line *n*, default the last, first  
**n|** .....column *n* of current line  
**%** ... match of next brace, bracket, comment, **#define**  
**- +** .....line up, down on first non-blank character  
**B W** ..... space-separated word left, right  
**gE E** .....end of space-separated word left, right  
**gO gm** .....beginning, middle of *screen* line  
**g^ g\$** ..... first, last character of *screen* line  
**f c F c** .....next, previous occurrence of character *c*  
**t c T c** ..... before next, previous occurrence of *c*

### Jumps

**:jumps** ..... print the jump list  
**:ta ^[** ..... jump to tag (under cursor)  
**^O ^I** .....jump to older/newer location btw. buffers  
**ng; ng,** ..... go to or edit *n* older/newer position in change list  
**'** ..... jump back on last edited line  
**''** .....toggle back/forward to previous/next position

### Insertion & Replace → insert mode

**i a** .....insert before, after cursor  
**I A** .....insert at beginning, end of line  
**gi gI** ....insert text on last edited line / first column  
**o O** .... open a new line below, above the current line  
**rc** .....replace character under cursor with *c*  
**grc** .....like **r**, but without affecting layout  
**R** .....replace characters starting at the cursor  
**gR** .....like **R**, but without affecting layout  
**sc** .....substitute char. *c* under cursor  
**cm** .....change text of movement command *m*  
**cc or S** ..... change current line

**C** ..... change to the end of line

### Deletion

**x X** .....delete character under, before cursor  
**dm** .....delete text of movement command *m*  
**dd D** .....delete current line, to the end of line  
**dgn** .....delete the next search pattern match  
**J gJ** .....join current line with next, without space  
**:rd** ..... delete range *r* lines  
**:rdx** .....delete range *r* lines into register *x*

### Insert/ Command Mode

**^Vc ^Vn** .....insert char *c* literally, decimal value *n*  
**^Vn** ..... insert decimal value of character  
**^A** .....insert previously inserted text  
**^@** ..... same as **^A** and stop insert → command mode  
**^Rx ^R^Rx** .....insert content of register *x*, literally  
**^R^W** ..... content under cursor to command mode  
**^N ^P** ..... text completion before, after cursor  
**^W** .....delete word before cursor  
**^U** .....delete to start of current line  
**^D ^T** ..... shift left, right one shift width  
**^Oc** .....execute *c* in temporary command mode  
**^X^E ^X^Y** ..... scroll up, down  
**<esc> or ^** ..... abandon edition → command mode

### Search & Substitution

**/s↔ ?s↔** .....search forward, backward for *s*  
**/s/o↔ ?s?o↔** .....search fwd, bwd for *s* with offset *o*  
**n or /↔** .....repeat forward last search  
**N or ?↔** .....repeat backward last search  
**# \*** ..search backward, forward for word under cursor  
**g# g\*** ..... same, but also find partial matches  
**gd gD** ..local, global definition of symbol under cursor  
**:rs/f/t/x** .....substitute *f* by *t* in range *r*  
[ *x* : **g**—all occurrences, **c**—confirm changes  
**:rs x** .....repeat substitution with new *r* & *x*  
**:rg/p/c :rv/p/c** ....execute *Ex c* on range *r* where *p* matches/does not match

### Misc Ex Commands (↔)

**:help holy-grail** ..... show all Ex commands  
**:e f** .....edit file *f*, reload current file if no *f*

**:rw f** .....write range *r* to file *f* (current file if no *f*)  
**:rw>>f** .....append range *r* to file *f*  
**:q :q!** .. quit and confirm, quit and discard changes  
**:wq or :x or ZZ** ..... write to current file and exit  
**:r f** .....insert content of file *f* below cursor  
**:r! c** ..... insert output of command *c* below cursor  
**:rc a :rm a** .....copy, move range *r* below line *a*  
**:rg/p/-1j** join all lines in *r* containing pattern *p* with prev. line  
**:rg/p/s/q/y/g** .....for every line in *r* containing *p*, substitute *q* with *y*  
**:r'a, 'bg/p/j** ..join any line containing the string *p* to its subsequent line, if it lies between the *a* and *b* marks

### Ex Ranges

**,** ; .....separates two lines numbers, set to first line  
**n** .....an absolute line number *n*  
**.** \$ .....the current line, the last line in file  
**% \*** .....entire file, visual area  
**'t** ..... position of mark *t*  
**/p/ ?p?** .... the next, previous line where *p* matches  
**+n -n** .....+*n*, −*n* to the preceding line number

### Standard Mode Formatting/ Filtering

Leave out *m* for visual mode commands  
**gqm gqgq** ... format movement *m*/current paragraph  
**:rce w** .....center lines in range *r* to width *w*  
**:rle i** .....left align lines in range *r* with indent *i*  
**:rri w** .....right align lines in range *r* to width *w*  
**!mc↔** ..filter lines of movement *m* through command *c*  
**n!!c↔** ..... filter *n* lines through command *c*  
**:r!c** .....filter range *r* lines through command *c*  
**~** .....switch case and advance cursor  
**g~m gum gUm** ... switch case, lc, uc on movement *m*  
**<m >m** .....shift left, right text of movement *m*  
**n<< n>>** .....shift *n* lines left, right  
**^A ^X** ..... increment/decrement number under cursor

### Visual Mode

**:h object-select** ..... Object selecting patterns  
**v V ^V** .start/stop highlighting characters, lines, block  
**o** ..exchange cursor position with start of highlighting  
**gv** .....start highlighting on previous visual area

**aw as ap** .....select a word, a sentence, a paragraph  
**ab aB** .....select a block ( ), a block { }  
**n> n< =** .....indent/unindent *n* levels, reindent

### Undoing, Repeating & Registers

**u U** .....undo last command, restore last changed line  
**. ^R** .....repeat last changes, redo last undo  
**n.** .....repeat last changes with count replaced by *n*  
**qc qC** .. record, append typed characters in register *c*  
**q** .....stop recording  
**@c** .....execute the content of register *c*  
**@@** .....repeat previous @ command  
**:@c** .....execute register *c* as an *Ex* command

### Copying

**"x** ..... use register *x* for next delete, yank, put  
**:reg** .....show the content of all registers  
**:reg x** .....show the content of registers *x*  
**ym** .....yank the text of movement command *m*  
**yy or Y** .....yank current line into register  
**p P** .....put register after, before cursor position  
**lp [p** .....like **p**, **P** with indent adjusted  
**gp gP** .....like **p**, **P** leaving cursor after new text

### Patterns (differences to Perl)

**:help pattern** .....show complete help on patterns  
**\< \>** .....start, end of word  
**\i \k \I \K** .....an identifier, keyword; excl. digits  
**\f \p \F \P** .. a file name, printable char.; excl. digits  
**\e \t \r \b** .....*<esc>*, *<tab>*, *<↵>*, *<←>*  
**\= \* \+** ...match 0..1, 0..∞, 1..∞ of preceding atoms  
**\{*n*,*m*>** ..... match *n* to *m* occurrences  
**\{->** ..... non-greedy match  
**\|** .....separate two branches (*≡ or*)  
**\( \)** .....group patterns into an atom  
**\& \1** .....the whole matched pattern, 1<sup>st</sup> () group  
**\u \l** .....upper, lowercase character  
**\c \C** .....ignore, match case on next pattern  
**\%x** .....match hex character  
**\@= \@!** .....(=?*pattern*) (?!*pattern*)  
**\@<= \@<!** .....(=?<*pattern*) (?<!*pattern*)  
**\@>** .....(=?>*pattern*)  
**\\_^ \\_\\$** .start-of-line/end-of-line, anywhere in pattern

**\\_.** .....any single char, including end-of-line  
**\zs \ze** .....set start/end of pattern  
**\%^ \%\$** .....match start/end of file  
**\%V** .....match inside visual area  
**\'m** .....match with position of mark *m*  
**\%( \)** .....unnamed grouping  
**\[ ]** .....collection with end-of-line included  
**\%[ ]** .....sequence of optionally matched atoms  
**\v** .....very magic: patterns almost like perl

### Spell Checking

**:set spell spelllang=de\_20** .... activate spellcheck  
**]s** .....next misspelled word  
**zg zG** .....add good word (to internal word list)  
**zug zuG**.undo the addition of a word to the dictionary  
**zw zW** .....mark bad word (to internal word list)  
**z=** .....suggest corrections

### Marks, Motions, and Tags

**mc** ..... mark current position with mark *c* ∈ [*a*..*Z*]  
**'c 'C** .....go to mark *c* in current, *C* in any file  
**'0..9** .....go to last exit position  
**' ' "** .....go to position before jump, at last edit  
**'[ ']** .... go to start, end of previously operated text  
**:marks** .....print the active marks list  
**n^0** .....go to *n*<sup>th</sup> older position in jump list  
**n^I** .....go to *n*<sup>th</sup> newer position in jump list  
**^]** **^T** ..jump to the tag under cursor, return from tag  
**:ts t** .....list matching tags and select one for jump  
**:tj t** ...jump to tag or select one if multiple matches  
**:tags** .....print tag list

### Multiple Files / Buffers (↔)

**:h buffers** .....get help for buffer-management  
**:tab ball** .....show buffer tablist  
**:buffers** .....show list of buffers  
**:on** .....make current window one on screen  
**:new :vnew** .....create new empty window (vert.)  
**:bn** .....switch to buffer *n*  
**:bnext :bprev :bfirst :blast** ...buffer movement  
**:bdn** .....delete buffer *n* (also with filename)  
**:badd f.txt** .....load file into new buffer

**:sbn** ..Split window and edit buffer *n* from the buffer list  
**:verticaln :horizontalc** ..execute *c* on vert./horiz. split  
**:rightabovew :leftbeloww** .....execute *c* (eg. *sbn*) right/left above/below window

### Buffer Shortcuts

**:h ctrl-w** ..... complete list of all buffer commands  
**^^** ....toggle between the current and the last window  
**^wf gf** .open file under cursor in new/current window  
**^ww ^wW** ..... move to window below, above (wrap)  
**^wj ^wk** .....move to window below, above  
**^wt ^wb** .....move to top/bottom window  
**^wo ^wc** .....close all other/current window(s)  
**^ws ^wv** .....split window in two (vert.)  
**^wx** .....swap open buffer windows  
**^wn+ ^wn-** .. increase/decrease window size by *n* lines  
**^wn > ^wn <** ..... increase/decrease window width  
**^w =** ..... Make all windows equally high and wide  
**^w n\_** .....set window height to *n* (default: very high)  
**^w n|** .....set current window width to *n*

### Tab Management

**:tabs** ..list all tabs including their displayed windows  
**:tabfirst** ..... go to first tab  
**:tablast** .....go to last tab  
**:tabnew** .....open a new empty tab page  
**:tabc** .....close current tab page  
**:wqa :qa** .....(save and) quit all tabs  
**:tabo** .....close all other tabs  
**gt gT** .....go to next/previous Tab  
**ngt** ..... goto tab in position *n*

### Advanced Scrolling

**^D ^U** .....scroll half a page up, down  
**^F ^B** .....scroll page up, down  
**zt zz zb** ..current line to top, center, bottom of win.  
**zh zl** .....scroll one character to the right, left  
**zH zL** .....scroll half a screen to the right, left

### Completion

**^X^L** ..... whole lines

```

^X^N ^X^I .. keywords in current file, plus included files
^X^K ^X^N ..... keywords in dictionary, thesaurus
^X`] ..... tags
^X^F ..... file names
^X^D ..... definitions or macros
^X^V ..... vim command line
^X^U ..... user defined completion
^X^O ..... omni completion

```

### *Folding*

```

:set fdm=indent ..... indent-foldmethod
zfm ..... create fold of movement m
:rfo ..... create fold for range r
zd zE ..... delete fold at cursor, all in window
zo zc zO zC ..... open, close one fold; recursively
[z ]z ..... move to start, end of current open fold
zj zk ..... move down, up to start, end of next fold
zm zM ..... fold more, close all folds
zr zR ..... fold less, open all folds
zn zN zi ..... fold non, fold normal, invert folding
:set foldcolumn=4 ..... show foldcolumn

```

### *Compiling*

```

:compiler c ..... set/show compiler plugins
:make ..... run makeprg, jump to first error
:cope ..... navigate errors from make
:cn :cp ..... display the next, previous error
:cl :cf ..... list all errors, read errors from file

```

### *Miscellaneous*

```

:sh :!c ..... start shell, execute command c in shell
:mks name ..... save session name
vim -S name ..... reload vim-session name
:mkview [f] :loadview [f] .. save/load configuration
K ...run keywordprg (manpage) on word under cursor
^L ..... redraw screen
g^G...show cursor column, line, and character position
:set cuc .....show cursor column visually
ga .....show ASCII value of character under cursor
gf ..... open file which filename is under cursor
:set ff=dos ..... convert file to dos eol format
:e ++ff=unix .....reopen file in unix eol format
:set hlsearch .....highlight searches

```

```

:rharcopy rw!lp ....sending r to printer (printout)
:rharcopy > file.ps .....print range to ps file
:set list .....show listchar characters (tabs etc.)
:set ic/noic (un)ignore cases in substitute-command

```

### *Most Common Digraphs*

```

:dig .....complete list of all digraphs
^Kc1c2 or c1←c2 ..... enter digraph {c1,c2}
Co .....Copyright
Rg .....Registered Trademark
!I .....¡: Inverteted Excl. Mark
?I .....¿: Inverteted Quest. Mark
Eu .....Euro Currency
Li .....Britain Pound Currency
14 12 34 ..... 1/4, 1/2, 3/4 etc.

```

---

For further examples for how to use Exec-Commands  
see: <http://stackoverflow.com/a/1220118>

This card may be freely distributed under the terms of the GNU  
general public licence — Copyright © 2009 by Michael Goerz.  
<http://www.physik.fu-berlin.de/~goerz/>. Based on original by  
Laurent Grégoire (<http://tnerual.eriogerg.free.fr/>)