User Acceptance Testing (UAT)

iMovies MERN Project • Phase-wise Documentation

Project: iMovies MERN **Document:** User Acceptance Testing (UAT)

1. Purpose

This document is a user acceptance testing plan and results template for the iMovies MERN prototype. It defines practical scenarios to verify that key workflows meet user needs. Test results must be filled in after executing the tests; this document does not claim that all tests have passed.

2. Test environment

Frontend: React/Vite, expected local URL http://localhost:5174. Backend: Express/Node.js, expected local URL http://localhost:5000. Database: MongoDB database named imovies. These values may differ in the tester's environment.

3. Entry criteria

- Backend starts without fatal errors and connects to MongoDB.
- Frontend starts and can reach the backend API.
- A test user and admin credentials are available.
- Test data exists or can be created safely.

4. Test cases

ID	Scenario / steps	Expected result	Actual result	Status
UAT-01	Open home page and browse movies.	Movie cards/details load from API.	To be filled	Not run
UAT-02	Search for a movie title.	Matching movies are shown; no-match state is clear.	To be filled	Not run
UAT-03	Register using valid test details.	Account is created and user can sign in.	To be filled	Not run
UAT-04	Sign in with valid credentials; refresh page.	User session is handled as designed and user remains in correct state.	To be filled	Not run
UAT-05	Try invalid login details.	Access is denied and a clear error is shown.	To be filled	Not run
UAT-06	Select movie, show and seats; submit booking.	Booking summary is correct and booking is stored.	To be filled	Not run
UAT-07	Attempt a seat already reserved by another booking.	Server rejects conflicting reservation; UI explains the result.	To be filled	Not run
UAT-08	Open My Bookings as a signed-in user.	Only the signed-in user's bookings are shown.	To be filled	Not run
UAT-09	Cancel an eligible booking.	Booking is cancelled/removed according to implementation.	To be filled	Not run
UAT-10	Open admin dashboard without admin token.	Admin access is denied.	To be filled	Not run
UAT-11	Admin adds a movie with valid details.	Movie is saved and appears in the movie list.	To be filled	Not run
UAT-12	Submit missing or invalid required fields.	Validation prevents invalid data and gives a clear message.	To be filled	Not run

5. Acceptance criteria

- Critical workflows work without blocking defects.
- Authorization is enforced for protected user/admin actions.
- Displayed price matches the selected seats and movie price.
- Errors and confirmation messages are understandable.
- No secrets are committed to the repository.

6. Defect log template

Defect ID	Steps to reproduce	Expected	Actual	Severity	Status
DEF-01	Fill in during testing	Fill in	Fill in	Low/Medium/High	Open

7. Sign-off

Tester name: _____ Date: _____
Acceptance decision: ■ Accepted ■ Accepted with issues ■ Rejected
Notes: _____

Prepared for academic project documentation. Verify implementation-specific details and fill in actual test evidence before final submission.