Project Planning Phase

Project Planning Template (Product Backlog, Sprint Planning, Stories, Story points)

Date	18 October 2026
Team ID	
Project Name	FORMULA 1 Race Intelligence Dashboard Analysis Report (2010-2026)
Maximum Marks	8 Marks

Product Backlog, Sprint Schedule, and Estimation (4 Marks)

Use the below template to create product backlog and sprint schedule

Sprint	Functional Requirement (Epic)	User Story Number	User Story / Task	Story Points	Priority	Team Members
Sprint 1	Data preparation	US-1	As an analyst, I can inspect and relate all five workbook sheets.	Profile columns, types, nulls, row grain and relationships.	5	High
Sprint 1	Data quality	US-2	As an analyst, I can validate the data before charting.	Document missing values and key uniqueness.	3	High
Sprint 2	Driver analysis	US-3	As a viewer, I can rank drivers by points.	Build leaderboard, labels and season filter.	3	High
Sprint 2	Constructor analysis	US-4	As a strategist, I can compare teams across seasons.	Build season line chart and filters.	3	High
Sprint 2	Tyre strategy	US-5	As a strategist, I can analyze compound and tyre-age patterns.	Create compound bars and lap-time scatter.	3	Medium
Sprint 3	Reliability	US-6	As an analyst, I can inspect DNF patterns.	Create DNF/reason/circuit charts.	3	High
Sprint 3	Story and validation	US-7	As a presenter, I can explain results as a coherent story.	Cross-check totals and assemble Story.	4	High

Project Tracker, Velocity & Burndown Chart: (4 Marks)

Sprint	Total Story Points	Duration	Sprint Start Date	Sprint End Date (Planned)	Story Points Completed (as on Planned End Date)	Sprint Release Date (Actual)
Sprint 1	8	6 working days	27 Oct 2026	1 Nov 2026	To be recorded after work	To be recorded
Sprint 2	9	6 working days	2 Nov 2026	7 Nov 2026	To be recorded after work	To be recorded
Sprint 3	10	6 working days	8 Nov 2026	13 Nov 2026	To be recorded after work	To be recorded
Sprint 4	5	6 working days	14 Nov 2026	19 Nov 2026	To be recorded after work	To be recorded

Velocity:
Imagine we have a 10-day sprint duration, and the velocity of the team is 20 (points per sprint). Let's calculate the team's average velocity (AV) per iteration unit (story points per day)

$$AV = \frac{sprint\ duration}{velocity} = \frac{20}{10} = 2$$

Burndown Chart:

A burn down chart is a graphical representation of work left to do versus time. It is often used in agile software development methodologies such as Scrum. However, burn down charts can be applied to any project containing measurable progress over time.

https://www.visual-paradigm.com/scrum/scrum-burndown-chart/
https://www.atlassian.com/agile/tutorials/burndown-charts

Reference:

https://www.atlassian.com/agile/project-management
https://www.atlassian.com/agile/tutorials/how-to-do-scrum-with-jira-software
https://www.atlassian.com/agile/tutorials/epics
https://www.atlassian.com/agile/tutorials/sprints
https://www.atlassian.com/agile/project-management/estimation
https://www.atlassian.com/agile/tutorials/burndown-charts

Project-specific Documentation

Dataset workbook: F1 Racing Project Dataset(1).xlsx.

Sheets and data rows (excluding headers): race_results 6,464; circuits 29; championship_standings 311; lap_intelligence 3,814; qualifying_results 3,130.

Observed race_results coverage: seasons 2010–2026; 334 distinct race_id values; 19 distinct driver labels; 10 distinct team labels; 21 distinct country labels.

Available analysis fields include race date/season/round, circuit type and location, driver/team, finish/grid position, points, DNF and DNF reason, weather/wet-race flag, safety-car/VSC/red-flag data, pit stops, tyre strategy/starting compound, overtakes and laps led.

Lap-level fields include lap/sector times, tyre compound and tyre age, DRS, speed trap and pit-lap flag. Qualifying fields include qualifying position, Q1/Q2/Q3 times, gap to pole and top speed.

Validation note: workbook is a multi-sheet analytical dataset, not necessarily official complete historical timing. Verify values and data types before presenting findings. Do not infer driver nationality: no nationality field is present.

Use COUNTD([race_id]) for race-event counts where appropriate; race_results contains multiple driver-result rows per event. Distinguish race-result row counts from unique Grand Prix counts.

• Recommended analysis: driver points; constructor season trajectory; tyre compound usage; tyre age versus lap time; podium distribution; country/circuit comparisons; DNF by team/season/reason; wet-race/circuit-type reliability; grid-to-finish position gain; pit-stop and safety-car context.

• Limitations: no driver nationality field; DNF reasons are sparse; dataset's historical coverage and synthetic-looking labels should be validated against an authoritative source before external claims.