

CSV Import Support for Dynamic Attributes

Version 1.3.0-SNAPSHOT, 2026-02-13T14:32:21Z

Chapter 1. Executive Summary

This document proposes a design for importing `dynamicAttributeSets` and `dynamicAttributes` via CSV. The challenge is that dynamic attributes are schema-less, nested structures where the attribute names and types are not known at compile time, yet CSV is an inherently flat, column-based format.

Chapter 2. Background: Dynamic Attributes Data Model

2.1. Current Structure

```
// A model with dynamic attributes
public class Product extends BaseModel {
    protected String name;
    protected String sku;
    protected List<DynamicAttributeSet> dynamicAttributeSets = new ArrayList<>();
}

// Container for related attributes
public class DynamicAttributeSet {
    protected String name; // e.g., "logistics", "compliance"
    protected List<DynamicAttribute> attributes;
}

// Individual attribute with type and value
public class DynamicAttribute {
    protected String id;
    protected String name; // e.g., "weight", "hazmat_class"
    protected DynamicAttributeType type; // String, Integer, Boolean, Date,
    etc.
    protected Object value; // The actual value
    protected Object defaultValue;
    protected boolean required;
    protected boolean hidden;
    // ... other metadata
}
```

2.2. Example JSON Representation

```
{
  "name": "Widget Pro",
  "sku": "WGT-001",
  "dynamicAttributeSets": [
    {
      "name": "logistics",
      "attributes": [
        { "name": "weight", "type": "Double", "value": 2.5 },
        { "name": "dimensions", "type": "String", "value": "10x5x3" },
        { "name": "hazmat", "type": "Boolean", "value": false }
      ]
    }
  ],
}
```

```
"name": "compliance",  
"attributes": [  
  { "name": "ce_certified", "type": "Boolean", "value": true },  
  { "name": "certification_date", "type": "Date", "value": "2024-01-15" }  
]  
}  
]
```

Chapter 3. Design Challenges

1. **Flat vs Nested:** CSV is flat; dynamic attributes are deeply nested (model → sets → attributes)
2. **Schema Variability:** Different rows may have different dynamic attributes
3. **Type Coercion:** CSV values are strings; dynamic attributes have typed values
4. **Merge Semantics:** Should import replace all attributes or merge with existing?
5. **Validation:** How to validate against DynamicAttributeSetDefinition if one exists?
6. **Performance:** Potentially many columns for dynamic attributes

Chapter 4. Proposed Design: All Three Strategies Supported

The design supports **all three import strategies**, configurable via ImportProfile. Each strategy has its use cases, and users can choose based on their data shape and tooling.

4.1. Strategy Overview

| Strategy | Best For | CSV Style | Configuration |
|--------------|---|---|---|
| DOT_NOTATION | Spreadsheet-friendly, sparse attributes | <code>dyn.setName.attrName</code> columns | <code>dynamicAttributeStrategy: DOT_NOTATION</code> |
| JSON_COLUMN | Complex structures, programmatic generation | Single <code>dynamicAttributes</code> JSON column | <code>dynamicAttributeStrategy: JSON_COLUMN</code> |
| VERTICAL | Attribute-centric imports, bulk attribute loading | Multiple rows per entity | <code>dynamicAttributeStrategy: VERTICAL</code> |

4.2. Strategy 1: DOT_NOTATION (Header Convention)

Use a special header prefix and dot notation to map CSV columns to dynamic attributes.

4.2.1. Header Format

```
dyn.<setName>.<attributeName>
dyn.<setName>.<attributeName>:type
```

4.2.2. Example CSV

```
name,sku,dyn.logistics.weight,dyn.logistics.dimensions,dyn.logistics.hazmat,dyn.compliance.ce_certified,dyn.compliance.certification_date
"Widget Pro","WGT-001",2.5,"10x5x3",false,true,"2024-01-15"
"Gadget X","GDG-002",1.2,"5x5x2",false,true,"2024-03-20"
```

4.2.3. Type Inference

Types can be inferred or explicitly specified:

| Method | Header | Notes |
|---------------------|-----------------------------------|--|
| Inferred from value | <code>dyn.logistics.weight</code> | Parser attempts: Boolean → Integer → Long → Double → Date → String |

| Method | Header | Notes |
|---|--|---|
| Explicit type suffix | <code>dyn.logistics.weight:Double</code> | Forces specific type |
| From DynamicAttribute SetDefinition | <code>dyn.logistics.weight</code> | Looks up type from definition if exists |
| From ImportProfile | Configured in profile | Type specified in column mapping |

4.2.4. Best For

- Spreadsheet editing (Excel, Google Sheets)
- Human-readable CSV files
- Sparse attributes (some rows have attributes, others don't)
- When attribute names are known upfront

4.3. Strategy 2: JSON_COLUMN (JSON-in-Cell)

Store the entire dynamic attributes structure as JSON in a dedicated CSV column.

4.3.1. Column Format

The column name is configurable (default: `dynamicAttributes`). The value is a JSON object:

```
{
  "setName": {
    "attrName": value,
    "attrName2": value2
  },
  "setName2": {
    "attrName": value
  }
}
```

4.3.2. Example CSV

```
name,sku,dynamicAttributes
"Widget Pro","WGT-001","{"logistics":{"weight":2.5,"dimensions":"10x5x3"},"hazmat":false},"compliance":{"ce_certified":true,"certification_date":"2024-01-15"}"
"Gadget X","GDG-002","{"logistics":{"weight":1.2,"dimensions":"5x5x2"}"}
```

4.3.3. Alternative: Relaxed JSON Format

For easier editing, support a relaxed format with single quotes or unquoted keys:

```
name,sku,dynamicAttributes
"Widget Pro","WGT-
001","{'logistics':{'weight':2.5,'hazmat':false},'compliance':{'ce_certified':true}}"
```

4.3.4. Full Structure JSON (Optional)

For complete control, support full DynamicAttributeSet structure:

```
name,sku,dynamicAttributeSets
"Widget Pro","WGT-
001","[{{"name":"","logistics":"","attributes":[{"name":"","weight","type":"","Double"
,"value":2.5}]}}]"
```

4.3.5. Best For

- Programmatically generated CSV files
- Complex attribute structures
- When attributes vary significantly between rows
- Integration with systems that export JSON

4.4. Strategy 3: VERTICAL (Multiple Rows per Entity)

One row per attribute, with a parent identifier to group rows into entities.

4.4.1. Column Format

Required columns:

| Column | Description |
|-------------------------|--|
| <code>_entityKey</code> | Unique identifier to group rows (e.g., SKU, refName) |
| <code>_attrSet</code> | Dynamic attribute set name |
| <code>_attrName</code> | Attribute name within the set |
| <code>_attrType</code> | Attribute type (optional, can be inferred) |
| <code>_attrValue</code> | The attribute value |

Column names are configurable in ImportProfile.

4.4.2. Example CSV

```
_entityKey,_attrSet,_attrName,_attrType,_attrValue
"WGT-001","logistics","weight","Double","2.5"
"WGT-001","logistics","dimensions","String","10x5x3"
"WGT-001","logistics","hazmat","Boolean","false"
"WGT-001","compliance","ce_certified","Boolean","true"
"WGT-001","compliance","certification_date","Date","2024-01-15"
"GDG-002","logistics","weight","Double","1.2"
"GDG-002","logistics","dimensions","String","5x5x2"
```

4.4.3. With Entity Fields

Include entity fields on each row (redundant but allows single-pass processing):

```
sku,name,_attrSet,_attrName,_attrType,_attrValue
"WGT-001","Widget Pro","logistics","weight","Double","2.5"
"WGT-001","Widget Pro","logistics","dimensions","String","10x5x3"
"WGT-001","Widget Pro","compliance","ce_certified","Boolean","true"
"GDG-002","Gadget X","logistics","weight","Double","1.2"
```

4.4.4. Best For

- Bulk attribute imports (adding many attributes to existing entities)
- Attribute-focused workflows
- When entity already exists and you're just updating attributes
- Exports from attribute management systems

4.5. Hybrid Mode: Combining Strategies

Enable multiple strategies in a single import by setting `dynamicAttributeStrategy: HYBRID`:

```
name,sku,dyn.logistics.weight,dynamicAttributes
"Widget Pro","WGT-001",2.5,{"compliance":{"ce_certified":true}}
"Gadget X","GDG-002",1.2,{"compliance":{"rohs":true}}
```

Processing order: 1. DOT_NOTATION columns processed first 2. JSON_COLUMN merged/overlaid 3. Explicit ColumnMappings applied last (highest priority)

Chapter 5. Detailed Design: Dot Notation Approach

5.1. Configuration in ImportProfile

5.1.1. New Enums

```
/**
 * Strategy for importing dynamic attributes from CSV.
 */
public enum DynamicAttributeImportStrategy {
    /**
     * Disable dynamic attribute import.
     */
    NONE,

    /**
     * Use dot-notation headers: dyn.setName.attrName[:type]
     * Best for spreadsheet-friendly imports.
     */
    DOT_NOTATION,

    /**
     * Use a single JSON column containing all dynamic attributes.
     * Best for programmatic imports.
     */
    JSON_COLUMN,

    /**
     * Use vertical format with multiple rows per entity.
     * Best for attribute-centric imports.
     */
    VERTICAL,

    /**
     * Support both DOT_NOTATION and JSON_COLUMN in same import.
     * DOT_NOTATION processed first, JSON_COLUMN merged on top.
     */
    HYBRID
}

/**
 * Strategy for merging imported dynamic attributes with existing.
 */
public enum DynamicAttributeMergeStrategy {
    /**
     * Remove all existing attributes, replace with imported.
```

```

    */
    REPLACE,

    /**
     * Keep existing attributes, update matching, add new.
     */
    MERGE,

    /**
     * Keep existing attributes, only add new (no updates to existing).
     */
    APPEND
}

```

5.1.2. DynamicAttributeMapping

```

@Data
@NoArgsConstructor
@AllArgsConstructor
@Builder
@Entity
public class DynamicAttributeMapping {
    /**
     * The CSV column name or pattern.
     * For DOT_NOTATION: can use "dyn.{setName}.{attrName}" for auto-discovery.
     * For JSON_COLUMN: the column containing JSON.
     * For VERTICAL: not used (uses verticalConfig).
     */
    private String sourceColumn;

    /**
     * Target attribute set name. If null, extracted from header.
     */
    private String targetSetName;

    /**
     * Target attribute name. If null, extracted from header.
     */
    private String targetAttributeName;

    /**
     * Force a specific type. If null, inferred.
     */
    private DynamicAttributeType type;

    /**
     * Date/time format for Date/DateTime types.
     */
    private String dateFormat;
}

```

```

/**
 * Reference to DynamicAttributeSetDefinition for validation.
 */
private String definitionRefName;
}

```

5.1.3. VerticalFormatConfig

```

@Data
@NoArgsConstructor
@AllArgsConstructor
@Builder
@Entity
public class VerticalFormatConfig {
    /**
     * Column containing the entity key for grouping rows.
     * Default: "_entityKey"
     */
    @Builder.Default
    private String entityKeyColumn = "_entityKey";

    /**
     * Field on the entity that matches entityKeyColumn values.
     * Used for lookups when updating existing entities.
     * Default: "refName"
     */
    @Builder.Default
    private String entityKeyField = "refName";

    /**
     * Column containing the attribute set name.
     * Default: "_attrSet"
     */
    @Builder.Default
    private String setNameColumn = "_attrSet";

    /**
     * Column containing the attribute name.
     * Default: "_attrName"
     */
    @Builder.Default
    private String attrNameColumn = "_attrName";

    /**
     * Column containing the attribute type (optional).
     * Default: "_attrType"
     */
    @Builder.Default

```

```

private String attrTypeColumn = "_attrType";

/**
 * Column containing the attribute value.
 * Default: "_attrValue"
 */
@Builder.Default
private String attrValueColumn = "_attrValue";

/**
 * If true, entity fields can be included on each row.
 * First occurrence of each field value is used.
 * Default: false
 */
@Builder.Default
private boolean allowEntityFieldsOnRows = false;

/**
 * Columns to exclude from entity field processing.
 * Typically the attribute columns themselves.
 */
private List<String> excludeFromEntityFields;
}

```

5.1.4. JsonColumnConfig

```

@Data
@NoArgsConstructor
@AllArgsConstructor
@Builder
@Entity
public class JsonColumnConfig {
    /**
     * The CSV column name containing JSON dynamic attributes.
     * Default: "dynamicAttributes"
     */
    @Builder.Default
    private String columnName = "dynamicAttributes";

    /**
     * JSON format style.
     * COMPACT: {"setName":{"attrName":value}} - values only, types inferred
     * FULL:
     [{"name":"setName","attributes":[{"name":"attrName","type":"String","value":"x"}]]
     */
    @Builder.Default
    private JsonFormatStyle formatStyle = JsonFormatStyle.COMPACT;

    /**

```

```

    * Allow relaxed JSON parsing (single quotes, unquoted keys).
    * Default: true
    */
    @Builder.Default
    private boolean relaxedParsing = true;
}

public enum JsonFormatStyle {
    /**
     * Compact format: {"setName":{"attrName":value,...},...}
     * Types are inferred from JSON value types.
     */
    COMPACT,

    /**
     * Full structure matching DynamicAttributeSet model:
     *
     * [{"name":"setName","attributes":[{"name":"attrName","type":"Type","value":val}]}]
     */
    FULL
}

```

5.1.5. Updated ImportProfile

```

public class ImportProfile extends BaseModel {
    // ... existing fields ...

    //
    //
    // DYNAMIC ATTRIBUTE CONFIGURATION
    //
    //
    /**
     * Strategy for importing dynamic attributes.
     * Default: NONE (disabled)
     */
    @Builder.Default
    private DynamicAttributeImportStrategy dynamicAttributeStrategy =
        DynamicAttributeImportStrategy.NONE;

    /**
     * Strategy for merging imported dynamic attributes with existing.
     * Default: MERGE
     */
    @Builder.Default
    private DynamicAttributeMergeStrategy dynamicAttributeMergeStrategy =

```

```

        DynamicAttributeMergeStrategy.MERGE;

// --- DOT_NOTATION Configuration ---

/**
 * Prefix for auto-discovery of dynamic attribute columns.
 * Only used when strategy is DOT_NOTATION or HYBRID.
 * Default: "dyn."
 */
@Builder.Default
private String dynamicAttributePrefix = "dyn.";

/**
 * Enable auto-discovery of dynamic attribute columns by prefix.
 * If false, only explicitly mapped columns are processed.
 */
@Builder.Default
private boolean enableDynamicAttributeDiscovery = true;

// --- JSON_COLUMN Configuration ---

/**
 * Configuration for JSON column strategy.
 * Only used when strategy is JSON_COLUMN or HYBRID.
 */
private JsonColumnConfig jsonColumnConfig;

// --- VERTICAL Configuration ---

/**
 * Configuration for vertical format strategy.
 * Only used when strategy is VERTICAL.
 */
private VerticalFormatConfig verticalFormatConfig;

// --- Common Configuration ---

/**
 * Explicit mappings for dynamic attribute columns.
 * Used for DOT_NOTATION when auto-discovery is disabled,
 * or to override inferred types/settings.
 */
private List<DynamicAttributeMapping> dynamicAttributeMappings;

/**
 * Reference to DynamicAttributeSetDefinition for type/validation lookup.
 * If specified, validates imported attributes against this definition.
 */
private String dynamicAttributeDefinitionRefName;

/**

```

```

    * If true, only allow attributes defined in the DynamicAttributeSetDefinition.
    * Unknown attributes will cause validation errors.
    * Default: false (allow any attributes)
    */
    @Builder.Default
    private boolean strictDynamicAttributeValidation = false;

    /**
     * Default type when type cannot be inferred.
     * Default: String
     */
    @Builder.Default
    private DynamicAttributeType defaultDynamicAttributeType =
        DynamicAttributeType.String;

    /**
     * Date format for parsing Date type attributes.
     * Default: "yyyy-MM-dd"
     */
    @Builder.Default
    private String dynamicAttributeDateFormat = "yyyy-MM-dd";

    /**
     * DateTime format for parsing DateTime type attributes.
     * Default: "yyyy-MM-dd'T'HH:mm:ss"
     */
    @Builder.Default
    private String dynamicAttributeDateTimeFormat = "yyyy-MM-dd'T'HH:mm:ss";
}

```

5.2. Processing Pipeline

5.2.1. Overall Flow

CSV File

|
□

0. Strategy Detection

- Read ImportProfile.dynamicAttributeStrategy
- Route to appropriate processor

|

| | | |
|--------------|---|---------------------------|
| DOT_NOTATION | → | □ DotNotationProcessor |
| JSON_COLUMN | → | □ JsonColumnProcessor |
| VERTICAL | → | □ VerticalFormatProcessor |

5.2.2. DOT_NOTATION Processing Pipeline

CSV Row

|
□

1. Header Parsing (once per import)
 - Identify columns with "dyn." prefix
 - Parse: dyn.<setName>.<attrName>[:type]
 - Build column → (setName, attrName, type) mapping
 - Validate header format

|
□

2. Regular Column Processing
 - Process non-dynamic columns as before
 - Apply existing transformations

|
□

3. Dynamic Attribute Extraction
 - For each dyn.* column with non-empty value:
 - a. Get parsed header info (setName, attrName)
 - b. Determine type (explicit > definition > inferred)
 - c. Convert string value to typed value
 - d. Create DynamicAttribute object
 - Group attributes by set name

|
□

4. Set Assembly
 - Create DynamicAttributeSet for each set name
 - Populate with collected attributes

|
□

5.2.3. JSON_COLUMN Processing Pipeline

CSV Row

|
[]

1. Locate JSON Column

- Find column by name (default: "dynamicAttributes")
- Skip if empty/null

|
[]

2. Parse JSON

- If COMPACT format:
Parse {"setName":{"attrName":value,...},...}
Infer types from JSON value types
- If FULL format:
Parse as List<DynamicAttributeSet>
Use explicit types from structure
- Handle relaxed JSON if enabled

|
[]

3. Build Attribute Sets

- Create DynamicAttributeSet for each entry
- Create DynamicAttribute for each nested entry
- Map JSON types to DynamicAttributeType

|
[]

[Merge & Validate] ———> Bean with dynamicAttributeSets

5.2.4. VERTICAL Processing Pipeline

CSV File (grouped by entity)

|
[]

1. Group Rows by Entity Key
 - Read all rows
 - Group by `_entityKey` column value
 - Each group becomes one entity

|
 |

2. For Each Entity Group

- a. Extract entity fields (if `allowEntityFieldsOnRows`)
 - Use first row's values for non-attribute columns

- b. Collect attributes from all rows in group
 - Read `_attrSet`, `_attrName`, `_attrType`, `_attrValue`
 - Group by set name

- c. Build `DynamicAttributeSets`
 - Create set for each unique `_attrSet` value
 - Add attributes to appropriate set

|
 |

3. Entity Resolution
 - If entity exists (lookup by `entityKeyField`):
Apply merge strategy with existing
 - If entity is new:
Create with collected attributes

|
|
[Validate] ———| Entities with dynamicAttributeSets

5.2.5. HYBRID Processing Pipeline

CSV Row

|
|

| 1. Process DOT_NOTATION columns first |
| - Extract dyn.* columns |
| - Build initial attribute sets |

|
|

| 2. Process JSON_COLUMN |
| - Parse JSON column |
| - Merge with DOT_NOTATION results: |
| * Same set+attr: JSON value overwrites |
| * New attrs: Added to sets |
| * New sets: Added to list |

|
|

[Merge & Validate] ———| Bean with dynamicAttributeSets

5.2.6. Common: Merge & Validate Stage

Collected Dynamic Attributes

|
|

| Merge with Existing (if updating) |
| - REPLACE: Clear existing sets, add new |
| - MERGE: Update existing attrs, add new attrs/sets |
| - APPEND: Only add attrs that don't exist |

|
|

Validation

- If DynamicAttributeSetDefinition exists:
 - a. Validate required attributes are present
 - b. Validate types match definition
 - c. Validate Select/MultiSelect values are allowed
- If strictDynamicAttributeValidation:
 - d. Reject unknown attributes not in definition

|
□

Bean with populated dynamicAttributeSets

5.3. New SPI: DynamicAttributeProcessor

```
package com.e2eq.framework.imports.spi;

/**
 * Processes dynamic attribute columns during CSV import.
 */
@ApplicationScoped
public class DynamicAttributeProcessor {

    @Inject
    DynamicAttributeSetDefinitionRepo definitionRepo;

    /**
     * Parse a dynamic attribute header.
     *
     * @param header the CSV header (e.g., "dyn.logistics.weight:Double")
     * @param prefix the dynamic attribute prefix (default "dyn.")
     * @return parsed header info, or null if not a dynamic attribute column
     */
    public ParsedDynamicHeader parseHeader(String header, String prefix) {
        if (!header.startsWith(prefix)) {
            return null;
        }

        String remainder = header.substring(prefix.length());
        // Parse: setName.attrName[:type]
        int typeIdx = remainder.lastIndexOf(':');
        String path;
        DynamicAttributeType explicitType = null;

        if (typeIdx > 0) {
            path = remainder.substring(0, typeIdx);
            String typeStr = remainder.substring(typeIdx + 1);
            try {
```

```

        explicitType = DynamicAttributeType.fromValue(typeStr);
    } catch (IllegalArgumentException e) {
        // Invalid type, treat as part of name
        path = remainder;
    }
} else {
    path = remainder;
}

int dotIdx = path.indexOf('.');
if (dotIdx <= 0 || dotIdx >= path.length() - 1) {
    return null; // Invalid format
}

String setName = path.substring(0, dotIdx);
String attrName = path.substring(dotIdx + 1);

return new ParsedDynamicHeader(header, setName, attrName, explicitType);
}

/**
 * Process dynamic attribute columns for a row.
 *
 * @param bean the target bean
 * @param rowData all column values
 * @param parsedHeaders map of column name to parsed header info
 * @param profile the import profile
 * @param context the import context
 * @return result with any errors
 */
public ProcessResult processDynamicAttributes(
    BaseModel bean,
    Map<String, Object> rowData,
    Map<String, ParsedDynamicHeader> parsedHeaders,
    ImportProfile profile,
    ImportContext context) {

    // Check if bean has dynamicAttributeSets field
    List<DynamicAttributeSet> sets = getDynamicAttributeSets(bean);
    if (sets == null) {
        return ProcessResult.skip("Bean does not support dynamic attributes");
    }

    // Load definition if specified
    DynamicAttributeSetDefinition definition = loadDefinition(profile, context);

    // Group columns by set name
    Map<String, List<AttributeValue>> bySet = new LinkedHashMap<>();

    for (Map.Entry<String, ParsedDynamicHeader> entry : parsedHeaders.entrySet())
{

```

```

        Object value = rowData.get(entry.getKey());
        if (value == null || value.toString().trim().isEmpty()) {
            continue; // Skip empty values
        }

        ParsedDynamicHeader parsed = entry.getValue();
        DynamicAttributeType type = determineType(parsed, value, definition);
        Object typedValue = convertValue(value.toString(), type, profile);

        bySet.computeIfAbsent(parsed.getSetName(), k -> new ArrayList<>())
            .add(new AttributeValue(parsed.getAttrName(), type, typedValue));
    }

    // Apply merge strategy
    applyMergeStrategy(sets, bySet, profile.getDynamicAttributeMergeStrategy());

    // Validate against definition if present
    if (definition != null) {
        List<String> errors = validateAgainstDefinition(sets, definition);
        if (!errors.isEmpty()) {
            return ProcessResult.error(String.join("; ", errors));
        }
    }

    return ProcessResult.success();
}

// ... helper methods ...
}

@Data
@AllArgsConstructor
public class ParsedDynamicHeader {
    private String originalHeader;
    private String setName;
    private String attrName;
    private DynamicAttributeType explicitType;
}

```

5.4. Type Inference Logic

```

public DynamicAttributeType inferType(String value) {
    if (value == null || value.isEmpty()) {
        return DynamicAttributeType.String;
    }

    // Boolean
    if ("true".equalsIgnoreCase(value) || "false".equalsIgnoreCase(value)) {
        return DynamicAttributeType.Boolean;
    }
}

```

```

}

// Integer
try {
    Integer.parseInt(value);
    return DynamicAttributeType.Integer;
} catch (NumberFormatException e) { }

// Long
try {
    Long.parseLong(value);
    return DynamicAttributeType.Long;
} catch (NumberFormatException e) { }

// Double
try {
    Double.parseDouble(value);
    return DynamicAttributeType.Double;
} catch (NumberFormatException e) { }

// Date (common formats)
if (isDateFormat(value)) {
    return DynamicAttributeType.Date;
}

// DateTime
if (isDateTimeFormat(value)) {
    return DynamicAttributeType.DateTime;
}

// Default to String
return DynamicAttributeType.String;
}

```

5.5. Merge Strategy Implementation

```

private void applyMergeStrategy(
    List<DynamicAttributeSet> existingSets,
    Map<String, List<AttributeValue>> importedBySet,
    DynamicAttributeMergeStrategy strategy) {

    switch (strategy) {
        case REPLACE:
            existingSets.clear();
            // Fall through to add all imported
        case MERGE:
        case APPEND:
            for (Map.Entry<String, List<AttributeValue>> entry : importedBySet
                .entrySet()) {

```



```

String setName = entry.getKey();
List<AttributeValue> importedAttrs = entry.getValue();

DynamicAttributeSet existingSet = findSetByName(existingSets, setName
);

if (existingSet == null) {
    // Create new set
    existingSet = new DynamicAttributeSet();
    existingSet.setName(setName);
    existingSet.setAttributes(new ArrayList<>());
    existingSets.add(existingSet);
}

for (AttributeValue av : importedAttrs) {
    DynamicAttribute existing = findAttrByName(existingSet
.getAttributes(), av.name);

    if (existing == null) {
        // Add new attribute
        DynamicAttribute attr = new DynamicAttribute();
        attr.setId(UUID.randomUUID().toString());
        attr.setName(av.name);
        attr.setType(av.type);
        attr.setValue(av.value);
        existingSet.getAttributes().add(attr);
    } else if (strategy == DynamicAttributeMergeStrategy.MERGE) {
        // Update existing
        existing.setType(av.type);
        existing.setValue(av.value);
    }
    // APPEND: skip if exists
}
}
break;
}
}

```

Chapter 6. CSV Examples

6.1. DOT_NOTATION Strategy Examples

6.1.1. Example 1: Simple Dynamic Attributes

```
refName,displayName,dyn.specs.color,dyn.specs.size,dyn.specs.weight:Double
prod-001,Red Widget,Red,Large,2.5
prod-002,Blue Gadget,Blue,Medium,1.8
```

6.1.2. Example 2: Multiple Attribute Sets

```
sku,name,dyn.logistics.weight:Double,dyn.logistics.hazmat:Boolean,dyn.compliance.ce_ma
rk:Boolean,dyn.compliance.rohs:Boolean
WGT-001,Widget Pro,2.5,false,true,true
GDG-002,Gadget X,1.2,false,true,false
```

6.1.3. Example 3: With Type Suffix

```
refName,dyn.dates.manufactured:Date,dyn.dates.expires:Date,dyn.counts.inventory:Intege
r
item-001,2024-01-15,2025-01-15,500
item-002,2024-02-20,2025-02-20,250
```

6.1.4. Example 4: Sparse Attributes (Optional)

```
refName,dyn.optional.note,dyn.optional.priority:Integer,dyn.optional.reviewed:Boolean
item-001,Important item,1,true
item-002,,,
item-003,Standard item,,false
```

In row 2, **note**, **priority**, and **reviewed** are all empty - these attributes won't be created. In row 3, only **note** and **reviewed** are set.

6.2. JSON_COLUMN Strategy Examples

6.2.1. Example 5: Compact JSON Format

```
refName,displayName,dynamicAttributes
prod-001,Red
Widget,{"specs":{"color":"Red","size":"Large","weight":2.5}}
prod-002,Blue
```

```
Gadget,{"specs":{"color":"Blue","size":"Medium"},"compliance":{"ce_mark":true}}
```

6.2.2. Example 6: Relaxed JSON (Single Quotes)

With `relaxedParsing: true`:

```
refName,displayName,dynamicAttributes
prod-001,Red Widget,{"specs":{"color':'Red','weight':2.5}}
prod-002,Blue Gadget,{"specs":{"color':'Blue'},'compliance':{'rohs':true}}
```

6.2.3. Example 7: Full Structure JSON

With `formatStyle: FULL`:

```
refName,displayName,dynamicAttributeSets
prod-001,Red
Widget,[{"name":"specs","attributes":[{"name":"color","type":"String","value":"Red"},{"name":"weight","type":"Double","value":2.5}]]
```

6.2.4. Example 8: Custom Column Name

With `jsonColumnConfig.columnName: "customAttrs"`:

```
refName,displayName,customAttrs
prod-001,Red Widget,{"specs":{"color":"Red"}}
```

6.3. VERTICAL Strategy Examples

6.3.1. Example 9: Basic Vertical Format

```
_entityKey,_attrSet,_attrName,_attrType,_attrValue
WGT-001,logistics,weight,Double,2.5
WGT-001,logistics,dimensions,String,10x5x3
WGT-001,logistics,hazmat,Boolean,false
WGT-001,compliance,ce_mark,Boolean,true
WGT-001,compliance,certification_date,Date,2024-01-15
GDG-002,logistics,weight,Double,1.2
GDG-002,logistics,dimensions,String,5x5x2
GDG-002,compliance,ce_mark,Boolean,true
```

6.3.2. Example 10: Vertical with Entity Fields

With `allowEntityFieldsOnRows: true`:

```
sku,name,_attrSet,_attrName,_attrValue
WGT-001,Widget Pro,logistics,weight,2.5
WGT-001,Widget Pro,logistics,dimensions,10x5x3
WGT-001,Widget Pro,compliance,ce_mark,true
GDG-002,Gadget X,logistics,weight,1.2
GDG-002,Gadget X,compliance,ce_mark,true
```

6.3.3. Example 11: Vertical with Type Inference

Type column is optional when `_attrType` is omitted:

```
_entityKey,_attrSet,_attrName,_attrValue
WGT-001,specs,color,Red
WGT-001,specs,weight,2.5
WGT-001,specs,active,true
WGT-001,specs,count,42
```

Types inferred: color=String, weight=Double, active=Boolean, count=Integer

6.3.4. Example 12: Custom Column Names

With custom `verticalFormatConfig`:

```
product_sku,set_name,attribute,type,value
WGT-001,logistics,weight,Double,2.5
WGT-001,logistics,hazmat,Boolean,false
```

6.4. HYBRID Strategy Examples

6.4.1. Example 13: Combined DOT_NOTATION + JSON

```
refName,displayName,dyn.specs.color,dyn.specs.size,dynamicAttributes
prod-001,Red Widget,Red,Large,"{"compliance":{"ce_mark":true,"rohs":true}}"
prod-002,Blue Gadget,Blue,Medium,"{"compliance":{"ce_mark":true}}"
```

Result: `specs` set from DOT_NOTATION columns, `compliance` set from JSON.

6.4.2. Example 14: Hybrid with Override

JSON values override DOT_NOTATION for same attribute:

```
refName,dyn.specs.color,dynamicAttributes  
prod-001,Red,"{"specs":{"color":"Dark Red","size":"XL"}}"
```

Result: **color** = "Dark Red" (JSON wins), **size** = "XL" (from JSON only)

Chapter 7. ImportProfile Configuration Examples

7.1. DOT_NOTATION: Auto-Discovery Mode

```
{
  "refName": "product-import-dot-notation",
  "displayName": "Product Import with Dot Notation",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "DOT_NOTATION",
  "enableDynamicAttributeDiscovery": true,
  "dynamicAttributePrefix": "dyn.",
  "dynamicAttributeMergeStrategy": "MERGE"
}
```

7.2. DOT_NOTATION: Explicit Mapping Mode

Map arbitrary column names to dynamic attributes:

```
{
  "refName": "product-import-explicit-mapping",
  "displayName": "Product Import with Explicit Mappings",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "DOT_NOTATION",
  "enableDynamicAttributeDiscovery": false,
  "dynamicAttributeMappings": [
    {
      "sourceColumn": "weight_kg",
      "targetSetName": "logistics",
      "targetAttributeName": "weight",
      "type": "Double"
    },
    {
      "sourceColumn": "is_hazmat",
      "targetSetName": "logistics",
      "targetAttributeName": "hazmat",
      "type": "Boolean"
    },
    {
      "sourceColumn": "ce_certified",
      "targetSetName": "compliance",
      "targetAttributeName": "ce_mark",
      "type": "Boolean"
    }
  ],
  "dynamicAttributeMergeStrategy": "REPLACE"
}
```

```
}
```

7.3. JSON_COLUMN: Compact Format

```
{
  "refName": "product-import-json-compact",
  "displayName": "Product Import with JSON Column",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "JSON_COLUMN",
  "jsonColumnConfig": {
    "columnName": "dynamicAttributes",
    "formatStyle": "COMPACT",
    "relaxedParsing": true
  },
  "dynamicAttributeMergeStrategy": "MERGE"
}
```

7.4. JSON_COLUMN: Full Structure Format

```
{
  "refName": "product-import-json-full",
  "displayName": "Product Import with Full JSON Structure",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "JSON_COLUMN",
  "jsonColumnConfig": {
    "columnName": "dynamicAttributeSets",
    "formatStyle": "FULL",
    "relaxedParsing": false
  },
  "dynamicAttributeMergeStrategy": "REPLACE"
}
```

7.5. VERTICAL: Basic Configuration

```
{
  "refName": "product-attributes-vertical",
  "displayName": "Product Attributes Vertical Import",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "VERTICAL",
  "verticalFormatConfig": {
    "entityKeyColumn": "_entityKey",
    "entityKeyField": "sku",
    "setNameColumn": "_attrSet",
    "attrNameColumn": "_attrName",
    "attrTypeColumn": "_attrType",
  }
}
```

```

    "attrValueColumn": "_attrValue",
    "allowEntityFieldsOnRows": false
  },
  "dynamicAttributeMergeStrategy": "MERGE"
}

```

7.6. VERTICAL: With Entity Fields on Rows

```

{
  "refName": "product-vertical-with-fields",
  "displayName": "Product Vertical with Entity Fields",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "VERTICAL",
  "verticalFormatConfig": {
    "entityKeyColumn": "sku",
    "entityKeyField": "sku",
    "setNameColumn": "attr_set",
    "attrNameColumn": "attr_name",
    "attrTypeColumn": "attr_type",
    "attrValueColumn": "attr_value",
    "allowEntityFieldsOnRows": true,
    "excludeFromEntityFields": ["attr_set", "attr_name", "attr_type", "attr_value"]
  },
  "dynamicAttributeMergeStrategy": "APPEND"
}

```

7.7. HYBRID: Combined Strategy

```

{
  "refName": "product-import-hybrid",
  "displayName": "Product Import with Hybrid Strategy",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "HYBRID",
  "dynamicAttributePrefix": "dyn.",
  "enableDynamicAttributeDiscovery": true,
  "jsonColumnConfig": {
    "columnName": "extraAttributes",
    "formatStyle": "COMPACT",
    "relaxedParsing": true
  },
  "dynamicAttributeMergeStrategy": "MERGE"
}

```


7.8. With Definition Validation

```
{
  "refName": "validated-product-import",
  "displayName": "Product Import with Strict Validation",
  "targetCollection": "com.example.Product",
  "dynamicAttributeStrategy": "DOT_NOTATION",
  "enableDynamicAttributeDiscovery": true,
  "dynamicAttributePrefix": "dyn.",
  "dynamicAttributeDefinitionRefName": "product-attributes-definition",
  "strictDynamicAttributeValidation": true,
  "dynamicAttributeMergeStrategy": "MERGE"
}
```

7.9. Complete Example with All Options

```
{
  "refName": "full-product-import-profile",
  "displayName": "Complete Product Import Profile",
  "description": "Demonstrates all dynamic attribute options",
  "targetCollection": "com.example.Product",

  "dynamicAttributeStrategy": "HYBRID",
  "dynamicAttributeMergeStrategy": "MERGE",

  "dynamicAttributePrefix": "dyn.",
  "enableDynamicAttributeDiscovery": true,

  "jsonColumnConfig": {
    "columnName": "jsonAttrs",
    "formatStyle": "COMPACT",
    "relaxedParsing": true
  },

  "dynamicAttributeMappings": [
    {
      "sourceColumn": "weight_lbs",
      "targetSetName": "logistics",
      "targetAttributeName": "weight_pounds",
      "type": "Double"
    }
  ],

  "dynamicAttributeDefinitionRefName": "product-attrs-def",
  "strictDynamicAttributeValidation": false,
  "defaultDynamicAttributeType": "String",
  "dynamicAttributeDateFormat": "MM/dd/yyyy",
  "dynamicAttributeDateTimeFormat": "MM/dd/yyyy HH:mm"
}
```

}

Chapter 8. Processing Order Integration

The dynamic attribute processing integrates into the existing CSV import pipeline:

1. CSV parsing with `CellProcessors`
2. Field calculators (timestamps, UUIDs, templates)
3. `RowValueResolvers` (arbitrary code with full row access)
4. `DynamicAttributeProcessor` (dynamic attribute import)
5. Pre-validation transformers
6. Bean validation

Chapter 9. RowValueResolver: Arc CDI Bean Integration

9.1. Overview

The `RowValueResolver` SPI provides a powerful mechanism for running arbitrary code during CSV import. Unlike static lookups or simple transformations, RowValueResolvers have access to:

- The entire row data (all columns)
- Full CDI injection capabilities (services, repositories, etc.)
- The import context (profile, realm, row number, session)

Key Feature: Since RowValueResolvers are Arc CDI beans, you can inject any other service and update multiple collections from a single CSV row.

9.2. Basic Implementation

```
@ApplicationScoped
public class SkuResolver implements RowValueResolver {

    @Inject
    ProductService productService;

    @Override
    public String getName() {
        return "skuResolver";
    }

    @Override
    public ResolveResult resolve(String inputValue, Map<String, Object> rowData,
    ImportContext context) {
        String category = (String) rowData.get("category");
        String vendor = (String) rowData.get("vendor");

        String resolvedSku = productService.findOrCreateSku(inputValue, category,
        vendor);

        if (resolvedSku != null) {
            return ResolveResult.success(resolvedSku);
        } else {
            return ResolveResult.error("Could not resolve SKU for: " + inputValue);
        }
    }
}
```

9.3. Multi-Collection Updates

Since RowValueResolvers are Arc beans, you can inject multiple repositories and update multiple collections from a single CSV row:

```
@ApplicationScoped
public class OrderLineResolver implements RowValueResolver {

    @Inject
    OrderRepo orderRepo;

    @Inject
    InventoryRepo inventoryRepo;

    @Inject
    AuditLogRepo auditLogRepo;

    @Override
    public String getName() {
        return "orderLineResolver";
    }

    @Override
    public ResolveResult resolve(String inputValue, Map<String, Object> rowData,
    ImportContext context) {
        String orderId = (String) rowData.get("order_id");
        String productSku = (String) rowData.get("product_sku");
        Integer quantity = Integer.parseInt((String) rowData.get("quantity"));

        // Update inventory (different collection)
        inventoryRepo.decrementStock(productSku, quantity, context.getRealmId());

        // Create audit log entry (another collection)
        AuditLog log = AuditLog.builder()
            .action("IMPORT_ORDER_LINE")
            .entityRef(orderId)
            .details("Imported line for SKU: " + productSku)
            .build();
        auditLogRepo.save(log);

        // Return the value for the main entity being imported
        return ResolveResult.success(productSku);
    }
}
```

9.4. Available Injections

RowValueResolvers can inject any Arc/CDI bean:

| Injection Type | Example |
|----------------------|--|
| Repositories | <code>@Inject ProductRepo productRepo;</code> |
| Services | <code>@Inject EmailService emailService;</code> |
| Configuration | <code>@ConfigProperty(name="app.import.threshold") int threshold;</code> |
| Other Resolvers | <code>@Inject Instance<RowValueResolver> allResolvers;</code> |
| MicroProfile Clients | <code>@Inject @RestClient ExternalApiClient client;</code> |

9.5. Configuration in ImportProfile

Configure a RowValueResolver in your ColumnMapping:

```
{
  "refName": "order-import-profile",
  "targetCollection": "com.example.Order",
  "columnMappings": [
    {
      "sourceColumn": "product_code",
      "targetField": "sku",
      "rowValueResolverName": "skuResolver"
    },
    {
      "sourceColumn": "line_data",
      "targetField": "lineInfo",
      "rowValueResolverName": "orderLineResolver"
    }
  ]
}
```

9.6. Result Types

| Result | Usage |
|--|--|
| <code>ResolveResult.success(value)</code> | Set the field to the resolved value |
| <code>ResolveResult.passthrough(original)</code> | Keep the original value unchanged |
| <code>ResolveResult.nullValue()</code> | Set the field to null |
| <code>ResolveResult.skip()</code> | Skip this row (no error, just don't process) |
| <code>ResolveResult.skip(reason)</code> | Skip with a reason (logged but not an error) |
| <code>ResolveResult.error(message)</code> | Mark the row as an error |

9.7. ImportContext Information

The `ImportContext` provides access to:

| Method | Returns |
|-------------------------------|--|
| <code>getProfile()</code> | The <code>ImportProfile</code> configuration |
| <code>getTargetClass()</code> | The class being imported |
| <code>getRealmId()</code> | The realm/tenant ID |
| <code>getRowIndex()</code> | Current row number (1-based) |
| <code>getSessionId()</code> | The import session ID |

9.8. Advanced: Conditional Processing

```
@ApplicationScoped
public class ConditionalResolver implements RowValueResolver {

    @Inject
    ConfigService configService;

    @Override
    public String getName() {
        return "conditionalResolver";
    }

    @Override
    public boolean appliesTo(Class<?> targetClass) {
        // Only apply to Order entities
        return Order.class.isAssignableFrom(targetClass);
    }

    @Override
    public int getOrder() {
        // Run before other resolvers (lower = earlier)
        return 50;
    }

    @Override
    public ResolveResult resolve(String inputValue, Map<String, Object> rowData,
        ImportContext context) {
        // Check configuration
        if (!configService.isFeatureEnabled("advanced-import", context.getRealmId()))
        {
            return ResolveResult.passthrough(inputValue);
        }

        // Skip certain rows based on data
        String status = (String) rowData.get("status");
```

```

    if ("CANCELLED".equals(status)) {
        return ResolveResult.skip("Skipping cancelled orders");
    }

    // Process normally
    return ResolveResult.success(processValue(inputValue, rowData));
}
}

```

9.9. Testing RowValueResolvers

```

@QuarkusTest
class SkuResolverTest {

    @Inject
    SkuResolver resolver;

    @Test
    void testResolveSuccess() {
        Map<String, Object> rowData = Map.of(
            "category", "electronics",
            "vendor", "acme"
        );
        ImportContext context = ImportContext.builder()
            .realmId("test-realm")
            .rowNumber(1)
            .build();

        RowValueResolver.ResolveResult result = resolver.resolve("PROD-001", rowData,
context);

        assertTrue(result.isSuccess());
        assertNotNull(result.getValue());
    }
}

```


Chapter 10. Edge Cases and Error Handling

10.1. Empty/Null Values

- Empty string → attribute not created (sparse support)
- Explicit null marker (configurable, e.g., "NULL") → attribute created with null value

10.2. Type Mismatches

- If type is explicit or from definition, conversion failure → error
- If type is inferred, use String as fallback

10.3. Invalid Header Format

- `dyn.` with no dot after set name → warning, skip column
- `dyn.setname` with no attribute name → warning, skip column

10.4. Missing Required Attributes

- If `DynamicAttributeSetDefinition` specifies `required=true`, validate presence
- Report all missing required attributes as validation errors

10.5. Unknown Sets/Attributes

- By default, allow any set/attribute names (schema-less)
- If `strictMode=true` in profile, only allow defined sets/attributes

Chapter 11. Implementation Components

11.1. New Model Classes

| Component | Package | Description |
|--------------------------------|---|---|
| DynamicAttributeImportStrategy | com.e2eq.framework.model.persistent.imports | Enum: NONE, DOT_NOTATION, JSON_COLUMN, VERTICAL, HYBRID |
| DynamicAttributeMergeStrategy | com.e2eq.framework.model.persistent.imports | Enum: REPLACE, MERGE, APPEND |
| DynamicAttributeMapping | com.e2eq.framework.model.persistent.imports | Configuration for mapping CSV columns to dynamic attributes |
| JsonColumnConfig | com.e2eq.framework.model.persistent.imports | Configuration for JSON_COLUMN strategy |
| JsonFormatStyle | com.e2eq.framework.model.persistent.imports | Enum: COMPACT, FULL |
| VerticalFormatConfig | com.e2eq.framework.model.persistent.imports | Configuration for VERTICAL strategy |
| ParsedDynamicHeader | com.e2eq.framework.imports.service | Parsed dynamic attribute header info for DOT_NOTATION |

11.2. New Service Classes

| Component | Package | Description |
|-------------------------------|------------------------------------|--|
| DynamicAttributeImportService | com.e2eq.framework.imports.service | Main orchestrator for dynamic attribute processing |
| DotNotationProcessor | com.e2eq.framework.imports.service | Processes DOT_NOTATION strategy columns |
| JsonColumnProcessor | com.e2eq.framework.imports.service | Processes JSON_COLUMN strategy |
| VerticalFormatProcessor | com.e2eq.framework.imports.service | Processes VERTICAL strategy with row grouping |
| DynamicAttributeTypeInferer | com.e2eq.framework.imports.service | Type inference from string values |
| DynamicAttributeMerger | com.e2eq.framework.imports.service | Applies merge strategies (REPLACE, MERGE, APPEND) |
| DynamicAttributeValidator | com.e2eq.framework.imports.service | Validates against DynamicAttributeSetDefinition |

11.3. Enhanced Existing Classes

| Component | Package | Description |
|----------------------------------|---|--|
| ImportProfile (enhanced) | com.e2eq.framework.model.persistent.imports | New fields for dynamic attribute configuration |
| ImportProfilesService (enhanced) | com.e2eq.framework.imports.service | Integration with DynamicAttributeImportService |
| CSVImportHelper (enhanced) | com.e2eq.framework.util | Strategy detection and processor routing |

Chapter 12. Future Considerations

1. **Nested Attributes:** Support for nested objects within attribute values (e.g., `dyn.address.coordinates.lat`)
2. **Multi-Value Attributes:** Support for MultiSelect with comma-separated values or JSON arrays
3. **Inheritance:** Respect `inheritable` flag when merging with parent entities
4. **Export Symmetry:** Ensure CSV export uses same conventions for round-trip imports
5. **Bulk Operations:** Streaming processor for VERTICAL strategy with very large files
6. **Mixed Entity Types:** VERTICAL format with multiple entity types in same file
7. **Attribute Templates:** Pre-defined attribute set templates for common patterns
8. **Change Detection:** Only update attributes that actually changed

Chapter 13. Summary

13.1. Dynamic Attribute Import Strategies

The design supports **four import strategies** for dynamic attributes, each suited to different use cases:

| Strategy | Description |
|---------------------|---|
| DOT_NOTATION | Spreadsheet-friendly with <code>dyn.setName.attrName[:type]</code> column headers. Best for human-edited CSV files with known attribute structures. |
| JSON_COLUMN | Single JSON column containing all attributes. Best for programmatic imports or complex/variable attribute structures. |
| VERTICAL | Multiple rows per entity with one attribute per row. Best for attribute-centric workflows or bulk attribute loading. |
| HYBRID | Combines DOT_NOTATION and JSON_COLUMN. Allows spreadsheet columns for common attributes with JSON for extras. |

All strategies share common features:

- **Merge Strategies:** REPLACE, MERGE, APPEND for handling existing attributes
- **Type Handling:** Explicit types, definition lookup, or inference
- **Validation:** Optional validation against `DynamicAttributeSetDefinition`
- **Sparse Support:** Missing/empty values handled gracefully

13.2. RowValueResolver: Extensible Import Logic

The `RowValueResolver` SPI enables powerful, custom import logic:

- **Arc CDI Beans:** Full dependency injection support
- **Multi-Collection Updates:** Update multiple collections from a single row
- **Full Row Access:** Read any column value, not just the mapped column
- **Context Awareness:** Access to realm, session, row number, and profile
- **Flexible Results:** Return values, skip rows, or report errors

13.3. Implementation Summary

The implementation includes:

13.3.1. Model Classes (quantum-models)

- `DynamicAttributeImportStrategy` - NONE, DOT_NOTATION, JSON_COLUMN, VERTICAL, HYBRID
- `DynamicAttributeMergeStrategy` - REPLACE, MERGE, APPEND

- `JsonColumnConfig` - Configuration for JSON_COLUMN strategy
- `VerticalFormatConfig` - Configuration for VERTICAL strategy
- `DynamicAttributeMapping` - Explicit column-to-attribute mappings
- `ParsedDynamicHeader` - Parsed header info for DOT_NOTATION
- `DynamicAttributeSupport` - Interface for models supporting dynamic attributes

13.3.2. Service Classes (quantum-framework)

- `DynamicAttributeImportService` - Main orchestrator
- `DotNotationProcessor` - DOT_NOTATION strategy processor
- `JsonColumnProcessor` - JSON_COLUMN strategy processor
- `VerticalFormatProcessor` - VERTICAL strategy processor
- `DynamicAttributeTypeInferer` - Type inference from string values
- `DynamicAttributeMerger` - Merge strategy implementation

13.3.3. Integration Points

- `ImportProfile` - Extended with dynamic attribute configuration
- `CSVImportHelper` - Integrated for automatic processing
- `RowValueResolver` - Arc CDI bean SPI for custom logic