OpenAI

February 11, 2026 Engineering

Harness engineering: leveraging Codex in an agent-first world

By Ryan Lopopolo, Member of the Technical Staff

Listen to article 18:08

Share

The product has internal daily users and external alpha testers. It ships, deploys, breaks, and gets fixed. What's different is that every line of code—application logic, tests, CI configuration, documentation, observability, and internal tooling—has been written by Codex. We estimate that we built this in about 1/10th the time it would have taken to write the code by hand.

Humans steer. Agents execute.

We intentionally chose this constraint so we would build what was necessary to increase engineering velocity by orders of magnitude. We had weeks to ship what ended up being a million lines of code. To do that, we needed to understand what changes when a software engineering team's primary job is no longer to write code, but to design environments, specify intent, and build feedback loops that allow Codex agents to do reliable work.

This post is about what we learned by building a brand new product with a team of agents—what broke, what compounded, and how to maximize our one truly scarce resource: human time and attention.

We started with an empty git repository

The first commit to an empty repository landed in late August 2025.

The initial scaffold—repository structure, CI configuration, formatting rules, package manager setup, and application framework—was generated by Codex CLI using GPT-5, guided by a small set of existing templates. Even the initial AGENTS.md file that directs agents how to work in the repository was itself written by Codex.

There was no pre-existing human-written code to anchor the system. From the beginning, the repository was shaped by the agent.

Five months later, the repository contains on the order of a million lines of code across application logic, infrastructure, tooling, documentation, and internal developer

throughput of 3.5 PRs per engineer per day, and surprisingly the throughput has *increased* as the team has grown to now seven engineers. Importantly, this wasn't output for output's sake: the product has been used by hundreds of users internally, including daily internal power users.

Throughout the development process, humans never directly contributed any code. This became a core philosophy for the team: **no manually-written code**.

Redefining the role of the engineer

The lack of hands-on human coding **introduced a different kind of engineering work, focused on systems, scaffolding, and leverage**.

Early progress was slower than we expected, not because Codex was incapable, but because the environment was underspecified. The agent lacked the tools, abstractions, and internal structure required to make progress toward high-level goals. The primary job of our engineering team became enabling the agents to do useful work.

In practice, this meant working depth-first: breaking down larger goals into smaller building blocks (design, code, review, test, etc), prompting the agent to construct those blocks, and using them to unlock more complex tasks. When something failed, the fix was almost never "try harder." Because the only way to make progress was to get Codex to do the work, human engineers always stepped into the task and asked: "what capability is missing, and how do we make it both legible and enforceable for the agent?"


Humans interact with the system almost entirely through prompts: an engineer describes a task, runs the agent, and allows it to open a pull request. To drive a PR to completion, we instruct Codex to review its own changes locally, request additional specific agent reviews both locally and in the cloud, respond to any human or agent given feedback, and iterate in a loop until all agent reviewers are satisfied (effectively this is a Ralph Wiggum Loop). Codex uses our standard development tools directly (gh, local scripts, and repository-embedded skills) to gather context without humans


Humans may review pull requests, but aren't required to. Over time, we've pushed almost all review effort towards being handled agent-to-agent.

Increasing application legibility

As code throughput increased, our bottleneck became human QA capacity. Because the fixed constraint has been human time and attention, we've worked to add more capabilities to the agent by making things like the application UI, logs, and app metrics themselves directly legible to Codex.

For example, we made the app bootable per git worktree, so Codex could launch and drive one instance per change. We also wired the Chrome DevTools Protocol into the agent runtime and created skills for working with DOM snapshots, screenshots, and navigation. This enabled Codex to reproduce bugs, validate fixes, and reason about UI behavior directly.






We did the same for observability tooling. Logs, metrics, and traces are exposed to Codex via a local observability stack that's ephemeral for any given worktree. Codex works on a fully isolated version of that app—including its logs and metrics, which get torn down once that task is complete. Agents can query logs with LogQL and metrics with PromQL. With this context available, prompts like "ensure service startup completes in under 800ms" or "no span in these four critical user journeys exceeds two seconds" become tractable.

Giving Codex a full observability stack

OpenAI


APP
OTLP METRICS
OTLP TRACES
VECTOR
Fan out
(local)
Observability
stack services
Victoria
Logs
Victoria
Metrics
Victoria
Traces
LogQL
API
PromQL
API
TraceQL
API
Query
Correlate
Reason
CODEX
Implement
change (PR)
+
Restart app
CODEBASE
UI
Feedback loop
Re-run



We regularly see single Codex runs work on a single task for upwards of six hours (often while the humans are sleeping).

We made repository knowledge the system of record

Context management is one of the biggest challenges in making agents effective at large and complex tasks. One of the earliest lessons we learned was simple: **give Codex a map, not a 1,000-page instruction manual.**

We tried the "one big `AGENTS.md`" approach. It failed in predictable ways:

- **Context is a scarce resource.** A giant instruction file crowds out the task, the code, and the relevant docs—so the agent either misses key constraints or starts optimizing for the wrong ones.
- **Too much guidance becomes *non-guidance*.** When everything is "important," nothing is. Agents end up pattern-matching locally instead of navigating intentionally.
- **It rots instantly.** A monolithic manual turns into a graveyard of stale rules. Agents can't tell what's still true, humans stop maintaining it, and the file quietly becomes an attractive nuisance.
- **It's hard to verify.** A single blob doesn't lend itself to mechanical checks (coverage, freshness, ownership, cross-links), so drift is inevitable.

So instead of treating `AGENTS.md` as the encyclopedia, we treat it as **the table of contents**.

serves primarily as a map, with pointers to deeper sources of truth elsewhere.

Plain Text

```
AGENTS.md
ARCHITECTURE.md
docs/
├── design-docs/
│   ├── index.md
│   ├── core-beliefs.md
│   └── ...
├── exec-plans/
│   ├── active/
│   ├── completed/
│   └── tech-debt-tracker.md
├── generated/
│   └── db-schema.md
├── product-specs/
│   ├── index.md
│   ├── new-user-onboarding.md
│   └── ...
├── references/
│   ├── design-system-reference-llms.txt
│   ├── nixpacks-llms.txt
│   ├── uv-llms.txt
│   └── ...
└── DESIGN.md
```

In-repository knowledge store layout.

Design documentation is catalogued and indexed, including verification status and a set of core beliefs that define agent-first operating principles. Architecture documentation provides a top-level map of domains and package layering. A quality document grades each product domain and architectural layer, tracking gaps over time.

Plans are treated as first-class artifacts. Ephemeral lightweight plans are used for small changes, while complex work is captured in execution plans with progress and decision logs that are checked into the repository. Active plans, completed plans, and known technical debt are all versioned and co-located, allowing agents to operate without relying on external context.

are taught where to look next, rather than being overwhelmed up front.


We enforce this mechanically. Dedicated linters and CI jobs validate that the knowledge base is up to date, cross-linked, and structured correctly. A recurring "doc-gardening" agent scans for stale or obsolete documentation that does not reflect the real code behavior and opens fix-up pull requests.


Agent legibility is the goal

As the codebase evolved, Codex's framework for design decisions needed to evolve, too.

Because the repository is entirely agent-generated, it's optimized first for *Codex's legibility*. In the same way teams aim to improve navigability of their code for new engineering hires, our human engineers' goal was making it possible for an agent to reason about the full business domain **directly from the repository itself.**

From the agent's point of view, anything it can't access in-context while running effectively doesn't exist. Knowledge that lives in Google Docs, chat threads, or people's heads are not accessible to the system. Repository-local, versioned artifacts (e.g., code, markdown, schemas, executable plans) are all it can see.





We learned that we needed to push more and more context into the repo over time. That Slack discussion that aligned the team on an architectural pattern? If it isn't discoverable to the agent, it's illegible in the same way it would be unknown to a new hire joining three months later.

Giving Codex more context means organizing and exposing the right information so the agent can reason over it, rather than overwhelming it with ad-hoc instructions. In

norms, and team culture (emoji preferences included), giving the agent this information leads to better-aligned output.

This framing clarified many tradeoffs. We favored dependencies and abstractions that could be fully internalized and reasoned about in-repo. Technologies often described as “boring” tend to be easier for agents to model due to composability, api stability, and representation in the training set. In some cases, it was cheaper to have the agent reimplement subsets of functionality than to work around opaque upstream behavior from public libraries. For example, rather than pulling in a generic `p-limit`-style package, we implemented our own map-with-concurrency helper: it’s tightly integrated with our OpenTelemetry instrumentation, has 100% test coverage, and behaves exactly the way our runtime expects.

Pulling more of the system into a form the agent can inspect, validate, and modify directly increases leverage—not just for Codex, but for other agents (e.g. Aardvark) that are working on the codebase as well.


Enforcing architecture and taste

Documentation alone doesn’t keep a fully agent-generated codebase coherent. **By enforcing invariants, not micromanaging implementations, we let agents ship fast without undermining the foundation.** For example, we require Codex to parse data shapes at the boundary, but are not prescriptive on how that happens (the model seems to like Zod, but we didn’t specify that specific library).

Agents are most effective in environments with strict boundaries and predictable structure, so we built the application around a rigid architectural model. Each business domain is divided into a fixed set of layers, with strictly validated dependency directions and a limited set of permissible edges. These constraints are enforced mechanically via custom linters (Codex-generated, of course!) and structural tests.

The diagram below shows the rule: within each business domain (e.g. App Settings), code can only depend “forward” through a fixed set of layers (Types → Config → Repo → Service → Runtime → UI). Cross-cutting concerns (auth, connectors, telemetry

disallowed and enforced mechanically.



allows speed without decay or architectural drift.

In practice, we enforce these rules with custom linters and structural tests, plus a small set of "taste invariants." For example, we statically enforce structured logging, naming conventions for schemas and types, file size limits, and platform-specific reliability requirements with custom lints. Because the lints are custom, we write the error messages to inject remediation instructions into agent context.

In a human-first workflow, these rules might feel pedantic or constraining. With agents, they become multipliers: once encoded, they apply everywhere at once.

At the same time, we're explicit about where constraints matter and where they do not. This resembles leading a large engineering platform organization: enforce boundaries centrally, allow autonomy locally. You care deeply about boundaries, correctness, and reproducibility. Within those boundaries, you allow teams—or agents—significant freedom in how solutions are expressed.

The resulting code does not always match human stylistic preferences, and that's okay. As long as the output is correct, maintainable, and legible to future agent runs, it meets the bar.

Human taste is fed back into the system continuously. Review comments, refactoring pull requests, and user-facing bugs are captured as documentation updates or encoded directly into tooling. When documentation falls short, we promote the rule into code

Throughput changes the merge philosophy

As Codex's throughput increased, many conventional engineering norms became counterproductive.

The repository operates with minimal blocking merge gates. Pull requests are short-lived. Test flakes are often addressed with follow-up runs rather than blocking progress indefinitely. In a system where agent throughput far exceeds human

This would be irresponsible in a low-throughput environment. Here, it's often the right tradeoff.

What "agent-generated" actually means

When we say the codebase is generated by Codex agents, we mean everything in the codebase.

Agents produce:

- Product code and tests
- CI configuration and release tooling
- Internal developer tools
- Documentation and design history
- Evaluation harnesses
- Review comments and responses
- Scripts that manage the repository itself
- Production dashboard definition files

Humans always remain in the loop, but work at a different layer of abstraction than we used to. We prioritize work, translate user feedback into acceptance criteria, and validate outcomes. When the agent struggles, we treat it as a signal: identify what is missing—tools, guardrails, documentation—and feed it back into the repository, always by having Codex itself write the fix.

Agents use our standard development tools directly. They pull review feedback, respond inline, push updates, and often squash and merge their own pull requests.

Increasing levels of autonomy

As more of the development loop was encoded directly into the system—testing

meaningful threshold where Codex can end-to-end drive a new feature.

Given a single prompt, the agent can now:

- Validate the current state of the codebase
- Reproduce a reported bug
- Record a video demonstrating the failure
- Implement a fix
- Validate the fix by driving the application
- Record a second video demonstrating the resolution
- Open a pull request
- Respond to agent and human feedback
- Detect and remediate build failures
- Escalate to a human only when judgment is required
- Merge the change

This behavior depends heavily on the specific structure and tooling of this repository and should not be assumed to generalize without similar investment—at least, not yet.

Entropy and garbage collection

Full agent autonomy also introduces novel problems. Codex replicates patterns that already exist in the repository—even uneven or suboptimal ones. Over time, this inevitably leads to drift.

Initially, humans addressed this manually. Our team used to spend every Friday (20% of the week) cleaning up "AI slop." Unsurprisingly, that didn't scale.

Instead, we started encoding what we call "golden principles" directly into the repository and built a recurring cleanup process. These principles are opinionated, mechanical rules that keep the codebase legible and consistent for future agent runs.

boundaries or rely on typed SDKs so the agent can't accidentally build on guessed shapes. On a regular cadence, we have a set of background Codex tasks that scan for deviations, update quality grades, and open targeted refactoring pull requests. Most of these can be reviewed in under a minute and automerged.

This functions like garbage collection. Technical debt is like a high-interest loan: it's almost always better to pay it down continuously in small increments than to let it compound and tackle it in painful bursts. Human taste is captured once, then enforced continuously on every line of code. This also lets us catch and resolve bad patterns on a daily basis, rather than letting them spread in the code base for days or weeks.

What we're still learning

This strategy has so far worked well up through internal launch and adoption at OpenAI. Building a real product for real users helped anchor our investments in reality and guide us towards long-term maintainability.

What we don't yet know is how architectural coherence evolves over years in a fully agent-generated system. We're still learning where human judgment adds the most leverage and how to encode that judgment so it compounds. We also don't know how this system will evolve as models continue to become more capable over time.

What's become clear: building software still demands discipline, but the discipline shows up more in the scaffolding rather than the code. The tooling, abstractions, and feedback loops that keep the codebase coherent are increasingly important.

Our most difficult challenges now center on designing environments, feedback loops, and control systems that help agents accomplish our goal: build and maintain complex, reliable software at scale.


As agents like Codex take on larger portions of the software lifecycle, these questions will matter even more. We hope that sharing some early lessons helps you reason about where to invest your effort so you can just build things.

OpenAI

Keep reading


View all

Author




Scaling Git at OpenAI

Engineering Nov 2, 2026



Rapidly scaling online storage to serve over 1 billion ChatGPT users (Part II)

Engineering Oct 23, 2026



How we bui stack for us

Engineering

Research

Research Index

Research Overview

Economic Research

Latest Advancements

GPT-6.1 Sol

GPT-6 Astra

GPT-5.6

OpenAI

Safety

Safety Approach

Deployment Safety ↗

Security & Privacy

Trust & Transparency

Products

ChatGPT ↗

ChatGPT Business ↗

ChatGPT Enterprise ↗

ChatGPT for Education ↗

Codex

Dots ↗

Release Notes

API Platform

Overview

API Log In ↗

Docs ↗

Business

Overview

Solutions

Resources

Plugins

Customer Stories

OpenAI

Contact Sales

Developers

Plugins ↗

Models ↗

Docs ↗

Resources ↗

Developer Forum ↗

Company

About Us

Our Charter

Careers

News

Support

Help Center ↗

OpenAI Status ↗

More

Stories

Academy

Supply Co.

Livestreams

Podcast

RSS

OpenAI

Terms of Use

Privacy Policy

Other Policies

OpenAI © 2015–2026 Manage Cookies

English United States