Adding layers

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R



Adam Loy Statistician, Carleton College




Wine data

```
glimpse(wine)
```


```
Rows: 178
Columns: 14
$ Type
                $ Alcohol
                <dbl> 14.23, 13.20, 13.16, 14.37, 13.24, 14.20, 14.3...
$ Malic
                <dbl> 1.71, 1.78, 2.36, 1.95, 2.59, 1.76, 1.87, 2.15...
$ Ash
                <dbl> 2.43, 2.14, 2.67, 2.50, 2.87, 2.45, 2.45, 2.61...
$ Alcalinity
               <dbl> 15.6, 11.2, 18.6, 16.8, 21.0, 15.2, 14.6, 17.6...
$ Color
                <dbl> 5.64, 4.38, 5.68, 7.80, 4.32, 6.75, 5.25, 5.05...
$ Hue
                <dbl> 1.04, 1.05, 1.03, 0.86, 1.04, 1.05, 1.02, 1.06...
$ Dilution
                <dbl> 3.92, 3.40, 3.17, 3.45, 2.93, 2.85, 3.58, 3.58...
$ Proline
                <int> 1065, 1050, 1185, 1480, 735, 1450, 1290, 1295,...
```

Adding a smoother




```
m <- loess(Alcohol ~ Flavanoids, data = wine, span = 1.5)
wine %>%
  plot_ly(x = ~Flavanoids, y = ~Alcohol) %>%
  add_markers() %>%
  add_lines(y = ~fitted(m)) %>%
  layout(showlegend = FALSE)
```

Adding a second smoother



```
m2 <- lm(Alcohol ~ poly(Flavanoids, 2), data = wine)
wine %>%
  plot_ly(x = ~Flavanoids, y = ~Alcohol) %>%
  add_markers(showlegend = FALSE) %>%
  add_lines(y = ~fitted(m), name = "LOESS") %>%
  add_lines(y = ~fitted(m2), name = "Polynomial")
```

Layering densities



Layering densities

```
d1 <- filter(wine, Type == 1)
d2 <- filter(wine, Type == 2)</pre>
d3 <- filter(wine, Type == 3)
density1 <- density(d1$Flavanoids)</pre>
density2 <- density(d2$Flavanoids)</pre>
density3 <- density(d3$Flavanoids)</pre>
plot_ly(opacity = 0.5) %>%
  add_lines(x = \simdensity1$x, y = \simdensity1$y, name = "Type 1") %>%
  add_lines(x = \simdensity2$x, y = \simdensity2$y, name = "Type 2") %>%
  add_lines(x = \simdensity3$x, y = \simdensity3$y, name = "Type 3") %>%
  layout(xaxis = list(title = 'Flavonoids'),
         yaxis = list(title = 'Density'))
```

Let's practice!

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R



Faceting plotly graphics

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R



Adam Loy Statistician, Carleton College



2016 video game sales


glimpse(vgsales2016)

```
Rows: 502
Columns: 16
$ Name
             <fct> FIFA 17, Pokemon Sun/Moon, Unchart...
$ Platform
              <fct> PS4, 3DS, PS4, PS4, PS4, PS4, X0ne...
$ Year
               <int> 2016, 2016, 2016, 2016, 2016, 2016...
              <fct> Sports, Role-Playing, Shooter, Sho...
$ Genre
$ Publisher
              <fct> Electronic Arts, Nintendo, Sony Co...
$ NA_Sales
              <dbl> 0.66, 2.98, 1.85, 1.61, 1.10, 1.35...
$ User_Score
              <fct> 5, NA, 7.9, 3.4, 8.4, 7, 5.5, 3.1,...
$ User_Count
              <int> 398, NA, 7064, 1129, 809, 2219, 20...
$ Developer
              <fct> EA Sports, EA Vancouver, NA, Naugh...
$ Rating
              <fct> E, NA, T, M, M, E, M, M, M, M, ...
```

Representing many categories

```
vgsales2016 %>%

plot_ly(x = ~Critic_Score, y = ~User_Score, color = ~Genre) %>%
  add_markers()
```




A single subplot

```
library(dplyr)
action_df <- vgsales2016 %>%
  filter(Genre == "Action")
glimpse(action_df)
```


A single subplot

```
action_df %>%
  plot_ly(x = ~Critic_Score, y = ~User_Score) %>%
  add_markers()
```



Two subplots

```
p1 <- action_df %>%
  plot_ly(x = ~Critic_Score, y = ~User_Score) %>%
  add_markers()
p2 <- vgsales2016 %>%
  filter(Genre == "Adventure") %>%
  plot_ly(x = ~Critic_Score, y = ~User_Score) %>%
  add_markers()
subplot(p1, p2, nrows = 1)
```




Legends

```
p1 <- plot_ly(x = ~Critic_Score, y = ~User_Score) %>%
   add_markers(name = ~Genre)

p2 <- vgsales2016 %>%
   filter(Genre == "Adventure") %>%
   plot_ly(x = ~Critic_Score, y = ~User_Score) %>%
   add_markers(name = ~Genre)

subplot(p1, p2, nrows = 1)
```




Axis labels

```
subplot(p1, p2, nrows = 1, shareY = TRUE, shareX = TRUE)
```



- Sharing an axis leads to linked interactivity
- If linked interactivity is not desired: use titleX and titleY arguments



```
library(tidyverse)
vgsales2016 %>%
group_by(Genre) %>%
nest()
```

```
# A tibble: 12 × 2
# Groups: Genre [12]
  Genre
              data
              <chr>
             <tibble [48 × 15]>
1 Sports
2 Role-Playing <tibble [54 × 15]>
             <tibble [47 × 15]>
3 Shooter
              <tibble [178 × 15]>
 4 Action
              <tibble [15 × 15]>
5 Platform
 6 Fighting
              <tibble [16 × 15]>
              <tibble [24 × 15]>
7 Racing
8 Adventure
              <tibble [56 × 15]>
9 Misc
              <tibble [32 × 15]>
```

```
library(tidyverse)
vgsales2016 %>%
  group_by(Genre) %>%
  nest() %>%
  mutate(
    plot = map2(data, Genre,
      \(data, Genre)
      plot_ly(data = data,
          x = ~Critic_Score,
          y = ~User_Score) %>%
      add_markers(name = ~Genre)
    ))
```

```
# A tibble: 12 × 3
# Groups:
           Genre [12]
  Genre
               data
                                   plot
  <chr>
               <tibble [48 × 15]>
1 Sports
                                  <plot
2 Role-Playing <tibble [54 × 15]>
                                  <plot
               <tibble [47 × 15]>
 3 Shooter
                                  <plot
               <tibble [178 × 15]> <plot
 4 Action
               <tibble [15 × 15]>
 5 Platform
                                  <plot
 6 Fighting
               <tibble [16 × 15]>
                                  <plot
               <tibble [24 × 15]>
 7 Racing
                                  <plot
 8 Adventure
               <tibble [56 × 15]>
                                  <plot
 9 Misc
               <tibble [32 × 15]>
                                  <plot
```

```
vgsales2016 %>%
  group_by(Genre) %>%
  nest() %>%
  mutate(
    plot = map2(
      data, Genre,
      \(data, Genre)
       plot_ly(data = data,
          x = ~Critic_Score,
          y = ~User_Score) %>%
      add_markers(name = ~Genre)
    )) %>%
  subplot(nrows = 2)
```

Let's practice!

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R



Interactive scatterplot matrices

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R




Adam Loy
Statistician, Carleton College



Wine data

glimpse(wine)

```
Rows: 178
Columns: 14
$ Type
                $ Alcohol
                <dbl> 14.23, 13.20, 13.16, 14.37, 13.24, 14.20, 14.3...
$ Malic
                <dbl> 1.71, 1.78, 2.36, 1.95, 2.59, 1.76, 1.87, 2.15...
$ Ash
                <dbl> 2.43, 2.14, 2.67, 2.50, 2.87, 2.45, 2.45, 2.61...
$ Alcalinity
                <dbl> 15.6, 11.2, 18.6, 16.8, 21.0, 15.2, 14.6, 17.6...
$ Magnesium
                <int> 127, 100, 101, 113, 118, 112, 96, 121, 97, 98,...
$ Color
                <dbl> 5.64, 4.38, 5.68, 7.80, 4.32, 6.75, 5.25, 5.05...
$ Hue
                <dbl> 1.04, 1.05, 1.03, 0.86, 1.04, 1.05, 1.02, 1.06...
$ Dilution
                <dbl> 3.92, 3.40, 3.17, 3.45, 2.93, 2.85, 3.58, 3.58...
$ Proline
                <int> 1065, 1050, 1185, 1480, 735, 1450, 1290, 1295,...
```



The template


```
data %>%
  plot_ly() %>%
  add_trace(
    type = 'splom',
    dimensions = list(
      list(label='string-1', values=~X1),
      list(label='string-2', values=~X2),
      list(label='string-n', values=~Xn))
```

- add_trace() to specify variables
- For each variable, two arguments:
 - String for axis label
 - Mapping specifying variable
- 'splom' trace type = scatterplot matrix

Wine SPLOM


```
wine %>%
  plot_ly() %>%
  add_trace(
    type = 'splom',
    dimensions = list(
      list(label='Alcohol', values=~Alcohol),
      list(label='Flavonoids', values=~Flavanoids),
      list(label='Color', values=~Color)
```

Linked brushing



Adding color

```
wine %>%
  plot_ly(color = ~Type) %>%
  add_trace(
    type = 'splom',
    dimensions = list(
      list(label='Alcohol', values=~Alcohol),
      list(label='Flavonoids', values=~Flavanoids),
      list(label='Color', values=~Color)
```



Let's practice!

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R




Binned scatterplots


INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R




Adam Loy Statistician, Carleton College











add_histogram2d()



```
sim_data %>%
  plot_ly(x = ~x, y = ~y) %>%
  add_histogram2d()
```

Changing the bins



```
sim_data %>%
  plot_ly(x = ~x, y = ~y) %>%
  add_histogram2d(nbinsx = 200, nbinsy = 100)
```

Let's practice!

INTERACTIVE DATA VISUALIZATION WITH PLOTLY IN R

