

Nonlinear Dimensionality Reduction: t-Stochastic Neighbor Embedding (t-SNE)

Prof. Endri Raco

Polytechnic University of Tirana

Erasmus+ Exchange Professor

Advanced Multivariate Analysis

Polytechnic University of Catalonia (UPC)

October 15, 2025



Welcome to Advanced Multivariate Analysis

Today's Journey

- **2-hour deep dive** into t-SNE
- **Mathematical foundations** to practical insights
- **Three key parts:**
 - 1 SNE - The original idea
 - 2 t-SNE - Solving the crowding problem
 - 3 Hyperparameters & interpretation

$$p_{j|i} = \frac{e^{-\|x_i - x_j\|^2 / 2\sigma_i^2}}{\sum_{k \neq i} e^{-\|x_i - x_k\|^2 / 2\sigma_i^2}}$$

Core t-SNE Formula (We'll derive this today)

The Curse of Dimensionality

Our Intuition Works Here:




2D: Simple



3D: Manageable

But Not Here:



100D? 1000D?


Problems:

- Distance concentration
- Volume: $V_n(r) \propto r^n$
- Sparse data

“Geometric intuition fails”


Goals of Dimensionality Reduction

Goal 1: Visualization



Key: "See" hidden structure

Goal 2: Feature Extraction



Benefits:

- Noise reduction
- Efficiency
- Better ML

Challenge: Preserve relationships while reducing dimensions

When Linear Methods Falter

Swiss Roll Dataset




3D Manifold

True Structure:

2D manifold in 3D space

PCA Projection



Problem:


Preserves variance,
destroys local structure

*Need methods that preserve **local relationships***

The Manifold Hypothesis

“High-dimensional data often lies on or near a much lower-dimensional manifold”

Example: Earth's Surface



2D surface in 3D

Mathematical Form

Data: $\mathbf{X} = \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$

where $\mathbf{x}_i \in \mathbb{R}^D$

Assumption:

\exists manifold \mathcal{M} with $\dim d \ll D$:


$$\mathbf{x}_i \approx f(\mathbf{z}_i) + \epsilon_i$$

- $\mathbf{z}_i \in \mathbb{R}^d$ (low-dim)
- $f : \mathbb{R}^d \rightarrow \mathbb{R}^D$
- ϵ_i (noise)

Goal: Uncover this hidden low-dimensional structure

Preserving Neighborhoods: t-SNE in Action

PCA on MNIST Digits



PCA: Mixed Clusters

Problems:

- Classes overlap significantly
- Linear projection limitations
- Poor cluster separation

t-SNE on MNIST Digits




t-SNE: Clear Separation

Advantages:

- Distinct clusters
- Preserves local structure
- Reveals true relationships

*"t-SNE focuses on preserving **local neighborhood structure**"*
Similar points in high-D \rightarrow nearby points in low-D


Today's Journey: From Theory to Mastery



From Distances to Probabilities: The Core Idea

Central Insight: Convert distances between points into probabilities
that represent neighborhood relationships


Traditional Approach



Euclidean Distances

Problem: How to weight different distances?

SNE/t-SNE Approach



Probabilities

Solution: Probabilities naturally normalize!

"What is the probability that point i would pick point j as its neighbor?"