


JMS_TIBCO Message Properties

- **JMS_TIBCO_COMPRESS**
 - Allow messages to be compressed for more efficient storage
- **JMS_TIBCO_IMPORTED**
 - Import messages from Rendezvous or SmartSockets
- **JMS_TIBCO_MSG_EXT**
 - Include sub-messages or arrays
- **JMS_TIBCO_SENDER**
 - User Name of the message sender
- **JMS_TIBCO_DISABLE_SENDER**
 - User name should not be included in the message
- **JMS_TIBCO_PRESERVE_UNDELIVERED**
 - Move undelivered message to undelivered message queue

© TIBCO Software Inc.TIBCO Education Programs

JMS_TIBCO Message Properties

Some of TIBCO-specific message properties are listed here:

JMS_TIBCO_COMPRESS: If set to true, the body of a message is compressed.

JMS_TIBCO_IMPORTED: Set by the server when the message has been imported from Rendezvous or SmartSockets.

JMS_TIBCO_MSG_EXT: Extends the MapMessage and StreamMessage body types. You can use arrays as well as primitive types for the values.

JMS_TIBCO_SENDER: Supply the user name given by the message producer when a connection is created.

JMS_TIBCO_DISABLE_SENDER: Producer's user name will not be included in the message.

JMS_TIBCO_PRESERVE_UNDELIVERED: If set to true, the server moves the message to the undelivered message queue, `$sys.undelivered`, instead of removing it.