Contents

Software Design Document — music-room **1**
1. Introduction . . . 1
2. References . . . 2
3. Stakeholders and design concerns . . . 2
4. Context viewpoint . . . 3
5. Composition viewpoint . . . 3
6. Logical viewpoint — domain model . . . 4
7. Dependency viewpoint . . . 5
8. Information viewpoint . . . 6
9. Interface viewpoint . . . 7
10. Interaction viewpoint . . . 8
11. State dynamics . . . 10
12. Concurrency viewpoint . . . 10
13. Security design . . . 11
14. Deployment and resource viewpoint . . . 13
15. Design rationale . . . 14
16. Requirements traceability . . . 15
17. Open design issues . . . 16
Related . . . 18

Software Design Document — music-room

Consolidated design view of the system, organised by the viewpoints of IEEE 1016.

Status: draft — design intent. No application code exists yet (`MusicRoom/` is empty). Every section below describes what is decided, and marks what is not with `UNKNOWN - requires decision`. A guess is never substituted for a decision.

---

1. Introduction

1.1 Purpose

One document an evaluator, a new teammate, or a future maintainer can read to understand how the system is designed and why. It consolidates the design; it does not replace the layers that own each part.

1.2 Scope

The `music-room` backend and the contract it exposes to clients. The React Native client is out of the current work scope — only the constraints it places on the backend appear here ([[ADR-0002-mobile-react-native]]).

1.3 Audience

Peer evaluators, team members, and any agent working in this repository.

1.4 Authority order

When two sources disagree:

`42 subject -> ADR -> standard -> this document -> note -> code comment`

This document **consolidates**; it is not the source of truth for anything. Rationale lives in ADRs, enforceable rules live in `docs/technical-guide/`, requirements live in the subject.

1.5 Relationship to the other layers

Layer	Owns	This document does
`brain/constraints/`	what is required	quote and trace it
`brain/decisions/`	why a choice was made	reference it, never restate the rationale
`brain/architecture/`	the working design notes	consolidate them into one readable view
`docs/technical-guide/`	enforceable rules	reference, never copy
`docs/owasp/`	the security conformance target and its evidence	reference, never copy
`MusicRoom/`	what the code does	describe intent only

---

2. References

Ref	Source
R1	42 subject "Music Room", v6 — `docs/subject/en.subject tr.pdf`, distilled in [[subject-requirements]]
R2	[[decisions-index]] — ADR-0001 through ADR-0006
R3	[[technical-guide-index]] — 19 engineering standards
R4	IEEE 1016 — software design description, used here as the section structure
R5	RFC 9110 (HTTP semantics), RFC 9457 (Problem Details), RFC 9700 (OAuth 2.0 BCP), OpenID Connect Core 1.0
R6	OWASP ASVS 5.0.0, vendored at `docs/owasp/upstream/asvs-5.0.0/`; conformance scope in [[asvs-conformance]]
R7	NIST SP 800-63B — password and verifier requirements

---


3. Stakeholders and design concerns

Stakeholder	Primary concern	Addressed in
End user at an event	the queue reflects the group's votes, immediately	§11, §12
Event owner	control over who may vote and edit	§9.2, §13.2
Peer evaluator	every mandatory requirement is met and defensible	§16
Team developer	knowing where code goes and which rule applies	§5, §7
Operator	the system can be run, measured, and recovered	§14

---

4. Context viewpoint

4.1 System context



4.2 External actors and interfaces

External element	Direction	Protocol	Owned by
React Native client	inbound	HTTPS REST/JSON, WebSocket	us (deferred)
Supabase PostgreSQL	outbound	PostgreSQL wire protocol	vendor, managed
YouTube Data API v3	outbound	HTTPS REST	vendor
YouTube player SDK	client-side only	—	vendor
Google / Facebook OIDC	outbound	OAuth 2.0 + PKCE	vendor
Mail provider	outbound	HTTPS API	hosted free tier – [[ADR-0013-mail-provider]]

Design constraint. No client ever reaches Supabase or YouTube Data API directly. Subject R1 V.3 makes the backend the single guardian of truth, and V.6 makes it the single authorisation gate. A direct client connection would route around both. See [[ADR-0006-datastore]].

---

5. Composition viewpoint

5.1 Physical composition

One repository, two application roots – [[ADR-0020-monorepo-layout]]:

Root	Contents	Owner
`MusicRoom/`	backend, .NET 10	backend developer
`MusicRoomApp/`	React Native client	UI developer

One clone is the whole submission, which subject VII requires. Neither root writes into the other; the contract between them is [[endpoint-inventory]] and the generated `docs/api/openapi.json`. `reference/` is read-only study material, never built, referenced or copied from – see [[reference-narchitecture]].

Five projects, per [[clean-architecture-cqrs]]:

Project	Responsibility
`Domain`	entities, value objects, enums, domain rules, domain exceptions
`Application`	commands, queries, handlers, validators, pipeline behaviours, abstractions
`Persistence`	`DbContext`, entity configurations, repositories, EF Core migrations
`Infrastructure`	YouTube adapter, mail, token and OTP services
`WebAPI`	controllers, SignalR hubs, middleware, DI composition, OpenAPI

Layout mirrors the reference repository – [[ADR-0011-solution-layout]]:

```
MusicRoom/
  MusicRoom.sln
  src/
    corePackages/   Core.Application | Core.CrossCuttingConcerns | Core.Persistence | Core.Security
    MusicRoom/      Domain | Application | Persistence | Infrastructure | WebAPI
  tests/
    <Project>.Tests/
```

The shape is copied; no file is. A type enters `corePackages` only if it is domain-agnostic.

5.2 Logical composition — bounded contexts

Context	Owns	Subject ref
Identity	user, credentials, email verification, password reset, social links	V.1
Profile	profile fields with per-field visibility, music preferences	V.1
Event (Track Vote)	event, attendee, track suggestion, vote, licence policy	V.2.1
Playlist (Editor)	playlist, collaborator, ordered tracks	V.2.3
Delegation (Control)	device, control grant	V.2.2
Playback	playback session, now-playing pointer, queue advance	V.2.1, V.2.2
Catalog	YouTube track lookup and cache	V.2, III
Audit	per-action record: platform, device, app version	V.6

Subject R1 V.2 requires at least 2 of 3 services. **All three ship** – [[ADR-0010-service-scope]]. Identity, Profile, Catalog and Audit are required regardless.

Consequence: the location+time licence mode is mandatory, decided in [[ADR-0014-location-time-licence]]. If the schedule slips, Control Delegation is dropped first – it is the smallest, and removing it still leaves two services, satisfying V.2.

---

6. Logical viewpoint — domain model

Detail source: [[domain-model]]. Field-level detail is deliberately absent until the first migration exists.

6.1 Aggregates

Aggregate	Root	Key invariant
User	`User`	email unique; an unverified email cannot use services
Profile	`Profile`	every field carries one of `Public / Friends / Private`
Event	`Event`	one vote per user per track; ranking derives from vote count
Playlist	`Playlist`	position ordering stays total and gap-tolerant
Device	`Device`	a control grant belongs to exactly one device
PlaybackSession	`PlaybackSession`	at most one active session per device; `controllerUserId` is what a control grant changes
TrackRef	value object	a YouTube reference only — never media content

6.2 Shared enumerations

Enum	Values	Source
`Visibility`	`Public`, `Private`	R1 V.2.1, V.2.3
`LicenceMode`	`Everyone`, `InvitedOnly`, `LocationAndTimeRestricted`	R1 V.2.1, V.2.3
`PresenceProof`	`Geofence`, `EventCode`, `Both`	policy carried by `LocationAndTimeRestricted` – [[ADR-0014-location-time-licence]]
`ProfileFieldVisibility`	`Public`, `Friends`, `Private`	R1 V.1
`Platform`	`iOS`, `Android`, `Web`, `Other`	R1 V.6


6.3 Deliberate exclusions


Audio and video content is never stored, cached, proxied or re-hosted. Only `TrackRef` metadata is persisted — [[ADR-0003-music-provider-youtube]].

---

7. Dependency viewpoint

7.1 The dependency rule





Enforced constraints, from [[clean-architecture-cqrs]]:

- `Domain` references no other project and no infrastructure package.
- `Application` references neither EF Core, nor ASP.NET Core, nor any vendor SDK.
- `WebAPI` never touches `DbContext` directly.
- A reference pointing outward is a build-breaking defect, not a style issue.

7.2 External dependency boundaries

External system	Isolated behind	Located in
YouTube Data API	one adapter, interface declared in `Application`	`Infrastructure`
SMTP	mail service abstraction	`Infrastructure`
Google / Facebook	provider token validation service	`Infrastructure`
PostgreSQL	repositories + `DbContext`	`Persistence`

---

8. Information viewpoint

8.1 Storage

Supabase-managed PostgreSQL, accessed through EF Core with the Npgsql provider ([[ADR-0006-datastore]]). Only the Postgres surface is used — Supabase Auth, Realtime, Storage and PostgREST are deliberately not adopted, because identity, realtime and the API are ours.

8.2 Constraints that carry invariants

Conventions and full rules: [[database-design-migrations]].

Constraint	Protects	Why it is in the database
`ux_votes_event_id_track_id_user_id`	one vote per user per track	a read-then-write check in C# is a race condition
`ux_users_email`	account uniqueness	concurrent registration
`xmin` concurrency token on `playlists`	reorder conflicts	last-writer-wins must be detectable
`xmin` concurrency token on `devices`	control takeover	two simultaneous claims must not both succeed

8.3 Common columns

Every table: `id`, `created_at_utc`, `updated_at_utc`. User-owned aggregates use soft delete (`deleted_at_utc`) so the audit trail survives. All instants are `timestamp with time zone`, written as UTC.

8.4 Ordering strategy

Playlist position uses sparse ordering keys with gaps, so inserting between two tracks does not rewrite the list. See §12.2.

8.5 Schema ownership and evolution

- EF Core migrations are the only mechanism that changes the schema. Editing the schema in the Supabase dashboard desynchronises migration history and is treated as an incident.
- Two connection strings: pooled (Supavisor) for the API, **direct** for migrations.
- Destructive changes follow expand -> migrate -> contract.
- Every migration is recorded in [[migrations-index]].

Concrete table and column definitions: `UNKNOWN - requires decision` until the first migration.

---

9. Interface viewpoint

9.1 REST API

Rules: [[rest-api-design]]. Documentation: [[openapi-documentation]].

Aspect	Design
Base path	`/api/v1`
Format	JSON, `camelCase`, UTF-8
Errors	RFC 9457 `application/problem+json`, one shape, with `traceId`
Collections	envelope `{ items, page, pageSize, total }`, page size capped
Timestamps	UTC ISO-8601
Privacy rule	a resource hidden from the caller returns `404`, never `403`
Auth	bearer JWT
Mandatory headers	`X-Client-Platform`, `X-Client-Device`, `X-Client-App-Version` on mutations
Documentation	OpenAPI 3.1 generated from code, exported to `docs/api/openapi.json`

The endpoint inventory is [[endpoint-inventory]] – around 60 endpoints across Identity, Profile, Catalog, Track Vote, Playlist Editor, Control Delegation, audit and operations, plus the client-to-server hub methods. Concrete request and response schemas come from the generated OpenAPI document, not from that file.

9.2 Realtime API

Rules: [[signalr-realtime]]. Rationale: [[ADR-0004-realtime-signalr]].

Hub	Group key	Server-to-client events
`EventHub`	`event:{eventId}`	`TrackSuggested`, `VoteChanged`, `QueueReordered`, `NowPlayingChanged`
`PlaylistHub`	`playlist:{playlistId}`	`TrackAdded`, `TrackRemoved`, `TrackMoved`, `CollaboratorChanged`
`ControlHub`	`user:{userId}`	`ControlGranted`, `ControlRevoked`, `ControlTakenOver`

Contract rules:

- Hubs are transport only. Every hub method dispatches the **same** CQRS handler the REST endpoint uses, so the two transports cannot diverge.
- Every payload carries the aggregate id and a monotonic `version`, so a client that missed a message can detect the gap and resynchronise over REST.
- Group membership is authorised server-side on every join and re-checked on reconnect.
- A broadcast is emitted only after the transaction commits.

9.3 External interfaces

Interface	Usage	Design note
YouTube Data API v3	`videos.list` preferred; `search.list` only on real user input	quota is billed in units and `search.list` is the expensive call; results are cached as normalised `TrackRef`
YouTube player SDK	client-side playback	backend decides what and when, never streams media
Google / Facebook	authorization code flow with PKCE	provider token validated server-side against JWKS; a client-supplied profile is never trusted
Mail provider	verification and reset mail	hosted free tier behind `IMailService`; API key server-side – [[ADR-0013-mail-provider]]

---

10. Interaction viewpoint

Representative flows. Steps are design intent, not implemented code.

10.1 Registration with email and password

```
1. Client POST /api/v1/auth/register
2. Validation behaviour rejects malformed input
3. Handler hashes the password (Argon2id), persists an unverified User
4. Infrastructure sends a verification mail with a single-use, hashed, 24h token
5. Response 201; the account cannot use services until verified
6. Client GET/POST the verification endpoint with the token
7. Handler marks the account verified and consumes the token
```

10.2 Social login

OpenID Connect, not bare OAuth 2.0 – [[ADR-0008-oidc-social-login]].

```
1. Device runs the OIDC authorization code flow with PKCE
2. Client POST /api/v1/auth/social with the provider ID TOKEN (never an access token)
3. Server validates, in order:
     a. signature against the provider JWKS from its discovery document
     b. iss matches the expected issuer
     c. aud matches our client id      <- stops token substitution
     d. exp and iat within tolerance
     e. nonce matches the one this server generated
     f. email_verified is true before any email-based account match
```

```
4. Server maps (provider, providerUserId) to a local user, or creates one
5. Server issues ITS OWN access + refresh token pair
   - a provider token is never accepted as an API credential
```

Provider asymmetry: Google is a full OIDC provider; Facebook is not uniformly OIDC (Limited Login issues an ID token, classic Facebook Login does not). The integration branches. See [[social-oauth]].

10.3 Casting a vote — the contended write path

```
1. Client POST /api/v1/events/{eventId}/tracks/{trackId}/votes
2. Authorisation behaviour evaluates ownership, then Visibility and LicenceMode
3. Rate limiting behaviour applies per account and per IP
4. Transaction behaviour opens the transaction
5. Handler inserts the vote row
   - the unique index is the arbiter; a duplicate insert fails here, not in C#
   - a duplicate is mapped to 409 Conflict, never silently ignored
6. Vote count is recomputed from the source rows, never incremented in memory
7. Transaction commits
8. ONLY THEN: EventHub broadcasts VoteChanged and QueueReordered to event:{eventId}
```

Step 8 after step 7 is the rule that prevents clients from seeing state the server rolls back.

10.4 Moving a track in a playlist

```
1. Client PATCH .../playlists/{id}/tracks/{trackId} with the target position,
   carrying the playlist's current concurrency token
2. Authorisation behaviour evaluates Visibility and LicenceMode for edit rights
3. Handler computes a new sparse ordering key between the neighbours
4. Save fails with DbUpdateConcurrencyException if another edit landed first
   - the handler reloads and reapplies, or returns 409
5. On commit, PlaylistHub broadcasts TrackMoved with the new version
6. Clients treat the event as a reconcile hint, tolerating duplicates and reordering
```

10.5 Delegating music control

```
1. Owner POST .../devices/{deviceId}/control-grants with the target friend
2. Handler transitions the Device control state under its concurrency token
3. A competing claim loses on the concurrency token - it must not silently win
4. ControlHub notifies user:{ownerId} and user:{granteeId}
```

10.6 Advancing the queue

```
1. Controller device detects the current track ended
2. POST /api/v1/playback-sessions/{id}/advances  { expectedNowPlayingId }
3. Authorisation behaviour verifies the caller is the session's controllerUserId
4. Handler picks the next item:
     Event    -> highest vote count, ties broken by earliest suggestion
     Playlist -> next ordering key
5. Write under the concurrency token; a stale expectedNowPlayingId returns the current
   state instead of skipping a second track
6. Commit
7. ONLY THEN: NowPlayingChanged broadcast to the source's group
```

The server is the arbiter of **what** plays; the client is the authority on **when** it ended. The backend cannot observe audio, and a `durationSeconds` timer drifts on pause and buffering. See [[ADR-0017-playback-session]].

10.7 Every mutating request — the mandatory audit path

```
1. Middleware reads X-Client-Platform, X-Client-Device, X-Client-App-Version
2. Missing headers on a mutating request -> 400 (a silent default would void R1 V.6)
3. Values are attached to the request scope
4. An audit behaviour writes one audit record per handled command
```

---

11. State dynamics

11.1 Account state

```
Registered(unverified) --verify--> Active
Active --reset password--> Active (all refresh tokens revoked)
```

An unverified account cannot use the three services.

11.2 Playback session state

```
None --create--> Playing(nowPlaying)
Playing --advance--> Playing(next)      server picks next; idempotent on expectedNowPlayingId
Playing --advance--> Ended              queue exhausted
Playing --delete--> None
```

If the controller device goes silent mid-track, nothing advances. Accepted: control can be taken over via `PUT /devices/{id}/control` and the owner can always revoke. No server-side watchdog – it would reintroduce the drift this design avoids.

11.3 Device control state

Single-row state machine on `Device`, guarded by a concurrency token:

```
Uncontrolled --claim--> ControlledBy(owner)
ControlledBy(owner) --delegate--> ControlledBy(grantee)
ControlledBy(x) --revoke--> ControlledBy(owner)
ControlledBy(x) --release--> Uncontrolled
```

Concurrent transitions are resolved by the token. Exact state names are settled when the Delegation slice is built.

---

12. Concurrency viewpoint

Subject R1 V.2.1 and V.2.3 both call out race conditions explicitly. They are graded, so they are designed here rather than discovered in review. Full notes: [[realtime-architecture]].

12.1 Hotspots

#	Hotspot	Failure if unhandled
1	two users vote on the same track simultaneously	duplicate votes, wrong ranking
2	two users reorder the same playlist simultaneously	divergent order, lost move
3	two devices claim control at once	two controllers, undefined playback

#	Hotspot	Failure if unhandled
4	two clients advance the same playback session at once	a track is silently skipped

12.2 Mechanisms

Hotspot	Mechanism
1	unique index `(EventId, TrackId, UserId)`; duplicate detected by the database, mapped to `409`
1	vote counts recomputed inside the transaction or aggregated database-side — never read-modify-write
2	sparse ordering keys plus an `xmin` concurrency token; on conflict, reload and reapply, else `409`
3	single-row state machine with a concurrency token; the losing writer must lose visibly
4	`expectedNowPlayingId` in the request plus the session's concurrency token; a stale expectation returns current state rather than advancing again

12.3 Governing principles

1. **The database is the arbiter, not the hub and not the application.**
2. **Broadcast after commit.** Never inside the transaction.
3. **Every realtime event is a reconcile hint.** Clients must tolerate duplicates and reordering.
4. **A sequential test proves nothing about a race.** Concurrency cases run in parallel and assert final database state — [[testing]].

---

13. Security design

Full rules: [[authentication-authorization]], [[application-security]], [[secrets-management]]. Design notes: [[auth-and-identity]]. Conformance target: [[asvs-conformance]] — ASVS 5.0.0 Level 1 for every applicable chapter, Level 2 for V6 Authentication, V7 Session Management, V8 Authorization, V9 Self-contained Tokens, V10 OAuth and OIDC, and V16 Security Logging and Error Handling.

13.1 Authentication

Element	Design
Password hashing	**BCrypt** (`BCrypt.Net-Next`), work factor >= 12, rehash on login when the stored cost is lower – [[ADR-0007-password-hashing-bcrypt]]
Password policy	12 to 64 characters, **<= 72 bytes UTF-8** (BCrypt truncates beyond that), no composition rules, no forced rotation (NIST SP 800-63B)
Session	15-minute JWT access token + opaque, hashed, rotating refresh token
Theft detection	reuse of a rotated refresh token revokes the whole family
Verification / reset	single-use, hashed, short-TTL tokens; identical responses whether or not the account exists

Element	Design
Social	**OpenID Connect** + PKCE; the ID token is validated server-side including `aud` and `nonce`; one provider identity maps to at most one user – [[ADR-0008-oidc-social-login]]

13.2 Authorisation — two independent gates

Both are mandatory, both server-side, both implemented as a pipeline behaviour rather than scattered conditionals:

1. **Ownership** — the caller owns the resource or is an authorised participant (R1 V.6).
2. **Visibility and licence** — resolved from `Visibility` and `LicenceMode`, evaluated on every request and every hub join.

Profile responses are filtered **per field** by the requester's relationship (self / friend / stranger). A full row is never returned for the client to filter.

Row Level Security is enabled in PostgreSQL with deny-by-default policies as defence in depth. It is never the only gate.

13.3 Abuse resistance

Rate limits keyed on account **and** IP for login, registration, reset, verification resend and vote casting. Progressive backoff on repeated login failure. Generic error text to prevent account enumeration. `429` with `Retry-After`.

13.4 Audit log — mandatory, and distinct from application logging

	Audit log	Application log
Purpose	satisfy R1 V.6 — record what a user did	diagnose the system
Store	database table, queryable	structured log sink
Retention	kept; it is evidence	rotated

Audit record: `userId`, `action`, `targetType`, `targetId`, `platform`, `device`, `appVersion`, `occurredAtUtc`, `correlationId`, outcome. See §10.7.

Both transports are covered. REST commands go through the pipeline behaviour; SignalR `JoinEvent`, `LeaveEvent`, `JoinPlaylist` and `LeavePlaylist` go through a hub filter writing the same record – [[ADR-0019-hub-action-auditing]]. Client context is captured at the handshake, since a hub invocation carries no HTTP headers, and a handshake without it is rejected. Connect and disconnect are deliberately not audited: mobile reconnect noise would bury deliberate user actions.

13.5 Never logged, never stored, never shipped to a client

Passwords, tokens, refresh tokens, API keys, `Authorization` headers, database connection strings, Supabase keys, OAuth client secrets. A mobile bundle can be unpacked, so it holds none of these.

13.6 Residual risk

R1 V.6 requires the remaining threats to be identified and their protections described. The register is [[threat-register]]: 18 threats with likelihood, impact, planned mitigation, residual risk, accepted-by and verification, plus an explicit out-of-scope list.

Every unfixed finding from [[owasp-top10-checklist]] or [[owasp-api-top10-checklist]] gets a row there before the pull request merges. An accepted risk that is written down is a defensible engineering decision; an unwritten one is an oversight.

---

14. Deployment and resource viewpoint

14.1 Topology

Element	Where	Note
API	local Docker on a declared machine – [[ADR-0015-hosting-and-deployment]]	multi-stage image, pinned base, non-root user
Database	S0-S3 a **local PostgreSQL container**; S4 onward Supabase Free tier, Frankfurt – [[ADR-0026-environment-bring-up]]	same engine, same migrations, different connection string
Client	user devices	React Native, built in parallel by the second team member
CI	GitHub Actions, separate `dev` and `prod` configurations, plus an independent client job	builds and tests; **does not deploy**
Observability	Serilog to stdout; OpenTelemetry exporter configuration-driven, **off by default** – [[ADR-0022-observability-stack]]	switched on for a load run

The defence runs on the local stack. No remote deployment target is chosen yet; Vercel cannot host this API (serverless, no long-lived process, no persistent WebSocket).

The database being off-premise must be stated in the load report: network latency to Supabase is part of the measured numbers, not an excuse for them.

14.2 Reproducibility

Subject R1 IV.1 requires dependencies to install automatically from a fresh clone. Target path:

```
clone  ->  cp .env.example .env  ->  fill values  ->  make up
```

The `Makefile` does not exist yet — there is no application to start. Issue O10, built in slice S0 of [[delivery-plan]]; rules in [[ci-cd-containerization]]. CI builds and tests but does not deploy – [[ADR-0015-hosting-and-deployment]].

14.3 Configuration

All configuration from environment variables, named after the role rather than the vendor (`DATABASE_URL`, not a provider name) – [[ADR-0026-environment-bring-up]]. External credentials are created just in time: mail before S1, YouTube and the Supabase project before S4, Google and Facebook before S8. Every key is listed in `.env.example` with a placeholder. `.env` is git-ignored. R1 V.8 makes a publicly stored credential an automatic project failure.

14.4 Capacity

Tool: **Gatling**, from its Docker image, simulations committed under `tests/load/` – [[ADR-0018-load-testing-tool]]. It is named in the subject and supports WebSocket natively, so one methodology covers both REST

throughput and SignalR fan-out.

Subject R1 V.7 requires a measured and justified concurrent-user figure with the server specification declared. The report at `docs/load/REPORT.md` does not exist yet. REST throughput and SignalR connection fan-out are measured **separately** — they are different limits. See [[load-testing]].

The API is on-premise and the database is off-premise: latency to Frankfurt is inside every measured number, and the report must say so rather than gloss over it. Confirm the free tier's current connection ceiling and quotas on the day of the run – the connection ceiling, not storage, is the operative limit.

---

15. Design rationale

Rationale is not restated here. Each decision has its own record with the alternatives that were rejected and why — evaluators ask "why not X", and the answer must be on file.

ADR	Decision	Status
[[ADR-0001-backend-dotnet-narchitecture]]	.NET 10, Clean Architecture + CQRS	Accepted
[[ADR-0002-mobile-react-native]]	React Native client, deferred	Accepted
[[ADR-0003-music-provider-youtube]]	YouTube as the music provider	Accepted
[[ADR-0004-realtime-signalr]]	SignalR over WebSocket	Accepted
[[ADR-0005-api-style-rest-json]]	REST + JSON + OpenAPI	Accepted
[[ADR-0006-datastore]]	Supabase managed PostgreSQL	Accepted
[[ADR-0007-password-hashing-bcrypt]]	BCrypt for password hashing	Accepted
[[ADR-0008-oidc-social-login]]	OpenID Connect for Google and Facebook	Accepted
[[ADR-0009-code-quality-gates]]	OWASP conformance and enforced code-size limits	Accepted
[[ADR-0010-service-scope]]	Ship all three services	Accepted
[[ADR-0011-solution-layout]]	Layout mirrors nArchitecture	Accepted
[[ADR-0012-test-stack]]	xUnit, NSubstitute, Testcontainers	Accepted
[[ADR-0013-mail-provider]]	Hosted transactional mail provider	Accepted
[[ADR-0014-location-time-licence]]	Geofence plus optional event code	Accepted
[[ADR-0015-hosting-and-deployment]]	Local Docker, CI without deployment	Accepted
[[ADR-0016-supabase-plan-region]]	Supabase Free tier, Frankfurt	Accepted
[[ADR-0017-playback-session]]	PlaybackSession aggregate, client-driven advance	Accepted
[[ADR-0018-load-testing-tool]]	Gatling for load testing	Accepted
[[ADR-0019-hub-action-auditing]]	Audit hub actions with the same record	Accepted
[[ADR-0020-monorepo-layout]]	Backend and client in one repository	Accepted
[[ADR-0021-backend-dependency-set]]	MediatR, FluentValidation, built-in rate limiting and OpenAPI	Accepted
[[ADR-0022-observability-stack]]	Serilog with OpenTelemetry	Accepted

ADR	Decision	Status
[[ADR-0023-catalog-cache]]	Two-level catalog cache	Accepted
[[ADR-0024-expiry-and-cleanup]]	Lazy expiry checks, one cleanup service	Accepted
[[ADR-0025-agent-git-protocol]]	Git protocol for unattended agent runs	Accepted
[[ADR-0026-environment-bring-up]]	Environment bring-up sequence	Accepted

An accepted ADR is never edited. It is superseded by a new one.

---

16. Requirements traceability

Every mandatory requirement of R1, mapped to the design element that satisfies it. This is the table to walk through at defence.

Subject	Requirement	Design element	Status
V.1	email+password or social registration	§10.1, §10.2, §13.1	designed
V.1	link a social account	§10.2, Identity context	designed
V.1	email verification + forgot password	§10.1, §13.1	designed
V.1	three profile visibility tiers	§6.2, §13.2	designed
V.2.1	live vote-ordered queue	§5.2, §10.3, §9.2	designed
V.2.1	a highly-voted track **plays** earlier	§10.6, §11.2, [[ADR-0017-playback-session]]	designed
V.2.1	public/private visibility	§6.2, §13.2	designed
V.2.1	licence modes incl. location+time	§6.2, [[ADR-0014-location-time-licence]]	**designed** — geofence + event code
V.2.1	vote race conditions	§12.1 #1, §12.2	designed
V.2.2	per-device control licence, delegation	§5.2, §10.5, §11.3	designed
V.2.2	what a delegate actually controls	`PlaybackSession.controllerUserId` – [[ADR-0017-playback-session]]	designed
V.2.3	realtime multi-user playlist editing	§9.2, §10.4	designed
V.2.3	reorder race conditions	§12.1 #2, §12.2	designed
V.2	at least 2 of the 3 services	§5.2, [[ADR-0010-service-scope]]	**designed** — all three
V.3	backend is the single source of truth	§4.2, §8.1	designed
V.4	REST, JSON, reference documentation	§9.1, [[endpoint-inventory]], [[ADR-0021-backend-dependency-set]]	**designed** – built-in generator emits `openapi.json` once code exists
V.5	client is a remote control	§4.1, §9.1	designed
V.5	configurable backend address	§9.1, [[musicroom-mobile]]	designed

Subject	Requirement	Design element	Status
V.5	social authentication on mobile	§10.2	designed
V.6	own data only, never another user's	§13.2	designed
V.6	brute force and session theft protections	§13.1, §13.3	designed
V.6	document remaining threats	§13.6, [[threat-register]]	**designed** — register written, verification pending
V.6	log platform, device, app version per action	§10.7, §13.4, [[ADR-0019-hub-action-auditing]]	**designed** – REST and hub both covered
V.7	measure and justify concurrent users	§14.4, [[ADR-0018-load-testing-tool]]	tool decided; measurement not started
V.7	declare server specification	§14.1, [[ADR-0015-hosting-and-deployment]], [[ADR-0016-supabase-plan-region]]	machine and region decided; measurement not started
V.6	OWASP conformance of all code	[[asvs-conformance]], §13	target committed, evidence pending
V.8	per-layer tests	[[testing]], [[ADR-0012-test-stack]]	stack decided, tests not written
V.8	continuous integration	[[ci-cd-containerization]]	rules defined, pipeline not written
V.8	credentials in a git-ignored `.env`	§14.3, `.env.example`	**done**
V.8	enforced code quality	[[dotnet-csharp]], `.editorconfig`	**done** — config written, fires once code exists
IV.1	no third-party source in the repo	§5.1, `.gitignore` excludes `reference/`	**done**
IV.1	dependencies install from a fresh clone	§14.2	**not started**
IV.2	mobile app covers all operations	`MusicRoomApp/`, [[musicroom-mobile]]	parallel workstream, owned by the UI developer
VII	submitted in the git repository	[[ADR-0020-monorepo-layout]]	**designed** – one clone holds backend, client and documentation
III	the SDK must not do our work	§4.2, §9.3	designed

"Designed" means the decision and the mechanism are recorded. No row in this table claims implemented code, because none exists.

---

17. Open design issues

Closed rows stay visible: a decision log that hides what it used to not know is less useful at defence, not more.

Open

#	Issue	Blocks	Note
O8	SignalR scale-out backplane (Redis)	multi-instance deployment	**deliberately open.** Not needed for a single-instance defence
O9	concrete table and column definitions	§8.5	resolved by the first migration, not by a document
O10	`Makefile` and `docker compose`	§14.2, IV.1	a task, not a decision. [[delivery-plan]] slice S0
O11	remote deployment target	a live demo URL	[[ADR-0015-hosting-and-deployment]]. Fly.io, Railway, Render, Azure Container Apps. **Not Vercel**
O12	fluent assertion library	test readability	add only if xUnit's built-ins prove insufficient
O13	silent-controller recovery	a stalled playback session	[[ADR-0017-playback-session]] accepted no watchdog; takeover is the manual path. Revisit only if it bites in testing
O14	music preferences have no consumer	nothing	V.1 requires storing and updating them, which is met. Note for defence: storage-only today
O15	MediatR licence terms	adding the package	[[ADR-0021-backend-dependency-set]]: verify the current free-tier terms before `dotnet add package` and record the result. Fallback is a hand-written dispatcher
O16	OpenTelemetry must earn its place	credibility of the V.7 bottleneck claim	[[ADR-0022-observability-stack]]: capture one trace during the Gatling run showing EF Core, HttpClient and total request time together

Closed

#	Issue	Closed by
O1	which services ship	[[ADR-0010-service-scope]] — all three
O2	solution and folder layout	[[ADR-0011-solution-layout]]
O3	test framework	[[ADR-0012-test-stack]]
O4	API hosting target	[[ADR-0015-hosting-and-deployment]]

#	Issue	Closed by
O5	Supabase plan tier and region	[[ADR-0016-supabase-plan-region]]
O6	SMTP provider	[[ADR-0013-mail-provider]]
O7	location+time licence enforcement	[[ADR-0014-location-time-licence]]
G1	queue advance / playback progression	[[ADR-0017-playback-session]]
G2	what a control delegate actually controls	[[ADR-0017-playback-session]]
G3	load testing tool	[[ADR-0018-load-testing-tool]]
G4	hub actions missing from the audit log	[[ADR-0019-hub-action-auditing]]

Related

[[HOME]] · [[MEMORY]] · [[system-overview]] · [[domain-model]] · [[realtime-architecture]] · [[auth-and-identity]] · [[decisions-index]] · [[subject-requirements]] · [[technical-guide-index]] · [[user-manual]]