# Contents

**Threat Register** **1**
Status . . . 1
Legend . . . 1
Register . . . 1
Explicitly out of scope . . . 19
Maintenance . . . 19
Related . . . 20

# Threat Register

Subject V.6 requires more than protections: *"you must identify other dangers and describe the protection measures that can be implemented"*. This is that document.

**A written accepted risk is an engineering decision. An unwritten one is an oversight.** Evaluators ask what you did *not* protect against; this table is the answer.

## Status

**Design-stage register.** 29 threats, plus one accepted residual risk recorded in the Accepted section (T-30, the hub's query-string token). Slice S0 landed the first verified rows, S1 added T-25, T-26 and T-27, and closed T-25; S1a closed T-26 by landing the hosted mail sender and gave T-19 its first evidence; S5 closed T-06 — the reorder race subject V.2.3 grades — gave T-11 and T-12 their first evidence (T-12 narrowed again at S9, when the hub limits landed), and accepted T-30. S6 filled T-17: the location-and-time licence is enforced, and its residual risk is restated rather than quietly closed. Every other mitigation below is *designed*, not verified. The Verified column stays empty until a test, a config artifact or a named code path proves it.

## Legend

Likelihood and Impact: L / M / H. Residual = what remains **after** the planned mitigation.

## Register

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-01 | Credential stuffing / brute force on login | H | H | rate limit per account **and** per IP, progressive backoff, generic errors, BCrypt cost >= 12 | **mitigated 2026-09-27 by SPEC-006**, within the limits of one instance: distributed low-and-slow attempts across many IPs remain possible, the per-account counter is the control that bounds them, and there is no breached-password feed at launch. A restart clears every counter | owner, 2026-09-27, on SPEC-006 | S1: `CredentialRateLimitingT` `CredentialAttemptLimite` and `BCryptPasswordHasherTes` for the cost floor |
| T-02 | Session hijacking via stolen access token | M | H | 15-minute access token, HTTPS only, no token in URLs or logs | a stolen token is valid until expiry; no device binding | | — |
| T-03 | Refresh-token theft | M | H | opaque, hashed at rest, rotated on every use, family revoked on reuse detection | detection is after the fact, not preventive | | — |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-04 | Broken object-level authorization (another user's data) | M | H | two gates in a pipeline behaviour, checked on every request and hub join; hidden resources return `404` | a new endpoint that bypasses the behaviour; mitigated by a required negative test per endpoint | | — |
| T-05 | Vote manipulation (double voting, stuffing) | H | M | unique index `(EventId, TrackId, UserId)` as the arbiter, rate limit on the vote endpoint | multiple accounts by one person (sybil) is not prevented; email verification raises the cost only | | — |
| T-06 | Playlist reorder conflict causing lost or divergent order | H | M | a `bigint` sparse ordering key, and every track write updating the playlist row inside its own transaction keyed on the `xmin` the caller read — so the guarded `UPDATE` is both the precondition and the lock that serialises writers | rapid concurrent edits still surface as `412` to the user, who must reload and reapply. The status is `412` rather than `409`: the precondition in the request is what failed, and the fix is a reload either way | **closed by SPEC-015 on 2026-10-01** | S5: `PlaylistTrackConcurrenc` — twenty parallel moves of one track with one token give exactly one `200`, nineteen `412`, and a final order that is a permutation of the original with distinct positions |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-07 | Account takeover through unverified provider email matching | L | H | match an existing account only when the provider asserts `email_verified` | a provider that wrongly asserts verification | | — |
| T-08 | ID token substitution (token minted for another app) | L | H | validate `aud`, `iss`, `exp`, `nonce` against JWKS, server-side | depends on correct JWKS caching and key rotation handling | | — |
| T-09 | API key or secret committed to git | L | **critical** | `.env` git-ignored from commit 1, `.env.example` placeholders only, rotate-first leak procedure | subject V.8 makes this an **automatic project failure**; process discipline is the only control | | S0: `MusicRoom/.dockerignore` excludes `.env`; no `.env` and no credential string in any layer of the built image; `docker-compose.yml` carries no literal |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-10 | YouTube quota exhaustion during the demo | M | M | **built 2026-10-04 by SPEC-025.** `videos.list` is preferred over `search.list`; both cache levels of [[ADR-0023-catalog-cache]] stand in front of the provider, so a restart does not re-burn the quota and a repeated search re-issues nothing; `GET /tracks` — the only route that can reach `search.list` — carries a per-account limit of 30 a minute; every call logs its unit cost so the day's budget is measurable before it runs out; `403 quotaExceeded` answers `503` with its own problem type, and a stale | **residual, carried deliberately.** No per-account quota *budget*: the limit bounds the rate, not the day's total, so thirty accounts searching all day can still exhaust a free tier. Nothing alerts when the budget runs low — the cost is in the log and nothing reads it. And the client-side debounce `youtube-integration` asks for does not exist yet, because `MusicRoomApp/` is empty until after S9; until then one keystroke per request is possible from a hand-written client, bounded only by the rate limit | | S4: `YouTubeCatalogProviderT` — the quota cost is in the log line, a `403` becomes an unavailable outcome rather than a `500`, and a provider `5xx` is retried a bounded number of times; `CachedCatalogTests` — a second read of one video and a repeated search both reach the provider zero times, a fresh database row calls nothing at all, and a provider outage serves the stale row; `TrackEndpointTests` — `503` on both routes when the catalog cannot answer, and `422` for a blank query so no quota is spent on it. No suite calls YouTube |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-11 | Denial of service via unbounded input or list requests | M | M | capped `pageSize`, bounded string and collection lengths, global plus per-endpoint rate limits, and a hard **500-track cap per playlist** answered `409` (SPEC-015), which also bounds the renumber a sparse key occasionally needs | a single instance has no upstream protection; capacity is whatever V.7 measures. The cap is per playlist, not per account: an account may still hold many playlists | | S5: `PlaylistTrackEndpointTe` |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-12 | SignalR connection exhaustion | M | M | bounded payloads, and explicit `KeepAliveInterval` of 15 seconds with a `ClientTimeoutInterval` of 60 (SPEC-016) rather than the framework defaults, so a dead mobile connection is dropped in a minute instead of being held; every hub connection must present a valid token and name a playlist it may see before it joins anything. **Since SPEC-026 the limits ADR-0030 decided exist:** 5 concurrent connections per account and 20 per address, refused at the handshake with `429` and `Retry-After` and again at connect; 60 hub invocations a | **narrowed 2026-10-04.** The gap this described — nothing capping connections per account, and one authorised connection able to invoke a hub method at request rate — is closed. **Residual, carried deliberately:** the counts are per process, so a second instance would hold its own (O8, and no backplane); a request with **no** `Origin` passes, which is every non-browser client including ours, with the JWT as the control behind it (ADR-0030 records this as a deliberate hole); and the numbers are a starting | | S9: `HubLimitTests` — the connection after the per-account ceiling is refused and the ones holding slots are not; a closed connection frees its slot, so a reconnecting client is not locked out; the address ceiling refuses a **different account** from the same address, which is the venue case; the invocation after the allowance throws and leaves one `refused` audit row; an allowed origin connects, an unlisted one is refused at the handshake, and no origin at all connects |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-13 | Database connection-pool exhaustion | M | M | small pool, short-lived connections, pooled connection string for the API | Supabase enforces a hard connection ceiling above ours | | — |
| T-14 | Personal data over-exposure in profile responses | M | M | per-field filtering server-side by requester relationship | a new profile field added without a visibility tier; mitigated by making the tier non-nullable | | — |
| T-15 | Sensitive data in logs | M | H | never-logged list, structured templates, no full bodies on credential endpoints | a developer logging an object graph that contains a token | | partial, S0: `GetHealthReady_WhenData` proves the readiness body carries no host, connection string or exception text |
| T-16 | Vulnerable transitive dependency | M | M | `dotnet list package --vulnerable --include-transitive` fails CI on high severity | a zero-day between scans | | S0: step present in both workflows and in `make agent-check`; clean across all 10 projects |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-17 | Location+time licence bypass (spoofed GPS) | M | M | a server-side great-circle check against the event's own centre and radius, **plus** an optional short-lived venue code — stored as a SHA-256 digest, 60 to 3600 seconds, single-use per account, rate limited per account — with the event's policy selecting `Geofence`, `EventCode` or `Both`; every evaluation uses server time, and a `LocationAndTimeRestricted` event cannot exist without a configured proof (SPEC-017 decision 3) — [[ADR-0014-location-time-licence]] | **client-reported coordinates remain spoofable**, and a code can be relayed by text to somebody off-site. Neither is fixable without infrastructure this project will not build, and both are stated plainly at defence: subject V.6 does not expect an unbreakable API, it expects the remaining danger to be `TimeRestricted`. What the design does buy is cost — a remote voter needs a confederate at the venue, per code, per account | **accepted, owner, 2026-09-24 on ADR-0014; the implementation of 2026-10-01 changes nothing about the residual risk** | S6: `EventPresenceEndpointTe` proves a coordinate outside the radius, a vote outside the window, an unknown code, an expired code, a code reused by the same account and a `Both` policy with only a code are each refused `422`, and that the same code admits a second account once; `EventVoteConcurrencyTes` proves the single use holds under concurrency; `GeodesyTests` proves the distance, including across the antimeridian |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-18 | Malicious content in user-supplied text (event names, playlist titles) | M | M | validation, length caps, output encoding at the consumer | the client is responsible for rendering safely; no web frontend today | | — |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-19 | Mail provider quota exhausted by a registration loop | L | M | rate limits on registration and verification resend; hosted provider free tier — [[ADR-0013-mail-provider]] | a quota exhausted mid-defence blocks the verification demo. **The rate limiter is a precondition of slice S1a** (owner decision, SPEC-004, 2026-09-27): `POST /api/v1/auth/verification-requests` is the first endpoint whose success path is one mail send per anonymous request, so the moment O17 lands the hosted provider the loop stops being theoretical. **Live since SPEC-024, 2026-10-04:** a send now spends real provider quota, and the limiter that was this slice's precondition is in place — per-IP on every credential endpoint plus a per-account | | S1a: `BrevoMailServiceTests` proves one attempt per call against a stubbed transport and `MailOptions.SendTimeout` bounds it; no suite sends a real message, so CI spends no provider requests. The cap itself is unmeasured. |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-20 | Supabase free project pauses from inactivity | M | H | touch the project before the defence; local PostgreSQL container as a fallback with identical migrations — [[ADR-0016-supabase-plan-region]] | a pause discovered on the day still costs demo time | | — |
| T-22 | Malicious controller skips the queue | L | M | only `controllerUserId` may advance; `expectedNowPlayingId` makes a replay idempotent; the owner can revoke control at any time | a legitimate controller can still play ahead — that is what control means | | — |
| T-23 | Playback stalls because the controller device went offline | M | M | control takeover via `PUT /devices/{id}/control`; the owner can revoke | no server-side watchdog by design ([[ADR-0017-playback-session]]); recovery is manual (issue O13) | | — |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-24 | Operational endpoints reachable by anyone who can reach the port | M | L | `/health` and `/health/ready` are anonymous by contract ([[endpoint-inventory]]) and report only check names and states — no version, host, connection string or exception text | an unauthenticated caller learns the service is up and whether its database is reachable, and can poll it: the endpoints carry no rate-limit policy, because a limiter that throttles a probe defeats the probe | | S0: readiness body asserted by test; no authentication is planned for these two |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-25 | Anonymous auth endpoints have no rate limit: `POST /api/v1/auth/registrations`, `POST /api/v1/auth/email-verifications`, `POST /api/v1/auth/verification-requests`, `POST /api/v1/auth/sessions` and `POST /api/v1/auth/tokens` can all be driven in a loop. SPEC-007 added `POST /api/v1/auth/password-reset-requests` and `POST /api/v1/auth/password-resets`, both limited from their first commit | M | M | rate limits keyed on IP and on the submitted address (SDD §13.3), built once for registration, verification, login and resend together | **closed 2026-09-27 by SPEC-006.** Deferred three times while the control was shared with endpoints that did not exist; built once, for all five at once. Each endpoint carries its own per-IP policy, so a registration loop cannot spend the sign-in allowance, and login, registration and resend also carry a per-account counter with progressive backoff. Refusals are `429` with `Retry-After` and an empty body, so the refusal itself says nothing about which key tripped. **Residual, carried deliberately:** limiter | owner, 2026-09-27, on SPEC-006 | S1: `CredentialRateLimitingT` — per-IP limit with `Retry-After`, per-account limit scoped to one address, a second client unaffected, and the registration, resend, verification and rotation loops each bounded; `CredentialAttemptLimite` — the window, the doubling penalty, the ceiling and the reset on success |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-26 | Development-only `LoggingMailService` writes the email verification link **and the password reset token** to the application log | M | M | registered as `IMailService` only when the host environment is Development; `AddInfrastructureServices` throws `InvalidOperationException` at start-up in any other environment rather than falling back silently or booting with no sender. With no `VERIFICATION_LINK_BASE_URL` configured the sender logs the bare token and says the variable is missing — it never invents a default link | **CLOSED 2026-10-04 by SPEC-024.** `MAIL_PROVIDER=brevo` registers `BrevoMailService`, which includes the link and the token to the recipient's mailbox and logs neither — only the address and the provider's message id. `LoggingMailService` still exists for local work and is still refused outside Development, now by the rule "the configured provider must be allowed on this host" rather than "the host must be Development": a typo in `MAIL_PROVIDER` stops start-up instead of falling back to the sender that logs credentials, and `MailOptionsTests` plus `MailProviderStartupTests` assert each | owner, 2026-09-26, on SPEC-003 | S1: `LoggingMailServiceTests` asserts one event carrying the link, one warning-level event carrying the reset token and naming this row, and the non-Development start-up throw is a named code path in `InfrastructureServiceRe` **S1a:** `MailProviderStartupTest` — a Development host with `logging` resolves the logging sender, any host with `brevo` and its two values resolves the hosted one, and a host with no provider or with `logging` outside Development fails to resolve a sender at all; `MailOptionsTests` — the nine configurations that may and may not start; `BrevoMailServiceTests` |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-27 | No security event is logged when a credential endpoint refuses a request: a failed login, a rejected refresh token and a detected refresh-token **reuse** all leave no record beyond the Serilog request line | M | M | the A09 event list in [[owasp-top10-checklist]]: log failed login, lockout, token reuse, authorisation denial and rate-limit trip, through the audit behaviour of slice S2 ([[ADR-0019-hub-action-auditing]], SDD §13.4) | **closed 2026-09-28 by SPEC-009.** Every credential refusal now leaves an `audit_records` row that says which refusal it was: `refused` for a wrong password or an unknown token, `throttled` when the account is out of attempts, `expired` for a spent window, and `reusedetected` when an already-rotated refresh token revoked a family — that last one naming the account whose family died. Recording a throttled attempt required the limiter's refusal to stop being an exception, because | owner, 2026-09-28, on SPEC-009 | S2: `AuditRecordEndpointTest` — refused, completed with a named account, `reusedetected`, expired, and a duplicate registration staying `completed`; `CredentialRateLimitingT` — a `throttled` row with the `429` unchanged; `AuditBehaviourTests` — every outcome value and the silent default |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-28 | Neither a password reset nor a logout revokes access tokens already issued: a JWT minted before either stays valid until `exp`, so a thief who signed in moments earlier keeps API access for the remainder of that window | M | M | the 15-minute access-token lifetime (SDD §13.1), which is why the lifetime is short; a `jti` or per-user not-valid-before denylist checked on every authenti-cated request would close it entirely | **accepted.** Revoking refresh families ends every session's ability to continue, which is the control the contract promises; the remaining exposure is bounded by the token lifetime and cannot exceed **15 minutes and 30 seconds** — 15 minutes signed plus the 30 seconds of clock skew the bearer handler allows (owner decision, 2026-09-28; the handler's five-minute default would have made it 20 minutes). SPEC-010 widened this row from reset to logout as well, for the same reason: a stateless token cannot be recalled without | owner, 2026-09-27, on SPEC-007 | S1: `Reset_WithTheIssuedToke` proves what a reset **does** revoke; S2: `Logout_ThenRotatingTheR` proves the same for logout, and `BearerValidationTests.S` proves the window closes. The window itself is stated, not measured |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-29 | The audit log is fail closed: a command whose `audit_records` insert fails is rolled back and answers `500`, so a fault confined to the audit table stops every mutating endpoint | L | H | the record and the effect share one transaction, so neither can exist without the other (SDD §13.4, §10.7); the table has two indexes and no foreign key, so the write is as cheap as an insert gets | **accepted, deliberately.** The alternative was fail open, which allows an action nobody can account for — the exact gap subject V.6 asks about. The owner chose evidence over availability on 2026-09-27, knowing an audit-table fault becomes a total mutation outage and that a defence demo would die on it. Reads, health probes and the OpenAPI document are unaffected, so the service stays diagnosable while refusing to act unrecorded. **SPEC-009 widened what this** | owner, 2026-09-27, on SPEC-008 | S2: `AuditBehaviourTests.Han` proves the rollback and the rethrow |

| # | Threat | L | I | Planned mitigation | Residual | Accepted by | Verified |
|---|---|---|---|---|---|---|---|
| T-21 | Voter location data stored unnecessarily | L | M | the submitted coordinate is used for the check and **not** persisted on the vote row; event centre stored at coarse precision | the coordinate exists in transit and in request logs unless excluded — add it to the never-logged list | | — |

## Explicitly out of scope

| Not defended against | Why |
|---|---|
| A determined attacker with unlimited resources | subject V.6: *"your API is not expected to be unbreakable"* |
| Physical device compromise | the token is in the platform secure store; a rooted device is outside our control |
| Supabase platform compromise | vendor trust boundary, stated rather than pretended away |
| Sybil accounts (T-05) | email verification raises cost; full prevention needs identity proofing this project will not build |
| An access token in a hub URL's query string (T-30) | A WebSocket handshake cannot carry an `Authorization` header, so SignalR documents `access_token` as a query parameter and the mobile client has no other option. Bounded three ways: it is read **only** under `/hubs`, so no REST route gains a second way to authenticate; Serilog's request logging records the path and not the query string, so it does not reach the application log; and the token already lives 15 minutes (ADR-0030, ADR-0032). What remains is that a URL is more copyable than a header — in a crash report, a proxy log the deployment owns, or a shared screen. Accepted on the same ground as the rest of the transport story: TLS is the deployment's job, and the alternative is no realtime on mobile at all (SPEC-016 decision 4) |

## Maintenance

- A finding from [[owasp-top10-checklist]] or [[owasp-api-top10-checklist]] that is not fixed in the pull request gets a row here **before** that PR merges.
- Fill Accepted by with a real name when the team agrees to carry a residual risk.
- Fill Verified with the test or artifact that proves the mitigation, once it exists.
- Never delete a row. Close it by pointing at the evidence.

## Related

[[owasp-index]] · [[asvs-conformance]] · [[application-security]] · [[authentication-authorization]] · [[sdd]] §13.6 · [[subject-requirements]]