EARLE M. JORGENSEN CO
6201 LUMBERDALE

HOUSTON
TX 77092
713 672-1621

APPROVED
By Heather Campbell at 2:37 pm, 11/17/25

PACKING SLIP

SOLD TO:
CACTUS WELLHEAD LLC
920 MEMORIAL CITY WAY STE 300
HOUSTON TX
77024

713 626-8800

SHIP TO:
CACTUS WELLHEAD LLC
4123B MEADOW LANE
BOSSIER CITY LA
71111

CUSTOMER PO:	TRP0051945
SHIPPING DATE:	14-NOV-25
SHIPPED VIA:	CCSAI
FREIGHT TERMS:	COLLECT
INSIDE SALES:	MICHAEL BAKER
EMJ SALES ORDER:	S584600 453
BUYER:	AASHA
COD AMOUNT ($):	

COLLECT

INTERNAL USE
TRUCK: WILL CALL
TR: B
CT:

DRIVER NOTES:

SAIA COLLECT GSS12 FOR MONDAY DELIVERY **

ITEM	DESCRIPTION	CUSTOMER PART #	QUANTITY
536883	17-4 HH1150 CMS303H CMS002L CMS004C CIR002F 7-1/4 RD S/C 4'1" (49") WGT/FT: 140.4470 ECCN: EAR99 HTS: 7222110031 CUST PART# BARCODE:	940007 REV A02 LINE: 1 JOB: COLOR:GLD / BRN CLS: 050	1.0000 EA 573 WT 1.0 PC

HEAT:
ST0163-70
1 PC @ 1 PCs
573 LB

Piece count based on theoretical weight.
Terms and conditions are located at https://www.emjmetals.com/pdf_indexer/pdfs/SalesOrderTerms.pdf and are incorporated by reference.
Questions or Concerns about your delivery contact your salesperson.

CERTIFICATE OF CONFORMANCE

Certification Date
17-NOV-2025

CUSTOMER ORDER NUMBER
TRP0051945

CUSTOMER PART NUMBER
940007 REV A02

EARLE M. JORGENSEN COMPANY
6201 LUMBERDALE
HOUSTON TX 77092

Invoice Number
S584600

SOLD TO: CACTUS WELLHEAD LLC
920 MEMORIAL CITY WAY STE 300
HOUSTON TX 77024

SHIP TO: CACTUS WELLHEAD LLC
4123B MEADOW LANE
BOSSIER CITY LA 71111

Description: 17-4 HH1150 CMS303H CMS002L CMS004C CIR002F
7-1/4 RD S/C 4'1" (49") Line Total: 573.4919 LB
HEAT: ST0163-70 ITEM: 536883

Specifications:

ASTM A564 19A	NACE STD MR0175	ISO 15156-3
NACE MR0103	ISO 17945 15	API 6A PSL3 18
AMS-H-6875C	API 6D APPENDIX F	EN 10204 3.1

CHEMICAL ANALYSIS

C	SI	MN	P	S	NI	CR	MO
0.02	0.41	0.60	0.02	0.002	4.33	15.15	0.22

CU	NBTA	NB	TA
3.30	0.22	0.22	0.0047

RCPT: R938623
VENDOR: GLORIA MATERIAL TECHNOLOGY
CTRY OF MELT/POUR: TAIWAN CTRY OF MANUFACTURE: TAIWAN

MECHANICAL PROPERTIES

DESCRIPTION	YLD STR KSI	ULT TEN KSI	%ELONG IN 02 IN	%RED IN AREA	HARDNESS RC
DBL H1150	122.0	139.0	21.0	64.0	30

DESCRIPTION	YLD STR	ULT TEN	%ELONG	%RED IN AREA	HARDNESS RC
SURFACE					30

The above data were transcribed from the manufacturer's Certificate of Test after verification for completeness and specification requirements of the information on the certificate. All test results remain on file subject to examination.

We hereby certify that the material covered by this report meets all specified order requirements as well as the applicable requirements described herein, including any specification forming a part of the description.

The willful recording of false, fictitious, or fraudulent statements in connection with test results may be punishable as a felony under federal statutes.

Material did not come in contact with mercury while in our possession.

SHANE LU

Manager, Quality Assurance

CERTIFICATE OF CONFORMANCE

Certification Date
17-NOV-2025

CUSTOMER ORDER NUMBER
TRP0051945

CUSTOMER PART NUMBER
940007 REV A02

EARLE M. JORGENSEN COMPANY
6201 LUMBERDALE
HOUSTON TX 77092

Invoice Number
S584600

SOLD TO: CACTUS WELLHEAD LLC
920 MEMORIAL CITY WAY STE 300
HOUSTON TX 77024

SHIP TO: CACTUS WELLHEAD LLC
4123B MEADOW LANE
BOSSIER CITY LA 71111

Description: 17-4 HH1150 CMS303H CMS002L CMS004C CIR002F
7-1/4 RD S/C 4'1" (49") Line Total: 573.4919 LB
HEAT: ST0163-70 ITEM: 536883

GRAIN SIZE :5 -

IMPACT TEST TYPE	TEMP	ORNT	UOM ft-lbs SMPL#1	#2	#3	AVG	% SHEAR	LAT EXPN	DESCRIPTION
CHARPY	-75 F	LONG	85.0	75.0	86.0	82.0			10MMx10MM

MATERIAL IS FREE FROM MERCURY CONTAMINATION
NO WELD REPAIR PERFORMED ON MATERIAL
THERMAL TREATMENT: OK
MACRO: OK
MICRO1: OK

COMMENTS
MELT PRACTICE: EAF/LHF/VOD
REDUCTION RATIO: 8.2:1
TENSILE SPECIMEN SIZE .500"
TEST PIECE IS A PROLONGATION OF THE BAR
HEAT TREATMENT:
SOLUTION ANNEALED @ 1900 DEG F FOR 4.7879 HOURS - AIR COOLED TO BELOW 90 DEG F
ANNEAL FURNACE MONITORED BY ATMOSPHERIC THERMOCOUPLES
HARDENED @ 1150 DEG F FOR 4.0513 HOURS - AIR COOLED TO BELOW 90 DEG F
HARDENED @ 1150 DEG F FOR 4.0513 HOURS - AIR COOLED TO BELOW 90 DEG F
AGING FURNACE MONITORED BY CONTACT SURFACE THERMOCOUPLES
PASSED UT TEST PER API 6A PSL3
HEAT TREAT LOT NUMBER: 70
LATERAL EXPANSION: 0.96/1.04/0.95 (MM)
SHEAR PERCENTAGE: 72/76/73

The above data were transcribed from the manufacturer's Certificate of Test after verification for completeness and specification requirements of the information on the certificate. All test results remain on file subject to examination.

We hereby certify that the material covered by this report meets all specified order requirements as well as the applicable requirements described herein, including any specification forming a part of the description.

The willful recording of false, fictitious, or fraudulent statements in connection with test results may be punishable as a felony under federal statutes.

Material did not come in contact with mercury while in our possession. SHANE LU

Manager, Quality Assurance

CERTIFICATE OF CONFORMANCE

Certification Date
17-NOV-2025

CUSTOMER ORDER NUMBER
TRP0051945

CUSTOMER PART NUMBER
940007 REV A02

EARLE M. JORGENSEN COMPANY
6201 LUMBERDALE
HOUSTON TX 77092

Invoice Number
S584600

SOLD TO: CACTUS WELLHEAD LLC
920 MEMORIAL CITY WAY STE 300
HOUSTON TX 77024

SHIP TO: CACTUS WELLHEAD LLC
4123B MEADOW LANE
BOSSIER CITY LA 71111

Description: 17-4 HH1150 CMS303H CMS002L CMS004C CIR002F
7-1/4 RD S/C 4'1" (49") Line Total: 573.4919 LB
HEAT: ST0163-70 ITEM: 536883
DELTA FERRITE: 0.7%
MATERIAL IS FREE FROM RADIOACTIVITY
YIELD TAKEN AT 0.2% OFFSET

The above data were transcribed from the manufacturer's Certificate of Test after verification for completeness and specification requirements of the information on the certificate. All test results remain on file subject to examination.

We hereby certify that the material covered by this report meets all specified order requirements as well as the applicable requirements described herein, including any specification forming a part of the description.

The willful recording of false, fictitious, or fraudulent statements in connection with test results may be punishable as a felony under federal statutes.

Material did not come in contact with mercury while in our possession. SHANE LU

Manager, Quality Assurance

7/30/25 536883 ST0163-70 (938623 (3)

GLORIA MATERIAL TECHNOLOGY CORP.
INSPECTION CERTIFICATE

Messrs: EARLE M. JORGENSEN COMPANY
Order No.: 2025001701-1
File No.: 2025001702-A
Grade: 17-4 DBL H1150 536883
Size: 7-1/4"
Heat-Lot No.: ST0163-70
Condition: HF-Solution Annealed-Double Aged-Peeled(-Stress Relief)

P.O.No.: P374715-453
Date: 06/03/2025
Weight: 2389KG 5266LB
P'cs: 3

Chemical Composition (wt%)

	C	Si	Mn	P	S	Ni	Cr
Min.						3.00	15.00
Max.	0.07	1.00	1.00	0.025	0.025	5.00	17.50
Result	0.02	0.41	0.60	0.020	0.002	4.33	15.15

	Mo	Cu	Nb+Ta	Nb	Ta
Min.		3.00	0.15	5C	
Max.	0.50	5.00	0.45	0.45	
Result	0.22	3.30	0.22	0.22	0.0047

Mechanical Properties Spec.

	Hardness 1/2R	Hardness 1/2R(2)	Hardness Surface	Hardness Surface(2)	Grain Size ASTM E112 T	Delta-Ferrite AMS 2315 L
Condition						
Spec.Min.					5	
Spec.Max.	33HRC	33HRC	33HRC	33HRC		5%
Result	30HRC	31HRC	30HRC	31HRC	5	0.7%

	Impact(1) DB H1150 1/2R L	Impact(2) DB H1150 1/2R L	Impact(3) DB H1150 1/2R L	Impact(Ave) DB H1150 1/2R L	LE(1) DB H1150 1/2R L	LE(2) DB H1150 1/2R L	LE(3) DB H1150 1/2R L	LE(Ave) DB H1150 1/2R L	Shear%(1) DB H1150 1/2R L
Condition	-75°F	-75°F	-75°F	-75°F	-75°F	-75°F	-75°F	-75°F	-75°F
Spec.Min.	20Ft.Lbs	20Ft.Lbs	20Ft.Lbs	20Ft.Lbs					
Spec.Max.									
Result	85Ft.Lbs	75Ft.Lbs	86Ft.Lbs	82Ft.Lbs	0.96mm	1.04mm	0.95mm	0.98mm	72%

	Shear%(2) DB H1150 1/2R L	Shear%(3) DB H1150 1/2R L	Shear%(Ave) DB H1150 1/2R L
Condition	-75°F	-75°F	-75°F
Spec.Min.			
Spec.Max.			
Result	72%	76%	73%

Peter Liu
Quality Manager
Peter Liu

Our quality and environment management systems have been certified by AS 9100(QMS), ISO 9001(QMS), IATF 16949(QMS), ISO 17025(Lab), ISO 14001(EMS), ISO 50001(EMS), ISO 45001(OH&S) and NADCAP.We hereby certify that the material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. Inspection Certificate comply with EN 10204 3.1.

台南台南市新市區新中路35號/NO.35,HSIN CHUNG RD., HSIN YING, TAINAN, TAIWAN
TEL: 886-6-6520031/FAX: 886-6-6230877
http://www.gmtc.com.tw

GLORIA MATERIAL TECHNOLOGY CORP.
INSPECTION CERTIFICATE

Messrs: EARLE M. JORGENSEN COMPANY
Order No.: 2025001701-1
File No.: 2025001702-A
Grade: 17-4 DBL H1150 536883
Size: 7-1/4"
Heat-Lot No.: ST0163-70
Condition: HF-Solution Annealed-Double Aged-Peeled(-Stress Relief)

P.O.No.: P374715-453
Date: 06/03/2025
Weight: 2389KG 5266LB
P'cs: 3

Tensile Test

	Elongation(A)	Tensile Strength(Rm)	Yield Strength(0.2% Rp)	Reduction of Area(Z)
Condition	23.1℃ DB H1150 1/2R L (Ave)	23.1℃ DB H1150 1/2R L (Ave)	23.1℃ DB H1150 1/2R L (Ave)	23.1℃ DB H1150 1/2R L (Ave)
Unit	%	KSI	KSI	%
Min.	15	135	105	35
Max.				
Result	21	139	122	64

Heat Treatment Condition

Condition	Temperature	Time/hour	Treatment
SOLUTION	1900°F	4.7879	FAST AIR COOL TO BELOW 90°F
DOUBLE AGED	1150°F	4.0513	AIR COOL TO BELOW 90°F

ACTUAL REDUCTION RATIO: 8.2:1
COUNTRY OF ORIGIN :GMTC, TAIWAN.
COUNTRY OF MANUFACTURE : GMTC, TAIWAN.
COUNTRY OF MELTING AND POURING:TAIWAN

Specification:
1. NACE MR 0175/ISO 15156-3(2015).
2. NACE MR 0103/ISO 17945(2015).
3. ASTM A564/A564M-19a.
4. API 6A PSL3-2018.
5. AMS-H-6875C.
6. API 6D APPENDIX F.

Remark:
1. MANUFACTURING PROCESS: AIR MELTING (EAF+LHF+VOD), HOT FORGING OR ROLLING.
2. MATERIAL IS FREE FROM KNOWN CONTACT WITH MERCURY AND RADIUM.
3. MATERIAL IS FREE FROM WELDS OR WELDING REPAIRS.

Peter Liu
Quality Manager
Peter Liu

Our quality and environment management systems have been certified by AS 9100(QMS), ISO 9001(QMS), IATF 16949(QMS), ISO 17025(Lab), ISO 14001(EMS), ISO 50001(EMS), ISO 45001(OH&S) and NADCAP.We hereby certify that the material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. Inspection Certificate comply with EN 10204 3.1.

台南合開南新工業區中區35號/NO.35,HSIN CHUNG RD.,HSIN YING,TAINAN,TAIWAN
TEL:886-6-6520031 FAX:886-6-6230877
http://www.gmtc.com.tw

GLORIA MATERIAL TECHNOLOGY CORP.
INSPECTION CERTIFICATE

Messrs: EARLE M. JORGENSEN COMPANY
Order No.: 2025001701-1
File No.: 2025001702-A
Grade: 17-4 DBL H1150 536883
Size: 7-1/4"
Heat-Lot No.: ST0163-70
Condition: HF-Solution Annealed-Double Aged-Peeled(-Stress Relief)

P.O.No.: P374715-453
Date: 06/03/2025
Weight: 2389KG 5266LB
P'cs: 3

4. ULTRASONIC TEST CONFORM TO API 6A PSL3.
5. MACRO STURCTURE: OK.
6. MICRO STRUCTURE: OK.
7. LONGITUDINAL IMPACT SPECIMEN SIZE IS 10mmX10mmX55mm.
8. LONGITUDINAL TENSILE SPECIMEN SIZE IS D (DIAMETER):0.5 INCH, G (GAGE LENGTH):2 INCH, TEST AT THE ROOM TEMPERATURE.
9. AIR COOLED BELOW 90 DEGREES F AFTER ANN AND AGING CYCLES.
10. AGING CYCLES TO BE MONITORED BY CONTACT SURFACE THERMOCOUPLE.
11. THE TEST PIECE IS A PROLONGATION OF THE BAR.
12. 17-4 DBL H1150 IS THE SAME WITH AISI 630 DBL H1150.
13. THE FURNACE IS MONITORED BY FURNACE ATMOSPHERE.
14. THE HEAT TREATMENT FURNACE IS QUALIFIED ACCORDING TO AMS-H-6875C.
15. MECHANICAL PROPERTIES TESTED PER ASTM A370.
16. THE BATCH TYPE FURNACES ARE USED FOR HEAT TREATMENT IN THE PRODUCTS.
17. FURNACES ARE CALIBRATED IN ACCORDANCE WITH AMS 2750H.
18. THE FURNACE CALIBRATION COMPLIES WITH API 6A 21ST EDITION ANNEX M.

Peter Liu
Quality Manager
Peter Liu

Our quality and environment management systems have been certified by AS 9100(QMS), ISO 9001(QMS), IATF 16949(QMS), ISO 17025(Lab), ISO 14001(EMS), ISO 50001(EMS), ISO 45001(OH&S) and NADCAP.We hereby certify that the material described herein has been manufactured and tested with satisfactory results in accordance with the requirement of the above material specification. Inspection Certificate comply with EN 10204 3.1.

台灣台南市新營區新中路35號 / NO.35,HSIN CHUNG RD.,HSIN YING,TAINAN,TAIWAN
TEL:886-6-6520031 / FAX:886-6-6230827
http://www.gmtc.com.tw

GMTC

GLORIA MATERIAL TECHNOLOGY CORP.

35 HSIN CHUNG ROAD, HSINYING, TAINAN, TAIWAN
TEL : (06)6520000 ; FAX: (06)6520033

NDE Results

Date	06/03/2025
FILE NO	2025001702-A

Job Detail

Product	Messrs	P.O.No.	Order No.
Round Bar	EARLE M. JORGENSEN COMPANY	P374715-453	2025001701
HEAT-Lot No.	Grade	Heat Treatment	Surface condition
ST0163-70	17-4 DBL H1150 536883	HF-Solution Annealed-Double Aged	Peeled
Dimension(Dia.)	Length(L)	Quantity	Weight
7-1/4"		3	2389KG 5266LB

Magnetic Particle Inspection	
Specification	
Standard Block	
Test Equipment	
Magnetic. Particle	
Mag. Method	
Kind Mag. Current	
Mag.Time&Current	
Surface condition	
Acceptance Criteria	
Test Result	
NDT Inspector	
Inspect Date	

Ultrasonic Inspection	
Specification	API 6A
Standard Block	630-RB1-00010
Test Equipment	GE-IT USN60-22
Scanning Method	Manual, Direct Contact, Straight Beam, Longitudinal Wave, Pulse Echo
Couplant	Machine oil
Probe	Waygate B2S 2MHz /Dia.24mm sn.:500036-62085
Sensitivity	3.2mm FBH DAC set to 80% FSH
Surface condition	Machined
Acceptance Criteria	API 6A PSL3
Test Result	OK
NDT Inspector	吳聖恩 Sheng-En Wu UT Level II
Inspect Date	03/31/2025

Test Sketch: Shown as below
Test Results: OK



Q.C. CHIEF	REVIEWED BY UT LEVEL III	REVIEWED By CUSTOMER
Peter Liu 06/03/2025 Peter Liu	Chung-Yi Wang 06/03/2025 Chung-Yi Wang	

SOP S06-708 Sheet Rev.1

榮剛材料科技股份有限公司
Gloria Material Technology Corp.

非破壞檢測人員資格證書
Certificate of Nondestructive Test Personnel

茲證屬員 吳聖恩　　授證編號

Be it know that Sheng-En Wu　　Cert. No: PQ-017



在如下表列之非破壞檢測技術領域，業已符合GMTC參照以下規範建立之B04-014非破壞檢測人員資格鑑定要求，認可授予為合格非破壞檢測技術人員。

an employee of Gloria Material Technology Corp. is qualified in the Nondestructive Testing Method as Specified in the Endorsements by meeting the qualification requirements of Gloria Material Technology Corp. Written Practice B04-014 in accordance with th

ASNT Recommended Practice SNT-TC-1A,2020 edition
AIA Standard Practice NAS-410,2020
ISO 11484

合格證書之檢測方法及期限為：
Endorsements:

檢測方法/技術 Method/Tech.	級別 Level	發證日期 Date Issued	授權代表簽署/日期 Authorized By / Date	有效期限 Date Expires	授證參照 Qualified reference	備註 Remarks
超音波檢測 UT(Conventional)	II	3/30/2021	03/30/2021	3/29/2026	■SNT-TC-1A & NAS-410 ■ISO 11484	Re-certification
磁粒檢測 MT(Bench)	II	3/30/2021	03/30/2021	3/29/2026	■SNT-TC-1A & NAS-410 ☐ISO 11484	Re-certification
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	
					☐SNT-TC-1A & NAS-410 ☐ISO 11484	

榮剛材料科技股份有限公司
Gloria Material Technology Corp.

非破壞檢測人員視力檢查報告表
NDT Personnel Qualification & Certification -Vision Examinations Records

本檢測係依照榮剛材料科技公司非破壞檢測人員資格鑑定作業標準(B04-014).
This vision test is executed based on the requirement of GMTC NDT Personnel Qualification and Certification standard practice (B04-014).

姓名 Name	吳聖恩 Sheng-En Wu	代號 Badge No.	300259	出生日期 Birthday	12/25/1971	性別 Sex	☑男Male ☐女Female	檢查日期 Exam.Date	01/03/2025

檢查項目 Exam. Item	檢查結果 Results				判讀結果 Judgment
	裸視(Naked eye)		矯正後(Corrected)		☑正常 OK
	左眼(Left eye)	右眼(Right Eye)	左眼(Left eye)	右眼(Right Eye)	☐異常 Reject
☑近距視力 Near Vision			J1	J1	
	裸視或矯正後，左右眼其中一眼視力需能在12英吋之距離判讀JAEGER表上之1號英文字母。 (Near vision results to JAEGER 1 Requirements at not less than 12" is required in at least one naked/corrected eye.)				

	Both eye	
☑辨色力 Color Vision		☑正常 OK ☐異常 Reject
	色盲檢查依據立誼出版社出版石原忍博士著之色盲檢辨圖。 (Distinguishing and differentiating contrast among colors by Dr. 石原忍 color chart.)	缺陷顏色 Color Deficiency

備註 Remark	Limitations/Special Conndtions:

受檢人執行NDT時是否帶眼鏡 Glasses required when examinee performing NDT inspection?	☑Yes	☐No
依照以上結果，受檢人之視力檢查結果為： Follow the above results,the Vision Examinations results is:	合格(Acceptance)	✓
	不合格(Reject)	

榮剛材料科技股份有限公司 醫務室 TEL:06-6520000轉651 FAX:06-6520030 台南縣新營市新中路85號

高級檢測師代表簽名 RLⅢ signature	周佳音 檢查人簽名 Examiner signature	吳聖恩 受檢人簽名 Examinee signature

CACTUS WELLHEAD, LLC

SDR NO. 28069

SUPPLIER DEVIATION REQUEST (SDR)

Complete this form and email to the Cactus Wellhead Buyer stated on the Purchase Order. Remember to include a detailed deviation description and provide marked up drawings when applicable.

Supplier Name & Address:	Purchase Order Number	Line Item
EMJ Metals 6201 Lumberdale Dr. Houston, TX 77092	TRP0051945	1

Part Number	940007	**Rev:**	A02	**Quantity:**	49"
Drawing Number:	n/a			**Rev:**	
Part Description:	7.25" 17-4 HH1150 SOLID BAR				
Heat Number(s):	ST0163-70		**Serial Number(s):**	n/a	

Deviation Description:

Requesting deviation to allow the mill UT along with the UT tech current eye test and level II/III UT certification

Submitted By:	Michael Baker	Date:	11/14/2025

Cactus Wellhead Disposition Only

Accept (Justify Below)	No. of Pcs. 49"	Rework	No. of Pcs. 0	Scrap	No. of Pcs. 0

Engineering			Quality		
Signature: Lu Huang	Digitally signed by Lu Huang Date: 2025.11.14 14:32:01 -06'00'	Date: 11/14/2025	Signature: Brandi Richardson	Digitally signed by Brandi Richardson Date: 2025.11.14 14:36:12 -06'00'	Date: 14Nov25

ACCEPT JUSTIFICATION:

QA approved UT.

REWORK ROUTING:

Supplier Action Required: *Material shall be tagged or marked with the SDR number and a copy of the SDR shall be included with the material certifications and/or bill of lading. If material is not delivered in accordance with these instructions, material will be subject to rejection and processed as a Supplier Nonconformance.*